



Tutorial Link <https://course.testpad.chitkara.edu.in/tutorials/SelectionSort/5a12e94346765b2b63e34754>

## TUTORIAL

# Selection Sort

## Topics

### 1.4 Video Solution

Selection Sort is an in-place comparison based sorting algorithm.

### Idea:

In an array that is sorted in ascending order, the first element is the minimum of all the  $n$  array elements, similarly the second element is the minimum of remaining  $n-1$  elements, the third element is the minimum of remaining  $n-2$  elements, and so on.

### Algorithm - Considering ascending order

Selection Sort algorithm works on the above idea.

- Firstly, find the minimum element in the given array( $arr[0...n-1]$ ) and swap it with the element at the 0th index.
- Then, in the remaining  $n-1$  elements( $arr[0...n-2]$ ) again find the minimum element and swap it with the 1st index element.
- After the  $i$ th iteration all the array elements from index 0 to  $i$  will be sorted, therefore we will continue the above process, to fill the remaining array positions with the correct element.

Let's visualise the algorithm with the following example:

```
arr[ ] = {6, 3, 8, 9, 5}
```

```
// Find the minimum element in arr[0...4] and swap it with the 0th  
index element
```

```
{3, 6, 8, 9, 5}
```

// Find the minimum element in arr[1...4] and swap it with the 1st index element

{3, **5**, 8, 9, 6}

// Find the minimum element in arr[2...4] and swap it with the 2nd index element

{3, 5, **6**, 9, 8}

// Find the minimum element in arr[3...4] and swap it with the 3rd index element

{3, 5, 6, **8**, 9}

We can notice that after the algorithm ends, the given array is sorted in ascending order.

### Pseudo Code

```
for i := 0 to n-2
    select the smallest among A[i], . . . , A[n-1]
    swap it with A[i];
end
```

```
1 function selectionSort(array) {
2     let n = array.length;
3
4     for(let i = 0; i < n; i++) {
5         let min_index = i;
6         for(let j = i+1; j < n; j++){
7             if(array[j] < array[min_index]) {
8                 min_index=j;
9             }
10        }
11        let tmp = array[i];
12        array[i] = array[min_index];
13        array[min_index] = tmp;
14    }
15 }
16
```

JavaScript

```
17
18 function main(){
19     let arr=[6, 3, 8, 9, 5]
20
21     console.log('Given Array:',arr.join(' '))
22     selectionSort(arr)
23     console.log('Sorted Array:',arr.join(' '))
24 }
25
26 main()
```

```
1 #include <stdio.h>
2
3 void swap(int *a, int *b)
4 {
5     int temp = *a;
6     *a = *b;
7     *b = temp;
8 }
9
10 void selectionSort(int arr[], int n)
11 {
12     int min_index;
13
14     for (int i = 0; i < n-1; i++)
15     {
16         min_index = i;
17         for (int j = i+1; j < n; j++)
18         {
19             if (arr[j] < arr[min_index])
20                 min_index = j;
21         }
22         swap(&arr[min_index], &arr[i]);
23     }
24 }
25
26 void printArray(int arr[], int n)
27 {
28     for (int i = 0; i < n; i++)
29         printf("%d ", arr[i]);
```

C

```
30     printf("\n");
31 }
32
33 int main()
34 {
35     int arr[] = {6, 3, 8, 9, 5};
36     int n = sizeof(arr)/sizeof(arr[0]);
37
38     printf("Given Array: ");
39     printArray(arr, n);
40
41     selectionSort(arr, n);
42
43     printf("Sorted Array: ");
44     printArray(arr, n);
45
46     return 0;
47 }
48
```

```
1 public class Main
2 {
3     static void selectionSort(int arr[], int n)
4     {
5         int min_index;
6
7         for (int i = 0; i < n-1; i++)
8         {
9             min_index = i;
10            for (int j = i+1; j < n; j++)
11            {
12                if (arr[j] < arr[min_index])
13                    min_index = j;
14            }
15
16            int temp = arr[min_index];
17            arr[min_index] = arr[i];
18            arr[i] = temp;
19        }
20    }
```

Java

```

21
22     static void printArray(int arr[], int n)
23     {
24         for (int i = 0; i < n; i++)
25             System.out.print(arr[i] + " ");
26         System.out.println();
27     }
28
29     public static void main(String args[])
30     {
31         int arr[] = {6, 3, 8, 9, 5};
32         int n = arr.length;
33
34         System.out.print("Given Array: ");
35         printArray(arr, n);
36
37         selectionSort(arr, n);
38
39         System.out.print("Sorted Array: ");
40         printArray(arr, n);
41     }
42 }
43

```

```

1  def selectionSort(array):
2      for i in range(len(array)):
3          min_index = i
4          for j in range(i+1, len(array)):
5              if array[min_index] > array[j]:
6                  min_index = j
7          array[i], array[min_index] =
array[min_index], array[i]
8
9  if __name__=='__main__':
10     arr=[6, 3, 8, 9, 5]
11     print('Given Array',' '.join( str(x) for x in
arr ))
12     selectionSort(arr);
13     print('Sorted Array',' '.join( str(x) for x in
arr ))

```

Python 3

```

1  #include <iostream>

```

C++

```
2 using namespace std;
3
4 void swap(int *a, int *b)
5 {
6     int temp = *a;
7     *a = *b;
8     *b = temp;
9 }
10
11 void selectionSort(int arr[], int n)
12 {
13     int min_index;
14
15     for (int i = 0; i < n-1; i++)
16     {
17         min_index = i;
18         for (int j = i+1; j < n; j++)
19         {
20             if (arr[j] < arr[min_index])
21                 min_index = j;
22         }
23         swap(&arr[min_index], &arr[i]);
24     }
25 }
26
27 void printArray(int arr[], int n)
28 {
29     for (int i = 0; i < n; i++)
30         cout << arr[i] << " ";
31     cout << "\n";
32 }
33
34 int main()
35 {
36     int arr[] = {6, 3, 8, 9, 5};
37     int n = sizeof(arr)/sizeof(arr[0]);
38
39     cout << "Given Array: ";
40     printArray(arr, n);
41
```

```
42     selectionSort(arr, n);  
43  
44     cout << "Sorted Array: ";  
45     printArray(arr, n);  
46  
47     return 0;  
48 }  
49
```

## Properties of Selection Sort

**Time Complexity:**  $O(n^2)$  ; *There is no best or worst case time complexity for selection sort, because in any case it will search the minimum element linearly for all  $n-1$  traversals.*

**Space Complexity:**  $O(1)$

**In-Place Sorting Algorithm:** Yes

**Stable Sorting Algorithm:** Depends on implementation

## Advantages

- The total number of swaps in the selection sort algorithm will never exceed  $O(n)$ . Therefore it will be useful in the problems where we want to minimize the number of swaps while sorting.
- It is an In-Place sorting algorithm that does not require any extra space.

## Video Solution

```
<iframe width="560" height="315"  
src="https://www.youtube.com/embed/Xb6Y-oP6nPs"  
title="YouTube video player" frameborder="0" allow="accelerometer;  
autoplay; clipboard-write; encrypted-media; gyroscope; picture-in-  
picture" allowfullscreen></iframe>
```



CodeQuotient

codequo

Tutorial by codequotient.com | All rights

reserved, CodeQuotient 2025

tient.com