Rudhira Metal Industries

ISO 9001-2015 CERTIFIED COMPANY

OFFICIAL TECHNICAL SPECIFICATION CATALOGUE

FORGE FITTINGS DIMENSIONS CATALOGUE

DIMENSIONAL DATA & ENGINEERING STANDARDS

High Pressure Screwed (Threaded) & Socket Weld Fittings to ASME B16.11

COVERED TECHNICAL STANDARDS & SPECIFICATIONS

- ASME B16.11 / ASA B2.1 — Forged Screwed (Threaded) Fittings (3000# & 6000# LBS)
- Screwed 90° Elbows, Tees, 45° Elbows, Unions, Couplings, Half Couplings, Caps, Bushings & Plugs
- ASME B16.11 (2016) — Socket Weld Fittings (3000# & 6000# LBS)
- Socket Weld 90° Elbows, Tees, 45° Elbows, Unions, Couplings, Reducers, Half Couplings & Caps
- Size Range: 1/8" NB to 4" NB (10.3 mm to 114.5 mm Outside Diameter)
- Custom Tolerances and High Pressure Dimensional Standards Available on Request

RUDHIRA METAL INDUSTRIES — QUALITY ASSURANCE

ISO 9001:2015 Certified Manufacturing & Stockholding Facility

Material Test Certificates (EN 10204 3.1) • Positive Material Identification (PMI)

Third Party Inspection: Bureau Veritas, DNV, TUV, Lloyd's Register, PDIL, SGS

RUDHIRA METAL INDUSTRIES


Commercial Office: Khetwadi, Mumbai - 400 004, Maharashtra, India

Branches: GIDC Ankleshwar (Gujarat) | Ranigunj, Hyderabad (Telangana)


Phone: +91 98920 71909 / +91 99879 73244 • Email: sales@rudhirametal.com • Web: www.rudhirametal.com

DIMENSION IN MM OF FORGED SCREWED FITTINGS TO ANSI B-16.11 THREADED TO ASA B 2.1


90° ELBOWS




TEE




45° ELBOW




UNION




COUPLING




PIPE CAP



BUSHING



HEX HEAD PLUG




HALF COUPLING =G/2


NOM BORE	PIPE O.D.	3000 L.B.S.						COMMON FACTORS						6000 L.B.S					
		A	B	C	G	H	K	D	E	F	I	J	L	A	B	C	G	H	K
1/8"	10.3	21	22	17	32	16	19	11	10	40	-	6	-	25	25	19	32	22	-
1/4"	13.7	25	25	19	35	19	25	16	11	43	3	6	32	29	33	22	35	25	27
3/8"	17.2	29	33	22	38	22	25	17.5	13	48	4	8	38	33	38	25	38	32	27
1/2"	21.3	33	38	25	48	29	32	22	15	51	5	8	46	38	46	29	48	38	33
3/4"	26.7	38	46	29	51	35	37	27	16	57	6	10	51	44	56	33	51	44	38
1"	33.4	44	56	33	60	44	41	35	19	64	6	10	60	51	62	35	60	57	43
1 1/4"	42.2	51	62	35	67	57	44	44.5	21	70	7	14	72	60	75	43	67	64	46
1 1'2"	48.3	60	75	43	79	64	44	51	21	79	8	16	80	64	84	44	79	76	48
2"	60.3	64	84	45	86	76	48	63.5	22	88	9	17	94	83	102	52	86	92	51
2 1/2"	73.02	83	102	52	92	92	60	76	27	118	10	21	122	95	121	64	92	108	64
3"	89.0	95	121	64	108	108	65	89	29	121	10	25	140	106	146	79	108	127	68
4"	114.5	114	152	79	121	140	68	117.5	32	150	13	25	180	114	152	79	121	159	75

SOCKET WELD FITTING TO ANSI B-16.11 - 2016


90° ELBOWS




TEE




45° ELBOW




UNION




COUPLING




REDUCER



HALF COUPLING



CAP



NOM BORE	PIPE O.D.	3000 L.B.S.									COMMON FACTORS				6000 L.B.S				
		A	B	K	J	L	M	N	P	Q	C min	D min	O min	O max	A	B	M	K	N
1/8"	10.3	22	18.5	26	16	40	17.3	32	17.5	10	10.7	10	5	8	22	22	20	25	46
1/4"	13.7	22	22	26	18	43	21.2	32	17.5	10	14.1	10	5	8	27	25	24	25	51
3/8"	17.2	25	25	26	19	48	25.4	36	19	10	17.6	10	3	9	27	28	28	26	60
1/2"	21.3	27	32	30	21	51	31	43	22	10	21.7	10	6	13	31	34	34	31	72
3/4"	26.7	34	38	36	24	57	37	50	25	13	27	13	6	13	37	42	41	35	80
1"	33.4	37	46	40	25	64	45.2	60	27	13	33.8	13	9	17	42	50	50	40	94
1 1/4"	42.2	42	56	40	29	70	55	70	30	13	42.6	13	9	17	47	59	58	41	100
1 1'2"	48.3	47	62	40	30	79	61.4	78	32	13	48.7	13	9	17	53	67	55	43	122
2"	60.3	56	75	52	37	89	75	95	38	13	61.2	16	15	23	59	84	83	55	-
2 1/2"	73.02	60	92	52	48	114	91.3	125	38	16	73.8	16	14	24	-	102	-	56	-
3"	89.00	76	110	52	51	127	108.8	140	44	16	89.8	16	14	24	-	121	-	58	-
4"	114.50	88	137	58	-	150	136.9	-	48	19	115.5	19	14	24	-	152	-	64	-

DIMENSIONS AND OTHERS SPECIFICATIONS AS PER CUSTOMERS REQUIREMENTS ARE AVAILABLE ON REQUEST