

Collaboration & Communication Enhancements





M-series



Immersive Virtual & Hybrid Meeting Tech

Glonet M Series is designed for the classroom and brings efficiency to your classes and teams. With embedded collaborative tools, extensive connectivity, fantastic ease of use, and paper-like writing technology, Glonet M Series helps teachers build a dynamic and engaging learning environment.



Wi-Fi Module with Wi-Fi 6 Connectivity



Android 14 **8GB RAM** 64GB+64GB ROM (EXPANDABLE)



Full Range Freq. 40W Speaker



4K Camera Fixed & PTZ



Broad Compatibility



Type-C



Zero Bonding Powered USB

<u>Models</u>	<u>GN-65 M25I</u>	<u>GN-75 M25I</u>	<u>GN-86 M25I</u>			
Display						
Active Screen Size	65"	75"	86"			
Backlight	DLED	DLED	DLED			
Display Area (mm)	1428.48 (H) x 803.52 (V)	1649.664(H)×927.936(V)	1895.04(H)×1065.96(V)			
Display Ratio	16:9					
Resolution	3840 x 2160					
Display Refresh Rate	120Hz					
Colors	1.07G (8bits + FRC)					
Brightness Center With Glass (Min)	400 cd/m²	450 cd/m²	500 cd/m²			
Contrast (Typical)	15000:1	15000:1	15000:1			
Response Time (Typical)	4ms	4ms	4ms			
Viewing Angle (Typical)	H = 178, V = 178					
Display Life Time (MTBF)	≥50000 hours					
	Glass Surf	ace Technology				
Thichness	3.2mm H2					
Anti-Glar	YES					
Anti-Fingerprint	YES					
Touch Surface Hardness	8H					
Transparency	≥88%					
Dynamic Coefficient of friction	≤0.9					
Haze	4~8					
Air Gap between oc and glass	Zero					

Touch Technology				
IR Touch technology	IR			
Sensor XY Precision	32767*32767			
Touch Android Points	40			
Touch Windows Points	40			
Response time (ms)	≤3.3ms			
Touch Frame Rate (Hz)	≥300Hz			
Accuracy (mm)	±1mm (Central 90% Area)			
Minimum object size	2mm			
recognizable pen	YES			
recognizable Finger	YES			
recognizable Palm	YES			
Contact Detect Height	1.5mm			
	Stero Speaker			
Speaker Position	bottom down			
Speaker Rated Impedance	6Ω			
Speaker Freq.Response	280~20K Hz S.P.L10dB			
Speaker Sensitivity	78±3dB			
Speaker Rated Power Output	20W*2			
Camera Module				
Fixed Position	Тор			
Fixed Form	external			
Network Module				
WIFI	WiFi6			

Smart System					
SoC Chipset	MT9679				
СРИ	A73*4				
GPU	G52				
RAM	8 GB				
ROM	64GB				
External Memory	64GB (EXPANDABLE)				
UI Resolution	4К				
Android Version	Android 14				
	Front Control Panel				
Key Buttons	5* button: Power/Custom/Back/HomeMenu/				
IR Remote Sensor	YES				
Ambient Light Sensor	YES				
Lamp Status	Standby Mode:red light ,Working Mode: white light				
	Front I/O				
Type-C (Full/PD-65W)	1				
HDMI IN 2.0	1				
TOUCH USB2.0-B	1				
USB 3.0-A Host Public	2				
Microphone In (Line in)	1				
Rear I/O					
HDMI 2.0 in	1				
USB2.0 Type-C	1				
B2.0 Type-C for Camera (To	1				
USB 3.0-A to SOC	1				
USB 2.0-A Host Public	1				
TOUCH USB 2.0-B Device	1				

VGA in	1					
PC Audio in	1					
RS232-DB9	1					
Audio Line Out		1				
SPDIF out		1				
RJ45 (10/100/1000M)		2				
OPS Slot (4K@60Hz)		1				
		Accessories				
USB2.0 A-B Cable 3m	1					
HDMI 2.0 Cable 3m	1					
AC Power Cabel 2m	1					
3&10mm Dubble Poits Pens	2					
Simple Remote Controller	1					
AAA Alkaline Battery	2					
		Electrical Parameter				
AC Input	AC100-240V Max 10A					
Working Voltage	AC100-240V Max 4 A	AC100-240V Max 4.5 A	AC100-240V Max 5 A			
Power Consumption (Eco mode)	295W	286W	386W			
Power Consumption (full load)	325W	315W	425W			
Power Consumption (Standby mode)	0.5W					
Mechanical Mechanical						
wall-mounted by Landscape	YES					
wall-mounted by Portrait	YES					

VESA mounting (mm)	600*400	800*400	800*400		
mobile Bracket	optional				
Tile Range	0%				
Handles	2	2	4		
Transportation / Storage					
Working Temperature/Humidity	0~40°C 20~80%RH (non-condensing)				
Storage Temperature/Humidity	-10~45°C 20~90%RH (non-condensing)				
Outline Dimension (without wall mount) (mm)	1512.9x922.83x109. 865	1735.05x1047.32x111.065	1981.04x1186.05x111.065		
Packing Dimension (mm)	1640 x 208 x 1036	1859 x 227 x 1160	2119 x 250 x 1290		
Net Weight (kg)	37	50	61.5		
Gross Weight (kg)	46.5	62	77.5		



Head Office: F-42, OKHLA INDUSTRIAL AREA, PHASE-1, NEW DELHI-110020

WH: B-4, BHANDARI HOUSE, BUILDING NUMBER 91, NEHRU PLACE, New Delhi, South East Delhi, Delhi, 110019 **Regd.Off:** 530, Mandakini Enclave, Kalkaji, New Delhi-110019

Tel.: 011-41435255

Mob. No: 9821664744, 9814865133

E-mail : info@glonet.in **Website:** www.glonet.in