A deterministic, auditable engine for cross-theory claim comparison: cross-field discovery with built-in verification*

Anuja Khatri
Independent Researcher

2026-10

Abstract

I present a deterministic, typed engine that compares scientific claims across theories: each claim is reduced to typed fields (entity_type, axis, polarity, value) and a fixed rule-based judge assigns a correspondence grade or a fork. The judge is reproducible, provable and auditable. I re-express it as a logic program (verdict equivalence **1.0**, $n = 213$ pairs), as a first-order theory under an SMT solver (congruence **1.0**, $n = 311$ verdicts), with machine-checked proof objects (coverage **0.9842**, $n = 316$) and **0** integrity violations ($n = 316$). On the discovery side the engine recovers the COGITATE adversarial-collaboration key at **2 of 3** predictions (revised; $n = 3$; not significant against a 1000-key permutation null, $p = 0.075$). The eLife synergistic-workspace key recovery is below chance: **0 exact / 6 partial of 14** validated rows, empirical $p = 0.981$ ($n = 1000$; random keys recover more). The method's limits are first-class results: both key recoveries are reported with their chance rates, single-pass extraction carries a measured noise floor, and the extraction front-end under-propagates negation.

1 Introduction

Comparing scientific claims across competing theories is usually done by hand and by argument. This paper presents a deterministic engine that does it mechanically and auditably. Each claim is reduced to a small typed record (entity type, axis, polarity, value), and a fixed rule-based judge compares two claims from the typed fields alone, returning a correspondence grade or a fork. Because the judge is a function of typed fields, every comparison is reproducible, and the judge can be re-expressed as a logic program, as a first-order theory under an SMT solver [6], and as machine-checked proof objects. This division of labour, in which a language model proposes typed candidates and a sound external program disposes, follows the LLM-Modulo pattern of pairing a generator with verifiers it cannot talk its way past [7].

I exercise the engine on a frozen corpus of six theories of consciousness, with bridge extensions that link active inference [2] to machine learning (control as probabilistic inference [9]; predictive coding as an approximation to backpropagation [13]) and that span integrated information theory in its current formulation [1]; nothing in the method is specific to that domain. I report two kinds of result. On the discovery side, the engine re-adjudicates a founding cross-field correspondence

*Numbers locked to registry snapshot `e9c877812c8c6897...` (2026-10), instrument v2 / corpus v1. Every figure renders from that one snapshot; the locked registry and verification scripts accompany the public code release at https://github.com/Anuja-Khatri/consilience-verification.

record and attempts to recover two held-out, published answer keys, the COGITATE adversarial collaboration [4] and the eLife synergistic-workspace bridge [10], each scored against an explicit permutation chance rate. On the verification side, the judge's decisions are a transparent, checkable function of the typed fields, and a preregistered statement-level perturbation suite measures how the extraction front-end behaves under meaning-preserving and meaning-flipping edits. Throughout, I report the method's limits as first-class results rather than hiding them: discovery claims carry their chance rates, including an honest below-chance negative; single-pass extraction carries a measured noise floor; and the extraction front-end's under-propagation of negation is stated plainly. All figures render from a single numbers-locked registry snapshot.

2 Discovery

2.1 Cross-field re-adjudication

Re-running a founding physics×neuroscience×contemplative correspondence corpus through the frozen instrument (v2) and the deterministic judge: of the pairs carrying a recorded prior tier ($n = 7$), the new grade agrees with the prior at **0.1429** (1/7, $n = 7$) and downgrades or withdraws at **0.8571** (6/7, $n = 7$). Most originally-asserted cross-field correspondences do not survive re-typing under a fixed codebook; I report this as the method's discipline, not a headline.

2.2 Unification index

Ranking persisted node correspondences by a preregistered score (forks-touched + support-cone + axis-reach, weights 1/1/1): Kendall's τ [8] rank stability across the weight simplex is **0.7165** ($n = 216$ correspondences), moderately weight-sensitive and reported honestly; the generative grade dominates and is flagged.

2.3 Held-out key recoveries, with chance rates

Against the held-out adversarial-collaboration key [4], preregistered in advance [11], the v2 instrument recovers **2 of 3** predictions (revised gated result {2,0,1,9}; $n = 3$). Outcome-informed disclosure (verbatim): "iit_c009 was initially rejected at the gate; after a sensitivity check showed it was the sole binding claim for P3, it was re-reviewed and approved on codebook-consistency grounds (matching approved canonical iit_c025). Original gated result {1,0,2,9} and revised {2,0,1,9} are both reported; fully ungated sensitivity {2,0,1,16}." The remaining miss (P2, temporal_profile) is attributed to the instrument: no IIT temporal_profile claim was ever extracted (not a gate effect). Chance rate: 1000 random typed-row keys recover $\geq$ the real 2/3 with empirical permutation $p = 0.075$ ($n = 1000$) beside a normal-approx $z = 2.2693$, from the same recovered-count null; the discrete, right-skewed null makes the z overstate significance, so $p = 0.075$ ($n = 1000$) governs: it does not reach $\alpha = 0.05$ and is suggestive only. The engine never ingested the key text (holdout clean).

Of **14 validated bridge rows** [10] the engine's IIT×GNWT fork/correspondence set recovers **0 exact** and **6 partial** ($n = 14$), misses 8, with **0** rows unmappable to any engine axis ($n = 14$; the one vocabulary-gap row in the provisional 16-row build was among the 2 dropped at the format gate as methods, so the validated denominator of 14 carries 0 unmappable). Chance rate (honest negative): the 6-partial recovery does not beat chance. 1000 random typed-row keys recover more (null mean 9.2), empirical $p = 0.981$ ($n = 1000$), below the null. I report it as found: on the engine's IIT×GNWT set the eLife bridge's partial recovery is at or below chance.

3 Verification

3.1 Audit method

A rule-based criterion audit (provenance, quote-support, Newman screen, testability, scale): discovery survivorship **1 of 9** ($n = 9$) and sampled-match survivorship **2 of 30** ($n = 30$); strict, since most prior discoveries fail at least one criterion.

3.2 Instrument

Adopted decoding is `baseline-single-pass`. One stability estimator is used throughout: the sprint estimator **0.25** (95% CI [0.1713, 0.3496], $n = 88$), a measured noise floor every downstream contrast is scored against. (The prior Task-5 estimator on the same 80 runs is 0.271, a coarser cluster unit, reported only for comparison.)

3.3 The verified judge

Verdict equivalence **1.0** ($n = 213$); SMT congruence **1.0** ($n = 311$), discharged by the Z3 solver [6]; proof coverage **0.9842** ($n = 316$), with derivations machine-checked in the spirit of formalised-mathematics libraries [14]; **0** integrity violations ($n = 316$).

3.4 Statement-level contracts: the negation headline

An OSF-preregistered perturbation suite (DOI 10.17605/OSF.IO/5N24M) with a re-extraction noise-floor control. Polarity caveat: the claim store is near single-class on polarity (92 asserts / 3 denies), so the identity-control polarity stability **0.975** ($n = 40$) and the panel polarity agreement reported below largely reflect the extractor's default rather than demonstrated polarity reading, which is why the negation figure is the informative one. Explicit negation flips polarity only **0.1765** of the time ($n = 34$ valid); double negation restores to asserts **0.0** ($n = 8$ valid, low-n, since the perturber mostly fails to negate twice); L2 verdict tracking **0.4189** ($n = 74$). The deterministic judge is correct given fields; the extraction front-end under-propagates negation. A single-reviewer hand-check agrees with the automated verifier at **0.893** ($n = 28$).

3.5 Obfuscation control

Obfuscating surface vocabulary leaves fork recovery essentially unchanged (gap **0.072**, $n = 14$), but the extractor re-identifies the theories and emits their coined terms (**12** de-obfuscation leaks, $n = 14$): surface obfuscation does not reduce fork recovery and does not blind the model to theory identity.

3.6 Reliability framing

A two-vendor panel (gpt-4.1 × gemini-3.1-pro-preview, full coverage) measures protocol reproducibility, not validity: cross-vendor entity κ [5] **0.525** ($n = 95$), axis κ **0.503** ($n = 95$), polarity PABAK [3] **0.811** ($n = 95$); the polarity PABAK carries the single-class caveat noted for the negation headline above. Standing self-consistency is the adopted stability **0.25** (sprint estimator, 95% CI [0.1713, 0.3496], $n = 88$); the prior Task-5 estimator on the same runs is 0.271.

4 Limitations

These limitations import the pre-sprint evaluation's, which that report records and this paper supersedes under the lock.

The engine's six theories are all theories of consciousness, so results may not transfer to other fields; cross-field reach rests on the re-adjudication record and the corpus extensions, not the core. The reference labels were produced by the builder: the judge-after-audit reference reflects one builder's choices, and a second, independent annotator is planned but not yet run, so human agreement, the ceiling against which model agreement is read, is not yet available. In production a smaller same-family model cross-checks the main extractor; the gpt-4.1 × gemini-3.1-pro-preview panel is an evaluation add-on, not part of the production pipeline, and it measures reproducibility rather than validity. The corpus is small (95 approved claims, six theories); the deeper arms, embedding alignment, unsupervised optimal transport via Gromov-Wasserstein couplings [12], and partial-information decomposition of the verdict [15], are pilot-scale feasibility studies in a planned second paper.

Single-pass extraction carries a measured noise floor (stability **0.25**, $n = 88$); every invariance and tracking number is reported relative to the identity control, and negation tracking is itself a measured limitation. The store is near single-class on polarity (92 asserts / 3 denies), so polarity-stability figures reflect the extractor's default rather than demonstrated polarity reading. Holdout controls the prompt, not the training data: held-out keys never entered extraction or judging prompts (measured clean), but they may sit in a model's pretraining, and the obfuscation control is the measured response, which shows that identity is not blinded. Several review packets were judged at the statement level or from truncated excerpts, without full fork-side source text, so those arms are reported as "no fork flagged by the scan", not as validation of the forks. Decisions were model-drafted suggestions (Claude) reviewed and confirmed by the author. Finally, the open-weight panel leg is not run (no hosted-open-weight key), so the panel is two-vendor, stated here as a limitation.

5 Conclusion

The engine turns cross-theory claim comparison into a reproducible, auditable computation: a typed intermediate representation, a deterministic judge, and three independent re-expressions of that judge that agree exactly. Its discovery claims are modest by construction: most prior cross-field correspondences do not survive re-typing, one held-out key is recovered only suggestively, and the other is recovered below chance. I report them that way. The verification lane, not the discovery headline, is the contribution I stand behind: a claim-comparison verdict that is a checkable function of its inputs.

References

[1] Larissa Albantakis, Leonardo Barbosa, Graham Findlay, Matteo Grasso, et al. Integrated information theory (IIT) 4.0: Formulating the properties of phenomenal existence in physical terms. *PLOS Computational Biology*, 19, 2023. DOI https://doi.org/10.1371/journal.pcbi.1011465.

[2] Christopher L. Buckley, Chang Sub Kim, Simon McGregor, and Anil K. Seth. The free energy principle for action and perception: A mathematical review. *Journal of Mathematical Psychology*, 81, 2017. https://arxiv.org/abs/1705.09156; DOI https://doi.org/10.1016/j.jmp.2017.09.004.

[3] Ted Byrt, Janet Bishop, and John B. Carlin. Bias, prevalence and kappa. *Journal of Clinical Epidemiology*, 46, 1993. DOI https://doi.org/10.1016/0895-4356(93)90018-V.

[4] Cogitate Consortium. Adversarial testing of global neuronal workspace and integrated information theories of consciousness. *Nature*, 642, 2025. DOI https://doi.org/10.1038/s41586-025-08888-1.

[5] Jacob Cohen. A coefficient of agreement for nominal scales. *Educational and Psychological Measurement*, 20, 1960. DOI https://doi.org/10.1177/001316446002000104.

[6] Leonardo de Moura and Nikolaj Bjørner. Z3: An efficient SMT solver. In *Tools and Algorithms for the Construction and Analysis of Systems (TACAS)*, volume 4963, 2008. LNCS. DOI https://doi.org/10.1007/978-3-540-78800-3_24.

[7] Subbarao Kambhampati, Karthik Valmeekam, Lin Guan, Mudit Verma, Kaya Stechly, Siddhant Bhambri, Lucas Saldyt, and Anil B. Murthy. Position: LLMs can't plan, but can help planning in LLM-modulo frameworks. In *International Conference on Machine Learning (ICML)*, 2024. PMLR 235.

[8] Maurice G. Kendall. A new measure of rank correlation. *Biometrika*, 30, 1938. DOI https://doi.org/10.1093/biomet/30.1-2.81.

[9] Sergey Levine. Reinforcement learning and control as probabilistic inference: Tutorial and review, 2018. https://arxiv.org/abs/1805.00909.

[10] Andrea I. Luppi, Pedro A. M. Mediano, Fernando E. Rosas, et al. A synergistic workspace for human consciousness revealed by integrated information decomposition. *eLife*, 12, 2024. DOI https://doi.org/10.7554/eLife.88173.

[11] Lucia Melloni, Liad Mudrik, Michael Pitts, et al. An adversarial collaboration protocol for testing contrasting predictions of global neuronal workspace and integrated information theory. *PLOS ONE*, 18, 2023. Preregistered study protocol, e0268577. DOI https://doi.org/10.1371/journal.pone.0268577. OSF registration https://osf.io/92tbg.

[12] Facundo Mémoli. Gromov-wasserstein distances and the metric approach to object matching. *Foundations of Computational Mathematics*, 11, 2011. DOI https://doi.org/10.1007/s10208-011-9093-5.

[13] Beren Millidge, Alexander Tschantz, and Christopher L. Buckley. Predictive coding approximates backprop along arbitrary computation graphs. *Neural Computation*, 34, 2022. https://arxiv.org/abs/2006.04182.

[14] The mathlib Community. The Lean mathematical library. In *Certified Programs and Proofs (CPP)*, 2020. DOI https://doi.org/10.1145/3372885.3373824.

[15] Paul L. Williams and Randall D. Beer. Nonnegative decomposition of multivariate information, 2010. https://arxiv.org/abs/1004.2515.