A deterministic, auditable engine for cross-theory claim comparison: cross-field discovery with built-in verification*

Anuja Khatri
Independent Researcher

2026-10

Abstract

I present a deterministic engine that compares scientific claims across competing theories. Each claim is first reduced to a fixed schema of typed fields, in the style of information extraction: its entity type, its axis (the aspect of the system the claim addresses), its polarity (assertion versus negation), and a value. A deterministic rule-based verifier, which I call the judge, then compares two claims from these fields alone. Its output, the verdict, is either a grade of correspondence, an ordinal label for how strongly the two claims agree, or a fork, a question on which the theories make mutually incompatible commitments. The judge is reproducible, provable and auditable. I re-express it as a logic program (verdict equivalence **1.0**, $n = 213$ pairs), as a first-order theory under an SMT solver (congruence **1.0**, $n = 311$ verdicts), and as machine-checked proof objects (coverage **0.9842**, $n = 316$), with **0** integrity violations ($n = 316$). On the discovery side the engine recovers the COGITATE adversarial-collaboration key at **2 of 3** predictions (revised; $n = 3$; not significant against a 1000-key permutation null, $p = 0.075$). The eLife synergistic-workspace key recovery is below chance: **0 exact / 6 partial of 14** validated rows, with empirical $p = 0.981$ ($n = 1000$; random keys recover more). The method's limits are first-class results: both key recoveries are reported with their chance rates, single-pass extraction carries a measured noise floor (its test-retest reliability across repeated runs), and the extraction front-end under-propagates negation.

1 Introduction

Comparing scientific claims across competing theories is usually done by hand and by argument. This paper presents a deterministic engine that does it mechanically and auditably. Each claim is reduced to a small schema of typed fields (entity type, axis, polarity, value), in the style of information extraction, and a deterministic rule-based verifier, the judge, compares two claims from those fields alone, returning a grade of correspondence or a fork. Because the judge is a function of the typed fields, every comparison is reproducible, and the judge can be re-expressed as a logic program, as a first-order theory under an SMT solver [6], and as machine-checked proof objects. This division of labour, a language model proposing typed candidates and a sound external program disposing, follows the LLM-Modulo pattern of a generator paired with verifiers it cannot talk its

*Numbers locked to registry snapshot `e9c877812c8c6897...` (2026-10), pipeline v2 / corpus v1. Every figure renders from that one snapshot; the locked registry and verification scripts accompany the public code release at https://github.com/Anuja-Khatri/consilience-verification.

way past [7]. The judge reads only the typed fields, so the generator has no text channel through which to argue a verdict into being.

I exercise the engine on a versioned, immutable dataset of six theories of consciousness (the frozen corpus). Bridge extensions link active inference [2] to machine learning, through control as probabilistic inference [9] and predictive coding as an approximation to backpropagation [13], and span integrated information theory in its current formulation [1]; nothing in the method is specific to that domain. Throughout, the extraction front-end (its model, prompts and decoding settings) is held fixed and versioned, and I call this frozen pipeline the instrument. I report two kinds of result. On the discovery side, the engine re-adjudicates a founding cross-field correspondence record and attempts to recover two published answer keys: the COGITATE adversarial collaboration [4] and the eLife synergistic-workspace bridge [10]. These keys are held out from the engine's prompts, though they may sit in the underlying models' pretraining, and each recovery is scored against an explicit permutation chance rate. On the verification side, the judge's decisions are a transparent, checkable function of the typed fields, and a preregistered statement-level perturbation suite measures how the instrument behaves under meaning-preserving and meaning-flipping edits.

The verification lane is the contribution I stand behind, and the discovery results are deliberately modest. I report the method's limits as first-class results: both key recoveries carry their chance rates, including an honest below-chance negative; single-pass extraction carries a measured noise floor; and the under-propagation of negation is stated plainly. Every figure in the paper renders from a single numbers-locked registry snapshot, so the same quantity never drifts from one document to the next.

2 Discovery

2.1 Cross-field re-adjudication

Before this evaluation, the engine's earliest corpus was a set of correspondences asserted across physics, neuroscience and contemplative texts. I chose that corpus deliberately: it is where the vocabularies are most alien to one another, the hardest place for surface wording to do the work, and where the original claims were made with the least discipline. The re-adjudication test asks a simple question: if the earliest asserted correspondences are re-typed under today's frozen instrument (v2) and judged by today's fixed rules, how many survive? I re-ran every pair end to end through the deterministic judge. Of the pairs that carry a recorded prior grade ($n = 7$), the new grade agrees with the old one for a single pair (agreement **0.1429**, that is 1 of 7) and downgrades or withdraws the other six (**0.8571**, 6 of 7). I read this as the method working rather than failing: most originally asserted cross-field correspondences do not survive re-typing under a fixed codebook (the judge's rule set and field definitions). A judge strict enough to retire most of its builder's own early claims is what makes its surviving claims worth attention.

2.2 Unification index

The unification index is a ranking. It orders the correspondences the engine has persisted (the claim pairs the judge graded as matching) by how much unifying work each one does, so the pairs that tie the most theories together rise to the top. A ranking like this is only useful if it is stable, and the worry is that the order is an artifact of the particular weights I chose when combining its ingredients. The weight-simplex test checks that worry: it recomputes the ranking under every weighting across the simplex and asks whether the order holds. I scored each persisted correspondence by a preregistered combination of three ingredients (how many forks it touches, the

size of its supporting evidence cone, and how many axes it reaches), with weights 1/1/1. I then swept the weights across the simplex and measured Kendall's τ [8], the rank correlation between the base ranking and each reweighted one. Across the 216 correspondences in the ranking, the minimum τ over the sweep is **0.7165** ($n = 216$). I report this as moderately weight-sensitive rather than robust: the order is largely but not entirely weight-independent, and one ingredient dominates the score, which I flag.

2.3 Held-out key recoveries, with chance rates

COGITATE is an adversarial collaboration between proponents of two rival theories of consciousness, integrated information theory and global neuronal workspace theory (IIT and GNWT, respectively). Over several years they negotiated, in advance, a shared set of predictions and the experiments that would adjudicate them [4]. That negotiated key is the right benchmark precisely because it was so expensive to produce: if the engine, reading only the theories' own texts, recovers predictions that took years of expert argument to fix, the judge is doing something the surface text alone does not hand it. The key was preregistered before the collaboration's results were known [11], and the engine never ingested the key text, so the holdout is clean. I ran the instrument end to end against the three held-out predictions and then applied the review gate, which accepts or rejects each extracted claim. The engine recovers **2 of 3** predictions; the full counts of recovered, partial, missed and beyond-key claims are {2,0,1,9} ($n = 3$). Outcome-informed disclosure (verbatim): "iit_c009 was initially rejected at the gate; after a sensitivity check showed it was the sole binding claim for P3, it was re-reviewed and approved on codebook-consistency grounds (matching approved canonical iit_c025). Original gated result {1,0,2,9} and revised {2,0,1,9} are both reported; fully ungated sensitivity {2,0,1,16}." The one remaining miss, the second prediction (P2, on temporal profile), is a property of the instrument rather than the gate: no IIT temporal_profile claim was ever extracted. To judge whether recovering two of three is meaningful, I compared it against a null of 1000 random typed-row keys. The fraction of those keys that recover at least as much as the real key is the empirical permutation p, here $p = 0.075$ ($n = 1000$), beside a normal approximation $z = 2.2693$ from the same null. Because that null is discrete and right-skewed, the z overstates significance and the empirical $p = 0.075$ ($n = 1000$) governs: it does not reach $\alpha = 0.05$, so I read the COGITATE recovery as suggestive only.

The eLife bridge is a second, independent key of a different kind: a published, information-theoretic analysis that formalises a quantitative bridge between the same two theories, deriving where integrated information and the global workspace should correspond [10]. Built by different authors with different machinery than COGITATE, it is an independent check against a key no one on the engine side wrote. I compared the engine's IIT×GNWT fork and correspondence set against the **14 validated** bridge rows. Across those 14 rows the engine recovers **0 exact** matches and **6 partial** ones ($n = 14$) and misses 8, with **0** rows unmappable to any engine axis ($n = 14$). (The one vocabulary-gap row in the provisional 16-row build was among the 2 dropped at the format gate as methods, so the validated denominator of 14 carries 0 unmappable.) Scored against the same 1000-key null, the result does not beat chance: the random keys recover more on average (null mean 9.2), and the fraction of null keys doing at least as well as the engine is empirical $p = 0.981$ ($n = 1000$), placing the engine below the null. I report this as found: on the engine's IIT×GNWT set, the eLife bridge's partial recovery is at or below chance.

3 Verification

3.1 Audit method

Which of the engine's own earlier discoveries survive a strict audit? Before trusting any correspondence the engine surfaces, I wanted to know how many of its prior demonstration discoveries hold up under explicit criteria rather than impression. I applied a five-part criterion audit to each discovery, checking provenance, quote-support, a screen for superficial analogy (the Newman screen), testability and scale, and failing any discovery that misses even one criterion. Of the 9 demonstration discoveries, **1 of 9** survives all five criteria ($n = 9$); of a separate sample of 30 engine-asserted matches, **2 of 30** survive ($n = 30$). The audit is deliberately strict: most prior discoveries fail at least one criterion, which I treat as the audit doing its job.

3.2 Instrument

How much does the extraction front-end disagree with itself when the input has not changed? This is the test-retest reliability of the instrument, its self-consistency across repeated runs, which I report as the stability. Every downstream invariance and tracking figure is only interpretable against that floor, so I fix one estimate of it and use it throughout, scoring each contrast against the measured floor rather than against an idealised assumption of zero noise. The adopted decoding is `baseline-single-pass`, and I estimate the stability with the sprint estimator over repeated runs of the same passages. Across the 88 repeated-run units the sprint estimator puts the stability at **0.25** (95% CI [0.1713, 0.3496], $n = 88$). For comparison only, an earlier, coarser estimator on the same 80 runs reports 0.271. A noise floor this high is itself a limitation, and every invariance number below is read against it.

3.3 The verified judge

Can the judge's rules be proved correct rather than merely trusted? Because the judge is a function of the typed fields alone, independent formal re-expressions of the same rules should reproduce its verdicts exactly, making each verdict a checkable consequence of the inputs rather than a behaviour of one program. I re-expressed the judge three ways and compared each against it over the corpus: as a logic program, as a first-order theory discharged by the Z3 SMT solver [6], and as machine-checked proof objects in the spirit of formalised-mathematics libraries [14]. Across the 213 theory pairs in the corpus, the logic program returns the identical verdict in every case (verdict equivalence **1.0**, $n = 213$). Under the solver, the first-order theory is congruent with the judge on all the verdicts checked (**1.0**, $n = 311$). The proof objects cover **0.9842** of the 316 derivations ($n = 316$), with **0** integrity violations across those same 316 ($n = 316$). Three independent re-expressions agreeing exactly is the result the verification lane rests on: the verdicts are provable from their inputs, not taken on trust.

3.4 Statement-level contracts: the negation headline

What happens to a verdict when a sentence's meaning is flipped by negation? The judge is only trustworthy if the fields it reads track meaning, so I ran a preregistered, statement-level perturbation suite. The suite applies meaning-preserving and meaning-flipping edits to each passage and measures how the typed fields and the verdicts respond, scored against a re-extraction noise-floor control (OSF preregistration DOI 10.17605/OSF.IO/5N24M). One caveat frames the polarity numbers. The claim store, the versioned, immutable dataset of extracted claims, is near single-class on polarity, that is

on assertion versus negation (92 asserts, 3 denies). Because of that imbalance, the polarity stability under an identity control (the same passage re-extracted with no edit) is **0.975** ($n = 40$). The panel polarity agreement reported below largely reflects the extractor's default of assertion rather than a demonstrated reading of polarity, so the negation figure is the informative one. Under explicit negation, the extracted polarity flips as it should only **0.1765** of the time ($n = 34$). Under double negation, the extractor restores the assertion **0.0** of the time ($n = 8$, a low count because the perturber mostly fails to negate twice). And the verdict tracks the edit correctly, meaning its output label changes as it should, for **0.4189** of the 74 meaning-flipping edits ($n = 74$). The deterministic judge is correct given its fields; what these numbers locate is the extraction front-end under-propagating negation into those fields. A single-reviewer hand-check agrees with the judge's automated verification on **0.893** of 28 items ($n = 28$), so the gap is in extraction, not in the check.

3.5 Obfuscation control

Does hiding each theory's coined vocabulary change the engine's verdicts? If the correspondences were driven by surface wording, masking the signature terms should degrade them; if by the typed fields, masking should leave them intact. I ran two arms of extraction and fork recovery, identical except that one operated on passages with the theories' surface vocabulary obfuscated, and I recorded both the change in recovery and whether the extractor re-emitted the coined terms. Fork recovery is the share of the known forks the engine reproduces. Across the 14 reference forks, obfuscation moves it by only **0.072** ($n = 14$), so surface masking does not reduce fork recovery. It does not, however, blind the model to theory identity: over those same 14 the extractor re-identifies the theories and re-emits their coined terms, producing **12** such leaks ($n = 14$). The verdicts survive obfuscation, but the model still recognises which theories it reads.

3.6 Reliability framing

Do two different vendors' models type the same claims the same way? Cross-vendor agreement speaks to whether the typing protocol is reproducible across independent models, not to whether its verdicts are valid. I ran a two-vendor panel (gpt-4.1 × gemini-3.1-pro-preview, full coverage) and measured inter-model agreement on each typed field, over the 95 claims typed by both vendors. On entity type the agreement is **0.525** (Cohen's κ [5], $n = 95$) and on axis it is **0.503** (κ, $n = 95$). On polarity it is **0.811** (the prevalence- and bias-adjusted kappa, PABAK [3], $n = 95$), though this figure carries the single-class caveat noted for the negation headline above. Within a single model, the stability is **0.25** (the sprint estimator, 95% CI [0.1713, 0.3496], $n = 88$; an earlier, coarser estimator gives 0.271). Moderate cross-vendor agreement shows the protocol is reproducible across models, not that its typing is valid.

4 Limitations

These limitations carry over from an earlier internal evaluation that this paper supersedes. The engine's six theories are all theories of consciousness, so results may not transfer to other fields; cross-field reach rests on the re-adjudication record and the corpus extensions, not the core. The reference labels were produced by the builder, so the judge-after-audit reference reflects one builder's choices; a second, independent annotator is planned but not yet run, so human agreement, the ceiling against which model agreement is read, is not yet available. In production a smaller same-family model cross-checks the main extractor; the two-vendor panel is an evaluation add-on measuring reproducibility, not validity. The corpus is small (95 approved claims, six theories); the deeper

arms, embedding alignment, unsupervised optimal transport via Gromov-Wasserstein couplings [12], and partial-information decomposition of the verdict [15], are pilot-scale feasibility studies in a planned second paper.

Single-pass extraction carries a measured noise floor (stability **0.25**, $n = 88$), so every invariance and tracking number is reported relative to the identity control, and negation tracking is itself a measured limitation. The store is near single-class on polarity (92 asserts / 3 denies), so polarity-stability figures reflect the extractor's default rather than demonstrated polarity reading. Holdout controls the prompt, not the training data: held-out keys never entered extraction or judging prompts (measured clean) but may sit in a model's pretraining, which the obfuscation control, showing identity is not blinded, addresses. Several review packets were judged at the statement level or from truncated excerpts without full fork-side source text, so those arms are reported as "no fork flagged by the scan", not as validation of the forks. Decisions were model-drafted suggestions (Claude) reviewed and confirmed by the author, and the open-weight panel leg is not run (no hosted-open-weight key), so the panel is two-vendor.

5 Conclusion

The engine turns cross-theory claim comparison into a reproducible, auditable computation: a typed intermediate representation, a deterministic judge, and three independent re-expressions of it that agree exactly. Two lessons generalise beyond this corpus. First, a generator and verifier split pays off when the verifier is provable and reads only the structured fields, so the generating model has no text channel through which to argue a verdict into being. Second, honest evaluation here rested on fixed reference points: the perturbation suite was preregistered and scored against a measured noise floor rather than against zero; chance rates were estimated by random-key permutation, so that even a below-chance recovery is reported as one; and every document renders from a single locked registry snapshot, so no number drifts from one place to the next. The discovery claims themselves are modest by construction: most prior cross-field correspondences do not survive re-typing, one held-out key is recovered only suggestively, and the other below chance. I report them that way. The verification lane, not the discovery headline, is the contribution I stand behind: a claim-comparison verdict that is a checkable function of its inputs.

References

[1] Larissa Albantakis, Leonardo Barbosa, Graham Findlay, Matteo Grasso, et al. Integrated information theory (IIT) 4.0: Formulating the properties of phenomenal existence in physical terms. *PLOS Computational Biology*, 19, 2023. DOI https://doi.org/10.1371/journal.pcbi.1011465.

[2] Christopher L. Buckley, Chang Sub Kim, Simon McGregor, and Anil K. Seth. The free energy principle for action and perception: A mathematical review. *Journal of Mathematical Psychology*, 81, 2017. https://arxiv.org/abs/1705.09156; DOI https://doi.org/10.1016/j.jmp.2017.09.004.

[3] Ted Byrt, Janet Bishop, and John B. Carlin. Bias, prevalence and kappa. *Journal of Clinical Epidemiology*, 46, 1993. DOI https://doi.org/10.1016/0895-4356(93)90018-V.

[4] Cogitate Consortium. Adversarial testing of global neuronal workspace and integrated information theories of consciousness. *Nature*, 642, 2025. DOI https://doi.org/10.1038/s41586-025-08888-1.

[5] Jacob Cohen. A coefficient of agreement for nominal scales. *Educational and Psychological Measurement*, 20, 1960. DOI https://doi.org/10.1177/001316446002000104.

[6] Leonardo de Moura and Nikolaj Bjørner. Z3: An efficient SMT solver. In *Tools and Algorithms for the Construction and Analysis of Systems (TACAS)*, volume 4963, 2008. LNCS. DOI https://doi.org/10.1007/978-3-540-78800-3_24.

[7] Subbarao Kambhampati, Karthik Valmeekam, Lin Guan, Mudit Verma, Kaya Stechly, Siddhant Bhambri, Lucas Saldyt, and Anil B. Murthy. Position: LLMs can't plan, but can help planning in LLM-modulo frameworks. In *International Conference on Machine Learning (ICML)*, 2024. PMLR 235.

[8] Maurice G. Kendall. A new measure of rank correlation. *Biometrika*, 30, 1938. DOI https://doi.org/10.1093/biomet/30.1-2.81.

[9] Sergey Levine. Reinforcement learning and control as probabilistic inference: Tutorial and review, 2018. https://arxiv.org/abs/1805.00909.

[10] Andrea I. Luppi, Pedro A. M. Mediano, Fernando E. Rosas, et al. A synergistic workspace for human consciousness revealed by integrated information decomposition. *eLife*, 12, 2024. DOI https://doi.org/10.7554/eLife.88173.

[11] Lucia Melloni, Liad Mudrik, Michael Pitts, et al. An adversarial collaboration protocol for testing contrasting predictions of global neuronal workspace and integrated information theory. *PLOS ONE*, 18, 2023. Preregistered study protocol, e0268577. DOI https://doi.org/10.1371/journal.pone.0268577. OSF registration https://osf.io/92tbg.

[12] Facundo Mémoli. Gromov-wasserstein distances and the metric approach to object matching. *Foundations of Computational Mathematics*, 11, 2011. DOI https://doi.org/10.1007/s10208-011-9093-5.

[13] Beren Millidge, Alexander Tschantz, and Christopher L. Buckley. Predictive coding approximates backprop along arbitrary computation graphs. *Neural Computation*, 34, 2022. https://arxiv.org/abs/2006.04182.

[14] The mathlib Community. The Lean mathematical library. In *Certified Programs and Proofs (CPP)*, 2020. DOI https://doi.org/10.1145/3372885.3373824.

[15] Paul L. Williams and Randall D. Beer. Nonnegative decomposition of multivariate information, 2010. https://arxiv.org/abs/1004.2515.