

Chapter 05 - Let's get Hooked!

Assignment

● What is the difference between Named Export, Default export and * as export?

Ans: In JavaScript/React, exports are used to share variables, functions or components Between files using ES6 modules.

There are mainly 3 types of exports

1. Default Export 2. Named Export 3. Namespace import (* as Import)

1. Default Export: Here a file can have only ONE default export..

Eg. App.js file

```
Function App () {  
  Return <h1> Hello </h1>  
}  
  
Export default App;  
  
Import App from “./App”;
```

2. Named Export

As default Export export only one thing at a time;

To export multiple things we use Named Export.

Eg. Export const name = “Anuja”;

```
Export function greet () {  
  Return “hello”;  
}
```

```
Import { name, greet } from “./App”;
```

Note: We have to use same name while importing, and

Use curly braces {}

3. * as Import

Imports ALL named exports as an object.

```
Export const name = “Anuja”;
```

```
Export const age = 22;
```

Import * as user from “./App”;

● What is the importance of config.js file?

Ans: A config.js file is used to store and manage configuration values of an Application in one place instead of Hard coding everywhere.

It for make Application Clean, reusable, scalable and easier to maintain.

Eg. Config.js

```
Export const CDN_URL = “https://cdn.example.com/images/”;
```

```
Export const API_URL = “https://api.example.com”;
```

Usage

```
Import { CDN_URL } from “./config”;
```

```
Const image = CDN_URL + “pizza.png”;
```

● What are React Hooks?

Ans: -“HOOKS” are the pre-build functions in React..

- Basically it is a regular JavaScript functions modified with the Underlying logic by React Developers.

- When we install React Via npm, we gain access to These Hooks.

● Why do we need a useState Hook?

Ans: We need useState Hook, because when State changes The Data Layer get updated, but UI layer is not getting update According to the State Change.

- To overcome this we use useState Hook.

Syntax of useState()

```
Const [ listOfRestaurants, setListOfRestaurants ] = useState ([]);
```

- Initially we pass the empty array inside the useState([]).
- In this example it serves the listOfRestaurants as a initial value.
- To modify we pass the second argument setListOfRestaurants.

We are using setListOfRestaurant inside the call-back function to show the filtered restaurant. on clicking the button we will see

the Updated top-rated restaurant.

```
<button  
  className="filter-btn"  
  onClick={() => {  
    const filtertheRestaurant = listOfRestaurant.filter((res)  
=> {  
      return ( res.data.avgRating > 4));  
    });  
    setListOfRestaurant(filtertheRestaurant);  
  }}  
>  
  Top Rated Restaurant  
</button>
```