


## ANUJA PANDEY BATCH 5

1. Console "Hello Word" in document.ready function

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="UTF-8">
  <title>JQuery Practice</title>
  <script type="text/javascript"
src="https://ajax.googleapis.com/ajax/libs/jquery/3.1.1/jquery.min.js"></script>
</head>
<body>
  <script>
    $(document).ready(function () {
      console.log("Hello World");
    });
  </script>
</body>
</html>
```




2. Select a ID name "#test" and add class "load" when DOM is loaded

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="UTF-8">
  <title>JQuery Practice</title>
  <style>
```

```

        .load{
            background-color: red;
        }
    </style>
    <script type="text/javascript"
src="https://ajax.googleapis.com/ajax/libs/jquery/3.1.1/jquery.min.js"></script>
</head>
<body>
    <div id="test">Assignment</div>
    <div class="load">Bye</div>
    <script>
        $( "#test" ).addClass( "load" );
    </script>
</body>
</html>

```



3. Change the color of element which class name end with "-new"

```


<!DOCTYPE html>
<html lang="en">
<head>
    <meta charset="UTF-8">
    <title>JQuery Practice</title>
    <script type="text/javascript"
src="https://ajax.googleapis.com/ajax/libs/jquery/3.1.1/jquery.min.js"></script>
</head>

```

```

<body>
  <div class="tothenew">The new Beginning</div>
  <div class="brandnew">New life</div>
  <div class="Welcome">Hello again</div>
  <script>
    $("div[class$='new']").css("color", "red");
  </script>
</body>
</html>

```



4. Disable submit button using jquery attr method

```

<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="UTF-8">
  <title>JQuery Practice</title>
  <script type="text/javascript"
src="https://ajax.googleapis.com/ajax/libs/jquery/3.1.1/jquery.min.js"></script>
</head>


<body>
<form>
  FName: <input type="text" id="FirstName">
  LName: <input type="text" id="LastName">
  <input type="submit" id="submit" value="submit">
</form>

```

```

<script>
$('#submit').prop('disabled', true);
</script>
</body>
</html>

```




5. Change the font size of ".target" which has parent element with id name "#main"

```

<!DOCTYPE html>
<html lang="en">
<head>
<meta charset="UTF-8">
<title></title>
</head>
<body>
<script type="text/javascript" src="https://ajax.googleapis.com/ajax/libs/jquery/3.1.1/jquery.min.js">
</script>
<div id="main">
Main
<div class="target"> First Line </div>

<div class="target1">
Second Line
</div>
</div>
<script>
$("#main").children(".target").css('font-size', "200%");
</script>
</body>
</html>

```



6. After page load change the HTML of div element with "p" element

```
<!DOCTYPE html>
```

```
<html lang="en">
```

```
<head>
```

```
<meta charset="UTF-8">
```

```
<title>JQuery Practice</title>
```

```
<style>
```

```
div{  
  color:green;  
}
```

```
p{  
  color:red;  
}
```

```
</style>
```

```
<script type="text/javascript"
```

```
src="https://ajax.googleapis.com/ajax/libs/jquery/3.1.1/jquery.min.js"></script>
```

```
</head>
```

```
<body>
```


```
<div class="target">Hello World</div>
```

```
<p class="text">text</p>
```

```
<script>
```

```
$("document").ready(function() {  
  var data=$("p.text").text();  
  $("div").replaceWith(data);
```

```
});
</script>
</body>
</html>
```



7. Bind a click function to an "click" element and append next "click" next to it.

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="UTF-8">
  <title>JQuery Practice</title>
</head>
<body>
  <button>Click me</button>
  <div class="prac">Welcome</div>
  <script type="text/javascript" src="https://ajax.googleapis.com/ajax/libs/jquery/3.1.1/jquery.min.js"></script>
  <script type="text/javascript">

    $(document).ready(function(){


      $("button").click(function(){

        $("div.prac").append("<p class='add'>First Element</p><button class='btn1'>AddElement</button>");

      });
    });

  </script>
</body>
```

</html>



8. Click event not working on element which added dynamically or via script, make it work using .on method

```
<!DOCTYPE html>
```

```
<html lang="en">
```

```
<head>
```

```
<meta charset="UTF-8">
```

```
<title>JQery Practice</title>
```

```
</head>
```

```
<body>
```

```
<button>Click me</button>
```

```
<div class="prac">Welcome</div>
```

```
<script type="text/javascript"
```

```
src="https://ajax.googleapis.com/ajax/libs/jquery/3.1.1/jquery.min.js"></script>
```

```
<script type="text/javascript">
```

```
$(document).ready(function(){
```


```
    $("button").click(function(){
```

```
        $("div.prac").append("<p class='add'>First Element</p><button  
class='btn1'>AddElement</button>");
```

```

});
});
$(document).on("click", "button.btn1", function() {
    $("button.btn1").remove();
    $("p.add").append("<p>Second Element</p><button class='btn2'>Add
Element</button>");
});
$(document).on("click", "button.btn2", function() {
    $("button.btn2").remove();
    $("p.add").append("<p>Third Element</p>");
});
</script>
</body>
</html>

```



9. Get dropdown selected value on onchange event and append in div container

```

<!DOCTYPE html>
<html lang="en">
<head>
    <meta charset="UTF-8">
    <title>JQuery Practice</title>
    <script src="https://code.jquery.com/jquery-1.10.2.js"></script>
</head>
<body>

```




```
<div>
<ul>
  <li class="drop"><a href="#">Link</a></li>
  <ul class="dropdown">
    <li><a href="#" class="link1">Hello</a> </li>
    <li><a href="#" class="link2">World</a> </li>
  </ul>
</ul>
</div>
<div class="add">hi!</div>
<script>
  $(document).ready(function() {

    $(".link1").click(function () {
      var value=$(".link1").text();
      $(".div.add").append(value);

    });
    $(".link2").click(function () {
      var value=$(".link2").text();
      $(".div.add").append(value);

    });
  });

</script>
</body>
</html>
```




10. Create a dropdown menu using hover method in jquery

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="UTF-8">
  <title>JQuery Practice</title>
  <script src="https://code.jquery.com/jquery-1.10.2.js"></script>
</head>
<body>
<div class="menu">
  <ul>
    <li><a href="#">Link</a>
    <ul class="dropdown-menu">
      <li>HTML</li>
      <li>CSS</li>
      <li>JScript</li>
      <li>jQuery</li>
    </ul>
  </li>
</ul>
</div>
<script>
  $( ".menu li" ).hover(
    function() {
      $(".dropdown-menu",this).slideDown(100);
```

```

    },function () {
        $(".dropdown-menu",this).stop().slideUp(100);
    }
);
</script>
</body>
</html>

```



11. On clicking on "google" tag. It is taking us to google home page. Stop it from happening.

```


<!DOCTYPE html>
<html lang="en">
<head>
    <meta charset="UTF-8">
    <title>jQuery Practice</title>
    <script src="https://code.jquery.com/jquery-1.10.2.js"></script>
</head>
<body>
<div><a href="www.google.com" class="link1">Link</a></div>
<script>
    $(document).ready(function() {
        $(".link1").click(function (e) {
            e.preventDefault();
        });
    });

```

```

</script>
</body>
</html>

```



12. We have bind a click funtion to parent div but we want stop it from performing when user clicks on its child li


```

<!DOCTYPE html>
<html lang="en">
<head>
<meta charset="UTF-8">
<title>JQuery Practice</title>
<script src="https://code.jquery.com/jquery-1.10.2.js"></script>
</head>
<body>
<div>
<button id="parentclick">parent button</button>
<div>
<ul>
<li><button class="childclick">child li</button></li>
<li><button class="childclick">child li</button></li>
<li><button class="childclick">child li</button></li>
<li><button class="childclick">child li</button></li>
</ul>
</div>
</div>
<script>

```

```
$("#parentclick").click(function () {
    alert("Hello World!!!");
});
```

```
$(".childclick").click(function () {
    $("#parentclick").prop("disabled",true);
});
</script>
</body>
</html>
```




13. Get the max height of elements using jquery each method

```
<!DOCTYPE html>
<html lang="en">
<head>
    <meta charset="UTF-8">
    <title>jQuery Practice</title>
    <script src="https://code.jquery.com/jquery-1.10.2.js"></script>
</head>
<body>
    <div class="div1" style="height: 100px">Hello World</div>
    <div class="div1" style="height: 50px">Welcome Again</div>
    <script>
        var max=-1;
        $(".div1").each(function() {
            var h= $(this).height();
```

```

    max= h > max ? h:max;
  });
  console.log(max);
</script>
</body>
</html>

```




14. Change color of every cell which has number I larger than 10.

```

<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="UTF-8">
  <title>JQuery Practice</title>
  <script src="https://code.jquery.com/jquery-1.10.2.js"></script>
</head>
<body>
  <div class="table1">
    <table>
      <tr>
        <td>11</td>
        <td>02</td>
        <td>33</td>
      </tr>
      <tr>
        <td>04</td>

```

```
<td>45</td>
<td>06</td>
</tr>
<tr>
  <td>77</td>
  <td>08</td>
  <td>19</td>
</tr>
<tr>
  <td>10</td>
  <td>01</td>
  <td>22</td>
</tr>
<tr>
  <td>03</td>
  <td>04</td>
  <td>15</td>
</tr>
</table>
</div>
<script>
  $(document).ready(function(){
    $("tr td").each(function () {
      if(parseInt($(this).text())>10)
        $(this).css( "color", "red" );
    });
  });
</script>
</body>
</html>
```




15. Retrieve the data from server using ajax get call

```
<!DOCTYPE html>
<html>
<head>
<script src="https://ajax.googleapis.com/ajax/libs/jquery/3.3.1/jquery.min.js"></script>

</head>
<body>
<div id="url"></div>
<script>
$.ajax({
  url:"https://jsonplaceholder.typicode.com/posts"
}).done(function (resp){
  console.log(resp);
  for(var i=0;i<resp.length;i++){
    $("#url").append(resp[i].title+ "<br/>");
  }
})
</script>

</body>
</html>
```





16. Add cross button on row and bind click function which make a delete request to server, after success event remove the row from dom

17. Create a image array and in div create a slide show to animate images of delay of 500ms.