Overview

TASK:- 2

Emails were analyzed to detect phishing attacks using common indicators.

Figure: Example phishing email

```
Downloading mail_parser-4.2.1-py3-none-any.whl (33 kB)
Installing collected packages: mail-parser
Successfully installed mail-parser-4.2.1

┌──(myenv)─(amuj㉿kali)-[~/futureintern]
└─$ mail-parser email1.txt
usage: mail-parser [-h] (-f FILE | -s STRING | -k) [-l {CRITICAL,ERROR,WARNING,INFO,DEBUG,NOTSET}] [-j] [-b] [-a] [-r] [-t] [-dt] [-m] [-u] [-c] [-d] [-o] [-i Trust mail server string] [-p] [-z] [-sa] [-ap ATTACHMENTS_PATH] [-v]
mail-parser: error: one of the arguments -f/--file -s/--string -k/--stdin is required

┌──(myenv)─(amuj㉿kali)-[~/futureintern]
└─$ mail-parser -f email1.txt

┌──(myenv)─(amuj㉿kali)-[~/futureintern]
└─$ nano email1.txt

┌──(myenv)─(amuj㉿kali)-[~/futureintern]
└─$ mail-parser -f email1.txt

┌──(myenv)─(amuj㉿kali)-[~/futureintern]
└─$ mail-parser -f email1.txt -j
{
  "to": [
    [
      "",
      "user@gmail.com"
    ]
  ],
  "message-id": "<1234@fake.com>",
  "timezone": "+0.0",
  "subject": "Urgent: Account Verification Required",
  "content-type": "text/plain",
  "to_domains": [
    "gmail.com"
  ],
  "mime-version": "1.0",
  "from": [
    [
      "",
      "support@amazon.in"
    ]
  ],
  "body": "Dear Customer,\n\nYour account has been suspended due to suspicious activity.\nClick here:\nhttp://amazon-security-login.xyz\n\nThank you,\nSupport Team\n",
  "date": "2026-04-13T10:00:00+00:00",
  "has_defects": false
}

┌──(myenv)─(amuj㉿kali)-[~/futureintern]
└─$
```

Phishing Attack: Analysis, Risk and Prevention

01

ANALYSIS

Fake sender domain
Suspicious link
Urgent message

02

RISK

Credential theft
Financial loss
Unauthorized access

03

PREVENTION

Verify sender
Avoid unknown links
Enable 2FA

Conclusion

User awareness is the best defense against phishing.