

Stack Data Structure

- Collection of similar type of elements. Element can be always added on top position and element can be deleted always from top position.
- Follows LIFO. Element which is added on stack at the end can be deleted first
- **Stack can be implemented**
 - **Using Static Implementation of Memory**
 - Stack size can not be increased or decreased at runtime.
 - Can be used when stack size is predefined
 - **Using Dynamic Implementation of Memory**
 - Stack size can be increased or decreased at runtime.
 - Optimized usage of memory



Stack Data Structure

- Operations can be performed on stack

- **push** – adds a element on stack
 - isfull - checks full state of stack

$\text{top} == \text{SIZE}-1 ? \text{TRUE} : \text{FALSE}$

- **pop** – deletes top most element from stack
 - isempty – checks empty state of stack

$\text{top} == -1 ? \text{TRUE} : \text{FALSE}$

- **peek** – retrieves top most element from stack
 - isempty – checks empty state of stack

$\text{top} == -1 ? \text{TRUE} : \text{FALSE}$



Applications of Stack

- Recursion
- Expression Conversion and Evaluation
- Undo / Redo Operations
- Forward / Backward Web pages
- Depth First search



Expressions

- Expressions can be represented in 3 forms

- **Infix Expression** $a + b$ Left Operand \rightarrow Operator \rightarrow Right Operand
- **Prefix Expression** $+ a b$ Operator \rightarrow Left Operand \rightarrow Right Operand
- **Postfix Expression** $a b +$ \rightarrow Left Operand \rightarrow Right Operand \rightarrow Operator



Infix to Postfix

```
If read char == '(' then
    Push Element on stack
Else if read char is operand then
    join to postfix string
Else if read char is operator then
    peek element from stack
    if peeked element is '(' then
        push element on stack
    else if peeked element is operator then
        if priority(peeked element) >= priority(read char)
            pop() element from stack
            join peeked element to postfix
        push read char on stack
Else if read char is ')' then
    pop elements from stack till peeked element is '('
    join each popped element to postfix except '('
```



(A + (B / C - (D * E ^ F) + G) * H		(Infix to Postfix)
((A
A	(A
+	(+	A
((+(A
B	(+(AB
/	(+(/	AB
C	(+(/	ABC
-	(+(-	ABC/
((+(-(ABC/
D	(+(-(ABC/D
*	(+(-(*	ABC/D
E	(+(-(*	ABC/DE
^	(+(-(* ^	ABC/DE
F	(+(-(* ^	ABC/DEF



)	(+(-	ABC/DEF^*
+	(+(+	ABC/DEF^*-
G	(+(+	ABC/DEF^*-G
)	(+	ABC/DEF^*-G+
*	(+*	ABC/DEF^*-G+
H	(+*	ABC/DEF^*-G+H
)		ABC/DEF^*-G+H*+



Prefix to Infix

- Start reading string in reverse order
- If read char is operand push on stack
- Else If read char is operator pop() twice
 - Consider first pop() result as left operand
 - Consider second pop() result as right operand
 - Concatenate left operand → Operator → Right Operand
 - Consider converted infix operand hence push on stack



Postfix Evaluation

Read is char from postfix string till not null

If read char is operand

push read char on stack

Else if read char is operator

pop() element twice

Consider first pop() result as right operand

Consider second pop() result as left operand

Evaluate operands based on read operator

Consider result as operand and push on stack

If postfix string reaches to null pop() left element from stack is result





Thank you!

