

Taxi demand prediction in New York City

In [2]:

```
import pandas as pd
import numpy as np

from google.colab import drive
drive.mount('/content/drive')
%cd ./drive/My Drive
```

Drive already mounted at /content/drive; to attempt to forcibly remount, call drive.mount("/content/drive", force_remount=True).
[Errno 2] No such file or directory: './drive/My Drive'
/content/drive/My Drive

In [3]:

```
#Importing Libraries
# pip3 install graphviz
!pip3 install gpxpy
#pip3 install toolz
#pip3 install cloudpickle
# https://www.youtube.com/watch?v=ieW3G7ZzRZ0
# https://github.com/dask/dask-tutorial
# please do go through this python notebook: https://github.com/dask/dask-tutorial/blob/master/07\_dataframe.ipynb
import dask.dataframe as dd#similar to pandas

import pandas as pd#pandas to create small dataframes

# pip3 install folium
# if this doesnt work refere install_folium.JPG in drive
import folium #open street map

# unix time: https://www.unixtimestamp.com/
import datetime #Convert to unix time

import time #Convert to unix time

# if numpy is not installed already : pip3 install numpy
import numpy as np#Do arithmetic operations on arrays

# matplotlib: used to plot graphs
import matplotlib
# matplotlib.use('nbagg') : matplotlib uses this protocol which makes plots more user
# interactive like zoom in and zoom out
matplotlib.use('nbagg')
import matplotlib.pyplot as plt
import seaborn as sns#Plots
from matplotlib import rcParams#Size of plots

# this lib is used while we calculate the stight line distance between two (lat,lon) pa
# irs in miles
import gpxpy.geo #Get the haversine distance

from sklearn.cluster import MiniBatchKMeans, KMeans#Clustering
import math
import pickle
import os

# download mingwin: https://mingw-w64.org/doku.php/download/mingw-builds
# install it in your system and keep the path, mingw_path ='installed path'
mingw_path = 'C:\\\\Program Files\\\\mingw-w64\\\\x86_64-5.3.0-posix-seh-rt_v4-rev0\\\\mingw64
\\\\bin'
os.environ['PATH'] = mingw_path + ';' + os.environ['PATH']

# to install xgboost: pip3 install xgboost
# if it didnt happen check install_xgboost.JPG
import xgboost as xgb

# to install sklearn: pip install -U scikit-learn
from sklearn.ensemble import RandomForestRegressor
from sklearn.metrics import mean_squared_error
from sklearn.metrics import mean_absolute_error
import warnings
warnings.filterwarnings("ignore")
```

```
Collecting gpxpy
  Downloading https://files.pythonhosted.org/packages/6e/d3/ce52e67771929d
e455e76655365a4935a2f369f76dfb0d70c20a308ec463/gpxpy-1.3.5.tar.gz (105kB)
    |████████████████████████████████████████| 112kB 2.9MB/s
Building wheels for collected packages: gpxpy
  Building wheel for gpxpy (setup.py) ... done
  Created wheel for gpxpy: filename=gpxpy-1.3.5-cp36-none-any.whl size=403
15 sha256=57436ba3e6b82d8edff5d5bc63fb9586d1da9525a4267c513daa9aa224d6878e
  Stored in directory: /root/.cache/pip/wheels/d2/f0/5e/b8e85979e66efec3ea
a0e47fbc5274db99fd1a07befd1b2aa4
Successfully built gpxpy
Installing collected packages: gpxpy
Successfully installed gpxpy-1.3.5
```

Data Information

Get the data from : http://www.nyc.gov/html/tlc/html/about/trip_record_data.shtml (2016 data) The data used in the attached datasets were collected and provided to the NYC Taxi and Limousine Commission (TLC)

Information on taxis:

Yellow Taxi: Yellow Medallion Taxicabs

These are the famous NYC yellow taxis that provide transportation exclusively through street-hails. The number of taxicabs is limited by a finite number of medallions issued by the TLC. You access this mode of transportation by standing in the street and hailing an available taxi with your hand. The pickups are not pre-arranged.

For Hire Vehicles (FHV)

FHV transportation is accessed by a pre-arrangement with a dispatcher or limo company. These FHVs are not permitted to pick up passengers via street hails, as those rides are not considered pre-arranged.

Green Taxi: Street Hail Livery (SHL)

The SHL program will allow livery vehicle owners to license and outfit their vehicles with green borough taxi branding, meters, credit card machines, and ultimately the right to accept street hails in addition to pre-arranged rides.

Credits: Quora

Footnote:

In the given notebook we are considering only the yellow taxis for the time period between Jan - Mar 2015 & Jan - Mar 2016

Data Collection

We Have collected all yellow taxi trips data from jan-2015 to dec-2016(Will be using only 2015 data)

file name	file name size	number of records	number of features
yellow_tripdata_2016-01	1. 59G	10906858	19
yellow_tripdata_2016-02	1. 66G	11382049	19
yellow_tripdata_2016-03	1. 78G	12210952	19
yellow_tripdata_2016-04	1. 74G	11934338	19
yellow_tripdata_2016-05	1. 73G	11836853	19
yellow_tripdata_2016-06	1. 62G	11135470	19
yellow_tripdata_2016-07	884Mb	10294080	17
yellow_tripdata_2016-08	854Mb	9942263	17
yellow_tripdata_2016-09	870Mb	10116018	17
yellow_tripdata_2016-10	933Mb	10854626	17
yellow_tripdata_2016-11	868Mb	10102128	17
yellow_tripdata_2016-12	897Mb	10449408	17
yellow_tripdata_2015-01	1.84Gb	12748986	19
yellow_tripdata_2015-02	1.81Gb	12450521	19
yellow_tripdata_2015-03	1.94Gb	13351609	19
yellow_tripdata_2015-04	1.90Gb	13071789	19
yellow_tripdata_2015-05	1.91Gb	13158262	19
yellow_tripdata_2015-06	1.79Gb	12324935	19
yellow_tripdata_2015-07	1.68Gb	11562783	19
yellow_tripdata_2015-08	1.62Gb	11130304	19
yellow_tripdata_2015-09	1.63Gb	11225063	19
yellow_tripdata_2015-10	1.79Gb	12315488	19
yellow_tripdata_2015-11	1.65Gb	11312676	19
yellow_tripdata_2015-12	1.67Gb	11460573	19

In [4]:

```
#Looking at the features
# dask dataframe : # https://github.com/dask/dask-tutorial/blob/master/07_dataframe.ipynb
month = dd.read_csv('yellow_tripdata_2015-01.csv')
print(month.columns)
```

```
Index(['VendorID', 'tpep_pickup_datetime', 'tpep_dropoff_datetime',
      'passenger_count', 'trip_distance', 'pickup_longitude',
      'pickup_latitude', 'RateCodeID', 'store_and_fwd_flag',
      'dropoff_longitude', 'dropoff_latitude', 'payment_type', 'fare_amo
nt',
      'extra', 'mta_tax', 'tip_amount', 'tolls_amount',
      'improvement_surcharge', 'total_amount'],
      dtype='object')
```

In [5]:

```
# However unlike Pandas, operations on dask.dataframes don't trigger immediate computation,
# instead they add key-value pairs to an underlying Dask graph. Recall that in the diagram below,
# circles are operations and rectangles are results.
```

```
# to see the visualization you need to install graphviz
# pip3 install graphviz if this doesnt work please check the install_graphviz.jpg in the drive
month.visualize()
```


Out[5]:



In [6]:

```
month.fare_amount.sum().visualize()
```

Out[6]:



Features in the dataset:

Field Name	Description
VendorID	1. A code indicating the TPEP provider that provided the record. 2. Creative Mobile Technologies VeriFone Inc.
tpep_pickup_datetime	The date and time when the meter was engaged.
tpep_dropoff_datetime	The date and time when the meter was disengaged.
Passenger_count	The number of passengers in the vehicle. This is a driver-entered value.
Trip_distance	The elapsed trip distance in miles reported by the taximeter.
Pickup_longitude	Longitude where the meter was engaged.
Pickup_latitude	Latitude where the meter was engaged.
RateCodeID	1. The final rate code in effect at the end of the trip. 2. Standard rate 3. JFK 4. Newark 5. Nassau or Westchester 6. Negotiated fare Group ride
Store_and_fwd_flag	This flag indicates whether the trip record was held in vehicle memory before sending to the vendor, aka "store and forward," because the vehicle did not have a connection to the server. Y= store and forward trip N= not a store and forward trip
Dropoff_longitude	Longitude where the meter was disengaged.
Dropoff_latitude	Latitude where the meter was disengaged.
Payment_type	1. A numeric code signifying how the passenger paid for the trip. 2. Credit card 3. Cash 4. No charge 5. Dispute 6. Unknown Voided trip
Fare_amount	The time-and-distance fare calculated by the meter.
Extra	Miscellaneous extras and surcharges. Currently, this only includes. the 0.50 <i>and</i> 1 rush hour and overnight charges.
MTA_tax	0.50 MTA tax that is automatically triggered based on the metered rate in use.
Improvement_surcharge	0.30 improvement surcharge assessed trips at the flag drop. the improvement surcharge began being levied in 2015.
Tip_amount	Tip amount – This field is automatically populated for credit card tips. Cash tips are not included.
Tolls_amount	Total amount of all tolls paid in trip.
Total_amount	The total amount charged to passengers. Does not include cash tips.

ML Problem Formulation

Time-series forecasting and Regression

- To find number of pickups, given location coordinates(latitude and longitude) and time, in the query region and surrounding regions.

To solve the above we would be using data collected in Jan - Mar 2015 to predict the pickups in Jan - Mar 2016.

Performance metrics

1. Mean Absolute percentage error.
2. Mean Squared error.

Data Cleaning

In this section we will be doing univariate analysis and removing outlier/illegitimate values which may be caused due to some error

In [7]:

```
#table below shows few datapoints along with all our features
month.head(5)
```

Out[7]:

	VendorID	tpep_pickup_datetime	tpep_dropoff_datetime	passenger_count	trip_distance	pi
0	2	2015-01-15 19:05:39	2015-01-15 19:23:42	1	1.59	
1	1	2015-01-10 20:33:38	2015-01-10 20:53:28	1	3.30	
2	1	2015-01-10 20:33:38	2015-01-10 20:43:41	1	1.80	
3	1	2015-01-10 20:33:39	2015-01-10 20:35:31	1	0.50	
4	1	2015-01-10 20:33:39	2015-01-10 20:52:58	1	3.00	

1. Pickup Latitude and Pickup Longitude

It is inferred from the source <https://www.flickr.com/places/info/2459115> (<https://www.flickr.com/places/info/2459115>) that New York is bounded by the location coordinates(lat,long) - (40.5774, -74.15) & (40.9176,-73.7004) so hence any coordinates not within these coordinates are not considered by us as we are only concerned with pickups which originate within New York.

In [8]:

```

# Plotting pickup coordinates which are outside the bounding box of New-York
# we will collect all the points outside the bounding box of newyork city to outlier_lo
cations
outlier_locations = month[((month.pickup_longitude <= -74.15) | (month.pickup_latitude
<= 40.5774)) | \
                        (month.pickup_longitude >= -73.7004) | (month.pickup_latitude >= 40.
9176)]]

# creating a map with the a base location
# read more about the folium here: http://folium.readthedocs.io/en/latest/quickstart.ht
ml


# note: you dont need to remember any of these, you dont need indepth knowledge on the
se maps and plots

map_osm = folium.Map(location=[40.734695, -73.990372], tiles='Stamen Toner')

# we will spot only first 100 outliers on the map, plotting all the outliers will take
more time
sample_locations = outlier_locations.head(10000)
for i,j in sample_locations.iterrows():
    if int(j['pickup_latitude']) != 0:
        folium.Marker(list((j['pickup_latitude'],j['pickup_longitude'])).add_to(map_os
m)
map_osm

```

Out[8]:

Leaflet (<http://leafletjs.com>)

Observation:- As you can see above that there are some points just outside the boundary but there are a few that are in either South america, Mexico or Canada

2. Dropoff Latitude & Dropoff Longitude

It is inferred from the source <https://www.flickr.com/places/info/2459115> (<https://www.flickr.com/places/info/2459115>) that New York is bounded by the location coordinates(lat,long) - (40.5774, -74.15) & (40.9176,-73.7004) so hence any coordinates not within these coordinates are not considered by us as we are only concerned with dropoffs which are within New York.

In [9]:

```
# Plotting dropoff coordinates which are outside the bounding box of New-York
# we will collect all the points outside the bounding box of newyork city to outlier_locations
outlier_locations = month[((month.dropoff_longitude <= -74.15) | (month.dropoff_latitude <= 40.5774)) | \
                           (month.dropoff_longitude >= -73.7004) | (month.dropoff_latitude >= 40.9176)]]

# creating a map with the a base location
# read more about the folium here: http://folium.readthedocs.io/en/latest/quickstart.html

# note: you dont need to remember any of these, you dont need indepth knowledge on the se maps and plots

map_osm = folium.Map(location=[40.734695, -73.990372], tiles='Stamen Toner')

# we will spot only first 100 outliers on the map, plotting all the outliers will take more time
sample_locations = outlier_locations.head(10000)
for i,j in sample_locations.iterrows():
    if int(j['pickup_latitude']) != 0:
        folium.Marker(list((j['dropoff_latitude'],j['dropoff_longitude'])).add_to(map_osm)
map_osm
```

Out[9]:



Leaflet (<http://leafletjs.com>)

Observation:- The observations here are similar to those obtained while analysing pickup latitude and longitude

3. Trip Durations:

According to NYC Taxi & Limousine Commission Regulations **the maximum allowed trip duration in a 24 hour interval is 12 hours.**

In [0]:

```

#The timestamps are converted to unix so as to get duration(trip-time) & speed also pickup-times in unix are used while binning

# in out data we have time in the formate "YYYY-MM-DD HH:MM:SS" we convert this string to python time formate and then into unix time stamp
# https://stackoverflow.com/a/27914405
def convert_to_unix(s):
    return time.mktime(datetime.datetime.strptime(s, "%Y-%m-%d %H:%M:%S").timetuple())

# we return a data frame which contains the columns
# 1.'passenger_count' : self explanatory
# 2.'trip_distance' : self explanatory
# 3.'pickup_longitude' : self explanatory
# 4.'pickup_latitude' : self explanatory
# 5.'dropoff_longitude' : self explanatory
# 6.'dropoff_latitude' : self explanatory
# 7.'total_amount' : total fair that was paid
# 8.'trip_times' : duration of each trip
# 9.'pickup_times' : pickup time converted into unix time
# 10.'Speed' : velocity of each trip
def return_with_trip_times(month):
    duration = month[['tpep_pickup_datetime', 'tpep_dropoff_datetime']].compute()
    #pickups and dropoffs to unix time
    duration_pickup = [convert_to_unix(x) for x in duration['tpep_pickup_datetime'].values]
    duration_drop = [convert_to_unix(x) for x in duration['tpep_dropoff_datetime'].values]
    #calculate duration of trips
    durations = (np.array(duration_drop) - np.array(duration_pickup))/float(60)

    #append durations of trips and speed in miles/hr to a new dataframe
    new_frame = month[['passenger_count', 'trip_distance', 'pickup_longitude', 'pickup_latitude', 'dropoff_longitude', 'dropoff_latitude', 'total_amount']].compute()

    new_frame['trip_times'] = durations
    new_frame['pickup_times'] = duration_pickup
    new_frame['Speed'] = 60*(new_frame['trip_distance']/new_frame['trip_times'])

    return new_frame

# print(frame_with_durations.head())
# passenger_count      trip_distance  pickup_longitude  pickup_latitude  dropoff
# _Longitude      dropoff_latitude  total_amount  trip_times  pickup_times
# Speed
# 1              1.59      -73.993896      40.750111      -73.974
785      40.750618      17.05      18.050000      1.421329e+09
5.285319
# 1              3.30      -74.001648      40.724243      -73.994
415      40.759109      17.80      19.833333      1.420902e+09
9.983193
# 1              1.80      -73.963341      40.802788      -73.951
820      40.824413      10.80      10.050000      1.420902e+09
10.746269
# 1              0.50      -74.009087      40.713818      -74.004
326      40.719986      4.80      1.866667      1.420902e+09
16.071429
# 1              3.00      -73.971176      40.762428      -74.004

```

```
181          40.742653          16.30          19.316667          1.420902e+09
9.318378
frame_with_durations = return_with_trip_times(month)
```

In [11]:

```
# the skewed box plot shows us the presence of outliers
sns.boxplot(y="trip_times", data =frame_with_durations)
plt.show()
```

In [12]:

```
#calculating 0-100th percentile to find a the correct percentile value for removal of o
utliers
for i in range(0,100,10):
    var =frame_with_durations["trip_times"].values
    var = np.sort(var,axis = None)
    print("{} percentile value is {}".format(i,var[int(len(var)*(float(i)/100))]))
print ("100 percentile value is ",var[-1])
```

```
0 percentile value is -1211.0166666666667
10 percentile value is 3.8333333333333335
20 percentile value is 5.383333333333334
30 percentile value is 6.816666666666666
40 percentile value is 8.3
50 percentile value is 9.95
60 percentile value is 11.866666666666667
70 percentile value is 14.283333333333333
80 percentile value is 17.633333333333333
90 percentile value is 23.45
100 percentile value is 548555.6333333333
```

In [13]:

```
#Looking further from the 99th percenctile
for i in range(90,100):
    var =frame_with_durations["trip_times"].values
    var = np.sort(var,axis = None)
    print("{} percentile value is {}".format(i,var[int(len(var)*(float(i)/100))]))
print ("100 percentile value is ",var[-1])
```

```
90 percentile value is 23.45
91 percentile value is 24.35
92 percentile value is 25.383333333333333
93 percentile value is 26.55
94 percentile value is 27.933333333333334
95 percentile value is 29.583333333333332
96 percentile value is 31.683333333333334
97 percentile value is 34.466666666666667
98 percentile value is 38.716666666666667
99 percentile value is 46.75
100 percentile value is 548555.6333333333
```

In [0]:

```
#removing data based on our analysis and TLC regulations
frame_with_durations_modified=frame_with_durations[(frame_with_durations.trip_times>1)
& (frame_with_durations.trip_times<720)]
```

In [0]:

```
#box-plot after removal of outliers
sns.boxplot(y="trip_times", data =frame_with_durations_modified)
plt.show()
```

In [16]:

```
#pdf of trip-times after removing the outliers
sns.FacetGrid(frame_with_durations_modified,size=6) \
    .map(sns.kdeplot,"trip_times") \
    .add_legend();
plt.show();
```

In [0]:

```
#converting the values to log-values to chec for log-normal
import math
frame_with_durations_modified['log_times']=[math.log(i) for i in frame_with_durations_m
odified['trip_times'].values]
```

In [18]:

```
#pdf of log-values
sns.FacetGrid(frame_with_durations_modified,size=6) \
    .map(sns.kdeplot,"log_times") \
    .add_legend();
plt.show();
```

In [0]:

```
import scipy
#Q-Q plot for checking if trip-times is log-normal
scipy.stats.probplot(frame_with_durations_modified['log_times'].values, plot=plt)
plt.show()
```

4. Speed

In [0]:

```
# check for any outliers in the data after trip duration outliers removed
# box-plot for speeds with outliers
frame_with_durations_modified['Speed'] = 60*(frame_with_durations_modified['trip_distan
ce']/frame_with_durations_modified['trip_times'])
sns.boxplot(y="Speed", data =frame_with_durations_modified)
plt.show()
```

In [21]:

```
#calculating speed values at each percentile 0,10,20,30,40,50,60,70,80,90,100
for i in range(0,100,10):
    var =frame_with_durations_modified["Speed"].values
    var = np.sort(var,axis = None)
    print("{} percentile value is {}".format(i,var[int(len(var)*(float(i)/100))]))
print("100 percentile value is ",var[-1])
```

```
0 percentile value is 0.0
10 percentile value is 6.409495548961425
20 percentile value is 7.80952380952381
30 percentile value is 8.929133858267717
40 percentile value is 9.98019801980198
50 percentile value is 11.06865671641791
60 percentile value is 12.286689419795222
70 percentile value is 13.796407185628745
80 percentile value is 15.963224893917962
90 percentile value is 20.186915887850468
100 percentile value is 192857142.85714284
```

In [22]:

```
#calculating speed values at each percentile 90,91,92,93,94,95,96,97,98,99,100
for i in range(90,100):
    var =frame_with_durations_modified["Speed"].values
    var = np.sort(var,axis = None)
    print("{} percentile value is {}".format(i,var[int(len(var)*(float(i)/100))]))
print("100 percentile value is ",var[-1])
```

```
90 percentile value is 20.186915887850468
91 percentile value is 20.91645569620253
92 percentile value is 21.752988047808763
93 percentile value is 22.721893491124263
94 percentile value is 23.844155844155843
95 percentile value is 25.182552504038775
96 percentile value is 26.80851063829787
97 percentile value is 28.84304932735426
98 percentile value is 31.591128254580514
99 percentile value is 35.7513566847558
100 percentile value is 192857142.85714284
```

In [23]:

```
#calculating speed values at each percentile 99.0,99.1,99.2,99.3,99.4,99.5,99.6,99.7,99.8,99.9,100
for i in np.arange(0.0, 1.0, 0.1):
    var =frame_with_durations_modified["Speed"].values
    var = np.sort(var,axis = None)
    print("{} percentile value is {}".format(99+i,var[int(len(var)*(float(99+i)/100
    ))]))
print("100 percentile value is ",var[-1])
```

```
99.0 percentile value is 35.7513566847558
99.1 percentile value is 36.31084727468969
99.2 percentile value is 36.91470054446461
99.3 percentile value is 37.588235294117645
99.4 percentile value is 38.33035714285714
99.5 percentile value is 39.17580340264651
99.6 percentile value is 40.15384615384615
99.7 percentile value is 41.338301043219076
99.8 percentile value is 42.86631016042781
99.9 percentile value is 45.3107822410148
100 percentile value is 192857142.85714284
```

In [0]:

```
#removing further outliers based on the 99.9th percentile value
frame_with_durations_modified=frame_with_durations[(frame_with_durations.Speed>0) & (frame_with_durations.Speed<45.31)]
```

In [25]:

```
#avg.speed of cabs in New-York
sum(frame_with_durations_modified["Speed"]) / float(len(frame_with_durations_modified["Speed"]))
```

Out[25]:

```
12.450173996027528
```

The avg speed in Newyork speed is 12.45miles/hr, so a cab driver can travel **2 miles per 10min on avg.**

4. Trip Distance

In [0]:

```
# up to now we have removed the outliers based on trip durations and cab speeds
# Lets try if there are any outliers in trip distances
# box-plot showing outliers in trip-distance values
sns.boxplot(y="trip_distance", data =frame_with_durations_modified)
plt.show()
```

In [27]:

```
#calculating trip distance values at each percentile 0,10,20,30,40,50,60,70,80,90,100
for i in range(0,100,10):
    var =frame_with_durations_modified["trip_distance"].values
    var = np.sort(var,axis = None)
    print("{} percentile value is {}".format(i,var[int(len(var)*(float(i)/100))]))
print("100 percentile value is ",var[-1])
```

```
0 percentile value is 0.01
10 percentile value is 0.66
20 percentile value is 0.9
30 percentile value is 1.1
40 percentile value is 1.39
50 percentile value is 1.69
60 percentile value is 2.07
70 percentile value is 2.6
80 percentile value is 3.6
90 percentile value is 5.97
100 percentile value is 258.9
```

In [28]:

```
#calculating trip distance values at each percentile 90,91,92,93,94,95,96,97,98,99,100
for i in range(90,100):
    var =frame_with_durations_modified["trip_distance"].values
    var = np.sort(var,axis = None)
    print("{} percentile value is {}".format(i,var[int(len(var)*(float(i)/100))]))
print("100 percentile value is ",var[-1])
```

```
90 percentile value is 5.97
91 percentile value is 6.45
92 percentile value is 7.07
93 percentile value is 7.85
94 percentile value is 8.72
95 percentile value is 9.6
96 percentile value is 10.6
97 percentile value is 12.1
98 percentile value is 16.03
99 percentile value is 18.17
100 percentile value is 258.9
```


In [29]:

```
#calculating trip distance values at each percentile 99.0,99.1,99.2,99.3,99.4,99.5,99.6,99.7,99.8,99.9,100
for i in np.arange(0.0, 1.0, 0.1):
    var =frame_with_durations_modified["trip_distance"].values
    var = np.sort(var,axis = None)
    print("{} percentile value is {}".format(99+i,var[int(len(var)*(float(99+i)/100))]))
print("100 percentile value is ",var[-1])
```

```
99.0 percentile value is 18.17
99.1 percentile value is 18.37
99.2 percentile value is 18.6
99.3 percentile value is 18.83
99.4 percentile value is 19.13
99.5 percentile value is 19.5
99.6 percentile value is 19.96
99.7 percentile value is 20.5
99.8 percentile value is 21.22
99.9 percentile value is 22.57
100 percentile value is 258.9
```

In [0]:

```
#removing further outliers based on the 99.9th percentile value
frame_with_durations_modified=frame_with_durations[(frame_with_durations.trip_distance>
0) & (frame_with_durations.trip_distance<23)]
```

In [0]:

```
#box-plot after removal of outliers
sns.boxplot(y="trip_distance", data = frame_with_durations_modified)
plt.show()
```

5. Total Fare

In [0]:

```
# up to now we have removed the outliers based on trip durations, cab speeds, and trip distances
# Lets try if there are any outliers in based on the total_amount
# box-plot showing outliers in fare
sns.boxplot(y="total_amount", data =frame_with_durations_modified)
plt.show()
```

In [33]:

```
#calculating total fare amount values at each percntile 0,10,20,30,40,50,60,70,80,90,100
0
for i in range(0,100,10):
    var = frame_with_durations_modified["total_amount"].values
    var = np.sort(var,axis = None)
    print("{} percentile value is {}".format(i,var[int(len(var)*(float(i)/100))]))
print("100 percentile value is ",var[-1])
```

```
0 percentile value is -242.55
10 percentile value is 6.3
20 percentile value is 7.8
30 percentile value is 8.8
40 percentile value is 9.8
50 percentile value is 11.16
60 percentile value is 12.8
70 percentile value is 14.8
80 percentile value is 18.3
90 percentile value is 25.8
100 percentile value is 3950611.6
```

In [34]:

```
#calculating total fare amount values at each percntile 90,91,92,93,94,95,96,97,98,99,100
for i in range(90,100):
    var = frame_with_durations_modified["total_amount"].values
    var = np.sort(var,axis = None)
    print("{} percentile value is {}".format(i,var[int(len(var)*(float(i)/100))]))
print("100 percentile value is ",var[-1])
```

```
90 percentile value is 25.8
91 percentile value is 27.3
92 percentile value is 29.3
93 percentile value is 31.8
94 percentile value is 34.8
95 percentile value is 38.53
96 percentile value is 42.6
97 percentile value is 48.13
98 percentile value is 58.13
99 percentile value is 66.13
100 percentile value is 3950611.6
```

In [35]:

```
#calculating total fare amount values at each percentile 99.0,99.1,99.2,99.3,99.4,99.5,99.6,99.7,99.8,99.9,100
for i in np.arange(0.0, 1.0, 0.1):
    var = frame_with_durations_modified["total_amount"].values
    var = np.sort(var,axis = None)
    print("{} percentile value is {}".format(99+i,var[int(len(var)*(float(99+i)/100))]))
print("100 percentile value is ",var[-1])
```

```
99.0 percentile value is 66.13
99.1 percentile value is 68.13
99.2 percentile value is 69.6
99.3 percentile value is 69.6
99.4 percentile value is 69.73
99.5 percentile value is 69.75
99.6 percentile value is 69.76
99.7 percentile value is 72.58
99.8 percentile value is 75.35
99.9 percentile value is 88.28
100 percentile value is 3950611.6
```

Observation:- As even the 99.9th percentile value doesn't look like an outlier, as there is not much difference between the 99.8th percentile and 99.9th percentile, we move on to do graphical analysis

In [0]:

```
#below plot shows us the fare values(sorted) to find a sharp increase to remove those values as outliers
# plot the fare amount excluding last two values in sorted data
plt.plot(var[:-2])
plt.show()
```

In [0]:

```
# a very sharp increase in fare values can be seen
# plotting last three total fare values, and we can observe there is sharp increase in the values
plt.plot(var[-3:])
plt.show()
```

In [0]:

```
#now looking at values not including the last two points we again find a drastic increase at around 1000 fare value
# we plot last 50 values excluding last two values
plt.plot(var[-50:-2])
plt.show()
```

Remove all outliers/erroneous points.

In [0]:

```
#removing all outliers based on our univariate analysis above
def remove_outliers(new_frame):

    a = new_frame.shape[0]
    print ("Number of pickup records = ",a)
    temp_frame = new_frame[((new_frame.dropoff_longitude >= -74.15) & (new_frame.dropoff_longitude <= -73.7004) & \
                             (new_frame.dropoff_latitude >= 40.5774) & (new_frame.dropoff_latitude <= 40.9176)) & \
                             ((new_frame.pickup_longitude >= -74.15) & (new_frame.pickup_latitude >= 40.5774) & \
                             (new_frame.pickup_longitude <= -73.7004) & (new_frame.pickup_latitude <= 40.9176))]
    b = temp_frame.shape[0]
    print ("Number of outlier coordinates lying outside NY boundaries:",(a-b))

    temp_frame = new_frame[(new_frame.trip_times > 0) & (new_frame.trip_times < 720)]
    c = temp_frame.shape[0]
    print ("Number of outliers from trip times analysis:",(a-c))

    temp_frame = new_frame[(new_frame.trip_distance > 0) & (new_frame.trip_distance < 23)]
    d = temp_frame.shape[0]
    print ("Number of outliers from trip distance analysis:",(a-d))

    temp_frame = new_frame[(new_frame.Speed <= 65) & (new_frame.Speed >= 0)]
    e = temp_frame.shape[0]
    print ("Number of outliers from speed analysis:",(a-e))

    temp_frame = new_frame[(new_frame.total_amount <1000) & (new_frame.total_amount >0)]
    f = temp_frame.shape[0]
    print ("Number of outliers from fare analysis:",(a-f))

    new_frame = new_frame[((new_frame.dropoff_longitude >= -74.15) & (new_frame.dropoff_longitude <= -73.7004) & \
                             (new_frame.dropoff_latitude >= 40.5774) & (new_frame.dropoff_latitude <= 40.9176)) & \
                             ((new_frame.pickup_longitude >= -74.15) & (new_frame.pickup_latitude >= 40.5774) & \
                             (new_frame.pickup_longitude <= -73.7004) & (new_frame.pickup_latitude <= 40.9176))]

    new_frame = new_frame[(new_frame.trip_times > 0) & (new_frame.trip_times < 720)]
    new_frame = new_frame[(new_frame.trip_distance > 0) & (new_frame.trip_distance < 23)]
    new_frame = new_frame[(new_frame.Speed < 45.31) & (new_frame.Speed > 0)]
    new_frame = new_frame[(new_frame.total_amount <1000) & (new_frame.total_amount >0)]

    print ("Total outliers removed",a - new_frame.shape[0])
    print ("---")
    return new_frame
```

In [40]:

```
print ("Removing outliers in the month of Jan-2015")
print ("----")
frame_with_durations_outliers_removed = remove_outliers(frame_with_durations)
print("fraction of data points that remain after removing outliers", float(len(frame_with_durations_outliers_removed))/len(frame_with_durations))
```

Removing outliers in the month of Jan-2015

Number of pickup records = 12748986

Number of outlier coordinates lying outside NY boundaries: 293919

Number of outliers from trip times analysis: 23889

Number of outliers from trip distance analysis: 92597

Number of outliers from speed analysis: 24473

Number of outliers from fare analysis: 5275

Total outliers removed 377910

fraction of data points that remain after removing outliers 0.9703576425607495

Data-preperation

Clustering/Segmentation

In [41]:

```
#trying different cluster sizes to choose the right K in K-means
coords = frame_with_durations_outliers_removed[['pickup_latitude', 'pickup_longitude']]
.values
neighbours=[]

def find_min_distance(cluster_centers, cluster_len):
    nice_points = 0
    wrong_points = 0
    less2 = []
    more2 = []
    min_dist=1000
    for i in range(0, cluster_len):
        nice_points = 0
        wrong_points = 0
        for j in range(0, cluster_len):
            if j!=i:
                distance = gpxpy.geo.haversine_distance(cluster_centers[i][0], cluster_
centers[i][1],cluster_centers[j][0], cluster_centers[j][1])
                min_dist = min(min_dist,distance/(1.60934*1000))
                if (distance/(1.60934*1000)) <= 2:
                    nice_points +=1
                else:
                    wrong_points += 1
            less2.append(nice_points)
            more2.append(wrong_points)
        neighbours.append(less2)
    print ("On choosing a cluster size of ",cluster_len,"\nAvg. Number of Clusters with
in the vicinity (i.e. intercluster-distance < 2):", np.ceil(sum(less2)/len(less2)), "\n
Avg. Number of Clusters outside the vicinity (i.e. intercluster-distance > 2):", np.cei
l(sum(more2)/len(more2)), "\nMin inter-cluster distance = ",min_dist,"\n---")

def find_clusters(increment):
    kmeans = MiniBatchKMeans(n_clusters=increment, batch_size=10000,random_state=42).fi
t(coords)
    frame_with_durations_outliers_removed['pickup_cluster'] = kmeans.predict(frame_with
_durations_outliers_removed[['pickup_latitude', 'pickup_longitude']])
    cluster_centers = kmeans.cluster_centers_
    cluster_len = len(cluster_centers)
    return cluster_centers, cluster_len

# we need to choose number of clusters so that, there are more number of cluster region
s
#that are close to any cluster center
# and make sure that the minimum inter cluster should not be very less
for increment in range(10, 100, 10):
    cluster_centers, cluster_len = find_clusters(increment)
    find_min_distance(cluster_centers, cluster_len)
```

On choosing a cluster size of 10
Avg. Number of Clusters within the vicinity (i.e. intercluster-distance < 2): 2.0
Avg. Number of Clusters outside the vicinity (i.e. intercluster-distance > 2): 8.0
Min inter-cluster distance = 1.0945442325142543

On choosing a cluster size of 20
Avg. Number of Clusters within the vicinity (i.e. intercluster-distance < 2): 4.0
Avg. Number of Clusters outside the vicinity (i.e. intercluster-distance > 2): 16.0
Min inter-cluster distance = 0.7131298007387813

On choosing a cluster size of 30
Avg. Number of Clusters within the vicinity (i.e. intercluster-distance < 2): 8.0
Avg. Number of Clusters outside the vicinity (i.e. intercluster-distance > 2): 22.0
Min inter-cluster distance = 0.5185088176172206

On choosing a cluster size of 40
Avg. Number of Clusters within the vicinity (i.e. intercluster-distance < 2): 8.0
Avg. Number of Clusters outside the vicinity (i.e. intercluster-distance > 2): 32.0
Min inter-cluster distance = 0.5069768450363973

On choosing a cluster size of 50
Avg. Number of Clusters within the vicinity (i.e. intercluster-distance < 2): 12.0
Avg. Number of Clusters outside the vicinity (i.e. intercluster-distance > 2): 38.0
Min inter-cluster distance = 0.365363025983595

On choosing a cluster size of 60
Avg. Number of Clusters within the vicinity (i.e. intercluster-distance < 2): 14.0
Avg. Number of Clusters outside the vicinity (i.e. intercluster-distance > 2): 46.0
Min inter-cluster distance = 0.34704283494187155

On choosing a cluster size of 70
Avg. Number of Clusters within the vicinity (i.e. intercluster-distance < 2): 16.0
Avg. Number of Clusters outside the vicinity (i.e. intercluster-distance > 2): 54.0
Min inter-cluster distance = 0.30502203163244707

On choosing a cluster size of 80
Avg. Number of Clusters within the vicinity (i.e. intercluster-distance < 2): 18.0
Avg. Number of Clusters outside the vicinity (i.e. intercluster-distance > 2): 62.0
Min inter-cluster distance = 0.29220324531738534

On choosing a cluster size of 90
Avg. Number of Clusters within the vicinity (i.e. intercluster-distance < 2): 21.0
Avg. Number of Clusters outside the vicinity (i.e. intercluster-distance > 2): 69.0

Min inter-cluster distance = 0.18257992857034985

Inference:

- The main objective was to find a optimal min. distance(Which roughly estimates to the radius of a cluster) between the clusters which we got was 40

In [0]:

```
# if check for the 50 clusters you can observe that there are two clusters with only 0.3 miles apart from each other
# so we choose 40 clusters for solve the further problem

# Getting 40 clusters using the kmeans
kmeans = MiniBatchKMeans(n_clusters=40, batch_size=10000, random_state=0).fit(coords)
frame_with_durations_outliers_removed['pickup_cluster'] = kmeans.predict(frame_with_durations_outliers_removed[['pickup_latitude', 'pickup_longitude']])
```

Plotting the cluster centers:

In [43]:

```
# Plotting the cluster centers on OSM
cluster_centers = kmeans.cluster_centers_
cluster_len = len(cluster_centers)
map_osm = folium.Map(location=[40.734695, -73.990372], tiles='Stamen Toner')
for i in range(cluster_len):
    folium.Marker(list((cluster_centers[i][0], cluster_centers[i][1])), popup=(str(cluster_centers[i][0]) + str(cluster_centers[i][1]))).add_to(map_osm)
map_osm
```

Out[43]:



Plotting the clusters:

In [44]:

```
#Visualising the clusters on a map
def plot_clusters(frame):
    city_long_border = (-74.03, -73.75)
    city_lat_border = (40.63, 40.85)
    fig, ax = plt.subplots(ncols=1, nrows=1)
    ax.scatter(frame.pickup_longitude.values[:100000], frame.pickup_latitude.values[:100000], s=10, lw=0,
               c=frame.pickup_cluster.values[:100000], cmap='tab20', alpha=0.2)
    ax.set_xlim(city_long_border)
    ax.set_ylim(city_lat_border)
    ax.set_xlabel('Longitude')
    ax.set_ylabel('Latitude')
    plt.show()

plot_clusters(frame_with_durations_outliers_removed)
```

Time-binning

In [0]:

```
#Refer:https://www.unixtimestamp.com/
# 1420070400 : 2015-01-01 00:00:00
# 1422748800 : 2015-02-01 00:00:00
# 1425168000 : 2015-03-01 00:00:00
# 1427846400 : 2015-04-01 00:00:00
# 1430438400 : 2015-05-01 00:00:00
# 1433116800 : 2015-06-01 00:00:00

# 1451606400 : 2016-01-01 00:00:00
# 1454284800 : 2016-02-01 00:00:00
# 1456790400 : 2016-03-01 00:00:00
# 1459468800 : 2016-04-01 00:00:00
# 1462060800 : 2016-05-01 00:00:00
# 1464739200 : 2016-06-01 00:00:00

def add_pickup_bins(frame,month,year):
    unix_pickup_times=[i for i in frame['pickup_times'].values]
    unix_times = [[1420070400,1422748800,1425168000,1427846400,1430438400,1433116800],\
                   [1451606400,1454284800,1456790400,1459468800,1462060800,1464739200]
    ]

    start_pickup_unix=unix_times[year-2015][month-1]
    # https://www.timeanddate.com/time/zones/est
    # (int((i-start_pickup_unix)/600)+33) : our unix time is in gmt to we are converting it to est
    tenminutewise_binned_unix_pickup_times=[(int((i-start_pickup_unix)/600)+33) for i in unix_pickup_times]
    frame['pickup_bins'] = np.array(tenminutewise_binned_unix_pickup_times)
    return frame
```

In [0]:

```
# clustering, making pickup bins and grouping by pickup cluster and pickup bins
frame_with_durations_outliers_removed['pickup_cluster'] = kmeans.predict(frame_with_durations_outliers_removed[['pickup_latitude', 'pickup_longitude']])
jan_2015_frame = add_pickup_bins(frame_with_durations_outliers_removed,1,2015)
jan_2015_groupby = jan_2015_frame[['pickup_cluster','pickup_bins','trip_distance']].groupby(['pickup_cluster','pickup_bins']).count()
```

In [47]:

```
# we add two more columns 'pickup_cluster'(to which cluster it belongs to)
# and 'pickup_bins' (to which 10min intravel the trip belongs to)
jan_2015_frame.head()
```

Out[47]:

	passenger_count	trip_distance	pickup_longitude	pickup_latitude	dropoff_longitude	dropoff_latitude
0	1	1.59	-73.993896	40.750111	-73.974785	40.750111
1	1	3.30	-74.001648	40.724243	-73.994415	40.724243
2	1	1.80	-73.963341	40.802788	-73.951820	40.802788
3	1	0.50	-74.009087	40.713818	-74.004326	40.713818
4	1	3.00	-73.971176	40.762428	-74.004181	40.762428

In [48]:

```
# here the trip_distance represents the number of pickups that are happen in that particular 10min intravel
# this data frame has two indices
# primary index: pickup_cluster (cluster number)
# secondary index : pickup_bins (we divid whole months time into 10min intravels 24*31*60/10 =4464bins)
jan_2015_groupby.head()
```

Out[48]:

		trip_distance
pickup_cluster	pickup_bins	
0	33	104
	34	200
	35	208
	36	141
	37	155

In [49]:

```
# upto now we cleaned data and prepared data for the month 2015,

# now do the same operations for months Jan, Feb, March of 2016
# 1. get the dataframe which includes only required columns
# 2. adding trip times, speed, unix time stamp of pickup_time
# 4. remove the outliers based on trip_times, speed, trip_duration, total_amount
# 5. add pickup_cluster to each data point
# 6. add pickup_bin (index of 10min intravel to which that trip belongs to)
# 7. group by data, based on 'pickup_cluster' and 'pickup_bin'

# Data Preparation for the months of Jan, Feb and March 2016
def datapreparation(month, kmeans, month_no, year_no):

    print ("Return with trip times..")

    frame_with_durations = return_with_trip_times(month)

    print ("Remove outliers..")
    frame_with_durations_outliers_removed = remove_outliers(frame_with_durations)

    print ("Estimating clusters..")
    frame_with_durations_outliers_removed['pickup_cluster'] = kmeans.predict(frame_with_durations_outliers_removed[['pickup_latitude', 'pickup_longitude']])
    #frame_with_durations_outliers_removed_2016['pickup_cluster'] = kmeans.predict(frame_with_durations_outliers_removed_2016[['pickup_latitude', 'pickup_longitude']])

    print ("Final groupbying..")
    final_updated_frame = add_pickup_bins(frame_with_durations_outliers_removed, month_no, year_no)
    final_groupby_frame = final_updated_frame[['pickup_cluster', 'pickup_bins', 'trip_distance']].groupby(['pickup_cluster', 'pickup_bins']).count()

    return final_updated_frame, final_groupby_frame

month_jan_2016 = dd.read_csv('yellow_tripdata_2016-01.csv')
month_feb_2016 = dd.read_csv('yellow_tripdata_2016-02.csv')
month_mar_2016 = dd.read_csv('yellow_tripdata_2016-03.csv')

jan_2016_frame, jan_2016_groupby = datapreparation(month_jan_2016, kmeans, 1, 2016)
feb_2016_frame, feb_2016_groupby = datapreparation(month_feb_2016, kmeans, 2, 2016)
mar_2016_frame, mar_2016_groupby = datapreparation(month_mar_2016, kmeans, 3, 2016)
```

```

Return with trip times..
Remove outliers..
Number of pickup records = 10906858
Number of outlier coordinates lying outside NY boundaries: 214677
Number of outliers from trip times analysis: 27190
Number of outliers from trip distance analysis: 79742
Number of outliers from speed analysis: 21047
Number of outliers from fare analysis: 4991
Total outliers removed 297784
---
Estimating clusters..
Final groupbying..
Return with trip times..
Remove outliers..
Number of pickup records = 11382049
Number of outlier coordinates lying outside NY boundaries: 223161
Number of outliers from trip times analysis: 27670
Number of outliers from trip distance analysis: 81902
Number of outliers from speed analysis: 22437
Number of outliers from fare analysis: 5476
Total outliers removed 308177
---
Estimating clusters..
Final groupbying..
Return with trip times..
Remove outliers..
Number of pickup records = 12210952
Number of outlier coordinates lying outside NY boundaries: 232444
Number of outliers from trip times analysis: 30868
Number of outliers from trip distance analysis: 87318
Number of outliers from speed analysis: 23889
Number of outliers from fare analysis: 5859
Total outliers removed 324635
---
Estimating clusters..
Final groupbying..

```

Smoothing

In [0]:

```

# Gets the unique bins where pickup values are present for each each reigion

# for each cluster region we will collect all the indices of 10min intravels in which t
he pickups are happened
# we got an observation that there are some pickpbins that doesnt have any pickups
def return_unq_pickup_bins(frame):
    values = []
    for i in range(0,40):
        new = frame[frame['pickup_cluster'] == i]
        list_unq = list(set(new['pickup_bins']))
        list_unq.sort()
        values.append(list_unq)
    return values

```

In [0]:

```
# for every month we get all indices of 10min intravels in which atleast one pickup got happened

#jan
jan_2015_unique = return_unq_pickup_bins(jan_2015_frame)
jan_2016_unique = return_unq_pickup_bins(jan_2016_frame)

#feb
feb_2016_unique = return_unq_pickup_bins(feb_2016_frame)

#march
mar_2016_unique = return_unq_pickup_bins(mar_2016_frame)
```

In [52]:

```
# for each cluster number of 10min intravels with 0 pickups
for i in range(40):
    print("for the ",i,"th cluster number of 10min intravels with zero pickups: ",4464 -
len(set(jan_2015_unique[i])))
    print('-'*60)
```

```
for the 0 th cluster number of 10min intavels with zero pickups: 40
-----
for the 1 th cluster number of 10min intavels with zero pickups: 1985
-----
for the 2 th cluster number of 10min intavels with zero pickups: 29
-----
for the 3 th cluster number of 10min intavels with zero pickups: 354
-----
for the 4 th cluster number of 10min intavels with zero pickups: 37
-----
for the 5 th cluster number of 10min intavels with zero pickups: 153
-----
for the 6 th cluster number of 10min intavels with zero pickups: 34
-----
for the 7 th cluster number of 10min intavels with zero pickups: 34
-----
for the 8 th cluster number of 10min intavels with zero pickups: 117
-----
for the 9 th cluster number of 10min intavels with zero pickups: 40
-----
for the 10 th cluster number of 10min intavels with zero pickups: 25
-----
for the 11 th cluster number of 10min intavels with zero pickups: 44
-----
for the 12 th cluster number of 10min intavels with zero pickups: 42
-----
for the 13 th cluster number of 10min intavels with zero pickups: 28
-----
for the 14 th cluster number of 10min intavels with zero pickups: 26
-----
for the 15 th cluster number of 10min intavels with zero pickups: 31
-----
for the 16 th cluster number of 10min intavels with zero pickups: 40
-----
for the 17 th cluster number of 10min intavels with zero pickups: 58
-----
for the 18 th cluster number of 10min intavels with zero pickups: 1190
-----
for the 19 th cluster number of 10min intavels with zero pickups: 1357
-----
for the 20 th cluster number of 10min intavels with zero pickups: 53
-----
for the 21 th cluster number of 10min intavels with zero pickups: 29
-----
for the 22 th cluster number of 10min intavels with zero pickups: 29
-----
for the 23 th cluster number of 10min intavels with zero pickups: 163
-----
for the 24 th cluster number of 10min intavels with zero pickups: 35
-----
for the 25 th cluster number of 10min intavels with zero pickups: 41
-----
for the 26 th cluster number of 10min intavels with zero pickups: 31
-----
for the 27 th cluster number of 10min intavels with zero pickups: 214
-----
for the 28 th cluster number of 10min intavels with zero pickups: 36
-----
for the 29 th cluster number of 10min intavels with zero pickups: 41
-----
for the 30 th cluster number of 10min intavels with zero pickups: 1180
```

```

-----
for the 31 th cluster number of 10min intervals with zero pickups: 42
-----
for the 32 th cluster number of 10min intervals with zero pickups: 44
-----
for the 33 th cluster number of 10min intervals with zero pickups: 43
-----
for the 34 th cluster number of 10min intervals with zero pickups: 39
-----
for the 35 th cluster number of 10min intervals with zero pickups: 42
-----
for the 36 th cluster number of 10min intervals with zero pickups: 36
-----
for the 37 th cluster number of 10min intervals with zero pickups: 321
-----
for the 38 th cluster number of 10min intervals with zero pickups: 36
-----
for the 39 th cluster number of 10min intervals with zero pickups: 43
-----

```

there are two ways to fill up these values

- Fill the missing value with 0's
- Fill the missing values with the avg values
 - Case 1:(values missing at the start)
 - Ex1: $_ _ _ x \Rightarrow \text{ceil}(x/4), \text{ceil}(x/4), \text{ceil}(x/4), \text{ceil}(x/4)$
 - Ex2: $_ _ x \Rightarrow \text{ceil}(x/3), \text{ceil}(x/3), \text{ceil}(x/3)$
 - Case 2:(values missing in middle)
 - Ex1: $x _ _ y \Rightarrow \text{ceil}((x+y)/4), \text{ceil}((x+y)/4), \text{ceil}((x+y)/4), \text{ceil}((x+y)/4)$
 - Ex2: $x _ _ _ y \Rightarrow \text{ceil}((x+y)/5), \text{ceil}((x+y)/5), \text{ceil}((x+y)/5), \text{ceil}((x+y)/5), \text{ceil}((x+y)/5)$
 - Case 3:(values missing at the end)
 - Ex1: $x _ _ _ \Rightarrow \text{ceil}(x/4), \text{ceil}(x/4), \text{ceil}(x/4), \text{ceil}(x/4)$
 - Ex2: $x _ \Rightarrow \text{ceil}(x/2), \text{ceil}(x/2)$

In [0]:

```
# Fills a value of zero for every bin where no pickup data is present
# the count_values: number pickps that are happened in each region for each 10min intravel
# there wont be any value if there are no pickups.
# values: number of unique bins

# for every 10min intravel(pickup_bin) we will check it is there in our unique bin,
# if it is there we will add the count_values[index] to smoothed data
# if not we add 0 to the smoothed data
# we finally return smoothed data
def fill_missing(count_values,values):
    smoothed_regions=[]
    ind=0
    for r in range(0,40):
        smoothed_bins=[]
        for i in range(4464):
            if i in values[r]:
                smoothed_bins.append(count_values[ind])
                ind+=1
            else:
                smoothed_bins.append(0)
        smoothed_regions.extend(smoothed_bins)
    return smoothed_regions
```

In [0]:

```
# Fills a value of zero for every bin where no pickup data is present
# the count_values: number pickups that are happened in each region for each 10min interval
# there wont be any value if there are no pickups.
# values: number of unique bins

# for every 10min interval(pickup_bin) we will check it is there in our unique bin,
# if it is there we will add the count_values[index] to smoothed data
# if not we add smoothed data (which is calculated based on the methods that are discussed in the above markdown cell)
# we finally return smoothed data
def smoothing(count_values,values):
    smoothed_regions=[] # stores list of final smoothed values of each region
    ind=0
    repeat=0
    smoothed_value=0
    for r in range(0,40):
        smoothed_bins=[] #stores the final smoothed values
        repeat=0
        for i in range(4464):
            if repeat!=0: # prevents iteration for a value which is already visited/resolved
                repeat-=1
                continue
            if i in values[r]: #checks if the pickup-bin exists
                smoothed_bins.append(count_values[ind]) # appends the value of the pickup bin if it exists
            else:
                if i!=0:
                    right_hand_limit=0
                    for j in range(i,4464):
                        if j not in values[r]: #searches for the left-limit or the pickup-bin value which has a pickup value
                            continue
                        else:
                            right_hand_limit=j
                            break
                    if right_hand_limit==0:
                        #Case 1: When we have the last/last few values are found to be missing,hence we have no right-limit here
                        smoothed_value=count_values[ind-1]*1.0/((4463-i)+2)*1.0
                        for j in range(i,4464):
                            smoothed_bins.append(math.ceil(smoothed_value))
                            smoothed_bins[i-1] = math.ceil(smoothed_value)
                            repeat=(4463-i)
                            ind-=1
                        else:
                            #Case 2: When we have the missing values between two known values
                            smoothed_value=(count_values[ind-1]+count_values[ind])*1.0/((right_hand_limit-i)+2)*1.0
                            for j in range(i,right_hand_limit+1):
                                smoothed_bins.append(math.ceil(smoothed_value))
                                smoothed_bins[i-1] = math.ceil(smoothed_value)
                                repeat=(right_hand_limit-i)
                            else:
                                #Case 3: When we have the first/first few values are found to be missing,hence we have no left-limit here
                                right_hand_limit=0
                                for j in range(i,4464):
```

```

        if j not in values[r]:
            continue
        else:
            right_hand_limit=j
            break
    smoothed_value=count_values[ind]*1.0/((right_hand_limit-i)+1)*1.0
    for j in range(i,right_hand_limit+1):
        smoothed_bins.append(math.ceil(smoothed_value))
    repeat=(right_hand_limit-i)

    ind+=1
    smoothed_regions.extend(smoothed_bins)
return smoothed_regions

```

In [0]:

```

#Filling Missing values of Jan-2015 with 0
# here in jan_2015_groupby dataframe the trip_distance represents the number of pickups
that are happened
jan_2015_fill = fill_missing(jan_2015_groupby['trip_distance'].values,jan_2015_unique)

#Smoothing Missing values of Jan-2015
jan_2015_smooth = smoothing(jan_2015_groupby['trip_distance'].values,jan_2015_unique)

```

In [56]:

```

# number of 10min indices for jan 2015= 24*31*60/10 = 4464
# number of 10min indices for jan 2016 = 24*31*60/10 = 4464
# number of 10min indices for feb 2016 = 24*29*60/10 = 4176
# number of 10min indices for march 2016 = 24*30*60/10 = 4320
# for each cluster we will have 4464 values, therefore 40*4464 = 178560 (length of the
jan_2015_fill)
print("number of 10min intravels among all the clusters ",len(jan_2015_fill))

```

number of 10min intravels among all the clusters 178560

In [57]:

```

# Smoothing vs Filling
# sample plot that shows two variations of filling missing values
# we have taken the number of pickups for cluster region 2
plt.figure(figsize=(10,5))
plt.plot(jan_2015_fill[4464:8920], label="zero filled values")
plt.plot(jan_2015_smooth[4464:8920], label="filled with avg values")
plt.legend()
plt.show()

```

In [0]:

```
# why we choose, these methods and which method is used for which data?

# Ans: consider we have data of some month in 2015 jan 1st, 10 _ _ _ 20, i.e there are
# 10 pickups that are happened in 1st
# 10st 10min intravel, 0 pickups happened in 2nd 10mins intravel, 0 pickups happened in
# 3rd 10min intravel
# and 20 pickups happened in 4th 10min intravel.
# in fill_missing method we replace these values like 10, 0, 0, 20
# where as in smoothing method we replace these values as 6,6,6,6,6, if you can check t
# he number of pickups
# that are happened in the first 40min are same in both cases, but if you can observe t
# hat we looking at the future values
# when you are using smoothing we are looking at the future number of pickups which mi
# ght cause a data leakage.

# so we use smoothing for jan 2015th data since it acts as our training data
# and we use simple fill_misssing method for 2016th data.
```

In [0]:

```
# Jan-2015 data is smoothed, Jan, Feb & March 2016 data missing values are filled with z
# ero
jan_2015_smooth = smoothing(jan_2015_groupby['trip_distance'].values, jan_2015_unique)
jan_2016_smooth = fill_missing(jan_2016_groupby['trip_distance'].values, jan_2016_unique
)
feb_2016_smooth = fill_missing(feb_2016_groupby['trip_distance'].values, feb_2016_unique
)
mar_2016_smooth = fill_missing(mar_2016_groupby['trip_distance'].values, mar_2016_unique
)

# Making list of all the values of pickup data in every bin for a period of 3 months an
# d storing them region-wise
regions_cum = []

# a =[1,2,3]
# b = [2,3,4]
# a+b = [1, 2, 3, 2, 3, 4]

# number of 10min indices for jan 2015= 24*31*60/10 = 4464
# number of 10min indices for jan 2016 = 24*31*60/10 = 4464
# number of 10min indices for feb 2016 = 24*29*60/10 = 4176
# number of 10min indices for march 2016 = 24*31*60/10 = 4464
# regions_cum: it will contain 40 lists, each list will contain 4464+4176+4464 values w
# hich represents the number of pickups
# that are happened for three months in 2016 data

for i in range(0,40):
    regions_cum.append(jan_2016_smooth[4464*i:4464*(i+1)]+feb_2016_smooth[4176*i:4176*(
i+1)]+mar_2016_smooth[4464*i:4464*(i+1)])

# print(len(regions_cum))
# 40
# print(len(regions_cum[0]))
# 13104
```

Time series and Fourier Transforms

In [60]:

```
def uniqueish_color():  
    """There're better ways to generate unique colors, but this isn't awful."""  
    return plt.cm.gist_ncar(np.random.random())  
first_x = list(range(0,4464))  
second_x = list(range(4464,8640))  
third_x = list(range(8640,13104))  
for i in range(40):  
    plt.figure(figsize=(10,4))  
    plt.plot(first_x,regions_cum[i][:4464], color=uniqueish_color(), label='2016 Jan month data')  
    plt.plot(second_x,regions_cum[i][4464:8640], color=uniqueish_color(), label='2016 Feb month data')  
    plt.plot(third_x,regions_cum[i][8640:], color=uniqueish_color(), label='2016 March month data')  
    plt.legend()  
    plt.show()
```


In [61]:

```
# getting peaks: https://blog.ytotech.com/2015/11/01/findpeaks-in-python/
# read more about fft function : https://docs.scipy.org/doc/numpy/reference/generated/numpy.fft.fft.html
Y = np.fft.fft(np.array(jan_2016_smooth)[0:4460])
# read more about the fftfreq: https://docs.scipy.org/doc/numpy/reference/generated/numpy.fft.fftfreq.html
freq = np.fft.fftfreq(4460, 1)
n = len(freq)
plt.figure()
plt.plot(freq[:int(n/2)], np.abs(Y)[:int(n/2)])
plt.xlabel("Frequency")
plt.ylabel("Amplitude")
plt.show()
```

In [0]:

```
#Preparing the Dataframe only with x(i) values as jan-2015 data and y(i) values as jan-2016
ratios_jan = pd.DataFrame()
ratios_jan['Given']=jan_2015_smooth
ratios_jan['Prediction']=jan_2016_smooth
ratios_jan['Ratios']=ratios_jan['Prediction']*1.0/ratios_jan['Given']*1.0
```

Modelling: Baseline Models

Now we get into modelling in order to forecast the pickup densities for the months of Jan, Feb and March of 2016 for which we are using multiple models with two variations

1. Using Ratios of the 2016 data to the 2015 data i.e $R_t = P_t^{2016} / P_t^{2015}$
2. Using Previous known values of the 2016 data itself to predict the future values

Simple Moving Averages

The First Model used is the Moving Averages Model which uses the previous n values in order to predict the next value

Using Ratio Values - $R_t = (R_{t-1} + R_{t-2} + R_{t-3} \dots R_{t-n})/n$

In [0]:

```

def MA_R_Predictions(ratios,month):
    predicted_ratio=(ratios['Ratios'].values)[0]
    error=[]
    predicted_values=[]
    window_size=3
    predicted_ratio_values=[]
    for i in range(0,4464*40):
        if i%4464==0:
            predicted_ratio_values.append(0)
            predicted_values.append(0)
            error.append(0)
            continue
        predicted_ratio_values.append(predicted_ratio)
        predicted_values.append(int(((ratios['Given'].values)[i])*predicted_ratio))
        error.append(abs((math.pow(int(((ratios['Given'].values)[i])*predicted_ratio)-(
ratios['Prediction'].values)[i],1))))
        if i+1>=window_size:
            predicted_ratio=sum((ratios['Ratios'].values)[(i+1)-window_size:(i+1)])/win
dow_size
        else:
            predicted_ratio=sum((ratios['Ratios'].values)[0:(i+1)])/(i+1)

    ratios['MA_R_Predicted'] = predicted_values
    ratios['MA_R_Error'] = error
    mape_err = (sum(error)/len(error))/(sum(ratios['Prediction'].values)/len(ratios['Pr
ediction'].values))
    mse_err = sum([e**2 for e in error])/len(error)
    return ratios,mape_err,mse_err

```

For the above the Hyperparameter is the window-size (n) which is tuned manually and it is found that the window-size of 3 is optimal for getting the best results using Moving Averages using previous Ratio values therefore we get $R_t = (R_{t-1} + R_{t-2} + R_{t-3})/3$

Next we use the Moving averages of the 2016 values itself to predict the future value using

$$P_t = (P_{t-1} + P_{t-2} + P_{t-3} \dots P_{t-n})/n$$

In [0]:

```

def MA_P_Predictions(ratios,month):
    predicted_value=(ratios['Prediction'].values)[0]
    error=[]
    predicted_values=[]
    window_size=1
    predicted_ratio_values=[]
    for i in range(0,4464*40):
        predicted_values.append(predicted_value)
        error.append(abs((math.pow(predicted_value-(ratios['Prediction'].values)[i],1
    )))
        if i+1>=window_size:
            predicted_value=int(sum((ratios['Prediction'].values)[(i+1)-window_size:(i+
1)]))/window_size)
        else:
            predicted_value=int(sum((ratios['Prediction'].values)[0:(i+1)])/(i+1))

    ratios['MA_P_Predicted'] = predicted_values
    ratios['MA_P_Error'] = error
    mape_err = (sum(error)/len(error))/(sum(ratios['Prediction'].values)/len(ratios['Pr
ediction'].values))
    mse_err = sum([e**2 for e in error])/len(error)
    return ratios,mape_err,mse_err

```

For the above the Hyperparameter is the window-size (n) which is tuned manually and it is found that the window-size of 1 is optimal for getting the best results using Moving Averages using previous 2016 values therefore we get $P_t = P_{t-1}$

Weighted Moving Averages

The Moving Avergaes Model used gave equal importance to all the values in the window used, but we know intuitively that the future is more likely to be similar to the latest values and less similar to the older values. Weighted Averages converts this analogy into a mathematical relationship giving the highest weight while computing the averages to the latest previous value and decreasing weights to the subsequent older ones

Weighted Moving Averages using Ratio Values -

$$R_t = (N * R_{t-1} + (N - 1) * R_{t-2} + (N - 2) * R_{t-3} \dots 1 * R_{t-n}) / (N * (N + 1) / 2)$$

In [0]:

```

def WA_R_Predictions(ratios,month):
    predicted_ratio=(ratios['Ratios'].values)[0]
    alpha=0.5
    error=[]
    predicted_values=[]
    window_size=5
    predicted_ratio_values=[]
    for i in range(0,4464*40):
        if i%4464==0:
            predicted_ratio_values.append(0)
            predicted_values.append(0)
            error.append(0)
            continue
        predicted_ratio_values.append(predicted_ratio)
        predicted_values.append(int(((ratios['Given'].values)[i])*predicted_ratio))
        error.append(abs((math.pow(int(((ratios['Given'].values)[i])*predicted_ratio)-
ratios['Prediction'].values)[i],1))))
        if i+1>=window_size:
            sum_values=0
            sum_of_coeff=0
            for j in range(window_size,0,-1):
                sum_values += j*(ratios['Ratios'].values)[i-window_size+j]
                sum_of_coeff+=j
            predicted_ratio=sum_values/sum_of_coeff
        else:
            sum_values=0
            sum_of_coeff=0
            for j in range(i+1,0,-1):
                sum_values += j*(ratios['Ratios'].values)[j-1]
                sum_of_coeff+=j
            predicted_ratio=sum_values/sum_of_coeff

    ratios['WA_R_Predicted'] = predicted_values
    ratios['WA_R_Error'] = error
    mape_err = (sum(error)/len(error))/(sum(ratios['Prediction'].values)/len(ratios['Pr
ediction'].values))
    mse_err = sum([e**2 for e in error])/len(error)
    return ratios,mape_err,mse_err

```

For the above the Hyperparameter is the window-size (n) which is tuned manually and it is found that the window-size of 5 is optimal for getting the best results using Weighted Moving Averages using previous Ratio values therefore we get $R_t = (5 * R_{t-1} + 4 * R_{t-2} + 3 * R_{t-3} + 2 * R_{t-4} + R_{t-5})/15$

Weighted Moving Averages using Previous 2016 Values -

$$P_t = (N * P_{t-1} + (N - 1) * P_{t-2} + (N - 2) * P_{t-3} \dots 1 * P_{t-n}) / (N * (N + 1) / 2)$$

In [0]:

```
def WA_P_Predictions(ratios,month):
    predicted_value=(ratios['Prediction'].values)[0]
    error=[]
    predicted_values=[]
    window_size=2
    for i in range(0,4464*40):
        predicted_values.append(predicted_value)
        error.append(abs((math.pow(predicted_value-(ratios['Prediction'].values)[i],1
    )))
        if i+1>=window_size:
            sum_values=0
            sum_of_coeff=0
            for j in range(window_size,0,-1):
                sum_values += j*(ratios['Prediction'].values)[i-window_size+j]
                sum_of_coeff+=j
            predicted_value=int(sum_values/sum_of_coeff)

        else:
            sum_values=0
            sum_of_coeff=0
            for j in range(i+1,0,-1):
                sum_values += j*(ratios['Prediction'].values)[j-1]
                sum_of_coeff+=j
            predicted_value=int(sum_values/sum_of_coeff)

    ratios['WA_P_Predicted'] = predicted_values
    ratios['WA_P_Error'] = error
    mape_err = (sum(error)/len(error))/(sum(ratios['Prediction'].values)/len(ratios['Prediction'].values))
    mse_err = sum([e**2 for e in error])/len(error)
    return ratios,mape_err,mse_err
```

For the above the Hyperparameter is the window-size (n) which is tuned manually and it is found that the window-size of 2 is optimal for getting the best results using Weighted Moving Averages using previous 2016 values therefore we get $P_t = (2 * P_{t-1} + P_{t-2})/3$

Exponential Weighted Moving Averages

https://en.wikipedia.org/wiki/Moving_average#Exponential_moving_average (https://en.wikipedia.org/wiki/Moving_average#Exponential_moving_average) Through weighted averaged we have satisfied the analogy of giving higher weights to the latest value and decreasing weights to the subsequent ones but we still do not know which is the correct weighting scheme as there are infinitely many possibilities in which we can assign weights in a non-increasing order and tune the the hyperparameter window-size. To simplify this process we use Exponential Moving Averages which is a more logical way towards assigning weights and at the same time also using an optimal window-size.

In exponential moving averages we use a single hyperparameter alpha (α) which is a value between 0 & 1 and based on the value of the hyperparameter alpha the weights and the window sizes are configured. For eg. If $\alpha = 0.9$ then the number of days on which the value of the current iteration is based is $\sim 1/(1 - \alpha) = 10$ i.e. we consider values 10 days prior before we predict the value for the current iteration. Also the weights are assigned using $2/(N + 1) = 0.18$, where N = number of prior values being considered, hence from this it is implied that the first or latest value is assigned a weight of 0.18 which keeps exponentially decreasing for the subsequent values.

$$R'_t = \alpha * R_{t-1} + (1 - \alpha) * R'_{t-1}$$

In [0]:

```
def EA_R1_Predictions(ratios,month):
    predicted_ratio=(ratios['Ratios'].values)[0]
    alpha=0.6
    error=[]
    predicted_values=[]
    predicted_ratio_values=[]
    for i in range(0,4464*40):
        if i%4464==0:
            predicted_ratio_values.append(0)
            predicted_values.append(0)
            error.append(0)
            continue
        predicted_ratio_values.append(predicted_ratio)
        predicted_values.append(int(((ratios['Given'].values)[i])*predicted_ratio))
        error.append(abs((math.pow(int(((ratios['Given'].values)[i])*predicted_ratio)-(
ratios['Prediction'].values)[i],1))))
        predicted_ratio = (alpha*predicted_ratio) + (1-alpha)*((ratios['Ratios'].values
)[i])

    ratios['EA_R1_Predicted'] = predicted_values
    ratios['EA_R1_Error'] = error
    mape_err = (sum(error)/len(error))/(sum(ratios['Prediction'].values)/len(ratios['Pr
ediction'].values))
    mse_err = sum([e**2 for e in error])/len(error)
    return ratios,mape_err,mse_err
```

$$P'_t = \alpha * P_{t-1} + (1 - \alpha) * P'_{t-1}$$

In [0]:

```
def EA_P1_Predictions(ratios,month):
    predicted_value= (ratios['Prediction'].values)[0]
    alpha=0.3
    error=[]
    predicted_values=[]
    for i in range(0,4464*40):
        if i%4464==0:
            predicted_values.append(0)
            error.append(0)
            continue
        predicted_values.append(predicted_value)
        error.append(abs((math.pow(predicted_value-(ratios['Prediction'].values)[i],1
))))
        predicted_value =int((alpha*predicted_value) + (1-alpha)*((ratios['Prediction']
.values)[i]))

    ratios['EA_P1_Predicted'] = predicted_values
    ratios['EA_P1_Error'] = error
    mape_err = (sum(error)/len(error))/(sum(ratios['Prediction'].values)/len(ratios['Pr
ediction'].values))
    mse_err = sum([e**2 for e in error])/len(error)
    return ratios,mape_err,mse_err
```

In [0]:

```
mean_err=[0]*10
median_err=[0]*10
ratios_jan,mean_err[0],median_err[0]=MA_R_Predictions(ratios_jan,'jan')
ratios_jan,mean_err[1],median_err[1]=MA_P_Predictions(ratios_jan,'jan')
ratios_jan,mean_err[2],median_err[2]=WA_R_Predictions(ratios_jan,'jan')
ratios_jan,mean_err[3],median_err[3]=WA_P_Predictions(ratios_jan,'jan')
ratios_jan,mean_err[4],median_err[4]=EA_R1_Predictions(ratios_jan,'jan')
ratios_jan,mean_err[5],median_err[5]=EA_P1_Predictions(ratios_jan,'jan')
```

Comparison between baseline models

We have chosen our error metric for comparison between models as **MAPE (Mean Absolute Percentage Error)** so that we can know that on an average how good is our model with predictions and **MSE (Mean Squared Error)** is also used so that we have a clearer understanding as to how well our forecasting model performs with outliers so that we make sure that there is not much of a error margin between our prediction and the actual value

In [70]:

```
print ("Error Metric Matrix (Forecasting Methods) - MAPE & MSE")
print ("-----")
print ("Moving Averages (Ratios) - MAPE: ",mean_err[0], "
MSE: ",median_err[0])
print ("Moving Averages (2016 Values) - MAPE: ",mean_err[1], "
MSE: ",median_err[1])
print ("-----")
print ("Weighted Moving Averages (Ratios) - MAPE: ",mean_err[2], "
MSE: ",median_err[2])
print ("Weighted Moving Averages (2016 Values) - MAPE: ",mean_err[3], "
MSE: ",median_err[3])
print ("-----")
print ("Exponential Moving Averages (Ratios) - MAPE: ",mean_err[4], "
MSE: ",median_err[4])
print ("Exponential Moving Averages (2016 Values) - MAPE: ",mean_err[5], "
MSE: ",median_err[5])
```

Error Metric Matrix (Forecasting Methods) - MAPE & MSE

```
-----
Moving Averages (Ratios) - MAPE: 0.2278515635
3133512 MSE: 1196.2953853046595
Moving Averages (2016 Values) - MAPE: 0.1558345871
2025738 MSE: 254.66309363799283
-----
Weighted Moving Averages (Ratios) - MAPE: 0.2270652914
4871415 MSE: 1053.083529345878
Weighted Moving Averages (2016 Values) - MAPE: 0.1479482182
992932 MSE: 224.81054547491038
-----
Exponential Moving Averages (Ratios) - MAPE: 0.2275474636148
534 MSE: 1019.3071012544802
Exponential Moving Averages (2016 Values) - MAPE: 0.1475381297798
153 MSE: 222.35159610215055
```

Please Note:- The above comparisons are made using Jan 2015 and Jan 2016 only

From the above matrix it is inferred that the best forecasting model for our prediction would be:-

$P'_t = \alpha * P_{t-1} + (1 - \alpha) * P'_{t-1}$ i.e Exponential Moving Averages using 2016 Values

Regression Models

Train-Test Split

Before we start predictions using the tree based regression models we take 3 months of 2016 pickup data and split it such that for every region we have 70% data in train and 30% in test, ordered date-wise for every region

In [0]:

```
# Preparing data to be split into train and test, The below prepares data in cumulative
form which will be later split into test and train
# number of 10min indices for jan 2015= 24*31*60/10 = 4464
# number of 10min indices for jan 2016 = 24*31*60/10 = 4464
# number of 10min indices for feb 2016 = 24*29*60/10 = 4176
# number of 10min indices for march 2016 = 24*31*60/10 = 4464
# regions_cum: it will contain 40 lists, each list will contain 4464+4176+4464 values w
hich represents the number of pickups
# that are happened for three months in 2016 data

# print(len(regions_cum))
# 40
# print(len(regions_cum[0]))
# 12960

# we take number of pickups that are happened in last 5 10min intravels
number_of_time_stamps = 5

# output varaible
# it is list of lists
# it will contain number of pickups 13099 for each cluster
output = []

# tsne_lat will contain 13104-5=13099 times latitude of cluster center for every clust
er
# Ex: [[cent_lat 13099times],[cent_lat 13099times], [cent_lat 13099times].... 40 lists]
# it is list of lists
tsne_lat = []

# tsne_lon will contain 13104-5=13099 times logitude of cluster center for every cluste
r
# Ex: [[cent_long 13099times],[cent_long 13099times], [cent_long 13099times].... 40 lis
ts]
# it is list of lists
tsne_lon = []

# we will code each day
# sunday = 0, monday=1, tue = 2, wed=3, thur=4, fri=5,sat=6
# for every cluster we will be adding 13099 values, each value represent to which day o
f the week that pickup bin belongs to
# it is list of lists
tsne_weekday = []

# its an numbpay array, of shape (523960, 5)
# each row corresponds to an entry in out data
# for the first row we will have [f0,f1,f2,f3,f4] fi=number of pickups happened in i+1t
h 10min intravel(bin)
# the second row will have [f1,f2,f3,f4,f5]
# the third row will have [f2,f3,f4,f5,f6]
# and so on...
tsne_feature = []

tsne_feature = [0]*number_of_time_stamps
for i in range(0,40):
    tsne_lat.append([kmeans.cluster_centers_[i][0]]*13099)
```



```

tsne_lon.append([kmeans.cluster_centers_[i][1]]*13099)
# jan 1st 2016 is thursday, so we start our day from 4: "(int(k/144))%7+4"
# our prediction start from 5th 10min intravel since we need to have number of pick
ups that are happened in last 5 pickup bins
tsne_weekday.append([int(((int(k/144))%7+4)%7) for k in range(5,4464+4176+4464)])
# regions_cum is a list of lists [[x1,x2,x3..x13104], [x1,x2,x3..x13104], [x1,x2,x
3..x13104], [x1,x2,x3..x13104], [x1,x2,x3..x13104], .. 40 lsits]
tsne_feature = np.vstack((tsne_feature, [regions_cum[i][r:r+number_of_time_stamps]
for r in range(0,len(regions_cum[i])-number_of_time_stamps)]))
output.append(regions_cum[i][5:])
tsne_feature = tsne_feature[1:]

```

In [72]:

```

len(tsne_lat[0])*len(tsne_lat) == tsne_feature.shape[0] == len(tsne_weekday)*len(tsne_w
eekday[0]) == 40*13099 == len(output)*len(output[0])

```

Out[72]:

True

In [0]:

```
# Getting the predictions of exponential moving averages to be used as a feature in cumulative form

# upto now we computed 8 features for every data point that starts from 50th min of the day
# 1. cluster center latitude
# 2. cluster center longitude
# 3. day of the week
# 4. f_t_1: number of pickups that are happened previous t-1th 10min intravel
# 5. f_t_2: number of pickups that are happened previous t-2th 10min intravel
# 6. f_t_3: number of pickups that are happened previous t-3th 10min intravel
# 7. f_t_4: number of pickups that are happened previous t-4th 10min intravel
# 8. f_t_5: number of pickups that are happened previous t-5th 10min intravel

# from the baseline models we said the exponential weighted moving average gives us the best error
# we will try to add the same exponential weighted moving average at t as a feature to our data
# exponential weighted moving average =>  $p'(t) = \alpha * p'(t-1) + (1-\alpha) * P(t-1)$ 
alpha=0.3

# it is a temporary array that store exponential weighted moving average for each 10min intravel,
# for each cluster it will get reset
# for every cluster it contains 13104 values
predicted_values=[]

# it is similar like tsne_lat
# it is list of lists
# predict_list is a list of lists [[x5,x6,x7..x13104], [x5,x6,x7..x13104], [x5,x6,x7..x13104], [x5,x6,x7..x13104], [x5,x6,x7..x13104], .. 40 lists]
predict_list = []
tsne_flat_exp_avg = []
for r in range(0,40):
    for i in range(0,13104):
        if i==0:
            predicted_value= regions_cum[r][0]
            predicted_values.append(0)
            continue
        predicted_values.append(predicted_value)
        predicted_value =int((alpha*predicted_value) + (1-alpha)*(regions_cum[r][i]))
    predict_list.append(predicted_values[5:])
    predicted_values=[]
```

In [74]:

```
# train, test split : 70% 30% split
# Before we start predictions using the tree based regression models we take 3 months of 2016 pickup data
# and split it such that for every region we have 70% data in train and 30% in test,
# ordered date-wise for every region
print("size of train data :", int(13099*0.7))
print("size of test data :", int(13099*0.3))
```

```
size of train data : 9169
size of test data : 3929
```

In [0]:

```
# extracting first 9169 timestamp values i.e 70% of 13099 (total timestamps) for our training data
train_features = [tsne_feature[i*13099:(13099*i+9169)] for i in range(0,40)]
# temp = [0]*(12955 - 9068)
test_features = [tsne_feature[(13099*(i))+9169:13099*(i+1)] for i in range(0,40)]
```

In [76]:

```
print("Number of data clusters",len(train_features), "Number of data points in training data", len(train_features[0]), "Each data point contains", len(train_features[0][0]),"features")
print("Number of data clusters",len(train_features), "Number of data points in test data", len(test_features[0]), "Each data point contains", len(test_features[0][0]),"features")
```

Number of data clusters 40 Number of data points in training data 9169 Each data point contains 5 features

Number of data clusters 40 Number of data points in test data 3930 Each data point contains 5 features

In [0]:

```
# extracting first 9169 timestamp values i.e 70% of 13099 (total timestamps) for our training data
tsne_train_flat_lat = [i[:9169] for i in tsne_lat]
tsne_train_flat_lon = [i[:9169] for i in tsne_lon]
tsne_train_flat_weekday = [i[:9169] for i in tsne_weekday]
tsne_train_flat_output = [i[:9169] for i in output]
tsne_train_flat_exp_avg = [i[:9169] for i in predict_list]
```

In [0]:

```
# extracting the rest of the timestamp values i.e 30% of 12956 (total timestamps) for our test data
tsne_test_flat_lat = [i[9169:] for i in tsne_lat]
tsne_test_flat_lon = [i[9169:] for i in tsne_lon]
tsne_test_flat_weekday = [i[9169:] for i in tsne_weekday]
tsne_test_flat_output = [i[9169:] for i in output]
tsne_test_flat_exp_avg = [i[9169:] for i in predict_list]
```

In [0]:

```
# the above contains values in the form of list of lists (i.e. list of values of each region), here we make all of them in one list
train_new_features = []
for i in range(0,40):
    train_new_features.extend(train_features[i])
test_new_features = []
for i in range(0,40):
    test_new_features.extend(test_features[i])
```

In [0]:

```
# converting lists of lists into sinle list i.e flatten
# a = [[1,2,3,4],[4,6,7,8]]
# print(sum(a,[]))
# [1, 2, 3, 4, 4, 6, 7, 8]

tsne_train_lat = sum(tsne_train_flat_lat, [])
tsne_train_lon = sum(tsne_train_flat_lon, [])
tsne_train_weekday = sum(tsne_train_flat_weekday, [])
tsne_train_output = sum(tsne_train_flat_output, [])
tsne_train_exp_avg = sum(tsne_train_flat_exp_avg,[])
```

In [0]:

```
# converting lists of lists into sinle list i.e flatten
# a = [[1,2,3,4],[4,6,7,8]]
# print(sum(a,[]))
# [1, 2, 3, 4, 4, 6, 7, 8]

tsne_test_lat = sum(tsne_test_flat_lat, [])
tsne_test_lon = sum(tsne_test_flat_lon, [])
tsne_test_weekday = sum(tsne_test_flat_weekday, [])
tsne_test_output = sum(tsne_test_flat_output, [])
tsne_test_exp_avg = sum(tsne_test_flat_exp_avg,[])
```

In [82]:

```
# Preparing the data frame for our train data
columns = ['ft_5', 'ft_4', 'ft_3', 'ft_2', 'ft_1']
df_train = pd.DataFrame(data=train_new_features, columns=columns)
df_train['lat'] = tsne_train_lat
df_train['lon'] = tsne_train_lon
df_train['weekday'] = tsne_train_weekday
df_train['exp_avg'] = tsne_train_exp_avg

print(df_train.shape)
```

(366760, 9)

In [83]:

```
# Preparing the data frame for our train data
df_test = pd.DataFrame(data=test_new_features, columns=columns)
df_test['lat'] = tsne_test_lat
df_test['lon'] = tsne_test_lon
df_test['weekday'] = tsne_test_weekday
df_test['exp_avg'] = tsne_test_exp_avg
print(df_test.shape)
```

(157200, 9)

In [84]:

df_test.head()

Out[84]:

	ft_5	ft_4	ft_3	ft_2	ft_1	lat	lon	weekday	exp_avg
0	143	145	119	113	124	40.776228	-73.982119	4	121
1	145	119	113	124	121	40.776228	-73.982119	4	120
2	119	113	124	121	131	40.776228	-73.982119	4	127
3	113	124	121	131	110	40.776228	-73.982119	4	115
4	124	121	131	110	116	40.776228	-73.982119	4	115

In [0]:

```

#https://github.com/UdiBhaskar/Taxi-Pickup-Prediction-New-York/blob/master/Yellow%20Taxi%20Pickup%20Prediction%20-%20New%20York.ipynb
def fourier_transform(X,n_predict=0,n_wave=144):
    ##fft
    fft_x = np.fft.fft(X)
    ##fft freq
    freq = np.fft.fftfreq(len(X),1)
    idx = list(range(len(X)))
    ##sorting
    idx.sort(key=lambda i:np.absolute(freq[i]))
    t = np.arange(0,len(X)+n_predict)
    ##restoring series
    restored_series = np.zeros(t.size)
    for j in idx[:1+n_wave*2]:
        #amplitude
        ampl = np.absolute(fft_x[j])/len(X)
        #phase
        phase = np.angle(fft_x[j])
        restored_series += ampl * np.cos(2 * np.pi * freq[j] * t + phase)
    #return np.absolute(np.fft.ifft(np.array(xf)[idx[:1+n_harm*2]]))
    return restored_series

```

In [0]:

```
from statsmodels.tsa.seasonal import seasonal_decompose
final_fourier_train = []
final_fourier_test = []
for i in range(40):
    #for each cluster
    temp_data = tsne_train_output[9169*i:9169*(i+1)]
    #seasonal decompose to get seasonal
    result = seasonal_decompose(x=temp_data, model='additive', freq=144)
    #getting top harmonics and predicting test samples aslo
    fourier_decom = fourier_transform(result.seasonal, n_predict=3930, n_wave=440)
    #training data
    train_fourier = fourier_decom[0:9169]
    #testing data
    test_fourier = fourier_decom[9169:]
    final_fourier_train.extend(train_fourier)
    final_fourier_test.extend(test_fourier)
```

In [0]:

```
df_train['fourier_decom'] = final_fourier_train
df_test['fourier_decom'] = final_fourier_test
```

Using Linear Regression

In [100]:

```
from sklearn.linear_model import Lasso
for alpha in [10**i for i in range(-5,5)]:
    lr_reg = Lasso(alpha=alpha).fit(df_train, tsne_train_output)
    y_pred = lr_reg.predict(df_test)
    lr_test_predictions = [round(value) for value in y_pred]
    y_pred = lr_reg.predict(df_train)
    lr_train_predictions = [round(value) for value in y_pred]
    print('Train MAPE = ', (mean_absolute_error(tsne_train_output, lr_train_predictions)
))/ (sum(tsne_train_output)/len(tsne_train_output)))
    print('Test MAPE = ', (mean_absolute_error(tsne_test_output, lr_test_predictions))/ (
sum(tsne_test_output)/len(tsne_test_output)))
```

```
Train MAPE = 0.14242436717475515
Test MAPE = 0.1350884271739152
Train MAPE = 0.1424246359517031
Test MAPE = 0.13508975662739683
Train MAPE = 0.14241289935830845
Test MAPE = 0.13510589999110217
Train MAPE = 0.1424263382057069
Test MAPE = 0.13527920374852706
Train MAPE = 0.14243014587913647
Test MAPE = 0.1352769246854157
Train MAPE = 0.14255759094863166
Test MAPE = 0.13531946719682741
Train MAPE = 0.14252986212683288
Test MAPE = 0.13534453689105214
Train MAPE = 0.14802218467010073
Test MAPE = 0.1390265532693493
Train MAPE = 0.27122447565313135
Test MAPE = 0.24741575609390612
Train MAPE = 0.8368776576160658
Test MAPE = 0.7633975437207396
```

In [0]:

```
# find more about LinearRegression function here http://scikit-learn.org/stable/modules/generated/sklearn.linear\_model.LinearRegression.html
# -----
# default paramters
# sklearn.linear_model.LinearRegression(fit_intercept=True, normalize=False, copy_X=True, n_jobs=1)

# some of methods of LinearRegression()
# fit(X, y[, sample_weight])    Fit linear model.
# get_params([deep])          Get parameters for this estimator.
# predict(X)                  Predict using the linear model
# score(X, y[, sample_weight]) Returns the coefficient of determination R^2 of the prediction.
# set_params(**params)       Set the parameters of this estimator.
# -----
# video link: https://www.appliedaicourse.com/course/applied-ai-course-online/lessons/geometric-intuition-1-2-copy-8/
# -----

from sklearn.linear_model import LinearRegression
lr_reg=LinearRegression().fit(df_train, tsne_train_output)

y_pred = lr_reg.predict(df_test)
lr_test_predictions = [round(value) for value in y_pred]
y_pred = lr_reg.predict(df_train)
lr_train_predictions = [round(value) for value in y_pred]
```

Using Random Forest Regressor

In [102]:

```
for n_estimators in [i for i in range(10,100,10)]:
    regr1 = RandomForestRegressor(max_features='sqrt',min_samples_leaf=4,min_samples_sp
lit=3,n_estimators=n_estimators, n_jobs=-1)
    regr1.fit(df_train, tsne_train_output)
    y_pred = regr1.predict(df_test)
    lr_test_predictions = [round(value) for value in y_pred]
    y_pred = regr1.predict(df_train)
    lr_train_predictions = [round(value) for value in y_pred]
    print('Train MAPE = ',(mean_absolute_error(tsne_train_output, lr_train_predictions
)))/(sum(tsne_train_output)/len(tsne_train_output)))
    print('Test MAPE = ',(mean_absolute_error(tsne_test_output, lr_test_predictions))/(
sum(tsne_test_output)/len(tsne_test_output)))
```

```
Train MAPE = 0.09900022590702476
Test MAPE = 0.13675014906497165
Train MAPE = 0.09704348492965413
Test MAPE = 0.13494389658827102
Train MAPE = 0.09631904146256232
Test MAPE = 0.13424431917405236
Train MAPE = 0.09586673465528886
Test MAPE = 0.13388565161690508
Train MAPE = 0.0957399167320056
Test MAPE = 0.13370921414770212
Train MAPE = 0.09554904030278977
Test MAPE = 0.13355442777805687
Train MAPE = 0.09546334525254574
Test MAPE = 0.13341103672396834
Train MAPE = 0.09542728434535992
Test MAPE = 0.133388056170929
Train MAPE = 0.09530687227266992
Test MAPE = 0.13330790911818016
```

In [103]:

```

# Training a hyper-parameter tuned random forest regressor on our train data
# find more about LinearRegression function here http://scikit-learn.org/stable/modules/generated/sklearn.ensemble.RandomForestRegressor.html
# -----
# default paramters
# sklearn.ensemble.RandomForestRegressor(n_estimators=10, criterion='mse', max_depth=None, min_samples_split=2,
# min_samples_leaf=1, min_weight_fraction_leaf=0.0, max_features='auto', max_leaf_nodes=None, min_impurity_decrease=0.0,
# min_impurity_split=None, bootstrap=True, oob_score=False, n_jobs=1, random_state=None, verbose=0, warm_start=False)

# some of methods of RandomForestRegressor()
# apply(X)      Apply trees in the forest to X, return leaf indices.
# decision_path(X)      Return the decision path in the forest
# fit(X, y[, sample_weight])      Build a forest of trees from the training set (X, y).
# get_params([deep])      Get parameters for this estimator.
# predict(X)      Predict regression target for X.
# score(X, y[, sample_weight])      Returns the coefficient of determination R^2 of the prediction.
# -----
# video link1: https://www.appliedaicourse.com/course/applied-ai-course-online/lessons/regression-using-decision-trees-2/
# video link2: https://www.appliedaicourse.com/course/applied-ai-course-online/lessons/what-are-ensembles/
# -----

regr1 = RandomForestRegressor(max_features='sqrt',min_samples_leaf=4,min_samples_split=3,n_estimators=40, n_jobs=-1)
regr1.fit(df_train, tsne_train_output)

```

Out[103]:

```

RandomForestRegressor(bootstrap=True, criterion='mse', max_depth=None,
                       max_features='sqrt', max_leaf_nodes=None,
                       min_impurity_decrease=0.0, min_impurity_split=None,
                       min_samples_leaf=4, min_samples_split=3,
                       min_weight_fraction_leaf=0.0, n_estimators=40, n_job
s=-1,
                       oob_score=False, random_state=None, verbose=0,
                       warm_start=False)

```

In [0]:

```

# Predicting on test data using our trained random forest model

# the models regr1 is already hyper parameter tuned
# the parameters that we got above are found using grid search

y_pred = regr1.predict(df_test)
rndf_test_predictions = [round(value) for value in y_pred]
y_pred = regr1.predict(df_train)
rndf_train_predictions = [round(value) for value in y_pred]

```

In [105]:

```
#feature importances based on analysis using random forest  
print (df_train.columns)  
print (regr1.feature_importances_)
```

```
Index(['ft_5', 'ft_4', 'ft_3', 'ft_2', 'ft_1', 'lat', 'lon', 'weekday',  
      'exp_avg', 'fourier_decom'],  
      dtype='object')  
[0.01718266 0.10004671 0.09635472 0.1383889  0.25441846 0.00234816  
 0.00266146 0.00168495 0.38246688 0.00444711]
```

Using XgBoost Regressor

In [107]:

```
# Training a hyper-parameter tuned Xg-Boost regressor on our train data

# find more about XGBRegressor function here http://xgboost.readthedocs.io/en/latest/python/python\_api.html?#module-xgboost.sklearn
# -----
# default paramters
# xgboost.XGBRegressor(max_depth=3, learning_rate=0.1, n_estimators=100, silent=True, objective='reg:linear',
# booster='gbtree', n_jobs=1, nthread=None, gamma=0, min_child_weight=1, max_delta_step=0, subsample=1,
# colsample_bytree=1, colsample_bylevel=1, reg_alpha=0, reg_lambda=1, scale_pos_weight=1, base_score=0.5, random_state=0, seed=None,
# missing=None, **kwargs)

# some of methods of RandomForestRegressor()
# fit(X, y, sample_weight=None, eval_set=None, eval_metric=None, early_stopping_rounds=None, verbose=True, xgb_model=None)
# get_params([deep]) Get parameters for this estimator.
# predict(data, output_margin=False, ntree_limit=0) : Predict with data. NOTE: This function is not thread safe.
# get_score(importance_type='weight') -> get the feature importance
# -----
# video link1: https://www.appliedaicourse.com/course/applied-ai-course-online/lessons/regression-using-decision-trees-2/
# video link2: https://www.appliedaicourse.com/course/applied-ai-course-online/lessons/what-are-ensembles/
# -----

x_model = XGBRegressor(
    learning_rate =0.1,
    n_estimators=1000,
    max_depth=3,
    min_child_weight=3,
    gamma=0,
    subsample=0.8,
    reg_alpha=200, reg_lambda=200,
    colsample_bytree=0.8,nthread=4)
x_model.fit(df_train, tsne_train_output)
```

[04:49:58] WARNING: /workspace/src/objective/regression_obj.cu:152: reg:linear is now deprecated in favor of reg:squarederror.

Out[107]:

```
XGBRegressor(base_score=0.5, booster='gbtree', colsample_bylevel=1,
             colsample_bynode=1, colsample_bytree=0.8, gamma=0,
             importance_type='gain', learning_rate=0.1, max_delta_step=0,
             max_depth=3, min_child_weight=3, missing=None, n_estimators=1000,
             n_jobs=1, nthread=4, objective='reg:linear', random_state=0,
             reg_alpha=200, reg_lambda=200, scale_pos_weight=1, seed=None,
             silent=None, subsample=0.8, verbosity=1)
```

In [0]:

```
#predicting with our trained Xg-Boost regressor
# the models x_model is already hyper parameter tuned
# the parameters that we got above are found using grid search

y_pred = x_model.predict(df_test)
xgb_test_predictions = [round(value) for value in y_pred]
y_pred = x_model.predict(df_train)
xgb_train_predictions = [round(value) for value in y_pred]
```

In [109]:

```
from xgboost.sklearn import XGBRegressor
from sklearn.model_selection import RandomizedSearchCV
xgb = XGBRegressor()
parameters = {'objective':['reg:linear'],
              'learning_rate': [.03, 0.05, .07],
              'max_depth': [5, 6, 7],
              'min_child_weight': [4],
              'subsample': [0.7],
              'colsample_bytree': [0.7],
              'n_estimators': [500]}

xgb_grid = RandomizedSearchCV(xgb,
                              parameters,
                              cv = 2,
                              n_jobs = 5,
                              verbose=True)

xgb_grid.fit(df_train,
             tsne_train_output)

print(xgb_grid.best_score_)
print(xgb_grid.best_params_)
```

Fitting 2 folds for each of 9 candidates, totalling 18 fits

[Parallel(n_jobs=5)]: Using backend LokyBackend with 5 concurrent workers.
 [Parallel(n_jobs=5)]: Done 18 out of 18 | elapsed: 12.3min finished

[05:04:10] WARNING: /workspace/src/objective/regression_obj.cu:152: reg:linear is now deprecated in favor of reg:squarederror.
 0.9473384837058241
 {'subsample': 0.7, 'objective': 'reg:linear', 'n_estimators': 500, 'min_child_weight': 4, 'max_depth': 5, 'learning_rate': 0.03, 'colsample_bytree': 0.7}

In [110]:

```
x_model = XGBRegressor(subsample= 0.7, n_estimators=500, min_child_weight= 4, max_depth
=5, learning_rate= 0.03, colsample_bytree= 0.7)
x_model.fit(df_train, tsne_train_output)

y_pred = x_model.predict(df_test)
xgb_test_predictions = [round(value) for value in y_pred]
y_pred = x_model.predict(df_train)
xgb_train_predictions = [round(value) for value in y_pred]
```

[05:07:59] WARNING: /workspace/src/objective/regression_obj.cu:152: reg:li
near is now deprecated in favor of reg:squarederror.

Calculating the error metric values for various models

In [0]:

```
train_mape=[]
test_mape=[]

train_mape.append((mean_absolute_error(tsne_train_output,df_train['ft_1'].values))/(sum
(tsne_train_output)/len(tsne_train_output)))
train_mape.append((mean_absolute_error(tsne_train_output,df_train['exp_avg'].values))/(
sum(tsne_train_output)/len(tsne_train_output)))
train_mape.append((mean_absolute_error(tsne_train_output,rndf_train_predictions))/(sum(
tsne_train_output)/len(tsne_train_output)))
train_mape.append((mean_absolute_error(tsne_train_output, xgb_train_predictions))/(sum(
tsne_train_output)/len(tsne_train_output)))
train_mape.append((mean_absolute_error(tsne_train_output, lr_train_predictions))/(sum(t
sne_train_output)/len(tsne_train_output)))

test_mape.append((mean_absolute_error(tsne_test_output, df_test['ft_1'].values))/(sum(t
sne_test_output)/len(tsne_test_output)))
test_mape.append((mean_absolute_error(tsne_test_output, df_test['exp_avg'].values))/(su
m(tsne_test_output)/len(tsne_test_output)))
test_mape.append((mean_absolute_error(tsne_test_output, rndf_test_predictions))/(sum(t
sne_test_output)/len(tsne_test_output)))
test_mape.append((mean_absolute_error(tsne_test_output, xgb_test_predictions))/(sum(tsn
e_test_output)/len(tsne_test_output)))
test_mape.append((mean_absolute_error(tsne_test_output, lr_test_predictions))/(sum(t
sne_test_output)/len(tsne_test_output)))
```

In [112]:

```

print ("Error Metric Matrix (Tree Based Regression Methods) - MAPE")
print ("-----")
print ("-----")
print ("Baseline Model -                                Train: ",train_mape[0],"      Tes
t: ",test_mape[0])
print ("Exponential Averages Forecasting -              Train: ",train_mape[1],"      Tes
t: ",test_mape[1])
print ("Linear Regression -                             Train: ",train_mape[3],"      Test:
",test_mape[3])
print ("Random Forest Regression -                      Train: ",train_mape[2],"      Test:
",test_mape[2])

```

Error Metric Matrix (Tree Based Regression Methods) - MAPE

```

-----
Baseline Model -                                Train:  0.14870666996426116
Test:  0.14225522601041551
Exponential Averages Forecasting -              Train:  0.14121603560900353
Test:  0.13490049942819257
Linear Regression -                             Train:  0.13746547728088931
Test:  0.13333088967121953
Random Forest Regression -                      Train:  0.09596779478772512
Test:  0.13385345985045738

```

Error Metric Matrix

In [113]:

```

print ("Error Metric Matrix (Tree Based Regression Methods) - MAPE")
print ("-----")
print ("-----")
print ("Baseline Model -                                Train: ",train_mape[0],"      Tes
t: ",test_mape[0])
print ("Exponential Averages Forecasting -              Train: ",train_mape[1],"      Tes
t: ",test_mape[1])
print ("Linear Regression -                             Train: ",train_mape[4],"      Test:
",test_mape[4])
print ("Random Forest Regression -                      Train: ",train_mape[2],"      Test:
",test_mape[2])
print ("XgBoost Regression -                             Train: ",train_mape[3],"      Tes
t: ",test_mape[3])
print ("-----")
print ("-----")

```

Error Metric Matrix (Tree Based Regression Methods) - MAPE

```

-----
-----
Baseline Model -                                Train:  0.14870666996426116
Test:  0.14225522601041551
Exponential Averages Forecasting -              Train:  0.14121603560900353
Test:  0.13490049942819257
Linear Regression -                             Train:  0.09530687227266992
Test:  0.13330790911818016
Random Forest Regression -                      Train:  0.09596779478772512
Test:  0.13385345985045738
XgBoost Regression -                             Train:  0.13746547728088931
Test:  0.13333088967121953
-----
-----

```