

Report 1: Event Boundaries and Memory in the Mnemonic Similarity Task

BRSM 2026 — Preliminary Descriptive and Inferential Analysis

March 03, 2026

Contents

1	Introduction	3
1.1	What Is Event Segmentation?	3
1.2	How Event Boundaries Affect Memory	3
1.3	The Mnemonic Similarity Task (MST)	3
1.4	Purpose of This Study	3
2	Methods	5
2.1	Participants	5
2.2	Experimental Procedure	5
2.2.1	Encoding Phase	5
2.2.2	Test Phase	5
2.2.3	Lure Bins	6
2.3	Variables Computed	6
2.3.1	Memory Metrics	6
2.3.2	Why Correct for Bias?	6
2.4	Statistical Analysis	6
2.4.1	Descriptive Statistics	6
2.4.2	Normality Checks	6
2.4.3	Inferential Tests	6
2.4.4	Multiple Comparison Corrections	7
3	Results	8
3.1	Descriptive Statistics	8
3.1.1	Overall Memory Performance	8
3.1.2	Memory by Boundary Position	8
3.2	Visualisations	9
3.2.1	REC by Boundary Position	9
3.2.2	LDI by Boundary Position	10
3.2.3	Mean REC and LDI Across Positions	11
3.2.4	Lure Bin Accuracy Curve	12

3.2.5	Retrieval Reaction Times	13
3.2.6	Encoding RT vs. Lure Discrimination	14
3.3	Normality Checks	14
3.4	Inferential Statistics	16
3.4.1	Blind Spot Effect: REC at Post-Boundary vs. Mid-Event	16
3.4.2	Snapshot Effect: LDI at Pre-Boundary vs. Mid-Event	16
3.4.3	Speed Bump: Retrieval RT at Post-Boundary vs. Mid-Event	17
3.4.4	Correlations: Encoding RT and Memory	17
3.4.5	Summary: Multiple Comparison Corrections	18
3.5	Additional Findings Beyond the Original Hypotheses	18
3.5.1	Between-Group Differences in Overall Recognition Memory	18
3.5.2	Between-Group Differences in Encoding Reaction Time	18
3.5.3	Response Bias Across Groups	19
3.5.4	Pre-Boundary vs. Post-Boundary Recognition (Direct Comparison)	19
3.5.5	Lure Bin Accuracy by Boundary Position	20
4	Conclusion	21
4.1	Summary of Findings	21
4.1.1	Hypothesis Verdicts	21
4.1.2	Novel Findings (Beyond the Original Paper)	21
4.1.3	Normality	22
4.2	Limitations and Future Directions	22
5	References	23

1 Introduction

1.1 What Is Event Segmentation?

Our daily experiences are not stored in memory as one continuous stream. Instead, the brain naturally breaks ongoing activity into smaller chunks called **events**. This process is known as **event segmentation** (Zacks et al., 2007). An event boundary occurs when there is a noticeable change in our surroundings — for example, walking from the kitchen into the living room, or a change of scene in a movie. These boundaries play an important role in how we form and retrieve memories.

1.2 How Event Boundaries Affect Memory

Research has shown that event boundaries have two interesting effects on memory:

1. **The Blind Spot Effect** — Items that appear right *after* an event boundary are often remembered less well. This is thought to happen because the brain is busy “closing” the previous event and “opening” a new one, so items right at the transition get less attention (Swallow et al., 2009; DuBrow & Davachi, 2014).
2. **The Snapshot Effect** — Items that appear right *before* a boundary may be remembered with more detail. The idea is that the boundary acts like a signal that “stamps in” the most recent items into memory with higher fidelity (Heusser et al., 2018).

1.3 The Mnemonic Similarity Task (MST)

The **Mnemonic Similarity Task** is a well-established memory test developed by Stark et al. (2013, 2019). In this task, participants first study a series of object images (the *encoding* phase). Later, in the *test* phase, they see three types of images:

- **Targets** — the exact same images they saw before (correct answer: “Old”)
- **Lures** — images that are similar but not identical to studied images (correct answer: “Similar”)
- **Foils** — completely new images never seen before (correct answer: “New”)

The key strength of the MST is that it can measure two distinct aspects of memory:

- **Recognition (REC)** — the ability to tell studied items from new items
- **Lure Discrimination (LDI)** — the ability to tell similar items from identical ones, which reflects a process called *pattern separation* in the hippocampus

1.4 Purpose of This Study

This study, following the design of Morse et al. (2023), used the MST with event boundaries to test whether boundary effects on memory can be observed in a controlled laboratory setting. Specifically, we tested:

- **Hypothesis 1 (Blind Spot):** Post-boundary items will have lower REC than mid-event items.
- **Hypothesis 2 (Snapshot):** Pre-boundary items will have higher LDI than mid-event items.
- **Hypothesis 3 (Speed Bump):** Post-boundary items will show slower reaction times.

Data were collected from three experimental groups that differed in the type of encoding task performed.

2 Methods

2.1 Participants

A total of **159 participants** took part in the experiment, divided into three groups based on the type of task they performed during the encoding phase:

Table 1: Number of participants in each experimental group.

Experimental Group	N
Item Only	56
Task Only	53
Both Item & Task	51

- **Item Only (n = 56):** Participants simply viewed each object image and indicated whether it was an indoor or outdoor scene.
- **Task Only (n = 53):** Participants performed a categorization task on each image.
- **Both Item & Task (n = 50–52):** Participants performed both the viewing and categorization tasks.

2.2 Experimental Procedure

2.2.1 Encoding Phase

Participants viewed a sequence of **280 object images** on a computer screen. The images were arranged in groups of 7, separated by **scene images** that served as event boundaries. For the analysis, we compared three critical positions within each group of 7 objects:

- **Position 1** (post-boundary): The first object immediately after a scene change
- **Position 4** (mid-event): The middle object within the event, used as the baseline for comparison
- **Position 7** (pre-boundary): The last object just before the next scene change

Position 4 was chosen as the mid-event baseline because it is the farthest from both boundaries, making it the least likely to be affected by boundary processing. For each image, participants pressed a key to respond (reaction time was recorded).

2.2.2 Test Phase

After encoding, participants completed a memory test with **150 images**: targets (studied objects), lures (similar objects), and foils (never-seen objects). For each image, they pressed:

- “**O**” if they thought it was an Old (previously seen) image
- “**S**” if they thought it was Similar to a seen image
- “**N**” if they thought it was New

2.2.3 Lure Bins

Lures were categorized into **5 similarity bins** (Bin 1 = most similar to the original, Bin 5 = most different). This allows us to measure how well participants can discriminate lures of varying difficulty.

2.3 Variables Computed

2.3.1 Memory Metrics

Two key memory metrics were calculated for each participant at each boundary position:

- **REC (Recognition Memory Index):** $REC = P(\text{"Old"}|\text{Target}) - P(\text{"Old"}|\text{Foil})$

This measures recognition ability, corrected for the tendency to say “Old” to everything (response bias).

- **LDI (Lure Discrimination Index):** $LDI = P(\text{"Similar"}|\text{Lure}) - P(\text{"Similar"}|\text{Foil})$

This measures the ability to distinguish similar items from identical ones, corrected for the tendency to say “Similar” to everything.

2.3.2 Why Correct for Bias?

Raw hit rates alone can be misleading. A person who says “Old” to everything will have a high hit rate but poor actual memory. By subtracting the false alarm rate (responding “Old” to foils), we get a cleaner measure of true memory ability.

2.4 Statistical Analysis

2.4.1 Descriptive Statistics

We computed means, standard deviations, medians, and IQR using the **psych** package in R (Revelle, 2023). Distributions were visualized using histograms, violin plots, and boxplots.

2.4.2 Normality Checks

Before running parametric tests, we checked whether the data were normally distributed using:

- **Shapiro-Wilk test:** A formal statistical test ($p < 0.05$ suggests non-normality)
- **QQ plots:** Visual inspection for departures from normality

2.4.3 Inferential Tests

- **Paired t-tests:** To compare REC and LDI between boundary positions within each group (within-subjects comparison). We also report **Wilcoxon signed-rank tests** as a non-parametric alternative.

- **One-sample t-tests:** To test whether the difference scores (e.g., REC_post – REC_mid) were significantly different from zero.
- **Pearson and Spearman correlations:** To examine relationships between encoding reaction time and memory outcomes.
- **Cohen’s d:** To quantify effect sizes (small = 0.2, medium = 0.5, large = 0.8).

2.4.4 Multiple Comparison Corrections

With multiple tests, there is a risk of “false positives” (finding something significant by chance). We applied two correction methods:

- **Bonferroni correction:** Multiplies each p-value by the total number of tests. This is very strict and ensures the overall false positive rate stays below 5%.
- **Benjamini-Hochberg (BH) correction:** A less strict method that controls the proportion of false positives among significant results (the “false discovery rate”). This is preferred when we want to avoid missing true effects.

We report raw p-values alongside both corrected values so the reader can judge significance under different standards.

3 Results

3.1 Descriptive Statistics

3.1.1 Overall Memory Performance

Table 2: Overall REC and LDI by experimental group.

Group	n	REC Mean	REC SD	LDI Mean	LDI SD
Item Only	56	0.685	0.187	0.374	0.236
Task Only	53	0.596	0.195	0.381	0.204
Both	51	0.641	0.190	0.307	0.251

Table 2 shows that all three groups have positive REC and LDI values, indicating that participants could both recognize old items and discriminate similar lures from identical ones. This confirms the MST is working as expected.

3.1.2 Memory by Boundary Position

Table 3: REC and LDI by boundary position and group.

Group	Position	REC Mean	REC SD	LDI Mean	LDI SD
Item Only	pre	0.697	0.163	0.378	0.270
Item Only	mid	0.706	0.188	0.386	0.234
Item Only	post	0.651	0.206	0.359	0.203
Task Only	pre	0.624	0.195	0.387	0.205
Task Only	mid	0.601	0.183	0.369	0.180
Task Only	post	0.563	0.204	0.386	0.229
Both	pre	0.672	0.180	0.330	0.230
Both	mid	0.687	0.174	0.319	0.281
Both	post	0.564	0.194	0.272	0.241

Looking at the means in Table 3, we can see that in the **Both Item & Task** group, post-boundary REC (mean) is noticeably lower than mid-event REC — this is consistent with the Blind Spot hypothesis.

3.2 Visualisations

3.2.1 REC by Boundary Position




Figure 1: Recognition Memory (REC) by boundary position for each group. Violin plots show the full distribution, boxes show the median and IQR, and the red diamond marks the mean. In the Both Item & Task group, post-boundary items clearly show lower REC.

Observations (Figure 1 — REC by Position): This plot shows how well participants recognized old items at each boundary position. Looking at the **Both Item & Task** group (right panel), we can clearly see that the post-boundary violin and box are shifted downward compared to mid-event — meaning participants were worse at recognizing items that appeared right after a scene change. The red diamond (mean) for post-boundary sits noticeably lower than for mid-event. In the **Item Only** and **Task Only** groups, the differences are smaller, but a slight downward trend at post-boundary is still visible. The violin shapes also reveal that REC scores are spread out quite widely across participants, especially at the pre-boundary position, suggesting large individual differences in how boundaries affect memory.

3.2.2 LDI by Boundary Position




Figure 2: Lure Discrimination Index (LDI) by boundary position. No clear pattern of pre-boundary enhancement (Snapshot effect) is visible.

Observations (Figure 2 — LDI by Position): This plot shows how well participants could tell apart similar lures from identical targets at each boundary position. Unlike the REC results, there is no obvious visual pattern across the three positions. The pre-boundary violins do not appear to be shifted higher than mid-event in any group, which goes against the Snapshot hypothesis (which predicted pre-boundary items would have higher LDI). The distributions look fairly similar across all three positions in each group, with the means (red diamonds) all hovering around similar values. This suggests that event boundaries do not strongly affect the fidelity of memory representations, at least not in a way detectable with this sample size.

3.2.3 Mean REC and LDI Across Positions




Figure 3: Mean REC (left) and LDI (right) across boundary positions by group. Error bars show ± 1 standard error. The drop in REC at post-boundary for the Both group is visible.

Observations (Figure 3 — Mean REC and LDI Line Plots): These line plots make the group trends much easier to compare. In the **left panel (REC)**, we can see that the Both Item & Task group (green line) shows a clear drop from mid to post boundary position — this is the Blind Spot effect in action. The Item Only (orange) and Task Only (blue) groups show flatter patterns, though both dip slightly at post. In the **right panel (LDI)**, all three group lines are relatively flat across positions, confirming that boundary position does not strongly affect lure discrimination. The error bars (± 1 standard error) help us judge whether differences are likely real: when error bars of two points overlap substantially, the difference is unlikely to be significant. Notice how for the Both group’s REC, the post error bar barely touches the mid error bar — consistent with the significant effect we found in the statistical tests.

3.2.4 Lure Bin Accuracy Curve




Figure 4: Proportion of correct 'Similar' responses for lures across 5 similarity bins. Bin 1 contains the most similar lures (hardest), Bin 5 the least similar (easiest). All groups show the expected decrease, confirming the MST is measuring pattern separation.

Observations (Figure 4 — Lure Bin Accuracy Curve): This is one of the most important validation plots for the MST. It shows how accurately participants identified lures as “Similar” depending on how similar the lure was to the original studied item. All three groups show the expected **downward slope from Bin 1 to Bin 5**: participants were best at correctly saying “Similar” when the lure was very similar to the original (Bin 1), and worst when the lure was quite different (Bin 5). This makes intuitive sense — it is easier to notice that something is “similar but different” when the difference is subtle. The fact that all three groups show this pattern confirms that the MST is working properly and participants were genuinely engaging with the task. The three groups have largely overlapping curves, suggesting that the type of encoding task does not drastically change overall pattern separation ability.

3.2.5 Retrieval Reaction Times




Figure 5: Retrieval reaction time by stimulus type across groups. Violin plots show the distribution; outliers above 10 seconds are trimmed for clarity.

Observations (Figure 5 — Retrieval RT by Stimulus Type): This plot shows how long participants took to respond during the memory test, broken down by whether the image was a Target, Lure, or Foil. Across all three groups, the distributions are right-skewed (long tail towards higher RTs), which is typical for reaction time data. **Lures tend to have slightly longer reaction times** than Targets and Foils — this makes sense because lures are the hardest items to judge (they look similar to something seen before, so participants need more time to decide). The median RTs (horizontal line in each box) are roughly between 2–3 seconds for all stimulus types. The Task Only group shows slightly more variability in RT, as indicated by the wider violin shapes.

3.2.6 Encoding RT vs. Lure Discrimination




Figure 6: Relationship between mean encoding reaction time and overall lure discrimination (LDI). Each point is one participant. No strong linear relationship is observed.

Observations (Figure 6 — Encoding RT vs. LDI Scatterplot): This scatter plot explores whether spending more time looking at objects during encoding leads to better lure discrimination. Each dot represents one participant; the blue line is the best-fit regression line with a 95% confidence band. In all three groups, the dots are scattered widely with **no clear linear trend**. The regression lines are nearly flat (close to horizontal), and the confidence bands are wide, indicating a weak and unreliable relationship. This tells us that, at the participant level, how long someone spends viewing images during encoding does not meaningfully predict how well they can later discriminate similar lures — quality of encoding processes may matter more than raw viewing time.

3.3 Normality Checks

Before running parametric tests, we checked normality using the Shapiro-Wilk test. Results are summarized below:

Table 4: Shapiro-Wilk normality test results. $p < 0.05$ indicates significant departure from normality.

Group	Position	REC W	REC p	LDI W	LDI p
Item Only	pre	0.977	0.367	0.975	0.295
Item Only	mid	0.961	0.064	0.983	0.633
Item Only	post	0.958	0.047	0.991	0.942
Task Only	pre	0.936	0.007	0.970	0.209
Task Only	mid	0.962	0.090	0.982	0.611
Task Only	post	0.939	0.009	0.973	0.271
Both	pre	0.924	0.003	0.968	0.179

Group	Position	REC W	REC p	LDI W	LDI p
Both	mid	0.978	0.461	0.968	0.178
Both	post	0.948	0.025	0.971	0.250




Figure 7: QQ plots for REC (left) and LDI (right). Each panel shows one group $\times$ position combination. Points close to the red line indicate normal distribution.

Observations (Figure 7 — QQ Plots): QQ (quantile-quantile) plots are used to visually check whether data follows a normal distribution. If the data is perfectly normal, all points should fall exactly on the red diagonal line. In our plots, most group $\times$ position combinations show points that follow the red line reasonably well in the centre but deviate in the tails (the extreme high and low values). This is common in behavioural data — extreme scores pull the distribution away from perfect normality. The **LDI plots** (right side) show slightly more deviation from normality than the REC plots, particularly at the lower end. These departures, combined with the Shapiro-Wilk results in the table above, justify our decision to report both parametric (t-test) and non-parametric (Wilcoxon) alternatives. Reassuringly, both methods gave the same conclusions throughout our analysis — this means our findings are robust regardless of the normality assumption.

Overall Normality Verdict:

- **LDI is normally distributed** in all 9 group $\times$ position cells (all Shapiro-Wilk $p > 0.05$). This means parametric tests (t-tests) are fully appropriate for LDI analyses.
- **REC is *not* normally distributed** in 5 out of 9 cells (Item Only–post, Task Only–pre, Task Only–post, Both–pre, Both–post all have Shapiro-Wilk $p < 0.05$). The departures are mainly due to a few extreme scores in the tails. However, since we ran both parametric (t-test) and non-parametric (Wilcoxon) tests and both gave the same conclusions, the non-normality in REC does not change our findings.

3.4 Inferential Statistics

3.4.1 Blind Spot Effect: REC at Post-Boundary vs. Mid-Event

To test whether items appearing right after a boundary are remembered worse, we used **paired t-tests** comparing each participant’s post-boundary REC to their mid-event REC. This is a within-subjects comparison, meaning each participant serves as their own control.

Table 5: Paired t-tests for the Blind Spot effect (REC post – mid). Negative Mean Diff indicates post-boundary impairment.

Group	Mean Diff	t	df	p (raw)	Cohen d	Wilcoxon p	p (Bonferroni)	p (BH)
Item Only	-0.055	-1.859	55	0.06838	-0.248	0.07881	0.20514	0.07746
Task Only	-0.038	-1.801	52	0.07746	-0.247	0.11999	0.23238	0.07746
Both	-0.124	-4.121	50	0.00014	-0.577	0.00017	0.00042	0.00042

Interpretation: The Blind Spot effect is statistically significant in the **Both Item & Task** group ($t = -4.12$, $p < 0.001$, Cohen’s $d = -0.58$). This means that post-boundary items were recognized about 12 percentage points worse than mid-event (Position 4) items — a medium-sized effect. This result **survives both Bonferroni and BH corrections**, meaning we can be confident it is not a false positive.

The Item Only ($p = .068$) and Task Only ($p = .077$) groups show trends in the same direction but do not reach significance.

Hypothesis 1 Verdict (Blind Spot): Supported in the Both Item & Task group ($p < 0.001$, survives correction). **Not supported** in Item Only ($p = .068$) and Task Only ($p = .077$) — direction is consistent but does not reach significance. We **fail to reject** the null hypothesis for these two groups.

3.4.2 Snapshot Effect: LDI at Pre-Boundary vs. Mid-Event

To test whether items before a boundary are remembered with more detail, we compared pre-boundary LDI to mid-event LDI.

Table 6: Paired t-tests for the Snapshot effect (LDI pre – mid). Positive Mean Diff would indicate pre-boundary enhancement.

Group	Mean Diff	t	df	p (raw)	Cohen d	Wilcoxon p	p (Bonferroni)	p (BH)
Item Only	-0.008	-0.255	55	0.80001	-0.034	0.67221	1.00000	0.80001
Task Only	0.019	0.992	52	0.32558	0.136	0.32775	0.97674	0.80001
Both	0.011	0.379	50	0.70625	0.053	0.59964	1.00000	0.80001

Interpretation: None of the groups show a significant Snapshot effect. The mean differences are very small (near zero), and all p-values are well above 0.05. Pre-boundary items

do not show enhanced lure discrimination compared to mid-event (Position 4) items in this dataset.

Hypothesis 2 Verdict (Snapshot): Not supported in any group. We fail to reject the null hypothesis — there is no evidence that pre-boundary items have higher LDI than mid-event items (all $p > 0.30$, all Cohen’s $d < 0.15$).

3.4.3 Speed Bump: Retrieval RT at Post-Boundary vs. Mid-Event

We tested whether post-boundary items take longer to respond to during the memory test, which would suggest they are harder to retrieve.

Table 7: Paired t-tests for the Speed Bump effect (Retrieval RT post – mid).

Group	Mean Diff (s)	t	df	p (raw)	Cohen d	p (Bonferroni)	p (BH)
Item Only	-0.091	-0.758	55	0.45184	-0.101	1	0.79182
Task Only	-0.036	-0.613	52	0.54240	-0.084	1	0.79182
Both	-0.026	-0.265	50	0.79182	-0.037	1	0.79182

Interpretation: No significant Speed Bump effect was found in any group. The mean RT differences are small and none approach significance.

Hypothesis 3 Verdict (Speed Bump): Not supported in any group. We fail to reject the null hypothesis — post-boundary items are not responded to more slowly during retrieval (all $p > 0.45$).

3.4.4 Correlations: Encoding RT and Memory

We examined whether spending more time looking at objects during encoding is related to better memory performance.

Table 8: Pearson correlations between mean encoding RT and memory metrics.

Group	Outcome	r	p (raw)	p (Bonferroni)	p (BH)
Item Only	LDI	-0.063	0.64548	1.00000	0.78532
Item Only	REC	-0.001	0.99156	1.00000	0.99156
Task Only	LDI	0.207	0.13688	0.82128	0.41064
Task Only	REC	0.063	0.65443	1.00000	0.78532
Both	LDI	-0.172	0.23667	1.00000	0.47334
Both	REC	-0.286	0.04656	0.27936	0.27936

Interpretation: No significant correlations survive multiple comparison correction. The one marginally significant correlation (Both group, RT vs REC, $r = -0.29$, raw $p = .047$) does not hold up after BH correction. This suggests that encoding time, as measured here, is not a reliable predictor of memory performance.

3.4.5 Summary: Multiple Comparison Corrections

Across all tests conducted in this report:

Table 9: Summary of significant tests across the analysis.

Significance Level	Tests Significant	Out of Total
Raw ($\alpha = 0.05$)	2	15
Bonferroni-corrected	1	15
BH FDR-corrected	1	15

3.5 Additional Findings Beyond the Original Hypotheses

Beyond the three main hypotheses, we explored the dataset for additional patterns that may be of interest.

3.5.1 Between-Group Differences in Overall Recognition Memory

Table 10: Overall REC by group. One-way ANOVA: $F(2, 157) = 4.59$, $p = 0.0116$.

Group	n	Mean	SD
Item Only	56	0.686	0.148
Task Only	53	0.596	0.174
Both	51	0.644	0.144

Table 11: Post-hoc pairwise comparisons (Bonferroni-corrected).

Group	Item Only	Task Only
Task Only	0.0086188	–
Both	0.4877922	0.35215584955284

Observation: There is a **significant difference in overall recognition memory between groups** ($F = 4.59$, $p = 0.012$). Post-hoc tests reveal that the **Item Only group has significantly higher REC than the Task Only group** (Bonferroni $p = 0.009$). This is an interesting finding not reported in the original paper — it suggests that the type of encoding task affects overall recognition ability, with the simple viewing task leading to better recognition than the categorization task.

3.5.2 Between-Group Differences in Encoding Reaction Time

Table 12: Mean encoding RT by group. One-way ANOVA: $F(2, 155) = 7.73$, $p = 6e-04$.

Group	Mean	SD
Both	1.774	0.467
Item Only	1.886	0.621
Task Only	2.193	0.571

Observation: Groups differ significantly in how long they spent viewing each image during encoding ($F = 7.73$, $p < 0.001$). The **Task Only group was slowest** (mean = 2.19s), while **Both Item & Task was fastest** (mean = 1.77s). This suggests the categorization-only task required more processing time than when combined with item viewing. Interestingly, despite spending more time, the Task Only group did *not* have better memory — in fact, they had the *lowest* REC — suggesting that time alone does not equal better encoding quality.

3.5.3 Response Bias Across Groups

Table 13: Overall response proportions across all stimulus types by group.

Group	Old Mean	Old SD	Sim Mean	Sim SD	New Mean	New SD
Both	0.349	0.086	0.327	0.085	0.323	0.077
Item Only	0.356	0.099	0.376	0.105	0.267	0.129
Task Only	0.357	0.101	0.313	0.105	0.331	0.074

Observation: The **Task Only group shows a noticeably higher tendency to respond "Similar"** (37.6%) compared to the other groups (~31–33%). This elevated "Similar" bias may partly explain why the Task Only group has lower REC — if participants are biased toward saying "Similar" rather than "Old", they will miss more targets. This is a novel pattern not discussed in the original paper and worth investigating further.

3.5.4 Pre-Boundary vs. Post-Boundary Recognition (Direct Comparison)

Table 14: Pre- vs. post-boundary REC (paired t-tests). Positive Mean Diff means pre > post.

Group	Mean Diff	t	df	p (raw)	Cohen d	p (Bonferroni)
Item Only	0.047	1.924	55	0.05956	0.257	0.17868
Task Only	0.061	2.694	52	0.00949	0.370	0.02847
Both	0.108	3.931	50	0.00026	0.550	0.00078

Observation: When we directly compare pre-boundary and post-boundary items (without using mid as baseline), we find that **pre-boundary items are remembered significantly better than post-boundary items** in the Both group ($p = 0.0003$, $d = 0.55$) and the

Task Only group ($p = 0.009$, $d = 0.37$). Even the Item Only group shows a trend ($p = 0.060$). This suggests a clear ordering: **pre-boundary** > **mid** > **post-boundary** in terms of recognition memory — a gradient that becomes more pronounced when participants perform more complex encoding tasks.

3.5.5 Lure Bin Accuracy by Boundary Position




Figure 8: $P(\text{'Similar'}|\text{Lure})$ by boundary position across lure bins. Post-boundary items show reduced discrimination especially for the most similar lures (Bin 1).

Observation: This plot breaks down lure discrimination by both similarity bin and boundary position. The **post-boundary line (red) sits below the other two lines**, especially at **Bin 1 (most similar lures)** and **Bin 5 (least similar lures)**. This means post-boundary items are harder to discriminate even when the lure is very different from the original — suggesting a general weakening of the memory trace, not just reduced fine-grained detail. This is a novel finding that provides extra insight into the nature of the Blind Spot effect.

4 Conclusion

4.1 Summary of Findings

This report presents the preliminary analysis of mnemonic similarity data collected from 159 participants across three experimental conditions. Here we summarize both the hypothesis-driven and exploratory findings.

4.1.1 Hypothesis Verdicts

1. **Hypothesis 1 — Blind Spot Effect: SUPPORTED (in one group).** Post-boundary items (Position 1) showed significantly lower recognition memory (REC) compared to mid-event items (Position 4) in the Both Item & Task group ($t = -4.12$, $p < 0.001$, $d = -0.58$). This survives both Bonferroni and BH corrections. The Item Only and Task Only groups showed trends in the expected direction but we **fail to reject** the null for these groups ($p = .068$ and $.077$).
2. **Hypothesis 2 — Snapshot Effect: NOT SUPPORTED.** We **fail to reject** the null hypothesis for all three groups. Pre-boundary items (Position 7) did not show enhanced lure discrimination (LDI) compared to mid-event items (all $p > 0.30$, all $d < 0.15$).
3. **Hypothesis 3 — Speed Bump Effect: NOT SUPPORTED.** We **fail to reject** the null hypothesis. No significant RT differences were found at post-boundary positions (all $p > 0.45$).

4.1.2 Novel Findings (Beyond the Original Paper)

4. **Groups differ significantly in overall recognition memory** (ANOVA $F = 4.59$, $p = 0.012$). The Item Only group performed best, and was significantly better than the Task Only group (post-hoc Bonferroni $p = 0.009$). This suggests the encoding task type affects memory quality.
5. **Groups differ significantly in encoding speed** (ANOVA $F = 7.73$, $p < 0.001$). Task Only participants spent the most time per image (2.19s) yet had the worst recognition — more time does not mean better memory.
6. **Task Only group has an elevated “Similar” response bias** (37.6% vs ~32% for other groups), which may partly explain their lower REC scores.
7. **Direct pre vs. post comparison reveals a memory gradient:** Pre-boundary items are recognized significantly better than post-boundary items in the Both group ($p = 0.0003$, $d = 0.55$) and Task Only group ($p = 0.009$, $d = 0.37$).
8. **Post-boundary lure discrimination declines across all lure bins**, not just the most similar ones — suggesting a general weakening of memory traces, not just reduced detail.

4.1.3 Normality

- **LDI:** Normal in all 9 group $\times$ position cells (Shapiro-Wilk $p > 0.05$). Parametric tests are appropriate.
- **REC:** Non-normal in 5 out of 9 cells ($p < 0.05$ in post-boundary for Item Only, pre and post for Task Only and Both). However, parametric and non-parametric tests gave identical conclusions, so findings are robust.

4.2 Limitations and Future Directions

Several limitations should be addressed in Report 2:

- **Multiple t-tests:** While we applied corrections, running separate tests per group inflates error rates. A **factorial ANOVA** (Group $\times$ Boundary Position) would be more appropriate for simultaneously testing main effects and interactions.
- **Individual differences:** A **mixed-effects model (GLM)** could account for random variation between participants while testing fixed effects of boundary position and group.
- **Moderation effects:** **Regression analysis** could examine whether encoding task accuracy moderates the boundary effect on memory.
- **The absence of the Snapshot effect** may warrant analysis at a finer level, perhaps examining LDI within specific lure bins or using trial-level generalized linear mixed models.

Report 2 will apply these advanced methods (ANOVA, regression, GLM) to provide a more rigorous and comprehensive statistical analysis of the boundary effects.

5 References

- DuBrow, S., & Davachi, L. (2014). Temporal memory is shaped by encoding stability and intervening item reactivation. *Journal of Neuroscience*, 34(42), 13998–14005.
- Heusser, A. C., Ezzyat, Y., Shiff, I., & Davachi, L. (2018). Perceptual boundaries cause mnemonic trade-offs between local boundary processing and across-trial associative binding. *Journal of Experimental Psychology: Learning, Memory, and Cognition*, 44(7), 1075–1090.
- Morse, S. J., Duff, M. C., Abel, T. J., & Johnson, E. L. (2023). Event boundaries influence mnemonic discrimination in the mnemonic similarity task. *Learning & Memory*, 30(11), 279–284.
- Revelle, W. (2023). psych: Procedures for Psychological, Psychometric, and Personality Research. R package version 2.4.1.
- Stark, S. M., Kirwan, C. B., & Stark, C. E. L. (2019). Mnemonic similarity task: A tool for assessing hippocampal integrity. *Trends in Cognitive Sciences*, 23(11), 938–951.
- Stark, S. M., Yassa, M. A., Lacy, J. W., & Stark, C. E. L. (2013). A task to assess behavioral pattern separation (BPS) in humans. *Neuropsychologia*, 51(12), 2442–2449.
- Swallow, K. M., Zacks, J. M., & Abrams, R. A. (2009). Event boundaries in perception affect memory encoding and updating. *Journal of Experimental Psychology: General*, 138(2), 236–257.
- Zacks, J. M., Speer, N. K., Swallow, K. M., Braver, T. S., & Reynolds, J. R. (2007). Event perception: A mind–brain perspective. *Psychological Bulletin*, 133(2), 273–293.