Crompton Greaves Consumer Electricals Limited, Appliances Division Equinox Business Park, Tower-3, 1st Floor,

LBS Marg, Kurla(W), Mumbai - 400070

Technical Data Sheet

Model:	SOL QUBE PLUS 25L	Date:	23 10 2020
SKU:	ASWH 3225	Document No	TDS-CA-SWH-048.00

Issued By	DESIGN
Issued To	Sourcing I Quality

INDEX

Revision No	Description	Date
00	First Release	23 nov 2020
01		
02		
03		

Prepared By: SACHIDANAND	Checked By: SACHIDANAND	Approved By: ANOOP
This document is only for internal cir	Documents: DD/FR/03	
Note: Please confirm the latest version of the document with design team		Rev No: 00, Date :01-07-2019

Crompton Greaves Consumer Electricals Limited, Appliances Division Equinox Business Park, Tower-3, 1st Floor,

LBS Marg, Kurla(W), Mumbai - 400070

Technical Data Sheet			
Model:	SOL QUBE PLUS 25L	Date:	23 10 2020
SKU:	ASWH 3225	Document No	TDS-CA-SWH-048.00

PRODUCT CATEGORY	STORAGE WATER HEATER
MODEL NO	ASWH 3225
MODEL NAME	Solarium Qube Plus
MANUFACTURER	Onkar, Noida
PRODUCT PHOTO	Offical, Noida
EAN CODE	8902653269655
DATE	0902033209033
REVISION	
Performance Details	
Rated Capacity	25 L
Real Capacity BEE Star Rating	5 Star
3. Standing Loss (kWh / 24 Hr / 45C difference)	≤ 0.511
4. Hot Water Output	42°C Minimum
<u> </u>	45 Minutes
5. Reheating Time (Maximum)	
6. Mixing Factor	35 % Maximum
7. Deviation of Dial Calibration	10°C Maximum 10°C Maximum
8. Cyclic Temperature Variation	
9. Finish	OK Qualified
Critical Components	
Multifunctional Safety Valve	0.0.005.14
Max Release Pressure	0.8 ± 0.05 Mpa
Inlet Pressure	≤ 0.01 Mpa
NRV Pressure	0.30 ± 0.05 Mpa
MFV Material	Brass
Finish	Zn Coated
Size	1/2' BSP
Internal Metal Tauls	
Internal Metal Tank	05.1
Rated Capacity	25 L
Bare Capacity	25.5 L Minimum
Mounting Capacity * (minimum)	25.2 L Minimum
Tank Material	MS
RM Thickness	1.2 MM
Tank Coating	Polymer
Average Coating Thickness *	250 - 400 Microns
Pressure Plate	
Material	MS
Thickness	1.8 mm
Finish	Zn Pasivation
Heating Element	
Wattage *	2000 W (+5%, -10%)
Shape	J Bend
Material	Copper
Finish	Ni Coated
Prepared By: SACHIDANAND Checked By: SACHID	DANIAND Approved By: ANOOP

Note: Please confirm the latest version of the document with design team		Rev No: 00, Date :01-07-2019
This document is only for internal circulation.		Documents: DD/FR/03
Prepared By: SACHIDANAND	Checked By: SACHIDANAND	Approved By: ANOOP

Crompton Greaves Consumer Electricals Limited, Appliances Division Equinox Business Park, Tower-3, 1st Floor,

LBS Marg, Kurla(W), Mumbai - 400070

Technical Data Sheet			
Model:	SOL QUBE PLUS 25L	Date:	23 10 2020
SKU:	ASWH 3225	Document No	TDS-CA-SWH-048.00

1200 Grammage 36 Inch 9 mm SS 1.5 mm SS 450 gms (± 10) Silicon 14 gms (± 2) Electronic Temp Control	
SS 1.5 mm SS 450 gms (± 10) Silicon 14 gms (± 2)	
1.5 mm SS 450 gms (± 10) Silicon 14 gms (± 2)	
SS 450 gms (± 10) Silicon 14 gms (± 2)	
SS 450 gms (± 10) Silicon 14 gms (± 2)	
450 gms (± 10) Silicon 14 gms (± 2)	
Silicon 14 gms (± 2)	
14 gms (± 2)	
14 gms (± 2)	
Electronic Temp Control	
Electronic Temp Control	
Electronic Temp Control	
NA	
NA	
NA	
NA	
25 - 75 C	
Stem Type	
7 Inch	
20A, 240V, AC	
Brass	
Brass	
84 - 96 C	
Yes	
16 A, 230V, AC, ISI Marked	
Yes	
1 MTR Minimum	
PVC	
Copper	
1 sq mm, 32/0.2	
Brass	
Yes	
1.00	
SS 304 Wire Braid	
EPDM	
10 Bar	
120 C	
1/2 Inch BSP, Brass	
Yes	

Note: Please confirm the latest version of the document with design team		Rev No: 00, Date :01-07-2019
This document is only for internal circulation.		Documents: DD/FR/03
Prepared By: SACHIDANAND	Checked By: SACHIDANAND	Approved By: ANOOP

Crompton Greaves Consumer Electricals Limited, Appliances Division

Equinox Business Park, Tower-3, 1st Floor, LBS Marg, Kurla(W), Mumbai - 400070

Technical Data Sheet Model: SOL QUBE PLUS 25L Date: 23 10 2020 SKU: ASWH 3225 Document No TDS-CA-SWH-048.00

Length	18 inch
Wire Harness (Main)	
Rating	6A, 230V , AC
Cross Section	32/0.2, 1 sq mm , & 16/0.2 ,0.5 Sq mm
FR Garde	YES
Connectors	Brass
Connectors Heat Shrink Sleeve	Yes
Packaging	
Ply	5 Ply
BS (Kg/cm2	10 - 12 BS
Box	Color
Lamination	Yes

^{*} Items are CTQ

	Digital Temp Display PCB		
SNO	Particulars	Parameters	
1	Temp Range of Display	25 C- 75 C	
2	Temp Adjustment Sensor "+" "-"	1C Change in single touch	
3	Set Temp Vs Current Temp Display	Set Temp should blink 2 times in every 30 seconds	
4	Temp Accuracy	± 3C	
5	LED Glow Color	Blue in ON , Orange OFF , Thermostat Condition	
6	Max Set Temp	75C	
7	Min Set Temp	25C	
8	Error Code	NO Error Codes	
9	Memory Backup	Yes	

Prepared By: SACHIDANAND Checked By: SACHIDANAND		Approved By: ANOOP	
This document is only for internal circulation.		Documents: DD/FR/03	
Note: Please confirm the latest version of the document with design team		Rev No: 00, Date :01-07-2019	

Crompton Greaves Consumer Electricals Limited, Appliances Division Equinox Business Park, Tower-3, 1st Floor,

LBS Marg, Kurla(W), Mumbai - 400070

Technical Data Sheet

Model:	SOL QUBE PLUS 25L	Date:	23 10 2020
SKU:	ASWH 3225	Document No	TDS-CA-SWH-048.00

Prepared By: SACHIDANAND	Checked By: SACHIDANAND	Approved By: ANOOP
This document is only for internal circulation.		Documents: DD/FR/03
Note: Please confirm the latest version of the document with design team		Rev No: 00, Date :01-07-2019