

```
#include <stdio.h>
```

```
int main() {
```

```
int n;
```

```
scanf("%d", &n);
```

```
int roll[1000];
```

```
for (int i = 0; i < n; i++) scanf("%d", &roll[i]);
```

```
int x;
```

```
scanf("%d", &x);
```

```
int found = 0;
```

```
for (int i = 0; i < n; i++) {
```

```
if (roll[i] == x) {
```

```
printf("Found at index %d\n", i);
```

```
found = 1;
```

```
break;
```

```
}
```

```
}
```

```
if (found == 0) printf("Not Found\n");
```

```
return 0;
```

```
#include <stdio.h>
```

```
int main() {
```

```
int n;
```

```
scanf("%d", &n);
```

```
int id[1000000];
```

```
for (int i = 0; i < n; i++) scanf("%d", &id[i]);
```

```
int target;
```

```
scanf("%d", &target);
```

```
int low = 0, high = n - 1;
```

```
int found = 0;
```

```
while (low <= high) {
```

```
int mid = (low + high) / 2;
```

```
if (id[mid] == target) {
```

```
found = 1;
```

```
break;
```

```
} else if (id[mid] < target) {
```

```
low = mid + 1;
```

```
} else {
```

```
high = mid - 1;
```

```
}
```

```
}
```

```
if (found == 1) printf("Product Available\n");
```

```
else printf("Product Not Available\n");
```

```
return 0;
```

```
}
```

```
#include <stdio.h>
```

```
int main() {
```

```
int n;
```

```
scanf("%d", &n);
```

```
int score[1000];
```

```
for (int i = 0; i < n; i++) scanf("%d", &score[i]);
```

```
for (int i = 0; i < n - 1; i++) {
```

```
for (int j = 0; j < n - 1 - i; j++) {
```

```
if (score[j] > score[j + 1]) {
```

```
int temp = score[j];
```

```
score[j] = score[j + 1];
```

```
score[j + 1] = temp;
```

```
}
```

```
}
```

```
}
```

```
for (int i = 0; i < n; i++) printf("%d ", score[i]);
```

```
printf("\n");
```

```
return 0;
```

```
}
```

```
#include <stdio.h>
```

```
int main() {
```

```
int n;
```

```
scanf("%d", &n);
```

```
int book[1000];
```

```
for (int i = 0; i < n; i++) scanf("%d", &book[i]);
```

```
for (int i = 1; i < n; i++) {
```

```
int key = book[i];
```

```
int j = i - 1;
```

```
while (j >= 0 && book[j] > key) {
```

```
book[j + 1] = book[j];
```

```
j--;
```

```
}
```

```
book[j + 1] = key;
```

```
}
```

```
for (int i = 0; i < n; i++) printf("%d ", book[i]);
```

```
printf("\n");
```

```
return 0;
```



```
#include <stdio.h>
```

```
int main() {
```

```
int n;
```

```
scanf("%d", &n);
```

```
int score[1000];
```

```
for (int i = 0; i < n; i++) scanf("%d", &score[i]);
```

```
for (int i = 0; i < n - 1; i++) {
```

```
int minIndex = i;
```

```
for (int j = i + 1; j < n; j++) {
```

```
if (score[j] < score[minIndex]) {
```

```
minIndex = j;
```

```
}
```

```
}
```

```
int temp = score[minIndex];
```

```
score[minIndex] = score[i];
```

```
score[i] = temp;
```

```
}
```

```
for (int i = 0; i < n; i++) printf("%d ", score[i]);
```

```
printf("\n");
```

```
return 0;
```

```
}
```