Analysis of the performance of min sum decode algorithm in Gaussian channel for random matrices

Anurag Gupta
Microelectronics (2015-17)
Instructor: Prof Madhay P. Desai

IIT-Bombay
Department of Electrical Engineering



Notations



- n Block size.
- Eb/No Input SNR in db to maintain input BER between 10^{-2} to 10^{-3} .
- BER(IN) Input bit error rate.
- BER(OUT) Output bit error rate.
- CDB Number of correctly decoded blocks.
- Itr Average number of iterations per block.

Min Sum Decode (Rate=0.75)



n	BER(In)	Eb/No(db)	BER(OUT)	CDB	ltr(/150)
4096	1.0×10^{-2}	5.5	0	100	2
	4.8×10^{-3}	6.5	0	100	1
	1.8×10^{-3}	7.5	0	100	1
8192	1.0×10^{-2}	5.5	0	100	2
	4.8×10^{-3}	6.5	0	100	1
	1.8×10^{-3}	7.5	0	100	1
12288	$1.0x10^{-2}$	5.5	0	100	2
	4.8×10^{-3}	6.5	0	100	1
	1.8×10^{-3}	7.5	0	100	1
16384	$1.0x10^{-2}$	5.5	0	100	2
	4.8×10^{-3}	6.5	0	100	1
	1.8×10^{-3}	7.5	0	100	1

Min Sum Decode (Rate=0.8)



n	BER(In)	Eb/No(db)	BER	CDB	ltr(/150)
4096	0.8×10^{-2}	5.5	0	100	2
	3.8×10^{-3}	6.5	0	100	1
	1.5×10^{-3}	7.5	0	100	1
8192	0.8×10^{-2}	5.5	0	100	2
	3.8×10^{-3}	6.5	0	100	1
	1.5×10^{-3}	7.5	0	100	1
12288	0.8×10^{-2}	5.5	0	100	2
	3.8×10^{-3}	6.5	0	100	1
	1.5×10^{-3}	7.5	0	100	1
16384	0.8×10^{-2}	5.5	0	100	2
	3.8×10^{-3}	6.5	0	100	1
	1.5×10^{-3}	7.5	0	100	1

Min Sum Decode (Rate=0.85)



n	BER(IN)	Eb/No(db)	BER	CDB	ltr(/150)
4096	1.0×10^{-2}	5	0	100	3
	4.5×10^{-3}	6	0	100	2
	1.7×10^{-3}	7	0	100	1
8192	$1.0x10^{-2}$	5	0	100	3
	4.5×10^{-3}	6	0	100	2
	1.7×10^{-3}	7	0	100	1
12288	$1.0x10^{-2}$	5	0	100	3
	4.5×10^{-3}	6	0	100	2
	1.7×10^{-3}	7	0	100	1
16384	$1.0x10^{-2}$	5	0	100	3
	4.5×10^{-3}	6	0	100	2
	1.7×10^{-3}	7	0	100	1

Min Sum Decode (Rate=0.9)



n	BER(IN)	Eb/No(db)	BER	CDB	ltr(/150)
4096	0.9×10^{-2}	5	0	100	3
	3.6×10^{-3}	6	0	100	2
	$1.3x10^{-3}$	7	0	100	1
8192	0.9×10^{-2}	5	0	100	3
	3.6×10^{-3}	6	0	100	2
	$1.3x10^{-3}$	7	0	100	1
12288	0.9×10^{-2}	5	0	100	4
	3.6×10^{-3}	6	0	100	2
	$1.3x10^{-3}$	7	0	100	1
16384	0.9×10^{-2}	5	0	100	4
	3.6×10^{-3}	6	0	100	2
	1.3×10^{-3}	7	0	100	1

Min Sum Decode (Rate=0.95)



n	Eb/No(db)	BER	CDB	ltr(/150)
4096	-	-	-	-
8192	-	-	-	-
12288	4.5	0.0075	0	-
	5.5	0	100	4
	6.5	0	100	2
16384	4.5	0.0072	0	-
	5.5	0	100	4
	6.5	0	100	2

■ n = 4096 and 8192 cycle free random matrix was not able to generate.

Min Sum Decode

First error till 10 million blocks



n≃	BER(In)≃	R=0.75	R=0.8
4K	$1.0x10^{-2}$	1.2799×10 ⁴	2.0754×10 ⁴
	0.5×10^{-3}	5.53727×10^5	1.72781×10^5
	1.0×10^{-3}	-	6.24436×10^5
8K	1.0×10^{-2}	1.92476×10 ⁵	8.3898×10 ⁴
	0.5×10^{-3}	3.21027×10^5	4.6092×10^4
	1.0×10^{-3}	-	-
12K	$1.0x10^{-2}$	2.20022×10^5	1.57371×10^5
	0.5×10^{-3}	2.17452×10^5	9.0158×10^4
	1.0×10^{-3}	-	-

First error till 10 million blocks



$n{\simeq}$	BER(In)≃	R=0.85	R=0.9	R=0.95
4K	1.0×10^{-2}	3.39×10^2	1.259×10^3	NA
	0.5×10^{-3}	6.6700×10^4	1.65511×10^5	NA
	1.0×10^{-3}	345503×10^5	1.19008×10^5	NA
8K	1.0×10^{-2}	5.193×10^3	5.947×10^3	NA
	0.5×10^{-3}	3.7952×10^4	1.1389×10^4	NA
	1.0×10^{-3}	-	_	NA
12K	1.0×10^{-2}	1.2894×10^4	1.2626×10 ⁴	1.1
	0.5×10^{-3}	1.56487×10^5	5.4866×10 ⁴	1.034×10^4
	$1.0x10^{-3}$			1.4759×10^4