

ConnectSphere Auth Service - Line-by-Line Explanation

This document walks through the auth-service source line by line. Every listed source, configuration, documentation, and test file is explained in the same order that it appears in the project.

Generated from actual source files.

File count: 2

Generated at: 2026-04-18 00:34:17

Glossary and Definitions

This section defines some of the important Java and Spring words used throughout the auth-service code. If you meant Java

Principal

when you wrote "principle", that definition is included here too.

Term	Definition and why it matters here
Record	A Java type designed mainly for holding data. We use records for DTOs because they remove boilerplate constructors, getters, equality, and toString code.
Principal	The currently authenticated identity attached to the request. In this service, Principal normally holds the logged-in user's email after the JWT filter authenticates the request.
DTO	Data Transfer Object. A small object used to receive input from the client or return output to the client without exposing internal entities directly.
Entity	A class mapped to a database table through JPA annotations. Entities represent persisted business data.
Repository	The data-access layer. Repositories read and write entities from the database so service classes do not have to write SQL manually.
Service	The business-logic layer. Services connect controllers, repositories, hashing, validation, tokens, and workflow rules.
Controller	The HTTP layer. Controllers receive requests, call the service layer, and send responses back to the client.
JWT	JSON Web Token. A signed token that carries identity and authorization data so the system can authenticate requests without server-side sessions.

Term	Definition and why it matters here
AuthenticationManager	A Spring Security component that verifies login credentials by delegating to configured authentication providers.
PasswordEncoder	A Spring Security abstraction used to hash passwords safely and compare raw passwords against stored hashes.
Filter	A component that runs before the controller on each request. The JWT filter checks the Authorization header and builds the authenticated security context.
JPA	Java Persistence API. It lets Java classes map to relational tables using annotations and repositories.
Stateless	A style where the server does not keep session state for each client. Here, auth state is carried by JWT tokens instead of HTTP session objects.
OAuth	A standard for logging in through another provider like Google or GitHub. This auth service has the configuration base for that future flow.
Enum	A type that restricts values to a fixed list, such as USER/ADMIN or LOCAL/GOOGLE/GITHUB.
Interface	A contract that says what methods a type must provide, without storing state or implementation details.

Why Access Token and Refresh Token Are Needed

The auth service uses two tokens because one token alone would force a bad tradeoff between security and user experience. An **access token** is the token sent with normal API requests. It proves who the user is and what role they have. It should not live forever, because if somebody steals it they could call protected endpoints as that user until it expires.

A **refresh token** exists so the client can ask for a brand new access token without forcing the user to type their email and password again. This means the access token can stay shorter-lived for safety, while the refresh token keeps the login session practical for real use.

Token Type	Why it exists	How it is used in this auth service
Access Token	Used as the main working token on protected requests. We need it so every normal API call can be authenticated quickly without querying a server-side session store.	Sent in the Authorization: Bearer ... header. Checked by JwtAuthenticationFilter . In this project it is configured to last 24 hours .

Token Type	Why it exists	How it is used in this auth service
Refresh Token	Used as the renewal token. We need it so users can stay signed in and receive a new access token after expiry without entering their password again.	Sent only to /auth/refresh . Checked by JwtTokenService.isRefreshTokenUsable(...) . In this project it is configured to last 7 days .

If the system had **only a long-lived access token**, it would be convenient but risky, because a stolen token would stay useful for too long. If the system had **only a short-lived access token** and no refresh token, security would be stronger but users would need to log in again and again.

Using both tokens solves both problems:

- Access token gives fast authentication for normal requests.
- Refresh token gives a safe way to renew access when the access token expires.
- The access token can be shorter-lived.
- The user does not have to repeatedly type credentials.

This auth service also revokes refresh tokens during rotation. That means when the client uses a refresh token successfully, the old refresh token is revoked and a new token pair is created. We need this so token reuse becomes harder after leakage or theft.

Login

-> server returns access token + refresh token

Normal protected API call

-> client sends access token
 -> JWT filter validates it
 -> request continues

Access token expires

-> protected request can no longer use it

Refresh flow

-> client sends refresh token to /auth/refresh
 -> service validates refresh token
 -> service revokes old refresh token
 -> service returns new access token + new refresh token

pom.xml

Why this file exists: Defines the Maven build, Java version, and all dependencies the auth service needs to compile, run, test, and create JWT-secured Spring Boot behavior.

Line count: 97

Line	Code	Explanation
1	<code><?xml version="1.0" encoding="UTF-8"?></code>	Declares the XML version and encoding used by this Maven file.
2	<code><project xmlns="http://maven.apache.org/POM/4.0.0"</code>	Opens the XML element <code>\$(System.Collections.Hashtable[1])</code> , which defines part of the Maven build configuration.
3	<code>xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"</code>	This line forms part of the Maven XML configuration.
4	<code>xsi:schemaLocation="http://maven.apache.org/POM/4.0.0 https://maven.apache.org/xsd/maven-4.0.0.xsd"></code>	This line forms part of the Maven XML configuration.
5	<code><modelVersion>4.0.0</modelVersion></code>	Opens the XML element <code>\$(System.Collections.Hashtable[1])</code> , which defines part of the Maven build configuration.
6		Blank line used to separate XML sections.
7	<code><parent></code>	Opens the XML element <code>\$(System.Collections.Hashtable[1])</code> , which defines part of the Maven build configuration.
8	<code><groupId>org.springframework.boot</groupId></code>	Opens the XML element <code>\$(System.Collections.Hashtable[1])</code> , which defines part of the Maven build configuration.
9	<code><artifactId>spring-boot-starter-parent</artifactId></code>	Opens the XML element <code>\$(System.Collections.Hashtable[1])</code> , which defines part of the Maven build configuration.
10	<code><version>3.3.5</version></code>	Opens the XML element <code>\$(System.Collections.Hashtable[1])</code> , which defines part of the Maven build configuration.
11	<code><relativePath/></code>	This line forms part of the Maven XML configuration.
12	<code></parent></code>	Closes the XML element <code>\$(System.Collections.Hashtable[1])</code> .
13		Blank line used to separate XML sections.
14	<code><groupId>com.connectsphere</groupId></code>	Opens the XML element <code>\$(System.Collections.Hashtable[1])</code> , which defines part of the Maven build configuration.
15	<code><artifactId>auth-service</artifactId></code>	Opens the XML element <code>\$(System.Collections.Hashtable[1])</code> , which defines part of the Maven build configuration.
16	<code><version>0.0.1-SNAPSHOT</version></code>	Opens the XML element <code>\$(System.Collections.Hashtable[1])</code> , which defines part of the Maven build configuration.
17	<code><name>auth-service</name></code>	Opens the XML element <code>\$(System.Collections.Hashtable[1])</code> , which defines part of the Maven build configuration.

Line	Code	Explanation
18	<code><description>ConnectSphere auth and user management service</description></code>	Opens the XML element <code>\$(System.Collections.Hashtable[1])</code> , which defines part of the Maven build configuration.
19		Blank line used to separate XML sections.
20	<code><properties></code>	Opens the XML element <code>\$(System.Collections.Hashtable[1])</code> , which defines part of the Maven build configuration.
21	<code><java.version>17</java.version></code>	This line forms part of the Maven XML configuration.
22	<code><jjwt.version>0.12.6</jjwt.version></code>	This line forms part of the Maven XML configuration.
23	<code></properties></code>	Closes the XML element <code>\$(System.Collections.Hashtable[1])</code> .
24		Blank line used to separate XML sections.
25	<code><dependencies></code>	Opens the XML element <code>\$(System.Collections.Hashtable[1])</code> , which defines part of the Maven build configuration.
26	<code><dependency></code>	Opens the XML element <code>\$(System.Collections.Hashtable[1])</code> , which defines part of the Maven build configuration.
27	<code><groupId>org.springframework.boot</groupId></code>	Opens the XML element <code>\$(System.Collections.Hashtable[1])</code> , which defines part of the Maven build configuration.
28	<code><artifactId>spring-boot-starter-web</artifactId></code>	Opens the XML element <code>\$(System.Collections.Hashtable[1])</code> , which defines part of the Maven build configuration.
29	<code></dependency></code>	Closes the XML element <code>\$(System.Collections.Hashtable[1])</code> .
30	<code><dependency></code>	Opens the XML element <code>\$(System.Collections.Hashtable[1])</code> , which defines part of the Maven build configuration.
31	<code><groupId>org.springframework.boot</groupId></code>	Opens the XML element <code>\$(System.Collections.Hashtable[1])</code> , which defines part of the Maven build configuration.
32	<code><artifactId>spring-boot-starter-validation</artifactId></code>	Opens the XML element <code>\$(System.Collections.Hashtable[1])</code> , which defines part of the Maven build configuration.
33	<code></dependency></code>	Closes the XML element <code>\$(System.Collections.Hashtable[1])</code> .
34	<code><dependency></code>	Opens the XML element <code>\$(System.Collections.Hashtable[1])</code> , which defines part of the Maven build configuration.
35	<code><groupId>org.springframework.boot</groupId></code>	Opens the XML element <code>\$(System.Collections.Hashtable[1])</code> , which defines part of the Maven build configuration.

Line	Code	Explanation
36	<code><artifactId>spring-boot-starter-data-jpa</artifactId></code>	Opens the XML element <code>\$(System.Collections.Hashtable[1])</code> , which defines part of the Maven build configuration.
37	<code></dependency></code>	Closes the XML element <code>\$(System.Collections.Hashtable[1])</code> .
38	<code><dependency></code>	Opens the XML element <code>\$(System.Collections.Hashtable[1])</code> , which defines part of the Maven build configuration.
39	<code><groupId>org.springframework.boot</groupId></code>	Opens the XML element <code>\$(System.Collections.Hashtable[1])</code> , which defines part of the Maven build configuration.
40	<code><artifactId>spring-boot-starter-security</artifactId></code>	Opens the XML element <code>\$(System.Collections.Hashtable[1])</code> , which defines part of the Maven build configuration.
41	<code></dependency></code>	Closes the XML element <code>\$(System.Collections.Hashtable[1])</code> .
42	<code><dependency></code>	Opens the XML element <code>\$(System.Collections.Hashtable[1])</code> , which defines part of the Maven build configuration.
43	<code><groupId>org.springframework.boot</groupId></code>	Opens the XML element <code>\$(System.Collections.Hashtable[1])</code> , which defines part of the Maven build configuration.
44	<code><artifactId>spring-boot-starter-oauth2-client</artifactId></code>	Opens the XML element <code>\$(System.Collections.Hashtable[1])</code> , which defines part of the Maven build configuration.
45	<code></dependency></code>	Closes the XML element <code>\$(System.Collections.Hashtable[1])</code> .
46	<code><dependency></code>	Opens the XML element <code>\$(System.Collections.Hashtable[1])</code> , which defines part of the Maven build configuration.
47	<code><groupId>org.springframework.boot</groupId></code>	Opens the XML element <code>\$(System.Collections.Hashtable[1])</code> , which defines part of the Maven build configuration.
48	<code><artifactId>spring-boot-starter-actuator</artifactId></code>	Opens the XML element <code>\$(System.Collections.Hashtable[1])</code> , which defines part of the Maven build configuration.
49	<code></dependency></code>	Closes the XML element <code>\$(System.Collections.Hashtable[1])</code> .
50	<code><dependency></code>	Opens the XML element <code>\$(System.Collections.Hashtable[1])</code> , which defines part of the Maven build configuration.
51	<code><groupId>com.h2database</groupId></code>	Opens the XML element <code>\$(System.Collections.Hashtable[1])</code> , which defines part of the Maven build configuration.
52	<code><artifactId>h2</artifactId></code>	Opens the XML element <code>\$(System.Collections.Hashtable[1])</code> , which defines part of the Maven build configuration.
53	<code><scope>runtime</scope></code>	Opens the XML element <code>\$(System.Collections.Hashtable[1])</code> , which defines part of the Maven build configuration.

Line	Code	Explanation
54	<code></dependency></code>	Closes the XML element <code>\$(System.Collections.Hashtable[1])</code> .
55	<code><dependency></code>	Opens the XML element <code>\$(System.Collections.Hashtable[1])</code> , which defines part of the Maven build configuration.
56	<code><groupId>com.mysql</groupId></code>	Opens the XML element <code>\$(System.Collections.Hashtable[1])</code> , which defines part of the Maven build configuration.
57	<code><artifactId>mysql-connector-j</artifactId></code>	Opens the XML element <code>\$(System.Collections.Hashtable[1])</code> , which defines part of the Maven build configuration.
58	<code><scope>runtime</scope></code>	Opens the XML element <code>\$(System.Collections.Hashtable[1])</code> , which defines part of the Maven build configuration.
59	<code></dependency></code>	Closes the XML element <code>\$(System.Collections.Hashtable[1])</code> .
60	<code><dependency></code>	Opens the XML element <code>\$(System.Collections.Hashtable[1])</code> , which defines part of the Maven build configuration.
61	<code><groupId>io.jsonwebtoken</groupId></code>	Opens the XML element <code>\$(System.Collections.Hashtable[1])</code> , which defines part of the Maven build configuration.
62	<code><artifactId>jjwt-api</artifactId></code>	Opens the XML element <code>\$(System.Collections.Hashtable[1])</code> , which defines part of the Maven build configuration.
63	<code><version>\${jjwt.version}</version></code>	Opens the XML element <code>\$(System.Collections.Hashtable[1])</code> , which defines part of the Maven build configuration.
64	<code></dependency></code>	Closes the XML element <code>\$(System.Collections.Hashtable[1])</code> .
65	<code><dependency></code>	Opens the XML element <code>\$(System.Collections.Hashtable[1])</code> , which defines part of the Maven build configuration.
66	<code><groupId>io.jsonwebtoken</groupId></code>	Opens the XML element <code>\$(System.Collections.Hashtable[1])</code> , which defines part of the Maven build configuration.
67	<code><artifactId>jjwt-impl</artifactId></code>	Opens the XML element <code>\$(System.Collections.Hashtable[1])</code> , which defines part of the Maven build configuration.
68	<code><version>\${jjwt.version}</version></code>	Opens the XML element <code>\$(System.Collections.Hashtable[1])</code> , which defines part of the Maven build configuration.
69	<code><scope>runtime</scope></code>	Opens the XML element <code>\$(System.Collections.Hashtable[1])</code> , which defines part of the Maven build configuration.
70	<code></dependency></code>	Closes the XML element <code>\$(System.Collections.Hashtable[1])</code> .
71	<code><dependency></code>	Opens the XML element <code>\$(System.Collections.Hashtable[1])</code> , which defines part of the Maven build configuration.
72	<code><groupId>io.jsonwebtoken</groupId></code>	Opens the XML element <code>\$(System.Collections.Hashtable[1])</code> , which defines part of the Maven build configuration.

Line	Code	Explanation
73	<code><artifactId>jjwt-jackson</artifactId></code>	Opens the XML element <code>\$(System.Collections.Hashtable[1])</code> , which defines part of the Maven build configuration.
74	<code><version>\${jjwt.version}</version></code>	Opens the XML element <code>\$(System.Collections.Hashtable[1])</code> , which defines part of the Maven build configuration.
75	<code><scope>runtime</scope></code>	Opens the XML element <code>\$(System.Collections.Hashtable[1])</code> , which defines part of the Maven build configuration.
76	<code></dependency></code>	Closes the XML element <code>\$(System.Collections.Hashtable[1])</code> .
77	<code><dependency></code>	Opens the XML element <code>\$(System.Collections.Hashtable[1])</code> , which defines part of the Maven build configuration.
78	<code><groupId>org.springframework.boot</groupId></code>	Opens the XML element <code>\$(System.Collections.Hashtable[1])</code> , which defines part of the Maven build configuration.
79	<code><artifactId>spring-boot-starter-test</artifactId></code>	Opens the XML element <code>\$(System.Collections.Hashtable[1])</code> , which defines part of the Maven build configuration.
80	<code><scope>test</scope></code>	Opens the XML element <code>\$(System.Collections.Hashtable[1])</code> , which defines part of the Maven build configuration.
81	<code></dependency></code>	Closes the XML element <code>\$(System.Collections.Hashtable[1])</code> .
82	<code><dependency></code>	Opens the XML element <code>\$(System.Collections.Hashtable[1])</code> , which defines part of the Maven build configuration.
83	<code><groupId>org.springframework.security</groupId></code>	Opens the XML element <code>\$(System.Collections.Hashtable[1])</code> , which defines part of the Maven build configuration.
84	<code><artifactId>spring-security-test</artifactId></code>	Opens the XML element <code>\$(System.Collections.Hashtable[1])</code> , which defines part of the Maven build configuration.
85	<code><scope>test</scope></code>	Opens the XML element <code>\$(System.Collections.Hashtable[1])</code> , which defines part of the Maven build configuration.
86	<code></dependency></code>	Closes the XML element <code>\$(System.Collections.Hashtable[1])</code> .
87	<code></dependencies></code>	Closes the XML element <code>\$(System.Collections.Hashtable[1])</code> .
88		Blank line used to separate XML sections.
89	<code><build></code>	Opens the XML element <code>\$(System.Collections.Hashtable[1])</code> , which defines part of the Maven build configuration.
90	<code><plugins></code>	Opens the XML element <code>\$(System.Collections.Hashtable[1])</code> , which defines part of the Maven build configuration.
91	<code><plugin></code>	Opens the XML element <code>\$(System.Collections.Hashtable[1])</code> , which defines part of the Maven build configuration.

Line	Code	Explanation
92	<code><groupId>org.springframework.boot</groupId></code>	Opens the XML element <code>\$(System.Collections.Hashtable[1])</code> , which defines part of the Maven build configuration.
93	<code><artifactId>spring-boot-maven-plugin</artifactId></code>	Opens the XML element <code>\$(System.Collections.Hashtable[1])</code> , which defines part of the Maven build configuration.
94	<code></plugin></code>	Closes the XML element <code>\$(System.Collections.Hashtable[1])</code> .
95	<code></plugins></code>	Closes the XML element <code>\$(System.Collections.Hashtable[1])</code> .
96	<code></build></code>	Closes the XML element <code>\$(System.Collections.Hashtable[1])</code> .
97	<code></project></code>	Closes the XML element <code>\$(System.Collections.Hashtable[1])</code> .

README.md

Why this file exists: Explains what the auth service does, what endpoints it exposes, and how to run it in development.

Line count: 69

Line	Code	Explanation
1	<code># ConnectSphere `auth-service`</code>	Markdown heading that introduces the section <code>\$(System.Collections.Hashtable[1])</code> .
2		Blank line used to separate paragraphs or list sections.
3	<code>This service is aligned with the PDF sections for:</code>	Narrative documentation text for the module.
4		Blank line used to separate paragraphs or list sections.
5	<code>- `2.1` general auth and profile rules</code>	Markdown bullet point that lists <code>\$(System.Collections.Hashtable[1])</code> .
6	<code>- `2.2` guest access to login/registration and user search</code>	Markdown bullet point that lists <code>\$(System.Collections.Hashtable[1])</code> .
7	<code>- `2.3` registered-user registration and account management</code>	Markdown bullet point that lists <code>\$(System.Collections.Hashtable[1])</code> .
8	<code>- `2.4` admin account management support</code>	Markdown bullet point that lists <code>\$(System.Collections.Hashtable[1])</code> .
9	<code>- `4.1` Auth/User-Service entity, repository, service, and resource responsibilities</code>	Markdown bullet point that lists <code>\$(System.Collections.Hashtable[1])</code> .

Line	Code	Explanation
10	- ``5` architecture naming (`com.connectsphere.auth`)	Markdown bullet point that lists \$(System.Collections.Hashtable[1]).
11	- ``6` security requirements such as bcrypt and 24-hour JWT access tokens	Markdown bullet point that lists \$(System.Collections.Hashtable[1]).
12		Blank line used to separate paragraphs or list sections.
13	## What is implemented	Markdown heading that introduces the section \$(System.Collections.Hashtable[1]).
14		Blank line used to separate paragraphs or list sections.
15	- User registration with email/password	Markdown bullet point that lists \$(System.Collections.Hashtable[1]).
16	- Login and logout	Markdown bullet point that lists \$(System.Collections.Hashtable[1]).
17	- 24-hour JWT access tokens plus rotating refresh tokens	Markdown bullet point that lists \$(System.Collections.Hashtable[1]).
18	- Token validation endpoint for downstream services	Markdown bullet point that lists \$(System.Collections.Hashtable[1]).
19	- Profile read and update	Markdown bullet point that lists \$(System.Collections.Hashtable[1]).
20	- Password change	Markdown bullet point that lists \$(System.Collections.Hashtable[1]).
21	- User search by username or full name	Markdown bullet point that lists \$(System.Collections.Hashtable[1]).
22	- Account deactivation	Markdown bullet point that lists \$(System.Collections.Hashtable[1]).
23	- MySQL-ready JPA model with an H2 default profile for local development	Markdown bullet point that lists \$(System.Collections.Hashtable[1]).
24	- OAuth2 client configuration placeholders for Google and GitHub	Markdown bullet point that lists \$(System.Collections.Hashtable[1]).
25		Blank line used to separate paragraphs or list sections.
26	## API surface	Markdown heading that introduces the section \$(System.Collections.Hashtable[1]).
27		Blank line used to separate paragraphs or list sections.

Line	Code	Explanation
28	The PDF names endpoints under <code>`/auth/...`</code> , while the non-functional requirements also call for versioned APIs under <code>`/api/v1/...`</code> .	Narrative documentation text for the module.
29		Blank line used to separate paragraphs or list sections.
30	To satisfy both, the controller exposes both route families:	Narrative documentation text for the module.
31		Blank line used to separate paragraphs or list sections.
32	- <code>`/auth/register`</code> and <code>`/api/v1/auth/register`</code>	Markdown bullet point that lists <code>\$(System.Collections.Hashtable[1])</code> .
33	- <code>`/auth/login`</code> and <code>`/api/v1/auth/login`</code>	Markdown bullet point that lists <code>\$(System.Collections.Hashtable[1])</code> .
34	- <code>`/auth/logout`</code> and <code>`/api/v1/auth/logout`</code>	Markdown bullet point that lists <code>\$(System.Collections.Hashtable[1])</code> .
35	- <code>`/auth/refresh`</code> and <code>`/api/v1/auth/refresh`</code>	Markdown bullet point that lists <code>\$(System.Collections.Hashtable[1])</code> .
36	- <code>`/auth/profile`</code> and <code>`/api/v1/auth/profile`</code>	Markdown bullet point that lists <code>\$(System.Collections.Hashtable[1])</code> .
37	- <code>`/auth/password`</code> and <code>`/api/v1/auth/password`</code>	Markdown bullet point that lists <code>\$(System.Collections.Hashtable[1])</code> .
38	- <code>`/auth/search`</code> and <code>`/api/v1/auth/search`</code>	Markdown bullet point that lists <code>\$(System.Collections.Hashtable[1])</code> .
39	- <code>`/auth/deactivate`</code> and <code>`/api/v1/auth/deactivate`</code>	Markdown bullet point that lists <code>\$(System.Collections.Hashtable[1])</code> .
40		Blank line used to separate paragraphs or list sections.
41	## Notes on OAuth	Markdown heading that introduces the section <code>\$(System.Collections.Hashtable[1])</code> .
42		Blank line used to separate paragraphs or list sections.
43	The PDF requires GitHub/Google OAuth support, but it does not define the website callback flow or provider credentials.	Narrative documentation text for the module.
44		Blank line used to separate paragraphs or list sections.
45	This starter includes:	Narrative documentation text for the module.
46		Blank line used to separate paragraphs or list sections.

Line	Code	Explanation
47	- Spring Security OAuth2 client dependency	Markdown bullet point that lists <code>\$(System.Collections.Hashtable[1])</code> .
48	- an opt-in `oauth` profile in `application-oauth.yml`	Markdown bullet point that lists <code>\$(System.Collections.Hashtable[1])</code> .
49	- `AuthProvider` support in the domain model	Markdown bullet point that lists <code>\$(System.Collections.Hashtable[1])</code> .
50		Blank line used to separate paragraphs or list sections.
51	That gives us the right foundation for the next iteration, where we can wire provider callbacks or gateway-driven social login once you want to tackle that piece.	Narrative documentation text for the module.
52		Blank line used to separate paragraphs or list sections.
53	## Run locally	Markdown heading that introduces the section <code>\$(System.Collections.Hashtable[1])</code> .
54		Blank line used to separate paragraphs or list sections.
55	```bash	Starts or ends a fenced code block in the README.
56	mvn spring-boot:run	Narrative documentation text for the module.
57	```	Starts or ends a fenced code block in the README.
58		Blank line used to separate paragraphs or list sections.
59	To use MySQL instead of the in-memory H2 database:	Narrative documentation text for the module.
60		Blank line used to separate paragraphs or list sections.
61	```bash	Starts or ends a fenced code block in the README.
62	mvn spring-boot:run -Dspring-boot.run.profiles=mysql	Narrative documentation text for the module.
63	```	Starts or ends a fenced code block in the README.
64		Blank line used to separate paragraphs or list sections.
65	To enable GitHub/Google OAuth once credentials are available:	Narrative documentation text for the module.
66		Blank line used to separate paragraphs or list sections.
67	```bash	Starts or ends a fenced code block in the README.

Line	Code	Explanation
68	<code>mvn spring-boot:run -Dspring-boot.run.profiles=oauth</code>	Narrative documentation text for the module.
69	<code>```</code>	Starts or ends a fenced code block in the README.