SRINIVAS UNIVERSITY

INSTITUTE OF ENGINEERING & TECHNOLOGY

MUKKA, MANGALURU-574146



MINI PROJECT REPORT

ON

NETWORK LOG ANALYZER FOR SECURITY AUDITING

Submitted in the partial fulfillment of the requirements for the award of the degree of

BACHELOR OF TECHNOLOGY

IN

CYBER SECURITY AND CYBER FORENSICS

Submitted By,

Anurandh K Vinod	**01SU24CF003**
Yadhunandan T A	**01SU24CF010**

Under the guidance of

Prof. Preethika Sequeira

Assistant Professor
Dept. of CSCF

2026-2027

DEPARTMENT OF CYBER SECURITY AND CYBER FORENSICS

SRINIVAS UNIVERSITY, MUKKA

SRINIVAS UNIVERSITY

INSTITUTE OF ENGINEERING & TECHNOLOGY

MUKKA, MANGALURU-574146

Department of Cyber Security and Cyber Forensics

CERTIFICATE

This is to certify that the Mini project entitled ***"Network Log Analyzer for Security Auditing"*** is a bonafide work carried out by ***Anurandh K Vinod*** bearing the **USN** ***01SU24CF003*** and ***Yadhunandan T A*** bearing the **USN** ***01SU24CF010*** in the partial fulfillment for the award of **Bachelor of Technology** in **Cyber Security and Cyber Forensics** of the **Srinivas University- Institute of Engineering & Technology** during the year **2026-2027.** It is certified that all corrections/suggestions indicated for internal assessment have been incorporated in the report deposited in the department library. The Mini Project report has been approved as it satisfies the academic requirements in respect of Mini Project work prescribed for the said degree.

Name & Signature	Name & Signature
Prof. Preethika Sequeira	**Prof. Anand S Uppar**
Internship Guide	**HoD, CSCF**

SRINIVAS UNIVERSITY
INSTITUTE OF ENGINEERING & TECHNOLOGY

MUKKA, MANGALURU-574146



Department of Cyber Security and Cyber Forensics

DECLARATION

I, **Anurandh K Vinod (USN: 01SU24CF003) and Yadhunandan T A (USN: 01SU24CF010)** the students of 5th semester, **B.Tech** in Cyber Security And Cyber Forensics, Srinivas University, Mukka, hereby declare that the Mini project entitled "***Network Log Analyzer for Security Auditing***" has been successfully completed by us in partial fulfillment of the requirements for the award of degree in **Bachelor of Technology** in **Cyber Security And Cyber Forensics of Srinivas University- Institute of Engineering & Technology** and no part of it has been submitted for the award of degree or diploma in any university or institution previously.

Date: 27/09/26

Place: Mukka

ABSTRACT

In contemporary enterprise infrastructures, computer networks are continuously subjected to sophisticated, multi-vector cyber attacks, including brute force authentication attempts, unauthorized multi-port reconnaissance, distributed denial of service (DoS) floods, data exfiltration, and web application injection vulnerabilities. While perimeter defense devices such as firewalls, intrusion detection systems (IDS), and web proxies generate voluminous event logs, manual inspection is infeasible, error-prone, and incapable of providing real-time forensic awareness. This mini project presents the design and implementation of the **Network Log Analyzer for Security Auditing**, an automated security operations center (SOC) log ingestion, forensic analysis, and security auditing framework developed using Python. The proposed system features a dual-mode log parser supporting both structured CSV files and semi-structured Syslog/Firewall text streams (RFC 3164/5424), normalizing diverse network records into unified schemas. A robust threat detection engine is formulated using sliding-time-window heuristics and regex signature inspection to uncover SSH/RDP brute force attempts ($\geq$ 4 failures in 60s), horizontal/vertical port scans ($\geq$ 5 distinct ports in 60s), single and cumulative volumetric data exfiltration spikes ($>$ 5 MB and $>$ 20 MB), high-frequency request floods ($>$ 40 requests in 30s), Threat Intelligence blacklist correlations, and web application attack payloads (SQL Injection, Cross-Site Scripting, Directory Traversal, and Command Injection). The framework couples an interactive web-based SOC dashboard developed with Streamlit and Plotly for deep visual triage with an automated forensic report generation engine capable of exporting executive PDF reports and SIEM-compliant CSV audit records. Experimental evaluations on simulated multi-attack datasets confirm 100% threat detection fidelity with negligible computational latency, establishing an accessible, cost-effective forensic auditing pipeline for modern academic and enterprise SOC environments.

Keywords: Network Security, Log Analysis, Security Auditing, Digital Forensics, Threat Detection, Brute Force, Port Scanning, Web Application Security, Anomaly Detection, Streamlit SOC Dashboard.

ACKNOWLEDGEMENT

We would like to express our sincere gratitude to our Mini Project Guide, **Prof. Preethika Sequeira**, Assistant Professor, Department of Cyber Security and Cyber Forensics, for her invaluable guidance, constant encouragement, constructive feedback, and timely support provided throughout the conceptualization and completion of this mini project.

We would like to sincerely thank **Prof. Preethika Sequeira** for coordinating the mini project activities and for the valuable guidance in preparing for the mini project technical demonstrations and exhibition presentations.

We are extremely thankful to the Head of the Department, **Prof. Anand S Uppar**, for granting permission, facilitating essential resources, and providing the necessary departmental laboratory infrastructure to carry out this project successfully.

We would also like to convey our heartfelt thanks to the Dean, **Dr. Ramakrishna N Hegde**, for his persistent motivation and administrative support, and to the Esteemed Management of Srinivas University for cultivating an inspiring academic ecosystem and providing state-of-the-art facilities for project-related research.

We extend our sincere appreciation to all the faculty members and technical staff of the Department of Cyber Security and Cyber Forensics for their cooperation, critical insights, and technical assistance during the course of this work.

Finally, we would like to express our profound debt of gratitude to our parents, family members, and friends for their continuous moral support, patience, and encouragement, which have been an enduring pillar throughout our academic journey.

Anurandh K Vinod (USN: **01SU24CF003**)

YADHUNANDAN T A (USN: **01SU24CF010**)

Dept. of Cyber Security and Cyber Forensics
Srinivas University, Mukka

CONTENTS

1 INTRODUCTION 1

1.1 Overview of the Project 1

1.2 Problem Definition 1

1.3 Objectives of the Project 2

1.4 Scope and Applications 3

1.4.1 Scope of the Project 3

1.4.2 Practical Applications 3

2 LITERATURE REVIEW 4

2.1 Review and Limitations of Existing Systems 4

2.1.1 Signature-Based Network Intrusion Detection (Snort & Suricata) 4

2.1.2 Enterprise SIEM Solutions (Splunk, Elastic SIEM, Graylog) 4

2.2 Proposed System Overview 5

3 SYSTEM ANALYSIS AND DESIGN 6

3.1 System Architecture 6

3.1.1 Architectural Component Specifications 6

3.2 Hardware Requirements 7

3.3 Software Requirements 8

4 METHODOLOGY / IMPLEMENTATION 9

4.1 Working Principle 9

4.2 Algorithm and Process Flow 9

4.2.1 Brute Force Authentication Detection Algorithm 9

4.2.2 Port Scanning and Reconnaissance Detection Algorithm 10

4.2.3 Volumetric Anomaly and Data Exfiltration Algorithm 10

4.2.4 Network Risk Score Metric Formulation 11

4.3 Module Description 11

4.3.1 Log Parser and Normalizer Module (`analyzer.py`) 11

4.3.2 Threat Detection Engine (`analyzer.py`) 11

4.3.3 Interactive Web Dashboard (`app.py`) 12

4.3.4 Forensic Report Generator Module (`report_generator.py`) 12

4.3.5 Synthetic Attack Generator Module (`log_generator.py`) 12

5 RESULTS 13

5.1 Screenshots and Evaluation Results 13

5.1.1 Performance Benchmarks 13

5.1.2 System Screenshots and Interface Walkthrough.....14
5.2 Challenges Faced and Solutions 14

6 CONCLUSION 16
6.1 Conclusion.....16
6.2 Future Enhancements 16

7 REFERENCES & BIBLIOGRAPHY 18

List of Figures

3.1 System Architecture and Data Flow Pipeline of Network Log Analyzer 6

5.1 Main Interactive Web Dashboard 14
5.2 Brute Force & Port Scan Detection Alerts 15

List of Tables

2.1 Comparative Analysis of Log Auditing and Security Systems 5

3.1 Hardware Specifications 7
3.2 Software Environment and Dependencies 8

5.1 Threat Detection Accuracy and Evaluation Results 13
5.2 Ingestion and Analysis Performance Latency 13

Chapter 1

INTRODUCTION

1.1 Overview of the Project

In the modern hyper-connected digital landscape, enterprise network infrastructures serve as the operational backbone for mission-critical services, financial transactions, and confidential data storage. Concurrently, the sophistication, velocity, and surface area of cyber attacks have grown exponentially. Threat actors exploit vulnerabilities across multiple network tiers, deploying advanced techniques ranging from automated reconnaissance port scans and brute-force credential stuffing to remote web code injections, volumetric denial of service (DoS) attacks, and covert data exfiltration channels.

Network devices, firewalls, routers, proxy servers, and operating systems continuously record operational telemetries into text-based log streams. These logs represent an authoritative chronological audit trail documenting communication parameters: timestamps, source and destination IP addresses, port numbers, protocols (TCP, UDP, ICMP), firewall filter actions (ALLOW, BLOCK), HTTP status codes, and message payloads. When properly parsed and analyzed, log files serve as the primary source of digital forensic evidence, enabling Security Operations Center (SOC) analysts to reconstruct intrusion timelines, identify Indicators of Compromise (IOCs), assess breach perimeters, and satisfy statutory compliance standards such as ISO/IEC 27001, PCI-DSS, and NIST SP 800-61.

However, modern IT infrastructures generate gigabytes of log telemetry daily. The sheer volume, high noise ratio, and syntactic heterogeneity of multi-vendor log formats render manual auditing technically impractical. The **Network Log Analyzer for Security Auditing** was developed to address this operational bottleneck. It delivers an automated, high-performance, Python-driven forensic pipeline that ingests heterogeneous raw network logs, normalizes them into structured analytical dataframes, applies sliding-time-window heuristics and signature recognition algorithms to detect active threat vectors, and visualizes security telemetries via an interactive web dashboard with one-click executive audit report generation.

1.2 Problem Definition

Network administrators and SOC triage teams encounter critical technical hurdles during security log auditing:

1. **Syntactic Heterogeneity and Unstructured Formatting:** Logs generated by disparate appliances (e.g., Linux Syslog RFC 3164/5424, Cisco ASA, pfSense, Apache/Nginx web

servers, and custom network CSV files) adhere to varied delimiters and schemas, requiring unified ingestion normalization.

2. **Cognitive Overload and Noise:** Over 95% of enterprise network traffic consists of benign, routine transactions. Sifting through millions of lines to isolate targeted reconnaissance or subtle exfiltration spikes without specialized automated heuristics leads to severe alert fatigue.

3. **Sluggish Post-Incident Forensic Reconstruction:** When a breach occurs, incident responders need immediate timeline correlation. Traditional command-line utilities (such as `grep`, `awk`, or `sed`) lack temporal sliding-window capabilities and cannot compute multi-port scanning metrics or burst rate statistics.

4. **Commercial SIEM Cost and Complexity:** Commercial enterprise SIEM platforms (such as Splunk Enterprise or IBM QRadar) demand high subscription licensing fees, dedicated server hardware clusters, and specialized query language certifications, making them inaccessible for academic research labs, small-to-medium enterprises (SMEs), and isolated forensic audits.

1.3 Objectives of the Project

The primary objective of this mini project is to engineer and validate a lightweight, automated, and standalone Network Log Analyzer and Security Auditing system. The specific technical objectives are:

- To build a versatile ingestion parser capable of auto-detecting and ingesting RFC-compliant Syslog files, raw firewall dumps, and structured comma-separated value (CSV) logs.
- To formulate a sliding-time-window anomaly detection engine that identifies:
  - Authentication Brute Force attacks across SSH, RDP, and Web portals (≥ 4 failed attempts within 60 seconds).
  - Horizontal and vertical Port Scanning reconnaissance (≥ 5 unique ports probed within 60 seconds).
  - Volumetric Data Exfiltration spikes (single transfers > 5 MB or cumulative transfers > 20 MB).
  - Denial of Service (DoS) request floods (> 40 requests within 30 seconds).
- To implement a deep regular expression (Regex) inspection engine targeting common web application vulnerabilities (SQL Injection, Cross-Site Scripting, Path Traversal, and Command Injection).

- To correlate network transactions against a simulated Threat Intelligence (TI) blacklist of known malicious Command and Control (C2) servers and Tor exit nodes.
- To construct an interactive, cybersecurity-themed SOC dashboard using Streamlit and Plotly for exploratory visual analytics, metric tracking, and threat triage.
- To automate the compilation and generation of publication-quality, non-repudiable executive PDF audit reports (via ReportLab) and SIEM-ready CSV exports.

1.4 Scope and Applications

1.4.1 Scope of the Project

The scope encompasses post-capture and real-time buffer-based log auditing of network layer (Layer 3/4) and application layer (Layer 7) events. The engine processes connection metadata, protocol headers, HTTP status codes, and uniform resource identifier (URI) payloads. The threat models address the reconnaissance, weaponization, delivery, and exfiltration phases of the Cyber Kill Chain.

1.4.2 Practical Applications

- **Enterprise Security Operations Centers (SOC):** Provides tier-1 and tier-2 SOC analysts with an on-demand triage tool to validate anomalous network alerts and inspect suspect host activities.
- **Digital Forensics & Incident Response (DFIR):** Assists forensic investigators in establishing precise timestamps, calculating total exfiltrated byte volumes, and generating courtroom-ready audit reports.
- **Academic Research & Training:** Serves as a modular reference platform for students and researchers in Cyber Security and Forensics to examine attack signatures, heuristic thresholds, and log parsing mechanics.
- **Compliance Auditing:** Enables compliance officers to generate empirical audit logs fulfilling regulatory log review requirements under PCI-DSS Requirement 10 and ISO/IEC 27001 Annex A.12.

Chapter 2

LITERATURE REVIEW

2.1 Review and Limitations of Existing Systems

Over the past two decades, academic researchers and commercial cybersecurity firms have investigated log management and intrusion detection architectures. This section reviews existing methodologies and identifies technical trade-offs.

2.1.1 Signature-Based Network Intrusion Detection (Snort & Suricata)

Roesch et al. introduced Snort, an open-source rule-based packet sniffing and logging engine. Suricata subsequently introduced multi-threaded inspection and deep packet inspection. While highly proficient at real-time wire-speed raw packet capture (PCAP) inspection, these tools require dedicated network tap interfaces and produce massive storage overhead. Furthermore, when analyzing pre-existing perimeter log files or server access logs post-incident, raw packet analyzers cannot readily ingest summarized firewall transaction records without packet reconstruction.

2.1.2 Enterprise SIEM Solutions (Splunk, Elastic SIEM, Graylog)

Enterprise Security Information and Event Management (SIEM) systems unify log collection, aggregation, and querying across corporate networks.

- **Splunk Enterprise:** Offers proprietary search processing language (SPL) and indexing. However, licensing is priced on ingested daily data volume, imposing prohibitive costs on academic institutions and smaller organizations.
- **Elastic Stack (ELK: Elasticsearch, Logstash, Kibana):** While open-source, ELK demands significant JVM memory allocations, cluster coordination, and intricate pipeline configurations (Filebeat/Logstash grok patterns), making rapid offline forensic analysis cumbersome.
- **Graylog:** Efficient for log aggregation via MongoDB and Elasticsearch, but lacks natively bundled, pre-configured incident playbooks and standalone PDF audit report compilation engines.

Table 2.1: Comparative Analysis of Log Auditing and Security Systems

System	Architecture	Detection Logic	Limitations	Cost Model
Snort / Suricata	Wire-level Packet Capture	Rule-based Payload Signatures	Requires raw PCAP; high storage and CPU demand	Open Source
Splunk Enterprise	Distributed Indexer Cluster	Proprietary SPL Queries	Ingestion volume pricing; heavy server requirements	High Commercial
Elastic SIEM	Java / Lucene Search Cluster	Query Rules & ML Modules	High memory footprint; complex grok configurations	Freemium
Zeek (Bro)	Behavioral Network Analysis	Scripting Framework	Steep learning curve; no turnkey visual reporting	Open Source
Proposed System	Lightweight Python Pipeline	Sliding-Window + Regex + Threat Intel	Specialized for log forensics; standalone offline execution	Open Source

2.2 Proposed System Overview

To overcome the constraints of existing platforms, the proposed **Network Log Analyzer for Security Auditing** adopts a modular, lightweight data-science approach. Leveraging Python's vectorized computational frameworks (`pandas` and `numpy`), the system processes large log datasets in seconds without requiring background database services, Java virtual machines, or distributed daemons.

Key architectural merits of the proposed system include:

1. **Zero Infrastructure Overhead:** Executes seamlessly as a self-contained local web application or headless command-line script.
2. **Temporal Sliding-Window Correlation:** Implements rolling temporal analysis (Δt) to uncover distributed brute force and stealthy multi-port reconnaissance attacks that evade static per-second thresholds.
3. **Integrated Multi-Vector Detection:** Blends behavioral metrics (bandwidth anomalies, request burst rates) with deterministic signatures (SQLi, XSS, Path Traversal) and Threat Intelligence IP blacklists.
4. **Automated Forensic Documentation:** Bridges the gap between detection and compliance by programmatically compiling verified alerts into publication-grade executive PDF security audits and SIEM-compliant CSV reports.

Chapter 3

SYSTEM ANALYSIS AND DESIGN

3.1 System Architecture

The system architecture follows a pipeline pattern comprising five decoupled subsystems: Ingestion & In-memory Storage, Parsing & Normalization, Threat Detection & Forensics Engine, Interactive Web Presentation Layer, and Automated Report Generation Subsystem. Figure 3.1 illustrates the end-to-end data flow.




Figure 3.1: System Architecture and Data Flow Pipeline of Network Log Analyzer

3.1.1 Architectural Component Specifications

1. **Ingestion Subsystem:** Ingests files via file upload dialogs or CLI arguments. Supports RFC 3164/5424 standard text streams, web proxy records, and structured CSV records.

2. **Parser and Normalizer:** Deploys regular expression tokenizers to extract named parameters: timestamp, source IP, source port, destination IP, destination port, protocol, action, status code, bytes, and message string. Missing fields are automatically populated with safe fallback defaults.

3. **Threat Detection Engine:** Contains isolated heuristic evaluators. Each module queries the

normalized DataFrame to identify specific violation conditions and appends standardized forensic alert dictionaries.

4. **Forensic Metrics Aggregator:** Computes network-level key performance indicators (KPIs), severity distributions (Critical, High, Medium, Low), top targeted internal hosts, threat actor rankings, and an overall Network Risk Score ($0 - 100$).
5. **Reporting Subsystem:** Converts structured alert records into formal PDF audit artifacts containing tabular evidence, threat summaries, and actionable incident response remediation playbooks.

3.2 Hardware Requirements

The software pipeline was intentionally engineered to operate with minimal hardware resource footprints, enabling deployment on local forensic workstations or edge SOC nodes.

Table 3.1: Hardware Specifications

Component	Minimum Specification	Recommended Specification
Processor	Dual-Core 2.0 GHz (Intel i3 / AMD Ryzen 3)	Quad-Core 2.5 GHz or higher (Intel i5/i7, AMD Ryzen 5/7)
System Memory (RAM)	4 GB DDR3/DDR4	8 GB – 16 GB DDR4
Storage	500 MB free space for code & libraries	10 GB SSD for high-volume log archives
Network Interface	Standard 10/100 Mbps NIC	1 Gbps Ethernet Interface / 802.11ac Wi-Fi
Display Resolution	1280×720 pixels	1920×1080 Full HD (for SOC Dashboard)

3.3 Software Requirements

Table 3.2: Software Environment and Dependencies

Software Layer	Component Name	Purpose
Operating System	Windows 10/11, Ubuntu 20.04/22.04 LTS, macOS	Host execution environment
Runtime Environment	Python 3.10.x or higher	Core programming interpreter
Data Processing	Pandas $\geq$ 2.0.0, NumPy $\geq$ 1.24.0	High-speed vectorized data analytics
Web Presentation	Streamlit $\geq$ 1.30.0	Real-time reactive SOC user interface
Visual Analytics	Plotly $\geq$ 5.18.0	Interactive exploratory charts and Sankey flows
Report Generation	ReportLab $\geq$ 4.0.0	Programmatic PDF compilation and typography
Testing Framework	Pytest $\geq$ 7.4.0	Automated unit testing and detection validation
Development IDE	Anti Gravity IDE / VS Code	Integrated development and debugging environment

Chapter 4

METHODOLOGY / IMPLEMENTATION

4.1 Working Principle

The Network Log Analyzer operates on the principle of *temporal event correlation and signature matching*. Raw log lines are parsed into time-indexed records. For every record, relevant metadata attributes are indexed. Rather than inspecting events in isolation, the engine executes sliding time-window aggregations across discrete source IP addresses (S_{ip}).

When an attack pattern satisfies predefined temporal and volumetric thresholds, the engine raises an alert object encapsulating:

- **Temporal Stamp:** Precise timestamp of the initial offending event.
- **Threat Vector & Severity:** Categorized using a five-tier hierarchy (CRITICAL, HIGH, MEDIUM, LOW, INFORMATIONAL).
- **Attacker & Target Identifiers:** Source IP, Destination IP, and Target Service Port.
- **Forensic Evidence:** Concrete log parameters, payload fragments, or burst rates justifying the alert.
- **Remediation Recommendations:** Standardized containment steps aligned with industry playbooks.

4.2 Algorithm and Process Flow

4.2.1 Brute Force Authentication Detection Algorithm

Brute force attacks manifest as repeated failed login transactions originating from a common source IP within a brief duration. Let E_{fail} denote the set of failed authentication events (status codes 401, 403, action BLOCK, or messages containing 'failed'/'unauthorized'). For a sliding time window W (default 60 seconds), the algorithm flags host S_{ip} if:

$$\left| \left\{ e \in E_{fail} \mid \mathrm{Src}(e) = S_{ip} \wedge t_0 \leq \mathrm{Time}(e) \leq t_0 + W \right\} \right| \geq \Theta_{BF} \tag{4.1}$$

where $\Theta_{BF} = 4$ is the failure threshold.

```
def detect_brute_force(df, max_attempts=4, window_sec=60):
    fail_mask = (df["status_code"].isin([401, 403])) | (df["action"] == "
   BLOCK") | \
```

```
                (df["message"].str.contains(r"failed|invalid|unauthorized",
    case=False))
    failed_df = df[fail_mask]

    for src_ip, group in failed_df.groupby("source_ip"):
        if len(group) < max_attempts:
            continue
        group = group.sort_values("timestamp")
        timestamps = group["timestamp"].tolist()
        for i in range(len(timestamps)):
            w_end = timestamps[i] + timedelta(seconds=window_sec)
            in_window = group[(group["timestamp"] >= timestamps[i]) &
                              (group["timestamp"] <= w_end)]
            if len(in_window) >= max_attempts:
                raise_alert(attack="Brute Force", src=src_ip,
                            count=len(in_window), target=in_window["
    destination_ip"].iloc[0])
                break
```

Listing 4.1: Brute Force Detection Algorithm Logic

4.2.2 Port Scanning and Reconnaissance Detection Algorithm

Port scanning is modeled as an attempt by a single host to probe multiple distinct destination ports (D_{port}) within sliding window W. Let $P(S_{\text{ip}}, W)$ denote the set of unique ports contacted:

$$P(S_{\text{ip}}, W) = \left\{ \text{DstPort}(e) \mid \text{Src}(e) = S_{\text{ip}} \wedge t_0 \leq \text{Time}(e) \leq t_0 + W \right\} \tag{4.2}$$

An alert is generated when:

$$P(S_{\text{ip}}, W) \geq \Theta_{\text{PS}} \tag{4.3}$$

where $\Theta_{\text{PS}} = 5$ distinct ports.

4.2.3 Volumetric Anomaly and Data Exfiltration Algorithm

Data exfiltration is evaluated under two heuristic criteria:

1. **Single Session Spike:** A solitary session transferring bytes $B_{\text{trans}} \geq \Theta_{\text{single}}$ (where $\Theta_{\text{single}} = 5\,\text{MB} = 5{,}242{,}880\,\text{bytes}$).
2. **Cumulative Outbound Surge:** Total bytes transferred by a source IP to an external destination across the observation period satisfying:

$$\sum B_{\text{trans}}(S_{\text{ip}} \rightarrow D_{\text{ip}}) \geq \Theta_{\text{cumul}} \quad (\Theta_{\text{cumul}} = 20\,\text{MB} = 20{,}971{,}520\,\text{bytes}) \tag{4.4}$$

4.2.4 Network Risk Score Metric Formulation

To furnish security executives with an instantaneous security health indicator, a composite Network Risk Score $R \in [0, 100]$ is computed:

$$R = \min\left(100, \sum_{s \in \text{Alerts}} w(s) \times 12\right) + \min\left(25, \frac{|\text{Alerts}|}{|\text{Logs}|} \times 100\right) \tag{4.5}$$

where weights $w(s)$ correspond to severity levels: Critical = 4, High = 3, Medium = 2, Low = 1.

4.3 Module Description

The system implementation is organized across five modular Python components:

4.3.1 Log Parser and Normalizer Module (`analyzer.py`)

The parser module processes incoming logs and standardizes field names using an internal dictionary mapping. For raw text and syslog files, it compiles the following regular expression:

```
LOG_LINE_PATTERN = re.compile(
    r'^(?P<timestamp>\d{4}-\d{2}-\d{2}\s+\d{2}:\d{2}:\d{2})\s+'
    r'(?P<source_ip>[0-9a-fA-F\.\:]+):(?P<source_port>\d+)\s+->\s+'
    r'(?P<destination_ip>[0-9a-fA-F\.\:]+):(?P<destination_port>\d+)\s+'
    r'(?P<protocol>[A-Z0-9]+)\s+'
    r'(?P<action>[A-Za-z]+)\s+'
    r'(?P<status_code>\d+)\s+'
    r'(?P<bytes_transferred>\d+)'
    r'(?:\s+"(?P<message>.*?)")?',
    re.MULTILINE
)
```

Listing 4.2: Syslog Regular Expression Pattern

The parsed data is cast into typed pandas columns: timestamps are converted to `datetime64[ns]`, ports and status codes to `int32`, and ports are cross-referenced against a standardized service dictionary (e.g., Port 22 → SSH, Port 80 → HTTP, Port 3389 → RDP, Port 445 → SMB).

4.3.2 Threat Detection Engine (`analyzer.py`)

Implements the core detection heuristics:

- **Threat Intelligence Correlation:** Cross-checks IP addresses against known malicious Tor exit nodes (e.g., `185.220.101.5`), Mirai botnet nodes (`194.26.29.112`), and CobaltStrike C2 controllers (`103.203.57.18`).
- **Web Attack Scanner:** Inspects the `message` column using regex patterns targeting:

  - SQL Injection: `' OR '1'='1`, `UNION SELECT`, `DROP TABLE`, `WAITFOR DELAY`.
  - Cross-Site Scripting: `<script>alert(1)</script>`, `javascript:`, `onerror=`.
  - Path Traversal: `../../etc/passwd`, `..%2fboot.ini`, `system32`.
  - Command Injection: `; cat /etc/shadow`, `| whoami`, `powershell.exe`.
- **DoS Flood Engine:** Identifies rapid request bursts exceeding 40 requests per 30-second window.

4.3.3 Interactive Web Dashboard (`app.py`)

Constructed using Streamlit and Plotly, the dashboard provides a cyber-defense command center themed in dark SOC styling (#0B0F19 background, JetBrains Mono typography). Key analytical views include:

- **Executive KPI Banners:** Total logs processed, total threats detected, network risk score meter, and total data throughput.
- **Visual Analytics:** Interactive temporal traffic histograms, Plotly attack-type sunburst diagrams, and Sankey protocol flows.
- **Threat Investigation Table:** Filterable alert table with dynamic severity badges and full evidence payloads.
- **Incident Response Playbooks:** Actionable containment checklists for each detected attack vector.

4.3.4 Forensic Report Generator Module (`report_generator.py`)

Utilizes ReportLab to programmatically generate audit artifacts:

- **Executive Summary Table:** Incident metadata, overall risk index, and severity counts.
- **Comprehensive Threat Evidence Registry:** Formatted tables listing timestamped attack events, affected IPs, evidence logs, and recommendations.
- **SIEM CSV Export:** Clean, schema-aligned CSV output suitable for ingestion into external security tooling.

4.3.5 Synthetic Attack Generator Module (`log_generator.py`)

Generates realistic multi-vector network traffic for testing, validation, and benchmarking. Supports configurable generation of legitimate background transactions interspersed with simulated attacks.

Chapter 5

RESULTS

5.1 Screenshots and Evaluation Results

To validate the detection fidelity and computational performance of the Network Log Analyzer, rigorous testing was conducted using multi-vector synthetic attack datasets generated by `log_generator.py` as well as real-world audit log samples. The evaluation benchmarked detection accuracy across six attack vectors.

Table 5.1: Threat Detection Accuracy and Evaluation Results

Attack Vector	Injected	Detected	Detection Rate (%)	False Positives
SSH / RDP Brute Force	12	12	100.0%	0
Multi-Port Reconnaissance	8	8	100.0%	0
Data Exfiltration (Volumetric)	5	5	100.0%	0
SQL Injection Payloads	15	15	100.0%	0
Cross-Site Scripting (XSS)	10	10	100.0%	0
Path Traversal / LFI	7	7	100.0%	0
Threat Intel Blacklisted IPs	6	6	100.0%	0
DoS Request Flooding	4	4	100.0%	0
Total / Average	**67**	**67**	**100.0%**	**0**

5.1.1 Performance Benchmarks

Execution latencies were measured across varying log volume increments on an Intel Core i5 processor with 8 GB RAM. As summarized in Table 5.2, the vectorized in-memory architecture processed 50,000 log records in under 1.6 seconds.

Table 5.2: Ingestion and Analysis Performance Latency

Log Record Count	Parse Latency (ms)	Analysis Latency (ms)	Peak Memory (MB)
500	14	8	22.4
2,500	58	26	28.1
10,000	210	94	45.6
25,000	520	240	78.2
50,000	1,080	490	136.0

5.1.2 System Screenshots and Interface Walkthrough

This section presents visual representations of the interactive graphical interfaces and reporting artifacts generated by the system.




Figure 5.1: Main Interactive Web Dashboard

5.2 Challenges Faced and Solutions

During system development and empirical validation, several domain-specific challenges were encountered and resolved:

1. **Challenge 1: Log Delimiter and Format Inconsistency:**
   Problem: Real-world network logs exhibit syntax disparities: firewalls output key-value strings, web servers use CLF/Combined format, and enterprise SIEMs export CSVs with arbitrary column headers.
   Solution: Implemented a two-tier parsing architecture. Tier 1 applies a fuzzy column dictionary normalizer mapping 25+ aliases (e.g., `SrcIP`, `Source IP`, `src_ip` to standard `source_ip`). Tier 2 employs a robust named-group regular expression with an automated fallback tokenization routine.

2. **Challenge 2: Algorithmic Complexity of Sliding Time-Window Analysis:**
   Problem: Naive sliding window algorithms comparing each timestamp against all other events exhibit $O(N^2)$ quadratic complexity, creating bottlenecks on large datasets.
   Solution: Optimized the detection algorithm to $O(N \log N)$ by first grouping records by source IP address and utilizing pre-sorted datetime indexes with boolean window filtering, reducing analysis duration by over 92%.




Figure 5.2: Brute Force & Port Scan Detection Alerts

3. **Challenge 3: Obfuscated Payloads in Web Exploits:**
   Problem: Attackers frequently encode malicious payloads using URL hex encoding (e.g., `%27` for single quote, `%2e%2e%2f` for path traversal) to evade simple substring filters.
   Solution: Incorporated pre-compiled regular expressions that match both raw character representations and hex-encoded equivalents in a single pass.

4. **Challenge 4: Portable and Documented Reporting Without External Tools:**
   Problem: Generating non-repudiable audit documents often requires external headless browsers or LaTeX servers, introducing heavy dependencies.
   Solution: Built a pure Python PDF compiler using `ReportLab` Flowables that calculates dynamic table column widths, enforces page wrapping, and embeds visual callouts without third-party dependencies.

Chapter 6

CONCLUSION

6.1 Conclusion

The mini project titled **"Network Log Analyzer for Security Auditing"** successfully achieved all formulated academic and engineering objectives. In response to the growing challenges of alert fatigue, high commercial SIEM licensing barriers, and complex log syntax variations, the project realized an autonomous, lightweight, and versatile security auditing pipeline tailored for academic labs and enterprise SOC teams.

The primary accomplishments of this work include:

- Developed a dual-mode parser capable of ingesting structured CSV logs and semi-structured Syslog/Firewall text streams.
- Implemented multi-vector detection algorithms incorporating temporal sliding windows and regular expressions, achieving a 100% true-positive detection rate on multi-attack test datasets.
- Integrated automated Threat Intelligence cross-referencing and contextual remediation playbooks.
- Engineered an interactive, responsive cybersecurity-themed SOC dashboard with real-time risk scoring.
- Formulated a one-click PDF forensic reporting system compliant with digital evidence audit standards.

The project underscores the viability of applying lightweight Python data-science frameworks to solve core cybersecurity and digital forensics challenges.

6.2 Future Enhancements

While the current framework provides robust forensic auditing capabilities, several avenues for future research and architectural enhancement remain:

1. **Unsupervised Machine Learning for Zero-Day Anomaly Detection:** Supplementing rule-based heuristics with unsupervised clustering (e.g., Isolation Forests, One-Class SVMs, or Autoencoders) to detect novel zero-day behavioral anomalies.

2. **Real-Time Wire Capture (eBPF / AF_PACKET Integration):** Expanding from offline log file ingestion to wire-speed kernel packet streaming via extended Berkeley Packet Filters (eBPF).

3. **Active Automated SOAR Response:** Integrating automated Security Orchestration, Automation, and Response (SOAR) webhooks to automatically push firewall blocking rules to perimeter equipment (e.g., `iptables`, Cisco ASA, or AWS Security Groups).

4. **Live Threat Intelligence API Ingestion:** Connecting live REST APIs (such as AlienVault OTX, AbuseIPDB, and VirusTotal) to fetch dynamic real-time IP reputation scores.

5. **Distributed Clustering for Big Data:** Porting the analytics engine to Apache PySpark or DuckDB for processing terabyte-scale enterprise log repositories across distributed clusters.

Chapter 7

REFERENCES & BIBLIOGRAPHY

[1] P. Cichonski, T. Millar, T. Grance, and K. Scarfone, "Computer Security Incident Handling Guide," *NIST Special Publication 800-61 Revision 2*, National Institute of Standards and Technology, Gaithersburg, MD, Aug. 2012.

[2] R. Gerhards, "The Syslog Protocol," *IETF RFC 5424*, Internet Engineering Task Force, Mar. 2009.

[3] MITRE Corporation, "MITRE ATT&CK® Matrix for Enterprise," *MITRE ATT&CK*, 2024. [Online]. Available: `https://attack.mitre.org/`

[4] OWASP Foundation, "OWASP Top 10: 2021 The Ten Most Critical Web Application Security Risks," *OWASP Foundation*, 2021. [Online]. Available: `https://owasp.org/Top10/`

[5] M. Roesch, "Snort - Lightweight Intrusion Detection for Networks," in *Proc. 13th USENIX Conf. on System Administration (LISA '99)*, Seattle, WA, 1999, pp. 229–238.

[6] V. Paxson, "Bro: A System for Detecting Network Intruders in Real-Time," *Computer Networks*, vol. 31, no. 23-24, pp. 2435–2463, Dec. 1999.

[7] R. Sommer and V. Paxson, "Outside the Closed World: On Using Machine Learning for Network Intrusion Detection," in *Proc. IEEE Symposium on Security and Privacy (SP)*, Oakland, CA, 2010, pp. 305–316.

[8] International Organization for Standardization, "Information technology — Security techniques — Guidelines for identification, collection, acquisition and preservation of digital evidence," *ISO/IEC 27037:2012*, Geneva, Switzerland, 2012.

[9] K. Kent and M. Souppaya, "Guide to Computer Security Log Management," *NIST Special Publication 800-92*, National Institute of Standards and Technology, Gaithersburg, MD, Sep. 2006.

[10] V. Chandola, A. Banerjee, and V. Kumar, "Anomaly Detection: A Survey," *ACM Computing Surveys*, vol. 41, no. 3, pp. 1–58, Jul. 2009.

[11] W. McKinney, "Data Structures for Statistical Computing in Python," in *Proc. 9th Python in Science Conf. (SciPy)*, Austin, TX, 2010, pp. 56–61.

[12] ReportLab Europe Ltd., "ReportLab PDF Generation User Guide," *ReportLab Open Source Documentation*, London, UK, 2023.