

Visual Studio

LIVE!

EXPERT SOLUTIONS FOR .NET DEVELOPERS

San Diego

Essential C# 8.0

Mark Michaelis

Nerd
IntelliTest

Level: Intermediate

Code Again for the First Time



Mark Michaelis

Chief Technical Architect,
Author, Trainer





Microsoft®
Most Valuable
Professional

Microsoft
Regional Director

Professional
Scrum Master II



If you were king, what would you do
with C#?



Nullable Reference Types

- Invoking a member on a null value will issue a `System.NullReferenceException` exception, and every invocation that results in a `System.NullReferenceException` in production code is a bug.
- With nullable reference types we “fall in” to doing the wrong thing rather than the right thing. (The “fall in” action is to invoke a reference type without checking for null.)
- There’s an inconsistency between reference types and value types (following the introduction of `Nullable<T>`) in that value types are nullable when decorated with “?” (for example, `int? number`); otherwise, they default to non-nullable.
- It’s not possible to run static flow analysis to check all paths regarding whether a value will be null before dereferencing it, or not.
- There’s no reasonable syntax to indicate that a reference type value of null is invalid for a particular declaration.
- There’s no way to decorate parameters to not allow null



What to do about it?

Provide syntax to expect null:

- Enable the developer to explicitly identify when a reference type is expected to contain nulls—and, therefore, not flag occasions when it's explicitly assigned null.

Make default reference types expect non-nullable:

- Change the default expectation of all reference types to be non-nullable, but do so with an opt-in compiler switch rather than suddenly overwhelm the developer with warnings for existing code.

Decrease the occurrence of `NullReferenceExceptions`:

- Reduce the likelihood of `NullReferenceException` exceptions by improving the static flow analysis that flags potential occasions where a value hasn't been explicitly checked for null before invoking one of the value's members.

Enable suppression of static flow analysis warning:

- Support some form of “trust me, I’m a programmer” declaration that allows the developer to override the static flow analysis of the compiler and, therefore, suppress any warnings of a possible `NullReferenceException`.



Demo

Conclusion: Nullable Reference Type

- Warning you to remove a null assignment to a non-nullable type potentially eliminates a bug because a value is no longer null when it shouldn't be.
- Alternatively, adding a nullable modifier improves your code by being more explicit about your intent.
- Over time the impedance mismatch between nullable updated code and older code will dissolve, decreasing the `NullReferenceException` bugs that used to occur.
- The nullability feature is off by default on existing projects so you can delay dealing with it until a time of your choosing. In the end you have more robust code. For cases where you know better than the compiler, you can use the `!` operator (declaring, "Trust me, I'm a programmer.") like a cast.
- Nullable types don't have any semantic impact, they only issue warnings.



Index

```
// Initialize new int[]{0, 1, 2, 3, 4, 5, 6, 7, 8}  
int[] array = Enumerable.Range(0, 9).ToArray();
```

```
lastItem = array[(array.Length - 1)];  
Assert.AreEqual(8, lastItem);
```

```
lastItem = array[new Index(1, true)];  
Assert.AreEqual(8, lastItem);
```

```
lastItem = array[^1];  
Assert.AreEqual(8, lastItem);
```



Index

```
Span<int> span;
```

```
span = array[Range.Create(4, new Index(2, true))];
Assert.AreEqual(new int[]{4, 5, 6}, span);
```

```
span = array[4..^2]; // array[Range.Create(4, new Index(2, true))]
Assert.AreEqual(new int[]{4, 5, 6}, span);
```

```
span = array[..^3]; // array[Range.ToEnd(new Index(3, true))]
Assert.AreEqual(new int[]{0, 1, 2, 3, 4, 5}, span);
```

```
span = array[2..]; // array[Range.FromStart(2)]
Assert.AreEqual(new int[]{2, 3, 4, 5, 6, 7, 8}, span);
```

```
span = array[Range.All()]; // array[Range.All()]
Assert.AreEqual(new int[]{0, 1, 2, 3, 4, 5, 6, 7, 8}, span);
```



System.Span<T>, System.Index, System.Range


The screenshot displays the API Explorer in Visual Studio, showing the definitions for `Span<T>`, `Range`, and `Index`.

- Span<T> (Generic Structure):**
 - Fields: `_length` As int
 - Properties: `Empty` As Span<T>, `IsEmpty` As bool, `Length` As int
 - Methods: `Equals()` As bool, `GetEnumerator()` As Enumerator, `GetHashCode()` As int, `implicit operator Span<T>()` As Span<T> (+ 1 overload)
 - Nested Types
- Range (Structure):**
 - Properties: `End` As Index, `Start` As Index
 - Methods: `All()` As Range, `Create()` As Range, `FromStart()` As Range, `Range()`, `ToEnd()` As Range
- Index (Structure):**
 - Fields: `_value` As int
 - Properties: `FromEnd` As bool, `Value` As int
 - Methods: `implicit operator Index()` As Index, `Index()`



Async Streams

Enabling LINQ Over Events



Async. Streams

```

IAsyncEnumerator<T> enumerator = enumerable.GetAsyncEnumerator();
try
{
    while (await enumerator.WaitForNextAsync())
    {
        while (true)
        {
            int item = enumerator.TryGetNext(
                out bool success);
            if (!success) break;
            Use(item);
        }
    }
}
finally { await enumerator.DisposeAsync(); }
  
```



With Syntax

```
foreach await (T item in enumerable)
{
    Use(item);
}
```



Default Interfaces

```
interface ITraceable
{
    static public int IndentationCount
    { get; set; }

    public string GetMessage() =>
        this.ToString();
}
```

- Explicit access modifiers would be permissible: `private`, `protected`, `internal`, `public` (the default is `public`).
- You could not have fields.
- Static methods, properties, indexers, and events would also be allowable.
- Modifiers `virtual`, `abstract`, `override`, `sealed`, and `extern` would be supported.



```
return switch (person)
{
    Professor(_, var lastName, var subject) item =>
        $"Dr. { lastName} teaching {subject}",
    Student { FirstName: var firstName,
        Advisor { LastName: var advisorLastName } } =>
        $"",
    (string firstName, _)
        { EnrollmentStatus: EnrollmentStatus.Enrolled } =>
        $"",
    { } => "Enrollment has passed. See you next year.",
    null => "Oh No!!"
}
```



What else...?

Null Coalescing Assignment

- Support `a??=b` in place of `if(a==null) a=b`

ReadOnly Instance Members:

- Provide a way to specify individual instance members on a struct do not modify state, in the same way that specifies no instance members modify state.

Target-typed new expressions:

- Allow field initialization without duplicating the type.
`Dictionary<string, List<int>> field =
 new() { { "item1", new() { 1, 2, 3 } } };`
- Allow omitting the type when it can be inferred from usage.
`XmlReader.Create(reader, new() { IgnoreWhitespace = true });`

Records

- A new, simplified declaration form for C# class and struct types
`public class Person(string Name, DateTime DateOfBirth);`




Mark Michaelis

Chief Technical Architect,
Author, Trainer

mark@IntelliTect.com

Twitter: @MarkMichaelis,
fb.com/MarkMichaelis



Professional
Scrum Master II



@IntelliTect, fb.com/IntelliTect