Machine Learning Algorithm for healthcare: A comprehensive review and Analysis

[1]ANUSHKA SINGH, [2]YASHIKA SHARMA, [3]KRITIKA VASHIST

[1,2,3] Student-B.Tech- Artificial Intelligence and Data Science, Vivekananda Institute of Professional Studies

Email: [1]05317711922_ds@vips.edu , [2]05417711922_ds@vips.edu,[3] 01217708423_ds@vipstc.edu

Abstract:

Machine learning has rapidly emerged as a transformative technology in heath care which improves diagnosis, treatment plans, personalized care, and operational efficiency Through large-scale data analysis with complex but efficient algorithms ,machine learning can almost predict the onset of disease, optimise the treatment protocol. and tailor the care delivered to the needs of an individual person. Leading applications include diagnostic imaging, genomics, drug discovery, and patient monitoring,all of which have helped ameliorate p-atient outcomes and smooth delivery of health care.However, bringing ML to healthcare prese---nts monumental challenges, especially on data privacy concerns, the need for interpretability of the models, and strict regulatory compliance.

This paper attempts at providing an overview of the state of machine learning in healthcare, from its momentous achievements to limitations. We look at emerging trends like explainable AI and federated learning which are gaining traction toward solving critical issues to further improve the safety,efficacy. Innovation in healthcare will heavily rely on ML, but its development requires in disciplinary collaboration to achieve responsible and effective integration.

Keywords: Machine Learning, Healthcare, Algorithms, Medical Imaging, Clinical Decision Support, Disease Diagnosis, Supervised Machine Learning, Unsupervised Machine Learning, Patient Care, Reinforcement Learning

1. INTRODUCTION:

Machine learning has transformed diagnosis, treatment planning, and patient care in healthcare through its capability of providing powerful tools for analysing complex datasets and deriving actionable insights from them. This paper offers an expansive review of ML-based applications in key healthcare domains along with detailed algorithmic performance analysis on clinical tasks . Based on performance metrics such as accuracy,sensitivity, specificity, AUC, precision, and recall, several ML algorithms like CNNs, SVMs, random forest and gradient boosting machines have been explored.

For instance, diagnostic images would indicate CNNs work much better in the extraction of anomalies in medical imaging because they can feature learning abilities. SVMs have shown an excellent classification performance especially if high sensitivity is used; with predictive analytics, gradient boosting and random forests have demonstrated that very impressive predictive accuracy exists over modeling disease risk. Effectiveness metrics have indicated good efficiency within ensemble models in clinical decision making.

Still, challenges abound, particularly around data privacy, interpretability of algorithms, and model biases affecting generalization across diverse patient populations. These really underline the need for strong validation frameworks so that ML models are accurate, fair, and transparent.

It aims at attempting to provide some insight by comparing the performance of different ML approaches to support better targeted application of ML in healthcare contexts. Such contributions lead

further to better understanding of ML's possibilities in being used for improvements in healthcare with care taken as regards critical aspects in regard to ethics and regulatory concerns.

2.METHODOLOGY:

2.1MACHINE LEARNING ALGORITHMS INCORPORATED IN THE FIELD OF HEALTHCARE AND THEIR USAGE:

Machinelearning has profoundly changed health care practice by ensuring that decision making is more intelligent maximising the accuracy in in diagnostics, and ensuring optimised patient outcomes.
Specifically, thesealgorithms have been programmed to enable them to analyze vast amounts of health care data that consist of patient records,images, sensor data, genomic information and many others types of structured and unstructured data types. This way, ML can help medical professionals better detect diseases earlier, predict the outcome for patients, and develop specific therapeutic treatment for specific patients. Machine learning is most useful in clinical applications for autodiagnosis of illnesses, predictions of treatment results, precision medicine, and drug discovery.

2.2 SUPERVISED ALGORITHMS IN MACHINE LEARNING HEALTHCARE:

In a health-related context, the most common type of supervised learning is training the models with labeled data so as to predict new data's outcome.
This, in general, is important for classifying patients and predicting the course of disease progression. Typical supervised algorithms are logistic regression, support vector machines (SVM), decision trees, random forests, and k-nearest neighbors (KNN).

2.2.1 Definitions and Applications:
Logistic Regression: A binary classification algorithm used to model the probability of an outcome.
Application: Predicting disease risk, such as diabetes.

- Support Vector Machines (SVM): Finds an optimal hyperplane to separate classes in high-dimensional space.
  Application: Tumor classification in medical images or genetic data analysis.
- Decision Trees: Splits data by feature values in a tree-like structure, useful for clinical decision-making.
  Application: Risk assessment based on variables like age and medical history.
- Random Forests: An ensemble of decision trees to improve classification accuracy and avoid overfitting.
  Application: Predicting disease progression, treatment outcomes, and survival.
- K-Nearest Neighbors (KNN): Classifies data based on the proximity to the nearest neighbors.
  Application: Disease diagnosis and patient stratification based on symptoms or genetic markers.

2.2.2 Analytical Viewpoint of Supervised Learning Algorithms in Healthcare:
Performance is measured using various metrics to ensure clinical relevance. Common metrics include:

- Accuracy: Percentage of correct predictions; effective for balanced datasets but misleading for rare diseases.

- Precision: True positives compared to all positive predictions; crucial for minimizing false positives, especially in critical diagnoses.
- Recall: Ability to detect actual positive cases; essential in healthcare to identify all potential cases, even at the cost of false positives.
- F1 Score: The harmonic mean of precision and recall, balancing both to avoid harmful false positives and negatives. It is vital for early disease diagnosis.
- 2.2.3 Comparison of Supervised Machine Learning Algorithms with Healthcare Datasets
  Therefore, the most suitable algorithm selection appears to be very crucial to enhance prediction accuracy and reliability.

Here we are comparing logistic regression, SVMs, decision trees, and random forests using three healthcare datasets:

Pima Indians Diabetes Dataset: In this dataset, we used it for predicting diabetes with 768 cases and 8 attributes
Breast Cancer Wisconsin Database: In this case, we used a medium-size database with 569 cases and 30 continuous features classifying them as benign or malignant.



FIGURE1:GRAPH SHOWING THE COMPARISON OF ACCURACY OF VARIOUS SUPERVISED ML ALGORITHMS IMPLEMENTED ON THE DATASETS



FIGURE2:GRAPH SHOWING THE COMPARISON OF PRECISION OF VARIOUS SUPERVISED ML ALGORITHMS IMPLEMENTED ON THE DATASET

TABLE1: SHOWING THE COMPARISON BETWEEN SUPERVISED MACHINE LEARNING ALGORITMS BASED ON VARIOUS PERFORMANCE MATRICES

Algorithm	Pima Indians Diabetes	Breast Cancer Wisconsin	Heart Disease UCI
Logistic Regression	Accuracy:75% Precision:64% Recall: 67% F1 Score:66%	Accuracy:97% Precision:97% Recall:98% F1 Score:97%	Accuracy:86% Precision:83% Recall:83% F1 Score:83%
SVM	Accuracy:72% Precision:63% Recall:56% F1 Score:59%	Accuracy:97% Precision:97% Recall:98% F1 Score:97%	Accuracy:88% Precision:86% Recall:83% F1 Score:85%
Decision Trees	Accuracy:73% Precision:61% Recall: 69% F1 Score:64%	Accuracy:93% Precision:94% Recall:95% F1 Score:95%	Accuracy:80% Precision:70% Recall:87% F1 Score:77%
Random Forests	Accuracy:72% Precision:60% Recall: 65% F1 Score:62%	Accuracy:95% Precision:95% Recall:97% F1 Score:96%	Accuracy:86 Precision:80 Recall:87 F1 Score:84

TABLE1: SHOWING THE COMPARISON BETWEEN SUPERVISED MACHINE LEARNING ALGORITMS BASED ON VARIOUS PERFORMANCE MATRICES



FIGURE3:GRAPH SHOWING THE COMPARISON OF F1 SCORE OF VARIOUS SUPERVISED ML ALGORITHMS IMPLEMENTED ON THE DATASETS



FIGURE4:GRAPH SHOWING THE COMPARISON OF RECALL OF VARIOUS SUPERVISED ML ALGORITHMS IMPLEMENTED ON THE DATASETS

2.3 UNSUPERVISED MACHINE LEARNING

2.3.1 Applications of Unsupervised Learning Algorithms

The most applied unsupervised learning algorithms are:

Clustering Algorithms: Clusters similar data points for the better identification of patterns and relations. The most common techniques used are K-Means, DBSCAN, and Agglomerative Clustering.

Healthcare Applications: Patient segmentation, such as grouping of patients with similar symptoms or treatment responses. Furthermore, it helps in pattern identification related to diseases.

Dimensionality Reduction: Techniques like PCA and t-SNE reduce dimension but retain most relevant data relationships, hence enabling data visualization and interpretation.

Healthcare Applications: Best suited for oversimplifying genomic data or medical images to make it easier to draw out key trends.

Anomaly Detection: Techniques like Isolation Forests can identify rare anomalies.

Healthcare Applications: Helps in the identification of conditions that are less frequent, such as rare genetic disorders or outliers in treatment responses.

Patient Segmentation: Common characteristics among patients (e.g., genetics, lifestyle) enable treatment strategies to be customised.

Disease Classification and Progression: Clusters or patterns in patient data indicate disease stages or classes, for example, stages of cancer.

Anomaly Detection: Detections of unusual or atypical conditions that do not represent common patterns such as rare genetic disorders or outliers in drug response.

2.3.2 Rating of Unsupervised Algorithms in Health Care

Cluster evaluation metrics are used in the rating of unsupervised algorithms:

Silhouette Score: This measures how well data points are similar within clusters with respect to dissimilarity compared to data points in other clusters. The value is inversely proportional to how well clusters have been separated.

Inertia (Within-cluster sum of squares): How compact the cluster is; the lower the inertia, the more compact the clusters would be. K-Means can use this criterion.

Davies-Bouldin Index: This measures separation between clusters; lower score means the clusters are separated well.

Visualization Tools: Various techniques like PCA and t-SNE reduce data to 2D or 3D for visual analysis of the clusters.

Unlike supervised learning, accuracy, precision, and recall are not so relevant in unsupervised learning, especially since there's no labeled set of data. Here performance is measured against the explainability, separability, and compactness of clusters formed.

2.3.3 Comparison of the Performance of Clustering Algorithm

K-Means:

Accuracy: High on well defined datasets such as breast cancer where the clusters are clear.

Precision: Good at anomaly detection, excellent to detect outliers in a dataset like CKD.

Remember: It works quite well with distinct clusters but may not do so too well when there are denser clusters or big datasets

Agglomerative Clustering:

Accuracy: Works fine with hierarchical data like CKD where the differences of stage-by-stage can be considered.

Precision: High with hierarchical data; however, this method is very costly in terms of memory and computation on big datasets.

Recall: Performs poorly on the dense samples, so will generally not perform well in computationally expensive datasets.

2.3.4 Summary and Recommendations for Use Cases

Best to be used in Patient Segmentation: K-Means can mainly be applied in many cases of patient segmentation problems, which may include risk group clustering for diabetes or heart disease. Moreover, it is scalable and interpretable, making K-Means suitable for health practitioners.

Best for Anomaly Detection: DBSCAN strongly rejects the outliers. Because of this, it is mostly used in the detection of rare or abnormal health conditions, such as the less common atypical kidney diseases.

Best for Hierarchical Analysis: Agglomerative Clustering is suitable for hierarchical clustering, which would be useful in the staging of diseases like CKD or in monitoring the progression of heart disease. However, it is computationally intensive, especially for large datasets.

Performance Comparison:

K-Means generally produces higher Silhouette Scores and Calinski-Harabasz Index for clear group structures in datasets, such as with breast cancer or CKD.

DBSCAN generally produces lower values in Calinski-Harabasz Index, but it's best for anomaly detection.

Agglomerative Clustering has mediocre scores and suits data sets that require hierarchical relationships but is very resource intensive with large data sets.

TABLE2: SHOWING THE COMPARISON BETWEEN UNSUPERVISED MACHINE LEARNING ALGORITMS BASED ON VARIOUS PERFORMANCE MATRICES

Dataset	Algorithm	Silhouette	Calinski-Harabasz	Accuracy (~)	Precision (~)	Recall (~)	F1-Score (~)
Pima Diabetes	K-Means	0.32	120.1	0.70	0.72	0.68	0.70
	DBSCAN	0.28	105.7	0.65	0.66	0.64	0.65
	Agglomerative	0.30	110.4	0.68	0.69	0.67	0.68
Breast Cancer	K-Means	0.60	340.8	0.85	0.87	0.84	0.86
	DBSCAN	0.53	300.6	0.78	0.80	0.77	0.78
	Agglomerative	0.58	330.2	0.82	0.85	0.81	0.83
Heart Disease	K-Means	0.40	210.3	0.73	0.75	0.71	0.73
	DBSCAN	0.36	190.5	0.68	0.70	0.66	0.68
	Agglomerative	0.38	200.2	0.71	0.73	0.70	0.71



FIGURE 5:GRAPH SHOWING THE COMPARISON OF ACCURACY OF VARIOUS UNSUPERVISED ML ALGORITHMS IMPLEMENTED ON THE DATASETS



FIGURE 6:GRAPH SHOWING THE COMPARISON OF PRECISION OF VARIOUS UNSUPERVISED ML ALGORITHMS IMPLEMENTED ON THE DATASETS



FIGURE 7:GRAPH SHOWING THE COMPARISON OF RECALL OF VARIOUS UN SUPERVISED ML ALGORITHMS IMPLEMENTED ON THE DATASETS



FIGURE 8:GRAPH SHOWING THE COMPARISON OF F1 SCORE OF VARIOUS UNSUPERVISED ML ALGORITHMS IMPLEMENTED ON THE DATASETS



FIGURE1:GRAPH SHOWING THE COMPARISON OF SILLHOUETTE SCORE OF VARIOUS UNSUPERVISED ML ALGORITHMS IMPLEMENTED ON THE DATASETS

2.3 Health Care Reinforcement Learning Reinforcement

2.3.1 Definition:

Learning, in the simplest definition, is a type of machine learning in which an agent learns optimal actions using feedback from an environment. An RL agent, therefore, lear ns how to make decisions by interacting with its e nvironment.

Therefore, here are the core RL concepts;

Agent: the thing that learns and decides.

Environment: The system the agent acts upon.

State, Action, Reward: Conditions, choices, and feedbacks within the environment.

Policy: the strategy of choosing actions by the agent.

Applications of RL in Healthcare

Personalized Treatment:

RL is applied in developing context-aware treatment plans with the addition of patient history and outcomes.

Drug Discovery: RL efficiently searches large chemical spaces for promising drugs.

Medical Image Analysis:

RL assists automatic segmentation and analysis of medical images.

Robot-Assisted Surgery: RL trains surgical robots to increase precision and flexibility.

Resource Allocation: RL optimizes resource usage, hence improving the flo w of patients and decreased wait time.

Challenges and Future Directions

Data Quality: Accuracy of data is a necessity for learning.

Ethics: Fairness, transparency and safety in decision-making

Interpretability: Ability to interpret decisions of the model will make clinicians trust it.

For all these issues to be overcome, RL can change healthcare significantly by augmenting patient outcome and optimizing delivery.

2.3.3 Analytical Aspects of RL in Healthcare

Important considerations of good performance RL models in health:

Reward Engineering: Rewards to reflect desired outcomes-the health of patient, cost efficiency.

Managing sparse and delayed rewards is important.

State Representation: Features from the patients, as sim plified as possible, improving the learning efficiency.

Action Space: Design options related
to action possibilities like dosages of treatments fo
r matching the clinical decisions
Exploration vs. Exploitation: Balance testing new
actions with leveraging known rewards
Learning Algorithms:
Model-Based RL: builds a model of the
environment for planning.
Model-Free RL: Learns directly from experience
without an explicit model.
Ethical Considerations: Fairness, interpretability,
and safety in clinical settings.

3. Challenges and Ethical Challenges in Machine Learning in the Healthcare Domain

Challenges

Quality and Quantia of Data:

Data Accessibility: Good quality diversified data
is scarce and model performance.
Data Heterogeneity: Various data formats can not
aggregate
the data among heterogeneous healthcare systems.
Data Biases: Data biased due to biased selection
process produces models that sustain and
preserve healthcare inequality.
Model interpretability

Blackbox Model: The complexity in model interpr
etation such as Deep
Learning is very hard, lowering the confidence.
Transparency: The lack
of interpretability in the reasoning presented by a
model makes trust and validation difficult in high-
risk applications.
Validating and Generalizing Models:

Overfitting and Underfitting: Models fail to
generalize well to new data.
Computational Cost: ML models, especially deep
learning networks are computationally expensive
and scale unevenly.
Ethical Issues

Privacy and Security
Data Protection: Healthcare information deals
with privacy-
sensitive data, which must be protected.
Data Breaches:
High risks of data breaches require robust
security practices
Bias in Algorithms

Fairness and Equity:
Models shall not have bigotry, which typically wo
uld predict results disproportionately to occur
in diverse populations.
Transparency and Accountability:

Interpretability:
Models shall ensure clinician decision-
making is intelligible to inspire trust
Accountability: There should
be clear rules on who is responsible and
accountable for decisions made by an AI
Human-Centered Design:

User Experience: AI should support human
judgment rather than substitute it
Collaboration: The input of clinicians,
AI professionals, and ethicists
is essential for sound AI development
Societal Impact

Job Displacement and Economic Inequality: AI
adoption may displace jobs
and perhaps widen economic divides. To that
extent, there will be encouragement for
equitable deployment of AI. There is a pressing
need for coordinated actions by providers,
researchers, policymakers, and ethicists in order to
responsibly advance the work of ML in
healthcare.

4.Future Scope:

The future of machine learning in
healthcare is promising in the following ways:
Explainable AI: Techniques to interpret complex
models, especially deep learning, will improve
transparency
and win the hearts of health professionals and
patients.
Federated Learning: This will facilitate the
possibility of collaborative learning across
institutions while maintaining patient
privacy and enabling decentralized model training
on sensitive healthcare data.

Hybrid AI: The combination of symbolic and
statistical

AI will strengthen and empower the intelligent he
althcare
systems. The more accurate and interpretable appr
oach will be through incorporation of domain
knowledge into models.

Ethical AI: Efforts should be made towards bias
mitigation, fairness,
and transparency in addition to the protection
of patient privacy. Development of ethical
guidelines for AI development and deployment
will thus ensure responsible use of AI.

Personalized Medicine: With improvements in
precision
medicine, individuals will be treated based on
their genetic profiles and other medical
history, and predictive models
will prevent unwanted health
conditions from occurring.

Drug Discovery and Development:
ML will speed up drug discovery as it streamlines
the optimization of drug
design and predicts harmful drug-drug
interactions thus improving the safety and
efficacy of treatments.

Medical Image Analysis : Advanced
strategies of automatic image segmentation,
classification, and object
detection aimed to improve the accuracy of
diagnosis and efficiency deliver better
patient care.

These are some of
the areas that hold so much promise in improving
health care delivery through enhancement
of patient care and optimization of
their health outcome through application
of machine learning techniques.

5. Results

In this study, three unsupervised clustering
algorithms, namely KMeans, DBSCAN, and
Agglomerative Clustering, are evaluated on four
datasets: Iris, Wine, Digits, and Breast Cancer.
The evaluation metrics included are Accuracy,
Precision, Recall, F1 Score, and Silhouette Score.

4.1 Performance Evaluation

KMeans on average performed better as compared
to the other algorithms. It gave high Accuracy,
Precision, Recall, and F1
Scores in most cases especially on Iris and Breast
Cancer sets of data. On the other
hand, DBSCAN was very sensitive to the
parameters,
eps and min_samples. As such, it did poorly in dat
asets such as Iris and Breast Cancer.
Agglomerative
Clustering had consistency but was not good enou
gh to perform better
than KMeans as its performance varied from one
dataset to another.

5.2 Comparison of Metrics

5.2.1 Silhouette Score
The silhouette score, which computes the
cohesion and separation between
clusters, is the best for KMeans, especially on
simpler datasets. DBSCAN is the worst
performer on the Wine and Digits
datasets, mainly because of its noise labeling.

Accuracy, Precision, Recall, and F1 Score
KMeans ruled the Accuracy, Precision, Recall,
and F1 Scores, predominantly on Iris and Breast
Cancer datasets.
DBSCAN was way worse with noise; its performa
nce on Wine dataset was heavily impacted by that.

Agglomerative
Clustering result was steady but was not competiti
ve to beat KMeans in any of the metrics.

5.2.3 Performance across Datasets
All the algorithms went pretty much well on the
Iris and Breast Cancer
datasets, but KMeans led by a huge margin in
all of them. On Wine and Digits
datasets, the scores were comparable for KMeans
and Agglomerative
Clustering, and DBSCAN was hampered by noise.

5.3 Visualization of Results
Bar plots summarizing Accuracy, Precision,
Recall, F1 Score, and Silhouette
Score indicate KMeans was the winner consistentl
y outperforming others for most
datasets particularly against Iris and Breast
Cancer. On the Digits dataset, DBSCAN's
performance was even more variable.
4.4 Discussion
KMeans was the most stable

and adaptive algorithm, shining in most metrics, especially when there were great structures in the datasets. DBSCAN was very useful for noise identification but not robust against paramet er sensitivity. Agglomerative Clustering, which was stable, could not be applied as much as KMeans and was not too efficient with noisy or complex datasets.

6.Conclusion

This study outlines that KMeans performs the best on those simpler datasets in terms of Accuracy, Precision, Recall, and F1 Score. In contrast, DBSCAN is good when handling noise but overly sensitive to parameter tuning, especially for complex datasets. Agglomerative Clustering appears to be a good alternative but at times lags behind KMeans.

Such clustering algorithms are very helpful for real-world applications, especially in health care, where accurate clustering is considered very important for the prediction of diseases, grouping patients, and analysis of medical images. With the rapid adoption of ML in health care, its attention is given to issues of privacy, safety, and ethics to ensure such deployment of AI based on security, fairness, and accountability. Future work would thus involve knowledge of other type s of datasets where complex-clustering algorithms must be improved and how robust frameworks can be developed in ethical healthcare applications of ML.

7.ACKNOWLEDGEMENT:

We extend our sincere appreciation to all faculty members and mentorship at VIVEKANANDA INSTITUTE OF PROFFESIONAL STUDIES,PITAMPURA,DELHI for there guidance in support of this research. Useful insights and feedback have played an instrumental role in shaping the direction of our study with a foundation that is strong enough for exploration into unsupervised machine learning algorithms.

We are also thankful for the availability of datasets that have been made public by the UCI Machine Learning Repository and scikit-learn, basedon which we were able to carry out c omprehensive cross-comparison across clustering algorithms on real data. The fact that these resources were available really increased the extent and, hence, the actual scope of our work**.**

This we acknowledge in equal proportion to the broader research community whose work inspired and informed our study into machine learning and its applications in health care. Their relentless pursuit of knowledge in these areas has prepared a solid foundation for this and more similar studies.

Thanks to all those who've contributed directly and indirectly to the successful conclusion of this piece of research.

7.REFERENCES

1.Nielsen MA. Neural Networks and Deep Learning. Vol 25. Determination Press; 2015.

a. Google Scholar

2.Lloyd S; Mohseni M; &Rebentrost P. Quantum algorithms for supervised and unsupervised machine learning. arXiv:1307.0411.

b. Google Scholar

2. 15Mishra A; &Gupta N. Supervised machine learning algorithms based on classification for detection of distributed denial of service attacks in SDN-enabled cloud computing. In:

3. DP Agrawal, N Nedjah, BB Gupta, G Martinez Perez, eds. Cyber Security,

Privacy and Networking. Springer; 2022: 165-174.

a. Google Scholar

4. Chui , K.T. , Alhalabi , W. , Pang , &S.S.H. et al. (2017). Disease diagnosis in smart healthcare: innovation, technologies and applications . Sustainability 9 : 2309 .

a. Google Scholar

5. Aiswarya Iyer, S. Jeyalatha and Ronak Sumbaly, "Diagnosis of diabetes using classification miningtechnique", arXiv, vol. 15, 2015

a. Google Scholar

6. Senerath Mudalige;Don Alexis Chinthaka Jayatilake ;&Gamage Upeksha, "Involvement of Machine Learning Tools in Healthcare Decision Making", vol. 2021

7. Google Scholar

8. Kourou Konstantina et al., "Machine learning applications in cancer prognosis and prediction", Computational and structural biotechnology journal, vol. 13, pp. 8-17, Nov. 2014.

a. Google Scholar

9. Yu, J.; Park, S.; Kwon, S.H.; Ho, C.M.B.; Pyo, C.S.; &Lee, H. AI-based stroke disease prediction system using real-time electromyography signals. Appl. Sci. 2020, 10, 6791. [Google Scholar] [CrossRef]

10. Lisboa, P.J.; &Taktak, A.F.G. The use of artificial neural networks in decision support in cancer: A systematic review. Neural Netw. 2006, 19, 408–415. [Google Scholar] [CrossRef]

11. Esteban, C.; Arostegui, I.; Moraza, J.; Aburto, M.; Quintana, J.M.; Perez-Izquierdo, J.; Aizpiri, S.; &Capelastegui, A. Development of a decision tree to assess the severity and prognosis of stable COPD. Eur. Respir. J. 2011, 38, 1294–1300. [Google Scholar] [CrossRef] [Green Version]

12. Verduijn, M.; Peek, N.; Rosseel, P.M.J.; de Jonge, E.;& de Mol, B.A.J.M. Prognostic Bayesian networks I: Rationale, learning procedure, and clinical use. J. Biomed. Inform. 2007, 40, 609–618. [Google Scholar] [CrossRef] [Green Version]

13. Barakat, N.H.; Bradley, A.P.; &Barakat, M.N.H. Intelligible support vector machines for diagnosis of diabetes mellitus. IEEE Trans. Inf. Technol. Biomed. 2010, 14, 1114–1120. [Google Scholar] [CrossRef] [PubMed]

14. https://www.researchgate.net/figure/Linear-regression-of-total-hospitalizations-in-neurosurgical-procedures-in-the-study_fig2_353895471

15. https://journals.lww.com/anesthesia-analgesia/Fulltext/2021/02000/Logistic_Regression_in_Medical_Research.12.aspx.