

Assignment 1:

1. Query : CREATE DATABASE spj;

```
[mysql> CREATE DATABASE spj;
Query OK, 1 row affected (0.01 sec)

[mysql> show databases;
+-----+
| Database |
+-----+
| information_schema |
| mysql |
| performance_schema |
| spj |
| sys |
+-----+
5 rows in set (0.00 sec)
```

2. Query : USE spj;

```
mysql> show databases;
+-----+
| Database |
+-----+
| information_schema |
| mysql |
| performance_schema |
| spj |
| sys |
+-----+
5 rows in set (0.00 sec)

[mysql> USE spj;
Database changed
```

3. Query : CREATE TABLE S (`S` CHAR(5) NOT NULL, Sname CHAR(20), status SMALLINT, city CHAR(15));

```
[mysql> USE spj;
Database changed
[mysql> CREATE TABLE S (`S` CHAR(5) NOT NULL, Sname CHAR(20), status SMALLINT, city CHAR(15));
Query OK, 0 rows affected (0.02 sec)
```

4. Query : INSERT INTO S(`s`,Sname,status,city) VALUES ('S1','Smith',20,'London');

```
mysql> INSERT INTO S(`s`,Sname,status,city) VALUES ('S1','Smith',20,'London');
Query OK, 1 row affected (0.02 sec)
```

5. Query : INSERT INTO S(`s`,Sname,status,city)
VALUES('S2','Jones',10,'Paris'), ('S3','Blake',30,'Paris'),
('S4','Clark',20,'London'),('S5','Adams',30,'Athens');

```
mysql> INSERT INTO S(`s`,Sname,status,city) VALUES('S2','Jones',10,'Paris'), ('S3','Blake',30,'Paris'),('S4','Clark',20,'London'),('S5','Adams',30,'Athens');
Query OK, 4 rows affected (0.01 sec)
Records: 4 Duplicates: 0 Warnings: 0

mysql> SELECT * FROM s;
+----+-----+-----+-----+
| S  | Sname | status | city  |
+----+-----+-----+-----+
| S1 | Smith | 20     | London |
| S2 | Jones | 10     | Paris  |
| S3 | Blake | 30     | Paris  |
| S4 | Clark | 20     | London |
| S5 | Adams | 30     | Athens |
+----+-----+-----+-----+
5 rows in set (0.01 sec)
```

6. CREATE TABLE P (`P` CHAR(6) NOT NULL, Pname CHAR(20),
color CHAR(6), weight SMALLINT, city CHAR(15));

```
mysql> CREATE TABLE P (`P` CHAR(6) NOT NULL, Pname CHAR(20), color CHAR(6), weight SMALLINT, city CHAR(15));
Query OK, 0 rows affected (0.03 sec)

mysql> DESC P;
+----+-----+-----+-----+-----+-----+
| Field | Type      | Null | Key | Default | Extra |
+----+-----+-----+-----+-----+-----+
| P     | char(6)   | NO   |     | NULL    |       |
| Pname | char(20)  | YES  |     | NULL    |       |
| color | char(6)   | YES  |     | NULL    |       |
| weight | smallint | YES  |     | NULL    |       |
| city  | char(15)  | YES  |     | NULL    |       |
+----+-----+-----+-----+-----+-----+
5 rows in set (0.01 sec)
```

INSERT INTO P(`p`,Pname,color,weight,city) VALUES(`p1`, 'Nut' , 'Red' ,12,
'London') , (`p2`, 'Bolt' , 'Green' ,17, 'Paris'), (`p3`, 'Screw' , 'Blue' ,17, 'Rome'),
(`p4`, 'Screw' , 'Red' ,14, 'London') , (`P5`, 'Cam' , 'Blue' ,12, 'Paris') , (`P6`,
'Cag' , 'Red' ,19, 'London');

```
mysql> INSERT INTO P(`p`,Pname,color,weight,city) VALUES('p1', 'Nut' , 'Red' ,12, 'London') , ('P5', 'Cam' , 'Blue' ,12, 'Paris') , ('P6', 'Cag' , 'Red' ,19, 'London');
Query OK, 6 rows affected (0.02 sec)
Records: 6 Duplicates: 0 Warnings: 0

mysql> SELECT * FROM P;
+----+-----+-----+-----+-----+
| P  | Pname | color | weight | city  |
+----+-----+-----+-----+-----+
| p1 | Nut   | Red   | 12     | London |
| p2 | Bolt  | Green | 17     | Paris  |
| p3 | Screw | Blue  | 17     | Rome   |
| p4 | Screw | Red   | 14     | London |
| P5 | Cam   | Blue  | 12     | Paris  |
| P6 | Cag   | Red   | 19     | London |
+----+-----+-----+-----+-----+
```

CREATE TABLE J (`J` CHAR(4) NOT NULL, Jname CHAR(10), City
CHAR(15));

```
mysql> CREATE TABLE J (`J` CHAR(4) NOT NULL, Jname CHAR(10), City CHAR(15));
Query OK, 0 rows affected (0.02 sec)
```

```
mysql> DESC J;
```

Field	Type	Null	Key	Default	Extra
J	char(4)	NO		NULL	
Jname	char(10)	YES		NULL	
City	char(15)	YES		NULL	

3 rows in set (0.00 sec)

```
INSERT INTO J(`J`,Jname,City) VALUES ('J1','Sorter','Paris'),
('J2','Punch','Rome'),('J3','Reader','Athens'),('J4','Console','Athens'),
('J5','Collator','London'),('J6','Terminal','Oslo'),('J6','Tape','London');
```

```
mysql> INSERT INTO J(`J`,Jname,City) VALUES ('J1','Sorter','Paris'),('J2','Punch','Rome'),('J3','Reader','Athens'),('J4','Console','Athens'),('J5','Collator','London'),('J6','Terminal','Oslo'),('J6','Tape','London');
Query OK, 7 rows affected (0.01 sec)
Records: 7 Duplicates: 0 Warnings: 0

mysql> SELECT * FROM J;
```

J	Jname	City
J1	Sorter	Paris
J2	Punch	Rome
J3	Reader	Athens
J4	Console	Athens
J5	Collator	London
J6	Terminal	Oslo
J6	Tape	London

7 rows in set (0.00 sec)

```
CREATE TABLE sp(`S` CHAR(4) NOT NULL,`P` CHAR (4) NOT NULL, `J` CHAR(4) NOT NULL ,QRY INT);
```

```
mysql> CREATE TABLE sp(`S` CHAR(4) NOT NULL,`P` CHAR (4) NOT NULL, `J` CHAR(4) NOT NULL ,QRY INT);
Query OK, 0 rows affected (0.02 sec)
```

```
mysql> DESC sp;
```

Field	Type	Null	Key	Default	Extra
S	char(4)	NO		NULL	
P	char(4)	NO		NULL	
J	char(4)	NO		NULL	
QRY	int	YES		NULL	

4 rows in set (0.02 sec)

```
D5_99253_AnushreeDesai>INSERT INTO sp(S,P,J,QRY) VALUES('S1','P1','J1',200);
Query OK, 1 row affected (0.01 sec)

D5_99253_AnushreeDesai>INSERT INTO sp(S,P,J,QRY) VALUES('S1','P1','J1',200),('S1','P2','J4',700),('S2','P3','J1',400),('S2','P3','J2',200),('S2','P3','J3',200);
Query OK, 5 rows affected (0.00 sec)
Records: 5 Duplicates: 0 Warnings: 0

D5_99253_AnushreeDesai>INSERT INTO sp(S,P,J,QRY) VALUES('S2','P3','J4',500),('S2','P3','J5',600),('S2','P3','J6',400),('S2','P3','J7',800),('S2','P5','J2',100);
Query OK, 5 rows affected (0.00 sec)
Records: 5 Duplicates: 0 Warnings: 0

D5_99253_AnushreeDesai>INSERT INTO sp(S,P,J,QRY) VALUES('S3','P3','J1',200),('S3','P4','J2',500),('S4','P6','J3',300),('S4','P6','J7',300),('S5','P2','J2',200);
Query OK, 5 rows affected (0.00 sec)
Records: 5 Duplicates: 0 Warnings: 0

D5_99253_AnushreeDesai>INSERT INTO sp(S,P,J,QRY) VALUES('S5','P2','J4',100),('S5','P5','J5',500),('S5','P5','J7',100),('S5','P6','J2',200),('S5','P1','J4',100);
Query OK, 5 rows affected (0.00 sec)
Records: 5 Duplicates: 0 Warnings: 0

D5_99253_AnushreeDesai>INSERT INTO sp(S,P,J,QRY) VALUES('S5','P3','J4',200),('S5','P4','J4',800),('S5','P5','J4',400),('S5','P6','J4',500);
Query OK, 4 rows affected (0.01 sec)
Records: 4 Duplicates: 0 Warnings: 0

D5_99253_AnushreeDesai>SELECT * FROM sp;
+-----+
| S | P | J | QRY |
+-----+
| S1 | P1 | J1 | 200 |
| S1 | P1 | J1 | 200 |
| S1 | P2 | J4 | 700 |
| S2 | P3 | J1 | 400 |
| S2 | P3 | J2 | 200 |
| S2 | P3 | J3 | 200 |
| S2 | P3 | J4 | 500 |
| S2 | P3 | J5 | 600 |
| S2 | P3 | J6 | 400 |
| S2 | P3 | J7 | 800 |
| S2 | P5 | J2 | 100 |
| S3 | P3 | J1 | 200 |
| S3 | P4 | J2 | 500 |
| S4 | P6 | J3 | 300 |
| S4 | P6 | J7 | 300 |
| S5 | P2 | J2 | 200 |
| S5 | P2 | J4 | 100 |
| S5 | P5 | J5 | 500 |
| S5 | P5 | J7 | 100 |
| S5 | P6 | J2 | 200 |
| S5 | P1 | J4 | 100 |
| S5 | P3 | J4 | 200 |
```