


Name: Neha T

Phone No: 6363873432

email: nehat6003@gmail.com

Pentagon ID: PS19FEB0F 25 JFS061



1. Register.jsp

```
<form action="register" method="post">  
<input type="text" name="id" required />  
Name: <input type="text" name="name" />  
Email <input type="text" name="email" required />  
Mobile: <input type="text" name="phone" required />  
Address: <input type="text" name="address" required />  
Password: <input type="password" name="pswd" required />  
Confpassword: <input type="password" name="confpswd" required />  
<input type="submit" name="register" value="Register" />  
</form>
```

register.java (Servlet).

@WebServlet (name="register", urlPatterns={"/register"})

public class register extends HttpServlet

protected void doPost (HttpServletRequest req, HttpServletResponse res) throws ServletException,

IOException {

HttpSession session = req.getSession();

Register reg = new Register (session);

if (req.getParameter("register") != null) {

String name = req.getParameter("name");

String email = req.getParameter("email");

String phone = req.getParameter("phone");

String address = req.getParameter("address");

String pswd = req.getParameter("pswd");

String Confpswd = req.getParameter("confpswd");

if (pswd.equals(Confpswd)) {

String status = req.Registration(name, email, phone, address, pswd);

if (status.equals("exited")) {

req.setAttribute("status", "Already Registered");

RequestDispatcher rd = req.getRequestDispatcher("login.jsp");
rd.forward(req, resp);

else if (status.equals("success")) {

req.setAttribute("status", "Registered Successfully");

RequestDispatcher rd = req.getRequestDispatcher("login.jsp");
rd.forward(req, resp);

else if (status.equals("failure")) {

req.setAttribute("status", "failed to register");

RequestDispatcher rd = req.getRequestDispatcher("Register.jsp");
rd.forward(req, resp);

Model - Register.java

```
class Register {
```

```
    HttpSession session
```

```
    private Connection con;
```

```
    public Register(HttpSession session) {
```

```
        try {
```

```
            Class.forName("com.mysql.cj.jdbc.Driver");
```

```
            con = DriverManager.getConnection("jdbc:mysql://localhost:3306/Food", "root", "tiger");
```

```
        } catch (Exception e) {
```

```
            e.printStackTrace();
```

```
        }
```

```
    }
```

```
    public String Registration(name, phone, email, address, password) {
```

```
        Statement st = null;
```

```
        String status = "";
```

```
        PreparedStatement ps = null;
```

```
        ResultSet rs = null;
```

```
        try { String query = "Select * from base Customer where  
            name = '" + name + "', phone = '" + phone + "',  
            email = '" + email + "' address = '" + address + "',  
            password = '" + password + "'";
```

```
        try {
```

```
            st = con.createStatement();
```

```
            boolean rs = st.executeQuery(query);
```

```
            if (rs.next()) {
```

```
                status = "exist";
```

```
            }
```

else {

ps = con.prepareStatement ("Insert into Customer values
(0, ?, ?, ?, ?, ?)");

int a = ps.executeUpdate ();

if (a > 0) {

status = "success";

}

else {

status = "failure";

}

}

catch (Exception e) {

e.printStackTrace ();

}

return status;

}

• Login.jsp •

<% String status = (String) request.getAttribute ("status");

if (status != null) { %>

<% = status %>

<% } %>

<form action="register" method="post">

Email

<input type="text" name="email" required />

Password

<input type="text" name="pwd" required />

<input type="submit" name="login" value="Login">

</form>

register.java (Servlet) (Controller)

```
else if (req.getParameter("login") != null) {
    String email = req.getParameter("email");
    String password = req.getParameter("pswd");
    Customer c = req.login(email, password);

    if (c != null) {
        req.setAttribute("customer", c);
        if (c.getId() == 1) {
            req.setAttribute("status", "logged in as Admin");
            RequestDispatcher rd = req.getRequestDispatcher("Admin.jsp");
            rd.forward(req, resp);
        }
        else {
            req.setAttribute("status", "logged as Normal Customer");
            RequestDispatcher rd = req.getRequestDispatcher("Customer.jsp");
            rd.forward(req, resp);
        }
    }
    else {
        req.setAttribute("status", "No Customer Found");
        RequestDispatcher rd = req.getRequestDispatcher("Register.jsp");
        rd.forward(req, resp);
    }
}
```

Model - Register.java

```
public Customer login (String email, String password){
```

```
    PreparedStatement ps = null;
```

```
    String query = "select * from Customer where email = ? + email  
password" + password + " ?";
```

```
    Customer c = null;
```

```
    try {
```

```
        ps = con.prepareStatement (query);
```

```
        ps.setString (1, email);
```

```
        ps.setString (2, password);
```

```
        = ps.executeUpdate();
```

```
        ResultSet rs = ps.executeQuery();
```

```
        if (rs.next()) {  
            Customer c = new Customer;
```

```
            c.setId (rs.getInt ("id"));
```

```
            c.setName (rs.getString ("name"));
```

```
            c.setPhone (rs.getString ("phone"));
```

```
            c.setEmail (rs.getString ("email"));
```

```
            c.setAddress (rs.getString ("address"));
```

```
            c.setPassword (rs.getString ("password"));
```

```
        }
```

```
        else {
```

```
            return null;
```

```
        }
```

```
        return c;
```

```
    }
```

```
}
```

Customer Module

Edit profile

Edit.jsp

```
<% String status = (String) request.getAttribute("status");  
    if (status != null) { %>  
        <% = status %>  
  
<% } %>  
  
<% Customer c = (Customer) request.getAttribute("customer"); %>  
<form action="register" method="post">  
    <input type="hidden" name="id" value="<% = c.getId %>" %>  
    <input type="text" name="name" value="<% c.getName %>" %>  
    <input type="text" name="email" value="<% c.getEmail %>" %>  
    <input type="text" name="phone" value="<% c.getPhone %>" %>  
    <input type="text" name="address" value="<% c.getAddress %>" %>  
    <input type="submit" name="edit" value="Edit Profile" %>  
</form>
```

Register.java (Servlet)

```
else if (req.getParameter("edit") != null) {  
    String name = req.getParameter("name");  
    String email = req.getParameter("email");  
    String phone = req.getParameter("phone");  
    String address = req.getParameter("Address");  
    String status = req.Edit(name, email, phone, address);  
    if (status.equals("success")) {  
        req.setAttribute("status", "Account updated successfully")  
        RequestDispatcher rd = req.getRequestDispatcher("Customer.jsp")  
    }  
}
```



```

        rd.forward(req, resp);
    }
    else if (status.equals("failure")) {
        req.setAttribute("status", "failed to update");
        RequestDispatcher rd = req.getRequestDispatcher("edit.jsp");
        rd.forward(req, resp);
    }
}

```

3.

Model - Register.java

```

public String Edit (String name, String email, String phone,
                    String address) {

```

```

    String status = " ";
    PreparedStatement ps = null;
    String query = "Update Customer set name = ?, email = ?,
                    phone = ?, address = ? ";

```

```

    try {

```

```

        ps = Con.prepareStatement(query);

```

```

        ps.setString(1, name);
        ps.setString(2, email);
        ps.setString(3, phone);
        ps.setString(4, address);

```

```

        int a = ps.executeUpdate();

```

```

        if (a > 0) {

```

```

            status = "Success";

```

```

        }
        else {

```

```

            status = "failure";

```

```

        }

```

```

        catch (Exception e) {

```

```

            e.printStackTrace();

```

```

        }
        return status;
    }

```


Search.jsp.

```
<form action="food" method="post">
Food: Name
  <input type="text" name="fname">
  <input type="submit" name="search by name" value="Food Name">
</form>
```

```
<form action="food" method="post">
Food: Category:
  <input type="text" name="fcategory">
  <input type="submit" name="search by Category" value="Food Category">
</form>
```

food.java (servlet).

```
@webServlet (name="food", urlPatterns={"/food"})
public class food extends HttpServlet {
    doProcess
    protected void doPost (HttpServletRequest req, HttpServletResponse
        resp throws ServletException, IOException) {
        HttpSession session = req.getSession();
        Food f = new Food (session);
        if (req.getParameter ("search by name") != null) {
            String name = req.getParameter ("fname");
            ArrayList<Food> fn = f.SearchByFood (name);
            if (fn != null) {
                req.setAttribute ("food", fn);
                RequestDispatcher rd = req.getRequestDispatcher ("Display
                    Food.jsp");
                rd.forward (req, resp);
            }
        }
    }
}
```

else {

req.setAttribute("status", "food Not Available.");

RequestDispatcher rd = req.getRequestDispatcher("Search.jsp");

rd.forward(req, resp);

}

{

if (req.getParameter("search by Category") != null) {

String category = req.getParameter("Category");

ArrayList<Food> fA = f.searchByCategory(category);

if (fA != null) {

req.setAttribute("food", fA);

RequestDispatcher rd = req.getRequestDispatcher("DisplayFood.jsp");

rd.forward(req, resp);

}

else {

req.setAttribute("status", "food not available");

RequestDispatcher rd = req.getRequestDispatcher("Search.jsp");

rd.forward(req, resp);

}

}

Model - Food.java

class Food {

HttpSession session;

private Connection con;

public Food(HttpSession session) {

try {

Class.forName("com.mysql.jdbc.Driver");

con = DriverManager.getConnection("jdbc:mysql://localhost:3306/Food", "root", "tiger");

this.session = session;

```

catch (ClassNotFoundException e) | SQLException e) {
    e.printStackTrace();
}
}

```

```

public ArrayList<Food> SearchByFood (String name) {
    PreparedStatement ps = null;
    ArrayList<Food> list = new ArrayList<>();
    String query = "Select * from food where name = ?";
    try {
        ps = con.prepareStatement(query);
        ps.setString(1, name);
        ResultSet rs = ps.executeQuery();
        while (rs.next()) {
            Food f = new Food();
            f.setId(rs.getInt("id"));
            f.setName(rs.getString("name"));
            f.setPrice(rs.getString("price"));
            f.setAvailability(rs.getString("Availability"));
            list.add(f);
        }
    }
}

```

```

catch (Exception e) {
    e.printStackTrace();
}
}

```

return list

```

public ArrayList<Food> SearchByCategory (String category) {
    PreparedStatement ps = null;
    ArrayList<Food> list = new ArrayList<>();
    String query = "Select * from food where category = ?";
}

```


try {

ps = con.prepareStatement (query);

ResultSet rs = ps.executeQuery();

while (rs.next()) {

Food f = new Food();

f.setId (rs.getInt("id"))

f.setName (rs.getString("name"))

f.setPrice (rs.getDouble("price"))

f.setAvailab (rs.getBoolean("availability"))

list.add(f);

}

Catch (Exception e) {

e.printStackTrace();

}

return list;

}

DisplayFood.jsp

<% Foods food(foods).request.getSession("foods") %>

<table >

<tr >

<th> Food ID <th>

<th> Food Name <th>

<th> Food Category <th>

<th> Food Price <th>

<th> Food Avail <th>

<% if (f != null) {

for (Food f : foods) {

%>

<tr >

<td = f.getId() %>

```

<% = f.getName() %>
<% = f.getCategory() %> <th>
<% = f.getPrice() %> <th>
<% = f.getAvailability() %> <th>

<%>
}
}
<%>

```

4. Logout.jsp

Customer.jsp

```

<a href = "Edit.jsp" > Edit Profile </a>
<a href = "search.jsp" > Search </a>
<form action = "logout" method = "post">
  <input type = "submit" name = "logout" value = "logout">
</form>

```

Servlet - logout.java.

```

@WebServlet (name = "logout", urlPattern = {"/logout/"}).
public class logout extends HttpServlet {
  protected void doGet (HttpServletRequest req, HttpServletResponse resp) throws ServletException, IOException {
    HttpSession session = req.getSession(false);
    if (session != null) {
      session.invalidate();
    }
    resp.sendRedirect ("login.jsp");
  }
}

```

Admin Module

View all Registered Customers

admin-viewCustomer.jsp

```
<% HttpSession session = request.getSession(false); %>
```

```
<% Register reg = new Register(session) %>
```

```
<% Custom ArrayList<Customer> c = reg.getAllCustomer() %>
```

```
<% if (c != null) %>
```

```
<table>
```

```
<tr>
```

```
<th> Customer ID </th>
```

```
<th> Customer Name </th>
```

```
<th> Customer Email </th>
```

```
<th> Customer Phone </th>
```

```
<th> Customer Address </th>
```

```
</tr>
```

```
<tr>  
<% if (c != null) %>
```

```
for (Customer cus : c) {
```

```
%>
```

```
<tr>
```

```
<th> <% = c.getID() %> </th>
```

```
<th> <% = c.getName() %> </th>
```

```
<th> <% = c.getEmail() %> </th>
```

```
<th> <% = c.getPhone() %> </th>
```

```
<th> <% = c.getAddress() %> </th>
```

```
</tr>
```

```
<% } %>
```

```
%>
```

```
%>
```

```
%>
```


Model - Register.java.

```
public ArrayList<Customer> getAllCustomers() {  
    ArrayList<Customer> list = new ArrayList<>();  
    PreparedStatement ps = null;  
    ResultSet rs = null;  
    String query = "Select * from Customer where id != ?";
```

try {

```
        ps = con.prepareStatement(query);
```

```
        ps.setInt(1, 1);
```

```
        rs = ps.executeQuery();
```

```
        while(rs.next()) {
```

```
            Customer c = new Customer();
```

```
            c.setId(rs.getInt("id"));
```

```
            c.setName(rs.getString("name"));
```

```
            c.setEmail(rs.getString("email"));
```

```
            c.setPhone(rs.getString("phone"));
```

```
            c.setAddress(rs.getString("address"));
```

```
            list.add(c);
```

```
        }
```

```
    }
```

```
    catch (Exception e) {
```

```
        e.printStackTrace();
```

```
    }
```

```
    return list
```

```
}
```

Add new food item.

Addfood.jsp.

```
<% String status = (String) request.getAttribute("status") %>
```

```
<% if (status != null) %>
```

```
<% = status %>
```

```
<% %>
```

```
<form method="post" action="/addfood">
```

Food Name:

```
<input type="text" name="fname" >
```

Food price

```
<input type="text" name="fprice" >
```

Food availability

```
<input type="text" name="faval" >
```

```
<input type="submit" name="addfood" value="Add Book">
```

```
</form>
```

Controller - Servlet - food.java.

```
else if (req.getParameter("addfood") != null) {
```

```
String name = req.getParameter("fname");
```

```
String price = req.getParameter("fprice");
```

```
String availability = req.getParameter("faval");
```

```
String status = f.addFood(name, price, availability)
```

```
if (status.equals("success")) {
```

```
req.setAttribute("status", "Food Added");
```

```
RequestDispatcher rd = req.getRequestDispatcher("admin.jsp");
```

```
rd.forward(req, resp);
```

}

```

else if (status.equals("failure")) {
    req.setAttribute("status", "failed to add Food");
    Request Dispatcher rd = req.getRequestDispatcher("addFood.jsp");
    rd.forward(req, resp);
}
}
}

```

Model - Food.java

```

public String addFood (name, price, availability) {
    String status = "";
    PreparedStatement ps = null;
    ResultSet rs = null;
    String query = "Insert into foods values (0, ?, ?, ?)";
}

```

```

try {
    ps = con.prepareStatement(query);
    ps.setString(1, name);
    ps.setString(2, price);
    ps.setString(3, availability);
    rs = ps.executeQuery(query);
    int a = rs.next();
    int a = ps.executeUpdate(query);
    if (a > 0) {
        status = "Success";
    }
}

```

```

catch {
    status = "failure";
}
}

```

1. Delete & Update the Food.

ViewAllFood.jsp

<% HTTP Session session = ~~new~~ request.getSession(false);

<% Food f = new Food(session) %>

<% ArrayList<Food> food = f.getAllFood(); %>

<table>

<tr>

<th> Food ID </th>

<th> Food Name </th>

<th> Food price </th>

<th> Food Availability </th>

<th> Action ^{Update} </th>

<tr> <th> Action Delete </th>

<% if (food != null) {

for (Food fn : food) {

%>

<tr> <th> <% = fn.getId() %> </th>

<th> <% = fn.getName() %> </th>

<th> <% = fn.getPrice() %> </th>

<th> <% = fn.getAvailability() %> </th>

<tr>

<th>

<a href = "update.jsp?id = <% = fn.getId() %> name = 'id'"

</th>

<tr>

<form method = "post" action = "food">

<input type = "text" value = "<% = fn.getId() %>" name = "id">

<input type = "submit" name = "delete food">

</form>

</tr>

</tr>

</table>

updateFood.jsp

```
<% Food f = new Food (session) %>
<% String strId = request.getParameter("id") %>
<% if (strId != null) {
    food f = f1.upo getFoodById(Integer.parseInt(strId))
} %>
<form action = "updateFood" method = "post">
    <input type = "hidden" value = <%= f.getId() %> name = id >
    <input type = "text" value = <%= f.getPrice() %> name = price
    <input type = "text" value = <%= f.getAvailability() %> name = avail >
    <input type = "submit" name = "updateFood" >
</form>
```

Food.java (Servlet).

```
protected void
else if (req.getParameter("updateFood") != null) {
    String price = req.getParameter("price");
    String availability = req.getParameter("avail");
    String status = f.updateFood(price, avail);
    if (status.equals("success")) {
        req.setAttribute("status", "Updated Successfully")
        RequestDispatcher rd = req.getRequestDispatcher("adminViewCustomer.jsp");
        rd.forward(req, resp);
    }
    else if (status.equals("failed")) {
        req.setAttribute("status", "Failed to update");
        RequestDispatcher rd = req.getRequestDispatcher("updateFood.jsp");
        rd.forward(req, resp);
    }
}
```

Model - Food.java

```
public Food getFoodById (int id) {
```

```
    PreparedStatement ps = null;
```

```
    String query = "Select * from foods where id = " + id + ";
```

```
    ResultSet rs = ps null;
```

```
    try {
```

```
        ps = con.prepareStatement ( );
```

```
        ps.setInt (1, id);
```

```
        rs = ps.executeQuery (query);
```

```
        if (rs.next()) {
```

```
            Food f = new Food ( );
```

```
            f.setId (rs.getInt ("id"));
```

```
            f.setName (rs.getString ("name"));
```

```
            f.setPrice (rs.getString ("price"));
```

```
            f.setAvailability (rs.getString ("aval"));
```

```
        }
```

```
    }
```

```
    catch (Exception e) {
```

```
        e.printStackTrace ();
```

```
    }
```

```
    return f;
```

```
}
```

```

public String updateFood (String price, String availability) {
    PreparedStatement ps = null;
    String query = "update food set price = ?, availability = ?";
}

```

ResultSet

```

ps = con.prepareStatement ();
ps.setString (1, price);
ps.setString (2, availability);
int a = ps.executeUpdate (query);

```

```

if (a > 0) {

```

```

    status = "success";

```

```

}

```

```

else {

```

```

    status = "failure";
}

```

```

}
catch (Exception e) {
    e.printStackTrace ();
}

```

```

return status;
}

```

Delete food:

Servlet food.java

```

protected void doPost (
    HttpServletRequest req) {
    if (req.getParameter ("deletefood") != null) {
        String id = req.getParameter ("id");
        String status = f.deleteFood (Integer.parseInt (id));
        if (status.equals ("success")) {
            req.setAttribute ("status", "deleted")
        }
    }
}

```



```

Request Dispatcher rd = req.getRequestDispatcher("viewAllFood.jsp");
rd.forward(req, resp);
}
else if (status.equals("failure")) {
    req.setAttribute("status", "failed to delete");
    Request Dispatcher rd = req.getRequestDispatcher("viewAllFood.jsp");
    rd.forward(req, resp);
}
}

```

Model - Food.java

```

public String deleteFood (int id) {
    PreparedStatement ps = null;
    String query = "delete from food where id = ?";
    try {
        ps = con.prepareStatement(query);
        ps.setInt(1, id);
        int a = ps.executeUpdate();
        if (a > 0) {
            status = "success";
        }
        else {
            status = "failure";
        }
    } catch (Exception e) {
        e.printStackTrace();
    }
    return status;
}

```


Admin Module.

Logout

Admin.jsp

```
<a href = "admin-view Customer.jsp" > All Customer </a>
<a href = "AddFood.jsp" > Add Food > AddFood </a>
<a href = "View All Food" > View All Food </a>
<form action = logout method = "post" >
    <input type = "submit" name = "logout" value = "logout"
</form>
```

Servlet - logout.java

```
@ webServlet (name = "logout", urlPatterns = { "/logout" })
public class logout extends HttpServlet {
    protected void doGet (HttpServletRequest req, HttpServletResponse resp) throws ServletException {
        HttpSession session = req.getSession(false);
        if (session != null) {
            session.invalidate();
        }
        resp.sendRedirect ("login.jsp")
    }
}
```