ANNEX 1

WORKSHEETS

Contents

Annex 1	Worksheets	
2A	Mineral Industry	A1.4
2A1	Cement Production	A1.4
2A2	Lime Production	A1.4
2A3	Glass Production	A1.5
2A4	Other Process Uses of Carbonates	A1.5
2B	Chemical Industry	A1.6
2B1	Ammonia Production	A1.6
2B2	Nitric Acid Production	A1.6
2B3	Adipic Acid Production	A1.7
2B4	Caprolactam, Glyoxal and Glyoxylic Acid Production	A1.7
2B5	Carbide Production	A1.7
2B6	Titanium Dioxide Production	A1.9
2B7	Soda Ash Production	A1.10
2B8	Petrochemical and Carbon Black Production	A1.10
2B9	Fluorochemical Production	A1.15
2C	Metal Industry	A1.17
2C1	Iron and Steel Production	A1.17
2C2	Ferroalloys Production	A1.18
2C3	Aluminium Production	A1.19
2C4	Magnesium Production	A1.20
2C5	Lead Production	A1.21
2C6	Zinc Production	A1.21
2D	Non-Energy Products from Fuels and Solvent Use	A1.22
2D1	Lubricant Use	A1.22
2D2	Paraffin Wax Use	A1.22
2E	Electronics Industry	A1.23
2E1	Integrated Circuit or Semiconductor	A1.23
2E2	TFT Flat Panel Display	A1.24
2E3	Photovoltaics	A1.24
2E4	Heat Transfer Fluid	A1.25
2F	Product Uses as Substitutes for Ozone Depleting Substances	A1.26
2F1	Refrigeration and Air Conditioning	A1.26
2F2	Foam Blowing Agents	A1.26
2F3	Fire Protection	A1.27
2F4	Aerosols	A1.27

2F5	Solvents	A1.28
2F6	Other Applications	A1.28
2G	Other Product Manufacture and Use	A1.29
2G1	Electrical Equipment	A1.29
2G2	SF ₆ and PFCs from Other Product Uses	A1.31
2G3	N ₂ O from Product Uses	A1.34

The worksheets in this annex are designed to enable users to perform at least the Tier 1 (and in some cases Tier 2) emission estimation for each category under IPPU Sector.

Sector	Industrial Processes and Product Use						
Category	Mineral Industry - Ceme	Mineral Industry - Cement Production					
Category Code	2A1						
Sheet	1 of 2						
			_				
	A	В	С				
Individual Type of Cement Produced ¹⁾	Mass of Individual Type of Cement Produced	Clinker Fraction in Cement	Mass of Clinker in the Individual Type of Cement Produced				
	(tonne)	(fraction)	(tonne)				
		C = A * B					
Total							
1) Insert additional rows in	f more than two types of cement ar	re produced.					

Sector		Industrial Processes and Product Use					
	Category	Mineral Industry	- Cement Production				
Categ	ory Code	2A1					
	Sheet	2 of 2					
D	Е	F	G	Н	1		
Imports for Consumption of Clinker	Exports of Clinker	Mass of Clinker Produced in the Country	Emission Factor for the Clinker in the Particular Cement	CO ₂ Emissions	CO ₂ Emissions		
(tonne)	(tonne)	(tonne)	(tonne CO ₂ / tonne clinker)	(tonne CO ₂)	(Gg CO ₂)		
		F = C – D + E		H=F*G	$I = H/10^3$		

Sector	Industrial Processes and Product Use						
Category	Mineral Indust	Mineral Industry - Lime Production					
Category Code	2A2						
Sheet	1 of 1						
		_					
	Α	В	С	D			
Type of Lime Produced ^{1), 2)}	Mass of Lime	Emission Factor for Lime	CO_2	CO ₂ Emissions			
Produced ^{1), 2)}	Produced	Production	Emissions				
	(tonne)	(tonne CO ₂ / tonne lime)	(tonne CO ₂)	(Gg CO ₂)			
			C = A * B	$D = C/10^3$			
Total							

¹⁾ Insert additional rows if more than two types of lime are produced.

When country-specific information on lime production by type is not available, apply the default emission factor to national level lime production data. (See Equation 2.8 in Chapter 2 of this volume.)

Sector	Industrial Processes and Product Use				
Category	Mineral Industry	- Glass Production	on		
Category Code	2A3				
Sheet	1 of 1				
Α	В	С	D	E	
Total Glass Production	Emission Factor for Glass Production	Average Annual Cullet Ratio	CO ₂ Emissions	CO ₂ Emissions	
(tonne)	(tonne CO ₂ / tonne glass)	(fraction)	(tonne CO ₂)	(Gg CO ₂)	
	$D = A * B * (1 - C)$ $E = D/10^3$				

Sector	Industrial Processes and Product Use					
Category	Mineral Industry - Other Process Uses of Carbonates ¹⁾					
Category Code	2A4					
Sheet	1 of 1					
	Α	В	С	D		
Type of Use	Mass of Carbonate Consumed	Emission Factor for Carbonate Consumption ^{3), 4)}	CO ₂ Emissions	CO ₂ Emissions		
	(tonne)	(tonne CO ₂ / tonne carbonate)	(tonne CO ₂)	(Gg CO ₂)		
			C = A * B	$D = C/10^3$		
Ceramics						
Other Uses of Soda Ash						
Non Metallurgical Magnesia Production						
Other ²⁾						

- 1) Limestone and other carbonate materials also are consumed in a variety of other industries not covered in Chapter 2 of Volume 3. Examples include carbonates used as fluxes and slagging agents in metals smelting and refining (e.g., iron and steel production and base metals such as copper), and as inputs to the chemical industry (e.g., fertiliser). The methods outlined here for estimating emissions from the use of carbonates are applicable to these other industries as well. It is *good practice* to allocate emissions from the use of limestone, dolomite and other carbonates to the industrial source category where they are emitted (e.g., iron and steel production).
- 2) This row should contain estimates of emissions that do not fit into any of the major sources presented in Table 2.7 in Chapter 2 of Volume 3. Insert additional rows, if necessary.
- 3) For the Tier 1 method, it is consistent with *good practice* for inventory compilers to assume that 85 percent of carbonates consumed are limestone and 15 percent of carbonates consumed are dolomite. For the Tier 1 method for soda ash use (Other Uses of Soda Ash), this default fraction (0.85:0.15) should not be applied, and the default value for sodium carbonate should be used. (For default emission factors for various carbonates, see Table 2.1 in Chapter 2 of Volume 3.
- 4) It is suggested that inventory compilers ensure that data on carbonates reflect pure carbonates and not carbonate rock. If data are only available on carbonate rock, a default purity of 95% can be assumed. For clays a default carbonate content of 10% can be assumed, if no other information is available.

Sector	Industrial Processes and Product Use				
Category	Chemical Industry - A	mmonia Produ	ction		
Category Code	2B1				
Sheet	1 of 2				
Α	В	С	D	E	
Amount of Ammonia Produced	Fuel Requirement for Ammonia Production	Carbon Content of Fuel	Carbon Oxidation Factor of Fuel	CO ₂ Generated	
(tonne)	(GJ/ tonne ammonia produced)	(kg C/GJ)	(fraction)	(kg CO ₂)	
				E = (A * B * C * D) * 44/12	

Sector	Industrial Processes and Product Use			
Category	Chemical Industry -	Ammonia Production		
Category Code	2B1			
Sheet	2 of 2			
F	G	Н	I	
Amount of Urea Produced	CO₂ Recovered for Urea Production	CO ₂ Emissions	CO ₂ Emissions	
(kg)	(kg CO ₂)	(kg CO₂)	(Gg CO ₂)	
	G = F * 44/60	H = E – G	$I = H/10^6$	

Sector	Industrial Processes and Product Use				
Category	Chemical Industry - Nitri	c Acid Production			
Category Code	2B2				
Sheet	1 of 1				
Α	В	С	D		
Amount of Nitric Acid Production	Emission Factor	N ₂ O Emissions	N₂O Emissions		
(tonne)	(kg N₂O/tonne nitric acid produced)	(kg)	(Gg)		
	$C = A * B$ $D = C/10^6$				

Sector	Industrial Processes and Product Use				
Category	Chemical Industry - A	Adipic Acid Production			
Category Code	2B3				
Sheet	1 of 1				
А	В	С	D		
Amount of Adipic Acid Production	Emission Factor	N₂O Emissions	N ₂ O Emissions		
(tonne)	(kg N ₂ O/tonne adipic acid produced)	(kg)	(Gg)		
	C = A * B D = C/10 ⁶				

Sector	Industrial Processes and Product Use					
Category	Chemical Industry - Caprolactam, Glyoxal and Glyoxylic Acid Production					
Category Code	2B4					
Sheet	1 of 1					
	Α	В	C	D		
Chemical	Amount of Chemical Production	Emission Factor	N ₂ O Emissions	N₂O Emissions		
	(tonne)	(kg N ₂ O/tonne chemical produced)	(kg)	(Gg)		
			C = A * B	$D = C/10^6$		
Caprolactam						
Glyoxal						
Glyoxylic Acid						
Total						

Sector Category Category Code Sheet	Industrial Processes and Product Use Chemical Industry - Carbide Production 2B5 1 of 6 CO ₂ Emissions (calculation based on raw material used)					
Officet	1 01 0 002 Emissio	ons (carculation base	a on raw mate			
	А	В	С	D		
Type of Carbide Produced/	Raw Material (Petroleum Coke) Consumption	Emission Factor ¹⁾	CO ₂ Emissions	CO ₂ Emissions		
	(tonne)	(tonne CO ₂ /tonne raw material used)	(tonne CO ₂)	(Gg CO ₂)		
			C = A * B	$D = C/10^3$		
Silicon Carbide (SiC)						
Calcium Carbide (CaC ₂)						

The emission factor needs to be adjusted to account for the carbon contained in the product. See Section 3.6.2.1 of Volume 3.

Note: Inventory compilers should use either this sheet (1 of 6) or the next sheet (2 of 6), not both.

Sector	Industrial Processes and Product Use				
Category	Chemical	Industry - Carbide P	roduction		
Category Code	2B5				
Sheet	2 of 6 CO	₂ Emissions (calcula	tion based on carb	ide produced)	
	Α	В	С	D	
Type of Carbide	Carbide	Emission Factor	CO ₂ Emissions	CO ₂ Emissions	
Produced	Produced				
	(tonne)				
			C = A * B	$D = C/10^3$	
Silicon Carbide (SiC)					
Calcium Carbide (CaC ₂)					
Note: Inventory compilers should use either this sheet (2 of 6) or the previous sheet (1 of 6), not both.					

Sector	Industrial Processes and Product Use				
Category	Chemical Industry - Carbide Pro	oduction			
Category Code	2B5				
Sheet	3 of 6 CO ₂ Emissions from Use of CaC ₂ in Acetylene Production				
Α	В	С	D		
Calcium Carbide Used in Acetylene Production	Emission Factor CO ₂ Emissions CO Emiss				
(tonne)	(tonne CO ₂ /tonne carbide used)	(tonne CO ₂)	(Gg CO ₂)		
		C = A * B	$D = C/10^3$		

Sector Category	Industrial Processes and Product Use Chemical Industry - Carbide Production					
Category Code	2B5	de i roddellon				
Sheet	4 of 6 CO ₂ Emission (Total	al)				
Α	В	С	D			
CO ₂ Emissions from Silicon Carbide (SiC) Production	CO ₂ Emissions from Calcium Carbide (CaC ₂) Production	CO ₂ Emissions from Use of CaC ₂ in Acetylene Production	Total CO ₂ Emissions			
(Gg CO ₂)	(Gg CO ₂)	(Gg CO ₂)	(Gg CO ₂)			
From D in Sheet 1 of 6 or D in Sheet 2 of 6	From D in Sheet 1 of 6 or D in Sheet 2 of 6	From D in Sheet 3 of 6	D = A + B+ C			

Sector	Industrial Processes and Product Use					
Category	Chemical Industry - Carbide Prod	uction				
Category Code	2B5					
Sheet		5 of 6 CH₄ Emissions from Silicon Carbide (SiC) Production (calculation based on raw material used)				
Α	В	С	D			
Raw Material (Petroleum Coke) Consumption	Emission Factor	CH ₄ Emissions	CH₄ Emissions			
(tonne)	(kg CH ₄ /tonne raw material used)	(kg)	(Gg)			
		C = A * B	$D = C/10^6$			
Note: Inventory compilers shou	ld use either this sheet (5 of 6) or the next sheet	t (6 of 6), not both.	•			

Sector	Industrial Processes and Product Use					
Category	Chemical Industry - Carbide Prod	uction				
Category Code	2B5					
Sheet	6 of 6 CH ₄ Emissions from Silicon Carbide (SiC) Production (calculation based on carbide produced)					
А	B C D					
Carbide Produced	Emission Factor CH ₄ Emissions CH ₄ Emissions					
(tonne)	(kg CH ₄ /tonne carbide produced)	(kg CH₄/tonne carbide produced) (kg) (Gg)				
	$C = A * B$ $D = C/10^6$					
Note: Inventory compilers shou	uld use either this sheet (6 of 6) or the previous s	sheet (5 of 6), not both.				

Sector	Industrial Processes and Product Use				
Category	Chemical Ind	lustry - Titanium Dio	xide Production		
Category Code	2B6				
Sheet	1 of 1				
	Α	В	С	D	
Type of production	Amount of Production	Emission Factor	CO ₂ Emissions	CO ₂ Emissions	
	(tonne)	(tonne CO ₂ /tonne produced)	(tonne CO ₂)	(Gg CO ₂)	
			C = A * B	$D = C/10^3$	
Titanium Slag					
Synthetic Rutile					
Rutile TiO ₂					
Total					

Sector	Industrial Processes and Product Use					
Category	Chemical Industry - Soda Ash P	Chemical Industry - Soda Ash Production				
Category Code	2B7					
Sheet	1 of 2 Natural Soda Ash (calcula	ation based on tro	na used)			
Α	В	С	D			
Amount of Trona Utilised	Emission Factor	CO ₂ Emissions	CO ₂ Emissions			
(tonne)	(tonne CO ₂ /tonne trona utilized)	(tonne CO ₂)	(Gg CO ₂)			
		C = A * B	$D = C/10^3$			
Note: Inventory compilers shou	ıld use either this sheet (1 of 2) or the next she	eet (2 of 2), not both.				

Sector	Industrial Processes and Product Use				
Category	Chemical Industry -Soda Ash Pi	roduction			
Category Code	2B7				
Sheet	2 of 2 Natural Soda Ash (calculated)	ation based on pro	duction)		
Α	В	С	D		
Amount of Natural Soda Ash Produced	Emission Factor	CO ₂ Emissions	CO ₂ Emissions		
(tonne)	(tonne CO ₂ /tonne natural soda ash produced) (tonne CO ₂) (Gg CO ₂)				
		C = A * B	$D = C/10^3$		
Note: Inventory compilers should use either this sheet (2 of 2) or the previous sheet (1 of 2), not both.					

Sector	Industrial Processes and Product Use				
Category	Chemical Industry - Petrochemical and Carbon Black Production				
Category Code	2B8				
Sheet	1 of 12 CO ₂ Emiss	ions from Methanol Pro	duction		
	Α	В	С	D	
Type of Process/Type of Feedstock ^{1), 2)}	Amount of Methanol Produced	Emission Factor	CO ₂ Emissions	CO ₂ Emissions	
	(tonne)	(tonne CO ₂ /tonne methanol produced)	(tonne CO ₂)	(Gg CO ₂)	
			C = A * B	$D = C/10^3$	
Type of Process = [] (please spec	cify)		
Feedstock = [] (Please specify)					
Type of Process = [] (please specify)				
Feedstock = [] (Please specify)					
Total					

¹⁾ For details of process types and feedstock types, see Table 3.12 in Chapter 3 of Volume 3. For the default process type and the default feedstock, see Table 3.11 in Chapter 3 of Volume 3.

²⁾ Insert additional rows if necessary.

Sector	Industrial Processes and Product Use			
Category	Chemical Industry - Petrochemic	cal and Carbon Bla	ck Production	
Category Code	2B8			
Sheet	2 of 12 CH ₄ Emissions from Met	hanol Production		
Α	В	С	D	
Amount of Methanol Produced	Emission Factor	CH₄ Emission	CH₄ Emission	
(tonne)	(kg CH₄/tonne methanol produced)	(kg)	(Gg)	
		C = A * B	$D = C/10^6$	

Sector	Industrial Processes and Product Use					
Category	Chemical I	ndustry - Petrochemic	cal and Carbon	Black Produ	ction	
Category Code	2B8					
Sheet	3 of 12 CO	₂ Emissions from Eth	ylene Producti	on		
	Α	В	С	D	E	
Type of Feedstock ^{1), 2)} (please specify)	Amount of Ethylene Produced	Emission Factor	Geographic Adjustment Factor ³⁾	CO ₂ Emissions	CO ₂ Emissions	
	(tonne)	(tonne CO ₂ /tonne ethylene produced)	(%)	(tonne CO ₂)	(Gg CO ₂)	
				D = A * B * C/100	$E = D/10^3$	
Total						

- 1) For details of feedstock types, see Table 3.14 in Chapter 3 of Volume 3. For the default feedstock, see Table 3.11 in Chapter 3 of Volume 3.
- 2) Insert additional rows if necessary.
- 3) For geographic adjustment factors, see Table 3.15 in Volume 3.

Sector	Industrial Processe	es and Product Use		
Category	Chemical Industry	- Petrochemical and Carbo	n Black Prod	uction
Category Code	2B8			
Sheet	4 of 12 CH ₄ Emissi	ions from Ethylene Produc	tion	
	Α	В	С	D
Type of Feedstock ^{1), 2)}	Amount of Ethylene	Emission Factor	CH₄	CH₄
Feedstock ^{1), 2)}	Produced		Emissions	Emissions
(please specify)	(tonne)	(kg CH₄/tonne ethylene produced)	(kg)	(Gg)
			C = A * B	$D = C/10^6$
Total				

- 1) For details of feedstock types, see Table 3.14 in Chapter 3 of Volume 3. For the default feedstock, see Table 3.11 in Chapter 3 of Volume 3.
- 2) Insert additional rows if necessary.

Sector	Industrial Processes and Product Use				
Category	Chemical Industry - Petr	ochemical and Carbo	n Black Prod	uction	
Category Code	2B8				
Sheet	5 of 12 CO ₂ Emissions from Monomer Production	om Ethylene Dichloride	e/Vinyl Chlorid	e	
	Α	В	С	D	
Type of Process ^{1), 2)} (please specify)	Amount of Ethylene Dichloride (EDC) or Vinyl Chloride Monomer (VCM) Produced ³⁾	Emission Factor	CO ₂ Emissions	CO ₂ Emissions	
	(tonne EDC produced) or (tonne VCM produced)	(tonne CO ₂ /tonne EDC produced) or (tonne CO ₂ /tonne VCM produced)	(tonne CO ₂)	(Gg CO ₂)	
			C = A * B	$D = C/10^3$	
				-	
Total					

¹⁾ For details of process types, see Table 3.17 in Chapter 3 of Volume 3. For the default process type, see Table 3.11 in Chapter 3 of Volume 3.

³⁾ Inventory compilers should use either EDC production or VCM production (not both) as activity data.

Sector	Industrial Processes and Product Use				
Category	Chemical Industry - Petr	ochemical and Carbo	n Black Prod	uction	
Category Code	2B8				
Sheet	6 of 12 CH ₄ Emissions from Production	om Ethylene Dichloride	Vinyl Chlorid	e Monomer	
	A	В	С	D	
Type of Process ^{1),} (please specify)	Amount of Ethylene Dichloride (EDC) or Vinyl Chloride Monomer (VCM) Produced ³⁾	Emission Factor	CH₄ Emission	CH₄ Emission	
	(tonne EDC produced) or (tonne VCM produced)	(kg CH₄/tonne EDC produced) or (kg CH₄/tonne VCM produced)	(kg)	(Gg)	
	$C = A * B \qquad D = C/10^6$				
			_		
Total					

¹⁾ For details of process types, see Tables 3.11 and 3.19 in Chapter 3 of Volume 3. For the default process type, see Table 3.11 in Chapter 3 of Volume 3.

²⁾ Insert additional rows if necessary.

Insert additional rows if necessary.

³⁾ Inventory compilers should use either EDC production or VCM production (not both) as activity data.

Industrial Processes and Product Use			
Chemical Indus	stry - Petrochemica	l and Carbon Blad	ck Production
2B8			
7 of 12 CO ₂ Em	nissions from Ethyl	ene Oxide Produc	ction
Α	В	С	D
Amount of Ethylene Oxide Produced	Emission Factor	CO ₂ Emissions	CO ₂ Emissions
(tonne ethylene oxide produced)	(tonne CO ₂ /tonne ethylene oxide produced)	(tonne CO ₂)	(Gg CO ₂)
		C = A * B	$D = C/10^3$
	Chemical Indus 2B8 7 of 12 CO ₂ En A Amount of Ethylene Oxide Produced (tonne ethylene oxide	Chemical Industry - Petrochemical 2B8 7 of 12 CO ₂ Emissions from Ethyl A B Amount of Ethylene Oxide Produced (tonne ethylene oxide (tonne CO ₂ /tonne ethylene oxide)	Chemical Industry - Petrochemical and Carbon Blace 2B8 7 of 12 CO ₂ Emissions from Ethylene Oxide Produce A B C Amount of Ethylene Oxide Produced Produced (tonne ethylene oxide produced) (tonne CO ₂ /tonne ethylene oxide produced) (tonne CO ₂) (tonne CO ₂)

¹⁾ For details of process types, see Table 3.20 in Chapter 3 of Volume 3. For the default process type, see Table 3.11 in Chapter 3 of Volume 3.

²⁾ Insert additional rows if necessary.

Sector	Industrial Proc	Industrial Processes and Product Use			
Category	Chemical Indus	stry - Petrochemica	I and Carbon Bla	ck Production	
Category Code	2B8				
Sheet	8 of 12 CH ₄ Em	nissions from Ethyl	ene Oxide Produc	ction	
	Α	В	С	D	
Type of Process ^{1), 2)} (please specify)	Amount of Ethylene Oxide Produced	Emission Factor	CH₄ Emissions	CH₄ Emissions	
	(tonne ethylene oxide produced)	(kg CH₄/tonne ethylene oxide produced)	(kg)	(Gg)	
			C = A * B	$D = C/10^6$	
		_			
Total				_	

¹⁾ For details of process types, see Table 3.21 in Chapter 3 of Volume 3. For the default process type, see Table 3.11 in Chapter 3 of Volume 3.

²⁾ Insert additional rows if necessary.

Sector	Industrial Processes and Product Use			
Category	Chemical Industr	ry - Petrochemical a	and Carbon Black	Production
Category Code	2B8			
Sheet	9 of 12 CO ₂ Emis	ssions from Acryloi	nitrile Production	
	Α	В	С	D
Type of Process ^{1), 2)} (please specify)	Amount of Acrylonitrile Produced	Emission Factor	CO ₂ Emissions	CO ₂ Emissions
	(tonne acrylonitrile produced)	(tonne CO ₂ /tonne acrylonitrile produced)	(tonne CO ₂)	(Gg CO ₂)
			C = A * B	$D = C/10^3$
Total				

¹⁾ For details of process types, see Table 3.22 in Chapter 3 of Volume 3. For the default process type, see Table 3.11 in Chapter 3 of Volume 3.

²⁾ Insert additional rows if necessary.

Sector	Industrial Processes and Product Use			
Category	Chemical Indust	ry - Petrochemical a	and Carbon Black	Production
Category Code	2B8			
Sheet	10 of 12 CH ₄ Em	issions from Acrylo	onitrile Production	n
	Α	В	С	D
Type of Process ^{1), 2)} (please specify)	Amount of Acrylonitrile Produced	Emission Factor	CH₄ Emissions	CH₄ Emissions
	(tonne acrylonitrile produced)	(kg CH₄/tonne acrylonitrile produced)	(kg)	(Gg)
			C = A * B	$D = C/10^6$
Total				

¹⁾ For details of process types, see Table 3.22 in Chapter 3 of Volume 3. For the default process type, see Table 3.11 in Chapter 3 of Volume 3.

²⁾ Insert additional rows if necessary.

Sector	Industrial Processes and Product Use			
Category	Chemical Industr	y - Petrochemical and Ca	rbon Black Pr	oduction
Category Code	2B8			
Sheet	11 of 12 CO ₂ Emi	issions from Carbon Blac	k Production	
	Α	В	С	D
Type of Process ^{1), 2)} (please specify)	Amount of Carbon Black Produced	Emission Factor	CO ₂ Emissions	CO ₂ Emissions
	(tonne carbon black produced)	(tonne CO ₂ /tonne carbon black produced)	(tonne CO ₂)	(Gg CO ₂)
			C = A * B	$D = C/10^3$
Total				

¹⁾ For details of process types, see Table 3.23 in Chapter 3 of Volume 3. For the default process type, see Table 3.11 in Chapter 3 of Volume 3.

²⁾ Insert additional rows if necessary.

Sector	Industrial Processes and Product Use			
Category	Chemical Industry	- Petrochemical and Ca	arbon Black Pr	oduction
Category Code	2B8			
Sheet	12 of 12 CH ₄ Emis	sions from Carbon Bla	ck Production	
	Α	В	С	D
Type of Process ^{1), 2)}	Amount of Carbon	Emission Factor	CH₄	CH₄
(please specify)	Black Produced		Emissions	Emissions
	(tonne carbon black produced)	(kg CH₄/tonne carbon black produced)	(kg)	(Gg)
			C = A * B	$D = C/10^6$
Total				

¹⁾ For details of process types, see Table 3.24 in Chapter 3 of Volume 3. For the default process type, see Table 3.11 in Chapter 3 of Volume 3.

²⁾ Insert additional rows if necessary.

Sector	Industrial Processes and Product Use			
Category	Chemical Industry - Fluorocher	mical Production		
Category Code	2B9			
Sheet	1 of 3 HFC-23 Emissions from	HCFC-22 Production	า	
Α	В	С	D	
Amount of HCFC-22 Produced	Emission Factor	HFC-23 Emissions	HFC-23 Emissions	
(kg)	(kg HFC-23/kg HCFC-22 produced)	(kg)	(Gg)	
		C = A * B	$D = C/10^6$	

Sector	Industrial Processes and Product Use				
Category	Chemical Industry - Fluorochemical Production				
Category Code	2B9	2B9			
Sheet	2 of 3 By-proc Compounds	duct Emissions from Pro	oduction of Oth	er Fluorinated	
	Α	В	С	D	
Fluorinated Compound Emitted as By-product and Principal Fluorinated Compound Produced	Amount of Principal Fluorinated Compound Produced	Byproduct Emission Factor ²⁾	Emissions	Emissions	
(Please specify such as "xxx from yyy production") 1)	(kg)	(kg by-product gas emitted/kg F- compound produced)	(kg)	(Gg)	
			C = A * B	$D = C/10^6$	
			<u>-</u>		

¹⁾ Insert additional rows if necessary.

²⁾ For sources that are not *key categories*, fugitive and by-product emissions are considered the same and those emissions are calculated using the next sheet (3 of 3).

Sector	Industrial Proc	Industrial Processes and Product Use			
Category	Chemical Indus	stry - Fluorochemical P	roduction		
Category Code	2B9				
Sheet	3 of 3 Fugitive Compounds	Emissions from Produ	ction of Other FI	uorinated	
	Α	В	С	D	
Fluorinated Compound Produced	Amount of Fluorinated Compound Produced	Fugitive Emission Factor ²⁾	Emissions	Emissions	
(Please specify) 1)	(kg)	(kg fugitive gas emitted/kg F- compound produced)	(kg)	(Gg)	
			C = A * B	$D = C/10^6$	

¹⁾ Insert additional rows if necessary.

²⁾ For sources that are not key categories, fugitive and by-product emissions are considered the same. For Tier 1, in the absence of abatement measures, a default emission factor of 0.5 percent of production, not counting losses in transport and transfer of materials, is suggested for HFCs and PFCs,

Sector	Industrial Processes and Product Use			
Category	Metal Industry - Iron and Steel Production			
Category Code	2C1			
Sheet	1 of 2 CO ₂ Emission	าร		
	Α	В	С	D
Type of Steelmaking Method, etc	Amount of Steel or Iron Production	Emission Factor	CO ₂ Emissions	CO ₂ Emissions
	(tonne crude steel produced, pig iron, DRI, sinter or pellet)	(tonne CO ₂ /tonne production)	(tonne CO ₂)	(Gg CO ₂)
			C = A * B	$D = C/10^3$
Basic Oxygen Furnace				
Electric Arc Furnace				
Open Hearth Furnace				
Pig Iron Production (not converted into steel)				
Direct Reduced Iron (DRI) Production				
Sinter Production				
Pellet Production				
TOTAL				-

Sector	Industrial Proces	Industrial Processes and Product Use			
Category	Metal Industry - I	ron and Steel Produ	uction		
Category Code	2C1				
Sheet	2 of 2 CH ₄ Emiss	sions			
	Α	В	С	D	
Type of Production	Amount of Production	Emission Factor	CH₄ Emissions	CH₄ Emissions	
	(tonne sinter, DRI or pig iron)	(kg CH₄/tonne production)	(kg)	(Gg)	
			C = A * B	$D = C/10^6$	
Sinter Production					
Direct Reduced Iron (DRI) Production					
Pig Iron Production				_	
TOTAL				_	

Sector	Industrial Processes and Product Use				
Category	Metal Industry - Ferroalloys Production				
Category Code	2C2				
Sheet	1 of 2 CO ₂ Emis	sions			
	Α	В	С	D	
Type of Ferroalloy ^{1), 2)}	Amount of Ferroalloy Production	Emission Factor	CO ₂ Emissions	CO ₂ Emissions	
(please specify)	(tonne ferroalloy produced)	(tonne CO ₂ /tonne ferroalloy produced)	(tonne CO ₂)	(Gg CO ₂)	
			C = A * B	$D = C/10^3$	
Total					

¹⁾ For details of ferroalloy types, see Table 4.5 in Chapter 4 of Volume 3.

²⁾ Insert additional rows if necessary.

Sector	Industrial Proce	Industrial Processes and Product Use				
Category	Metal Industry - Ferroalloys Production					
Category Code	2C2					
Sheet	2 of 2 CH ₄ Emis	sions				
	Α	В	С	D		
Type of Ferroalloy ^{1), 2)}	Amount of Ferroalloy Production	Emission Factor	CH₄ Emissions	CH₄ Emissions		
(please specify)	(tonne ferroalloy produced)	(kg CH ₄ /tonne ferroalloy produced)	(kg)	(Gg)		
			C = A * B	$D = C/10^6$		
			_			
Total						

¹⁾ For details of ferroalloy types, see Table 4.7 in Chapter 4 of Volume 3.

²⁾ Insert additional rows if necessary.

Sector	Industrial Processes and Product Use			
Category	Metal Industry - Alun	ninium Production		
Category Code	2C3			
Sheet	1 of 3 CO ₂ Emission	s		
	Α	В	С	D
Type of Technology	Amount of Aluminium Production	Emission Factor	CO ₂ Emissions	CO ₂ Emissions
	(tonne aluminium produced)	(tonne CO ₂ /tonne aluminium produced)	(tonne)	(Gg)
			C = A * B	$D = C/10^3$
Prebake				
Soderberg				
Total				

Sector	Industrial Processes and Product Use			
Category	Metal Industry - Alun	ninium Production		
Category Code	2C3			
Sheet	2 of 3 CF ₄ Emissions	S		
	Α	В	С	D
Type of Technology	Amount of Aluminium Production	Emission Factor	CF₄ Emissions	CF₄ Emissions
	(tonne aluminium produced)	(kg CF ₄ /tonne aluminium produced)	(kg)	(Gg)
			C = A * B	$D = C/10^6$
CWPB				
SWPB				
VSS				
HSS				
Total				

Sector	Industrial Processes and Product Use			
Category	Metal Industry - Alun	ninium Production		
Category Code	2C3			
Sheet	3 of 3 C ₂ F ₆ Emission	ns		
	Α	В	С	D
Type of Technology	Amount of Aluminium Production	Emission Factor	C_2F_6 Emissions	C ₂ F ₆ Emissions
	(tonne aluminium produced)	(kg C ₂ F ₆ /tonne aluminium produced)	(kg)	(Gg)
			C = A * B	$D = C/10^6$
CWPB				
SWPB				
VSS				
HSS				
Total				

Sector	Industrial Processes and Product Use			
Category	Metal Industry - M	agnesium Production		
Category Code	2C4			
Sheet	1 of 2 CO ₂ Emissi	ons from Primary Produc	ction	
	Α	В	С	D
Raw Material Source	Amount of Primary Magnesium Production	Emission Factor	CO ₂ Emissions	CO ₂ Emissions
	(tonne primary magnesium produced)	(tonne CO ₂ /tonne primary magnesium produced)	(tonne)	(Gg)
			C = A * B	$D = C/10^3$
Dolomite				
Magnesite				
Total				

Sector	Industrial Processes and Product Use		
Category	Metal Industry - Magnesiu	m Production	
Category Code	2C4		
Sheet	2 of 2 SF ₆ Emissions from	n Magnesium Casting P	rocesses
Α	В	С	D
Amount of Magnesium Casting	Emission Factor	SF ₆ Emissions	SF ₆ Emissions
(tonne magnesium casting)	(kg SF ₆ /tonne magnesium casting)	(kg)	(Gg)
		C = A * B	$D = C/10^6$

Note: As regards HFC 134-a, FK 5-1-12 and their decomposition products (e.g., PFCs), no Tier 1 method is provided because the industrial experience in using these compounds (HFC 134-a and FK 5-1-12) for magnesium protection purposes is yet very limited. However, if the greenhouse gas emission from the use of magnesium cover gases is a national *key category*, it is *good practice*, for inventory preparation purposes, to collect direct measurements of these greenhouse gas emissions.

Sector	Metal Industry				
Category	Metal Industry	Metal Industry - Lead Production			
Category Code	2C5				
Sheet	1 of 1				
	Α	В	С	D	
Source and Furnace Type ^{1), 2)}	Amount of Lead Production	Emission Factor	CO ₂ Emissions	CO ₂ Emissions	
(please specify)	(tonne lead produced)	(tonne CO ₂ /tonne lead produced)	(tonne)	(Gg)	
			C = A * B	$D = C/10^3$	
	_				
Total					

¹⁾ For details of source and furnace types, see Table 4.21 in Chapter 4 of Volume 3.

²⁾ Insert additional rows if necessary.

Sector	Industrial Processes and Product Use			
Category	Metal Industry - Zinc Production			
Category Code	2C6			
Sheet	1 of 1			
	Α	В	С	D
Type of Process ^{1), 2)}	Amount of Zinc Production	Emission Factor	CO ₂ Emissions	CO ₂ Emissions
(please specify)	(tonne zinc produced)	(tonne CO ₂ /tonne zinc produced)	(tonne)	(Gg)
			C = A * B	$D = C/10^3$
Total				
1) For details of process to	ines see Table 4 24	in Chanter 4 of Volume 3		

¹⁾ For details of process types, see Table 4.24 in Chapter 4 of Volume 3.

²⁾ Insert additional rows if necessary.

Sector	Industrial Processes and Product Use			
Category	Non-Energy Products from Fuels and Solvent Use - Lubricant Use			
Category Code	2D1			
Sheet	1 of 1			
Α	В	С	D	E
Amount of Lubricant Consumed	Lubricant Carbon Content	Fraction Oxidized During Use (ODU factor)	CO ₂ Emissions	CO ₂ Emissions
(TJ)	(tonne-C/TJ)	(fraction)	(tonne CO ₂)	(Gg CO ₂)
			D = A * B * C * 44/12	$E = D/10^3$

Sector	Industrial Processes and Product Use					
Category	Non-Energy Products from Fuels and Solvent Use – Paraffin Wax Use					
Category Code	2D2					
Sheet	1 of 1					
Α	В	С	D	E		
Amount of Paraffin Waxes Consumed	Paraffin Waxes Carbon Content	Fraction Oxidized During Use (ODU factor)	CO ₂ Emissions	CO ₂ Emissions		
(TJ)	(tonne-C/TJ)	(fraction)	(tonne CO ₂)	(Gg CO ₂)		
			D = A * B * C * 44/12	$E = D/10^3$		

Sector	Industrial Processes and Product Use
Category	Electronics Industry - Integrated Circuit or Semiconductor
Category Code	2E1
Sheet	1 of 1

	Α	В	С	D	E
Fluorinated	Fraction of	Annual	Tier 1	CO_2	FC
Compounds (FCs)	Annual	Manufacturing	Default FC	Equivalent	Emissions ⁴⁾
(FCS)	Plant Production	Design Capacity ¹⁾	Emission Factor ²⁾	Conversion Factor ³⁾	
	Capacity	Capacity	Factor	Factor	
	Utilization ¹⁾				
	(fraction)	(Gm ² of silicon processed)	(kg FC/m ² of silicon processed)	(tonne CO ₂ /tonne FC)	(Gg CO ₂ equivalent)
			,		E = A * B * C * D * 10 ³
CF ₄			0.9		
C_2F_6			1		
CHF ₃			0.04		
C ₃ F ₈			0.05		
NF ₃			0.04		
SF ₆			0.2		
Total					

- 1) The same value should be entered in each row.
- 2) In using Tier 1, inventory compilers should not modify, in any way, the set of the FCs assumed here. Inventory compilers should not combine emissions estimated using Tier 1 method with emissions estimated using the Tier 2 or 3 methods. Neither may inventory compilers change the values of any factors in this column.
- 3) Typically, global warming potential (100 year time horizon) identified in the IPCC Assessment Report can be used. These factors should be the same as those used for other sectors/categories to ensure that they are all internally consistent in the inventory.
- 4) The Tier 1 method, unlike the Tier 3 or 2 methods, is designed to give an aggregated estimate of FC emissions although its methodology appears to produce gas-specific emissions.

Soctor	Industrial Processes and Product Use							
Sector								
Category	Electronics I	ndustry - TFT Flat	Panel Display	1				
Category Code	2E2	2E2						
Sheet	1 of 1							
	А	В	С	D	E			
Fluorinated Compounds (FCs)	Fraction of Annual Plant Production Capacity Utilization ¹⁾	Annual Manufacturing Design Capacity ¹⁾	Tier 1 Default FC Emission Factor ²⁾	CO ₂ Equivalent Conversion Factor ³⁾	FC Emissions ⁴⁾			
	(fraction)	(Gm ² of glass processed)	(g FC/m ² of glass processed)	(tonne CO ₂ /tonne FC)	(Gg CO ₂ equivalent)			
					E = A * B * C * D			
CF ₄			0.5					
NF ₃			0.9					
SF ₆			4					
Total								

- 1) The same value should be entered in each row.
- 2) In using Tier 1, inventory compilers should not modify, in any way, the set of the FCs assumed here. Inventory compilers should not combine emissions estimated using Tier 1 method with emissions estimated using the Tier 2 or 3 methods. Neither may inventory compilers change the values of any factors in this column.
- 3) Typically, global warming potential (100 year time horizon) identified in the IPCC Assessment Report can be used. These factors should be the same as those used for other sectors/categories to ensure that they are all internally consistent in the inventory.
- 4) The Tier 1 method, unlike the Tier 3 or 2 methods, is designed to give an aggregated estimate of FC emissions although its methodology appears to produce gas-specific emissions.

Sector	Industrial Processes a	Industrial Processes and Product Use				
Category	Electronics Industry -	Photovoltaics				
Category Code	2E3					
Sheet	1 of 2					
	A	В	С			
Fluorinated Compounds (FCs)	Fraction of Annual Plant Production Capacity Utilization ¹⁾	Annual Manufacturing Design Capacity ¹⁾	Fraction of PV manufacture that uses fluorinated compounds			
	(fraction)	(Mm ² of substrate processed)	(fraction)			
CF ₄						
C ₂ F ₆						
Total						
1) The same value show	uld be entered in each row.					

Sector	Industrial Processes and	Industrial Processes and Product Use					
Category	Electronics Industry - Ph	otovoltaics					
Category Code	2E3						
Sheet	2 of 2						
	D	E	F				
Fluorinated Compounds (FCs)	Tier 1 Default FC Emission Factor ¹⁾	CO ₂ Equivalent Conversion Factor ²⁾	FC Emissions ³⁾				
	(g FC/m ² of substrate processed)	(tonne CO ₂ /tonne FC)	(Gg CO ₂ equivalent)				
			F = A * B * C * D * E / 10 ³				
CF ₄	5						
C ₂ F ₆	0.2						
Total							

- 1) In using Tier 1, inventory compilers should not modify, in any way, the set of the FCs assumed here. Inventory compilers should not combine emissions estimated using Tier 1 method with emissions estimated using the Tier 2 or 3 methods. Neither may inventory compilers change the values of any factors in this column.
- 2) Typically, global warming potential (100 year time horizon) identified in the IPCC Assessment Report can be used. These factors should be the same as those used for other sectors/categories to ensure that they are all internally consistent in the inventory.
- 3) The Tier 1 method, unlike the Tier 3 or 2 methods, is designed to give an aggregated estimate of FC emissions although its methodology appears to produce gas-specific emissions.

Sector	Industrial Pro	Industrial Processes and Product Use						
Category	Electronics Industry - Heat Transfer Fluid							
Category Code	2E4							
Sheet	1 of 1							
	Α	В	С	D	Е			
Fluorinated Compounds (FCs)	Fraction of Annual Plant Production Capacity Utilization	Annual Manufacturing Design Capacity	Tier 1 Default FC Emission Factor ¹⁾	CO ₂ Equivalent Conversion Factor ²⁾	FC Emissions ³⁾			
	(fraction)	(Gm ² of silicon consumed)	(kg C ₆ F ₁₄ /m ² of silicon consumed)	(tonne CO ₂ /tonne C ₆ F ₁₄)	(Gg CO ₂ equivalent)			
					E = A * B * C * D * 10 ³			
C ₆ F ₁₄			0.3					

- 1) Tier 1 default emission factor assumes heat transfer fluids have the same GWP and C₆F₁₄ represents a suitable proxy. Inventory compilers should not change this value in using Tier 1 method.
- 2) Typically, global warming potential (100 year time horizon) identified in the IPCC Assessment Report can be used. These factors should be the same as those used for other sectors/categories to ensure that they are all internally consistent in the inventory.
- 3) The Tier 1 method, unlike the Tier 3 or 2 methods, is designed to give an aggregated estimate of FC emissions although its methodology appears to produce gas-specific emissions.

Sector	Industrial Processes and Product Use						
Category		Product Uses as Substitutes for Ozone Depleting Substances – Refrigeration and Air Conditioning					
Category Code	2F1						
Sheet	1 of 1						
	Α	В	С	D			
HFCs/PFCs (please specify)	Bank in Inventory Year ¹⁾	Average Emission Factor from installed base	Agent in Retired Equipment in Inventory Year	Emissions in Inventory Year			
	(tonne)	(%)	(tonne)	(tonne)			
				D = A * B/100 + C			
HFC-23							

1) In reality, it is necessary in the refrigeration and air conditioning application to deal with the development and tracking of banks. This means that an historical time series of country-specific or globally or regionally derived activity data is required dating back to the introduction of any new HFC or PFC. In order to do this, inventory compilers will need to implement spreadsheet calculations. A typical example, which is workable and inventory compilers could use, can be found in the 2006 Guidelines CDROM. (V3_An1_Calculation_example_for_2F1.xls)

Sector	Industrial Processes and Product Use					
Category	Product Uses as Substitutes for Ozone Depleting Substances – Foam Blowing Agents					
Category Code	2F2					
Sheet	1 of 1					
	Α	В	С	D		
HFCs/PFCs (please specify)	Original Charge in Each of Previous Years ¹⁾	Annual Losses Emission Factor	First Year Loss in Inventory Year ²⁾	Emissions in Inventory Year		
	(tonne)	(%)	(tonne)	(tonne)		
				D = A * B/100 + C		
HFC-245fa						

In reality, it is necessary in the foam application to deal with the historical time series of country-specific
or globally or regionally derived activity data dating back to the introduction of any new HFC or PFC. In
order to do this, inventory compilers will need to implement spreadsheet calculations. A typical example,
which is workable and inventory compilers could use, can be found in the 2006 Guidelines CDROM.
(V3_An1_Calculation_example_for_2F2.xls)

²⁾ For details on the first year loss emission factor, see Table 7.5 in Chapter 7 of this volume. In the case of open-cell foams, the first year loss emission factor is typically 100 %.

Sector	Industrial	Processes and	d Product Use					
Category		Product Uses as Substitutes for Ozone Depleting Substances – Fire Protection						
Category Code	2F3							
Sheet	1 of 1							
	Α	В	С	D	E			
HFCs/PFCs (please specify)	Bank in Inventory Year ¹⁾	Average Emission Factor from installed base	Agent in Retired Equipment in Inventory Year	Rate of Recovery of the Agent in Retired Equipment	Emissions in Inventory Year			
	(tonne)	(%)	(tonne)	(%)	(tonne)			
					E = A * B/100 + C * (1 – D/100)			
HFC-23								

¹⁾ In reality, it is necessary in the fire protection application to deal with the development and tracking of banks. This means that an historical time series of country-specific or globally or regionally derived activity data is required dating back to the introduction of any new HFC or PFC. In order to do this, inventory compilers will need to implement spreadsheet calculations. A typical example, which is workable and inventory compilers could use, can be found in the 2006 Guidelines CDROM. (V3_An1_Calculation_example_for_2F3.xls)

	Sector	Industrial Pro	cesses and Pr	oduct Use			
	Category	Product Uses - Aerosols	Product Uses as Substitutes for Ozone Depleting Substances - Aerosols				
Categ	ory Code	2F4					
	Sheet	1 of 1					
Α		В	С	D	Е		
Quantity of HFCs/PFCs Contained in Aerosol Products Sold in Inventory Year		Quantity of HFCs/PFCs Contained in Aerosol Products Sold in Prior Year	Emission Factor (Loss of Current Year's Use)	Emissions of HFCs/PFCs from Aerosol Products	Emissions of HFCs/PFCs from Aerosol Products		
Chemical ^{1), 2)}	(tonne)	(tonne)	(fraction)	(tonne)	(Gg)		
(please specify)				D = A * C + B * (1 - C)	$E = D/10^3$		
For chemicals	that are used fo	or this application, see	Table 7.1 in Chap	ter 7 of Volume 3.			

²⁾ Insert additional rows if necessary.

	Sector	Industrial Pro	cesses and Pr	oduct Use		
	Category	Product Uses as Substitutes for Ozone Depleting Substances - Solvents				
Categ	ory Code	2F5				
Sheet 1 of 1						
Α		В	С	D	Е	
Quantity of Solvents (HFCs/PFCs) Sold in Inventory Year		Quantity of Solvents (HFCs/PFCs) Sold in Prior Year	Emission Factor (Loss of Current Year's Use)	Emission of HFCs/PFCs from Solvents	Emission of HFCs/PFCs from Solvents	
Chemical ^{1), 2)}	(tonne)	(tonne)	(fraction)	(tonne)	(Gg)	
(please specify)				D = A * C + B * (1 – C)	$E = D/10^3$	
4) Famabamirata	4h a4 auaa a -1 £-	u this souliseties	Table 7.4 in Object			
, i	tnat are used to al rows if neces	or this application, see	rable 7.1 in Chapt	ter / or volume 3.		

	Sector	Industrial Pro	Industrial Processes and Product Use					
	Category	Product Uses as Substitutes for Ozone Depleting Substances – Other Applications						
Categ	ory Code	2F6						
	Sheet	1 of 1						
Α		В	С	D	E			
Quantity of HFCs/PFCs Sold in Inventory Year		Quantity of HFCs/PFCs Sold in Prior Year	Emission Factor (Loss of Current Year's Use)	Emission of HFCs/PFCs from Other Applications	Emission of HFCs/PFCs from Other Applications			
Chemical ^{1), 2)}	(tonne)	(tonne)	(fraction)	(tonne)	(Gg)			
(please specify)				D = A * C + B * (1 – C)	$E = D/10^3$			
For chemicals:	414	r this application, se	- T-bl- 7.4 i- Ob	t 7 - f \ / - h 0				

²⁾ Insert additional rows if necessary.

Sector	Industrial Processes and Product Use				
Category	Other Product Manufacture and Use - Electrical Equipment				
Category Code	2G1				
Sheet	1 of 5 Manufacturing Emissions	of SF ₆ ¹⁾			
	Α	В	С		
Type of Equipment	Total SF ₆ Consumption by Equipment Manufacturers	Manufacturing Emission Factor ²⁾	Manufacturing Emissions		
	(tonne SF ₆)	(fraction)	(tonne SF ₆)		
			C = A * B		
Sealed-Pressure					
Closed-Pressure					
Gas-Insulated Transformers					
Total					

- 1) Emissions of PFCs can be estimated by the same calculation procedure.
- 2) Default emission factors depend on region for which emissions are being estimated. See Tables 8.2 through 8.4 in Chapter 8 of this volume.

Sector	Industrial Processes and Product Use				
Category	Other Product Manufacture and Use - Electrical Equipment				
Category Code	2G1				
Sheet	2 of 5 Equipment Installation I	Emissions of SF ₆ 1)			
	D	E	F		
Type of Equipment	Total Nameplate Capacity of New Equipment Filled on Site (not at the factory)	Installation Emission Factor ²⁾	Equipment Installation Emissions		
	(tonne SF ₆)	(fraction)	(tonne SF ₆)		
			F = D * E		
Sealed-Pressure					
Closed-Pressure					
Gas-Insulated Transformers					
Total			_		

- 1) Emissions of PFCs can be estimated by the same calculation procedure.
- Default emission factors depend on region for which emissions are being estimated. See Tables 8.2 through 8.4 in Chapter 8 of this volume.

Sector	Industrial Processes and Product Use						
Category	Other Product Manufacture an	d Use - Electrical Equip	pment				
Category Code	2G1						
Sheet	3 of 5 Equipment Use Emission	ons of SF ₆ ¹⁾					
	G	Н	I				
Type of Equipment	Total Nameplate Capacity of Installed Equipment	Use Emission Factor ^{2), 3)}	Equipment Use Emissions				
	(tonne SF ₆)	(fraction)	(tonne SF ₆)				
		I = G * H					
Sealed-Pressure							
Closed-Pressure							
Gas-Insulated Transformers							
Total							

- 1) Emissions of PFCs can be estimated by the same calculation procedure.
- Default emission factors depend on region for which emissions are being estimated. See Tables 8.2 through 8.4 in Chapter 8 of this volume.
- 3) The 'use emission factor' includes emissions due to leakage, servicing, maintenance, and equipment failures.

Sector	Industrial Processes and Product Use				
Category	Other Product Manufacture an	d Use - Electrical Equip	oment		
Category Code	2G1				
Sheet	4 of 5 Equipment Disposal Em	nissions of SF ₆ 1)			
	J	K	L		
Type of Equipment	Total Nameplate Capacity of Retiring Equipment	Fraction of SF ₆ Remaining at Retirement ²⁾	Equipment Disposal Emissions		
	(tonne SF ₆)	(fraction)	(tonne SF ₆)		
			L = J * K		
Sealed-Pressure					
Closed-Pressure					
Gas-Insulated Transformers					
Total			_		

- 1) Emissions of PFCs can be estimated by the same calculation procedure.
- 2) Default emission factors depend on region for which emissions are being estimated. See Tables 8.2 through 8.4 in Chapter 8 of this volume.

Sector	Industrial Processes and Product I	llaa			
Sector	industrial Processes and Product	Industrial Processes and Product Use			
Category	Other Product Manufacture and Us	se - Electrical Equipment			
Category Code	2G1				
Sheet	5 of 5 Total Emissions of SF ₆ ¹⁾				
	M	N			
Type of Equipment	Total Emissions	Total Emissions			
	(tonne SF ₆)	(Gg SF ₆)			
	M = C + F + I + L	$N = M/10^3$			
Sealed-Pressure					
Closed-Pressure					
Gas-Insulated					
Transformers					
Total					
Emissions of PFCs can be estimated by the same calculation procedure.					

Sector	Industrial Processes and F		
Category	Other Product Manufacture Uses	and Use - SF ₆ and PFCs	from Other Product
Category Code	2G2		
Sheet	1 of 7 SF ₆ Emissions from	Military Applications (AWACS)
Α	В	С	D
National AWACS Fleet	Emission Factor	SF ₆ Emissions	SF ₆ Emissions
(number of AWACS)	(kg SF ₆ /plane)	(kg)	(Gg)
		C = A * B	$D = C/10^6$

Sector	Industria	I Processes and I	Product Use		
Category	Other Pro Uses	oduct Manufacture	and Use - SF ₆	and PFCs from Othe	r Product
Category Code	2G2				
Sheet	2 of 7 SI Accelera		University a	nd Research Particl	е
Α	В	С	D	E	F
Number of University and Research Particle Accelerators in the Country	SF ₆ Use Factor	SF ₆ Charge Factor	SF ₆ Emission Factor	SF ₆ Emissions	SF ₆ Emissions
(number)	(fraction)	(kg SF ₆ /particle accelerator)	(fraction)	(kg)	(Gg)
				E = A * B * C * D	F = E/10 ⁶

Sector	Industrial Processes and Product Use						
Category	Other Product Uses	Other Product Manufacture and Use - SF ₆ and PFCs from Other Product Uses					
Category Code	2G2						
Sheet	3 of 7 SF ₆ Em Accelerators	nissions from Indu	ustrial and I	Medical Particle			
	Α	В	С	D	E		
Process Description	Number of Particle Accelerators that use SF ₆ by Process Description in the Country	SF ₆ Charge Factor	SF ₆ Emission Factor	SF ₆ Emissions	SF ₆ Emissions		
	(number)	(kg SF ₆ /particle accelerator)	(fraction)	(kg)	(Gg)		
				D = A * B * C	$E = D/10^6$		
Industrial Accelerator (High Voltage: 0.3-23 MV)							
Industrial Accelerator (Low Voltage: <0.3 MV)							
Medical							
Total							

Sector	Industrial Processes and Product Use				
Category	Other Product Manufacture and Use - SF ₆ and PFCs from Other Product Uses				
Category Code	2G2				
Sheet	4 of 7 SF ₆ Emissions ¹⁾ from Adiabatic Uses				
	Α	В	С		
Type of Applications ^{2), 3)}	Sales into application in year t-3	SF ₆ Emissions in year t	SF ₆ Emissions in year t		
(please specify)	(tonne)	(tonne)	(Gg)		
		B = A	$C = B/10^3$		
Total					

- 1) Emissions of PFCs can be estimated by the same calculation procedure.
- 2) For example, car tires, sport shoe soles and tennis balls.
- 3) Insert additional rows, if necessary.

Sector	Industrial Pro	Industrial Processes and Product Use				
Category	Other Produc Uses	t Manufacture an	d Use - SF ₆ and PF	Cs from Othe	er Product	
Category Code	2G2					
Sheet	5 of 7 SF ₆ Er	nissions from S	ound-Proof Glazii	ng		
Α	В	С	D	Е	F	
SF ₆ Purchased to Fill Windows Assembled in Inventory Year	Assembly Emission Factor	Assembly Emissions	Capacity of Existing Windows in Inventory Year	Leakage Emission Factor	Leakage Emissions	
(tonne SF ₆)	(fraction)	(tonne SF ₆)	(tonne SF ₆)	(fraction)	(tonne SF ₆)	
		C = A * B			F = D * E	

Sector	Industrial Proc	esses and Product	Use		
Category	Other Product N Uses	Other Product Manufacture and Use - SF ₆ and PFCs from Other Product Uses			
Category Code	2G2				
Sheet	6 of 7 SF ₆ Emi	ssions from Sound	-Proof Glazing		
G	Н		J	K	
Amount Left in Windows at End of Lifetime (Disposed of in Inventory Year)	Recovery Factor ¹⁾	Disposal Emissions	Total Emissions	Total Emissions	
(tonne SF ₆)	(fraction)	(tonne SF ₆)	(tonne SF ₆)	(Gg SF ₆)	
		I = G * (1 – H)	J = C + F + I	$K = J/10^3$	
Recovery factor is as	sumed to be zero unle	ss country-specific informations	ation is available.		

Sector	Industrial Processes and Product Use				
Category	Other Product Manufacture and Use - SF ₆ and PFCs from Other Product Uses				
Category Code	2G2				
Sheet	7 of 7 Emissions of SF ₆ and PFCs from Other Prompt Emissive Applications				
	Α	В	О	D	
Type of Applications	Sales into application in year t	Sales into application in year t-1	Emissions in year t	Emissions in year t	
(please specify)	(tonne)	(tonne)	(tonne)	(Gg)	
			C = 0.5 * (A + B)	$D = C/10^3$	
Total					

¹⁾ For example, tracers and use in production of optical cables.

²⁾ Insert additional rows, if necessary.

Sector	Industrial Processes and Product Use				
Category	Other Product Manufacture and Use - N₂O from Product Uses				
Category Code	2G3				
Sheet	1 of 2				
	A	В	С		
Type of Applications	Quantity of N ₂ O Supplied	Quantity of N ₂ O Supplied	Emission		
	in this Application Type in	in this Application Type	Factor		
	Year t	in Year t-1			
	(tonne)	(tonne)	(fraction)		
Medical Applications					
Propellant in Aerosol					
Products					
Other (please specify) 1)					
Total					
1) Insert additional rows, if necessary.					

Sector	Industrial Processes and Product Use			
Category	Other Product Manufacture and Use - N ₂ O from Product Uses			
Category Code	2G3			
Sheet	2 of 2			
	D	E		
Type of Applications	N₂O Emission	N ₂ O Emission		
	(tonne)	(Gg)		
	D = (0.5 * A + 0.5 * B) * C	$E = D/10^3$		
Medical Applications				
Propellant in Aerosol				
Products				
Other (please specify) 1)				
Total				
1) Insert additional rows, if necessary.				