

## 8.3: Apache Hadoop


- **Instructor:** Dr. GP Saggese - [gsaggese@umd.edu](mailto:gsaggese@umd.edu)
- **References**
  - Ghemawat et al.: *The Google File System*, 2003
  - Dean et al.: *MapReduce: Simplified Data Processing on Large Clusters*, 2004

- ***Apache Hadoop***
  - Hadoop Ecosystem
  - Hadoop Distributed File System
  - Hadoop MapReduce

- Apache Hadoop
  - *Hadoop Ecosystem*
  - Hadoop Distributed File System
  - Hadoop MapReduce

# Hadoop Ecosystem (aka Hadoop Zoo)

- **Hadoop Map-Reduce**
- **HDFS**
  - Distributed file system
- **Pig**
  - High-level data-flow framework for parallel computation



- **HBase**
  - Scalable, distributed database
  - Structured data storage for large tables (like Google BigTable)
- **Cassandra**
  - Scalable multi-master database with no single points of failure
- **Hive**
  - Data warehouse infrastructure
  - Provide data summarization and ad-hoc querying
- **ZooKeeper**
  - High-performance coordination service for distributed applications
- **YARN, Kafka, Storm, Spark, Solr, ...**

- Apache Hadoop
  - Hadoop Ecosystem
  - *Hadoop Distributed File System*
  - Hadoop MapReduce


# Hadoop Distributed File System (HDFS)

- **HDFS** is a **distributed file system**
  - Designed to store large data sets reliably
  - Part of the Apache Hadoop ecosystem
  - Inspired by the Google File System (GFS)
- 1. Optimized for **high-throughput access** to large files
  - Suitable for batch processing
  - Not low-latency access
- 2. Designed for **fault tolerance and scalability**
  - Ensures fault tolerance through replication
    - Blocks are stored on different nodes and racks
    - Provides data availability even if some nodes fail
  - Follows a primary-secondary architecture
  - Replication strategy improves read performance



# HDFS Architecture

- **NameNode**
  - Store file/dir hierarchy
  - Store file metadata
    - E.g., block location, size, permissions
- **DataNodes**
  - Store actual data blocks
  - Split file into 16-256MB blocks
  - Replicate chunks (2x or 3x) across multiple *DataNodes*
  - Keep replicas in different racks
- **Client**
  - API (e.g., Python, Java) to library
  - Mount HDFS on local filesystem




# HDFS: Read / Write Protocols

## • Read

- Contact *NameNode* for *DataNode* and block pointer
- Choose the nearest *DataNode* for each block
- Connect to *DataNode* for data access
- Reads blocks in parallel to improve performance
- Data is reassembled by the client in correct order

## • Write

- *NameNode* creates blocks
- Assign blocks to multiple *DataNodes*
- Client sends data to *DataNodes*
- *DataNodes* store data
- Blocks are pipelined to other replicas
- Write is considered successful after all replicas acknowledge





# Fault Tolerance and Recovery

---

- *NameNode* monitors *DataNode* heartbeat signals
- On failure, blocks are re-replicated to maintain replication factor
- *NameNode* itself is a single point of failure
  - Solved with HDFS High Availability
- Data integrity ensured using checksums

# HDFS vs Traditional File Systems

---

- Best for **\*\*storing** and processing large-scale files
  - E.g., logs, media, sensor data
  - Commonly used in data lakes and ETL pipelines
  - Supports very large files and directories
  - Performance degrades with many small files
- Optimized for **write-once, read-many** access pattern
- Lacks low-latency access, but provides **high throughput**
  - Good for analytics (OLAP)
  - Not suitable for transactional systems (OLTP)
    - E.g., bank

- Apache Hadoop
  - Hadoop Ecosystem
  - Hadoop Distributed File System
  - *Hadoop MapReduce*

# MapReduce: Hadoop

---

- **Hadoop**: open-source MapReduce implementation



- **Functionalities**

- Partition input data (HDFS)
- Input adapters
  - E.g., HBase, MongoDB, Cassandra, Amazon Dynamo
- Schedule program execution across machines
- Handle machine failures
- Manage inter-machine communication
- Perform *GroupByKey* step
- Output adapters
  - E.g., Avro, ORC, Parquet
- Schedule multiple *MapReduce* jobs

# Data Flow

---

- Store input, intermediate, final outputs in HDFS
  - Operations in Hadoop move disk to disk
- Use adapters to read/partition data in chunks
- Scheduler places map tasks near physical storage of input data
  - Store intermediate results on local FS of Map and Reduce workers
- Output often serves as input for another MapReduce task

# Hadoop Distributed File System (HDFS): Overview

---

- Designed for distributed storage of large datasets
- Built on master-slave architecture
  - NameNode: manages metadata and directory structure
  - DataNodes: store actual data blocks
- Optimized for high throughput rather than low latency
- Stores large files across multiple machines
- Writes are append-only, simplifying consistency
- Fault-tolerant using data replication
  - Default: each block is replicated 3 times
- Ideal for batch processing and big data workloads

# HDFS: Data Storage and Access

---

- Files are split into fixed-size blocks (default: 128MB)
- Blocks distributed across DataNodes for parallelism
- NameNode maintains block-to-DataNode mapping
- Client reads data directly from DataNodes
- Ensures reliability through block replication
- If a DataNode fails, replicas serve the data
- Data locality: computation is moved to where data resides

# Hadoop MapReduce: Overview

---

- Programming model for distributed data processing
- Processes data in parallel across a cluster
- Consists of two main functions:
  - Map: filters and sorts input data
  - Reduce: aggregates intermediate outputs
- Suited for batch jobs over large datasets
- Fault-tolerant: tasks are retried upon failure



# MapReduce: Execution Phases

---

- Input data split into chunks processed by Mappers
- Mapper outputs key-value pairs
- Shuffle and Sort: organizes data by key
  - Intermediate keys are grouped and sent to Reducers
- Reducers aggregate values by key
- Final output written back to HDFS

# Example: Word Count with MapReduce

---

- Input: text files containing words
- Mapper:
  - Reads lines and emits (word, 1) for each word
- Shuffle and Sort:
  - Groups by word, e.g., (word, [1,1,1])
- Reducer:
  - Sums values: emits (word, total\_count)
- Output: word frequencies stored in HDFS

# HDFS vs MapReduce: Complementary Roles

---

- HDFS: distributed storage system
  - Stores large datasets efficiently
- MapReduce: distributed compute model
  - Processes data stored in HDFS
- Together enable scalable and fault-tolerant data analysis

# Benefits and Limitations

---

- Benefits:
  - Scalable and fault-tolerant
  - Handles petabytes of data
  - Open-source and cost-effective
- Limitations:
  - High latency, not suitable for real-time
  - Difficult for complex iterative algorithms
  - Superseded in many cases by Spark and other engines