



UMD DATA605 - Big Data Systems

Lesson 4.3: Data Storage

Instructor: Dr. GP Saggese, gsaggese@umd.edu

- Sources
 - Silberschatz et al. 2020, Chap 12, Physical Storage Systems
 - Silberschatz et al. 2020, Chap 13: Data Storage Structures

- ***Storage***
 - Magnetic Disks / SSD
 - RAID
 - DB Internals

Storage Characteristics


- Storage media trade-offs:
 - Speed of access (e.g., 500-3,500MB/sec)
 - Cost per data unit (e.g., 50 USD/TB)
 - Medium reliability
- Volatile vs non-volatile storage
 - **Volatile**: loses contents when power switched off
 - **Non-volatile**: can survive failures and system crashes
- Sequential vs random access
 - **Sequential**: read the data contiguously
`SELECT * FROM employee`
 - **Random**: read the data from anywhere at any time
`SELECT * FROM employee`
`WHERE name LIKE '__a__b'`
- Need to know how data is stored in order to optimize access



Storage Hierarchy


Organize storage by speed and cost

- **Cache**
 - Fastest, most costly
 - ~MBs on chip
 - DB developers consider cache effects
- **Main memory**
 - Up to 100s of GBs
 - Typically can't store entire DB
 - Volatile
- **Flash memory / SSDs**
 - More expensive than RAM, less than magnetic disk
 - Non-volatile, random access
- **Magnetic disk**
 - Long-term online storage
 - Non-volatile
- **Optical disk (CD, Blue Ray)**
 - Mainly read-only
- **Magnetic tapes**
 - Backup, archival data
 - Stored long-term, e.g., legal reasons
 - Sequential-access



- **Primary storage:** cache, main memory
- **Secondary (or online):** flash memory, magnetic disk
- **Offline:** optical, magnetic tape

Storage Hierarchy



source: <http://cse1.net/recaps/4-memory.html>

How Important Is Memory Hierarchy?

- Trade-offs shifted over last 10-15 years
- **Innovations:**
 - Fast network, SSDs, large memories
 - Data volume growing rapidly
- **Observations:**
 - Faster to access another computer's memory through network than your own disk
 - Cache plays a crucial role
 - In-memory DBs
 - Data often fits in memory of a machine cluster
 - Disk considerations less important
 - Disks still store most data today
- Algorithms depend on available technology

- Storage
 - *Magnetic Disks / SSD*
 - RAID
 - DB Internals

Connecting disks to a server

Connecting Disks to a Server

- **Disks** (magnetic and SSDs) connect to computer:
 - High-speed bus interconnections
 - High-speed network
- **High-speed interconnection**
 - Serial ATA (SATA)
 - Serial Attached SCSI (SAS)
 - NVMe (Non-volatile Memory Express)
- **High-speed networks**
 - Storage Area Network (SAN): iSCSI, Fiber Channel, InfiniBand
 - **Network Attached Storage (NAS)**
 - Provides file-system interface (e.g., NFS)
 - Cloud storage: Data stored in cloud, accessed via API, Object store, High latency

Magnetic Disks

- 1956
 - IBM RAMAC
 - 24" platters
 - 5 million characters



From Computer Desktop Encyclopedia
Reproduced with permission.
© 1996 International Business Machines Corporation
Unauthorized use not permitted.



Magnetic Disks


- 1979



- SEAGAT

- 5MB

From Computer Desktop Encyclopedia
Reproduced with permission.
© 1998 Seagate Technologies



- 1998



- SEAGAT

- 47GB

From Computer Desktop Encyclopedia
Reproduced with permission.
© 1998 Seagate Technologies



- 2006

- Western
Digital
 - 500GB



NEW!

500 GB
WD Caviar® SE16

16 MB cache. SATA 300 MB/s.
Fast. Cool. Quiet.

[Shop Now](#) [More Info](#)

Magnetic Disks: Components

- **Platters**

- Rigid metal with magnetic material on both surfaces
- Spins at 5400 or 9600 RPM
- *Tracks* subdivided into *sectors* (smallest unit read/written, with a checksum)

- **Read-write heads**


- Store information magnetically
- Spinning creates a cushion maintaining heads a few microns from the surface
- *Cylinder* is the i -th tracks of all platters (read/written together)

- **Arm**

- Moves all heads along the disks

- **Disk controller**

- Accepts commands to read/write a sector
- Operates arm/heads
- Remaps bad sectors to a different location



Magnetic Disks: Current Specs



- **Capacity**
 - 10 terabyte and more
- **Access time**
 - Time to start reading data
 - Seek time
 - Move arm across cylinders (2-20ms)
 - Rotational latency time
 - Wait for sector access (4-12ms)
- **Data-transfer rate**
 - Transfer begins once data is reached
 - Transfer rate: 50-200MB/sec
 - Sector (disk block): logical unit of storage (4-16KB)
 - Sequential access: blocks on same or adjacent tracks
 - Random access: each request requires a seek
 - IOPS: number of random single block accesses per second (50-200 IOPS)
- **Reliability**
 - Mean time to failure (MTTF): average time system runs without failure
 - HDD lifespan: ~5 years

Accessing Data Speed

- **Random data transfer rates**

- Time to read a random sector
- It has 3 components
 - Seek time: Time to seek to the track (Average 4 to 10ms)
 - Rotational latency: Waiting for the sector to get under the head (Average 4 to 11ms)
 - Transfer time: Time to transfer the data (Very low)
- About 10ms per access
 - Randomly accessed blocks: 100 block transfers ($100/\text{sec} \times 4 \text{ KB/block} = 50 \text{ KB/s}$)


- **Serial data transfer rates**

- Data transfer rate without seek
- 30-50MB/s to 200MB/s

- **Seeks are bad!**

Solid State Disk (SSD)

- Mainstream around 2000s
- Like non-volatile RAM (NAND and NOR)
- **Capacity**
 - 250, 500 GBs (vs 1-10 TB for HDD)
- **Access time**
 - Latency for random access 1,000x smaller than HDD
 - E.g., 20-100 us (vs 10 ms HDDs)
 - Multiple random requests (e.g., 32) in parallel
 - 10,000 IOPS (vs 50/200 for HDDs)
 - Require reading an entire “page” of data (typically 4KB)
 - Equivalent to a block in magnetic disks
- **Data-transfer rate**
 - 1 GB/s (vs 200 MB/s HDD)
 - Typically limited by interface speed
 - Reads and writes ~500MB/s for SATA and 2-3 GB/s for NVMe
 - Lower power consumption than HDDs
 - Writing to SSD slower than reading (~2-3x)
 - Requires erasing all pages in the block
- **Reliability**
 - Limit to how many times a flash page can be erased (~1M times)
- Better than HDD from any point of view, but more expensive per GB



- Storage
 - Magnetic Disks / SSD
 - **RAID**
 - DB Internals

RAID

- RAID = Redundant Array of Independent Disks
- **Problem**
 - Storage capacity growing exponentially
 - Data-storage needs (web, DBs, multimedia) growing faster
 - Need many disks
 - MTTF between disk failures shrinking (e.g., days)
 - Single data copy leads to unacceptable data loss frequency
- **Observations**
 - Disks cheap
 - Failures costly
 - Use extra disks for reliability
 - Store data redundantly
 - Data survives disk failure
 - Bonus: faster data access
- **Goal**
 - Present a logical view of a large, reliable disk from many unreliable disks
 - Different RAID levels (reliability vs performance)




Improve Reliability / Performance with RAID

- **Reliability**

- Use redundancy
 - Store data multiple times: E.g., mirroring
 - Reconstruct data if a disk fails
 - Increase MTTF
- Assume independence of disk failure
 - Consider power failures and natural disasters
 - Aging disks increase failure probability

- **Performance**

- Parallel access to multiple disks: E.g., mirroring, increase read requests
- Stripe data across multiple disks: Increase transfer rate



RAID Levels


- **RAID 0: No redundancy**
 - Array of independent disks
 - Same access-time
 - Increased transfer rate
- **RAID 1: Mirroring**
 - Copy of disks
 - If one disk fails, you have a copy
 - Reads: higher data rate possible
 - Writes: write to both disks
- **RAID 2: Memory-style error correction**
 - Use extra bits to reconstruct
 - Superseded by RAID 5
- **RAID 3: Interleaved parity**
 - One disk contains parity for main data disks
 - Handle single disk failure
 - Little overhead (only 25%)
- **RAID 5: Block-interleaved distributed parity**
 - Distributed parity blocks



(a) RAID 0: nonredundant striping



(b) RAID 1: mirrored disks



(c) RAID 2: memory-style error-correcting codes



(d) RAID 3: bit-interleaved parity



(f) RAID 5: block-interleaved distributed parity

Choosing a RAID Level

- Main choice: RAID 1 vs. RAID 5
- **RAID 1 better write performance**
 - E.g., writing a single block
 - RAID 1: 2 block writes
 - RAID 5: 2 block reads, 2 block writes
 - Best for high update rate, small data (e.g., log disks)
- **RAID 5 lower storage cost**
 - RAID 1: 2x more disks
 - Best for low update rate, large data




(a) RAID 0: nonredundant striping



(b) RAID 1: mirrored disks



(c) RAID 2: memory-style error-correcting codes



(d) RAID 3: bit-interleaved parity




(f) RAID 5: block-interleaved distributed parity




- Storage
 - Magnetic Disks / SSD
 - RAID
 - ***DB Internals***

(Centralized) DB Internals

- User processes
 - Issue commands to DB
- Server processes
 - Receive commands, call DB code
- Process monitor process
 - Monitor DB processes
 - Recover from failures
- Lock manager process
 - Lock grant/release
 - Detect deadlocks
- Database writer process
 - Write modified buffer blocks to disk continuously
- Log writer process
 - Write log records to stable storage
- Checkpoint process
 - Perform periodic checkpoints
- Shared memory
 - Contain shared data
 - Buffer pool, Lock table, Log buffer, Caches (e.g., query plans)
 - Protect data with mutual exclusion locks



DB Internals



- **Query Processing Engine**
 - Execute user query
 - Specify page sequence for memory
 - Operate on tuples for results
- **Buffer Manager**
 - Transfer pages from disk to memory
 - Manage limited memory
- **Storage hierarchy**
 - Map tables to files
 - Map tuples to disk blocks