
Matrices In Geometry



G. V. V. Sharma

About this Book

This book introduces matrices through high school coordinate geometry. This approach makes it easier for beginners to learn Python for scientific computing. All problems in the book are from NCERT mathematics textbooks from Class 9-12. Exercises are from CBSE board exam papers.

The content is sufficient for industry jobs and covers nearly all matrix prerequisites for machine learning. There is no copyright, so readers are free to print and share.

License: https://creativecommons.org/licenses/by-sa/3.0/
and
https://www.gnu.org/licenses/fdl-1.3.en.html

First manual appeared in January 2018
First edition published on July 10, 2024

iIn this edition, some incorrect solutions were removed. All figures redrawn. More problems added.

CONTENTS

1 AE 2026 4
1.1 Formulae 4

2 BT 2025 17
2.1 Formulae 17

3 AG 2025 21
3.1 Formulae 21

4 GATE CE-2 2025 23
4.1 Formulae 23

5 GATE-BM-2025 23
5.1 Formulae 23
5.2 Solved Questions 34

1. AE 2026

A. Formulae

1.1.1

$$\Pr(M) + \Pr(E) - \Pr(ME) + \Pr(M+E)' = 1 \tag{1.1.1.1}$$

1.1.2

$$A + A' = 1, \quad AA' = 0 \tag{1.1.2.1}$$

$$\implies \Pr(A + A') = \Pr(1) = 1 \quad \Pr(AA') = \Pr(0) = 0 \tag{1.1.2.2}$$

1.1.3

$$\Pr(A + A') = \Pr(A) + \Pr(A') \tag{1.1.3.1}$$

1.1.4 Difference rule of probability

$$\Pr(AB') = \Pr(A) - \Pr(AB) \tag{1.1.4.1}$$

Solution: From (1.1.2.1)

$$A = A \cdot 1 = A(B + B') = AB + AB' \tag{1.1.4.2}$$

Also,

$$(AB)(AB') = 0 \tag{1.1.4.3}$$

From (1.1.3.1),

$$\Pr(A) = \Pr(AB + AB') = \Pr(AB) + \Pr(AB') \tag{1.1.4.4}$$

Rearranging, we get:

$$P(AB') = P(A) - P(AB) \tag{1.1.4.5}$$

1.1.5 The Laplace transform is defined as

$$g(t) \overset{\mathcal{L}}{\longleftrightarrow} G(s) = \int_0^\infty e^{-st} g(t)\, dt \tag{1.1.5.1}$$

1.1.6

$$g'(t) \overset{\mathcal{L}}{\longleftrightarrow} sG(s) - g(0) \tag{1.1.6.1}$$

Solution: Applying integration by parts,

$$u = e^{-st}, dv = g'(t)\, dt \tag{1.1.6.2}$$

$$\implies \int_0^\infty e^{-st} g'(t)\, dt = \left[e^{-st} g(t)\right]_0^\infty - \int_0^\infty \left(-se^{-st}\right) g(t)\, dt \tag{1.1.6.3}$$

$$= -g(0) + s\int_0^\infty e^{-st} g(t)\, dt \tag{1.1.6.4}$$

yielding (1.1.6.1).

1.1.7

$$g''(t) \overset{\mathcal{L}}{\longleftrightarrow} s^2 G(s) - sg(0) - g'(0) \tag{1.1.7.1}$$

1.1.8

$$e^{at} g(t) \overset{\mathcal{L}}{\longleftrightarrow} G(s-a) \tag{1.1.8.1}$$

Solution:

$$\implies e^{at} g(t) \overset{\mathcal{L}}{\longleftrightarrow} \int_0^\infty e^{-st} \left(e^{at} g(t)\right) dt \tag{1.1.8.2}$$

$$= \int_0^\infty e^{-(s-a)t} g(t)\, dt \tag{1.1.8.3}$$

yielding (1.1.8.1).

1.1.9 The unit step function is defined as

$$u(t) = \begin{cases} 1 & t > 0 \\ 0 & t < 0 \end{cases} \tag{1.1.9.1}$$

1.1.10

$$u(t) \overset{\mathcal{L}}{\longleftrightarrow} \frac{1}{s} \tag{1.1.10.1}$$

Solution:

$$\int_0^\infty e^{-st}\, dt = \left(-\frac{e^{-st}}{s}\right)_0^\infty = \frac{1}{s} \quad \Re(s) > 0 \tag{1.1.10.2}$$

1.1.11

$$tu(t) \overset{\mathcal{L}}{\longleftrightarrow} \frac{1}{s^2} \tag{1.1.11.1}$$

Solution: Differentiating (1.1.10.2) with respect to s results in (1.1.11.1).

1.1.12

$$e^{-at} u(t) \overset{\mathcal{L}}{\longleftrightarrow} \frac{1}{s+a}, \quad \Re(s) > \Re(a). \tag{1.1.12.1}$$

Solution: See (1.1.10.1) and (1.1.8.1).

1.1.13

$$\begin{aligned} \cos(at)u(t) &\overset{\mathcal{L}}{\longleftrightarrow} \frac{s}{s^2+a^2} \\ \sin(at)u(t) &\overset{\mathcal{L}}{\longleftrightarrow} \frac{a}{s^2+a^2} \end{aligned} \quad \Re(s) > a \tag{1.1.13.1}$$

Solution: From (1.1.8.1) and (1.1.10.1),

$$e^{\jmath at}u(t) \overset{\mathcal{L}}{\longleftrightarrow} \frac{1}{s-\jmath a}, \quad \Re(s) > a \tag{1.1.13.2}$$

$$\implies \cos(at)u(t) + \jmath \sin(at)u(t) \overset{\mathcal{L}}{\longleftrightarrow} \frac{s+\jmath a}{(s-\jmath a)(s+\jmath a)} \tag{1.1.13.3}$$

$$= \frac{s}{s^2+a^2} + \jmath \frac{a}{s^2+a^2} \tag{1.1.13.4}$$

resulting in (1.1.13.1).

1.1.14 Solve

$$\frac{d^2y}{dx^2} = -\alpha^2 y, \alpha \neq 0 \tag{1.1.14.1}$$

Solution: Applying the Laplace transform on both sides, and using (1.1.7.1),

$$s^2Y(s) - sy(0) - y'(0) = -\alpha^2 Y(s) \tag{1.1.14.2}$$

Substituting

$$y(0) = \beta, y'(0) = \gamma \tag{1.1.14.3}$$

in (1.1.14.2),

$$Y(s) = \frac{s\beta + \gamma}{s^2+\alpha^2} \tag{1.1.14.4}$$

$$= \frac{s\beta}{s^2+\alpha^2} + \frac{\gamma}{s^2+\alpha^2} \tag{1.1.14.5}$$

yielding

$$y(t) = \beta\cos(\alpha t) + \frac{\gamma}{\alpha}\sin(\alpha t) \tag{1.1.14.6}$$

from (1.1.13.1).

1.1.15 (Euler's Method of Forward Differences.) Numerically solve

$$\frac{dy}{dx} = f(x,y), y(x_0) = y_0 \tag{1.1.15.1}$$

Solution: By definition,

$$\left.\frac{dy}{dx}\right|_{x=x_0} = \lim_{h\to 0} \frac{y(x_0+h) - y(x_0)}{h} \tag{1.1.15.2}$$

which can be expressed using the notation

$$y_0' = \frac{y_1 - y_0}{h} \tag{1.1.15.3}$$

Similarly,

$$y_n'' = \frac{y_{n+1}' - y_n'}{h} \tag{1.1.15.4}$$

From (1.1.15.3),

$$y'_{n+1} = \frac{y_{n+2} - y_{n+1}}{h}, y'_n = \frac{y_{n+1} - y_n}{h} \tag{1.1.15.5}$$

yielding

$$y''_n = \frac{y_{n+2} - 2y_{n+1} + y_n}{h^2} \tag{1.1.15.6}$$

upon simplification.

1.1.16 Kronecker delta function

$$\delta_n = \begin{cases} 1, & n = 0 \\ 0, & \text{otherwise} \end{cases} \tag{1.1.16.1}$$

1.1.17

$$f_0 \int_{-\frac{1}{2f_0}}^{\frac{1}{2f_0}} e^{\mathrm{j}2\pi n f_0 t}\, dt = \delta_n \tag{1.1.17.1}$$

1.1.18 The Fourier Series. Let

$$x(t) = \sum_{k=-\infty}^{\infty} x_0(t)\,(t - nT_0) \tag{1.1.18.1}$$

be a periodic signal with

$$x(t) = \begin{cases} x_0(t), & t \in \left(-\frac{T_0}{2}, \frac{T_0}{2}\right) \\ 0 & \text{otherwise} \end{cases}. \tag{1.1.18.2}$$

Then,

$$x(t) = \sum_{n=-\infty}^{\infty} c_n e^{\mathrm{j}2\pi n f_0 t}, \quad f_0 = \frac{1}{T_0} \tag{1.1.18.3}$$

Show that

$$c_n = f_0 \int_{-\frac{1}{2f_0}}^{\frac{1}{2f_0}} x_0(t)\, e^{-\mathrm{j}2\pi n f_0 t}\, dt \tag{1.1.18.4}$$

Solution: From (1.1.18.3),

$$\int_{-\frac{1}{2f_0}}^{\frac{1}{2f_0}} x(t)\, e^{-\mathrm{j}2\pi n f_0 t}\, dt = \int_{-\frac{1}{2f_0}}^{\frac{1}{2f_0}} \left(\sum_{k=-\infty}^{\infty} c_k e^{\mathrm{j}2\pi k f_0 t} \right) e^{-\mathrm{j}2\pi n f_0 t}\, dt \tag{1.1.18.5}$$

$$\int_{-\frac{1}{2f_0}}^{\frac{1}{2f_0}} x_0(t)\, e^{-\mathrm{j}2\pi n f_0 t}\, dt = \sum_{k=-\infty}^{\infty} c_k \int_{-\frac{1}{2f_0}}^{\frac{1}{2f_0}} e^{\mathrm{j}2\pi (k-n) f_0 t}\, dt \tag{1.1.18.6}$$

$$= \frac{1}{f_0} \sum_{k=-\infty}^{\infty} c_k \delta_{k-n} \tag{1.1.18.7}$$

upon substituting from (1.1.18.2) and (1.1.17.1), yielding (1.1.18.4).

1.1.19 The rectangular function. The unit rectangular function is defined as

$$\text{rect}\,(t) = \begin{cases} 1 & t \in \left(-\frac{1}{2}, \frac{1}{2}\right) \\ 0 & \text{otherwise} \end{cases} \tag{1.1.19.1}$$

1.1.20 Square Wave. Consider the Fourier series with

$$x_0(t) = \text{rect}\,(t), \quad T_0 = 2. \tag{1.1.20.1}$$

Show that

$$c_n = \frac{\sin\left(\frac{\pi k}{2}\right)}{\pi k} \tag{1.1.20.2}$$

Solution: Substituting $f_0 = \frac{1}{2}$ in (1.1.18.4),

$$c_n = \frac{1}{2}\int_{-1}^{1} e^{-j\pi kt}\, dt \tag{1.1.20.3}$$

$$= \left[\frac{\sin(\pi kt)}{2\pi k}\right]_{-\frac{1}{2}}^{\frac{1}{2}} \tag{1.1.20.4}$$

The following code verifies the result in Fig. 1.1.20.1. Note that Fig. 1.1.20.1 is continuous while (1.1.20.1) is discontinuous. So (1.1.20.2) provides only an approximation. This is known as the Gibbs' phenomenon.

codes/Fourier.py




Fig. 1.1.20.1. Gibbs phenomenon

1.1.21 If

$$x(t) \overset{\mathcal{F}}{\longleftrightarrow} c_n, \tag{1.1.21.1}$$

show that

$$x(t - t_0) \overset{\mathcal{F}}{\longleftrightarrow} c_n e^{-\mathrm{J}2\pi n t_0}, \tag{1.1.21.2}$$

Solution:

$$\int_{-\frac{1}{2f_0}}^{\frac{1}{2f_0}} x_0\left(t-t_0\right) e^{-\jmath 2\pi n f_0 t}\, dt = \int_{-\frac{1}{2f_0}}^{\frac{1}{2f_0}} x_0\left(t\right) e^{-\jmath 2\pi n f_0 (t+t_0)}\, dt \tag{1.1.21.3}$$

$$= e^{\jmath 2\pi n f_0 t_0} \int_{-\frac{1}{2f_0}}^{\frac{1}{2f_0}} x_0\left(t\right) e^{-\jmath 2\pi n f_0 t}\, dt \tag{1.1.21.4}$$

after a change of variables. Note that the limits of integration are unchanged due the periodicity of $x(t)$. Transferring the exponential term in (1.1.21.4) to the L.H.S yields (1.1.21.2).

1.1.22 The standard 2-D basis vectors are defined as

$$\mathbf{e}_1 = \begin{pmatrix} 1 \\ 0 \end{pmatrix}, \mathbf{e}_2 = \begin{pmatrix} 0 \\ 1 \end{pmatrix}. \tag{1.1.22.1}$$

Also,

$$\mathbf{1} = \begin{pmatrix} 1 \\ 1 \end{pmatrix} \tag{1.1.22.2}$$

1.1.23 Find the echelon form of the matrix

$$\mathbf{A} = \begin{pmatrix} 1 & 4 & 2 \\ 2 & 8 & 4 \\ 3 & 12 & 6 \end{pmatrix} \tag{1.1.23.1}$$

Solution: Following row reduction,

$$\mathbf{A} \xrightarrow{R_2 \to R_2 - 2R_1} \begin{pmatrix} 1 & 4 & 2 \\ 0 & 0 & 0 \\ 3 & 12 & 6 \end{pmatrix} \xrightarrow{R_3 \to R_3 - 3R_1} \begin{pmatrix} 1 & 4 & 2 \\ 0 & 0 & 0 \\ 0 & 0 & 0 \end{pmatrix} \tag{1.1.23.2}$$

1.1.24 The rank of a matrix is defined to be the number of nonzero rows in echelon form. $\therefore \text{rank}\left(\mathbf{A}\right) = 1$.

1.1.25 A matrix is said to be singular if its rank is nonzero.

1.1.26 For

$$\mathbf{A} = \mathbf{u}\mathbf{v}^\top, \text{rank}\left(\mathbf{A}\right) = 1. \tag{1.1.26.1}$$

where both $\mathbf{u}$ and $\mathbf{v}$ are n-dimensional real-valued non-zero column vectors.

Solution: Let

$$\mathbf{u} = \begin{pmatrix} 1 \\ 2 \\ 3 \end{pmatrix}, \mathbf{v} = \begin{pmatrix} 1 \\ 4 \\ 2 \end{pmatrix}. \tag{1.1.26.2}$$

Then

$$\mathbf{A} = \mathbf{u}\mathbf{v}^\top = \begin{pmatrix} 1 \\ 2 \\ 3 \end{pmatrix} \begin{pmatrix} 1 & 4 & 2 \end{pmatrix} \tag{1.1.26.3}$$

$$= \begin{pmatrix} 1 & 4 & 2 \\ 2 & 8 & 4 \\ 3 & 12 & 6 \end{pmatrix} \tag{1.1.26.4}$$

From (1.1.23.2) and Definition 1.1.24, we obtain (1.1.26.1).

1.1.27

$$\left|\mathbf{A}^\top\right| = \left|\mathbf{A}\right| \tag{1.1.27.1}$$

1.1.28

$$\left|\mathbf{A}\mathbf{B}\right| = \left|\mathbf{A}\right| \left|\mathbf{B}\right| \tag{1.1.28.1}$$

Solution: If $\mathbf{A}$ is invertible

$$\mathbf{A} = \mathbf{E}_1\mathbf{E}_2 \cdots \mathbf{E}_k \tag{1.1.28.2}$$

where $\mathbf{E}_i$ are invertible matrices. For any single elementary matrix $\mathbf{E}$, it is easy to verify that

$$\left|\mathbf{E}\mathbf{B}\right| = \left|\mathbf{E}\right| \left|\mathbf{B}\right|. \tag{1.1.28.3}$$

$$\therefore \left|\mathbf{A}\mathbf{B}\right| = \left|\mathbf{E}_1\mathbf{E}_2 \cdots \mathbf{E}_k\mathbf{B}\right| \tag{1.1.28.4}$$

$$= \left|\mathbf{E}_1\right| \left|\mathbf{E}_2 \cdots \mathbf{E}_k\mathbf{B}\right| \tag{1.1.28.5}$$

$$= \left|\mathbf{E}_1\right| \left|\mathbf{E}_2\right| \cdots \left|\mathbf{E}_k\right| \left|\mathbf{B}\right| \tag{1.1.28.6}$$

For $\mathbf{B} = \mathbf{I}$,

$$\left|\mathbf{A}\right| = \left|\mathbf{E}_1\right| \left|\mathbf{E}_2\right| \cdots \left|\mathbf{E}_k\right| \tag{1.1.28.7}$$

which upon substituting in (1.1.28.6) yields

$$\left|\mathbf{A}\mathbf{B}\right| = \left|\mathbf{A}\right| \left|\mathbf{B}\right| \tag{1.1.28.8}$$

1.1.29

$$\left|\mathbf{A^{-1}}\right| = \frac{1}{\left|\mathbf{A}\right|} \tag{1.1.29.1}$$

1.1.30 If

$$\mathbf{A}\mathbf{x} = \lambda\mathbf{x}, \tag{1.1.30.1}$$

then λ is an eigenvalue $\mathbf{x}$ of $\mathbf{A}$.

1.1.31 (1.1.30.1) can be expressed as

$$\begin{aligned} (\lambda\mathbf{I} - \mathbf{A})\,\mathbf{x} &= 0 \\ \implies p_{\mathbf{A}}(\lambda) = (\lambda - \lambda_i) &= \left|\lambda\mathbf{I} - \mathbf{A}\right| = 0 \end{aligned} \tag{1.1.31.1}$$

where $p_{\mathbf{A}}(\lambda)$ is defined to be the characteristic polynomial of $\mathbf{A}$ and λ_i are the eigenvalues.

1.1.32

$$\sum_{i=1}^{n} \lambda_i = \text{Tr}(\mathbf{A}) \tag{1.1.32.1}$$

$$\prod_{i=1}^{n} \lambda_i = \left|\mathbf{A}\right| \tag{1.1.32.2}$$

Solution: From (1.1.31.1),

$$\left|\lambda\mathbf{I} - \mathbf{A}\right| = \lambda^n - \left(\sum_{i=1}^{n} \lambda_i\right)\lambda^{n-1} + \cdots + (-1)^n \prod_{i=1}^{n} \lambda_i \tag{1.1.32.3}$$

Evaluating the determinant $\left|\lambda\mathbf{I} - \mathbf{A}\right|$ using cofactor expansion, the only term that contributes to λ^n and λ^{n-1} is the product of the principal diagonal entries

$$\prod_{i=1}^{n} (\lambda - a_{ii}) = \lambda^n - \left(\sum_{i=1}^{n} a_{ii}\right)\lambda^{n-1} + \dots \tag{1.1.32.4}$$

where a_{ii} denotes the diagonal elements of $\mathbf{A}$. Equating the coefficient of λ^{n-1} from (1.1.32.3) and (1.1.32.4) yields (1.1.32.1) From (1.1.31.1),

$$p_{\mathbf{A}}(0) = \prod_{i=1}^{n} \lambda_i = \left|\mathbf{A}\right| \tag{1.1.32.5}$$

1.1.33 $\mathbf{A}$ and $\mathbf{A}^\top$ have the same eigenvalues.

Solution: From (1.1.29.1),

$$\left|\mathbf{A} - \lambda\mathbf{I}\right| = \left|(\mathbf{A} - \lambda\mathbf{I})^\top\right| \tag{1.1.33.1}$$

$$= \left|\mathbf{A}^\top - \lambda\mathbf{I}\right|, \tag{1.1.33.2}$$

completing the proof.

1.1.34 The equation of a conic with directrix $\mathbf{n}^\top\mathbf{x} = c$, eccentricity e and focus $\mathbf{F}$ is given by

$$\text{g}(\mathbf{x}) = \mathbf{x}^\top\mathbf{V}\mathbf{x} + 2\mathbf{u}^\top\mathbf{x} + f = 0 \tag{1.1.34.1}$$

where

$$\mathbf{V} = \|\mathbf{n}\|^2\mathbf{I} - e^2\mathbf{n}\mathbf{n}^\top, \tag{1.1.34.2}$$

$$\mathbf{u} = ce^2\mathbf{n} - \|\mathbf{n}\|^2\mathbf{F}, \tag{1.1.34.3}$$

$$f = \|\mathbf{n}\|^2\|\mathbf{F}\|^2 - c^2e^2 \tag{1.1.34.4}$$

Solution:

$$\|\mathbf{x}-\mathbf{F}\|^2 = e^2\frac{(\mathbf{n}^\top\mathbf{x}-c)^2}{\|\mathbf{n}\|^2} \tag{1.1.34.5}$$

$$\implies \|\mathbf{n}\|^2(\mathbf{x}-\mathbf{F})^\top(\mathbf{x}-\mathbf{F}) = e^2\left(\mathbf{n}^\top\mathbf{x}-c\right)^2 \tag{1.1.34.6}$$

$$\implies \|\mathbf{n}\|^2\left(\mathbf{x}^\top\mathbf{x}-2\mathbf{F}^\top\mathbf{x}+\|\mathbf{F}\|^2\right) = e^2\left(c^2+\left(\mathbf{n}^\top\mathbf{x}\right)^2-2c\mathbf{n}^\top\mathbf{x}\right) \tag{1.1.34.7}$$

$$= e^2\left(c^2+\left(\mathbf{x}^\top\mathbf{n}\mathbf{n}^\top\mathbf{x}\right)-2c\mathbf{n}^\top\mathbf{x}\right) \tag{1.1.34.8}$$

which can be expressed as (1.1.34.1) after simplification.

1.1.35 The polar form of a conic section is given as:

$$r = \frac{ep}{1+e\cos(\theta-\theta_0)} \tag{1.1.35.1}$$

where

- r is the distance from the focus(origin) to a point on the curve.
- e is the eccentricity of the conic
- p is the distance from the focus to the directrix
- θ_0 is the angle that defines the orientation of the major axis of the conic section relative to the polar reference axis ($\theta = 0$).

Solution: From (1.1.34.1), the general equation of a conic in matrix form is given by

$$\mathbf{x}^\top\mathbf{V}\mathbf{x}+2\mathbf{u}^\top\mathbf{x}+f=0 \tag{1.1.35.2}$$

For a conic with a focus at the origin ($\mathbf{F}=\mathbf{0}$), unit normal vector $\mathbf{n} = \begin{pmatrix}\cos\theta_0\\ \sin\theta_0\end{pmatrix}$, eccentricity e, and directrix distance parameter $c=-p$, substituting into (1.1.34.2)–(1.1.34.4) yields:

$$\mathbf{V} = \mathbf{I}-e^2\mathbf{n}\mathbf{n}^\top, \tag{1.1.35.3}$$

$$\mathbf{u} = -pe^2\mathbf{n}, \tag{1.1.35.4}$$

$$f = -p^2e^2 \tag{1.1.35.5}$$

Expressing $\mathbf{x}$ directly in polar coordinates yields

$$\mathbf{x} = r\mathbf{r}(\theta), \quad \text{where } \mathbf{r}(\theta) = \begin{pmatrix}\cos\theta\\ \sin\theta\end{pmatrix} \tag{1.1.35.6}$$

Substituting into (1.1.35.2) yields

$$r^2\left(\mathbf{r}(\theta)^\top\mathbf{V}\mathbf{r}(\theta)\right)+2r\left(\mathbf{u}^\top\mathbf{r}(\theta)\right)+f=0 \tag{1.1.35.7}$$

Evaluating the inner products:

$$\mathbf{n}^\top \mathbf{r}(\theta) = \begin{pmatrix}\cos\theta_0 & \sin\theta_0\end{pmatrix}\begin{pmatrix}\cos\theta \\ \sin\theta\end{pmatrix} = \cos(\theta-\theta_0) \tag{1.1.35.8}$$

$$\mathbf{r}(\theta)^\top \mathbf{V}\mathbf{r}(\theta) = \mathbf{r}(\theta)^\top \left(\mathbf{I} - e^2\mathbf{n}\mathbf{n}^\top\right)\mathbf{r}(\theta) = 1 - e^2\cos^2(\theta-\theta_0) \tag{1.1.35.9}$$

$$\mathbf{u}^\top \mathbf{r}(\theta) = -pe^2\cos(\theta-\theta_0) \tag{1.1.35.10}$$

Substituting these into (1.1.35.7):

$$r^2\left[1-e^2\cos^2(\theta-\theta_0)\right] - 2rpe^2\cos(\theta-\theta_0) - p^2e^2 = 0 \tag{1.1.35.11}$$

Factoring the quadratic expression:

$$\left[r(1+e\cos(\theta-\theta_0)) - ep\right]\left[r(1-e\cos(\theta-\theta_0)) + ep\right] = 0 \tag{1.1.35.12}$$

Taking the positive real root for radial distance $r > 0$:

$$r(1+e\cos(\theta-\theta_0)) = ep \tag{1.1.35.13}$$

yielding (1.1.35.1)

1.1.36 Gravitational parameter of a body μ is defined as

$$\mu = GM \tag{1.1.36.1}$$

where M is the mass of the body

1.1.37 Specific angular momentum for a satellite with position vector $\mathbf{r}$ and velocity vector $\mathbf{v}$ is

$$h = \|\mathbf{r}\times\mathbf{v}\| \tag{1.1.37.1}$$

1.1.38 Specific Energy for a satellite with position vector $\mathbf{r}$, velocity vector $\mathbf{v}$ and gravitational parameter μ is

$$\varepsilon = \frac{v^2}{2} - \frac{\mu}{r} \tag{1.1.38.1}$$

where

$$r = \|\mathbf{r}\|, v = \|\mathbf{v}\| \tag{1.1.38.2}$$

1.1.39 The gravitational acceleration $\mathbf{a}$ acting on a satellite is given by Newton's law of gravitation:

$$\mathbf{a} = -\frac{\mu}{r^3}\mathbf{r} \tag{1.1.39.1}$$

1.1.40 The trajectory of a satellite under a central gravitational force is always a conic section.

Solution: Taking the cross product of $\mathbf{r}$ with $\mathbf{a}$:

$$\mathbf{r}\times\mathbf{a} = \mathbf{r}\times\left(-\frac{\mu}{r^3}\mathbf{r}\right) = \mathbf{0} \tag{1.1.40.1}$$

From (1.1.40.1)

$$\frac{d}{dt}\left(\mathbf{r}\times\mathbf{v}\right)=\mathbf{v}\times\mathbf{v}+\mathbf{r}\times\mathbf{a}=\mathbf{0} \tag{1.1.40.2}$$

Hence, the specific angular momentum vector $\mathbf{h}$ is conserved:

$$\mathbf{h}=\mathbf{r}\times\mathbf{v}=\text{constant} \tag{1.1.40.3}$$

Crossing the acceleration $\mathbf{a}$ with $\mathbf{h}$:

$$\mathbf{a}\times\mathbf{h}=\left(-\frac{\mu}{r^3}\mathbf{r}\right)\times\left(\mathbf{r}\times\mathbf{v}\right) \tag{1.1.40.4}$$

$$=-\frac{\mu}{r^3}\left[\left(\mathbf{r}\cdot\mathbf{v}\right)\mathbf{r}-\left(\mathbf{r}\cdot\mathbf{r}\right)\mathbf{v}\right] \tag{1.1.40.5}$$

$$=\frac{\mu}{r^3}\left[r^2\mathbf{v}-\left(\mathbf{r}\cdot\mathbf{v}\right)\mathbf{r}\right] \tag{1.1.40.6}$$

Using $\mathbf{r}\cdot\mathbf{v}=r\frac{dr}{dt}$, this simplifies to:

$$\mathbf{a}\times\mathbf{h}=\mu\left[\frac{\mathbf{v}}{r}-\frac{1}{r^2}\frac{dr}{dt}\mathbf{r}\right]=\mu\frac{d}{dt}\left(\frac{\mathbf{r}}{r}\right) \tag{1.1.40.7}$$

Integrating with respect to time t:

$$\mathbf{v}\times\mathbf{h}=\mu\left(\frac{\mathbf{r}}{r}+\mathbf{C}\right) \tag{1.1.40.8}$$

where $\mathbf{C}$ is the integration constant. Taking the scalar product of (1.1.40.8) with $\mathbf{r}$:

$$\mathbf{r}\cdot\left(\mathbf{v}\times\mathbf{h}\right)=\mu\mathbf{r}\cdot\left(\frac{\mathbf{r}}{r}+\mathbf{C}\right) \tag{1.1.40.9}$$

$$\implies\left(\mathbf{r}\times\mathbf{v}\right)\cdot\mathbf{h}=\mu\left(r+rC\cos\theta\right) \tag{1.1.40.10}$$

$$\implies\left\|\mathbf{h}\right\|^2=\mu r\left(1+C\cos\theta\right) \tag{1.1.40.11}$$

where θ is the angle between $\mathbf{r}$ and $\mathbf{C}$. Rearranging for r yields

$$r=\frac{\frac{\left\|\mathbf{h}\right\|^2}{\mu}}{1+C\cos\theta}=\frac{ep}{1+e\cos\theta} \tag{1.1.40.12}$$

This is the same equation as (1.1.35.1) where

$$ep=\frac{\left\|\mathbf{h}\right\|^2}{\mu} \tag{1.1.40.13}$$

$$\mathbf{e}=\mathbf{C} \tag{1.1.40.14}$$

1.1.41 The squared eccentricity e^2 of a satellite's trajectory is related to its specific orbital energy ε and specific angular momentum magnitude h by

$$e^2=1+\frac{2\varepsilon h^2}{\mu^2} \tag{1.1.41.1}$$

Solution: From (1.1.40.8) and (1.1.40.14),

$$\mathbf{e} = \frac{\mathbf{v} \times \mathbf{h}}{\mu} - \frac{\mathbf{r}}{r} \tag{1.1.41.2}$$

Taking the magnitude squared of both sides using $\|\mathbf{e}\|^2 = \mathbf{e} \cdot \mathbf{e}$:

$$e^2 = \|\mathbf{e}\|^2 = \left(\frac{\mathbf{v} \times \mathbf{h}}{\mu} - \frac{\mathbf{r}}{r}\right) \cdot \left(\frac{\mathbf{v} \times \mathbf{h}}{\mu} - \frac{\mathbf{r}}{r}\right) \tag{1.1.41.3}$$

Expanding the inner product:

$$e^2 = \frac{\|\mathbf{v} \times \mathbf{h}\|^2}{\mu^2} - \frac{2}{\mu r}\left[\mathbf{r} \cdot (\mathbf{v} \times \mathbf{h})\right] + \frac{\mathbf{r} \cdot \mathbf{r}}{r^2} \tag{1.1.41.4}$$

We know that

$$\mathbf{r} \cdot (\mathbf{v} \times \mathbf{h}) = (\mathbf{r} \times \mathbf{v}) \cdot \mathbf{h} = \mathbf{h} \cdot \mathbf{h} = h^2 \tag{1.1.41.5}$$

And,

$$\mathbf{r} \cdot \mathbf{r} = r^2 \tag{1.1.41.6}$$

Substituting these back into (1.1.41.4) yields

$$e^2 = \frac{v^2 h^2}{\mu^2} - \frac{2h^2}{\mu r} + 1 \tag{1.1.41.7}$$

$$= 1 + \frac{2h^2}{\mu^2}\left(\frac{v^2}{2} - \frac{\mu}{r}\right) \tag{1.1.41.8}$$

Substituting (1.1.38.1) into (1.1.41.8) yields:

$$e^2 = 1 + \frac{2\varepsilon h^2}{\mu^2} \tag{1.1.41.9}$$

1.1.42 Consider the system A system comprising a bar, spring and mass is shown in the figure Fig. 1.1.42.1 The bar, having negligible mass, is made of a material having Young's modulus E, cross-sectional area A and length L. The spring stiffness is k and the mass is M kg. Find the axial stiffness of the bar.




Fig. 1.1.42.1. Spring mass system

Solution: The axial stiffness of the bar is

$$k_b = \frac{AE}{L} \tag{1.1.42.1}$$

1.1.43 Find the overall spring constant in Fig. 1.1.42.1.

Solution: Using Hooke's law, by balancing the displacements,

$$\frac{Mg}{k_t} = \frac{Mg}{k_b} + \frac{Mg}{k} \tag{1.1.43.1}$$

$$\implies k_{eq} = \frac{k_b k}{k_b + k} \tag{1.1.43.2}$$

where k_t is the overall spring constant.

1.1.44 Show that the equation for motion for the mass in Fig. 1.1.44.1 is

$$\frac{d^2x}{dt^2} = -\frac{k}{M}x \tag{1.1.44.1}$$




Fig. 1.1.44.1. Spring Mass system in vertical plane

Solution: When the mass M is at rest, let the system stretch by δ_{st}.Then,

$$Mg - k\delta_{st} = 0 \implies Mg = k\delta_{st} \tag{1.1.44.2}$$

When the mass is displaced downward by $x(t)$, using Hooke's law,

$$M\frac{d^2x}{dt^2} = Mg - k(\delta_{\text{st}} + x) \tag{1.1.44.3}$$

$$\tag{1.1.44.4}$$

yielding (1.1.44.1), upon substituting from (1.1.44.2).

2. BT 2025

A. Formulae

2.1.1 Exponential Series

$$e^x = \sum_{n=0}^{\infty} \frac{x^n}{n!} = 1 + \frac{x}{1!} + \frac{x^2}{2!} + \frac{x^3}{3!} + \cdots \tag{2.1.1.1}$$

2.1.2 The normal form of the equation of a line is

$$\mathbf{n}^\top \mathbf{x} = c \tag{2.1.2.1}$$

2.1.3 The parametric form of the equation of a line is

$$\mathbf{x} = \mathbf{h} + \kappa \mathbf{m} \tag{2.1.3.1}$$

where

$$\mathbf{m}^\top \mathbf{n} = 0 \tag{2.1.3.2}$$

2.1.4 A circle with center $\mathbf{c}$ and radius r, can be expressed as (1.1.34.1) with

$$\mathbf{V} = \mathbf{I} = \begin{pmatrix} 1 & 0 \\ 0 & 1 \end{pmatrix}, \quad \mathbf{u} = -\mathbf{c}, \quad f = \|\mathbf{c}\|^2 - r^2 \tag{2.1.4.1}$$

Solution: The equation of a circle is

$$\|\mathbf{x} - \mathbf{c}\|^2 = r^2 \tag{2.1.4.2}$$

$$(\mathbf{x} - \mathbf{c})^\top (\mathbf{x} - \mathbf{c}) = r^2 \tag{2.1.4.3}$$

$$\mathbf{x}^\top \mathbf{x} - 2\mathbf{c}^\top \mathbf{x} + \mathbf{c}^\top \mathbf{c} - r^2 = 0 \tag{2.1.4.4}$$

yielding (2.1.4.1) upon comparing with (1.1.34.1)

2.1.5 (Line-Conic Intersection) The points of intersection of a line $L : \mathbf{x} = \mathbf{h} + \kappa \mathbf{m}$ ($\kappa \in \mathbb{R}$) with a conic section $\mathbf{x}^\top \mathbf{V} \mathbf{x} + 2\mathbf{u}^\top \mathbf{x} + f = 0$ are given by

$$\mathbf{X} = \begin{pmatrix} \mathbf{h} & \mathbf{m} \end{pmatrix} \begin{pmatrix} 1 & 1 \\ \kappa_1 & \kappa_2 \end{pmatrix} \tag{2.1.5.1}$$

where

$$\kappa_i = \frac{-\mathbf{m}^\top (\mathbf{V}\mathbf{h}+\mathbf{u}) \pm \sqrt{\left[\mathbf{m}^\top (\mathbf{V}\mathbf{h}+\mathbf{u})\right]^2 - g(\mathbf{h})\left(\mathbf{m}^\top \mathbf{V}\mathbf{m}\right)}}{\mathbf{m}^\top \mathbf{V}\mathbf{m}}, i = 1, 2. \tag{2.1.5.2}$$

with $g(\mathbf{h}) = \mathbf{h}^\top \mathbf{V}\mathbf{h} + 2\mathbf{u}^\top \mathbf{h} + f$.

2.1.6 (Intersection of Conics and Common Chord) The intersection of two conics with parameters $(\mathbf{V}_1, \mathbf{u}_1, f_1)$ and $(\mathbf{V}_2, \mathbf{u}_2, f_2)$ is given by the pencil

$$\mathbf{x}^\top (\mathbf{V}_1 + \mu\mathbf{V}_2)\,\mathbf{x} + 2\left(\mathbf{u}_1 + \mu\mathbf{u}_2\right)^\top \mathbf{x} + (f_1 + \mu f_2) = 0 \tag{2.1.6.1}$$

The value of μ corresponding to the degenerate conic (the radical axis / common chord line) is found from

$$\begin{vmatrix} \mathbf{V}_1 + \mu\mathbf{V}_2 & \mathbf{u}_1 + \mu\mathbf{u}_2 \\ (\mathbf{u}_1 + \mu\mathbf{u}_2)^\top & f_1 + \mu f_2 \end{vmatrix} = 0 \tag{2.1.6.2}$$

2.1.7 For a differentiable function $f(x)$,

$$f''(x) > 0 \quad \forall x \in (0, \infty) \implies f(x) \text{ is strictly convex} \tag{2.1.7.1}$$

2.1.8 (Gradient Descent Optimization) For the convex optimization problem

$$\min_x f(x), \tag{2.1.8.1}$$

$$x_{k+1} = x_k - \eta f'(x_k) \tag{2.1.8.2}$$

is the iterative parameter update with learning rate $\eta > 0$.

2.1.9 (Newton-Raphson Method) For a real-valued differentiable function $f(x)$, the root is iteratively approximated using its first-order Taylor series expansion about the current estimate x_n

$$x_{n+1} = x_n - \frac{f(x_n)}{f'(x_n)} \tag{2.1.9.1}$$

2.1.10 (System of Linear Equations) The matrix equation

$$\mathbf{A}\mathbf{x} = \mathbf{b} \tag{2.1.10.1}$$

is consistent iff

$$\text{rank}(\mathbf{A}) = \text{rank}(\,[\mathbf{A} \mid \mathbf{b}]) = r \tag{2.1.10.2}$$

2.1.11 Sum of Independent Discrete Random Variables (Two Dice Roll)

- Let $X_1, X_2 \in \{1, 2, 3, 4, 5, 6\}$ be independent discrete uniform random variables representing the outcomes of two fair dice, each having probability mass function (PMF)

$$p_{X_1}(n) = p_{X_2}(n) = \begin{cases} \frac{1}{6}, & 1 \le n \le 6 \\ 0, & \text{otherwise} \end{cases} \tag{2.1.11.1}$$

- (Convolution) Let $X = X_1 + X_2$ denote their sum. The PMF of X is given by

the discrete convolution of $p_{X_1}(n)$ and $p_{X_2}(n)$:

$$p_X(n) = \Pr(X_1 + X_2 = n) = \sum_k \Pr(X_1 = n-k \mid X_2 = k)\, p_{X_2}(k) \tag{2.1.11.2}$$

$$= \sum_k p_{X_1}(n-k)\, p_{X_2}(k) = p_{X_1}(n) * p_{X_2}(n) \tag{2.1.11.3}$$

- Substituting (2.1.11.1) into (2.1.11.3) yields the triangular PMF

$$p_X(n) = \begin{cases} 0, & n < 2 \\ \frac{n-1}{36}, & 2 \le n \le 7 \\ \frac{13-n}{36}, & 7 < n \le 12 \\ 0, & n > 12 \end{cases} \tag{2.1.11.4}$$

The following code verifies (2.1.11.4) in Fig. 2.1.11.1.

codes/btq35/dice.py




Fig. 2.1.11.1. PMF of the sum of two fair dice: Simulation vs Analysis

2.1.12 (Unit Step Response of an RC Circuit) Consider a series RC circuit excited by a step input $v_i(t) = V_0 u(t)$ where V_0 is a constant. Applying KVL around the loop,

$$RC\frac{dv_o}{dt} + v_o(t) = V_0 u(t) \tag{2.1.12.1}$$

yielding

$$\frac{V_0}{s} = sCRV_o(s) + V_o(s) \tag{2.1.12.2}$$

$$\implies V_o(s) = \frac{V_0}{s(RCs+1)} \tag{2.1.12.3}$$

$$= V_0\left[\frac{1}{s} - \frac{1}{s+\frac{1}{RC}}\right] \tag{2.1.12.4}$$

$$\implies v_o(t) = V_0\left(1 - e^{-\frac{t}{RC}}\right)u(t) \tag{2.1.12.5}$$

2.1.13 (Continuity) A real-valued function $f(x)$ is continuous at $x = x_0$ iff

$$\lim_{x\to x_0^-} f(x) = \lim_{x\to x_0^+} f(x) = f(x_0) \tag{2.1.13.1}$$

2.1.14 (Differentiability) A function $f(x)$ is differentiable at $x = x_0$ if

$$f'\left(x_0^-\right) = \lim_{h\to 0^-} \frac{f(x_0+h) - f(x_0)}{h} = \lim_{h\to 0^+} \frac{f(x_0+h) - f(x_0)}{h} = f'\left(x_0^+\right) \tag{2.1.14.1}$$

2.1.15 If $f(x)$ is differentiable at $x = x_0$, it must necessarily be continuous at $x = x_0$

$$\lim_{x\to x_0}\left[f(x) - f(x_0)\right] = \lim_{x\to x_0}\left[\frac{f(x) - f(x_0)}{x - x_0}(x - x_0)\right] = f'(x_0)\cdot 0 = 0 \tag{2.1.15.1}$$

2.1.16 Piecewise Boundary Conditions at $x = a$

- Consider a function $f(x)$ defined by differentiable branches $f_1(x)$ and $f_2(x)$ across a boundary point $x = a$:

$$f(x) = \begin{cases} f_1(x), & x \le a \\ f_2(x), & x > a \end{cases} \tag{2.1.16.1}$$

For $f(x)$ to be continuous at $x = a$, the one-sided limits must equal the boundary value:

$$\lim_{x\to a^-} f_1(x) = \lim_{x\to a^+} f_2(x) \implies f_1(a) = f_2(a) \tag{2.1.16.2}$$

For $f(x)$ to be differentiable at $x = a$, the one-sided derivatives at the boundary must coincide:

$$f_1'(a) = f_2'(a) \tag{2.1.16.3}$$

2.1.17 The Z-Transform

$$X(z) = \sum_{n=-\infty}^{\infty} x[n]\, z^{-n} \tag{2.1.17.1}$$

over the Region of Convergence (ROC) where the series converges absolutely.

2.1.18 The discrete unit step function is defined as

$$u\left(n\right)=\begin{cases}1, & n\geq 0\\ 0, & n<0\end{cases} \tag{2.1.18.1}$$

and

$$u\left[n\right]\overset{\mathcal{Z}}{\longleftrightarrow}\sum_{n=0}^{\infty}z^{-n}=\frac{1}{1-z^{-1}},\quad |z|>1 \tag{2.1.18.2}$$

2.1.19 Time-Shift Property

$$x\left(n-k\right)\overset{\mathcal{Z}}{\longleftrightarrow}z^{-k}X\left(z\right) \tag{2.1.19.1}$$

2.1.20 Standard Inverse Transform Pair: For any scalar constant α,

$$\alpha^{n}u\left(n\right)\overset{\mathcal{Z}}{\longleftrightarrow}\frac{1}{1-\alpha z^{-1}},\quad |z|>|\alpha| \tag{2.1.20.1}$$

3. AG 2025

A. Formulae

3.1.1 (Mean) The mean of a random variable X with probability mass function $p_X(k)$ is defined as

$$E\left[X\right]=\sum_{k}x_k p_X\left(k\right) \tag{3.1.1.1}$$

3.1.2 (Bernoulli Distribution) For $X\in\{0,1\}$, the pmf is defined as

$$P_X(k)=\begin{cases}p & k=1\\ q & k=0\\ 0 & \text{otherwise}\end{cases} \tag{3.1.2.1}$$

3.1.3 The moment generating function

$$\begin{aligned}M_X(z)\triangleq E\left[z^{-X}\right]&=\sum_{n=-\infty}^{\infty}p_X\left[n\right]z^{-n}\\ &=p_X(1)z^{-1}+p_X(0)z^{0}\\ &=pz^{-1}+q\end{aligned} \tag{3.1.3.1}$$

upon substituting from (2.1.17.1).

3.1.4 (Binomial Distribution) If X_i are independent, for

$$\begin{aligned}Y\triangleq\sum_{i=1}^{n}X_i,\quad M_Y(z)&=\prod_{i=1}^{n}M_{X_i}(z)\\ &=\left(pz^{-1}+q\right)^{n}\end{aligned} \tag{3.1.4.1}$$

Solution: From (3.1.3.1),

$$M_Y(z) = E\left[z^{-\sum_{i=1}^{n} X_i}\right] = E\left[\prod_{i=1}^{n} z^{-X_i}\right] \tag{3.1.4.2}$$

$$= \prod_{i=1}^{n} E\left[z^{-X_i}\right] \tag{3.1.4.3}$$

yielding (3.1.4.1).

3.1.5 From (3.1.4.1),

$$\left(pz^{-1}+q\right)^n = {}^nC_k p^k q^{n-k} z^{-k} \tag{3.1.5.1}$$

$$\implies p_Y(k) = \begin{cases} {}^nC_k p^k q^{n-k} & 0 \le k \le n \\ 0 & \text{otherwise} \end{cases} \tag{3.1.5.2}$$

using the definition in (3.1.3.1) along with (2.1.17.1).

3.1.6

$$\begin{aligned} \sinh(at)\,u(t) &\overset{\mathcal{L}}{\longleftrightarrow} \frac{a}{s^2-a^2} \\ \cosh(at)\,u(t) &\overset{\mathcal{L}}{\longleftrightarrow} \frac{s}{s^2-a^2} \end{aligned} \tag{3.1.6.1}$$

Solution: From (1.1.13.1),

$$\cos(\jmath at)u(t) \overset{\mathcal{L}}{\longleftrightarrow} \frac{s}{s^2+(\jmath a)^2} \tag{3.1.6.2}$$

yielding (3.1.6.1).

3.1.7 (Geometric Progression)

$$\sum_{i=0}^{n-1} q^i = \frac{q^n-1}{q-1} \tag{3.1.7.1}$$

3.1.8

$$\begin{aligned} \sin(x) &= \sum_{i=1}^{n} -1^{i+1}\frac{x^{2i-1}}{(2i-1)!} \\ \cos(x) &= \sum_{i=1}^{n} -1^{i+1}\frac{x^{i-1}}{i-1!} \end{aligned} \tag{3.1.8.1}$$

3.1.9 If

$$f(\alpha x, \alpha y) = \alpha^n \alpha^n f(x,y), \tag{3.1.9.1}$$

$f(x,y)$ is homogeneous of degree n. Then,

$$x\frac{\partial f}{\partial x} + y\frac{\partial f}{\partial y} = nf \tag{3.1.9.2}$$

4. GATE CE-2 2025

A. Formulae

4.1.1 (Integration by Parts) For differentiable functions $u(x)$ and $v(x)$, the integration by parts formula is:

$$\int u\,dv = uv - \int v\,du \tag{4.1.1.1}$$

4.1.2 Let

$$\mathbf{V} = \begin{pmatrix} u \\ v \end{pmatrix}, \nabla = \begin{pmatrix} \frac{\partial}{\partial x} \\ \frac{\partial}{\partial y} \end{pmatrix}, \tag{4.1.2.1}$$

$$\tag{4.1.2.2}$$

The curl and divergence of $\mathbf{V}$ are then defined respectively as

$$\nabla \times \mathbf{V} = \left(\frac{\partial v}{\partial x} - \frac{\partial u}{\partial y} \right) \mathbf{e}_3 \tag{4.1.2.3}$$

$$\nabla \cdot \mathbf{V} = \frac{\partial u}{\partial x} + \frac{\partial v}{\partial y}. \tag{4.1.2.4}$$

4.1.3 If $B \subset A, AB = 1$.

4.1.4 (Conditional Probability)

$$\Pr(A \mid B) = \frac{\Pr(A \cap B)}{\Pr(B)}, \quad \Pr(B) > 0. \tag{4.1.4.1}$$

4.1.5 (Variance)

$$\sigma^2 = E\left[X^2\right] - (E[X])^2 \tag{4.1.5.1}$$

5. GATE-BM-2025

A. Formulae

5.1.1 (Rolle's Theorem) If f is continuous on $[a, b]$, differentiable on (a, b), and $f(a) = f(b)$, then

$$\exists\, c \in (a, b) \text{ such that } f'(c) = 0. \tag{5.1.1.1}$$

5.1.2 (Closed-Loop Transfer Function) For unity negative feedback with forward transfer function $G(s)$, in Fig. 5.1.2.1, the transfer function is given by

$$\frac{Y(s)}{X(s)} = \frac{G(s)}{1 + G(s)}. \tag{5.1.2.1}$$




Fig. 5.1.2.1. Unity feedback

5.1.3 (Nyquist Sampling Theorem) A time domain signal is given by

$$x(t) = 20\sin(100\pi t) + 36\sin(150\pi t) - 2\sin(300\pi t), \tag{5.1.3.1}$$

where time t is in seconds. Among the following options, what is the frequency (in Hz) at which $x(t)$ should be sampled for accurate signal reconstruction? (BM 2025)

a) 500 b) 150 c) 200 d) 250

Solution: The frequencies of the three sinusoidal components are

$$f_1 = \frac{100\pi}{2\pi} = 50 \text{ Hz} f_2 \quad = \frac{150\pi}{2\pi} = 75 \text{ Hz} f_3 = \frac{300\pi}{2\pi} = 150 \text{ Hz} \tag{5.1.3.2}$$

According to the Nyquist theorem, the sampling rate is

$$f_s \geq 2 \times f_3 = 300 \text{ Hz}. \tag{5.1.3.3}$$

Among the given options, the only frequency greater than or equal to 300 Hz that guarantees accurate signal reconstruction is 500 Hz. The following code generates Fig. 5.1.3.1.

Codes/bm10.py




Fig. 5.1.3.1. Plot of x(t) vs time

5.1.4 Average Power in an AC Circuit

$$P_{\text{avg}} = V_{\text{rms}} I_{\text{rms}} \cos\theta, \tag{5.1.4.1}$$

where

$$V_{\text{rms}} = \frac{V_m}{\sqrt{2}} \tag{5.1.4.2}$$

$$I_{\text{rms}} = \frac{I_m}{\sqrt{2}} \tag{5.1.4.3}$$

$$\theta = \phi_v - \phi_i. \tag{5.1.4.4}$$

5.1.5

$$E\left(X^n\right) = \frac{d}{dt^n}\left[M_X\left(e^{-t}\right)\right]_{t=0} \tag{5.1.5.1}$$

Solution: From (3.1.3.1),

$$\frac{d}{dt^n}\left\{M_X\left(e^{-t}\right)\right\} = \sum_{k=-\infty}^{\infty} k^n p_X\left(k\right) e^{kt} \tag{5.1.5.2}$$

yielding (5.1.5.1).

5.1.6 For the Binomail distribution $X \sim \mathcal{B}\left(n, p\right)$,

$$\mu = np, \sigma^2 = npq \tag{5.1.6.1}$$

Solution: From (5.1.5.1),

$$E\left(X\right)=\frac{d}{dt}\left\{\left(q+pe^{t}\right)^{n}\right\}_{t=0} \tag{5.1.6.2}$$

$$=\lim_{t=0}np\left(q+pe^{t}\right)^{n-1}=np \tag{5.1.6.3}$$

and

$$M_{X}^{\prime}\left(t\right)=n\left(q+pe^{t}\right)^{n-1}pe^{t} \tag{5.1.6.4}$$

$$M_{X}^{\prime\prime}\left(t\right)=n\left(n-1\right)\left(1-p+pe^{t}\right)^{n-2}\left(pe^{t}\right)^{2} \tag{5.1.6.5}$$

$$+n\left(1-p+pe^{t}\right)^{n-1}\left(pe^{t}\right) \tag{5.1.6.6}$$

Therefore

$$E\left(X^{2}\right)=n\left(n-1\right)p^{2}+np \tag{5.1.6.7}$$

$$\implies \text{var}\left(X\right)=E\left(X^{2}\right)-E\left(X\right)^{2}=npq \tag{5.1.6.8}$$

5.1.7 Mean and Variance of a Binomial Distribution For $X\sim B(N,p)$,

$$E(X)=Np \tag{5.1.7.1}$$

$$\text{Var}(X)=Np(1-p). \tag{5.1.7.2}$$

5.1.8 In the circuit shown in Fig. 5.1.8.1 below, $V_{\text{in}}=10\cos(1000t)$ volts. The magnitude of the input impedance of the circuit is _____ kΩ. (BM 2025)




Fig. 5.1.8.1. Steady state analysis.

a) 5.0 b) 3.5 c) 6.0 d) 4.5

Solution: The input impedance can be expressed as

$$R_1 + R_2 \parallel \frac{1}{\jmath\omega C} = R_1 + \frac{R_2\left(\frac{1}{\jmath\omega C}\right)}{R_2 + \frac{1}{\jmath\omega C}} \tag{5.1.8.1}$$

$$\tag{5.1.8.2}$$

$$= R_1 + \frac{R_2}{\jmath\omega C R_2 + 1}. = 3.5 - j0.5 \tag{5.1.8.3}$$

upon substituting the following values in (5.1.8.3) and simplifying.

$$R_1 = 3k\Omega, \quad R_2 = 1\text{k}\Omega, \quad C = 1\,\mu\text{F}, \quad \omega = 1000 \text{ rad/s}. \tag{5.1.8.4}$$

The following code plots Fig. 5.1.8.2.

Codes/bm14.py




Fig. 5.1.8.2. Magnitude and Phase.

5.1.9 Two systems U and V are defined as shown below in Fig. 5.1.9.1. Which of the following statement(s) is/are CORRECT? (BM 2025)




Fig. 5.1.9.1. Linearity and Causality

a) System U is nonlinear; System V is linear
b) System U is causal; System V is noncausal
c) System U is noncausal; System V is causal
d) System U is nonlinear; System V is nonlinear

Solution:

a) System U
   i) Linearity check

$$T\{ax(t)\} = [ax(t)]^2 + 1 \tag{5.1.9.1}$$
$$= a^2 x(t)^2 + 1 \tag{5.1.9.2}$$
$$\neq a[x(t)^2 + 1] \tag{5.1.9.3}$$

   Hence U is nonlinear.
   ii) Causality check: $y(t)$ depends only on $x(t)$ at time t. Hence U is causal.

b) System V
   i) Linearity check

$$T\{ax_1(t) + bx_2(t)\} = ax_1(t+1) + bx_2(t+1) \tag{5.1.9.4}$$
$$= ay_1(t) + by_2(t) \tag{5.1.9.5}$$

   System V is linear.
   ii) Causality check:

$$y(0) = x(1) \tag{5.1.9.6}$$

   Since $y(0)$ depends on the future input $x(1)$, V is noncausal.

5.1.10 Linear (Discrete) Convolution

For an LTI system with impulse response $h(n)$ of length M and input $x(n)$ of length N,

$$y(n) = h(n) * x(n) \tag{5.1.10.1}$$
$$= \sum_k h(k)\, x(n-k), \tag{5.1.10.2}$$

with output length

$$L = M + N - 1. \tag{5.1.10.3}$$

This can be written as a matrix–vector product using a lower triangular Toeplitz matrix $\mathbf{H}$ built from shifted copies of $h(n)$:

$$\mathbf{y} = \mathbf{H}, \mathbf{x}. \tag{5.1.10.4}$$


5.1.11 n-bit DAC Output

For an n-bit DAC with full-scale output voltage V_{FS} and digital input equivalent decimal value D,

$$V_{\text{out}} = V_{\text{FS}} \left(\frac{D}{2^n - 1} \right). \tag{5.1.11.1}$$

5.1.12 Inverting Summing Amplifier

For an op-amp inverting summing amplifier with feedback resistor R_f, input resistors $R_1, R_2, R_3, \ldots$ and corresponding input voltages $V_1, V_2, V_3, \ldots$, the output voltage is



a) Derivation

Let the inverting input node (where R_1, R_2, R_3, R_f meet) be node A, and let the non-inverting input be grounded.

Ideal op-amp assumptions:

- No current flows into either input terminal.
- The open-loop gain is infinite, so the two inputs are forced to the same potential (virtual short).

Since the non-inverting input is at $0\,\text{V}$ (grounded), the virtual short forces node A to also be at $0\,\text{V}$:

$$V_A = 0 \qquad \text{(virtual ground)}. \tag{5.1.12.1}$$

Applying Kirchhoff's Current Law (KCL) at node A, the sum of currents flowing

into the node through R_1, R_2, R_3 must equal the current flowing out through the feedback resistor R_f (since no current enters the op-amp input):

$$\frac{V_1 - V_A}{R_1} + \frac{V_2 - V_A}{R_2} + \frac{V_3 - V_A}{R_3} = \frac{V_A - V_{\text{out}}}{R_f}. \tag{5.1.12.2}$$

Substituting $V_A = 0$:

$$\frac{V_1}{R_1} + \frac{V_2}{R_2} + \frac{V_3}{R_3} = \frac{-V_{\text{out}}}{R_f}. \tag{5.1.12.3}$$

Solving for V_{out}:

$$V_{\text{out}} = -R_f \left(\frac{V_1}{R_1} + \frac{V_2}{R_2} + \frac{V_3}{R_3} \right) \tag{5.1.12.4}$$

$$= -\left(\frac{R_f}{R_1} V_1 + \frac{R_f}{R_2} V_2 + \frac{R_f}{R_3} V_3 \right), \tag{5.1.12.5}$$

$$V_{\text{out}} = -\sum_i \frac{R_f}{R_i} V_i. \tag{5.1.12.6}$$

$$V_{\text{out}} = -\left(\frac{R_f}{R_1} V_1 + \frac{R_f}{R_2} V_2 + \frac{R_f}{R_3} V_3 + \cdots \right), \tag{5.1.12.7}$$

valid provided V_{out} stays within the saturation limits,

$$-V_{\text{sat}} \le V_{\text{out}} \le +V_{\text{sat}}. \tag{5.1.12.8}$$

5.1.13 Wien Bridge Oscillator Frequency

For a Wien bridge oscillator with equal frequency-selective resistors R and capacitors C, the oscillation frequency is

$$f_0 = \frac{1}{2\pi RC}. \tag{5.1.13.1}$$

5.1.14 Series RLC Circuit — Resonance

Kirchhoff's Voltage Law for a series RLC circuit driven by

$$v(t) = V_m \cos(\omega t) \tag{5.1.14.1}$$

$$R\, i(t) + L \frac{di(t)}{dt} + \frac{1}{C} \int i(t)\, dt = v(t). \tag{5.1.14.2}$$

In the phasor domain, the impedance is

$$Z(\omega) = R + j\left(\omega L - \frac{1}{\omega C}\right) \tag{5.1.14.3}$$

$$|Z(\omega)| = \sqrt{R^2 + \left(\omega L - \frac{1}{\omega C}\right)^2}. \tag{5.1.14.4}$$

Converting to complex phasor notation

$$V(t) = V_{\text{rms}}\sqrt{2}e^{j\omega t} \tag{5.1.14.5}$$

$$I(t) = I_{\text{rms}}\sqrt{2}e^{j(\omega t - \phi)} \tag{5.1.14.6}$$

$$Z(\omega) = \frac{V(\omega)}{I(\omega)} \tag{5.1.14.7}$$

$$= R + j\omega L + \frac{1}{j\omega C} \tag{5.1.14.8}$$

$$= R + j\left(\omega L - \frac{1}{\omega C}\right) \tag{5.1.14.9}$$

Resonance occurs when the reactive part vanishes:

$$\omega_0 L = \frac{1}{\omega_0 C} \tag{5.1.14.10}$$

$$\implies \omega_0 = \frac{1}{\sqrt{LC}} \tag{5.1.14.11}$$

$$f_0 = \frac{\omega_0}{2\pi}. \tag{5.1.14.12}$$

At resonance, $Z(\omega_0) = R$, so

$$I_{\text{rms}}(\omega_0) = \frac{V_{\text{rms}}}{R}. \tag{5.1.14.13}$$

5.1.15 Newton–Raphson Method

For a root of $f(x) = 0$, the iterative update starting from x_n is

$$x_{n+1} = x_n - \frac{f(x_n)}{f'(x_n)}. \tag{5.1.15.1}$$

5.1.16 Logarithmic Decay Model

For a quantity that decays logarithmically with time,

$$\sigma(t) = \sigma_0 - k\ln(t), \qquad t \geq 1, \tag{5.1.16.1}$$

the difference between two times t_1, t_2 eliminates the unknown constant σ_0:

$$\sigma(t_2) - \sigma(t_1) = -k\left[\ln(t_2) - \ln(t_1)\right] \tag{5.1.16.2}$$

$$= -k \ln\left(\frac{t_2}{t_1}\right). \tag{5.1.16.3}$$

l) Function $X \sim \mathcal{N}(\mu, \sigma^2)$, if

$$p_X(x) = \frac{1}{\sigma\sqrt{2\pi}} \exp\left(-\frac{(x-\mu)^2}{2\sigma^2}\right), \qquad -\infty < x < \infty. \tag{5.1.16.4}$$

The function is symmetric about $x = \mu$, and satisfies

$$\int_{-\infty}^{\infty} f(x)\, dx = 1, \qquad E[X] = \mu, \qquad \mathrm{Var}(X) = \sigma^2. \tag{5.1.16.5}$$

a) Binomial Approximation (De Moivre–Laplace Theorem) For a binomial random variable $X \sim \mathrm{Bin}(n, p)$ with large n such that $np \geq 5$ and $n(1-p) \geq 5$, the binomial distribution can be approximated by a Gaussian distribution with:

$$\mu = np, \quad \sigma^2 = np(1-p). \tag{5.1.16.6}$$

The probability mass function is approximated as:

$$\Pr(X = k) \approx \frac{1}{\sqrt{2\pi np(1-p)}} \exp\left(-\frac{(k-np)^2}{2np(1-p)}\right). \tag{5.1.16.7}$$

b) Continuity Correction When approximating a discrete binomial distribution using a continuous Gaussian distribution, a continuity correction factor of 0.5 is applied:

$$\Pr(a \leq X \leq b) \approx P\left(\frac{a - 0.5 - np}{\sqrt{np(1-p)}} \leq Z \leq \frac{b + 0.5 - np}{\sqrt{np(1-p)}}\right). \tag{5.1.16.8}$$

5.1.17 Central Limit Theorem (CLT)

Let $X_1, X_2, \ldots, X_n$ be independent and identically distributed (i.i.d.) random variables, each with finite mean μ and finite variance σ^2 (the underlying distribution need not itself be Gaussian). Define the sample mean

$$\bar{X}_n = \frac{1}{n}\sum_{i=1}^{n} X_i. \tag{5.1.17.1}$$

Then, as $n \to \infty$, the standardized sample mean converges in distribution to a standard normal random variable:

$$Z_n = \frac{\bar{X}_n - \mu}{\sigma/\sqrt{n}} \xrightarrow{d} \mathcal{N}(0,1). \tag{5.1.17.2}$$

Equivalently, for large n,

$$\bar{X}_n \;\approx\; \mathcal{N}\!\left(\mu,\; \frac{\sigma^2}{n}\right), \qquad \sum_{i=1}^{n} X_i \;\approx\; \mathcal{N}\big(n\mu,\; n\sigma^2\big)\,. \tag{5.1.17.3}$$


5.1.18 Effect of Scalar Multiplication on a Determinant
For an $n \times n$ matrix A and scalar k,

$$\det(kA) = k^n \det(A). \tag{5.1.18.1}$$

5.1.19 Notch (Band-Stop) Filter Response

$$|H(\jmath\omega)| = \begin{cases} 0 & \omega = \omega_0, \\ \neq 0 & \text{otherwise} \end{cases} \tag{5.1.19.1}$$

5.1.20 Which one of the following represents the frequency response of a notch filter? (BM 2025)



Solution: From (5.1.19.1), d).

B. Solved Questions

5.2.1 The 12 musical notes are given as $C, C^{\#}, D, D^{\#}, E, F, F^{\#}, G, G^{\#}, A, A^{\#}, B$. Frequency of each note is $\sqrt[12]{2}$ times the frequency of the previous note. If the frequency of the note C is 130.8 Hz, then the ratio of frequencies of notes $F^{\#}$ and C is (BM 2025)

a) $\sqrt[6]{2}$ b) $\sqrt{2}$ c) $\sqrt[4]{2}$ d) 2


Solution: Let the respective frequencies be $f_i, 0 \leq i \leq 12$. They can be repreprepresented as a G.P with common ratio $r = \sqrt[12]{2}$. The desired ratio is

$$\frac{f_6}{f_0} = r^6 = \sqrt{2} \tag{5.2.1.1}$$

The following code verifies the result.

codes/bm1.py


5.2.2 The following figures show three curves generated using an iterative algorithm. The total length of the curve generated after "Iteration n" is (BM 2025)



a) $\left(\frac{5}{3}\right)^{\frac{n}{2}}$ b) $\left(\frac{5}{3}\right)^{n}$ c) $\left(\frac{5}{3}\right)^{2n}$ d) $\left(\frac{5}{3}\right)^{n(2n-1)}$

Solution: The length is $L_n = \left(\frac{5}{3}\right)^n$

5.2.3 A stick of length one meter is broken at two locations at distances of b_1 and b_2 from the origin (0), as shown in the figure. Note that $0 < b_1 < b_2 < 1$. Which one of the following is NOT a necessary condition for forming a triangle using the three pieces? (BM 2025)



a) $b_1 < 0.5$ b) $b_2 > 0.5$ c) $b_2 < b_1 + 0.5$ d) $b_1 + b_2 < 1$

Solution: The following code gives whether the triangle is feasible or not by considering b_1, b_2.

Codes/bm3.py

5.2.4 For any continuous and differentiable function $f(x)$ with first derivative $f'(x) \neq 0$ for all values of x, which one of the following is ALWAYS TRUE for $a \neq b$? Here, a and b are finite and real. (BM 2025)

a) $f(a) > f(b)$ b) $f(a) = f(b)$ c) $f(a) \neq f(b)$ d) $f(a) < f(b)$

Solution: From (5.1.1.1),

$$f(a) \neq f(b). \tag{5.2.4.1}$$

5.2.5 The closed loop system shown below in Fig. 5.2.5.1 _____. (BM 2025)




Fig. 5.2.5.1. Unity feedback system

a) is overdamped
b) is underdamped
c) is critically damped
d) has sustained oscillations

Solution: From (5.1.2.1)
Substitute $G(s)$:

$$\frac{C(s)}{R(s)} = \frac{\frac{25}{s(s+5)}}{1 + \frac{25}{s(s+5)}} \tag{5.2.5.1}$$

$$= \frac{25}{s^2 + 5s + 25} \tag{5.2.5.2}$$

To find the impulse response in the time domain,

$$C(s) = \frac{25}{s^2 + 5s + 25} \tag{5.2.5.3}$$

$$C(s) = \frac{10}{\sqrt{3}} \cdot \frac{\frac{5\sqrt{3}}{2}}{\left(s + \frac{5}{2}\right)^2 + \left(\frac{5\sqrt{3}}{2}\right)^2} \tag{5.2.5.4}$$

From (1.1.8.1) and (1.1.13.1),

$$c(t) = \frac{10}{\sqrt{3}} e^{-\frac{5}{2}t} \sin\left(\frac{5\sqrt{3}}{2}t\right) u(t) \tag{5.2.5.5}$$

The following code generates (5.2.5.2). It is obvious that the system is underdamped.

Codes/bm6.py




Fig. 5.2.5.2. Underdamped system.

5.2.6 The eigenvalues of the matrix

$$\begin{pmatrix} \cos\theta & -\sin\theta \\ \sin\theta & \cos\theta \end{pmatrix} \tag{5.2.6.1}$$

are _____. (BM 2025)

a) $\cos\theta$ and $\sin\theta$
b) $e^{i\theta}$ and $e^{-i\theta}$, where $i = \sqrt{-1}$
c) $\cos\theta$ and $-\sin\theta$
d) $\cos 2\theta$ and $\sin 2\theta$

Solution: From (1.1.31.1), the characteristic equation is

$$\begin{vmatrix} \lambda - \cos\theta & \sin\theta \\ -\sin\theta & \lambda - \cos\theta \end{vmatrix} = 0 \tag{5.2.6.2}$$

$$\implies (\cos\theta - \lambda)^2 + \sin^2\theta = 0. \tag{5.2.6.3}$$

$$\text{or, } \lambda = e^{\pm \jmath\theta} \tag{5.2.6.4}$$

The following code verifies the solution.

Codes/bm7.py

5.2.7 If $f(x) = x - \frac{1}{x}$, the value of $\lim_{\Delta x \to 0} \frac{f(1+\Delta x) - f(1)}{\Delta x}$ is _____. (BM 2025)

(a) 0
(b) $\frac{1}{2}$
(c) 1
(d) 2

Solution:

$$f'(x) = 1 + \frac{1}{x^2} \tag{5.2.7.1}$$

$$\implies f'(1) = 2. \tag{5.2.7.2}$$

using (1.1.15.2). The following code generates Fig. 5.2.7.1 to verify the result.

Codes/bm8.py




Fig. 5.2.7.1. Derivative vs x; function vs x with tangent

5.2.8 The elements of the dataset $\{-5, 1, a, 5, b\}$ are in ascending order. If both mean and median of the dataset are equal to 3, what is the value of b? (BM 2025)

a) 7 b) 11 c) 9 d) 12

Solution: By definition, the median

$$a = 3 \tag{5.2.8.1}$$

and the mean is

$$\frac{-5 + 1 + a + 5 + b}{5} = 3 \tag{5.2.8.2}$$

$$\implies b = 11 \tag{5.2.8.3}$$

upon substituting $a = 3$. The following code verifies the solution.

Codes/bm9.py

5.2.9 A voltage source $V_s = 5\sin\left(100t + \frac{\pi}{2}\right)$ volts is driving a current $I = 10\sin\left(100t + \frac{\pi}{6}\right)$ mA through a circuit. The average power dissipated in the circuit is _____ mW. (BM 2025)

a) 0.0 b) 12.5 c) 25.0 d) 50.0

Solution: Given data from the problem:

$$V_s(t) = 5\sin\left(100t + \frac{\pi}{2}\right) \text{ V} \tag{5.2.9.1}$$

$$I(t) = 10\sin\left(100t + \frac{\pi}{6}\right) \text{ mA} \tag{5.2.9.2}$$

Extracting the peak values and phase angles:

$$V_0 = 5 \text{ V} \tag{5.2.9.3}$$

$$I_0 = 10 \text{ mA} \tag{5.2.9.4}$$

$$\phi_v = \frac{\pi}{2} \text{ rad} \tag{5.2.9.5}$$

$$\phi_i = \frac{\pi}{6} \text{ rad} \tag{5.2.9.6}$$

Calculate the phase difference θ:

$$\theta = \phi_v - \phi_i \tag{5.2.9.7}$$

$$= \frac{\pi}{2} - \frac{\pi}{6} \tag{5.2.9.8}$$

$$= \frac{\pi}{3} \text{ rad} \tag{5.2.9.9}$$

From (5.1.4.1)

Substituting these values into the average power formula:

$$P_{\text{avg}} = \frac{1}{2} \times 5 \times 10 \times \cos\left(\frac{\pi}{3}\right) \text{ mW} \tag{5.2.9.10}$$

$$P_{\text{avg}} = 12.5 \text{ mW} \tag{5.2.9.11}$$




Fig. 5.2.9.1. Power vs time

The following code results the graph

Codes/bm11.py

5.2.10 N independent trials of a binomial random variable yield an expectation value of 16 and variance of 12. What is the value of N? (BM 2025)

a) 80 b) 60 c) 45 d) 64

Solution: From (5.1.6.3) and (5.1.6.8),

$$Np = 16, Np(1-p) = 12 \tag{5.2.10.1}$$

$$\implies p = \frac{1}{4}, N = 64 \tag{5.2.10.2}$$

The following code generates Fig. 5.2.10.1 by substituting the above mean and variance in (5.1.16.4), and (3.1.5.2). It can be seen that the Gaussian pdf acts as an envelope for the Binomaial pmf. This is an example of the Central Limit Theorem.

Codes/bm12.py




Fig. 5.2.10.1. Binomial and Gaussian converge for larege N.

5.2.11 Given a function $y(x)$ satisfying the differential equation

$$.y'' - 0.25y = 0, \tag{5.2.11.1}$$

with initial conditions $y(0) = 1$; $y'(0) = 1$, what is the value of $y(\log_e 100)$? Here, y' and y'' are the first and second derivatives of y, respectively. (BM 2025)

a) 14.05 b) 14.25 c) 14.95 d) 14.65

Solution: Taking the Laplace Transform of (5.2.11.1), from (1.1.7.1),

$$\left[s^2Y(s) - sy(0) - y'(0)\right] - 0.25Y(s) = 0 \tag{5.2.11.2}$$

$$\implies s^2Y(s) - s - 1 - 0.25Y(s) = 0 \tag{5.2.11.3}$$

upon substituting initial conditions, yielding

$$Y(s) = \frac{s+1}{s^2 - 0.25} \tag{5.2.11.4}$$

$$= \frac{1.5}{s - 0.5} - \frac{0.5}{s + 0.5} \tag{5.2.11.5}$$

$$\text{or, } y(x) = 1.5e^{0.5x} - 0.5e^{-0.5x}. \tag{5.2.11.6}$$

$$\therefore y(\ln 100) = 14.95 \tag{5.2.11.7}$$

The following code generates Fig. 5.2.11.1 where a comparison of the theoretical solution with the Euler's numerical approach is provided.




Fig. 5.2.11.1. Stem plot of Euler Reccurrence relation

Codes/bm13.py

5.2.12 Which of the following is/are CORRECT about the value of $y = \log_e(-e^x)$, where x is a real number. (BM 2025)

a) y is real valued
b) y is complex valued
c) $y = x \pm in\pi$, where n is an odd integer and $i = \sqrt{-1}$
d) $y = x \pm in\pi$, where n is an even integer and $i = \sqrt{-1}$

Solution: Taking the prinipal argument,

$$e^{\mathrm{j}\pi} = -1 \implies e^{\mathrm{j}(2k+1)\pi} = -1, \tag{5.2.12.1}$$

$$\text{or, } e^{\pm \mathrm{j}n\pi} = -1, \text{ n odd} \tag{5.2.12.2}$$

$$\therefore y = \ln\left(e^{x \pm \mathrm{j}n\pi}\right) = x \pm jn\pi, \tag{5.2.12.3}$$

5.2.13 A discrete linear time invariant system has an impulse response function given by

$$h(n) = \delta(n) + \frac{1}{2}\delta(n-1) + \frac{1}{3}\delta(n-2). \tag{5.2.13.1}$$

For input signal $x(n) = \delta(n) + \delta(n-1)$, which of the following option(s) is/are CORRECT for the output signal $y(n)$? (BM 2025)

(a) $y(2) = 11/6$
(b) $y(2) = 5/6$
(c) $y(2) = 0$ for all $k \geq 3$
(d) $y(2) = 0$ for all $k \geq 4$

Solution:
Express sequences in vector form

The impulse response sequence $h(n)$ of length $M = 3$ is:

$$\mathbf{h(n)} = \begin{pmatrix} 1 & 1/2 & 1/3 \end{pmatrix} \tag{5.2.13.2}$$

The input signal sequence $x(n)$ of length $N = 2$ is:

$$\mathbf{x(n)} = \begin{pmatrix} 1 & 1 \end{pmatrix} \tag{5.2.13.3}$$

The linear convolution $y(n) = h(n) * x(n)$ has a total length of 4 points (spanning $n = 0, 1, 2, 3$). (From (5.1.10.3))
Construct the Convolution (Toeplitz) Matrix Linear convolution can be represented as a matrix-vector product **y = H x**, where $\mathbf{H}$ is a (M+N-1)*N=8 lower-triangular Toeplitz matrix formed by shifting $h(n)$ downwards:

$$\mathbf{H} = \begin{pmatrix} h(0) & 0 \\ h(1) & h(0) \\ h(2) & h(1) \\ 0 & h(2) \end{pmatrix} \tag{5.2.13.4}$$

$$= \begin{pmatrix} 1 & 0 \\ 1/2 & 1 \\ 1/3 & 1/2 \\ 0 & 1/3 \end{pmatrix} \tag{5.2.13.5}$$

The input vector $\mathbf{x}$ is:

$$\mathbf{x} = \begin{pmatrix} x(0) \\ x(1) \end{pmatrix} = \begin{pmatrix} 1 \\ 1 \end{pmatrix} \tag{5.2.13.6}$$

Matrix-Vector Multiplication

$$\begin{pmatrix} y(0) \\ y(1) \\ y(2) \\ y(3) \end{pmatrix} = \begin{pmatrix} 1 & 0 \\ 1/2 & 1 \\ 1/3 & 1/2 \\ 0 & 1/3 \end{pmatrix} \begin{pmatrix} 1 \\ 1 \end{pmatrix} \tag{5.2.13.7}$$

Computing each element:

$$y(0) = 1(1) + 0(1) = 1 \tag{5.2.13.8}$$

$$y(1) = \frac{1}{2}(1) + 1(1) = \frac{3}{2} \tag{5.2.13.9}$$

$$y(2) = \frac{1}{3}(1) + \frac{1}{2}(1) = \frac{5}{6} \tag{5.2.13.10}$$

$$y(3) = 0(1) + \frac{1}{3}(1) = \frac{1}{3} \tag{5.2.13.11}$$

For $k \geq 4$, $y(k) = 0$ since the signal duration ends at $n = 3$.
Verify the Options

- Option (a): $y(2) = \frac{11}{6}$ (Incorrect)

- Option (b): $y(2) = \frac{5}{6}$ (Correct)
- Option (c): $y(k) = 0$ for all $k \geq 3$ (Incorrect, since $y(3) = \frac{1}{3} \neq 0$)
- Option (d): $y(k) = 0$ for all $k \geq 4$ (Correct)




Fig. 5.2.13.1. x[n],h[n],y[n] vs n

The following code results the graph

Codes/bm17a.py

5.2.14 For an 8-bit Digital to Analog Converter (DAC), the binary input 0000 0000 results in 0 V, and 1111 1111 results in 5 V. The output of the DAC for an input of 1011 0111 is _____ (in volts, rounded off to two decimal places). (BM 2025)

Solution:

First, convert the binary input $(10110111)_2$ into its equivalent decimal value D:

$$D = 1 \cdot 2^7 + 0 \cdot 2^6 + 1 \cdot 2^5 + 1 \cdot 2^4 + 0 \cdot 2^3 + 1 \cdot 2^2 + 1 \cdot 2^1 + 1 \cdot 2^0 \quad (5.2.14.1)$$

$$D = 128 + 0 + 32 + 16 + 0 + 4 + 2 + 1 = 183 \quad (5.2.14.2)$$

For an 8-bit DAC:

- Minimum digital value $(00000000)_2 = 0$ corresponds to 0 V.
- Maximum digital value $(11111111)_2 = 255$ corresponds to Full-Scale Voltage $V_{FS} = 5$ V.

From (5.1.11.1) where $n = 8$ bits, so $2^8 - 1 = 255$.
Substituting $D = 183$ and $V_{FS} = 5$ V:


$$V_{out} = 5 \times \left(\frac{183}{255}\right) \quad (5.2.14.3)$$

$$V_{out} = \frac{915}{255} \approx 3.5882 \text{ V} \quad (5.2.14.4)$$

Rounding off to two decimal places gives: 3.59
The following code verifies the answer

Codes/bm18.py

5.2.15 What is the output voltage Vout for the circuit shown below? _____ (in volts, rounded off to the nearest integer).



(BM 2025)

Solution:
The given operational amplifier circuit is an inverting summing amplifier.
Given:

- $R_f = 10$ kΩ
- $R_1 = 5$ kΩ, $V_1 = 2$ V
- $R_2 = 4$ kΩ, $V_2 = 2$ V

- $R_3 = 2\ \text{k}\Omega, \quad V_3 = 1\ \text{V}$
- Power supply saturation limits: $\pm V_{\text{sat}} = \pm 15\ \text{V}$

Substitute the given component values into (5.1.12.7)

$$V_{\text{out}} = -\left(\frac{10}{5}(2) + \frac{10}{4}(2) + \frac{10}{2}(1)\right) \tag{5.2.15.1}$$


$$V_{\text{out}} = -\left(2(2) + 2.5(2) + 5(1)\right) \tag{5.2.15.2}$$

$$V_{\text{out}} = -(4 + 5 + 5) = -14\ \text{V} \tag{5.2.15.3}$$

Since the calculated voltage (-14 V) lies within the saturation limits (-15 V to $+15$ V), the op-amp stays in its linear region.

5.2.16 The frequency of the oscillator circuit shown in the figure below is _____ kHz. (rounded off to two decimal places)

Given: $R = 1\ \text{k}\Omega$; $R_1 = 2\ \text{k}\Omega$; $R_2 = 6\ \text{k}\Omega$; $C = 0.1\ \mu\text{F}$



(BM 2025)

Solution:

The given circuit is a Wien Bridge Oscillator.

Given values:

- $R = 1\ \text{k}\Omega = 10^3\ \Omega$

- $C = 0.1\ \mu\text{F} = 0.1 \times 10^{-6}\ \text{F} = 10^{-7}\ \text{F}$

Substitute R and C into equation (5.1.13.1)

$$f_0 = \frac{1}{2\pi(10^3)(10^{-7})} = \frac{1}{2\pi \times 10^{-4}}\ \text{Hz} \tag{5.2.16.1}$$


$$f_0 = \frac{10^4}{2\pi}\ \text{Hz} = \frac{10000}{2\pi} \approx 1591.549\ \text{Hz} \tag{5.2.16.2}$$

Converting to kilohertz (kHz):

$$f_0 = \frac{1591.549}{1000}\ \text{kHz} \approx 1.5915\ \text{kHz} \tag{5.2.16.3}$$

Rounding off to two decimal places: 1.59

5.2.17 For the RLC circuit shown below, the root mean square current (I_{rms}) at the resonance frequency is _____ amperes. (rounded off to the nearest integer)



(BM 2025)

Solution:

From (5.1.14)

Evaluating the resonance angular frequency and cyclic frequency:

$$\omega_0 = \frac{1}{\sqrt{(10 \times 10^{-3}\ \text{H})(8 \times 10^{-6}\ \text{F})}} \tag{5.2.17.1}$$

$$= \frac{1}{\sqrt{8 \times 10^{-8}}} \tag{5.2.17.2}$$

$$= 3535.53\ \text{rad/s} \tag{5.2.17.3}$$

$$f_0 = \frac{\omega_0}{2\pi} \approx 562.7\ \text{Hz} \tag{5.2.17.4}$$

At $\omega = \omega_0$, the net reactance is zero ($Z(\omega_0) = R = 60\,\Omega$).

RMS Current Evaluation at Resonance From (5.1.14.13)
Substituting the given numerical values ($V_{\text{rms}} = 240$ V, $R = 60\,\Omega$):

$$I_{\text{rms}}(\omega_0) = \frac{240 \text{ V}}{60\,\Omega} = 4 \text{ A} \tag{5.2.17.5}$$




Fig. 5.2.17.1. Impedence mag vs angular frequency, Impedence phase angle vs angular frequency

The following code results in graph

Codes/bm21.py

5.2.18 Newton Raphson method is used to solve the equation $x^3-2x-5=0$ with an initial guess $x_0 = 3$. What is x_1, the value after ONE iteration? _____ (rounded off to two decimal places) (BM 2025)

Solution:

Function Definition & Derivative

Given the non-linear equation:

$$f(x) = x^3 - 2x - 5 = 0 \tag{5.2.18.1}$$

Taking the derivative with respect to x:

$$f'(x) = 3x^2 - 2 \tag{5.2.18.2}$$

General Newton-Raphson Update Equation

From (5.1.15.1) Substituting $f(x_n)$ and $f'(x_n)$ into the update equation gives the explicit recurrence relation:

$$x_{n+1} = x_n - \frac{x_n^3 - 2x_n - 5}{3x_n^2 - 2} \tag{5.2.18.3}$$

$$= \frac{2x_n^3 + 5}{3x_n^2 - 2} \tag{5.2.18.4}$$

First Iteration Calculation ($n = 0$ with $x_0 = 3$)

Evaluating $f(x_0)$ and $f'(x_0)$:

$$f(3) = (3)^3 - 2(3) - 5 = 16 \tag{5.2.18.5}$$

$$f'(3) = 3(3)^2 - 2 = 25 \tag{5.2.18.6}$$

Using the update equation to calculate x_1:

$$x_1 = 3 - \frac{16}{25} = 2.36 \tag{5.2.18.7}$$

Subsequent Iterations (Finding the Actual Root)

Using the simplified update equation $x_{n+1} = \frac{2x_n^3+5}{3x_n^2-2}$:

$$x_0 = 3.0000 \tag{5.2.18.8}$$

$$x_1 = 2.3600 \tag{5.2.18.9}$$

$$x_2 = \frac{2(2.36)^3+5}{3(2.36)^2-2} \approx 2.1272 \tag{5.2.18.10}$$

$$x_3 = \frac{2(2.1272)^3+5}{3(2.1272)^2-2} \approx 2.0951 \tag{5.2.18.11}$$

$$x_4 \approx 2.0946 \quad \text{(Converged Real Root } \alpha\text{)} \tag{5.2.18.12}$$

x_1 after ONE iteration: 2.36




Fig. 5.2.18.1. Newton Raphson iteration for f(x)

The following code results in graph

Codes/bm22a.py

5.2.19 Strength (σ) of an implanted suture is given by the equation

$$\sigma = \sigma_0 - 2\log_e(t) \quad \text{for } t \geq 1, \tag{5.2.19.1}$$

where σ_0 represents the original strength and time t is measured in weeks. If the strength of the suture is 2 MPa at 4 weeks, what will be its strength (in MPa) at 8 weeks? _____ (rounded off to two decimal places) (BM 2025)

Solution:

Let $\sigma(t)$ denote the strength of the suture at time t weeks:

$$\sigma(t) = \sigma_0 - 2\ln(t) \tag{5.2.19.2}$$

We are given that at $t = 4$ weeks, the strength $\sigma(4) = 2$ MPa:
Now, we need to find the strength at $t = 8$ weeks, From (5.1.16.3)

$$\sigma(8) - 2 = -2\ln\left(\frac{8}{4}\right) \tag{5.2.19.3}$$

$$= -2\ln(2) \tag{5.2.19.4}$$

Substituting $\ln(2) \approx 0.69315$:

$$\sigma(8) - 2 = -1.3863 \tag{5.2.19.5}$$

$$\sigma(8) = 2 - 1.3863 = 0.6137 \text{ MPa} \tag{5.2.19.6}$$

Rounding off to two decimal places gives: 0.61




Fig. 5.2.19.1. Strength vs Time


The following code results in graph

Codes/bm23.py

5.2.20 Eight students (P, Q, R, S, T, U, V, and W) are playing musical chairs. The figure indicates their order of position at the start of the game. They play the game by moving forward in a circle in the clockwise direction.
After the 1st round, 4th student behind P leaves the game. After 2nd round, 5th student behind Q leaves the game. After 3rd round, 3rd student behind V leaves the game.

After 4th round, 4th student behind U leaves the game. Who all are left in the game after the 4th round?

Note: The figure shown is representative.



(A) P; T; Q; S

(B) V; P; T; Q

(C) W; R; Q; V

(D) Q; T; V; W

(BM 2025)

Solution:

Since students move forward in a **clockwise** direction around the circle, the direction **behind** a student corresponds to counting in the **counter-clockwise** direction.

Initial Setup (Counter-Clockwise sequence from P):

$$P \to W \to U \to V \to S \to Q \to T \to R \tag{5.2.20.1}$$

—

After 1st Round

- Condition: 4th student behind P leaves.
- Counter-clockwise from P: $1^{st} = W$, $2^{nd} = U$, $3^{rd} = V$, $4^{th} = S$.
- S leaves the game.
- Remaining students: P, R, T, Q, V, U, W

—

After 2nd Round

- Condition: 5th student behind Q leaves.
- Counter-clockwise from Q in the remaining circle: $1^{st} = T$, $2^{nd} = R$, $3^{rd} = P$, $4^{th} = W$, $5^{th} = U$.
- U leaves the game.
- Remaining students: P, R, T, Q, V, W

—

After 3rd Round

- Condition: 3rd student behind V leaves.
- Counter-clockwise from V in the remaining circle: 1st = Q, 2nd = T, 3rd = R.
- R leaves the game.
- Remaining students: P, T, Q, V, W

—

After 4th Round

- Condition: 4th student behind U leaves (since U was eliminated, we count starting from the position where U was, i.e., behind V / ahead of W).
- Counter-clockwise sequence of remaining students: V → W → P → T → Q.
- 1st = W, 2nd = P, 3rd = T, 4th = Q.
- W leaves the game.
- Remaining students: P, T, Q, V

—

Thus, the four students remaining after the 4th round are **P, T, Q, and S** (or **V, P, T, Q**).

(A) P; T; Q; S (5.2.20.2)

codes/bm24.py

5.2.21 The table lists the top 5 nations according to the number of gold medals won in a tournament; also included are the number of silver and the bronze medals won by them. Based only on the data provided in the table, which one of the following statements is INCORRECT?

Nation	Gold	Silver	Bronze
USA	40	44	41
Canada	39	27	24
Japan	20	12	13
Australia	17	19	16
France	16	26	22

(a) France will occupy the third place if the list were made on the basis of the total number of medals won.

(b) The order of the top two nations will not change even if the list is made on the basis of the total number of medals won.

(c) USA and Canada together have less than 50% of the medals awarded to the nations in the above table.

(d) Canada has won twice as many total medals as Japan.

(BM 2025)

Solution:

First, calculate the total number of medals for each nation:

- USA: $40 + 44 + 41 = 125$
- Canada: $39 + 27 + 24 = 90$
- Japan: $20 + 12 + 13 = 45$
- Australia: $17 + 19 + 16 = 52$
- France: $16 + 26 + 22 = 64$

Total medals won by all 5 nations combined:

$$\text{Total Medals} = 125 + 90 + 45 + 52 + 64 = 376 \tag{5.2.21.1}$$

Now, evaluate each statement:

(a) France in 3rd place by total medals: Ranking by total medals: USA (125), Canada (90), France (64), Australia (52), Japan (45). France is indeed in 3rd place. *(Correct statement)*

(b) Top two order unchanged: USA (125) is 1st and Canada (90) is 2nd in total medals, which matches their original gold medal ranking order. *(Correct statement)*

(c) USA and Canada have less than 50% of total medals: Combined total for USA and Canada: $125 + 90 = 215$. Percentage of total medals:

$$\frac{215}{376} \times 100\% \approx 57.18\% \tag{5.2.21.2}$$

Since $57.18\% > 50\%$, USA and Canada have more than 50% of the medals, making statement (c) INCORRECT.

(d) Canada has twice as many total medals as Japan: Japan = 45, Canada = $90 = 2 \times 45$. *(Correct statement)*

The following code verifies the solution

Codes/bm25.py

5.2.22 An organization allows its employees to work independently on consultancy projects but charges an overhead on the consulting fee. The overhead is 20% of the consulting fee, if the fee is up to rupee $5,00,000$. For higher fees, the overhead is rupee $1,00,000$ plus 10% of the amount by which the fee exceeds rupee $5,00,000$. The government charges a Goods and Services Tax of 18% on the total amount (the consulting fee plus the overhead). An employee of the organization charges this entire amount, i.e., the consulting fee, overhead, and tax, to the client. If the client cannot pay more than rupee $10,00,000$, what is the maximum consulting fee that the employee can charge?

(a) rupee $7,01,438$
(b) rupee $7,24,961$
(c) rupee $7,51,232$
(d) rupee $7,75,784$

(BM 2025)

Solution:

Let F be the consulting fee charged by the employee. Since the maximum total payable amount is rupee $10,00,000$, we assume $F > 5,00,000$.

1. Calculate the Overhead (O):

$$O = 1,00,000 + 0.10 \times (F - 5,00,000) \tag{5.2.22.1}$$

$$O = 1,00,000 + 0.10F - 50,000 = 50,000 + 0.10F \tag{5.2.22.2}$$

2. Calculate the Total before Tax ($T_{\text{pre-tax}}$):

$$T_{\text{pre-tax}} = F + O = F + (50,000 + 0.10F) = 1.10F + 50,000 \tag{5.2.22.3}$$

3. Calculate Total Amount Payable by Client (T_{total}):

$$T_{\text{total}} = T_{\text{pre-tax}} + 0.18 \times T_{\text{pre-tax}} = 1.18 \times T_{\text{pre-tax}} \tag{5.2.22.4}$$

Given that the maximum total amount $T_{\text{total}} = 10,00,000$:

$$1.18 \times (1.10F + 50,000) = 10,00,000 \tag{5.2.22.5}$$

$$1.10F + 50,000 = \frac{10,00,000}{1.18} \tag{5.2.22.6}$$

$$1.10F + 50,000 \approx 847,457.627 \tag{5.2.22.7}$$

$$1.10F = 847,457.627 - 50,000 = 797,457.627 \tag{5.2.22.8}$$

$$F = \frac{797,457.627}{1.10} \approx 724,961.48 \tag{5.2.22.9}$$

Rounding off to the nearest integer gives rupee $7,24,961$.

5.2.23 The determinant of a 3×3 matrix $\mathbf{M}$ is 8. If every element of $\mathbf{M}$ is multiplied by -2, the determinant of the modified matrix will be: (BM 2025)

(a) -64
(b) -16
(c) 8
(d) 64

Solution:
Given Data:
Order of matrix $\mathbf{M}$, $n = 3$ Determinant of matrix $\mathbf{M}$, $\det \mathbf{M} = 8$ Scalar multiplier, $k = -2$ Substituting the given values into (5.1.18.1)

$$\det(-2\mathbf{M}) = (-2)^3 \cdot \det(\mathbf{M}) \tag{5.2.23.1}$$

$$\det(-2\mathbf{M}) = -8 \cdot 8 = -64 \tag{5.2.23.2}$$

The following code verifies solution

Codes/bm26.py