

Django Request Object — Complete Developer Reference

What Is a Request Object?

In Django, every incoming HTTP request is represented by an instance of the `HttpRequest` class.

It holds **everything the server knows about the client's request** — including URL info, headers, cookies, files, and metadata.

◆ 1. `req.META` — Low-Level Metadata

Definition:

A dictionary containing **low-level metadata** — raw data from the web server, including environment variables, HTTP headers, and connection details.

What is Low-Level Metadata?

Low-level metadata means “**data about the request at the network or server level**” — unprocessed values like IP addresses, protocol, ports, and raw headers.

Difference from Headers:

Headers are part of metadata, but metadata also includes deeper system-level info.

Example Keys in `req.META`:

| Key | Example Value | Meaning |
|------------------------------|--|---------------------------|
| <code>REMOTE_ADDR</code> | <code>'192.168.0.12'</code> | Client IP address |
| <code>HTTP_USER_AGENT</code> | <code>'Mozilla/5.0 (Windows NT 10.0)'</code> | Browser info |
| <code>SERVER_PORT</code> | <code>'8000'</code> | Port Django is running on |

| | | |
|-----------------------------|---|----------------------|
| <code>REQUEST_METHOD</code> | <code>'POST'</code> | HTTP method |
| <code>PATH_INFO</code> | <code>' /shop/2/ '</code> | Requested path |
| <code>QUERY_STRING</code> | <code>'search=laptop&page=2'</code> | Raw query parameters |

Example:

```
def log_request(req):
    print("IP:", req.META.get("REMOTE_ADDR"))
    print("User-Agent:", req.META.get("HTTP_USER_AGENT"))
    return HttpResponse("Logged request info")
```

Real-World Example:

Used in **logging, analytics, and security** to capture client IPs, request origins, or devices.

♦ 2. `req.headers`

Definition:

A **high-level**, dictionary-like object that contains all HTTP headers sent by the client (browser, Postman, etc.).

It is **case-insensitive** and **user-friendly**, built from the low-level `req.META`.

Difference from `req.META`:

| <code>req.headers</code> | <code>req.META</code> |
|---|---|
| High-level, readable | Low-level, raw server data |
| Keys look like <code>"User-Agent"</code> | Keys look like <code>"HTTP_USER_AGENT"</code> |
| Only contains headers | Contains headers + other environment info |

Example Use Case:

Restrict your app from being accessed by Postman or cURL.

```
def secure_view(req):
```

```
user_agent = req.headers.get("User-Agent", "")
if "Postman" in user_agent:
    return HttpResponseForbidden("Requests from Postman are not
allowed.")
return HttpResponse("Welcome, browser user!")
```

Real-World Example:

Allow only browser-originated requests while blocking testing tools or bots.

◆ 3. `req.path`

Definition:

Returns the **path part of the URL**, excluding the domain name and query parameters.

Example:

`https://myshop.com/products/15?ref=home`

➡ `req.path = '/products/15'`

Real-World Example:

Track which product page a user is visiting.

◆ 4. `req.path_info`

Definition:

Similar to `req.path`, but it gives the **decoded URL path** (used internally for routing).
If the path contains URL-encoded characters, this shows the readable version.

Example:

`/product/%E2%9C%93 ➡ req.path_info = '/product/✓'`

Real-World Example:

Useful when writing middleware that intercepts raw URLs before Django resolves them.

◆ 5. req.user

Definition:

Represents the **authenticated user** associated with the request.
If not logged in, it defaults to an `AnonymousUser`.

Example:

```
if req.user.is_authenticated:
    return HttpResponse(f"Welcome, {req.user.username}")
else:
    return HttpResponse("Please log in first.")
```

Real-World Example:

Used in dashboards, access control, or personalization.

◆ 6. req.COOKIE — 🍪 Cookies

Definition:

A dictionary containing all cookies sent by the client's browser.

What are Cookies?

Cookies are **small pieces of data stored in the browser** to help websites remember user information between requests.

They solve the **stateless** nature of HTTP.

Example Cookie Data:

| Key | Value | Meaning |
|-------------------------|------------------------------|---------------------------|
| <code>session id</code> | <code>3adf76b90e9d12c</code> | Django session identifier |
| <code>csrftoken</code> | <code>xYz123AbC</code> | Protects against CSRF |
| <code>theme</code> | <code>dark</code> | User's theme preference |

Example (Access):

```
def get_theme(req):
    theme = req.COOKIE.get('theme', 'light')
    return HttpResponse(f"Theme: {theme}")
```

Example (Set/Delete):

```
def set_cookie(req):
    res = HttpResponse("Cookie set!")
    res.set_cookie('theme', 'dark', max_age=3600)
    return res

def clear_cookie(req):
    res = HttpResponse("Cookie cleared!")
    res.delete_cookie('theme')
    return res
```

Real-World Uses:

- Login sessions (`sessionid`)
- Preferences (language, dark mode)
- Analytics or tracking
- Cart persistence

◆ 7. `req.FILES`

Definition:

Contains all files uploaded via POST requests (`<input type="file">`).

Example:

```
from django.core.files.storage import FileSystemStorage

def upload_file(req):
    if 'pic' in req.FILES:
```

```
fs = FileSystemStorage()
filename = fs.save(req.FILES['pic'].name, req.FILES['pic'])
image_url = fs.url(filename)
return JsonResponse({'image_url': image_url})
return JsonResponse({'error': 'No file uploaded'})
```

Real-World Example:

Profile picture uploads, document submission, etc.

◆ 8. `req.session`

Definition:

A dictionary-like object used to store **per-user session data** (stored on the server).

How it works with Cookies:

Django stores a small cookie (`sessionid`) in the browser, which links to data stored on the server.

Example:

```
req.session['cart'] = ['laptop', 'mouse']
```

Real-World Example:

Maintaining a shopping cart or keeping login info.

◆ 9. `req.scheme`

Definition:

Returns `'http'` or `'https'`, indicating which protocol the client used.

Example:

```
if req.scheme != 'https':
    return HttpResponseForbidden("Use HTTPS only.")
```

Real-World Example:

Redirecting all traffic to HTTPS in production.

◆ 10. `req.encoding`

Definition:

Specifies the character encoding (like `'utf-8'`) used to decode form data or the request body.

Real-World Example:

Ensures that non-English text or emojis are correctly decoded from a POST body.

◆ 11. `req.content_type` — MIME Type

Definition:

Shows the **MIME type** (or **Content-Type**) of the request body.

✚ What is MIME?

Full form: Multipurpose Internet Mail Extensions

It defines **what type of data** is being sent over HTTP.

Structure:

`type/subtype`

Examples:

| MIME Type | Meaning |
|-------------------------------|------------|
| <code>text/html</code> | HTML page |
| <code>text/plain</code> | Plain text |
| <code>application/json</code> | JSON data |
| <code>image/jpeg</code> | JPEG image |

`multipart/form-` File upload
`data` data

Example (in Django):

```
def check_type(req):  
    print(req.content_type)  
    if req.content_type == 'application/json':  
        data = json.loads(req.body)  
        return JsonResponse({'received': data})
```

Real-World Example:

APIs check MIME type to know if they should parse `req.body` as JSON, form data, or file data.



URL Parameter Example

When you define:

```
path('sample/<int:id>/', views.sample)
```

Your view receives both `req` and `id`:

```
def sample(req, id):  
    return HttpResponse(f"Product ID: {id}")
```

Real-World Example:

Dynamic routes for products, users, etc.



Example with a Fake Product Dictionary

```
# products.py  
prod_list = {  
    1: {"name": "Laptop", "price": 60000},  
    2: {"name": "Mobile", "price": 25000},
```

```
        3: {"name": "Headphones", "price": 2000},
    }

# views.py
from . import products

def sample(req, id):
    product = products.prod_list.get(id, {"error": "Product not
found"})
    return JsonResponse(product)
```

How to View All Request Attributes

Use this to explore everything Django provides:

```
def debug_request(req):
    print(dir(req))
    return HttpResponse("Check console for all request attributes.")
```