

1

```
a, b = 5, 3
a += b * 2
print(a)
```

答案: 11

2

```
lst = [1,2,3,4]
lst.insert(1, 9)
del lst[-1]
print(lst)
```

答案: [1, 9, 2, 3]

3

```
def func(x, y=2):
    return x ** y
print(func(3), func(2,3))
```

答案: 9 8

4

```
s = {1,2,2,3,4,4}
print(len(s), 3 in s)
```

答案: 4 True

5

```
total = 0
for i in range(1,6):
    if i % 2 == 0:
        total += i
print(total)
```

答案: 6

6

```
d = {"a":10, "b":20}
d["c"] = d["a"] + d["b"]
print(d)
```

答案: {'a': 10, 'b': 20, 'c': 30}

7

```
t = (1,2,3,4)
print(t[1:3], len(t))
```

答案: (2, 3) 4

8

```
x = [i*3 for i in range(4) if i != 2]
print(x)
答案: [0, 3, 9]
```

9

```
a = 7
print(a > 5 and a < 10 or a == 0)
答案: True
```

10

```
nums = [2,5,1,6]
nums.sort()
print(nums[-2])
答案: 5
```

11

```
def test():
    global x
    x = 10
x = 5
test()
print(x)
答案: 10
```

12

```
lst = list(range(1,8,2))
print(sum(lst))
答案: 16
```

13

```
i = 0
while i < 4:
    if i == 2:
        i += 1
        continue
    print(i, end=" ")
    i += 1
答案: 0 1 3
```

14

```
d1 = {"name": "Python", "score": 90}
print(d1.get("age", 0))
答案: 0
```

15

```
a, b, c = [10,20,30]
print(c > b > a)
```

答案: True

16

```
s1 = {1,2,3}
s2 = {3,4,5}
print(s1 & s2, s1 | s2)
```

答案: {3} {1,2,3,4,5}

17

```
res = lambda x,y:x*y+1
print(res(2,3))
```

答案: 7

18

```
lst = [1,[2,3],4]
print(lst[1][1] + lst[2])
```

答案: 7

19

```
count = 0
for i in range(10):
    if i > 5:
        break
    count +=1
print(count)
```

答案: 6

20

```
t = (5,)
print(type(t), len(t))
```

答案: <class 'tuple'> 1

21

```
def add(*args):
    return sum(args)
print(add(1,2,3), add(4,5))
```

答案: 6 9

22

```
a = [1,2,3]
b = a.copy()
```

```
b.append(4)
print(a)
```

答案: [1,2,3]

23

```
x = 9
print(x % 4, x // 4)
```

答案: 1 2

24

```
dic = {}
dic[1] = "one"
dic[2] = "two"
print(list(dic.keys()))
```

答案: [1,2]

25

```
s = 0
for i in [1,3,5,7]:
    s += i * 2
print(s)
```

答案: 32

26

```
lst = [True, False, True]
print(all(lst), any(lst))
```

答案: False True

27

```
def outer():
    x = 1
    def inner():
        nonlocal x
        x +=1
        return x
    return inner()
print(outer())
```

答案: 2

28

```
a = reversed([1,2,3])
print(list(a))
```

答案: [3,2,1]

29

```
x = 0
if x:
    print("yes")
else:
    print("no")
```

答案: no

30

```
lst = [1,2,3,2,1]
print(lst.count(1), max(lst))
```

答案: 2 3

31

```
s = set(range(5))
s.remove(2)
print(s)
```

答案: {0,1,3,4}

32

```
def f(x):
    if x > 0:
        return x + f(x-1)
    return 0
print(f(3))
```

答案: 6

33

```
a = [1,2]
b = [3,4]
c = a + b
print(c[1:3])
```

答案: [2,3]

34

```
d = {"x":5}
if "x" in d:
    d["x"] *= 2
print(d)
```

答案: {'x':10}

35

```
i = 5
while i > 0:
    i -= 1
    if i == 3:
```

```
        continue
    print(i, end=" ")
```

答案: 4 2 1 0

36

```
lst = [i for i in range(1,6) if i%2!=0]
print(lst)
```

答案: [1,3,5]

37

```
t1 = (1,2)
t2 = (3,)
print(t1 + t2)
```

答案: (1,2,3)

38

```
a = 3
b = "6"
print(str(a) + b)
```

答案: 36

39

```
def show(**kwargs):
    print(kwargs["a"])
show(a=10, b=20)
```

答案: 10

40

```
lst = [2,4,6,8]
print(lst[::2])
```

答案: [2,6]

41

```
s1 = {1,2}
s2 = {2,3}
print(s1 - s2)
```

答案: {1}

42

```
x = 10
def demo():
    x = 20
demo()
print(x)
```

答案: 10

43

```
res = sorted([9,5,7], reverse=True)
print(res)
答案: [9,7,5]
```

44

```
a = [1,2,3]
a[0] = a[-1]
print(a)
答案: [3,2,3]
```

45

```
for i in range(3):
    for j in range(2):
        if j ==1:
            print(i+j, end=" ")
答案: 1 2 3
```

46

```
d = dict.fromkeys(["a","b"], 0)
d["a"] = 5
print(d)
答案: {'a':5, 'b':0}
```

47

```
x = [1,2]
x.extend([3,4])
print(len(x))
答案: 4
```

48

```
print(abs(-5), round(3.7))
答案: 5 4
```

49

```
def calc(a,b):
    return a+b, a-b
x, y = calc(5,2)
print(y)
答案: 3
```

50

```
import numpy as np
arr = np.array([1,2,3])
```

```
print(arr * 2)
```

答案: [2 4 6]

51

```
Plain
lst = [1, 2, 3, 4, 5]
new_lst = lst[1:-2][::-1]
print(new_lst)
```

答案: [3, 2]

52

```
Plain
x = 0
for i in range(1, 5):
    for j in range(i):
        x += 1
print(x)
```

答案: 10

53

```
Plain
def func(n):
    if n <= 1:
        return 1
    return func(n-1) * n // 2
print(func(4))
```

答案: 6

54

```
Plain
a = [1, [2, 3], 4]
b = a.copy()
a[1][0] = 99
print(b)
```

答案: [1, [99, 3], 4]

55

```
Plain
s = {i % 3 for i in range(7)}
print(s)
```


答案: {0, 1, 2}

56

```
Plain
d = {"a": [1,2], "b":[3,4]}
d["a"].append(d["b"][1])
print(sum(d["a"]))
```

答案: 7

57

```
Plain
x = 5
def f():
    global x
    x += 3
    def g():
        nonlocal x
        x *= 2
    g()
f()
print(x)
```

答案: 16

58

```
Plain
lst = list(range(2,11,3))
res = [x**2 for x in lst if x%4 !=0]
print(res)
```

答案: [4, 25]

59

```
Plain
i = 1
while i < 10:
    if i % 4 == 0:
        i += 2
        continue
    print(i, end="")
    i += 1
```

答案: 1235679

60

```
Plain
t = (1,2,3)
a, *b = t
print(a, b)
```

答案: 1 [2, 3]

61

```
Plain
def demo(*args, **kwargs):
    print(sum(args) + kwargs["num"])
demo(1,2,3, num=10)
```

答案: 16

62

```
Plain
s1 = set(range(1,6))
s2 = set(range(3,8))
print(len(s1 ^ s2))
```

答案: 4

63

```
Plain
lst = [3,1,4,1,5,9]
lst.sort(reverse=True)
print(lst[:3][-1])
```

答案: 4

64

```
Plain
x = lambda a,b: a if a>b else b
print(x(x(5,8), x(7,3)))
```

答案: 8

65

```
Plain
strs = "hello python"
res = [c for c in strs if c not in 'aeiou']
print(len(res))
```

答案: 9

66

```
Plain
count = 0
for i in range(3):
    for j in range(i+1,4):
        count +=1
print(count)
```

答案: 6

67

```
Plain
d = dict(zip([1,2,3], ['a','b','c']))
print(list(d.values())[1])
```

答案: b

68

```
Plain
def outer(x):
    def inner(y):
        return x * y + x
    return inner
f = outer(3)
print(f(4))
```

答案: 15

69

```
Plain
lst = [i for i in range(10) if i%3==0 and i%2!=0]
print(lst)
```

答案: [3, 9]

70

```
Plain
a = 10
b = 20
a, b = b, a+b
print(a, b)
```

答案: 20 30

71

```
Plain
import numpy as np
arr1 = np.array([1,2])
arr2 = np.array([3,4])
print(arr1.dot(arr2))
```

答案: 11

72

```
Plain
nums = [2,5,8,11]
print(list(filter(lambda x:x%2==1, nums)))
```

答案: [5, 11]

73

```
Plain
s = ""
for i in range(2,6):
    if i ==4:
        break
    s += str(i)
print(s)
```

答案: 23

74

```
Plain
t = tuple([x*2 for x in range(1,5)])
print(t[1:3])
```

答案: (4, 6)

75

```
Plain
x = [1,2,3]
y = x
y[1] = 99
print(x is y)
```

答案: True

76

```
Plain
def calc(x):
    return x+1, x-1
```

```
m, n = calc(6)
print(m * n)
```

答案: 35

77

```
Plain
d = {"name": "Li", "age": 20}
d.setdefault("age", 30)
print(d["age"])
```

答案: 20

78

```
Plain
lst = [[i+j for j in range(2)] for i in range(3)]
print(lst[2])
```

答案: [2, 3]

79

```
Plain
i = 0
while True:
    i += 2
    if i > 7:
        break
print(i)
```

答案: 8

80

```
Plain
s1 = {1, 2, 3}
s2 = {2, 3, 4}
s1.update(s2 - {3})
print(s1)
```

答案: {1, 2, 3, 4}

81

```
Plain
def f(n):
    s = 0
    while n > 0:
        s += n % 10
```

```
        n //=10
    return s
print(f(1234))
```

答案: 10

82

```
Plain
a = [1,3,5,7]
print(sum(a[1::2]))
```

答案: 10

83

```
Plain
str1 = "abcd123"
new_s = ''.join([c for c in str1 if c.isalpha()])
print(new_s)
```

答案: abcd

84

```
Plain
x = 0
for i in range(1,4):
    x = x * 2 + i
print(x)
```

答案: 11

85

```
Plain
lst = [5,2,9,1]
lst1 = sorted(lst, key=lambda x:-x)
print(lst1[-2])
```

答案: 2

86

```
Plain
def g():
    global a
    a = 100
a = 10
g()
print(a)
```

答案: 100

87

```
Plain
t = (1,2,3,4)
print(sum(t[1:-1]) * len(t))
```

答案: 20

88

```
Plain
d = {k:k**2 for k in range(1,5)}
print(d[3])
```

答案: 9

89

```
Plain
for i in range(5):
    if i % 2 ==0:
        continue
    print(i, end="")
```

答案: 13

90

```
Plain
import numpy as np
arr = np.arange(2,10,2)
print(arr.mean())
```

答案: 5.0

91

```
Plain
a = [1,2]
b = [3,4]
print([x+y for x in a for y in b])
```

答案: [4, 5, 5, 6]

92

```
Plain
x = bool([]) or bool([0])
```

```
print(x)
```

答案: True

93

```
Plain
def func(a,b):
    while b:
        a,b = b,a%b
    return a
print(func(24,18))
```

答案: 6

94

```
Plain
lst = [1,2,3]
lst.append(lst.pop(0))
print(lst)
```

答案: [2, 3, 1]

95

```
Plain
s = "python"
print(s[1::2][::-1])
```

答案: nty

96

```
Plain
nums = list(map(int, "1 3 5 7".split()))
print(max(nums) + min(nums))
```

答案: 8

97

```
Plain
x = 5
y = 3
x ^= y
print(x)
```

答案: 6

98

```
Plain
def inner_func(x):
    return lambda t: x*t
f1 = inner_func(2)
f2 = inner_func(3)
print(f1(5)+f2(5))
```

答案: 25

99

```
Plain
s = set()
for i in range(4):
    s.add(i//2)
print(s)
```

答案: {0, 1}

100

```
Plain
lst = [i for i in range(10) if bin(i).count('1')==2]
print(lst)
```

答案: [3,5,6,9]

101

```
Plain
lst = [2, 4, 6, 8, 10]
res = list(map(lambda x: x//2 if x%4==0 else x*2, lst))
print(res)
```

答案: [4, 2, 12, 4, 20]

102

```
Plain
total = 0
for i in range(1, 6):
    total += i if i%2 else -i
print(total)
```

答案: 3

103

```
Plain
def test(n):
    return sum([i for i in range(n) if i%3 and i%5])
print(test(16))
```

答案: 60

104

```
Plain
a = [10,20,[30,40]]
b = a[:]
a[2][0] = 99
a[1] = 88
print(b)
```

答案: [10, 20, [99, 40]]

105

```
Plain
d = {"x":1, "y":2, "z":3}
res = sum(v for k,v in d.items() if k!="y")
print(res)
```

答案: 4

106

```
Plain
x = 1
while x < 20:
    x *= 2
    if x == 8:
        continue
print(x)
```

答案: 32

107

```
Plain
def outer():
    num = 0
    def inner():
        nonlocal num
        num += 5
        return num
    return inner
f = outer()
print(f(), f(), f())
```

答案: 5 10 15

108

```
Plain
s = {1,2,3}
s.add(2)
s.update([3,4,5])
s.discard(1)
print(len(s))
```

答案: 3

109

```
Plain
lst = [i**2 for i in range(6) if i%2==1]
print(lst[1:])
```

答案: [9, 25]

110

```
Plain
a, b = 6, 4
a = a ^ b
b = a ^ b
a = a ^ b
print(a, b)
```

答案: 4 6

111

```
Plain
import numpy as np
arr = np.array([[1,2],[3,4]])
print(arr.sum(axis=0))
```

答案: [4 6]

112

```
Plain
str1 = "12ab34cd"
res = [int(c) for c in str1 if c.isdigit()]
print(sum(res))
```

答案: 10

113

```
Plain
count = 0
for i in range(4):
    for j in range(4):
        if i == j:
            count +=1
print(count)
```

答案: 4

114

```
Plain
def func(*nums):
    return max(nums) - min(nums)
print(func(2,8,1,9,3))
```

答案: 8

115

```
Plain
lst = [5,3,8,3,5]
new_lst = sorted(list(set(lst)))
print(new_lst[-2])
```

答案: 5

116

```
Plain
x = False
if 0 or [] or None:
    x = True
else:
    x = False
print(x)
```

答案: False

117

```
Plain
t = (2,4,6,8,10)
print(sum(t[::2]) - sum(t[1::2]))
```

答案: 4

118

```
Plain
d = {}
for i in range(3):
    d[i] = d.get(i, 0) + i
print(d)
```

答案: {0: 0, 1: 1, 2: 2}

119

```
Plain
res = 0
i = 10
while i > 1:
    res += i%3
    i -= 2
print(res)
```

答案: 9

120

```
Plain
f = lambda x: x+2 if x%2 else x-2
print(f(5), f(4))
```

答案: 7 2

121

```
Plain
lst = [[1,2],[3,4],[5,6]]
print([y for x in lst for y in x if y%2==0])
```

答案: [2, 4, 6]

122

```
Plain
global_num = 10
def change():
    global global_num
    global_num *= 2
change()
global_num += 5
print(global_num)
```

答案: 25

123

```
Plain
s1 = set(range(2,11,2))
s2 = set(range(3,12,3))
print(s1 & s2)
```

答案: {6}

124

```
Plain
def fib(n):
    a,b = 1,1
    for _ in range(n-2):
        a,b = b,a+b
    return b
print(fib(6))
```

答案: 8

125

```
Plain
strs = "a1b2c3"
new_str = ''.join([s.upper() for s in strs if not s.isdigit()])
print(new_str)
```

答案: ABC

126

```
Plain
lst = [1,2,3,4,5]
lst.insert(2, lst.pop(-1))
print(lst)
```

答案: [1, 2, 5, 3, 4]

127

```
Plain
x = 0
for i in range(1,5):
    for j in range(i):
        if j%2 ==0:
            x +=j
print(x)
```

答案: 8

128

```

Plain
d = {"a":10, "b":20, "c":30}
keys = [k for k,v in d.items() if v>15]
print(keys)

```

答案: ['b', 'c']

129

```

Plain
import numpy as np
arr = np.array([1,3,5,7])
print(arr[arr>3])

```

答案: [5 7]

130

```

Plain
def calc(a, b=4):
    return a * b - a
print(calc(3), calc(3,2))

```

答案: 9 3

131

```

Plain
num = 15
res = "奇数" if num%2 else "偶数"
res += "且是3的倍数" if num%3==0 else ""
print(res)

```

答案: 奇数且是3的倍数

132

```

Plain
lst = [9,5,7,2,8]
lst.sort(key=lambda x: x%5)
print(lst)

```

答案: [5, 2, 7, 8, 9]

133

```

Plain
s = 0
for i in range(10):
    if i % 4 == 3:
        continue

```

```
s += i
print(s)
```

答案: 33

134

```
Plain
t = (1,2,3)
print(t * 2 + (4,))
```

答案: (1, 2, 3, 1, 2, 3, 4)

135

```
Plain
def add_num(x):
    def inner(y):
        return x + y
    return inner
a = add_num(10)
b = add_num(20)
print(a(5)+b(5))
```

答案: 40

136

```
Plain
words = "python java c++"
lst = words.split()
print(len(lst), lst[1].upper())
```

答案: 3 JAVA

137

```
Plain
a = [1,3,5]
b = [2,4,6]
print([a[i]+b[i] for i in range(len(a))])
```

答案: [3, 7, 11]

138

```
Plain
x = 12
print(bin(x).count('0'), bin(x).count('1'))
```

答案: 2 2

139

```
Plain
d = dict.fromkeys([1,2,3], [])
d[1].append(5)
print(d)
```

答案: {1: [5], 2: [5], 3: [5]}

140

```
Plain
i = 0
res = []
while len(res) < 4:
    i += 3
    res.append(i)
print(res[-1])
```

答案: 12

141

```
Plain
def judge(n):
    return n>0 and n%2==0
print(list(filter(judge, [-2,0,3,4,6])))
```

答案: [4, 6]

142

```
Plain
lst = [i for i in range(20) if 10<i<15]
print(lst[::-1][2])
```

答案: 12

143

```
Plain
import numpy as np
arr = np.array([2,4,6,8])
print(arr.max() - arr.min())
```

答案: 6

144

```
Plain
s = ""
```

```
for i in range(5):
    if i ==2:
        continue
    s += str(i*2)
print(s)
```

答案: 0268

145

```
Plain
a = 8
b = 5
print(a//b, a%b, divmod(a,b))
```

答案: 1 3 (1, 3)

146

```
Plain
lst = [1,2,3,4]
lst.remove(2)
lst.insert(0,9)
print(lst.index(3))
```

答案: 2

147

```
Plain
def func(x,y):
    while x < y:
        x +=2
        y -=1
    return x-y
print(func(2,9))
```

答案: 1

148

```
Plain
data = [11,22,33,44]
new_data = data[1:-1]
new_data[0] = 99
print(data)
```

答案: [11, 22, 33, 44]

149

```

Plain
s1 = {i for i in range(8) if i%2==0}
s2 = {i for i in range(8) if i%3==0}
print(len(s1 - s2))

```

答案: 3

150

```

Plain
total = 0
for i in range(1,7):
    total += 1 if i%2==0 else -1
print(total)

```

答案: 0

151

```

Plain
lst = [1, 2, 3, 4, 5, 6]
res = []
for i in lst:
    if i % 2 == 0:
        res.append(i**2)
    else:
        res.append(i**3)
print(res[2:-2])

```

答案: [27, 16]

152

```

Plain
def func():
    a = 10
    def inner():
        nonlocal a
        a += 5
        return a
    return inner
f1 = func()
f2 = func()
print(f1(), f2(), f1())

```

答案: 15 15 20

153

```

Plain
d = {"a": 5, "b": 12, "c": 8}

```

```
sort_d = sorted(d.items(), key=lambda x: x[1])
print(sort_d[-1][0])
```

答案: b

154

```
Plain
x, y = 0, 0
for i in range(1, 4):
    x += i
    y = x * 2
print(x, y)
```

答案: 6 12

155

```
Plain
s = set()
for i in range(5):
    s.add(i // 2 + i % 2)
print(sorted(s))
```

答案: [0, 1, 2, 3]

156

```
Plain
lst = [2, 3, 5, 7]
new_lst = list(map(lambda x: x%3, lst))
print(new_lst.count(1))
```

答案: 2

157

```
Plain
import numpy as np
arr = np.array([[1, 3], [2, 4]])
print(np.sum(arr[1,:]) - np.max(arr[:,0]))
```

答案: 4

158

```
Plain
str_s = "program"
res = str_s[1:-1][::-2]
print(res)
```

答案: mar

159

```
Plain
total = 0
i = 1
while i <= 8:
    if i % 3 == 0:
        i += 1
        continue
    total += i
    i += 1
print(total)
```

答案: 27

160

```
Plain
def test(a, *args):
    return a + sum(args)
print(test(2), test(2,3,4), test(1,2,3,4))
```

答案: 2 9 10

161

```
Plain
lst = [1, [2, [3, 4]], 5]
print(lst[1][1][0] + lst[-1])
```

答案: 8

162

```
Plain
a = 15
b = 4
print(a & b, a | b, a ^ b)
```

答案: 4 15 11

163

```
Plain
d = {}
for i in range(1,4):
    d[i] = d.get(i-1, 0) + i
print(d)
```

答案: {1: 1, 2: 3, 3: 6}

164

```
Plain
lst = [i for i in range(12) if (i%4==0 or i%3==0) and i!=0]
print(len(lst))
```

答案: 6

165

```
Plain
x = True
y = 0
z = None
print(x and y or z, x or y and z)
```

答案: None True

166

```
Plain
t = (1,3,5,7,9)
new_t = t[1::2]
print(sum(new_t) * len(new_t))
```

答案: 30

167

```
Plain
def outer(x):
    def inner(y):
        return x**2 - y
    return inner
f = outer(5)
print(f(10))
```

答案: 15

168

```
Plain
s1 = set(range(1,10,2))
s2 = set(range(2,11,3))
print(s1.intersection(s2))
```

答案: {5}

169

```
Plain
nums = [4, 2, 9, 1, 7]
nums.sort(reverse=True)
print(nums[:-2][-1])
```

答案: 4

170

```
Plain
res = ""
for i in range(3):
    for j in range(2):
        res += str(i+j)
print(res)
```

答案: 011223

171

```
Plain
import numpy as np
arr = np.array([3,6,9,12])
arr2 = arr / 3
print(arr2[arr2>2])
```

答案: [4.]

172

```
Plain
def func(n):
    if n == 1:
        return 1
    return func(n-1) + n
print(func(5))
```

答案: 15

173

```
Plain
lst = [10,20,30]
lst.append(lst.pop(1))
print(lst)
```

答案: [10, 30, 20]

174

```
Plain
a = [1,2,3]
b = a * 2
b[2] = 99
print(a)
```

答案: [1, 2, 3]

175

```
Plain
d = {"name":"Tom", "age":18}
print(d.get("gender", "unknown").upper())
```

答案: UNKNOWN

176

```
Plain
count = 0
for i in range(6):
    if i % 2 == 1 and i % 3 != 0:
        count +=1
print(count)
```

答案: 2

177

```
Plain
x = lambda a,b : (a+b, a-b)
m, n = x(9,4)
print(m * n)
```

答案: 65

178

```
Plain
s = "ABCDEFGH"
print(len(s[2:5]) + len(s[:3]))
```

答案: 6

179

```
Plain
num_list = [x for x in range(15) if x >5 and x%2==0]
print(sum(num_list))
```

答案: 36

180

```
Plain
global_x = 0
def change_x():
    global global_x
    global_x += 3
change_x()
global_x *= 2
change_x()
print(global_x)
```

答案: 9

181

```
Plain
lst = [[x*y for y in range(1,3)] for x in range(2,4)]
print(lst[-1][0])
```

答案: 3

182

```
Plain
s1 = {2,4,6,8}
s2 = {4,5,6,7}
s1.difference_update(s2)
print(s1)
```

答案: {2, 8}

183

```
Plain
def calc(**kwargs):
    return kwargs["x"] + kwargs["y"]
print(calc(x=5, y=6, z=7))
```

答案: 11

184

```
Plain
i = 8
while i > 0:
    if i % 3 == 0:
        break
    i -= 1
print(i)
```

答案: 6

185

```
Plain
str1 = "12345abcde"
num = [int(c) for c in str1 if c.isdigit()]
char = [c for c in str1 if c.isalpha()]
print(len(num) * len(char))
```

答案: 25

186

```
Plain
t = (3,6,9)
a, *b, c = t
print(a, b, c)
```

答案: 3 [] 9

187

```
Plain
lst = [5,1,9,3,7]
new_lst = sorted(lst, key=lambda x: -x//2)
print(new_lst[0])
```

答案: 1

188

```
Plain
x = 0
for i in range(1,7):
    if i == 4:
        continue
    x += i * 2
print(x)
```

答案: 32

189

```
Plain
import numpy as np
arr = np.arange(1,11,2)
print(np.median(arr))
```

答案: 5.0

190

```
Plain
d = {k:k**3 for k in range(1,5)}
print(d[2] + d[4])
```

答案: 72

191

```
Plain
def is_prime(n):
    for i in range(2,n):
        if n%i==0:
            return False
    return True
print([x for x in range(2,10) if is_prime(x)])
```

答案: [2, 3, 5, 7]

192

```
Plain
a = [1,2,3]
b = [4,5]
res = [x+y for x in a for y in b if x%2==1]
print(res)
```

答案: [5, 6, 7, 8]

193

```
Plain
x = 7
y = 2
x -= y * 3
print(x)
```

答案: 1

194

```
Plain
words = ["apple", "banana", "pear"]
print(max(words, key=len))
```

答案: banana

195

```
Plain
s = set()
s.add((1,2))
s.add([3,4])
print(len(s))
```

答案: 报错

196

```
Plain
def func(a,b):
    return a if a<b else b
print(func(func(3,9), func(5,2)))
```

答案: 2

197

```
Plain
lst = [0,1,2,3,4,5]
res = list(filter(lambda x:x%2==0, lst))
print(sum(res))
```

答案: 6

198

```
Plain
i = 0
res = 0
while i <= 10:
    res += i
    i += 2
print(res)
```

答案: 30

199

```
Plain
str_s = "abc123def456"
new_str = ''.join([c for c in str_s if c.isalpha()])
print(new_str * 2)
```

答案: abcdefabcdef

200

```
Plain
import numpy as np
```

```
arr1 = np.array([1,2,3])  
arr2 = np.array([4,5,6])  
print(arr1+arr2)
```

答案: [5 7 9]

In []: