Fachbereich 07 Informatik/Mathematik



Praktikum Datenbanksysteme II Wintersemester 2018/19

Prof. Dr. Martin Staudt

Übung 2

Wimmer, Anja IF8 Gabl, Daniel IF6

Inhaltsverzeichnis

INHALTSVERZEICHNIS	II
AUFGABEN	1
AUFGABE 1	
AUFGABE 2	
AUFGABE 3	
Aufgabe 4	4
Aufgabe 5 (Fallstudie)	6
SCREENDUMPS DER TABELLEN	17
ANMERKUNGEN	20

Aufgaben

Aufgabe 1

_

Aufgabe 2

Die zwei Möglichkeiten, die wir in Betracht ziehen:

- 1. Allmögliche Objekt-Typen definieren und gegenseitig referenzieren. Bspw. könnte die Adresse ein Typ sein, die sich aus der Straße und der Hausnummer (und ggf. PLZ und Ort) zusammensetzt. Auch könnte ein Kontotyp mit Konto-Nr., Kontostand, Art und ID der Zweigstelle ein eigenes Attribut sein. (Es ist keine Zuordnungstabelle erforderlich, da es sich bei Zweigstelle <-> Konto um eine 1:n-Beziehung handelt.)
- 2. Beispielsweiße könnten wir den Konto-Typ nicht als eigene Tabelle speichern sondern als innere Tabelle beim Zweigstellen-Typs speichern, dadurch entfällt die Referenz auf diese Tabelle.

Aufgabe 3

Wir würden folgendes Schema aufstellen: (Legende: 1. Möglichkeit, 2. Möglichkeit, beide)


5 Typen wie folgt:

- Adress-Typ mit Straße und Hausnummer (und ggf. PLZ und Ort)
- Kontolisten-Typ als Tabelle vom Typ Integer (Kontonummern)
- Kunden-Typ mit Kunden-Nr., -Name, Adress-Typ, Status **und Kontolisten-Typ**
- Kontoinhaber-Typ als Tabelle vom Kunden-Typ
- Zweigstellenkonten-Typ als Tabelle von Konto-Typen
- Zweigstellen-Typ mit Zweigstellenname, Adress-Typ, Leiter-Id und Zweigkonten
- Konto-Typ mit Konto-Nr., Kontostand, Art, Kontoinhaber-Typ und Zweigstellen-Typ

Dazu noch folgende Tabellen:

- Kunden-Tabelle mit Kunden-Typ
- Zweigstellen-Adresse mit Zweigstellen-Typ
- Konto-Tabelle mit Konto-Typ (entfällt bei der 2. Möglichkeit)

Eine Skizzierung des Zusammenspiels der Typen und Tabellen:



```
SQL-Statements zum Erzeugen der Typen und Tabellen (1. Möglichkeit):
CREATE TYPE AddressType AS Object(street VARCHAR(31), houseNr
VARCHAR(7), zip INT(5), place VARCHAR(31));
CREATE TYPE CustomerType AS Object (customerNr INT, customerName
VARCHAR (63), addr AddressType, status VARCHAR (15));
CREATE TYPE AccountOwnerType AS TABLE OF REF CustomerType;
CREATE TYPE BranchOfficeType AS Object(branchOfficeName VARCHAR(63),
addr AddressType, leaderId INT);
CREATE TYPE AccountType AS Object(accountNr INT,
balance DOUBLE PRECISION, kind VARCHAR(1),
owners AccountOwnerType, branchOffice REF BranchOfficeType);
CREATE TABLE Customer OF CustomerType;
CREATE TABLE BranchOffice OF BranchOfficeType;
CREATE TABLE AccountTable OF AccountType NESTED TABLE owners STORE
AS lorem ipsum;
SQL-Statements zum Einfügen von Beispieldatensätzen in die Datenbank (1. Möglichkeit):
INSERT INTO Customer VALUES (CustomerType (2345, 'H. Fach',
AddressType('Münchenerstr.', '33', 60329, 'Frankfurt am Main'),
'Geschäftskunde'));
INSERT INTO Customer VALUES (CustomerType (7654, 'B. Meier',
AddressType('Eschenweg', '12', 85354, 'Freising'), 'Privatkunde'));
INSERT INTO Customer VALUES (CustomerType (8764, 'J. Wiesner',
AddressType('Schellingstr.', '42', 80799, 'München'),
'Geschäftskunde'));
INSERT INTO BranchOffice VALUES (BranchOfficeType ('Bachdorf',
AddressType('Hochstr.', '1', 81669, 'München'), 1768));
INSERT INTO BranchOffice VALUES (BranchOfficeType ('Riedering',
AddressType('Simseestr.', '3', 81549, 'München'), 9823));
INSERT INTO AccountTable VALUES (AccountType (120768, 234.56, 'S',
AccountOwnerType((SELECT REF(c) FROM Customer c WHERE c.customerNr =
2345)), (SELECT REF(b) FROM BranchOffice b WHERE b.branchOfficeName =
'Bachdorf')));
INSERT INTO AccountTable VALUES (AccountType (678453, -456.78, 'G',
AccountOwnerType((SELECT REF(c) FROM Customer c WHERE c.customerNr =
8764)), (SELECT REF(b) FROM BranchOffice b WHERE b.branchOfficeName =
'Bachdorf')));
INSERT INTO AccountTable VALUES (AccountType (348973, 12567.56, 'G',
AccountOwnerType((SELECT REF(c) FROM Customer c WHERE c.customerNr =
2345), (SELECT REF(c) FROM Customer c WHERE c.customerNr = 8764)),
(SELECT REF(b) FROM BranchOffice b WHERE b.branchOfficeName =
'Bachdorf')));
INSERT INTO AccountTable VALUES (AccountType (987654, 789.65, 'G',
AccountOwnerType((SELECT REF(c) FROM Customer c WHERE c.customerNr =
7654)), (SELECT REF(b) FROM BranchOffice b WHERE b.branchOfficeName =
'Riedering')));
INSERT INTO AccountTable VALUES (AccountType (745363, -23.67, 'S',
AccountOwnerType((SELECT REF(c) FROM Customer c WHERE c.customerNr =
8764)), (SELECT REF(b) FROM BranchOffice b WHERE b.branchOfficeName =
'Riedering')));
```

```
SQL-Statements zum Erzeugen der Typen und Tabellen (2. Möglichkeit):
CREATE TYPE AddressType AS Object(street VARCHAR(31), houseNr
VARCHAR(7), zip INT(5), place VARCHAR(31));
CREATE TYPE AccountsT AS TABLE OF INT;
CREATE TYPE CustomerType AS Object (customerNr INT, customerName
VARCHAR(63), addr AddressType, status VARCHAR(15), accNr AccountsT);
CREATE TYPE AccountType AS Object (accountNr INT,
balance DOUBLE PRECISION, kind VARCHAR(1));
CREATE TYPE BranchAccountsType AS TABLE OF AccountType;
CREATE TYPE BranchOfficeType AS Object(branchOfficeName VARCHAR(63),
addr AddressType, leaderId INT, accounts BranchAccountsType);
CREATE TABLE Customer OF CustomerType
NESTED TABLE accNr STORE AS accNr useless;
CREATE TABLE BranchOffice OF BranchOfficeType
NESTED TABLE accounts STORE AS accounts useless;
SQL-Statements zum Einfügen von Beispieldatensätzen in die Datenbank (2. Möglichkeit):
INSERT INTO Customer
VALUES (CustomerType (2345, 'H. Fach',
AddressType('Münchenerstr.', '33', 60329, 'Frankfurt am Main'),
'Geschäftskunde', AccountsT(120768, 348973)));
INSERT INTO Customer
VALUES (CustomerType (7654, 'B. Meier',
AddressType('Eschenweg', '12', 85354, 'Freising'), 'Privatkunde',
AccountsT(987654)));
INSERT INTO Customer
VALUES (CustomerType (8764, 'J. Wiesner',
AddressType('Schellingstr.', '42', 80799, 'München'), 'Geschäftskunde',
AccountsT(745363, 678453, 348973)));
INSERT INTO BranchOffice
VALUES (BranchOfficeType ('Bachdorf', AddressType ('Hochstr.', '1', 81669,
'München'), 1768, BranchAccountsType()));
INSERT INTO TABLE (SELECT accounts FROM BranchOffice WHERE
branchOfficeName='Bachdorf')
VALUES (AccountType (120768, 234.56, 'S'));
INSERT INTO TABLE (SELECT accounts FROM BranchOffice WHERE
branchOfficeName='Bachdorf')
VALUES (AccountType (678453, -456.78, 'G'));
INSERT INTO TABLE (SELECT accounts FROM BranchOffice WHERE
branchOfficeName='Bachdorf')
VALUES (AccountType (348973, 12567.56, 'G'));
INSERT INTO BranchOffice
VALUES (BranchOfficeType ('Riedering', AddressType ('Simseestr.', '3',
81549, 'München'), 9823, BranchAccountsType()));
INSERT INTO TABLE (SELECT accounts FROM BranchOffice WHERE
branchOfficeName='Riedering')
VALUES (AccountType (987654, 789.65, 'G'));
INSERT INTO TABLE (SELECT accounts FROM BranchOffice WHERE
branchOfficeName='Riedering')
VALUES (AccountType (745363, -23.67, 'S'));
```

Aufgabe 4

Bei der 1. Möglichkeit:

- b) SELECT a.accountNr, DEREF(o.COLUMN_VALUE).customerName AS customerName, CONCAT(CONCAT(DEREF(o.COLUMN_VALUE).addr.street, '
 '), DEREF(o.COLUMN_VALUE).addr.houseNr) as addr FROM AccountTable a, TABLE(a.owners) o;

Bei der 2. Möglichkeit:

- a) SELECT a.accountNr, a.balance, a.kind, CONCAT(CONCAT(b.addr.street, ' '), b.addr.houseNr) AS addr FROM BranchOffice b, TABLE(b.accounts) a;
- b) SELECT a.COLUMN_VALUE, CONCAT(CONCAT(c.addr.street, ' '),c.addr.houseNr) AS addr FROM Customer c, TABLE(c.accNr) a;

Screendumps

Hier Screendumps unserer Tabellen und den Ergebnissen aus Aufgabe 4.

1. Möglichkeit:

Screendump von Aufgabe 4a) (Kontonummer, -stand, -art und Adresse der Zweigstelle):

		BALANCE	∜ KIND	
1	120768	234,56	S	Hochstr. 1
2	678453	-456,78	G	Hochstr. 1
3	348973	12567,56	G	Hochstr. 1
4	987654	789,65	G	Simseestr. 3
5	745363	-23,67	S	Simseestr. 3

Screendump von Aufgabe 4b) (Paare von Kontonummern, Namen und Adressen der Inhaber):

		⊕ C	USTOMERNAME		
1	120768	Н.	Fach	Münchenerstr.	33
2	678453	J.	Wiesner	Schellingstr.	42
3	348973	Н.	Fach	Münchenerstr.	33
4	348973	J.	Wiesner	Schellingstr.	42
5	987654	в.	Meier	Eschenweg 12	
6	745363	J.	Wiesner	Schellingstr.	42

Zweigstellen-Tabelle:

	♦ BRANCHOFFICENAME	ADDR	
1	Bachdorf	[DBST42.ADDRESSTYPE]	1768
2	Riedering	[DBST42.ADDRESSTYPE]	9823

Kunden-Tabelle:

			ADDR	
1	2345	H. Fach	[DBST42.ADDRESSTYPE]	Geschäftskunde
2	7654	B. Meier	[DBST42.ADDRESSTYPE]	Privatkunde
3	8764	J. Wiesner	[DBST42.ADDRESSTYPE]	Geschäftskunde

Konten-Tabelle:

			∜ KIND	OWNERS	BRANCHOFFICE
1	120768	234,56	S	DBST42.ACCOUNTOWNERTYPE([DBST42.CUSTOMERTYPE])	[DBST42.BRANCHOFFICETYPE]
2	678453	-456,78	G	DBST42.ACCOUNTOWNERTYPE([DBST42.CUSTOMERTYPE])	[DBST42.BRANCHOFFICETYPE]
3	348973	12567,56	G	DBST42.ACCOUNTOWNERTYPE([DBST42.CUSTOMERTYPE],[DBST42.CUSTOMERTYPE])	[DBST42.BRANCHOFFICETYPE]
4	987654	789,65	G	DBST42.ACCOUNTOWNERTYPE([DBST42.CUSTOMERTYPE])	[DBST42.BRANCHOFFICETYPE]
5	745363	-23,67	S	DBST42.ACCOUNTOWNERTYPE([DBST42.CUSTOMERTYPE])	[DBST42.BRANCHOFFICETYPE]

2. Möglichkeit:

Screendump von Aufgabe 4a)

	1			
		BALANCE	∯ KIND	
1	120768	234,56	S	Hochstr. 1
2	678453	-456,78	G	Hochstr. 1
3	348973	12567,56	G	Hochstr. 1
4	987654	789,65	G	Simseestr. 3
5	745363	-23,67	S	Simseestr. 3

Screendump von Aufgabe 4b)

		,	
	COLUMN_VALUE		
1	120768	Münchenerstr.	33
2	348973	Münchenerstr.	33
3	987654	Eschenweg 12	
4	745363	Schellingstr.	42
5	678453	Schellingstr.	42
6	348973	Schellingstr.	42

Zweigstellen-Tabelle:

	BRANCHOFFICENAME	ADDR		ACCOUNTS
1	Bachdorf	[DBST42.ADDRESSTYPE]	1768	DBST42.BRANCHACCOUNTSTYPE([DBST42.ACCOUNTTYPE],[DBST42.ACCOUNTTYPE],[DBST42.ACCOUNTTYPE])
2	Riedering	[DBST42.ADDRESSTYPE]	9823	DBST42.BRANCHACCOUNTSTYPE([DBST42.ACCOUNTTYPE],[DBST42.ACCOUNTTYPE])

Kunden-Tabelle:

			ADDR		ACCNR
1	2345	H. Fach	[DBST42.ADDRESSTYPE]	Geschäftskunde	DBST42.ACCOUNTST(120768,348973)
2	7654	B. Meier	[DBST42.ADDRESSTYPE]	Privatkunde	DBST42.ACCOUNTST(987654)
3	8764	J. Wiesner	[DBST42.ADDRESSTYPE]	Geschäftskunde	DBST42.ACCOUNTST(745363,678453,348973)

Aufgabe 5 (Fallstudie)

Zuerst haben wir für die Fallstudie die Aufgabenstellung analysiert und angefangen, Typen zu definieren um die Tabellen vollständig korrekt zu speichern.

Hierfür haben wir 30 Typen (Normale und List-Typen) angelegt, die wie folgt aussehen:

```
CREATE TYPE CampusT AS OBJECT (campus location VARCHAR(15),
campus addr VARCHAR(127), campus phone VARCHAR(15), campus fax
VARCHAR(15), campus head VARCHAR(31));
CREATE TYPE ProfessorT AS OBJECT (prof id INTEGER, prof name
VARCHAR(31), prof contact VARCHAR(31), prof research
VARCHAR (63), prof year INTEGER);
CREATE TYPE ProfessorListT AS TABLE OF REF ProfessorT;
CREATE TYPE DepartmentT AS OBJECT (dept id VARCHAR(3),
dept name VARCHAR(31), dept head VARCHAR(31), dept prof
ProfessorListT);
CREATE TYPE DepartmentListT AS TABLE OF DepartmentT;
CREATE TYPE SchoolT AS OBJECT (school id VARCHAR(3),
school name VARCHAR (31), school head VARCHAR (31), school prof
ProfessorListT);
/
CREATE TYPE SchoolListT AS TABLE OF SchoolT;
CREATE TYPE RCUnitT AS TABLE OF VARCHAR (127);
CREATE TYPE ResearchCentreT AS OBJECT (rc id VARCHAR(3),
rc name VARCHAR(127), rc head VARCHAR(31), rc unit RCUnitT);
CREATE TYPE ResearchCentreListT AS TABLE OF ResearchCentreT;
-- TODO aggregation clustering technique
CREATE TYPE FacultyT AS OBJECT (fac id INTEGER, fac name
VARCHAR(31), fac dean VARCHAR(15), dept DepartmentListT,
school SchoolListT, rc ResearchCentreListT);
CREATE TYPE BuildingT AS OBJECT (bld id VARCHAR(4), bld name
VARCHAR (31), bld location VARCHAR (2), bld level INTEGER,
campus REF CampusT, fac REF FacultyT, MEMBER PROCEDURE
show bld details));
CREATE TYPE PersonT AS OBJECT (person id VARCHAR(8),
person surname VARCHAR(15), person forename VARCHAR(15),
person_title VARCHAR(7), person addr VARCHAR(127),
person phone VARCHAR(15), person postcode VARCHAR(5), campus
REF CampusT) NOT FINAL;
```

```
CREATE TYPE OfficeT AS OBJECT (office No VARCHAR(7), bld REF
BuildingT, office phone VARCHAR(15));
CREATE TYPE ClassroomT AS OBJECT (class no VARCHAR(4), bld REF
BuildingT, class capacity INTEGER);
CREATE TYPE LabEquipmentT AS TABLE OF VARCHAR(15);
CREATE TYPE LabT AS OBJECT (lab no VARCHAR(5), bld REF
BuildingT, lab capacity INTEGER, lab equipment LabEquipmentT);
CREATE TYPE DegreeT AS OBJECT (deg id VARCHAR(4), deg name
VARCHAR (31), deg length INTEGER, deg prereg VARCHAR (31), fac
REF FacultyT);
CREATE TYPE ComputerskillsT AS TABLE OF VARCHAR (15);
CREATE TYPE OfficeskillsT AS TABLE OF VARCHAR(31);
CREATE TYPE TechnicianskillsT AS TABLE OF VARCHAR (15);
CREATE TYPE StaffT UNDER PersonT (office No VARCHAR(7),
staff type VARCHAR(15)) NOT FINAL;
CREATE TYPE StudentT UNDER PersonT (student year INTEGER,
MEMBER PROCEDURE insert student, MEMBER PROCEDURE
delete student);
CREATE TYPE AdminT UNDER StaffT (admin title VARCHAR (31),
admin computerskills ComputerskillsT, admin officeskills
OfficeskillsT);
CREATE TYPE TechnicianT UNDER StaffT (tech title VARCHAR(31),
tech skills TechnicianskillsT);
CREATE TYPE TutorT UNDER StaffT (tutor hours INTEGER,
tutor rate DOUBLE PRECISION);
CREATE TYPE LecturerT UNDER StaffT (lect area VARCHAR(31),
lect type VARCHAR (15)) NOT FINAL;
CREATE TYPE SeniorLecturerT UNDER LecturerT (senlect phd
INTEGER, senlect master INTEGER, senlect honours INTEGER);
CREATE TYPE AssociateLecturerT UNDER LecturerT
(asslect honours INTEGER, asslect year INTEGER);
CREATE TYPE SubjectT AS OBJECT (subject id VARCHAR(8),
subject name VARCHAR(31), subject credit INTEGER,
subject prereq VARCHAR(8), person REF PersonT);
```

Dazu haben wir noch folgende 20 Tabellen angelegt, um konkrete Exemplare zu speichern:

```
CREATE TABLE Campus OF CampusT;
CREATE TABLE Professor OF ProfessorT;
CREATE TABLE Faculty OF FacultyT
    NESTED TABLE dept STORE AS department nm (NESTED TABLE
dept prof STORE AS dept prof nm)
    NESTED TABLE school STORE AS school nm(NESTED TABLE
school prof STORE AS school prof nm)
    NESTED TABLE rc STORE AS rc nm (NESTED TABLE rc unit STORE
AS rc unit nm);
CREATE TABLE Building OF BuildingT;
CREATE TABLE Person OF PersonT;
CREATE TABLE Office OF OfficeT;
CREATE TABLE Classroom OF ClassroomT;
CREATE TABLE Lab OF LabT
    NESTED TABLE lab equipment STORE AS lab equip nm;
CREATE TABLE DegreeTbl OF DegreeT;
CREATE TABLE Staff OF StaffT;
CREATE TABLE Student OF StudentT;
CREATE TABLE AdminTbl OF AdminT
    NESTED TABLE admin computerskills STORE AS adm comskill nm
    NESTED TABLE admin officeskills STORE AS adm offskill nm;
CREATE TABLE Technician OF TechnicianT
    NESTED TABLE tech skills STORE AS tech skill nm;
CREATE TABLE Tutor OF TutorT;
CREATE TABLE Lecturer OF LecturerT;
CREATE TABLE SeniorLecturer OF SeniorLecturerT;
CREATE TABLE AssociateLecturer OF AssociateLecturerT;
CREATE TABLE Subject OF SubjectT;
CREATE TABLE Enrolls in (student REF StudentT, deg REF
DegreeT);
CREATE TABLE Takes (student REF StudentT, subject REF
SubjectT, mark INTEGER);
```

Dazu haben wir noch die im Diagramm eingezeichneten Funktionen wir folgt implementiert:

```
CREATE OR REPLACE FUNCTION show bld details (in bld id IN
VARCHAR2)
   RETURN VARCHAR2
   IS building details VARCHAR2 (255);
BEGIN
SELECT 'ID: '|| building.bld id ||', Name: '|| building.bld name
||', Location: '|| building.bld location ||', Level: '||
building.bld level ||', Campus: '||
DEREF (building.campus).campus location | | ', Faculty:
'||DEREF(building.fac).fac name
  INTO building details
  FROM Building building
  WHERE building.bld id = in bld id;
  RETURN (building details);
END show bld details;
-- SELECT show bld details('BB1') AS "Building Info" FROM DUAL;
-- not working correctly, declaration would be needed
CREATE OR REPLACE FUNCTION insert student (in person id IN
VARCHAR2, in year IN NUMBER)
   RETURN VARCHAR2
   IS success state VARCHAR2(5); -- boolean type not supported
BEGIN
INSERT INTO Student (
  SELECT pers.*, in year FROM Person pers
  WHERE pers.person id = in person id
);
success state := 'TRUE';
RETURN (success state);
END insert student;
CREATE OR REPLACE FUNCTION delete student(in person id IN
VARCHAR2)
   RETURN VARCHAR2
   IS success state VARCHAR2(5); -- boolean type not supported
BEGIN
DELETE FROM Student student WHERE student.person id =
in person id;
success state := 'TRUE';
RETURN (success state);
END delete student;
```

Schlussendlich haben wir mittels folgenden Insert-Statements Daten in die Tabellen angelegt:

```
INSERT INTO Campus
VALUES (CampusT('Albury/Wodonga', 'Parkers Road Wodonga VIC
3690',
          '61260583700', '620260583777', 'John Hill'));
INSERT INTO Campus
VALUES (CampusT('City', '215 Franklin St. Melb VIC 3000',
          '61392855100', '610392855111', 'Michael A.
0''Leary'));
INSERT INTO Campus
VALUES (CampusT('Mildura', 'Benetook Ave. Mildura VIC 3502',
          '61350223757', '61350223646', 'Ron Broadhead'));
INSERT INTO Campus
VALUES (CampusT('Bundoora', '221b Baker St. London NW1',
          '6195135755', '6137196482', 'Sherlock Holmes'));
INSERT INTO Faculty
VALUES (FacultyT(1, 'Health Science', 'S. Duckett',
          DepartmentListT(), SchoolListT(),
ResearchCentreListT());
INSERT INTO Faculty
VALUES (FacultyT(2, 'Humanity '||'&'||' Social Sc.', 'J. A.
Salmond',
          DepartmentListT(), SchoolListT(),
ResearchCentreListT());
INSERT INTO Faculty
VALUES (FacultyT(3, 'Law '||'&'||' Management', 'G. C.
O''Brien',
          DepartmentListT(), SchoolListT(),
ResearchCentreListT());
INSERT INTO Faculty
VALUES (FacultyT(4, 'Science, Tech. '||'&'||' Eng.', 'D.
Finlay',
          DepartmentListT(), SchoolListT(),
ResearchCentreListT());
INSERT INTO Faculty
VALUES (FacultyT(5, 'Regional Department', 'L. Kilmartin',
          DepartmentListT(), SchoolListT(),
ResearchCentreListT());
INSERT INTO Professor VALUES (ProfessorT (42, 'Nick
Hoogenraad', 'hoogenraad@cu.edu', 'Advanced Software
Engineering', 2007));
INSERT INTO Professor VALUES (ProfessorT(88, 'Robin Anders',
'robin.anders@cu.edu', 'Computer Architecture', 2017));
INSERT INTO Professor VALUES (ProfessorT(101, 'Claude
Bernard', 'cbernard@cu.edu', 'Networking', 2016));
INSERT INTO Professor VALUES (ProfessorT (420, 'Bruce Stone',
'b.stone@cu.edu', 'Software Development', 2015));
INSERT INTO Professor VALUES (ProfessorT(555, 'Chris Handley',
'handley@cu.edu', 'Compiler', 2009));
```

```
INSERT INTO Professor VALUES (ProfessorT(782, 'Sheena Reilly',
'sheenareilly@cu.edu', 'Discrete Mathematics', 2005));
INSERT INTO Professor VALUES (ProfessorT(1001, 'Alison Perry',
'Alison.Perry@cu.edu', 'Physics', 2012));
INSERT INTO Professor VALUES (ProfessorT(1337, 'Jan Branson',
'branson@cu.edu', 'Software Architecture', 2018));
INSERT INTO TABLE (SELECT dept FROM Faculty WHERE fac id=4)
VALUES (DepartmentT ('4-1', 'Agricultural Sciences', 'Mark
Sandeman',
          ProfessorListT());
INSERT INTO TABLE (SELECT dept FROM Faculty WHERE fac id=4)
VALUES (DepartmentT ('4-2', 'Biochemistry', 'Nick Hoogenraad',
          ProfessorListT()));
INSERT INTO TABLE (SELECT school FROM Faculty WHERE fac id=1)
VALUES (SchoolT ('1-1', 'Human Biosciences', 'Chris Handley',
          ProfessorListT((SELECT REF(p) FROM Professor p WHERE
p.prof id=555))));
INSERT INTO TABLE (SELECT school FROM Faculty WHERE fac id=1)
VALUES (SchoolT('1-2', 'Human Comm. Sciences', 'Elizabeth
Lavender',
          ProfessorListT()));
INSERT INTO TABLE (SELECT rc FROM Faculty WHERE fac id=1)
VALUES(ResearchCentreT('1-1', 'Australian Research Centre in
Sex, Health '||'&'||' Society', 'Martin Pitts', RCUnitT()));
INSERT INTO TABLE (SELECT rc FROM Faculty WHERE fac id=1)
VALUES (ResearchCentreT ('1-2', 'Australian Institute for
Primary Care', 'Hal Swerissen', RCUnitT()));
INSERT INTO TABLE (SELECT dept prof FROM TABLE (SELECT dept FROM
Faculty WHERE fac id=4) dep WHERE dep.dept id = '4-2') (SELECT
REF(p) FROM Professor p WHERE p.prof id=42 OR p.prof id=88 OR
p.prof id=101 OR p.prof id=420);
INSERT INTO TABLE (SELECT school prof FROM TABLE (SELECT school
FROM Faculty WHERE fac id=1) scho WHERE scho.school id = '1-
2') (SELECT REF(p) FROM Professor p WHERE p.prof id=782 OR
p.prof id=1001 OR p.prof id=1337);
INSERT INTO TABLE (SELECT rc unit FROM TABLE (SELECT rc FROM
Faculty WHERE fac id=1) r WHERE r.rc id='1-1')
VALUES('SSAY Projects');
INSERT INTO TABLE (SELECT rc unit FROM TABLE (SELECT rc FROM
Faculty WHERE fac id=1) r WHERE r.rc id='1-1')
VALUES('HIV Futures');
INSERT INTO TABLE (SELECT rc unit FROM TABLE (SELECT rc FROM
Faculty WHERE fac id=1) r WHERE r.rc id='1-1')
VALUES ('Australian Study of Health and Relationships');
```

```
INSERT INTO TABLE (SELECT rc unit FROM TABLE (SELECT rc FROM
Faculty WHERE fac id=1) r WHERE r.rc id='1-2')
VALUES ('Centre for Dev. and Innovation in Health');
INSERT INTO TABLE (SELECT rc unit FROM TABLE (SELECT rc FROM
Faculty WHERE fac id=1) r WHERE r.rc id='1-2')
VALUES ('Centre for Quality in Health '||'&'||' Community
Svc.');
INSERT INTO TABLE (SELECT rc unit FROM TABLE (SELECT rc FROM
Faculty WHERE fac id=1) r WHERE r.rc id='1-2')
VALUES('Lincoln Gerontology Centre');
INSERT INTO Building
VALUES (BuildingT('BB1', 'Beth Gleeson', 'D5', 4,
          (SELECT REF(c) FROM Campus c WHERE
c.campus location='Bundoora'),
          (SELECT REF(f) FROM Faculty f WHERE f.fac id=4)));
INSERT INTO Building
VALUES (BuildingT('BB2', 'Martin Building', 'F5', 4,
          (SELECT REF(c) FROM Campus c WHERE
c.campus location='Bundoora'),
          (SELECT REF(f) FROM Faculty f WHERE f.fac id=3)));
INSERT INTO Building
VALUES (BuildingT('BB3', 'Thomas Cherry', 'D4', 4,
          (SELECT REF(c) FROM Campus c WHERE
c.campus location='Bundoora'),
          (SELECT REF(f) FROM Faculty f WHERE f.fac id=1)));
INSERT INTO Building
VALUES (BuildingT('BB4', 'Physical Science 1', 'D5', 3,
          (SELECT REF(c) FROM Campus c WHERE
c.campus location='Bundoora'),
          (SELECT REF(f) FROM Faculty f WHERE f.fac id=4)));
INSERT INTO Office
VALUES (OfficeT('BG207',
          (SELECT REF(b) FROM Building b WHERE
b.bld id='BB4'),
          '94791118'));
INSERT INTO Office
VALUES (OfficeT('BG208',
          (SELECT REF(b) FROM Building b WHERE
b.bld id='BB4'),
          '94792393'));
INSERT INTO Classroom
VALUES (ClassroomT('TCLT',
          (SELECT REF(b) FROM Building b WHERE
b.bld id='BB3'),
          50));
INSERT INTO Classroom
VALUES (ClassroomT('TC01',
          (SELECT REF(b) FROM Building b WHERE
b.bld id='BB3'),
          30));
```

```
INSERT INTO Lab
VALUES (LabT('BG113',
          (SELECT REF(b) FROM Building b WHERE
b.bld id='BB1'),
          25, LabEquipmentT('25 PC', '1 Printer')));
INSERT INTO Lab
VALUES (LabT('BG114',
          (SELECT REF(b) FROM Building b WHERE
b.bld id='BB1'),
          20, LabEquipmentT('21 PC')));
INSERT INTO DegreeTbl
VALUES (DegreeT('D100', 'Bachelor of Comp. Sci', 3, 'Year 12
or equivalent',
          (SELECT REF(f) FROM Faculty f WHERE f.fac id=4)));
INSERT INTO DegreeTbl
VALUES (DegreeT('D101', 'Master of Comp. Sci', 2, 'Bachelor of
Comp. Sci',
          (SELECT REF(f) FROM Faculty f WHERE f.fac id=4)));
INSERT INTO Person
VALUES (PersonT('01234234', 'Grant', 'Felix', 'Mr', '2 Boadle
Rd Bundoora VIC', '0398548753', '3083',
          (SELECT REF(c) FROM Campus c WHERE
c.campus location='Bundoora')));
INSERT INTO Person
VALUES (PersonT('10008895', 'Xin', 'Harry', 'Mr', '6 Kelley St
Kew VIC',
          '0398875542', '3088',
          (SELECT REF(c) FROM Campus c WHERE
c.campus location='Bundoora')));
INSERT INTO Person
VALUES (PersonT('10002935', 'Jones', 'Felicity', 'Ms', '14
Rennie St Thornbury VIC', '0398722001', '3071',
          (SELECT REF(c) FROM Campus c WHERE
c.campus location='Bundoora')));
-- additional People needed for Staff
INSERT INTO Person
VALUES (PersonT('01958652', 'Doe', 'John', 'Mr', '64 Austin St
Holow VIC', '0321343123', '1337',
          (SELECT REF(c) FROM Campus c WHERE
c.campus location='City')));
INSERT INTO Person
VALUES (PersonT('10008957', 'Jane', 'Patrick', 'Mr', '23
Rainbow Rd Allumy VIC', '0236263636', '3033',
          (SELECT REF(c) FROM Campus c WHERE
c.campus location='City')));
INSERT INTO Person
VALUES (PersonT('10005825', 'Gibbs', 'Lewroy', 'Mr', '127
Moltres Way Jotho VIC', '0285624733', '3042',
          (SELECT REF(c) FROM Campus c WHERE
c.campus location='Mildura')));
```

```
INSERT INTO Person
VALUES (PersonT('10015826', 'Beckett', 'Kate', 'Ms', '42
Donestry St Jibisy VIC', '0263957394', '3087',
          (SELECT REF(c) FROM Campus c WHERE
c.campus location='Mildura')));
INSERT INTO Person
VALUES (PersonT('10000255', 'Morgan', 'Henry', 'Mr', '2 London
Ave Karrigan VIC', '0395182649', '3062',
          (SELECT REF(c) FROM Campus c WHERE
c.campus location='City')));
INSERT INTO Person
VALUES (PersonT('10000258', 'Flow', 'Max', 'Mr', '26 Hollow
Tips St Precidense VIC', '0492849184', '3012',
          (SELECT REF(c) FROM Campus c WHERE
c.campus location='Mildura')));
INSERT INTO Person
VALUES (PersonT('10006935', 'Gunn', 'Montgomery', 'Mr', '65
Arrow Ave Catery VIC', '0492847294', '3085',
          (SELECT REF(c) FROM Campus c WHERE
c.campus location='Mildura')));
INSERT INTO Person
VALUES (PersonT('10012568', 'Shields', 'Duncan', 'Mr', '13
Flame St Seaside VIC', '0195837592', '3037',
          (SELECT REF(c) FROM Campus c WHERE
c.campus location='City')));
-- additional Staff over
INSERT INTO Staff (SELECT pers.*, 'BG212', 'Lecturer' FROM
Person pers WHERE pers.person id = 10008895);
INSERT INTO Staff (SELECT pers.*, 'BG210', 'Admin' FROM Person
pers WHERE pers.person id = 10002935);
-- additional Staff needed for Subtypes
INSERT INTO Staff (SELECT pers.*, 'BG221', 'Admin' FROM Person
pers WHERE pers.person id = 10008957);
INSERT INTO Staff (SELECT pers.*, 'BG231', 'Technician' FROM
Person pers WHERE pers.person id = 10005825);
INSERT INTO Staff (SELECT pers.*, 'BG232', 'Technician' FROM
Person pers WHERE pers.person id = 10015826);
INSERT INTO Staff (SELECT pers.*, 'BG225', 'Lecturer' FROM
Person pers WHERE pers.person id = 10000255);
INSERT INTO Staff (SELECT pers.*, 'BG226', 'Lecturer' FROM
Person pers WHERE pers.person id = 10000258);
INSERT INTO Staff (SELECT pers.*, 'BG225', 'Lecturer' FROM
Person pers WHERE pers.person id = 10006935);
INSERT INTO Staff (SELECT pers.*, 'BG265', 'Tutor' FROM Person
pers WHERE pers.person id = 01234234);
INSERT INTO Staff (SELECT pers.*, 'BG265', 'Tutor' FROM Person
pers WHERE pers.person id = 01958652);
-- additional Subtypes over
```

```
INSERT INTO Student (SELECT pers.*, 2000 FROM Person pers
WHERE pers.person id = 01234234);
INSERT INTO Student (SELECT pers.*, 2000 FROM Person pers
WHERE pers.person id = 01958652);
-- additional Student needed for Enrolls in / Takes
INSERT INTO Student (SELECT pers.*, 1995 FROM Person pers
WHERE pers.person id = 10012568);
-- additional Students over
INSERT INTO AdminTbl (SELECT staff.*, 'Office Manager',
ComputerskillsT(), OfficeskillsT() FROM Staff staff WHERE
staff.person id = 10002935);
INSERT INTO AdminTbl (SELECT staff.*, 'Receptionist',
ComputerskillsT(), OfficeskillsT() FROM Staff staff WHERE
staff.person id = 10008957);
INSERT INTO TABLE (SELECT admin officeskills FROM AdminTbl
WHERE person id = '10002935')
VALUES('Managerial');
INSERT INTO TABLE (SELECT admin computerskills FROM AdminTbl
WHERE person id = '10008957')
VALUES('MS Office');
INSERT INTO TABLE (SELECT admin officeskills FROM AdminTbl
WHERE person id = '10008957')
VALUES('Customer Service');
INSERT INTO TABLE (SELECT admin officeskills FROM AdminTbl
WHERE person id = '10008957')
VALUES('Phone');
INSERT INTO Technician (SELECT staff.*, 'Network Officer',
TechnicianskillsT() FROM Staff staff WHERE staff.person id =
10005825);
INSERT INTO Technician (SELECT staff.*, 'Photocopy
Technician', TechnicianskillsT() FROM Staff staff WHERE
staff.person id = 10015826);
INSERT INTO TABLE (SELECT tech skills FROM Technician WHERE
person id = '10005825')
VALUES('UNIX');
INSERT INTO TABLE (SELECT tech skills FROM Technician WHERE
person id = '10005825')
VALUES('NT');
INSERT INTO TABLE (SELECT tech skills FROM Technician WHERE
person id = '10015826')
VALUES('Electrician');
INSERT INTO Lecturer (SELECT staff.*, 'Software Engineering',
'Associate' FROM Staff staff WHERE staff.person id =
10008895);
INSERT INTO Lecturer (SELECT staff.*, 'Business Information',
'Senior' FROM Staff staff WHERE staff.person id = 10000255);
-- additional Lecturers needed for Sub-Lecturers
```

```
INSERT INTO Lecturer (SELECT staff.*, 'Business
Administration', 'Senior' FROM Staff staff WHERE
staff.person id = 10000258);
INSERT INTO Lecturer (SELECT staff.*, 'Software Development',
'Associate' FROM Staff staff WHERE staff.person id =
10006935);
-- additional Sub-Lecturers over
INSERT INTO SeniorLecturer (SELECT lec.*, 2, 5, 7 FROM
Lecturer lec WHERE lec.person id = 10000255);
INSERT INTO SeniorLecturer (SELECT lec.*, NULL, 1, 5 FROM
Lecturer lec WHERE lec.person id = 10000258);
INSERT INTO AssociateLecturer (SELECT lec.*, 2, 1999 FROM
Lecturer lec WHERE lec.person id = 10008895);
INSERT INTO AssociateLecturer (SELECT lec.*, NULL, 2001 FROM
Lecturer lec WHERE lec.person id = 10006935);
INSERT INTO Tutor (SELECT staff.*, 10, 20.00 FROM Staff staff
WHERE staff.person id = 01234234);
INSERT INTO Tutor (SELECT staff.*, 30, 35.00 FROM Staff staff
WHERE staff.person id = 01958652);
INSERT INTO Subject
VALUES (SubjectT('CSE21NET', 'Networking', 10, 'CSE11IS',
          (SELECT REF(p) FROM Person p WHERE
p.person id='10008895')));
INSERT INTO Subject
VALUES (SubjectT('CSE42ADB', 'Advanced Database', 15,
'CSE21DB',
          (SELECT REF(p) FROM Person p WHERE
p.person id='10006935')));
INSERT INTO Enrolls in VALUES ((SELECT REF(s) FROM Student s
WHERE s.person id='01234234'), (SELECT REF(d) FROM DegreeTbl d
WHERE d.deg id='D101'));
INSERT INTO Enrolls in VALUES ((SELECT REF(s) FROM Student s
WHERE s.person id='10012568'), (SELECT REF(d) FROM DegreeTbl d
WHERE d.deg id='D101'));
INSERT INTO Takes VALUES ((SELECT REF(s) FROM Student s WHERE
s.person_id='01234234'), (SELECT REF(s) FROM Subject s WHERE
s.subject id='CSE42ADB'), 70);
INSERT INTO Takes VALUES ((SELECT REF(st) FROM Student st
WHERE st.person id='10012568'), (SELECT REF(su) FROM Subject
su WHERE su.subject id='CSE42ADB'), 80);
```

Bitte verzeihen Sie das fehlende Syntax-Highlighting, wir machen dies immer von Hand.

Screendumps der Tabellen

Campus-Table:

	CAMPUS_ADDR	CAMPUS_PHONE	CAMPUS_HEAD
1 Albury/Wodonga	Parkers Road Wodonga VIC 3690	61260583700 620260583777	John Hill
2 City	215 Franklin St. Melb VIC 3000	61392855100 610392855111	Michael A. O'Leary
3 Mildura	Benetook Ave. Mildura VIC 3502	61350223757 61350223646	Ron Broadhead
4 Bundoora	221b Baker St. London NW1	6195135755 6137196482	Sherlock Holmes

Professor-Table:

				PROF_RESEARCH	
1	42	Nick Hoogenraad	hoogenraad@cu.edu	Advanced Software Engineering	2007
2	88	Robin Anders	robin.anders@cu.edu	Computer Architecture	2017
3	101	Claude Bernard	cbernard@cu.edu	Networking	2016
4	420	Bruce Stone	b.stone@cu.edu	Software Development	2015
5	555	Chris Handley	handley@cu.edu	Compiler	2009
6	782	Sheena Reilly	sheenareilly@cu.edu	Discrete Mathematics	2005
7	1001	Alison Perry	Alison.Perry@cu.edu	Physics	2012
8	1337	Jan Branson	branson@cu.edu	Software Architecture	2018

Faculty-Table:

<u> </u>	ity ruoic.		
	∯ FAC_ID ∯ FAC_NAME		DEPT
1	1 Health Science	S. Duckett	DBST42.DEPARTMENTLISTT()
2	2 Humanity & Social Sc.	J. A. Salmond	DBST42.DEPARTMENTLISTT()
3	3 Law & Management	G. C. O'Brien	DBST42.DEPARTMENTLISTT()
4	4 Science, Tech. & Eng.	D. Finlay	DBST42.DEPARTMENTLISTT([DBST42.DEPARTMENTT],[DBST42.DEPARTMENTT])
5	5 Regional Department	L. Kilmartin	DBST42.DEPARTMENTLISTT()
SCHOOL			RC
DBST4	2.SCHOOLLISTT([DBST42.SCHOOLT],[DBST42.SCHOOLT])	DBST42.RESEARCHCENTRELISTT([DBST42.RESEARCHCENTRET],[DBST42.RESEARCHCENTRET])
DBST4	2.SCHOOLLISTT()		DBST42.RESEARCHCENTRELISTT()

Building-Table:

	BLD_ID	BLD_NAME		BLD_LEVEL	CAMPUS	FAC
1	BB1	Beth Gleeson	D5	4	[DBST42.CAMPUST]	[DBST42.FACULTYT]
2	BB2	Martin Building	F5	4	[DBST42.CAMPUST]	[DBST42.FACULTYT]
3	вв3	Thomas Cherry	D4	4	[DBST42.CAMPUST]	[DBST42.FACULTYT]
4	BB4	Physical Science 1	D5	3	[DBST42.CAMPUST]	[DBST42.FACULTYT]

Person-Table:

			PERSON_FORENAME	PERSON_TITLE	♦ PERSON_ADDR	PERSON_PHONE	₱ PERSON_POSTCODE	CAMPUS
1	01234234	Grant	Felix	Mr	2 Boadle Rd Bundoora VIC	0398548753	3083	[DBST42.CAMPUST]
2	10008895	Xin	Harry	Mr	6 Kelley St Kew VIC	0398875542	3088	[DBST42.CAMPUST]
3	10002935	Jones	Felicity	Ms	14 Rennie St Thornbury VIC	0398722001	3071	[DBST42.CAMPUST]
4	01958652	Doe	John	Mr	64 Austin St Holow VIC	0321343123	1337	[DBST42.CAMPUST]
5	10008957	Jane	Patrick	Mr	23 Rainbow Rd Allumy VIC	0236263636	3033	[DBST42.CAMPUST]
6	10005825	Gibbs	Lewroy	Mr	127 Moltres Way Jotho VIC	0285624733	3042	[DBST42.CAMPUST]
7	10015826	Beckett	Kate	Ms	42 Donestry St Jibisy VIC	0263957394	3087	[DBST42.CAMPUST]
8	10000255	Morgan	Henry	Mr	2 London Ave Karrigan VIC	0395182649	3062	[DBST42.CAMPUST]
9	10000258	Flow	Max	Mr	26 Hollow Tips St Precidense VIC	0492849184	3012	[DBST42.CAMPUST]
10	10006935	Gunn	Montgomery	Mr	65 Arrow Ave Catery VIC	0492847294	3085	[DBST42.CAMPUST]

Office-Table:

	♦ OFFICE_NO	BLD	♦ OFFICE_PHONE
1	BG207	[DBST42.BUILDINGT]	94791118
2	BG208	[DBST42.BUILDINGT]	94792393

Classroom-Table:

	CLASS_NO	BLD	
1	TCLT	[DBST42.BUILDINGT]	50
2	TC01	[DBST42.BUILDINGT]	30

Lab-Table:

∜ LAB	NO.	BLD	\$ LAB_CAPACITY	LAB_EQUIPMENT
1 BG1	13	[DBST42.BUILDINGT]	25	DBST42.LABEQUIPMENTT('25 PC','1 Printer')
2 BG1:	14	[DBST42.BUILDINGT]	20	DBST42.LABEQUIPMENTT('21 PC')

Degree-Table:

	♦ DEG_ID	DEG_NAME	DEG_LENGTH	FAC
1	D100	Bachelor of Comp. Sci	3 Year 12 or equivalent	[DBST42.FACULTYT]
2	D101	Master of Comp. Sci	2 Bachelor of Comp. Sci	[DBST42.FACULTYT]

Student-Table:

		♦ PERSON_SURNAME	♦ PERSON_FORENAME	PERSON_TITLE		PERSON_PHONE		CAMPUS	
1	01234234	Grant	Felix	Mr	2 Boadle Rd Bundoora VIC	0398548753	3083	[DBST42.CAMPUST]	2000
2	01958652	Doe	John	Mr	64 Austin St Holow VIC	0321343123	1337	[DBST42.CAMPUST]	2000
3	10012568	Shields	Duncan	Mr	13 Flame St Seaside VIC	0195837592	3037	[DBST42.CAMPUST]	1995

Staff-Table:

	PERSON_ID	PERSON_SURNAME	PERSON_FORENAME	PERSON_TITLE	₱ PERSON_ADDR	PERSON_PHONE	♦ PERSON_POSTCODE	CAMPUS	♦ OFFICE_NO	STAFF_TYPE
1	10008895	Xin	Harry	Mr	6 Kelley St Kew VIC	0398875542	3088	[DBST42.CAMPUST]	BG212	Lecturer
2	10002935	Jones	Felicity	Ms	14 Rennie St Thornbury VIC	0398722001	3071	[DBST42.CAMPUST]	BG210	Admin
3	10008957	Jane	Patrick	Mr	23 Rainbow Rd Allumy VIC	0236263636	3033	[DBST42.CAMPUST]	BG221	Admin
4	10005825	Gibbs	Lewroy	Mr	127 Moltres Way Jotho VIC	0285624733	3042	[DBST42.CAMPUST]	BG231	Technicia
5	10015826	Beckett	Kate	Ms	42 Donestry St Jibisy VIC	0263957394	3087	[DBST42.CAMPUST]	BG232	Technicia
6	10000255	Morgan	Henry	Mr	2 London Ave Karrigan VIC	0395182649	3062	[DBST42.CAMPUST]	BG225	Lecturer
7	10000258	Flow	Max	Mr	26 Hollow Tips St Precidense VIC	0492849184	3012	[DBST42.CAMPUST]	BG226	Lecturer
8	10006935	Gunn	Montgomery	Mr	65 Arrow Ave Catery VIC	0492847294	3085	[DBST42.CAMPUST]	BG225	Lecturer
9	01234234	Grant	Felix	Mr	2 Boadle Rd Bundoora VIC	0398548753	3083	[DBST42.CAMPUST]	BG265	Tutor
10	01958652	Doe	John	Mr	64 Austin St Holow VIC	0321343123	1337	[DBST42.CAMPUST]	BG265	Tutor

Admin-Table:

	PERSON_ID		N_SURNAME	♦ PERSON_FORE	NAME		PER	SON_ADDR				PERSON_PHON	IE PERSON_POSTCODE	CAMPUS	♦ OFFICE_NO
1 1	0002935	Jones		Felicity		Ms	14 F	Rennie	St T	hornbury	VIC	039872200	1 3071	[DBST42.CAMPUST]	BG210
2 1	2 10008957 Jane Patrick			Patrick	Mr 23 Rainbow Rd Allumy VIC				IC	023626363	3033	[DBST42.CAMPUST]	BG221		
♦ OFFICE	OFFICE_NO STAFF_TYPE ADMIN_TITLE				ADMIN	ADMIN_COMPUTERSKILLS					ADI	IN_OFFICESKILL	S		
BG210	G210 Admin Office Manager DBST42.COMPUT					ERSE	KILLST	()		DB	ST42.OFFI	CESKILLST ('Mar	nagerial')		
BG221	3221 Admin Receptionist DBST42.COMPUTERS						ERSE	KILLST	('MS	Office') DB	ST42.OFFI	CESKILLST ('Cus	stomer Service',	'Phone')

<u>Technician-Table:</u>

	♦ PERSON_II	PERSON_SURNAME	♦ PERSON_FOR	RENAME () PERSO	N_TITLE 0 P	ERSON_ADDR			♦ PERSON_POSTCODE
1	1 10005825 Gibbs		Lewroy	Mr	12	7 Moltres V	Nay Jotho VIO	0285624733	3042
2	1001582	6 Beckett	Kate	Ms	42	Donestry S	St Jibisy VIC	0263957394	3087
♦ PERSOI	N_POSTCODE	CAMPUS	OFFICE_NO		TECH_TITLE		TECH_SKILLS		
3042		[DBST42.CAMPUST	BG231	Technician	Network	Officer	DBST42.TECHN	ICIANSKILLST	('UNIX','NT')
3087		[DBST42.CAMPUST	1 BG232	Technician	Photocor	v Technicia	n DBST42.TECHN	ICIANSKILLST	('Electrician')

<u>Tutor-Table:</u>

#	PERSON_II	D PERSON_SURNAME	\$ PERSON_FOREN	NAME () PERSO	ON_TITLE	PERS	SON_ADDR		
1 (0123423	4 Grant	Felix	Mr		2 Bc	adle Rd Bu	ndoora VIC	0398548753
2 (0195865	2 Doe	John	Mr		64 A	ustin St H	lolow VIC	0321343123
♦ PERSO	N_PHONE	PERSON_POSTCODE	CAMPUS		♦ OFFICE	E_NO		⊕ TUTOR_HOURS	↑ TUTOR_RATE
03985	48753	3083	[DBST42.0	AMPUST]	BG265	5	Tutor	10	20
03213	43123	1337	[DBST42.0	AMPUST]	BG265	5	Tutor	30	35

<u>Lecturer-Table:</u>

	PERSON_	JD ∯	PERSON_SURNAME	♦ PERSON_F	ORENAME	PERSON_	TITLE				PERSON_PHONE
1	100088	95 X	in	Harry		Mr		6 Kelley S	t Kew VI	2	0398875542
2	100002	55 M	organ	Henry		Mr		2 London A	ve Karri	gan VIC	0395182649
3	100002	58 F	low	Max		Mr		26 Hollow	Tips St B	Precidense VIC	0492849184
4	100069	35 G	unn	Montgom	ery	Mr		65 Arrow A	ve Catery	V AIG	0492847294
PERSO	ON_PHONE		SON_POSTCODE C	AMPUS		∜ OFFI	CE_NO		LECT_AREA		
03988	375542	3088	8 [DBST42.	CAMPUS!	r] BG21	2	Lecturer	Software	Engineering	Associate
03951	82649	3062	2 [DBST42.	CAMPUS	r] BG22	5	Lecturer	Business	Information	Senior
04928	349184	3012	2 [DBST42.	CAMPUS!	r] BG22	6	Lecturer	Business	Administration	n Senior
04928	347294	3085	5 [DBST42.	CAMPUS!	r] BG22	5	Lecturer	Software	Development	Associate

Senior-Lecturer-Table:

	PERSON_SURNAME	PERSON_FORENAM	E PERSON_TITLE			♦ PERSON_PHONE	PERSON_POSTCODE
1 1000025	5 Morgan	Henry	Mr	2 London Ave Kar	rigan VIC	0395182649	3062
2 1000025	8 Flow	Max	Mr	26 Hollow Tips S	t Precidense VIC	0492849184	3012
♦ PERSON_POSTCODE	CAMPUS		TAFF_TYPE \$\tect_A	REA	\$ LECT_TYPE \$ SENLECT_PHO	SENLECT_MASTER	SENLECT_HONOURS
	CAMPUS [DBST42.CAMPUST				<pre>\$\text{\text_TYPE} \$\text{\text_SENLECT_PHI}\$</pre>	SENLECT_MASTER	

Associate-Lecturer-Table:

♦ PERSON_ID	PERSON_SURNAME	♦ PERSON_FORENAME			♦ PERSON_PHONE	RSON_POSTCODE
1 10008895	Xin	Harry	Mr	6 Kelley St Kew VIC	0398875542 308	8
2 10006935	Gunn	Montgomery	Mr	65 Arrow Ave Catery VIC	0492847294 308	5
PERSON POSTCODE	CAMPILIC	A OFFICE NO /	A STAFE TOPE A LEST	A	Λ	A
⊕ PERSON_POSTCODE	CAMPUS		STAFF_TYPE UECT_	AREA & LECT_TYPE		# ASSLECT_YEAR
3088	[DBST42.CAMPU	· -	v - v -	ware Engineering Associat	· -	# ASSLECT_YEAR 1999

Subject-Table:

			\$ SUBJECT_CREDIT		PERSON
1	CSE21NET	Networking	10	CSE11IS	[DBST42.PERSONT]
2	CSE42ADB	Advanced Database	15	CSE21DB	[DBST42.PERSONT]

Enrolls-In-Table:

	STUDENT	DEG
1	[DBST42.STUDENTT]	[DBST42.DEGREET]
2	[DBST42.STUDENTT]	[DBST42.DEGREET]

Takes-Table:

	STUDENT	SUBJECT	∯ MARK
1	[DBST42.STUDENTT]	[DBST42.SUBJECTT]	70
2	[DBST42.STUDENTT]	[DBST42.SUBJECTT]	80

Anmerkungen

Uns ist bei der Planung von Typen und Tabellen aufgefallen, dass einige Tabellenattribute unnötig waren, da man über Joins an dieses Attribut gelangen könnte. So hatte bspw. die Staff-Tabelle in der Fallstudien-Beschreibung noch ein Attribut für das Gebäude (Building), dieses haben wir nicht übernommen, da man mit dem Office_Nr-Attribut über einen Join zur Office-Tabelle zu dem Gebäude gelangen kann. So haben wir unnötige Redundanzen / Speicherplatz-Verschwendung vermieden.

Auf der anderen Seite haben wir in vielen Tabellen wie bspw. Building, Person, Office, Classroom, Lab uvm. mit Referenzen statt einfachen IDs gehabt, dies hat zwei Vorteile:

- Wir können ohne Join sofort auf die Daten zugreifen (Dereferenzierung)
- Wir können sicherstellen das in bspw. der Takes-Tabelle nur gültige Studenten sind

Ich hoffe, dass diese Änderungen in Ihrem Sinn sind und unsere Gedankengänge für Sie sinnvoll bzw. nachvollziehbar erscheinen.

Falls Sie sich die SQL-Statements genauer ansehen oder zum selbst Testen kopieren möchten, finden Sie diese und alle anderen Dateien / Informationen auf GitHub.com/AnyaW/DBS2.