

The MeloSol Corpus

David John Baker<sup>1</sup>

<sup>1</sup> Louisiana State University

Author Note

David John Baker now works at Flatiron School in London, England.

Correspondence concerning this article should be addressed to David John Baker, .

E-mail: davidjohnbaker1@gmail.com

## Abstract

9 This paper introduces the *MeloSol* corpus, a collection of 783 Western, tonal monophonic  
10 melodies. We first begin by describing the overall structure of the corpus, then proceed to  
11 detail its contents as they would be helpful for researchers working in the field of  
12 computational musicology or music psychology. In order to contextualize the MeloSol  
13 corpus, compare descriptive statistics generated using the FANTASTIC feature extraction  
14 toolkit with that of the Essen Folk Song Collection as well as The Densmore Collection of  
15 Native American Songs. We suggest possible uses of this corpus including extending  
16 research which investigates Western tonality, perceptual experiments needing novel  
17 ecological stimuli, or work involving the musical generation of monophonic melodies in the  
18 style of Western tonal.

19 *Keywords:* corpus studies, FAIR data, kern

20 Word count: X

## The MeloSol Corpus

### Introduction

This data report introduces the *MeloSol* corpus, a collection of 783 monophonic melodies taken from *A New Approach to Sight Singing: Fifth Edition* (Berkowitz, Fontrier, Kraft, Goldstein, & Smaldone, 2011). The title *MeloSol* derives from a combination of the corpus' content— *Melo* dic data— and the first name of the original author of the collection, *Sol* Berkowitz.

The corpus is divided into two major sections: a collection of sight singing melodies composed specifically for pedagogical purposes ( $n = 629$ ) taken from Chapter One and examples from Western Classical literature ( $n = 154$ ) taken from Chapter Five. The original text also contains materials for practicing rhythm (Chapter Two), Singing Duets (Chapter Three), Sing and Plays that incorporate a melody and piano accompaniment (Chapter Four), and Supplementary Exercises that are not included here. Within each of the larger sections exists five further subdivisions. These five subdivisions are mapped in conjunction with the trajectory of many aural skills classrooms.

For example, the first section of both the sight singing melodies and the first section of literature align with melodies a first semester undergraduate student in a music degree program might be expected to learn during their first semester of university in an aural skills classroom. As the original book was designed as a pedagogical text, each section of the book and consequently each melody within each section is meant to increase in complexity as new topics are being introduced. The fifth and final section of both the sight singing melodies and examples from the literature contains melodies which break from Western tonal practice. These melodies contain either modal, atonal, or tonally ambiguous melodies. A visual depiction of the breakdown of melodies from the two larger sections in terms of count data is presented in FIGURE ONE.

- FIGURE ONE HERE

In terms of analyzable data, the 783 melodies are encoded in **\*\*kern** format (Huron, 1994), with each individual file containing metadata listing the unique identifier, chapter from which the melody originates, section within that chapter of the larger text, page number, as well as what mode the encoder labeled the melody as. Modes were only noted for a small subset of the corpus, the vast majority of these melodies are either major (ionian) or minor (aeolean). Other corpora should be consulted for questions pertaining to mode such as work by Albrecht and Huron (Albrecht & Huron, 2014).

Overall, the corpus consists of 49,730 tokens, a subset of which are 36,641 note heads. All melodies in the corpus were encoded by hand using the software MuseScore (Werner, Nicholas, & Bonte, 2019), initially saved as XML, then converted to **\*\*kern** using the humdrum extras **xml2hum** tool (Sapp, 2008) with the current meta data added using the **name-of-script.R**. Further addition to the metadata can be added with modifications to **name-of-script** found in the **scripts** directory. We describe the corpus from a macro perspective in figure TWO and THREE. Figure TWO presents the combined tonal materials, sections one through four of Chapter One and Five; figure THREE presents the same information for section five of Chapter One and Five. Tonal and non-tonal materials were separated as not to distort key representations since non-tonal melodies are encoded with a no sharps, no flats key signature.

- FIGURE TWO (Subset out Section Five)
- FIGURE THREE (Section Five)

## Comparison

In order to further contextualize the *MeloSol* corpus with the context of other corpora found in the literature, we briefly compare descriptive statistics from the *MeloSol*

corpus with both *The Densmore Collection of Native American Songs* (Neubarth, Shanahan, & Conklin, 2018; Shanahan & Shanahan, 2014) as well as the European and Chinese subset of the *Essen Folk Song Collection* (Schaffrath, 1995). We chose both the *Densmore* as well as the *Essen* collection as both corpora represent corpora of melodies that have been used to study singing as well as investigations into computationally modeling the implicit understanding of patterns found in different musical cultures. Further, we compare the *MeloSol* with the *Essen* collection as the *Essen* collection has been used as a proxy for representing the implicit understanding of the structure of Western, tonal music in computational models that depend theoretically on the concept of implicit, statistical learning (Demorest & Morrison, 2016; Huron, 2006; Pearce, 2018). Comparisons of descriptive statistics were conducted using the FANTASTIC toolbox (Mullensiefen, 2009). The accompanying calculations for each melody are found in `corpus/melosol_fantastic_features.csv`.

In FIGURE FOUR, we compare ... In FIGURE FIVE, we compare ...

- FIGURE FOUR
- FIGURE FIVE

## Useful

As the *MeloSol* corpus comprises Western, tonal music, this corpora might be utilized in order to continue research investigating empirical claims about about patterns intrinsic to Western, tonal music. For example claims made by Huron CITE regarding contour class—initially explored using this dataset by BAKER—could be further modeled using *MeloSol*. Additionally, as *MeloSol* strictly contains music associated with Western, tonal music, the corpus could be used in further work replacing the *Essen* collection as a dataset in which to train computational models of melodic expectation (Pearce, 2018). We finally note that as this corpus was initially developed in order to investigate how to make

95 pedagogical improvements in aural skills classrooms, using *MeloSol* for this purpose would  
96 be a logical extension to this programme of research CITE ME.

## 97 **Data analysis**

98 We used R (Version 3.6.2; R Core Team, 2019) and the R-package *papaja* (Version  
99 0.1.0.9942; Aust & Barth, 2020) for all our analyses.

## References

- Albrecht, J. D., & Huron, D. (2014). A statistical approach to tracing the historical development of major and minor pitch distributions, 1400-1750. *Music Perception: An Interdisciplinary Journal*, 31(3), 223–243.
- Aust, F., & Barth, M. (2020). *papaja: Create APA manuscripts with R Markdown*. Retrieved from <https://github.com/crsh/papaja>
- Berkowitz, S., Fontrier, G., Kraft, L., Goldstein, P., & Smaldone, E. (2011). *A new approach to sight singing* (5th ed). New York: W.W. Norton.
- Demorest, S. M., & Morrison, S. J. (2016). 12 quantifying culture: The cultural distance hypothesis of melodic expectancy. *The Oxford Handbook of Cultural Neuroscience*, 183.
- Huron, D. (1994). *The Humdrum Toolkit: Reference Manual*. Center for Computer Assisted Research in the Humanities.
- Huron, D. (2006). *Sweet Anticipation*. MIT Press.
- Mullensiefen, D. (2009). Fantastic: Feature ANalysis Technology Accessing STatistics (In a Corpus): Technical Report v1.5.
- Neubarth, K., Shanahan, D., & Conklin, D. (2018). Supervised descriptive pattern discovery in Native American music. *Journal of New Music Research*, 47(1), 1–16. <https://doi.org/10.1080/09298215.2017.1353637>
- Pearce, M. T. (2018). Statistical learning and probabilistic prediction in music cognition: Mechanisms of stylistic enculturation: Enculturation: Statistical learning and prediction. *Annals of the New York Academy of Sciences*, 1423(1), 378–395. <https://doi.org/10.1111/nyas.13654>
- R Core Team. (2019). *R: A language and environment for statistical computing*. Vienna, Austria: R Foundation for Statistical Computing. Retrieved from

- 125           <https://www.R-project.org/>
- 126   Sapp, C. (2008). Humdrum Extras.
- 127   Schaffrath, H. (1995). The Essen Folk Song Collection, D. Huron.
- 128   Shanahan, D., & Shanahan, E. (2014). The Densmore Collection of Native American
- 129       Songs: A New Corpus for Studies of Effects of Geography, Language, and Social
- 130       Function on Folk Song. In *Proceedings of the Fourteenth Annual International*
- 131       *Conference for Music Perception and Cognition*. San Francisco.
- 132   Werner, S., Nicholas, F., & Bonte, T. (2019). MuseScore.