


<b>Name: Aaron Martin P. Caro</b>	<b>Date Performed: Sep 5, 2023</b>
<b>Course/Section: CPE232/CPE31S5</b>	<b>Date Submitted: Sep 5, 2023</b>
<b>Instructor: Prof. Roman Richard</b>	<b>Semester and SY: 1st sem 2023-2024</b>
<b>Activity 3: Install SSH server on CentOS or RHEL 8</b>	
<b>1. Objectives:</b> 1.1 Install Community Enterprise OS or Red Hat Linux OS 1.2 Configure remote SSH connection from remote computer to CentOS/RHEL-8	
<b>2. Discussion:</b>  <b>CentOS vs. Debian: Overview</b>  CentOS and Debian are Linux distributions that spawn from opposite ends of the candle.  CentOS is a free downstream rebuild of the commercial Red Hat Enterprise Linux distribution where, in contrast, Debian is the free upstream distribution that is the base for other distributions, including the Ubuntu Linux distribution.  As with many Linux distributions, CentOS and Debian are generally more alike than different; it isn't until we dig a little deeper that we find where they branch.  <b>CentOS vs. Debian: Architecture</b>  The available supported architectures can be the determining factor as to whether a distro is a viable option or not. Debian and CentOS are both very popular for x86_64/AMD64, but what other archs are supported by each?  Both Debian and CentOS support AArch64/ARM64, armhf/armhfp , i386 , ppc64el/ppc64le. (Note: armhf/armhfp and i386 are supported in CentOS 7 only.)  CentOS 7 additionally supports POWER9 while Debian and CentOS 8 do not. CentOS 7 focuses on the x86_64/AMD64 architecture with the other archs released through the AltArch SIG (Alternate Architecture Special Interest Group) with CentOS 8 supporting x86_64/AMD64, AArch64 and ppc64le equally.  Debian supports MIPSel, MIPS64el and s390x while CentOS does not. Much like CentOS 8, Debian does not favor one arch over another—all supported architectures are supported equally.  <b>CentOS vs. Debian: Package Management</b>  Most Linux distributions have some form of package manager nowadays, with some more complex and feature-rich than others.  CentOS uses the RPM package format and YUM/DNF as the package manager.	

Both offer full-feature package management with network-based repository support, dependency checking and resolution, etc.. If you're familiar with one but not the other, you may have a little trouble switching over, but they're not overwhelmingly different. They both have similar features, just available through a different interface.

1. Download the image of the CentOS here:



# RISE

The [fastest internet](#) in the Philippines

WELCOME TO THE RISE #MIRROR

Files can be downloaded using <http://mirror.rise.ph> and <ftp://mirror.rise.ph>  
 Please Note: Mirror is currently undergoing maintenance so you may find some repositories is not up to date.

Directory: /centos/7.9.2009/isos/x86\_64/

Name	Last modified	Size
Parent Directory	-	-
<a href="#">0_README.txt</a>	2022-06-05 02:03	2.7K
<a href="#">CentOS-7-x86_64-DVD-&gt;</a>	2020-11-04 19:37	4.4G
<a href="#">CentOS-7-x86_64-DVD-&gt;</a>	2020-11-06 22:44	176K
<a href="#">CentOS-7-x86_64-DVD-&gt;</a>	2022-07-26 23:10	4.4G
<a href="#">CentOS-7-x86_64-Ever-&gt;</a>	2020-11-02 23:18	9.5G
<a href="#">CentOS-7-x86_64-Ever-&gt;</a>	2020-11-06 22:44	381K
<a href="#">CentOS-7-x86_64-Ever-&gt;</a>	2022-07-27 02:09	9.6G
<a href="#">CentOS-7-x86_64-Mini-&gt;</a>	2020-11-03 22:55	1.0G
<a href="#">CentOS-7-x86_64-Mini-&gt;</a>	2020-11-06 22:44	39K
<a href="#">CentOS-7-x86_64-Mini-&gt;</a>	2022-07-26 23:10	1.0G
<a href="#">CentOS-7-x86_64-Hell-&gt;</a>	2020-10-27 00:26	575M
<a href="#">CentOS-7-x86_64-Hell-&gt;</a>	2020-11-06 22:44	23K
<a href="#">sha256sum.txt</a>	2022-06-05 01:56	703
<a href="#">sha256sum.txt.asc</a>	2022-06-05 01:58	1.5K

Downloads


CentOS-7-x86\_64-DVD-2009.iso

2.1 MiB/s - 563 MiB of 4.4 GB, 31 mins left

Activity 3 - Install SSH server on CentOS or RHEL 6.docx

(removed)

See more

- 

Create Virtual Machine

?

✕

## Virtual machine Name and Operating System

Please choose a descriptive name and destination folder for the new virtual machine. The name you choose will be used throughout VirtualBox to identify this machine. Additionally, you can select an ISO image which may be used to install the guest operating system.

Name:

Ccentos

✓

Folder:

C:\Users\tipqc\VirtualBox VMs

▼

ISO Image:

C:\Users\tipqc\Downloads\CentOS-7-x86\_64-DVD-2009.iso

▼


Edition:

▼

Type:

Linux

▼




Version:

Red Hat (64-bit)

▼

☐ Skip Unattended Installation

 Detected OS type: Red Hat (64-bit). This OS type can be installed unattendedly. The install will start after this wizard is closed.



Help

Expert Mode



Back



Next



Cancel




3. Install the downloaded image.







4. Show evidence that the OS was installed already.



## Task 2: Install the SSH server package *openssh*

1. Install the ssh server package *openssh* by using the *dnf* command:

*\$ dnf install openssh-server*

```
Complete!
[acaro@localhost ~]$ dnf install openssh-server
Error: This command has to be run under the root user.
[acaro@localhost ~]$ sudo yum dnf install openssh-server
Loaded plugins: fastestmirror, langpacks
No such command: dnf. Please use /bin/yum --help
[acaro@localhost ~]$ sudo su
[root@localhost acaro]# 1221
bash: 1221: command not found...
[root@localhost acaro]# dnf install openssh-server
CentOS-7 - Base                1.9 MB/s | 10 MB    00:05
CentOS-7 - Updates             2.0 MB/s | 28 MB    00:13
```

2. Start the *sshd* daemon and set to start after reboot:

*\$ systemctl start sshd*

*\$ systemctl enable sshd*

```
[root@localhost acaro]# systemctl start sshd
[root@localhost acaro]# systemctl enable sshd
[root@localhost acaro]# █
```

3. Confirm that the sshd daemon is up and running:

*\$ systemctl status sshd*

```
[root@localhost acar0]# systemctl status sshd
● sshd.service - OpenSSH server daemon
   Loaded: loaded (/usr/lib/systemd/system/sshd.service; enabled; vendor preset:
   d)
   Active: active (running) since Tue 2023-09-05 06:20:29 EDT; 10min ago
     Docs: man:sshd(8)
           man:sshd_config(5)
  Main PID: 1158 (sshd)
    Tasks: 1
   CGroup: /system.slice/sshd.service
           └─1158 /usr/sbin/sshd -D

Sep 05 06:20:29 localhost.localdomain systemd[1]: Starting OpenSSH server daemon.
Sep 05 06:20:29 localhost.localdomain sshd[1158]: Server listening on 0.0.0.0 por
Sep 05 06:20:29 localhost.localdomain sshd[1158]: Server listening on :: port 22.
Sep 05 06:20:29 localhost.localdomain systemd[1]: Started OpenSSH server daemon.
Hint: Some lines were ellipsized, use -l to show in full.
[root@localhost acar0]#
```

4. Open the SSH port 22 to allow incoming traffic:

```
$ firewall-cmd --zone=public --permanent --add-service=ssh
$ firewall-cmd --reload
```

```
[root@localhost acar0]# firewall-cmd --zone=public --permanent --add-service=ssh
Warning: ALREADY_ENABLED: ssh
success
[root@localhost acar0]# firewall-cmd --reload
success
[root@localhost acar0]#
```

5. Locate the ssh server man config file */etc/ssh/sshd\_config* and perform custom configuration. Every time you make any change to the */etc/ssh/sshd-config* configuration file reload the *sshd* service to apply changes:


```
$ systemctl reload sshd
```

```
[root@localhost acar0]# systemctl reload sshd
[root@localhost acar0]#
```

### Task 3: Copy the Public Key to CentOS

1. Make sure that *ssh* is installed on the local machine.
2. Using the command *ssh-copy-id*, connect your local machine to CentOS.
3. On CentOS, verify that you have the *authorized\_keys*.





#### Task 4: Verify ssh remote connection

1. Using your local machine, connect to CentOS using ssh.
2. Show evidence that you are connected.

```
aaron@workstation:~$ ssh-copy-id -i ~/.ssh/id_rsa acar@192.168.56.104
/usr/bin/ssh-copy-id: INFO: Source of key(s) to be installed: "/home/aaron/.ssh/id_rsa.pub"
The authenticity of host '192.168.56.104 (192.168.56.104)' can't be established.
ED25519 key fingerprint is SHA256:4Kb09vrm1QP0mDi1zkj+Gd8kBxWsFP10mbJE+ZEsLhI.
This key is not known by any other names
Are you sure you want to continue connecting (yes/no/[fingerprint])? yes
/usr/bin/ssh-copy-id: INFO: attempting to log in with the new key(s), to filter out any that are already installed
/usr/bin/ssh-copy-id: INFO: 1 key(s) remain to be installed -- if you are prompted now it is to install the new keys
acar@192.168.56.104's password:

Number of key(s) added: 1

Now try logging into the machine, with: "ssh 'acar@192.168.56.104'"
and check to make sure that only the key(s) you wanted were added.
```

```
aaron@workstation:~$ ssh acar@192.168.56.104
Last login: Tue Sep  5 09:01:28 2023
[acar@localhost ~]$
```

#### Reflections:

Answer the following:

1. What do you think we should look for in choosing the best distribution between Debian and Red Hat Linux distributions?

When choosing the best distribution between Debian and RedHat Linux, there are several factors to consider. System administration, consider the ease of use and management of the distribution. The choice between Debian and RedHat typically comes down to factors like hardware architecture, system administration, support,

usability, and licensing. Both distributions are known for their stability and performance for enterprise-grade applications, but Red Hat Enterprise Linux (RHEL) comes out on top due to its excellent enterprise support and robust security which ensures data and application security to the highest degree. However, RHEL is costly, and Debian is a community-supported distribution that is known for its reliability and flexibility.

**2. What are the main differences between Debian and Red Hat Linux distributions?**

CentOS and Debian are two popular Linux distributions that have key similarities and differences. CentOS is a free downstream rebuild of the commercial Red Hat Enterprise Linux distribution, while Debian is the free upstream distribution that is the base for other distributions, including the Ubuntu Linux distribution.