

# A review of R neural network packages (with NNbenchmark): accuracy and ease of use

by Salsabila Mahdi, Akshaj Verma, Christophe Dutang, Patrice Kiener, John C. Nash

## Abstract

In the last three decades, neural networks (NN) have evolved from an academic topic to a common scientific computing tool. CRAN currently hosts approximately 80 packages in May 2020 involving neural network modeling, some offering more than one algorithm. However, to our knowledge, there is no comprehensive study which checks the accuracy, the reliability and the ease-of-use of those NN packages.

In this paper, we attempted to test this rather large number of packages against a common set of datasets with different levels of complexity, and to benchmark and rank them with certain metrics.

Restricting our evaluation to regression algorithms applied on the one-hidden layer perceptron and ignoring those for classification or other specialized purposes, there were approximately 60 package::algorithm pairs left to test. The criteria used in our benchmark were: (i) the accuracy, i.e. the ability to find the global minima on 13 datasets, measured by the Root Mean Square Error (RMSE) in a limited number of iterations; (ii) the speed of the training algorithm; (iii) the availability of helpful utilities; (iv) and the quality of the documentation.

We have attempted to give a score for each evaluation criterion and to rank each package::algorithm pair in a global table. Overall, 15 pairs are considered accurate and reliable and can be recommended for daily usage. Most others should be avoided as they are either less accurate, too slow, too difficult to handle, or have poor or no documentation.

To carry out this work, we developed various codes and templates, as well as the NNbenchmark package used for testing. This material is available at <https://akshajverma.com/NNbenchmarkWeb/index.html> and <https://github.com/pkR-pkR/NNbenchmark>, and can be used to verify our work and, we hope, improve both packages and their evaluation. Finally, we provide some hints and features to guide the development of an idealized neural network package for R.

## Introduction

The R Project for Statistical Computing ([www.r-project.org](http://www.r-project.org)), as any opensource platform, relies on its contributors to keep it up to date. Neural networks (NN), inspired on the brain's own connections system, are a class of models in the growing field of machine learning for which R has a number of tools. During the last 30 years, neural networks have evolved from an academic topic to a common tool in scientific computing. Previously, neural networks were considered more theory than practice, partly because the algorithms used were computationally demanding.

As a convenience in the general conversation, the same term is used in a generic manner for different model structures and applications: multilayer perceptron for regression, multilayer perceptron for classification, multilayer perceptron for specialized applications, recurrent neural network for autoregressive time series, convolutional neural networks for dimension reduction and pattern recognition, deep neural networks for image or voice recognition. Most of the above types of neural networks can be found in R packages hosted on CRAN but without any warranty about the accuracy or the speed of computation. This is an issue as many poor algorithms are available in the literature and hence poor packages implemented on CRAN.

A neural network algorithm requires complicated calculations to improve the model

control parameters. As with other optimization problems, the gradient of the chosen cost function that indicates the lack of suitability of the model is sought. This lets us improve the model by changing the parameters in the negative gradient direction. Parameters for the model are generally obtained using part of the available data (a training set) and tested on the remaining data. Modern software allows much of this work, including approximation of the gradient, to be carried out without a large effort by the user.

The training process can generally be made more efficient if we can also approximate second derivatives of the cost function, allowing us to use its curvature via the Hessian matrix. There are a large number of approaches, of which quasi-Newton algorithms are perhaps the most common and useful. Within this group, methods based on the Broyden-Fletcher-Goldfarb-Shanno (BFGS) algorithm for updating the (inverse) Hessian approximation provide several well-known examples. In conducting this study, we believed that these second-order algorithms would perform better than first-order methods for fit-in-memory datasets.

Regardless of our belief, we wished to be able to conduct a thorough examination of these training algorithms in R. There are many packages, but barely any information to allow comparison. Our work, reported here, aims to provide a framework for benchmarking neural network packages. We restrict our examination to packages for R, and in this report focus on those that provide neural networks of the perceptron type, that is, one input layer, one normalized layer, one hidden layer with a nonlinear activation function that is usually the hyperbolic tangent  $\tanh()$ , and one output layer. The criteria used in our benchmark were: (i) the accuracy, i.e. the ability to find the global minima on 13 datasets in a limited number of iterations; (ii) the speed of the training algorithm; (iii) the availability of helpful utilities; (iv) and the quality of the documentation. We restricted our evaluation to regression algorithms applied on the one-hidden layer perceptron and ignored those for classification or other specialized purposes.

## Neural Networks: the perceptron

Here, we give a short description of the one hidden layer perceptron. As the “layer” term suggests it, some terms come from the representation of graphs whereas some other terms come from the traditional literature on nonlinear models.

Using the graph description, a one-hidden layer neural network is made of 3 parts: (i) the layer of the input(s), (ii) the hidden layer which consists of independent neurons, each of them performing two operations: a linear combination of the inputs plus an offset, then a nonlinear function applied on this linear combination. (iii) the layer of the output(s) which is a linear combination of the output of the nonlinear functions in the hidden layer.


The nonlinear function used in the hidden layer must have the following four properties: continuous, differentiable, monotonic, bounded. The logistic (logit), the hyperbolic tangent ( $\tanh$ ) and the arctangent ( $\text{atan}$ ) functions are the usual candidates.

The above description has a simple mathematical equivalence. Let us give two examples.

The model  $y = a_1 + a_2 \times \tanh(a_3 + a_4 \times x) + a_5 \times \tanh(a_6 + a_7 \times x) + a_8 \times \tanh(a_9 + a_{10} \times x)$  describes a neural network with one input, three hidden neurons, one output model where  $x$  is the input,  $\tanh()$  is the activation function,  $y$  is the output and  $a_1, \dots, a_{10}$  are the parameters.

The model  $y = a_1 + a_2 \times \text{atan}(a_3 + a_4 \times x_1 + a_5 \times x_2 + a_6 \times x_3 + a_7 \times x_4 + a_8 \times x_5) + a_9 \times \text{atan}(a_{10} + a_{11} \times x_1 + a_{12} \times x_2 + a_{13} \times x_3 + a_{14} \times x_4 + a_{15} \times x_5) + a_{16} \times \text{atan}(a_{17} + a_{18} \times x_1 + a_{19} \times x_2 + a_{20} \times x_3 + a_{21} \times x_4 + a_{22} \times x_5)$  describes a neural network with five inputs, three hidden neurons, one output model where  $x$  is the input,  $\text{atan}()$  is the activation function,  $y$  is the output and  $a_1, \dots, a_{22}$  are the parameters.

In order to get large gradients at the first steps of the training algorithm, it is recommended to use normalized inputs, normalized outputs, odd functions like the hyperbolic tangent function or the arctangent function and small random values to initialize the param-



**Figure 1:** 3 neural networks with structures 1-3-1, 5-3-1, 5-5N-3-1N-1

eters, for instance extracted from a centered Gaussian distribution  $\mathcal{N}(0, 0.1)$  distribution. Such good practices help find good local minima and possibly the global minimum.

The dataset used for the training is assumed to have a number of rows much larger than the number of parameters. While “much larger” is subject to discussion, values of 3 to 5 are generally accepted. (In experimental design, some iterative strategies start with a dataset having a number of experiments/lines equal to 1.8 times the number of parameters and then increase the number of experiments to finetune the model.)

It is rather clear from the mathematical formula above that neural networks of perceptron type are nonlinear models and require for their parameter estimation some training algorithms that can handle (highly) nonlinear models. Indeed, the intrinsic and parametric curvatures of such models are usually very high and, with so many parameters, the Jacobian matrix might exhibit some collinearities between its columns and become nearly singular. As a result, appropriate algorithms for such dataset::model pairs are rather limited and well-known. There is the second-order algorithms BFGS which is Quasi-Newton in how it approximates the Jacobian and Levenberg-Marquardt which stabilizes the Gauss-Newton.

Unfortunately, due to some simple literature on the gradient and the hype around “deep neural networks” that manipulate ultra-large models with hundreds or thousands parameters and sometimes more parameters than examples in the datasets, many papers and many R packages emphasize the use of first-order gradient algorithms. In the case of the perceptron, this is an error and the goal of this paper is to demonstrate it.

JN??: replace previous paragraph with ??

Unfortunately, there are widely-discussed articles concerning the gradient and “deep neural networks” that manipulate ultra-large models with hundreds or thousands parameters and sometimes more parameters than examples in the datasets. These, along with some R packages, emphasize the use of first-order gradient algorithms. In the case of the perceptron, we contend this is an error, and provide evidence to that effect in this paper.

## Methodology

### - What does “convergence” mean in our context? ??JN: Something like

When training neural networks, we attempt to tune a set of hyperparameters so that the root mean squared error (RMSE) is minimized. When our method for such adjustment can no longer reduce the RMSE, we say that the given algorithm terminated. It converged when the terminated RMSE value is relatively small<sup>1</sup>. In practice, some algorithms require that we stop the optimization process in exceptional situations (e.g., a divide by zero), or a pre-set limit on the number of steps or elapsed time is reached.

More precisely, second-order algorithms are all set to a maximum of 200 iterations. On the other hand, first-order algorithms were set to several values, depending on how

<sup>1</sup>So, we do not choose the mean absolute error (MAE) neither for overall ranking nor for convergence value as there is no consensus in the literature, see e.g. (Willmott and Matsuura, 2005; Chai and Draxler, 2014).

well and how fast they converged: `maxit1storderA=1000` iterations, `maxit1storderB=10000` iterations, and `maxit1storderC=100000` iterations. The full list of the maximum iteration number per package:algorithm is given in Appendix C. It can be seen that we were unable to completely harmonize the hyperparameters as an appropriate learning rate differed between package, despite the algorithm being similarly named.

#### - What do we mean by “performance”? Other goals? ??JN: perhaps?

We measure performance primarily by relative computing time between methods on a particular computing platform. We could also count measures of iterations, function evaluations or similar quantities that indicate the computing effort. We note that differences in machine architecture and in the attached libraries (e.g., BLAS choices for R) will modify our measures. We are putting our tools on a Github repository so that further evaluation can be made by ourselves and others as hardware and software evolves.

The resulting files in the repository were mostly generated by one of us (SM) on a Windows system build 10.0.18362.752 with a i7-8750H CPU, a Intel(R) UHD Graphics 630 and NVIDIA GeForce GTX 1060 chip, and 16 GB of RAM.

---

Our research process was divided into 3 phases.

### Phase 1 - Preparation of benchmark datasets

#### Datasets => NEED TO BE FINISHED??

All the datasets we use cannot generally be modeled using a non-iterative calculation such as Ordinary Least Squares. Varying levels of difficulty in modeling the different data sets are intended to allow us to further classify different algorithms and the packages that implement them. Sonja Surjanovic and Derek Bingham of Simon Fraser University created a useful website from which three of the multivariate datasets were drawn. We note the link, name and difficulty level of the three datasets:

- <http://www.sfu.ca/~ssurjano/fried.html> (Friedman - average)
- <http://www.sfu.ca/~ssurjano/dettep10curv.html> (Dette - medium)
- <http://www.sfu.ca/~ssurjano/ishigami.html> (Ishigami - high)

The other multivariate dataset, Ref153, was taken from ...

Three of the univariate datasets we used were taken from a website of the US National Institute for Standards and Technology (NIST): [https://www.itl.nist.gov/div898/strd/nls/nls\\_main.shtml](https://www.itl.nist.gov/div898/strd/nls/nls_main.shtml). (Gauss1 - low; Gauss2 - low; Gauss3 - average)

Univariate datasets Dmod1, Dmod2 are from ...

Dreyfus1 is a pure neural network which has no error. This can make it difficult for algorithms that assume an error exists. Dreyfus2 is Dreyfus1 with errors. NeuroOne from ...

Finally, we also consider a Simon Wood test dataset, used in (Wood, 2011) for benchmarking generalized additive models. Precisely, we consider a generation of Gaussian random variates  $Y_i$ ,  $i = 1, \dots, n$  with the mean  $\mu_i$  defined as

$$\mu_i = 1 + f_0(x_{i,0}) + f_1(x_{i,1}) + f_2(x_{i,2}) + f_3(x_{i,3}) + f_4(x_{i,4}) + f_0(x_{i,5})$$

and standard deviation  $\sigma = 1/4$  where  $f_j$  are Simon Wood's smooth functions defined in Appendix B,  $x_{i,j}$  are uniform variates and  $n = 20,000$ .

### Packages

Using **RWsearch** (Kiener, 2020) we sought to automate the process of searching for neural network packages. All packages that have “neural network” as a keyword in the package title or in the package description were included. In May 2020, around 80 packages falls

into this category. Packages **nlsr**, **minpack.lm**, **caret** were added because the former 2 are important implementations of second-order algorithms while the latter is the first cited meta package in the CRAN's task view for machine learning, <https://CRAN.R-project.org/view=MachineLearning>, as well as the dependency for some of the other packages tested. Restricting to regression analysis left us with 49 package::algorithm pairs in 2019 and 60 package::algorithm pairs in 2020.

## Phase 2 - Review of packages and development of a benchmarking template

From documentation and example code, we learned that not all packages selected by the automated search fit the scope of our research. Some have no function to generate neural networks. Others were not regression neural networks of the perceptron type or were only intended for very specific purposes. Basically, each package was inspected 3 times.

1. The discard/not discard phase: depending on the package, this could be decided as easily as looking at the DESCRIPTION file or having to go through the process of making the code and seeing the results.
2. Benchmarking with template that was developed in 2019 and encapsulated in the functions of 2020, keeping notes of whether or not the package was easy to use.

### Templates for Testing Accuracy and Speed

As we inspected the packages, we developed a template for benchmarking. The structure of this template (for each package) is as follows:

1. Set up the test environment - loading of packages, setting working directory and options;
2. Summary of tested datasets;
3. Loop over datasets:
  - a. setting parameters for a specific dataset,
  - b. selecting benchmark options,
  - c. training a neural network with a tuned functions for each package,
  - d. calculation of convergence metrics (RMSE, MAE, WAE)<sup>2</sup>,
  - e. plot each training over one initial graph, then plot the best result,
  - f. add results to the appropriate existing record (\*.csv file) and
  - g. clear the environment for next loop.
4. Clearing up the environment for the next package. It is optional to print warnings.

To simplify this process, we developed tools in the **NNbenchmark** package, of which the first version was created as part of GSoC 2019. In GSoC 2020, 3 functions encapsulating the template, that had been made generic with an extensive use of the incredible `do.call` function, were added:

1. In `trainPredict_1mth1data` a neural network is trained on one dataset and then used for predictions, with several utilities. Then, the performance of the neural network is exported, plotted and/or summarized.
2. `trainPredict_1data` serves as a wrapper function for `trainPredict_1mth1data` for multiple methods.
3. `trainPredict_1pkg` serves as a wrapper function for `trainPredict_1mth1data` for multiple datasets.

A function for the summary of accuracy and speed, `NNsummary`, was also added. The package repository is <https://github.com/pkR-pkR/NNbenchmark>, with package templates in <https://github.com/pkR-pkR/NNbenchmarkTemplates>.

<sup>2</sup>We measure the quality of our model by RMSE, but the mean absolute error (MAE) and the worst absolute error (WAE) may help distinguish packages with close RMSE values. See Appendix A for definition of convergence metrics.

3. summarizing or re-reviewing the tested packages utility functions & documentation

### Ease of Use Scoring

We define an ease-of-use measure based on what we considered a user would need when using a neural network package for nonlinear regression, namely, utility functions and sufficient documentation.

1. Utilities (1 star)
  - a. a predict function exists
  - b. scaling capabilities exist
2. Sufficient documentation (2 stars)
  - a. the existence of useful example/vignette = (1 star)
    - clear, with regression = 2 points
    - unclear, examples use iris or are for classification only = 1 point
    - no examples = 0 points
  - b. input/output is clearly documented, e.g., what values are expected and returned by a function = (1 star)
    - clear input and output = 2 points
    - only one is clear = 1 point
    - both are not documented = 0 points

The ease-of-use measure ranges from 0 to 3 stars.

## Phase 3 - Collection of and analysis of results

### Results collection

Looping over the datasets using each package template, we collected results in the relevant package directories in the templates repository.

### Analysis

To rank how well a package converged and its speed, we developed the following method:

1. The results datasets are loaded into the R environment as one large list. The dataset names, package:algorithm names and all 10 run numbers, durations, and RMSE are extracted from that list.
2. For the duration score (DUR), the duration is averaged by dataset. 3 criteria for the RMSE score by dataset are calculated:
  - a. The minimum value of RMSE for each package:algorithm as a measure of their best performance;
  - b. The median value of RMSE for each package:algorithm as a measure of their average performance, without the influence of outliers;
  - c. The spread of the RMSE values for each package which is measured by the difference between the median and the minimum RMSE (d51).
3. Then, the ranks are calculated for every dataset and the results are merged into one wide dataframe.
  - a. The duration rank only depends on the duration;
  - b. For minimum RMSE values, ties are decided by duration mean, then the RMSE median;
  - c. For median RMSE values, ties are decided by the RMSE minimum, then the duration mean;
  - d. The d51 rank only depends on itself.

4. A global score for all datasets is found by a sum of the ranks (of duration, minimum RMSE, median RMSE, d51 RMSE) of each package:algorithm for each dataset.
5. The final table is the result of ranking by the global minimum RMSE scores for each package:algorithm.

To rank how easy or not a package was to use (TO BE DISCUSSED FURTHER): -  
 Functionality (util): scaling, input, output, trace - Documentation (docs): examples, structure/functions, vignettes

## Results

Table 1 gives the RMSE and time score per package and per algorithm. The full list of score is given in Table 2 in Appendix C.

### Tables

## Discussion and Recommendations

The following is a list of packages we included in this study, with brief descriptions.

1. **AMORE** (Limas et al., 2020),
2. **ANN2** (Lammers, 2020),
3. **appnn** (Família et al., 2015),
4. **autoencoder** (Dubossarsky and Tyshetskiy, 2015),
5. **automl** (Boulangé, 2020),
6. **BNN** (Jia, 2018),
7. **brnn** (Rodriguez and Gianola, 2020),
8. **Buddle** (Kim, 2020),
9. **CaDENCE** (Cannon, 2017a),
10. **cld2** (Ooms, 2018),
11. **cld3** (Ooms, 2020),
12. **condmixt** (Carreau, 2020),
13. **DamiaNN** (Siniakowicz, 2016),
14. **deep** (Mayer, 2019),
15. **deepdive** (Balakrishnan, 2020),
16. **deepnet** (Rong, 2014),
17. **deepNN** (Taylor, 2020),
18. **DNMF** (Jia and Zhang, 2015),
19. **elmNNRcpp** (Mouselimis and Gosso, 2020),
20. **ELMR** (Petrozziello, 2015),
21. **EnsembleBase** (Mahani and Sharabiani, 2016),
22. **evclass** (Denoeux, 2017),
23. **gamlss.add** (Stasinopoulos et al., 2020),
24. **gcForest** (Jing, 2018),
25. **GMDH** (Dag and Yozgatligil, 2016),
26. **GMDH2** (Dag et al., 2019),
27. **GMDHreg** (Tilve, 2020),
28. **gnn** (Hofert and Prasad, 2020),
29. **grnn** (Chasset, 2013a),
30. **h2o** (LeDell et al., 2020),
31. **hybridEnsemble** (Ballings et al., 2015),
32. **isingLenzMC** (Suzen, 2016),
33. **keras** (Allaire and Chollet, 2020),
34. **kerasR** (Arnold, 2017),
35. **leabRa** (Titz, 2017),
36. **learNN** (Quast, 2015),

**Table 1:** Result from Tested Packages

Package	Individual score		Algorithm	Global score	
	Util	Doc		Time	RMSE
AMORE	1	3.0	ADAPTgd	10	34
	1	3.0	ADAPTgdwm	17	25
	1	3.0	BATCHgd	39	40
	1	3.0	BATCHgdwm	40	39
ANN2	2	3.0	adam	16	33
	2	3.0	rmsprop	14	28
	2	3.0	sgd	12	41
automl	1	3.0	trainwgrad_adam	50	18
	1	3.0	trainwgrad_RMSprop	47	26
	1	3.0	trainwpso	57	42
brnn	2	4.0	Gauss-Newton	8	13
CaDENCE	2	3.0	optim(BFGS)	46	10
	2	3.0	pso_psoptim	54	54
	2	3.0	Rprop	56	51
caret	2	3.0	avNNet_nnet_optim(BFGS)	9	22
deepdive	2	3.0	adam	32	45
	2	3.0	gradientDescent	52	58
	2	3.0	momentum	53	56
	2	3.0	rmsProp	34	53
deepnet	1	3.0	BP	23	18
elmNNRcpp	2	3.0	ELM	1	59
ELMR	2	3.0	ELM	2	60
EnsembleBase	1	1.0	nnet_optim(BFGS)	5	12
h2o	2	2.0	first-order	51	11
keras	2	0.0	adadelata	60	47
	2	0.0	adagrad	58	36
	2	0.0	adam	42	35
	2	0.0	adamax	48	23
	2	0.0	nadam	44	36
	2	0.0	rmsprop	37	52
	2	0.0	sgd	48	43
MachineShop	1	3.0	nnet_optim(BFGS)	6	4
minpack.lm	1	3.5	Levenberg-Marquardt	13	24
monmlp	2	3.5	optimx(BFGS)	26	9
	2	3.5	optimx(Nelder-Mead)	32	46
neuralnet	1	3.0	backprop	37	48
	1	3.0	rprop-	21	21
	1	3.0	rprop+	18	20
	1	3.0	sag	41	38
	1	3.0	slr	31	30
nlsr	1	4.0	NashLM	18	1
nnet	1	3.0	optim (BFGS)	3	3
qrnn	2	3.0	nlm()	28	15
radiant.model	2	2.0	nnet_optim(BFGS)	11	7
rminer	2	3.5	nnet_optim(BFGS)	14	2
RSNNS	2	3.0	BackpropBatch	43	49
	2	3.0	BackpropChunk	26	29
	2	3.0	BackpropMomentum	25	30
	2	3.0	BackpropWeightDecay	29	32
	2	3.0	Quickprop	45	57
	2	3.0	Rprop	24	16
	2	3.0	SCG	30	17
	2	3.0	Std_Backpropagation	22	27
snnR	2	2.0	SemiSmoothNewton	7	49
traineR	1	2.5	nnet_optim(BFGS)	4	6
validann	1	4.0	optim(BFGS)	35	4
	1	4.0	optim(CG)	59	8
	1	4.0	optim(L-BFGS-B)	36	14
	1	4.0	optim(Nelder-Mead)	55	44
	1	4.0	optim(SANN)	20	55



37. **LilRhino** (Barton, 2019),
38. **minpack.lm** (Elzhov et al., 2016),
39. **MachineShop** (Smith, 2020),
40. **monmlp** (Cannon, 2017b),
41. **neural** (Nagy, 2014),
42. **neuralnet** (Fritsch et al., 2019),
43. **NeuralNetTools** (Beck, 2018),
44. **NeuralSens** (Portela González et al., 2020),
45. **NlinTS** (Hmamouche, 2020),
46. **nlshr** (Nash and Murdoch, 2019),
47. **nnet** (Ripley, 2020),
48. **nnetpredint** (Ding, 2015),
49. **nnfor** (Kourentzes, 2019),
50. **nntrf** (Aler and Valls, 2020),
51. **nnli2bRcpp** (Nikolaidis, 2020),
52. **onnx** (Tang and ONNX Authors, 2018),
53. **OptimClassifier** (Perez-Martin et al., 2020),
54. **OSTSC** (Dixon et al., 2017),
55. **pnn** (Chasset, 2013b),
56. **polyreg** (Matloff et al., 2020),
57. **predictoR** (with contributions from Diego Jimenez A. and D., 2020),
58. **qrnn** (Cannon, 2019),
59. **QuantumOps** (Resch, 2020),
60. **quarrint** (Barthelemy et al., 2016),
61. **radiant.model** (Nijs, 2020),
62. **rasclass** (Wiesmann and Quinn, 2016),
63. **rcane** (Suresh et al., 2018),
64. **regressoR** (Rodriguez R., 2019a),
65. **rminer** (Cortez, 2020),
66. **rnn** (Quast and Fichou, 2020),
67. **RSNNS** (Bergmeir, 2019),
68. **ruta** (Charte et al., 2019),
69. **simpleNeural** (Dernoncourt, 2020),
70. **snnR** (Wang et al., 2017),
71. **softmaxreg** (Ding, 2016),
72. **Sojourn.Data** (Hibbing and Lyden, 2019),
73. **spnn** (Ebrahimi, 2020),
74. **TeachNet** (Steinbuss, 2018),
75. **tensorflow** (Allaire and Tang, 2020),
76. **tfestimators** (Allaire et al., 2018),
77. **trackdem** (Bruijning et al., 2020),
78. **TrafficBDE** (Chatzopoulou et al., 2018),
79. **tsensembler** (Cerqueira et al., 2017),
80. **validann** (Humphrey, 2017),
81. **zFactor** (Reyes, 2019).

## 2nd order algorithms

Out of all the algorithms, the following second algorithms generally performed better in terms of convergence despite being set to a much lower number of iterations, to be precise a fifth or even less, than the first-order algorithms.

An important finding is that 11 out of 15 of these package::algorithms use the algorithms included in `optim` from **stats**. 2 of them, **CaDENCE**'s BFGS (Cannon, 2017a) and **validann**'s BFGS and L-BFGS-B (Humphrey, 2017), do so with no intermediate package. However, it is not clearly stated in **CaDENCE**'s documentation that `optim`'s BFGS algorithm is used and not one of the other algorithms. Furthermore, the mention of Nelder-Mead in the

documentation might lead users to believe that `optim`'s Nelder-Mead is used instead. Speed and variation between results are also not as good as other package's that use `optim`. This could be because **CaDENCE** is intended for probabilistic nonlinear models with a full title of "Conditional Density Estimation Network Construction and Evaluation". On the other hand, **validann** is clearly a package that allows a user to use all `optim`'s algorithms. **validann::L-BFGS-B** ranks lower than **validann::BFGS** in just about everything for most runs, despite the former being more sophisticated. This is probably due to our efforts to harmonize parameters under-utilizing the possibilities of the L-BFGS-B algorithm. Both **CaDENCE** and **validann**'s BFGS are outperformed by **nnet**, especially in terms of speed.

**nnet** (Ripley, 2020) differs from the two packages because it uses the C code from `optim` (converted earlier from Fortran) instead of calling `optim` from R. It also only implements the BFGS algorithm. This could be what allows it to be faster. **nnet** is only beaten by the Extreme Learning Machine (ELM) algorithms in terms of speed. However, there is a larger variation between results (see the RMSEd51 in Appendix C) in comparison to **validann::BFGS**. Most likely, the different default values are the cause of this. For instance, **nnet** uses a range of initial random weights of 0.7 while **validann** uses a value of 0.5. In spite of these results, the real reason most authors or users are likely to choose **nnet** is because it ships with base R and is even mentioned as the very first package in CRAN's task view for machine learning (<https://CRAN.R-project.org/view=MachineLearning>).

Our research found that 6 of the 11 packages that use `optim` do so through **nnet**. Moreover, 8 packages for neural networks, though not tested, use **nnet**. The total number of **nnet** dependencies found through a search through the offline database of CRAN with **RWsearch** came up with 136 packages, although some might be using **nnet** for the multinomial log-linear models, not neural networks. As for the ones we tested, there were several similarities and differences. The packages that use **nnet** for neural networks are often meta packages with a host of other machine learning algorithms. **caret** (Kuhn, 2020), also mentioned in the taskview, boasts 238 methods with around 13 different neural network packages with somewhat deceptively simple name of "Classification and Regression Training". It has many pre-processing utilities available, as well as other tools.

**EnsembleBase** (Mahani and Sharabiani, 2016) maybe useful for those who wish to make ensembles and test a grid of parameters although the documentation. **MachineShop** (Smith, 2020) has 51 algorithms, with some additional information about the response variable types in the second vignette, functions for preprocessing and tuning, performance assesment, and presentation of results. **radiant.model** (Nijs, 2020) has an unchangeable maxit of 10000 in the original package. Perhaps the author thought this was reasonable as source of the algorithm, **nnet**, is quite fast. We changed this to harmonize the parameters. **rminer** (Cortez, 2020) is the only package dependant on **nnet** that ranks above **nnet** at number 2 for minimum RMSE, and even number 1 in some runs. It also ranks number 1 on the other accuracy measures (median RMSE, minimum MAE, minimum WAE) and is only behind **deepdive** and **minpack.lm** in terms of results that are consistent and do not vary (RMSEd51). The difference is probably from the change of maximum allowable weights in **rminer** to 10000 from 1000 in **nnet**, which is also probably the reason it its fits are slower. **traineR** (Rodriguez R., 2019b) claims to unify the different methods of creating models between several learning algorithms.

Something worth noting is that **nnet** and **validann** do not have external normalization, and it is especially recommended for **validann**. However, some of the packages dependent on **nnet** do have this utility and it is included in the scoring for ease of use. With **NNbenchmark**, this is done through setting `scale = TRUE` in the function `prepare.ZZ`. Note that scaling might lead to complicating the constraints which is not always worth it. Regardless, users might want to have the utility and most likely want a clear explanation of the method chosen to center the variables. Scaling is one of the things that **optimx** (Nash and Varadhan, 2020) incorporates in an attempt to make a more useful version of `optim` that only allows for changing the sign of the function which might not even be considered as scaling (Nash, 2014).

**optimx** itself still has several algorithms yet to be used by neural network packages,

although it does have 45 packages dependent on it at the moment. [monmlp](#) (Cannon, 2017b) of all the packages, only monmlp uses optimx for its 2 algorithms: BFGS and Nelder-Mead. It's implementation of BFGS does not particularly stand out in comparison to the ones from optim. Note however, that the author, Alex J. Cannon who is also the author of CaDENCE, has once again created a package meant to fill a certain niche. This package is intended for multi-layer perceptrons with optional partial monotonicity constraints. GAM-style effect plots are also an interesting utility. Another package by Cannon is [qrnn](#) (Cannon, 2019) which uses yet another algorithm: nlm(), a "Newton-type" algorithm from stats. Although it's performance is at the bottom of second order algorithms, sometimes even being beaten by first order algorithms, this could also be because of what the package is intended for. qrnn is designed for quantile regression neural networks, with several options. Cannon has included automatic scaling for all 3 of his packages.

### Recommended: 1st order algorithms

validann optim CG -slow RSNNS SCG h2o back-propagation RSNNS Rprop ANN2 adam CaDENCE Rprop -SLOW deepnet BP AMORE ADAPTgdwm AMORE ADAPTgd ANN2 sgd automl trainwgrad ANN2 rmsprop RSNNS BackpropChunk RSNNS BackWeightDecay RSNNS Std\_Backpropagation RSNNS BackpropMomentum automl trainwpso validann optim NelderMead snnR Semi Smooth Newton RSNNS BackpropBatch validann optim SANN monmlp optimx Nelder Mead

### Not recommended: 1st order algorithms <- DISCUSS CUTOFF

By package ELMR, elmNNRcpp - fast ELM algorithms. Unfortunately, can't finetune, does not converge well. neuralnet: a large ammount of iterations, slow, erratic failures tensorflow: NOT EASY TO USE, subsequently keras, tfestimators, ruta ... user needs to understand the language However, advanced users might be able to highly specify a neural network to their needs (customization?)

By algorithm: neuralnet rprop+ neuralnet rprop- neuralnet slr - once ranked well with 100000 iterations AMORE BATCHgd CaDENCE pso psoptim - need to reconfigure? elmNNRcpp - fast, no iterations RSNNS Quickprop (?) AMORE BATCHgdwm tensorflow MomentumOptimizer tensorflow AdamOptimizer ELMR - fast, no iterations tensorflow GradientDescentOptimizer keras rmsprop keras adagrad keras sgd keras adadelta tensorflow AdagradOptimizer keras adam tensorflow FtrlOptimizer neuralnetwork sag tensorflow AdadeltaOptimizer neuralnet backprop - note, might not actually reflect standings, somehow from template to template the learning rate disappeared. Will fix this in future runs

### Untested => TO DO - LIST

## Conclusion and perspective

??JN: Can we start to put in some major findings? i.e., important positive findings, big negatives?

### Positives (no particular order)

1. We are happy to note the existence of neural network packages in R with algorithms that converge well.
- **nnet**, which uses ?? need font choice?? optim's BFGS method, is already often chosen to represent neural networks for packages that are either a collection of independent machine learning algorithms, ensembles, or even applications in a field such as ... ?? need to complete sentence??. JN??: Why is this positive? ==> B: its meant to be part of the above, because nnet's algorithm converged well in our tests, thus the fact that

it is being used by other packages is a plus? See the part about `nnet` & packages that depend on it in the results

- R users have access to a wide variety of neural network methods, including from libraries of other programming languages and using many different types of algorithms. ?? have we defined hyperparameters?? hyperparameters, and uses

## Negatives

- We are disappointed that many of the packages we reviewed had poor documentation.
- It would be helpful if there were more packages with (different) second order algorithms. A number of the
- We often found it difficult to discover what default starting values were used for model parameters, or

## Future work

As the field of neural networks continue to grow, there will always be more algorithms to validate. For current algorithms in R, our research should be extended to encompass more types of neural networks and their data formats (classifier neural networks, recurrent neural networks, and so on). Different rating schemes and different parameters for package functions can also be tried out.

- The dreamed NN package: Recommendation to package authors
- Conclusion

## Acknowledgements

This work was possible due to the support of the Google Summer of Code initiative for R during years 2019 and 2020. Students Salsabila Mahdi (2019 and 2020) and Akshaj Verma (2019) are grateful to Google for the financial support.

## Bibliography

- R. Aler and J. Valls. *nntrf: Supervised Data Transformation by Means of Neural Network Hidden Layers*, 2020. URL <https://CRAN.R-project.org/package=nntrf>. R package version 0.1.3. [p9]
- J. Allaire and F. Chollet. *keras: R Interface to 'Keras'*, 2020. URL <https://CRAN.R-project.org/package=keras>. R package version 2.3.0.0. [p7]
- J. Allaire and Y. Tang. *tensorflow: R Interface to 'TensorFlow'*, 2020. URL <https://CRAN.R-project.org/package=tensorflow>. R package version 2.2.0. [p9]
- J. Allaire, Y. Tang, K. Ushey, and K. Kuo. *tfestimators: Interface to 'TensorFlow' Estimators*, 2018. URL <https://CRAN.R-project.org/package=tfestimators>. R package version 1.9.1. [p9]
- T. Arnold. *kerasR: R Interface to the Keras Deep Learning Library*, 2017. URL <https://CRAN.R-project.org/package=kerasR>. R package version 0.6.1. [p7]
- R. Balakrishnan. *deepdive: Deep Learning for General Purpose*, 2020. URL <https://CRAN.R-project.org/package=deepdive>. R package version 1.0.1. [p7]
- M. Ballings, D. Vercamer, and D. Van den Poel. *hybridEnsemble: Build, Deploy and Evaluate Hybrid Ensembles*, 2015. URL <https://CRAN.R-project.org/package=hybridEnsemble>. R package version 1.0.0. [p7]

- J. Barthelemy, T. Carletti, L. Collier, V. Hallet, M. Moriame, and A. Sartenaer. *quarrint: Interaction Prediction Between Groundwater and Quarry Extension Using Discrete Choice Models and Artificial Neural Networks*, 2016. URL <https://CRAN.R-project.org/package=quarrint>. R package version 1.0.0. [p9]
- T. Barton. *LilRhino: For Implementation of Feed Reduction, Learning Examples, NLP and Code Management*, 2019. URL <https://CRAN.R-project.org/package=LilRhino>. R package version 1.2.0. [p9]
- M. W. Beck. *NeuralNetTools: Visualization and Analysis Tools for Neural Networks*, 2018. URL <https://CRAN.R-project.org/package=NeuralNetTools>. R package version 1.5.2. [p9]
- C. Bergmeir. *RSNNS: Neural Networks using the Stuttgart Neural Network Simulator (SNNS)*, 2019. URL <https://CRAN.R-project.org/package=RSNNS>. R package version 0.4-12. [p9]
- A. Boulangé. *automl: Deep Learning with Metaheuristic*, 2020. URL <https://CRAN.R-project.org/package=automl>. R package version 1.3.2. [p7]
- M. Bruijning, M. D. Visser, C. A. Hallmann, and E. Jongejans. *trackdem: Particle Tracking and Demography*, 2020. URL <https://CRAN.R-project.org/package=trackdem>. R package version 0.5.2. [p9]
- A. J. Cannon. *CaDENCE: Conditional Density Estimation Network Construction and Evaluation*, 2017a. URL <https://CRAN.R-project.org/package=CaDENCE>. R package version 1.2.5. [p7, 9]
- A. J. Cannon. *monmlp: Multi-Layer Perceptron Neural Network with Optional Monotonicity Constraints*, 2017b. URL <https://CRAN.R-project.org/package=monmlp>. R package version 1.1.5. [p9, 11]
- A. J. Cannon. *qrnn: Quantile Regression Neural Network*, 2019. URL <https://CRAN.R-project.org/package=qrnn>. R package version 2.0.5. [p9, 11]
- J. Carreau. *condmixt: Conditional Density Estimation with Neural Network Conditional Mixtures*, 2020. URL <https://CRAN.R-project.org/package=condmixt>. R package version 1.1. [p7]
- V. Cerqueira, L. Torgo, and C. Soares. Arbitrated ensemble for solar radiation forecasting. *International Work-Conference on Artificial Neural Networks*, pages 720–732, 2017. The R package *tsensembler* has been archived as of July 2020 because it has not been maintained. [p9]
- T. Chai and R. R. Draxler. Root mean square error (rmse) or mean absolute error (mae)?—arguments against avoiding rmse in the literature. *Geoscientific model development*, 7(3): 1247–1250, 2014. [p3]
- D. Charte, F. Charte, and F. Herrera. *ruta: Implementation of Unsupervised Neural Architectures*, 2019. URL <https://CRAN.R-project.org/package=ruta>. R package version 1.1.0. [p9]
- P.-O. Chasset. *grnn: General regression neural network*, 2013a. URL <https://CRAN.R-project.org/package=grnn>. R package version 0.1.0. [p7]
- P.-O. Chasset. *pnn: Probabilistic neural networks*, 2013b. URL <https://CRAN.R-project.org/package=pnn>. R package version 1.0.1. [p9]
- A. Chatzopoulou, K. Koupidis, and C. Bratsas. *TrafficBDE: Traffic Status Prediction in Urban Places using Neural Network Models*, 2018. URL <https://CRAN.R-project.org/package=TrafficBDE>. R package version 0.1.0. [p9]
- P. Cortez. *rminer: Data Mining Classification and Regression Methods*, 2020. URL <https://CRAN.R-project.org/package=rminer>. R package version 1.4.5. [p9, 10]



- O. Dag and C. Yozgatligil. *GMDH: Short Term Forecasting via GMDH-Type Neural Network Algorithms*, 2016. URL <https://CRAN.R-project.org/package=GMDH>. R package version 1.6. [p7]
- O. Dag, E. Karabulut, and R. Alpar. *GMDH2: Binary Classification via GMDH-Type Neural Network Algorithms*, 2019. URL <https://CRAN.R-project.org/package=GMDH2>. R package version 1.5. [p7]
- T. Denoeux. *evclass: Evidential Distance-Based Classification*, 2017. URL <https://CRAN.R-project.org/package=evclass>. R package version 1.1.1. [p7]
- D. DERNONCOURT. *simpleNeural: An Easy to Use Multilayer Perceptron*, 2020. URL <https://CRAN.R-project.org/package=simpleNeural>. R package version 0.1.3. [p9]
- X. Ding. *nnetpredint: Prediction Intervals of Multi-Layer Neural Networks*, 2015. URL <https://CRAN.R-project.org/package=nnetpredint>. R package version 1.2. [p9]
- X. Ding. *softmaxreg: Training Multi-Layer Neural Network for Softmax Regression and Classification*, 2016. URL <https://CRAN.R-project.org/package=softmaxreg>. R package version 1.2. [p9]
- M. Dixon, D. Klabjan, and L. Wei. *OSTSC: Over Sampling for Time Series Classification*, 2017. URL <https://CRAN.R-project.org/package=OSTSC>. R package version 0.0.1. [p9]
- E. Dubossarsky and Y. Tyshetskiy. *autoencoder: Sparse Autoencoder for Automatic Learning of Representative Features from Unlabeled Data*, 2015. URL <https://CRAN.R-project.org/package=autoencoder>. R package version 1.1. [p7]
- R. Ebrahimi. *spnn: Scale Invariant Probabilistic Neural Networks*, 2020. URL <https://CRAN.R-project.org/package=spnn>. R package version 1.2.1. [p9]
- T. V. Elzhov, K. M. Mullen, A.-N. Spiess, and B. Bolker. *minpack.lm: R Interface to the Levenberg-Marquardt Nonlinear Least-Squares Algorithm Found in MINPACK, Plus Support for Bounds*, 2016. URL <https://CRAN.R-project.org/package=minpack.lm>. R package version 1.2-1. [p9]
- C. Família, S. R. Dennison, A. Quintas, and D. A. Phoenix. *appnn: Amyloid Propensity Prediction Neural Network*, 2015. URL <https://CRAN.R-project.org/package=appnn>. R package version 1.0-0. [p7]
- S. Fritsch, F. Guenther, and M. N. Wright. *neuralnet: Training of Neural Networks*, 2019. URL <https://CRAN.R-project.org/package=neuralnet>. R package version 1.44.2. [p9]
- P. R. Hibbing and K. Lyden. *Sojourn.Data: Supporting Objects for Sojourn Accelerometer Methods*, 2019. URL <https://CRAN.R-project.org/package=Sojourn.Data>. R package version 0.1.0. [p9]
- Y. Hmamouche. *NlinTS: Models for Non Linear Causality Detection in Time Series*, 2020. URL <https://CRAN.R-project.org/package=NlinTS>. R package version 1.4.2. [p9]
- M. Hofert and A. Prasad. *gnn: Generative Neural Networks*, 2020. URL <https://CRAN.R-project.org/package=gnn>. R package version 0.0-2. [p7]
- G. B. Humphrey. *validann: Validation Tools for Artificial Neural Networks*, 2017. URL <https://CRAN.R-project.org/package=validann>. R package version 1.2.1. [p9]
- B. Jia. *BNN: Bayesian Neural Network for High-Dimensional Nonlinear Variable Selection*, 2018. URL <https://CRAN.R-project.org/package=BNN>. R package version 1.0.2. [p7]
- Z. Jia and X. Zhang. *DNMF: Discriminant Non-Negative Matrix Factorization*, 2015. URL <https://CRAN.R-project.org/package=DNMF>. R package version 1.3. [p7]

- X. Jing. *gcForest: Deep Forest Model*, 2018. URL <https://CRAN.R-project.org/package=gcForest>. R package version 0.2.7. [p7]
- P. Kiener. *RWsearch: Lazy Search in R Packages, Task Views, CRAN, the Web. All-in-One Download*, 2020. URL <https://CRAN.R-project.org/package=RWsearch>. R package version 4.8.0. [p4]
- J. Kim. *Buddle: A Deep Learning for Statistical Classification and Regression Analysis with Random Effects*, 2020. URL <https://CRAN.R-project.org/package=Buddle>. R package version 2.0.1. [p7]
- N. Kourentzes. *nnfor: Time Series Forecasting with Neural Networks*, 2019. URL <https://CRAN.R-project.org/package=nnfor>. R package version 0.9.6. [p9]
- M. Kuhn. *caret: Classification and Regression Training*, 2020. URL <https://CRAN.R-project.org/package=caret>. R package version 6.0-86. [p10]
- B. Lammers. *ANN2: Artificial Neural Networks for Anomaly Detection*, 2020. URL <https://CRAN.R-project.org/package=ANN2>. R package version 2.3.3. [p7]
- E. LeDell, N. Gill, S. Aiello, A. Fu, A. Candel, C. Click, T. Kraljevic, T. Nykodym, P. Aboyoun, M. Kurka, and M. Malohlava. *h2o: R Interface for the 'H2O' Scalable Machine Learning Platform*, 2020. URL <https://CRAN.R-project.org/package=h2o>. R package version 3.30.0.1. [p7]
- M. C. Limas, J. B. O. Mere, A. G. Marcos, F. J. M. de Pison Ascacibar, A. V. P. Espinoza, F. A. Elias, and J. M. P. Ramos. *AMORE: Artificial Neural Network Training and Simulating*, 2020. URL <https://CRAN.R-project.org/package=AMORE>. R package version 0.2-16. [p7]
- A. S. Mahani and M. T. Sharabiani. *EnsembleBase: Extensible Package for Parallel, Batch Training of Base Learners for Ensemble Modeling*, 2016. URL <https://CRAN.R-project.org/package=EnsembleBase>. R package version 1.0.2. [p7, 10]
- N. Matloff, X. Cheng, P. Mohanty, B. Khomtchouk, M. Kotila, R. Yancey, R. Tucker, A. Zhao, and T. Jiang. *polyreg: Polynomial Regression*, 2020. URL <https://CRAN.R-project.org/package=polyreg>. R package version 0.6.7. [p9]
- B. L. Mayer. *deep: A Neural Networks Framework*, 2019. URL <https://CRAN.R-project.org/package=deep>. R package version 0.1.0. [p7]
- L. Mouselimis and A. Gosso. *elmNNRcpp: The Extreme Learning Machine Algorithm*, 2020. URL <https://CRAN.R-project.org/package=elmNNRcpp>. R package version 1.0.2. [p7]
- A. Nagy. *neural: Neural Networks*, 2014. URL <https://CRAN.R-project.org/package=neural>. R package version 1.4.2.2. [p9]
- J. C. Nash. *Nonlinear Parameter Optimization Using R Tools*. John Wiley & Sons: Chichester, May 2014. ISBN 978-1-118-56928-3. Companion website (see <http://www.wiley.com/legacy/wileychi/nash/>). [p10]
- J. C. Nash and D. Murdoch. *nlsr: Functions for Nonlinear Least Squares Solutions*, 2019. URL <https://CRAN.R-project.org/package=nlsr>. R package version 2019.9.7. [p9]
- J. C. Nash and R. Varadhan. *optimx: Expanded Replacement and Extension of the 'optim' Function*, 2020. URL <https://CRAN.R-project.org/package=optimx>. R package version 2020-4.2. [p10]
- V. Nijs. *radiant.model: Model Menu for Radiant: Business Analytics using R and Shiny*, 2020. URL <https://CRAN.R-project.org/package=radiant.model>. R package version 1.3.10. [p9, 10]
- V. Nikolaidis. *nnlib2Rcpp: A Collection of Neural Networks*, 2020. URL <https://CRAN.R-project.org/package=nnlib2Rcpp>. R package version 0.1.4. [p9]

- J. Ooms. *cld2: Google's Compact Language Detector 2*, 2018. URL <https://CRAN.R-project.org/package=cld2>. R package version 1.2. [p7]
- J. Ooms. *cld3: Google's Compact Language Detector 3*, 2020. URL <https://CRAN.R-project.org/package=cld3>. R package version 1.3. [p7]
- A. Perez-Martin, A. Perez-Torregrosa, M. Vaca-Lamata, and A. J. Verdu-Jover. *OptimClassifier: Create the Best Train for Classification Models*, 2020. URL <https://CRAN.R-project.org/package=OptimClassifier>. R package version 0.1.5. [p9]
- A. Petrozziello. *ELMR: Extreme Machine Learning (ELM)*, 2015. URL <https://CRAN.R-project.org/package=ELMR>. R package version 1.0. [p7]
- J. Portela González, A. Muñoz San Roque, and J. Pizarroso Gonzalo. *NeuralSens: Sensitivity Analysis of Neural Networks*, 2020. URL <https://CRAN.R-project.org/package=NeuralSens>. R package version 0.2.1. [p9]
- B. Quast. *learNN: Examples of Neural Networks*, 2015. URL <https://CRAN.R-project.org/package=learNN>. R package version 0.2.0. [p7]
- B. Quast and D. Fichou. *rnn: Recurrent Neural Network*, 2020. URL <https://CRAN.R-project.org/package=rnn>. R package version 1.4.0. [p9]
- S. Resch. *QuantumOps: Performs Common Linear Algebra Operations Used in Quantum Computing and Implements Quantum Algorithms*, 2020. URL <https://CRAN.R-project.org/package=QuantumOps>. R package version 3.0.1. [p9]
- A. R. Reyes. *zFactor: Calculate the Compressibility Factor 'z' for Hydrocarbon Gases*, 2019. URL <https://CRAN.R-project.org/package=zFactor>. R package version 0.1.9. [p9]
- B. Ripley. *nnet: Feed-Forward Neural Networks and Multinomial Log-Linear Models*, 2020. URL <https://CRAN.R-project.org/package=nnet>. R package version 7.3-14. [p9, 10]
- P. P. Rodriguez and D. Gianola. *brnn: Bayesian Regularization for Feed-Forward Neural Networks*, 2020. URL <https://CRAN.R-project.org/package=brnn>. R package version 0.8. [p7]
- O. Rodriguez R. *regressoR: Regression Data Analysis System*, 2019a. URL <https://CRAN.R-project.org/package=regressoR>. R package version 1.1.9. [p9]
- O. Rodriguez R. *traineR: Predictive Models Homologator*, 2019b. URL <https://CRAN.R-project.org/package=traineR>. R package version 1.0.0. [p10]
- X. Rong. *deepnet: deep learning toolkit in R*, 2014. URL <https://CRAN.R-project.org/package=deepnet>. R package version 0.2. [p7]
- D. Siniakowicz. *DamiaNN: Neural Network Numerai*, 2016. URL <https://CRAN.R-project.org/package=DamiaNN>. R package version 1.0.0. [p7]
- B. J. Smith. *MachineShop: Machine Learning Models and Tools*, 2020. URL <https://CRAN.R-project.org/package=MachineShop>. R package version 2.5.0. [p9, 10]
- M. Stasinopoulos, B. Rigby, V. Voudouris, and D. Kiose. *gamlss.add: Extra Additive Terms for Generalized Additive Models for Location Scale and Shape*, 2020. URL <https://CRAN.R-project.org/package=gamlss.add>. R package version 5.1-6. [p7]
- G. Steinbuss. *TeachNet: Fits Neural Networks to Learn About Backpropagation*, 2018. URL <https://CRAN.R-project.org/package=TeachNet>. R package version 0.7.1. [p9]
- A. Suresh, S. Acharekar, H. Chao, and S. Y. Biradar. *rcane: Different Numeric Optimizations to Estimate Parameter Coefficients*, 2018. URL <https://CRAN.R-project.org/package=rcane>. R package version 1.0. [p9]
- M. Suzen. *isingLenzMC: Monte Carlo for Classical Ising Model*, 2016. URL <https://CRAN.R-project.org/package=isingLenzMC>. R package version 0.2.5. [p7]



- Y. Tang and ONNX Authors. *onnx: R Interface to 'ONNX'*, 2018. URL <https://CRAN.R-project.org/package=onnx>. R package version 0.0.2. [p9]
- B. Taylor. *deepNN: Deep Learning*, 2020. URL <https://CRAN.R-project.org/package=deepNN>. R package version 1.0. [p7]
- M. V. Tilve. *GMDHreg: Regression using GMDH Algorithms*, 2020. URL <https://CRAN.R-project.org/package=GMDHreg>. R package version 0.2.1. [p7]
- J. Titz. *leabRa: The Artificial Neural Networks Algorithm Leabra*, 2017. URL <https://CRAN.R-project.org/package=leabRa>. R package version 0.1.0. [p7]
- Y. Wang, P. Lin, Z. Chen, Z. Bao, and G. J. M. Rosa. *snnR: Sparse Neural Networks for Genomic Selection in Animal Breeding*, 2017. URL <https://CRAN.R-project.org/package=snnR>. R package version 1.0. [p9]
- D. Wiesmann and D. Quinn. *rasclass: Supervised Raster Image Classification*, 2016. URL <https://CRAN.R-project.org/package=rasclass>. R package version 0.2.2. [p9]
- C. J. Willmott and K. Matsuura. Advantages of the mean absolute error (mae) over the root mean square error (rmse) in assessing average model performance. *Climate research*, 30(1): 79–82, 2005. [p3]
- O. R. R. with contributions from Diego Jimenez A. and A. N. D. *predictoR: Predictive Data Analysis System*, 2020. URL <https://CRAN.R-project.org/package=predictoR>. R package version 1.1.3. [p9]
- S. N. Wood. Fast stable restricted maximum likelihood and marginal likelihood estimation of semiparametric generalized linear models. *Journal of the Royal Statistical Society: Series B (Statistical Methodology)*, 73(1):3–36, 2011. [p4]

## Appendix

### Appendix A

Consider a set of observations  $y_i$  and its corresponding predictions  $\hat{y}_i$  for  $i = 1, \dots, n$ . The three metrics used were:

$$MAE = \frac{1}{n} \sum_{i=1}^n |y_i - \hat{y}_i|, RMSE = \frac{1}{n} \sqrt{\sum_{i=1}^n (y_i - \hat{y}_i)^2}, WAE = \frac{1}{n} \max_{i=1, \dots, n} |y_i - \hat{y}_i|.$$

These values represent the absolute, the squared and the maximum norm of residual vectors.

### Appendix B

We define three smooth functions for Simon Wood's test dataset

$$f_0 = 5 * \sin(2\pi x), f_1 = \exp(3 * x) - 7, f_2 = 0.5x^{11} * (10(1 - x))^6 - 10(10 * x)^3 * (1 - x)^{10},$$

$$f_3 = 15 \exp(-5|x - 1/2|) - 6, f_4 = 2 - 1_{(x \leq 1/3)}(6 * x)^3 - 1_{(x > 2/3)}(6 - 6 * x)^3 - 1_{(2/3 > x > 1/3)}(8 + 2 \sin(9 * (x - 1/2)))$$

### Appendix C

### Appendix D

### Appendix ??

```
library(NNbenchmark)
nrep <- 5
```

**Table 2:** All convergence scores per package:algorithm

Num	Input parameter			Score			
	Input format	Maxit	Learn. rate	RMSE median	RMSE d51	MAE	WAE
1	x & y	1000	0.01	24	8	26	19
2	x & y	1000	0.01	22	28	17	26
3	x & y	10000	0.1	37	24	42	31
4	x & y	10000	0.1	33	14	36	27
5	x & y	1000	0.01	27	26	28	23
6	x & y	1000	0.01	26	33	27	22
7	x & y	1000	0.01	36	20	35	28
8	x & y	1000	0.01	20	35	16	19
9	x & y	1000	0.01	31	50	29	38
10	x & y	1000	-	40	49	40	37
11	x & y	200	-	11	9	12	11
12	x & y	200	-	28	48	23	39
13	x & y	1000	-	56	56	54	56
14	x & y	1000	0.01	54	60	52	58
15	x & y	200	-	13	30	14	12
16	x & y	10000	0.4	41	1	37	44
17	x & y	10000	0.8	57	2	57	53
18	x & y	1000	0.8	52	3	53	51
19	x & y	1000	0.8	45	4	47	50
20	x & y	1000	0.8	18	38	24	17
21	x & y	-	-	59	55	59	59
22	fmla & data	-	-	60	54	60	60
23	x & y	200	-	15	33	15	15
24	"y" & data	10000	0.01	7	7	8	8
25	x & y	10000	0.1	48	27	51	41
26	x & y	10000	0.1	42	51	41	33
27	x & y	10000	0.1	28	44	30	25
28	x & y	10000	0.1	16	19	20	16
29	x & y	10000	0.1	38	58	39	40
30	x & y	10000	0.1	54	57	55	54
31	x & y	10000	0.1	44	47	43	43
32	fmla & data	200	-	9	20	10	7
33	full fmla & data	200	-	18	5	19	14
34	x & y	200	-	10	17	9	10
35	x & y	10000	-	46	46	43	47
36	fmla & data	100000	0.001	50	11	48	45
37	fmla & data	100000	-	21	41	22	18
38	fmla & data	100000	-	23	40	21	24
39	fmla & data	100000	-	50	59	46	52
40	fmla & data	100000	-	38	37	38	46
41	full fmla & data	200	-	3	16	3	6
42	x & y	200	-	2	17	2	3
43	x & y	200	-	14	22	7	35
44	"y" & data	200	-	8	32	11	9
45	fmla & data	200	-	1	6	1	1
46	x & y	10000	0.1	47	25	50	49
47	x & y	1000	-	34	41	32	34
48	x & y	1000	-	35	38	34	30
49	x & y	1000	-	30	43	33	32
50	x & y	10000	-	58	36	58	57
51	x & y	1000	-	24	51	25	29
52	x & y	1000	-	16	22	18	19
53	x & y	1000	0.1	32	30	31	36
54	x & y	200	-	48	13	49	47
55	fmla & data	200	-	5	15	6	2
56	x & y	200	-	4	11	4	5
57	x & y	1000	-	6	10	5	4
58	x & y	200	-	12	29	13	12
59	x & y	10000	-	43	45	45	41
60	x & y	1000	-	53	53	56	55

Table 3: Review of Ommitted Packages

No	Name (package)	Category	Comment
1	<b>appnn</b>	AP	This package provides a feed forward neural network to predict the amyloidogenicity propensity of polypeptide sequences
2	<b>autoencoder</b>	AP	This package provides a sparse autoencoder, an unsupervised algorithm that learns useful features from the data its given
3	<b>BNN</b>	RE*	This package uses a feed forward neural network to perform regression as provided in the examples, however, it is unclear whether it fits the form of perceptron that is the scope of our research. Moreover, it states that it is intended for variable selection. Although how exactly the package would be used to do so isn't accessible in the package, especially considering the source code is based on .c code that users of R might not understand. It's performance is slow, which may have to do with the 100.000 iterations it needs, although quite accurate for simple datasets.
4	<b>Buddle</b>	RE**	(errors)
5	<b>cld2</b>	00	
6	<b>cld3</b>	AP	
7	<b>condmixt</b>	AP	
8	<b>deep</b>	CL	
9	<b>DALEX2</b>	00	removed keyword, included in 2019
10	<b>DamiaNN</b>	RE**	(errors) exported functions, still doesn't work
11	<b>DChaos</b>	??	removed keyword for some reason, need to check out!
12	<b>deepNN</b>	RE**	(errors) I/O weird, ragged vector array
13	<b>DNMF</b>	AP	
14	<b>evclass</b>	CL	
15	<b>gamlss.add</b>	RE	there is some code but dist not appropriate
16	<b>gcForest</b>	00	
17	<b>GMDH</b>	TS	
18	<b>GMDH2</b>	CL	
19	<b>GMDHreg</b>	RE*	
20	<b>grnn</b>	RE**	
21	<b>hybridEnsemble</b>	??	
22	<b>isingLenzMC</b>	AP	
23	<b>leabRa</b>	??	
24	<b>learNN</b>	??	
25	<b>LilRhino</b>	AP	
26	<b>neural</b>	CL	
27	<b>NeuralNetTools</b>	UT	tools for neural networks
28	<b>NeuralSens</b>	UT	tools for neural networks
29	<b>NlinTS</b>	TS	Time Series
30	<b>nnetpredint</b>	UT	confidence intervals for NN
31	<b>nnfor</b>	TS	Times Series, uses neuralnet
32	<b>nntrf</b>	UT	
33	<b>onnx</b>		provides an open source format
34	<b>OptimClassifier</b>		choose classifier parameters, nnet
35	<b>OSTSC</b>		solving oversampling classification
36	<b>passt</b>		
36	<b>pnn</b>		Probabilistic
37	<b>polyreg</b>		polyregression as alternative to NN
38	<b>predictoR</b>		shiny interface, neuralnet
39	<b>ProcData</b>		
40	<b>QuantumOps</b>		classifies MNIST, Schuld (2018), removed keyword, in 2019
41	<b>quarrint</b>		specified classifier for quarry data
42	<b>rasclass</b>		classifier for raster images, nnet?
43	<b>rcane</b>		
44	<b>regressoR</b>		a manual rich version of predictoR
45	<b>rnn</b>		Recurrent
46	<b>RTextTools</b>		
47	<b>ruta</b>		
48	<b>simpleNeural</b>		
49	<b>softmaxreg</b>		
50	<b>Sojourn.Data</b>		sojourn Accelerometer methods, nnet?
51	<b>spnn</b>		classifier, probabilistic
52	<b>studyStrap</b>		
53	<b>TeachNet</b>		classifier, selfbuilt, slow
54	<b>tensorflow</b>		
55	<b>tfestimators</b>		
56	<b>trackdem</b>		classifier for particle tracking
57	<b>TrafficBDE</b>	RE*	
58	<b>tsfgrnn</b>		
59	<b>yap</b>		
60	<b>yager</b>	RE*	
61	<b>zFactor</b>	AP	'compressibility' of hydrocarbon gas

```
odir <- tempdir()
```

```
library(nnet)
```

```
nnet.method <- "BFGS"
```





```
hyperParams.nnet <- function(...) {
```

```
      return (list(iter=200, trace=FALSE))
    }
    NNtrain.nnet <- function(x, y, dataxy, formula, neur, method, hyperParams, ...) {

      hyper_params <- do.call(hyperParams, list(...))

      NNreg <- nnet::nnet(x, y, size = neur, linout = TRUE, maxit = hyper_params$iter, trace=hyper_params$trace)
      return(NNreg)
    }
    NNpredict.nnet <- function(object, x, ...) { predict(object, newdata=x) }
    NNclose.nnet <- function() { if("package:nnet" %in% search())
                                detach("package:nnet", unload=TRUE) }
    nnet.prepareZZ <- list(xdmv = "d", ydmv = "v", zdm = "d", scale = TRUE)

    res <- trainPredict_1pkg(4:5, pkgname = "nnet", pkgfun = "nnet", nnet.method,
      prepareZZ.arg = nnet.prepareZZ, nrep = nrep, doplot = TRUE,
      csvfile = FALSE, rdafile = FALSE, odir = odir, echo = FALSE)
```

**mRef153\_nnet::nnet\_BFGS****mRef153\_nnet::nnet\_BFGS****uDmod1\_nnet::nnet\_BFGS****uDmod1\_nnet::nnet\_BFGS**

Salsabila Mahdi  
Universitas Syiah Kuala

*JL. Syech Abdurrauf No.3, Aceh 23111, Indonesia*  
[bila.mahdi@mhs.unsyiah.ac.id](mailto:bila.mahdi@mhs.unsyiah.ac.id)

*Akshaj Verma*  
*Manipal Institute of Technology*  
*Manipal, Karnataka, 576104, India*  
[akshajverma7@gmail.com](mailto:akshajverma7@gmail.com)

*Christophe Dutang*  
*University Paris-Dauphine, University PSL, CNRS, CEREMADE*  
*Place du Maréchal de Lattre de Tassigny, 75016 Paris, France*  
[dutang@ceremade.dauphine.fr](mailto:dutang@ceremade.dauphine.fr)

*Patrice Kiener*  
*InModelia*  
*5 rue Malebranche, 75005 Paris, France*  
[patrice.kiener@inmodelia.com](mailto:patrice.kiener@inmodelia.com)

*John C. Nash*  
*Telfer School of Management, University of Ottawa*  
*55 Laurier Avenue East, Ottawa, Ontario K1N 6N5 Canada*  
[nashjc@uottawa.ca](mailto:nashjc@uottawa.ca)