BRANDLIGHT BI API · V1

Endpoint reference for AI search visibility data.

Seven endpoints. Visibility, share-of-voice, and content recommendations across the AI engines that surface your brand. Authenticated, paginated, and meant to drop into the data stack you already run.

BASIC REFERENCE

BASE URL	https://bi.brandlight.ai/v1
AUTH	Bearer token in Authorization header
VERSION	v1
UPDATED	April 28, 2026

CONTENTS

- List Brands — GET /brands
- Visibility Ranking — GET /visibility/ranking
- Share of Voice — GET /visibility/share-of-voice
- My Content Recommendations — GET /recommendations/my-content
- List Reports — GET /brands/:brand/reports
- Ranking by Category — GET /visibility/ranking-by-category
- New Content Opportunities — GET /recommendations/new-content-opportunities

01 List Brands

Returns all brands associated with your account. Use the returned `name` as the `brandName` path parameter on every other endpoint.

`GET` /v1/brands

RESPONSE FIELDS

FIELD	TYPE	DESCRIPTION
name	string	Brand name. Use this as `brandName` in other endpoints.

No input. The endpoint takes no parameters; results are scoped to the bearer token.

SAMPLE RESPONSE

200 · APPLICATION/JSON

```
{
  "data": [
    {
      "name": "Acme Corp"
    }
  ],
  "meta": {}
}
```

02 List Reports

Returns a paginated list of reports for a brand, including the dates each was generated and the locations available for that report.

`GET` /v1/brands/:brandName/reports

QUERY PARAMETERS

PARAM	TYPE	REQ	DEFAULT	DESCRIPTION
page	integer	No	1	Page number.
pageSize	integer	No	20	Results per page (max 100).

RESPONSE FIELDS

FIELD	TYPE	DESCRIPTION
generatedAt	string · ISO 8601	Date the report was generated.
locations	array	Available locations for this report.
locations[].id	string	Location identifier (country code or `global`).
locations[].name	string	Location display name.
meta.page	integer	Current page number.
meta.pageSize	integer	Results per page.
meta.total	integer	Total number of reports.

SAMPLE RESPONSE

200 · APPLICATION/JSON

```
{
  "data": {
    "generatedAt": "2026-04-07T10:00:00.000Z",
    "locations": [
      { "id": "US", "name": "United States" },
      { "id": "GB", "name": "United Kingdom" },
      { "id": "global", "name": "Global" }
    ]
  },
  "meta": {
    "page": 1,
    "pageSize": 20,
    "total": 84
  }
}
```

03 Visibility Ranking

Returns per-report visibility scores for your brand and competitors over a date range. Always cite the time window when reporting these in dashboards or decks.

`GET` /v1/brands/:brandName/visibility/ranking

QUERY PARAMETERS

PARAM	TYPE	REQ	DESCRIPTION
startDate	string · ISO 8601	Yes	Start of date range.
endDate	string · ISO 8601	Yes	End of date range (max 1 year span).
location	string	Yes	Location ID (e.g. `US`, `global`). Available locations come from List Reports.

RESPONSE FIELDS

FIELD	TYPE	DESCRIPTION
reportDate	string · ISO 8601	Date of the report.
scores	array	Visibility scores for all brands in this report.
scores[].name	string	Brand name.
scores[].visibilityScore	string	Visibility percentage (0–100).

SAMPLE RESPONSE

200 · APPLICATION/JSON

```
{
  "data": [
    {
      "reportDate": "2026-03-15T00:00:00.000Z",
      "scores": [
        {
          "name": "Acme Corp",
          "visibilityScore": "45.50"
        },
        {
          "name": "Competitor A",
          "visibilityScore": "32.20"
        }
      ]
    }
  ],
  "meta": {}
}
```

04 Ranking by Category

Returns visibility ranking per category, showing your brand's score alongside competitors in each category.

`GET` /v1/brands/:brandName/visibility/ranking-by-category

QUERY PARAMETERS

PARAM	TYPE	REQ	DESCRIPTION
startDate	string · ISO 8601	Yes	Start of date range.
endDate	string · ISO 8601	Yes	End of date range (max 1 year span).
location	string	Yes	Location ID (e.g. `US`, `global`).

RESPONSE FIELDS

FIELD	TYPE	DESCRIPTION
categoryName	string	Category name.
myBrand	object	Your brand's visibility in this category.
myBrand.name	string	Your brand name.
myBrand.score	string	Visibility percentage (0–100).
competitors	array	Competitor brands, sorted by score (highest first).
competitors[].name	string	Competitor name.
competitors[].score	string	Visibility percentage (0–100).

SAMPLE RESPONSE

200 · APPLICATION/JSON

```
{
  "data": [
    {
      "categoryName": "Enterprise Software",
      "myBrand": {
        "name": "Acme Corp",
        "score": "42.50"
      },
      "competitors": [
        {
          "name": "Competitor A",
          "score": "38.10"
        },
        {
          "name": "Competitor B",
          "score": "25.30"
        }
      ]
    }
  ],
  "meta": {}
}
```

05 Share of Voice

Returns per-report share of voice percentages for your brand and competitors.

`GET` /v1/brands/:brandName/visibility/share-of-voice

QUERY PARAMETERS

PARAM	TYPE	REQ	DESCRIPTION
startDate	string · ISO 8601	Yes	Start of date range.
endDate	string · ISO 8601	Yes	End of date range (max 1 year span).
location	string	Yes	Location ID (e.g. `US`, `global`).

RESPONSE FIELDS

FIELD	TYPE	DESCRIPTION
reportDate	string · ISO 8601	Date of the report.
scores	array	Share of voice for all brands in this report.
scores[].name	string	Brand name.
scores[].shareOfVoice	string	Share of voice percentage (0–100).

SAMPLE RESPONSE

200 · APPLICATION/JSON

```
{
  "data": [
    {
      "reportDate": "2026-03-15T00:00:00.000Z",
      "scores": [
        {
          "name": "Acme Corp",
          "shareOfVoice": "38.80"
        },
        {
          "name": "Competitor A",
          "shareOfVoice": "28.10"
        }
      ]
    }
  ],
  "meta": {}
}
```

06 New Content Opportunities

Returns content recommendations for new topics your brand should create, grouped by category. Automatically uses the latest report.

`GET` /v1/brands/:brandName/recommendations/new-content-opportunities

QUERY PARAMETERS

PARAM	TYPE	REQ	DESCRIPTION
location	string	Yes	Location ID (e.g. `US`, `global`). Available locations come from List Reports.

RESPONSE FIELDS

FIELD	TYPE	DESCRIPTION
categoryName	string	Category name.
recommendations	array	List of content recommendations for this category.
recommendations[].topicName	string	The topic this recommendation targets.
recommendations[].priority	string	Priority level · `VERY-HIGH` · `HIGH` · `MEDIUM` · or `LOW`.
recommendations[].recommendationType	string	Type of recommendation (e.g. `NEW_CONTENT_CREATION`).
recommendations[].recommendationAction	string	Actionable description of what to do.
recommendations[].impactPotential	array	Expected impact metrics (may be empty).
recommendations[].impactPotential[].percentage	number	Impact percentage (0–100).
recommendations[].impactPotential[].type	string	Impact type (e.g. `"visibility"`).
recommendations[].suggestions	object	Detailed suggestions — keys are strategy names, values are arrays of actionable instructions.

SAMPLE RESPONSE

200 · APPLICATION/JSON

```
{
  "data": [
    {
      "categoryName": "Enterprise Software",
      "recommendations": [
        {
          "topicName": "Best Banks in Canada for Identity Theft Support",
          "priority": "HIGH",
          "recommendationType": "NEW_CONTENT_CREATION",
          "recommendationAction": "Instruct content team to write a concise H2 led guide...",
          "impactPotential": [],
          "suggestions": {
            "Use a Clear How-To Format": [
              "Structure the page as a step-by-step How To Guide..."
            ],
            "Use Simple, Precise Language": [
              "Write in clear, straightforward sentences..."
            ],
            "Incorporate Short, Direct Bullets": [
              "Use concise bullet points highlighting key features..."
            ],
            "Include Calls-to-Action": [
              "End sections with actionable tips guiding users..."
            ]
          }
        }
      ]
    }
  ],
  "meta": {}
}
```

07 My Content Recommendations

Returns recommendations for your brand's existing content sources, including citation frequency data. Automatically uses the latest report.

`GET` /v1/brands/:brandName/recommendations/my-content

QUERY PARAMETERS

PARAM	TYPE	REQ	DESCRIPTION
location	string	Yes	Location ID (e.g. `US`, `global`). Available locations come from List Reports.

RESPONSE FIELDS

FIELD	TYPE	DESCRIPTION
url	string	URL of the content source.
domain	string	Domain name.
citationFrequency	number	Number of times this source is cited across AI engine answers.
citationChangePercent	number	Percentage change in citation frequency vs. previous report.
recommendation	object	Content recommendation for this source.
recommendation.recommendationType	string	Type (e.g. `OPTIMIZE`, `NEW_CONTENT_CREATION`).
recommendation.recommendationAction	string	Actionable description of what to improve.
recommendation.impactPotential	array	Expected impact metrics (may be empty).
recommendation.suggestions	object	Detailed suggestions — keys are strategy names, values are arrays of actionable instructions.

SAMPLE RESPONSE

200 · APPLICATION/JSON

```
{
  "data": {
    "url": "https://acme.com/blog/pricing-guide",
    "domain": "acme.com",
    "citationFrequency": 42,
    "citationChangePercent": 12.5,
    "recommendation": {
      "recommendationType": "OPTIMIZE",
      "recommendationAction": "Page is comprehensive but lacks structure...",
      "impactPotential": [],
      "suggestions": {
        "Add Clear Headings": [
          "Introduce descriptive H2 sections..."
        ],
        "Add Summary Sections": [
          "Include brief summaries at the top of sections..."
        ],
        "Create FAQ Section": [
          "Add FAQs to target LLM query patterns..."
        ],
        "Include Comparison Tables": [
          "Add side-by-side spec tables..."
        ],
        "Incorporate Lists": [
          "Use bulleted or numbered lists for key features..."
        ],
        "Use Short Paragraphs": [
          "Break long paragraphs into 3-5 sentences..."
        ],
        "Clear Call to Action": [
          "Add compelling CTAs to guide user action..."
        ]
      }
    }
  },
  "meta": {}
}
```


All rights reserved to Brandlight © 2026