

SPP-R310plusiK / EVN

2 - 3 inch Mobile Printer



Mobile POS
/ Retail



Deliveries



Customer
Service Center



Ticketing

Compact and Ergonomic



Smaller and Lighter Design

- Easy to grip: 30% lighter and 26% slimmer than SPP-R300
- One touch cover open and easy paper loading



SPP-R300

SPP-R310plusiK / EVN

Made for
iPod iPhone iPad



1.8m

Mobile Field-Work Optimization

- Wireless and wired connectivity options including Bluetooth, WiFi, USB and Serial
- Supporting Easy Bluetooth Pairing™ via embedded NFC tag enabling auto pairing
- Dual-band WLAN (5GHz and 2.4 GHz)
- Dual-mode Bluetooth V4.1 Classic (MFi AP2 certified) and LE
- IP43 (Printer only) / IP54 (with protective case)
- 1.8 m / 6 ft. drop rate
- Long-lasting battery life (24-hour stand by time)



Built for Multi-Purpose

- Fast printing speed up to 130mm / sec (Optional)
- Designed for the receipt and label printing (Simple to switch via the feed button)
- Optional linerless label printing (80 mm/sec at 203dpi)

BIXOLON®
a Better Solution for your Business™

SPP-R310plusiK / EVN

2 - 3 inch Mobile Printer



Reported by
Chunichisha



Specifications

Printer Specifications

Print Method

Direct Thermal

Print Speed

Up to 130 mm/sec (Optional)
12.5% pattern

Print Resolution

203 dpi

Print Width & Long Life

Up to 72 mm - 100 Km

Sensor

Paper End: Reflective sensor
Paper Cover Open: Mechanical switch

Media Characteristics

Media Type

Receipt, Label and Linerless (Optional)

Media Width

50 - 80 mm (2" - 3")

Media Roll Diameter

Up to 50 mm

Media Thickness

0.07 ± 0.005 mm

Supply Method

Easy paper loading

Physical Characteristics

Dimensions (WxLxD)

105.0 x 126.0 x 58.0 mm
(4.14 x 4.97 x 2.29 inch)

Weight

Including battery: 385 g (0.85 lbs.)
Including MSR: 405 g (0.9 lbs.)
Paper: 133 g (0.29 lbs.)

Battery

7.4 V Li-ion, 2,600 mAh, Rechargeable
Charging time: Up to 4.0 hrs
Operation time: Up to 10h, 700 bills, 200mm/bill

Performance Characteristics

Memory

64 Mbit SDRAM, 32 Mbit FlashROM

Interface Options

USB V2.0 FS
Serial
Bluetooth V4.1 + EDR*
WLAN 802.11b/g/n
(Infrastructure, Ad-hoc, Wi-Fi Direct)
- WEP40/104, WPA1/2(PSK, EAP)
* Easy Bluetooth Pairing™ via NFC

Environment Characteristics

Temperature

Operating: -15 ~ 50°C (5 ~ 122°F)
Storage: -30 ~ 70°C (-22 ~ 158°F)

Humidity

Operating: 10 ~ 80% RH

Sealing

IP43 (IP54 with protective case)

Drop Rate

1.8 m (6 ft.)

Software

Emulation

BXL / POS

Drivers

Windows Driver, OPOS Driver, JPOS Driver,
Linux CUPS Driver

SDKs

iOS SDK, Android SDK, Windows SDK

Fonts / Graphics / Symbolologies

Character Size

Font A: 12 x 24 Font B: 9 x 17 Font C: 9 x 24
KOR, CHN: 24 x 24

Characters Per Line

Font A: 48 Font B, C: 64
KOR, CHN: 24

Character Sets

Alphanumeric: 95
Expanded Graphics: 128 x 33 page
International: 32

Graphics

Supporting user-defined fonts, graphics,
formats, layouts, and logos

Barcode

1D: Codabar, Code 39, Code 93, Code 128, EAN-8,
EAN-13, ITF, UPC-A, UPC-E
2D: Aztec, Data Matrix, GS1 Databar, MaxiCode,
PDF417, QR code

Accessories

Standard

Belt Clip, Battery Pack, Battery Charger,
Power Cord, Paper

Optional

Belt Strap, Case, Protective Case, Shoulder Strap,
Single Battery Cradle, Quad Battery Charger,
Cigarette Lighter Charger, Serial/USB Cable,
Cleaning Pen

Integrated Card Reader (Optional)

MSR

3 Track (T-DES/DUKPT(Optional))



BR-SPP-R310plusiK/EVN-AUG17-V1-NF Copyright © BIXOLON Co., Ltd. All rights reserved. Features and specifications are subject to change without prior notice.

BIXOLON®

BIXOLON Co., Ltd.
+82 (0) 31 218 5500
sales@bixolon.com

BIXOLON America Inc.
+1 858 764 4580
sales@bixolonusa.com

BIXOLON Europe GmbH
+49 211 68 78 54 0
sales@bixolon.de

www.Bixolon.com

