



DR3

VERSATILE STANDALONE SOLUTION

FEATURES

- Fast Speed Printing
- Durability
- Enduring
- Accommodates Large Label Rolls

APPLICATIONS

- Food Manufacturing
- Retail
- Department Store
- Entertainment
- Transportation and Logistics

PRINTING SPECIFICATION		DR308e
Printing Method		Direct Thermal, Thermal Transfer
Print Resolution, dots/mm (dpi)		8 dots/mm (203dpi)
Max. Print Area	Width, mm (inch)	80mm (3.15")
	Length, mm (inch)	181mm (7.13")
Print Speed, mm/sec (ips)		Up to 127mm/sec (5ips)
CPU		32 bit RISC
Printer Memory		Flash-ROM 8MB

CONSUMABLES SPECIFICATION (Recommended to use printer supplies manufactured or certified by SATO)			
Sensor Type		I-Mark Sensor (Reflective), Label Gap Sensor (Transmissive), Jump-Hole Sensor	
Media Type		Roll die cut labels, Plain paper face stock, Synthetics, Continuous stock and Tags	
Media Thickness		0.07 – 0.265mm (0.0028" – 0.01")	
Label Shape	Diameter		Max. outside diameter: Ø 250mm (9.84"), Core diameter: Ø 38.1mm (1.5") or Ø 101.6mm (4")
	Wind Direction		Face-in
Label Size	Continuous	Width	29 – 77mm (1.14" – 3.03")
		Length	16 – 178mm (0.63" – 7.01")
	Tear-Off	Width	29 – 77mm (1.14" – 3.03")
		Length	22 – 178mm (0.87" – 7.01")
	Cutter	Width	29 – 77mm (1.14" – 3.03")
		Length	22 – 178mm (0.87" – 7.01")
	Dispenser	Width	29 – 77mm (1.14" – 3.03")
		Length	22 – 178mm (0.87" – 7.01")
Ribbon	Size		Width: 39.5mm (1.56") to 84mm (3.31"), Max. Length: 300m (984')
	Core Diameter		Ø 25.4mm (1")
	Wind Direction		Face-in

FONTS / SYMBOLOGIES		
Fonts	Standard Fonts	Bitmap Fonts Alphanumeric and Symbol: WB (18x30 dot), WL (28x52 dot), XU (5x9 dot), XS (17x17 dot), XM (24x24 dot), XB (48x48 dot), XL (48x48 dot), OCR-A (15x22 dot), OCR-A (22x23 dot), OCR-B (20x24 dot), OCR-B (30x36 dot)
	Rasterized Fonts	CG Times, CG Triumvirate
Barcode	1D Barcode	UPC-A/E, JAN/EAN-8/13, Code 39, Code 128, GS1-128 (UCC /EAN128), Codabar (NW-7), Interleaved 2 of 5, Bookland (2/5 char add-on code), GS1 Databar (RSS14), Composite JAN/EAN-8/13; Composite UPC A/E; Composite GS1 128/CC
	2D Barcode	PDF417 (Ver2.4), MAXI Code (Ver3.0), QR Code, GS1 Data Matrix (ECC200)
Print Rotation	Character Data / Barcode	0°, 90°, 180°, 270°

COMMUNICATION INTERFACES	
Optional Plug-in Interface	IEEE1284, Centronics parallel, RS232C (2400-19,200 Baud), RS232C highspeed (9,600-57,600 baud), USB (12Mbit/s), LAN (TCP/IP protocol 10/100BaseT), Wireless LAN 802.11b/g
Command Language	SBPL
Other Interfaces (standard)	External Port connector, RS-232C D-SUB9 pins (exclusively for Keypad)

OPERATING CHARACTERISTICS	
Power Requirements	
Input voltage AC100-240V (auto switching)/104W (peak)	
Dimensions	
(W x D x H): 211 x 350 x 240mm, (8.31" x 13.78" x 9.45")	
Weight	
Approx. 8kg (17.6 lbs)	
Environment	Operating
	5 – 40°C / 30 – 80% RH (without condensation)
Storage	Storage
	-5 – 60°C / 30 – 90% RH (without condensation)

MISCELLANEOUS	
Certifications	FCC, UL, CSA, CCC, CE, ROHS compliant Bluetooth® certified

OPTIONS	
Accessories	Cutter, Stacker, External Rewinder, Dispenser, Keypad, Real-Time Clock, SATO Label Gallery™



www.logiscenter.com
902 050 030



www.logiscenter.it
02 479 216 97



www.logiscenter.de
info@logiscenter.de



www.logiscenter.pt
308 800 842

About LOGISCENTER

Grupo Logiscenter is the leading provider in Europe of automatic identification and data capture equipments. Our products include barcode printing and reading devices, mobile computing devices, wireless access points, identification cards, and consumables.

Reasons to work with us

Our customers come first. Our objective is not only selling our products but also holding a long-lasting relationship with our customers, based on the benefits and advantages we create for you and your company.

The best brands. We offer products from the best manufacturers worldwide.

Expert technical support team. Our support staff are experts in the products we sell. But not just the products, they can tell you the best solution for your particular problem or need.

Largest stock. We have a permanent stock of more than 12,000 products.

Same-day shipping. For all orders placed and confirmed before 16:00 on working days.


Best prices. With Logiscenter, you can be sure that you are paying a fair price for your products we will not overcharge you.

Easy returns. Damaged or defective products can be returned easily, for an exchange or reimbursement.

Solutions for: Industry • Consumer • Mobility Transportation and Logistics • Retail • Health




Label printers



Barcode readers



Data terminals & PDA



PVC card printers



RFID



Consumables
(labels, ribbons, PVC cards)

Our Brands



MOTOROLA



Intermec®

Honeywell®

DATALOGIC™



datamax • o'neil

Metrologic

LXE

EPSON®

elo

star

unitech

PRINTRONIX

symbol®



All Brands
Technical Service