



TTP-243 PRO SERIES – Desktop Thermal Transfer Bar Code Printer
YOU CAN COUNT ON IT!
THE NEW LEGENDARY TTP-243 PRO HAS ARRIVED!



KEY FEATURES

- Dual-motor print engine
- 4 MB Flash and 8 MB SDRAM memory
- Optional SD card reader for expanding memory up to 4 GB
- Ribbon capacity up to 300 m (984 feet)
- Label capacity up to 214 mm (8.4") OD
- Serial & USB 2.0 connectivity are standard
- Optional serial & parallel ports
- Optional stand-alone keyboard display unit, rotary cutter, Bluetooth module and external 802.11 b/g/n wireless module

APPLICATIONS

- Shipping & Receiving
- Compliance Labeling
- Asset Tracking
- Inventory Control
- Document Management
- Shelf Labeling
- Product Marking
- Specimen Labeling
- Patient Tracking

TTP-243 PRO SERIES – Desktop Thermal Transfer Bar Code Printer

PRINTER MODEL	TTP-243 PRO	TTP-243E PRO	TTP-342 PRO
Resolution	8 dots/mm (203 DPI)	8 dots/mm (203 DPI)	12 dots/mm (300 DPI)
Printing method	Thermal Transfer & Direct Thermal		
Max. print speed	76 mm (3")/second	76 mm (3")/second	51 mm (2")/second
Max. print width	104 mm (4.09")	104 mm (4.09")	104 mm (4.09")
Max. print length	2,286 mm (90")	2,286 mm (90")	1,016 mm (40")
Enclosure	ABS plastic		
Physical dimension	232 mm (W) x 156 mm (H) x 288 mm (D) 9.13" (W) x 6.14" (H) x 11.34" (D)		
Weight	2.5 kg (5.51 lbs)		
Label roll capacity	Internal: 110 mm (4.33") OD External: 214 mm (8.42") OD	Internal: 110 mm (4.33") OD External: 214 mm (8.42") OD (Optional)	Internal: 110 mm (4.33") OD External: 214 mm (8.42") OD
Ribbon	300 m long, max. OD 67 mm, 1" core (ink coated outside)		
Ribbon width	40 mm ~ 110 mm (1.6" ~ 4.3")		
Processor	32-bit RISC CPU		
Memory	• 4 MB Flash memory • 8 MB SDRAM • SD card reader for Flash memory expansion, up to 4 GB (user option)		
Interface	• USB 2.0 • RS-232 • Centronics (factory option) • Bluetooth (user option) • External 802.11 b/g/n wireless (user option)		
Power	External universal switching power supply • Input: AC 100-240V, 1.8A, 50-60Hz • Output: DC 24V, 2.5A, 60W		
Operation switch, button, LED	1 power switch, 1 feed button, 1 pause button & 3 LEDs (Power, Error, On-line)		
Sensors	• Transmissive gap sensor • Black mark reflective sensor • Ribbon end sensor • Peel off sensor	• Transmissive gap sensor • Black mark reflective sensor • Ribbon end sensor	• Transmissive gap sensor • Black mark reflective sensor • Ribbon end sensor • Peel off sensor
Internal fonts	• 8 alpha-numeric bitmap fonts • 1D bar code		
Bar code	Code 39, Code 93, Code 128UCC, Code 128 subset A, B, C, Codabar, Interleave 2 of 5, EAN-8, EAN-13, EAN-128, UPC-A, UPC-E, EAN and UPC 2 (5) digits add-on, MSI, PLESSEY, POSTNET, RSS-Stacked, GS1 DataBar, Code 11 • 2D bar code PDF-417, Maxicode, DataMatrix, QR Code, Aztec		
Font and barcode rotation	0, 90, 180, 270 degree		
Printer language	TSPL, TPLe		
Media type	Continuous, die cut, fan-fold, tag, black mark, ticket (outside wound)		
Media width	25.4 ~ 114 mm (1" ~ 4.49")		
Media thickness	0.06 ~ 0.25 mm (2.36 ~ 9.84 mil)		
Media core diameter	25.4 ~ 76.2 mm (1" ~ 3")		
Label length	10 ~ 2,286 mm (0.39" ~ 90")	10 ~ 2,286 mm (0.39" ~ 90")	10 ~ 1,016 mm (0.39" ~ 40")
Environment condition	Operation: 5 ~ 40°C, 25 ~ 85% non-condensing Storage: -40 ~ 60°C, 10 ~ 90% non-condensing		
Safety regulation	FCC Class A, CE Class A, C-Tick Class A, TÜV/Safety, CCC		
Environmental concern	Comply with RoHS, WEEE		
Accessories	• Windows labeling software CD disk • Quick start guide • USB cable • Power cord • External universal switching power supply • Label spindle, fixing tab x 2 • Ribbon spindle x 2 • Ribbon paper core • Ribbon & label sample roll • External label roll mount	• Windows labeling software CD disk • Quick start guide • USB cable • Power cord • External universal switching power supply • Label spindle, fixing tab x 2 • Ribbon spindle x 2 • Ribbon paper core	• Windows labeling software CD disk • Quick start guide • USB cable • Power cord • External universal switching power supply • Label spindle, fixing tab x 2 • Ribbon spindle x 2 • Ribbon paper core • Ribbon & label sample roll • External label roll mount
Limited warranty	• Printer: 2 years • Print head: 25 km (1 million inches) or 12 months which comes first • Platen: 50 km (2 million inches) or 12 months which comes first		
Factory options	• Centronics parallel & RS-232 serial interfaces • Position centered gap sensor		
Dealer options	• Rotary cutter (full cut)	N/A	• Rotary cutter (full cut)
User options	• Bluetooth module (serial interface) • 802.11 b/g/n wireless module (serial interface) • SD Flash memory card reader • 3" core label spindle • KP-200 Plus keyboard display unit • KU-007 Plus programmable smart keyboard N/A	• External roll mount, media OD. 214 mm (8.4") with 1" or 3" core label spindle N/A	N/A



CORPORATE HEADQUARTERS

TSC Auto ID Technology Co., Ltd.
 Tel: +886 2 2218 6789
 E-mail: printer_sales@tsprinters.com

LI ZE PLANT

TSC Auto ID Technology Co., Ltd.
 Tel: +886 3 990 6677
 E-mail: printer_sales@tsprinters.com

AMERICAS

TSC Auto ID Technology America Inc. Corporate Office
 Tel: +1 909 525 9779
 E-mail: sales@tsprinters.com

Orlando Office

Tel: +1 407 704 8918
 E-mail: sales@tsprinters.com

CANADA

TSC Auto ID Technology America Inc.
 Tel: +1 909 525 9779
 E-mail: sales@tsprinters.com

MEXICO

TSC Mexico Representative Office
 Tel: +52 (33) 3836 6682
 E-mail: sales@idc-componentes.com

BRAZIL

TSC Brazil Representative Office
 Tel: +55 (11) 9597 8098
 E-mail: paul_liao@tsprinters.com

EMEA

TSC Auto ID Technology EMEA GmbH
 Tel: +49 (0) 8106 37979 00
 E-mail: info@tsceu.com

RUSSIA

TSC Auto ID Technology EMEA GmbH
 Tel: +7 915 422 8889
 E-mail: victoria.grobushkina@tsceu.com

MIDDLE EAST

TSC Auto ID Technology ME Ltd, FZE
 Tel: +971 4 2533 069
 E-mail: info@tsmea.com

ASIA PACIFIC

TSC Auto ID Technology Co., Ltd.
 Tel: +886 2 2218 6789
 E-mail: printer_sales@tsprinters.com

CHINA

Tianjin TSC Auto ID Technology Co., Ltd.
 Tel: +86 22 5981 6661
 E-mail: sale@tsprinters.com.cn

TSC is a trademark of TSC Auto ID Technology Co., Ltd.
 TSC Auto ID Technology Co., Ltd. is an ISO 9001/14001 registered company.
 © 2012 TSC Auto ID Technology Co., Ltd.
 Product models and Specifications are subject to change without notice.
 Contact your TSC sales representative for specific information.



www.logiscenter.com
902 050 030



www.logiscenter.it
02 479 216 97



www.logiscenter.de
info@logiscenter.de



www.logiscenter.pt
308 800 842

About LOGISCENTER

Grupo Logiscenter is the leading provider in Europe of automatic identification and data capture equipments. Our products include barcode printing and reading devices, mobile computing devices, wireless access points, identification cards, and consumables.

Reasons to work with us

Our customers come first. Our objective is not only selling our products but also holding a long-lasting relationship with our customers, based on the benefits and advantages we create for you and your company.

The best brands. We offer products from the best manufacturers worldwide.

Expert technical support team. Our support staff are experts in the products we sell. But not just the products, they can tell you the best solution for your particular problem or need.

Largest stock. We have a permanent stock of more than 12,000 products.

Same-day shipping. For all orders placed and confirmed before 16:00 on working days.

Best prices. With Logiscenter, you can be sure that you are paying a fair price for your products we will not overcharge you.

Easy returns. Damaged or defective products can be returned easily, for an exchange or reimbursement.

Solutions for: Industry • Consumer • Mobility Transportation and Logistics • Retail • Health



Label printers



Barcode readers



Data terminals & PDA



PVC card printers



RFID



Consumables
(labels, ribbons, PVC cards)

Our Brands



MOTOROLA



Intermec®

Honeywell®

DATALOGIC™



datamax • o'neil

Metrologic

LXE

EPSON®

elo

star

unitech

PRINTRONIX

symbol®



All Brands
Technical Service