



## MULTI-PURPOSE USES FOR DIFFERENT APPLICATIONS

The QuickScan reader series is Datalogic's value line of general purpose handheld data collection products. The QuickScan I QD2100 linear imaging reader is an entry level product that is perfect for use in retail and office environments plus activities associated with couriers and postal services.

## READING CAPABILITY

The QD2100 reader is small, lightweight and its ergonomic design is comfortable to use during daily operations. It offers snappy reading performance especially on hard-to-read bar codes and is capable of reading a wide range of symbologies including the majority of 1D codes plus GS1 DataBar™ linear codes. The QD2100 reader features Datalogic's patented 'Green Spot' for good read feedback directly on the code. When in Stand Mode, the Green Spot remains on to show the operator where to position the code for quick and intuitive reading.



## USER REPLACEABLE WINDOW PACK LOWERS THE COST OF OWNERSHIP

Like the QuickScan L reader, the QD2100 reader has been designed with durability in mind. One of the most vulnerable features of any scanner is damage to the scan window. When such incidents happen, the scanner may have to be replaced. The QD2100 scanner was specifically designed so that a replacement window pack can be ordered to replace damaged or scratched windows without having to send the scanner away for repairs. This helps to reduce the total cost of ownership during the life of the scanner and helps to ensure that it is always available for use.



### FEATURES

- Datalogic's Green Spot for good read feedback
- User replaceable scan window
- Two multi-interface options support the most popular interface combinations
- Supports GS1 DataBar™ codes
- Remote host download functions (Model QD2110)
- Water and Particulate Sealing Rating: IP42
- Drop resistance to 1.5 m / 5.0 ft
- EASEOFCARE Service Plans offer a wide range of service options to protect your investment, ensuring maximum productivity and ROI

### INDUSTRY-APPLICATIONS

- Retail: Point of Sale, Mobile Marketing Capabilities, Age Verification, 2D Bar Codes
- Commercial Services: Postal, Banks, Public Administration and Utilities
- Access Control, Transportation and Entertainment

## TECHNICAL SPECIFICATIONS

### DECODING CAPABILITY

|                   |                                                                                        |
|-------------------|----------------------------------------------------------------------------------------|
| 1D / LINEAR CODES | Autodiscriminates all standard 1D codes including GS1 DataBar™ linear codes.           |
| POSTAL CODES      | China Post                                                                             |
| STACKED CODES     | GS1 DataBar Expanded Stacked; GS1 DataBar Stacked; GS1 DataBar Stacked Omnidirectional |

### ELECTRICAL

|               |                                                                               |
|---------------|-------------------------------------------------------------------------------|
| CURRENT       | Operating (Typical): 340 mA @ 5 VDC<br>Standby/Idle (Typical): 190 mA @ 5 VDC |
| INPUT VOLTAGE | QD2110: 4 -14 VDC; QD2130: 5 VDC +/- 10%                                      |

### ENVIRONMENTAL

|                                |                                                                                         |
|--------------------------------|-----------------------------------------------------------------------------------------|
| AMBIENT LIGHT                  | 100,000 lux                                                                             |
| DROP RESISTANCE                | Withstands repeated drops from 1.5 m / 5.0 ft onto a concrete surface.                  |
| ESD PROTECTION (AIR DISCHARGE) | 20 kV                                                                                   |
| HUMIDITY (NON-CONDENSING)      | 5 - 95%                                                                                 |
| PARTICULATE AND WATER SEALING  | IP42                                                                                    |
| TEMPERATURE                    | Operating: 0 to 50 °C / 32 to 122 °F<br>Storage/Transport: -40 to 70 °C / -40 to 158 °F |

### INTERFACES

|            |                                                                                                                 |
|------------|-----------------------------------------------------------------------------------------------------------------|
| INTERFACES | QD2110: RS-232 / IBM 46XX / USB Multi-Interface<br>QD2130: RS-232 / USB / Keyboard Wedge / Wand Multi-Interface |
|------------|-----------------------------------------------------------------------------------------------------------------|

### PHYSICAL CHARACTERISTICS

|                  |                                          |
|------------------|------------------------------------------|
| COLORS AVAILABLE | Black; White                             |
| DIMENSIONS       | 17.0 x 7.1 x 6.6 cm / 6.7 x 2.8 x 2.6 in |
| WEIGHT           | 121.9 g / 4.3 oz                         |

### READING PERFORMANCE

|                                |                                                                                       |
|--------------------------------|---------------------------------------------------------------------------------------|
| LIGHT SOURCE                   | Red LED 610-650 nm                                                                    |
| PRINT CONTRAST RATIO (MINIMUM) | 15%                                                                                   |
| READ RATE (MAXIMUM)            | 270 reads/sec.                                                                        |
| READING ANGLE                  | Pitch: +/- 65°; Roll (Tilt): +/- 45°;<br>Skew (Yaw): +/- 65°                          |
| READING INDICATORS             | Beeper (Adjustable Tone); Datalogic 'Green Spot'<br>Good Read Feedback; Good Read LED |
| RESOLUTION (MAXIMUM)           | 0.102 mm / 4 mils                                                                     |

### READING RANGES

|                        |                                                                                                                                                                                                                                                                                                                                                                                                  |
|------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| TYPICAL DEPTH OF FIELD | Minimum distance determined by symbol length and scan angle.<br>Printing resolution, contrast, and ambient light dependent.<br>4 mils: 2.0 to 11.0 cm / 0.8 to 4.3 in<br>5 mils: 1.5 to 15.0 cm / 0.6 to 6.0 in<br>7.5 mils: 0.8 to 25.0 cm / 0.3 to 10.0 in<br>10 mils: 0.8 to 38.0 cm / 0.3 to 15.0 in<br>13 mils: 1.9 to 45.0 cm / 0.7 to 18.0 in<br>20 mils: 2.5 to 65.0 cm / 1.0 to 26.0 in |
|------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

### SAFETY & REGULATORY

|                                                |                                                                                                                                                                                                                                                                    |
|------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| AGENCY APPROVALS                               | The product meets necessary safety and regulatory approvals for its intended use. The Quick Reference Guide for this product can be referred to for a complete list of certifications. Complies to China RoHS; Complies to EU RoHS IEC 60825-1 Class 1 LED Product |
| ENVIRONMENTAL COMPLIANCE<br>LED CLASSIFICATION |                                                                                                                                                                                                                                                                    |

### UTILITIES

|                      |                                                                                 |
|----------------------|---------------------------------------------------------------------------------|
| DATALOGIC ALADDIN™   | Datalogic Aladdin configuration program is available for download at no charge. |
| REMOTE HOST DOWNLOAD | Lowers service costs and improves operations: QD2110                            |


### WARRANTY

|          |                         |
|----------|-------------------------|
| WARRANTY | 5-Year Factory Warranty |
|----------|-------------------------|

## ACCESSORIES

### Mounts/Stands

- 11-0360 Holder, Multi-Purpose, Black
- 11-0362 Holder, Multi-Purpose, Grey
- STD-QD20-BK Gooseneck Stand, Black
- STD-QD20-WH Gooseneck Stand, White



### Miscellaneous

- 11-0318 Replacement Windows, 5-Pack





[www.logiscenter.com](http://www.logiscenter.com)  
902 050 030



[www.logiscenter.it](http://www.logiscenter.it)  
02 479 216 97



[www.logiscenter.de](http://www.logiscenter.de)  
info@logiscenter.de



[www.logiscenter.pt](http://www.logiscenter.pt)  
308 800 842

## About LOGISCENTER

Grupo Logiscenter is the leading provider in Europe of automatic identification and data capture equipments. Our products include barcode printing and reading devices, mobile computing devices, wireless access points, identification cards, and consumables.

## Reasons to work with us

**Our customers come first.** Our objective is not only selling our products but also holding a long-lasting relationship with our customers, based on the benefits and advantages we create for you and your company.

**The best brands.** We offer products from the best manufacturers worldwide.

**Expert technical support team.** Our support staff are experts in the products we sell. But not just the products, they can tell you the best solution for your particular problem or need.

**Largest stock.** We have a permanent stock of more than 12,000 products.

**Same-day shipping.** For all orders placed and confirmed before 16:00 on working days.

**Best prices.** With Logiscenter, you can be sure that you are paying a fair price for your products we will not overcharge you.

**Easy returns.** Damaged or defective products can be returned easily, for an exchange or reimbursement.

## Our Brands



**MOTOROLA**



**Intermec**

**Honeywell**

**DATALOGIC**



datamax • o'neil

**Metrologic**

**LXE**

**EPSON**

**elo**

**star**

**unitech**

**PRINTRONIX**

**symbol**



**All Brands  
Technical Service**


## Solutions for: Industry • Consumer • Mobility Transportation and Logistics • Retail • Health



Label printers




Barcode readers



Data terminals & PDA



PVC card printers



RFID



Consumables  
(labels, ribbons, PVC cards)