

RG760

Specifications



Physical Characteristics

Dimension	147.1 (L) * 74.5 (W) * 158.1 (H) mm
Weight	218g (without terminal)
Electronic Type	Connected with PA760 via pogo pin
Power Input	From PA760
User Input	Trigger

RFID Performance

Standards Supported	EPC Class1 Gen2 V2
RFID Engine	M6e-Micro (RAIN RFID supported)
RFID Chip	Impinj R2000
Read Rate	750 tags/sec
Read Distance	6m (Circular antenna)
Frequency Range	TW: 922-928 MHz US: 902-928 MHz EU: 865-868 MHz Japan: 916-921 MHz

Communication

Host Connection	Electrical 10-pin connection
Host Computer	Unitech PA760 mobile computer

User Environment

Drop Specification	1.2m (with terminal)
Operating Temp.	-20 ~ 50°C
Storage Temp.	-30 ~ 60°C
Humidity	5% ~ 95%
Electrostatic Discharge	+/- 8kV air discharge +/- 4kV contact discharge
Sealing	IP52 (with terminal)

NOTE:

- * Please make sure PA760 OS version requires MR3 or higher.
- * Demo APP: Please download RFID Reader App on PA760



Headquarters

Taipei, Taiwan
<http://www.ute.com> e-mail: info@hq.ute.com

unitech America

Los Angeles
<http://us.ute.com> e-mail: info@us.ute.com
<http://can.ute.com> e-mail: info@can.ute.com
Mexico
<http://latin.ute.com> e-mail: info@latin.ute.com

unitech Asia Pacific & Middle East

Taipei
<http://apac.ute.com> e-mail: info@apac.ute.com / info@india.ute.com
<http://mideast.ute.com> e-mail: info@mideast.ute.com

unitech Europe

Tilburg / Netherlands
<http://eu.ute.com> e-mail: info@eu.ute.com

unitech Japan

Tokyo
<http://jp.ute.com> e-mail: info@jp.ute.com

unitech Greater China

Beijing, Shanghai, Guang Zhou, Xiamen
<http://cn.ute.com> e-mail: info@cn.ute.com
Taipei <http://tw.ute.com> e-mail: info@tw.ute.com

