



G500 / G530

High-Tech Power with a Customer Friendly Price

"Twin-Sensor Technology" makes the G500 perfect for printing on all types of specialty materials especially for retail and industrial applications



300 meter ribbon plus the optional label stand provides maximum printing volume



"Twin-Sensor" technology allows you to use a broad range of labels



Available interface combinations include:

- USB2.0, Serial and Ethernet
- USB2.0 and Parallel



Strong and stable mechanism design for long term reliability

Barcodes Made Easy

Model		G500		G530	
Print Method		Thermal Transfer/Direct Thermal			
Resolution		203 dpi (8 dot/mm)		300 dpi (12 dots/mm)	
Print Speed		5 IPS (127 mm/s)		4 IPS (102 mm/s)	
Print Width		4.25" (108 mm)		4.16" (105.7 mm)	
Print Length		Min. 0.16" (4 mm)**; Max. 68" (1727 mm)		Min. 0.16" (4 mm)**; Max. 30" (762 mm)	
Processor		32 bit RISC CPU			
Memory	Flash	8 MB Flash (4 MB for user storage)			
	SDRAM	16 MB			
Sensor Type		Adjustable reflective sensor 2 fixed transmissive sensors, central aligned			
Media	Types	Continuous form, gap labels, black mark sensing, and punched hole; label length set by auto sensing or programming			
	Width	1" (25.4 mm) Min. - 4.64" (118 mm) Max.			
	Thickness	0.003" (0.06 mm) Min. - 0.01" (0.25 mm) Max.			
	Label Roll Diameter	Max. 5" (127 mm)			
	Core Diameter	1" (25.4 mm), 1.5" (38.1 mm), 3" (76.2 mm)			
Ribbon	Types	Wax, wax / resin, resin			
	Length	981' (300 m)			
	Width	Min. 1.18" (30 mm) – Max. 4.33" (110 mm)			
	Ribbon Roll Diameter	2.67" (68 mm)			
	Core Diameter	1" (25.4 mm)			
Printer Language		EZPL, GEPL, GZPL auto switch			
Software	Label Design Software	GoLabel (for EZPL only)			
	Driver	Windows 2000, XP, Vista, 7 and Windows Server 2003 & 2008			
	DLL	Windows 2000, XP and Vista			
Resident Fonts	Bitmap Fonts	6, 8, 10, 12, 14, 18, 24, 30, 16x26 and OCR A&B Bitmap fonts 90°, 180°, 270° rotatable, single characters 90°, 180°, 270° rotatable Bitmap fonts 8 times expandable in horizontal and vertical directions			
	Scalable Fonts	90°, 180°, 270° rotatable			
Download Fonts	Bitmap Fonts	90°, 180°, 270° rotatable, single characters 90°, 180°, 270° rotatable			
	Asian Fonts	90°, 180°, 270° rotatable and 8 times expandable in horizontal and vertical directions			
	Scalable Fonts	90°, 180°, 270° rotatable			
Barcodes	1-D Bar Codes	Code 39, Code 93, EAN 8 /13 (add on 2 & 5), UPC A / E (add on 2 & 5), I 2 of 5 & I 2 of 5 with Shipping Bearer Bars, Codabar, Code 128 (subset A, B, C), EAN 128, RPS 128, UCC 128, UCC / EAN-128 K-Mart, Random Weight, Post NET, ITF 14, China Postal Code, HIBC, MSI, Plessey, Telepen, FIM and GS1 DataBar			
	2-D Bar Codes	PDF417, Datamatrix code, MaxiCode, QR code, Micro PDF417, Micro QR code and Aztec code			
Code Pages		Codepage 437, 850, 851, 852, 855, 857, 860, 861, 862, 863, 865, 866, 869, 737 Windows 1250, 1251, 1252, 1253, 1254, 1255, 1257 Unicode (UTF8, UTF16)			
Graphics		Resident graphic file types are BMP and PCX, other graphic formats are downloadable from the software			
Interfaces		USB 2.0	USB 2.0	USB 2.0	USB 2.0
		Parallel port	Serial port	Parallel port	Serial port
		Ethernet		Ethernet	
Control Panel		Two bi-color status-LEDs: Ready, Status Control key: FEED			
Environment	Power	Auto Switching 100-240VAC, 50-60Hz			
	Operation Temperature	41°F to 104°F (5°C to 40°C)			
	Storage Temperature	-4°F to 122°F (-20°C to 50°C)			
Humidity	Operation	30-85%, non-condensing			
	Storage	10-90%, non-condensing			
Agency Approvals		CE (EMC), FCC Class A, CB, CCC			
Dimension	Length	11.2" (285 mm)			
	Height	6.8" (171 mm)			
	Width	8.9" (226 mm)			
Weight		6 lbs (2.72 Kg), excluding consumables			
Options & Accessories		Cutter module Label Dispenser External label roll holder for 10" (250 mm) O.D. label rolls External label rewinder			

* Specifications are subject to change without notice. All company and/or product names are trademarks and/or registered trademarks of their respective owners.

** Minimum print height and maximum print speed specification compliance can be dependent on non-standard material variables such as label type, thickness, spacing, liner construction, etc. Godex is pleased to test non-standard materials for minimum print height and maximum print speed capability.



www.logiscenter.com
902 050 030



www.logiscenter.it
02 479 216 97



www.logiscenter.de
info@logiscenter.de



www.logiscenter.pt
308 800 842

About LOGISCENTER

Grupo Logiscenter is the leading provider in Europe of automatic identification and data capture equipments. Our products include barcode printing and reading devices, mobile computing devices, wireless access points, identification cards, and consumables.

Reasons to work with us

Our customers come first. Our objective is not only selling our products but also holding a long-lasting relationship with our customers, based on the benefits and advantages we create for you and your company.

The best brands. We offer products from the best manufacturers worldwide.

Expert technical support team. Our support staff are experts in the products we sell. But not just the products, they can tell you the best solution for your particular problem or need.

Largest stock. We have a permanent stock of more than 12,000 products.

Same-day shipping. For all orders placed and confirmed before 16:00 on working days.

Best prices. With Logiscenter, you can be sure that you are paying a fair price for your products we will not overcharge you.

Easy returns. Damaged or defective products can be returned easily, for an exchange or reimbursement.

Solutions for: Industry • Consumer • Mobility Transportation and Logistics • Retail • Health



Label printers



Barcode readers



Data terminals & PDA



PVC card printers



RFID



Consumables
(labels, ribbons, PVC cards)

Our Brands



MOTOROLA



Intermec®

Honeywell®

DATALOGIC™



datamax • o'neil

Metrologic

LXE

EPSON®

elo

star

unitech

PRINTRONIX

symbol®



All Brands
Technical Service