



NICF -TEXT ANALYTICS

MODULE 7: LINGUISTIC RESOURCES

Fan Zhenzhen
Institute of Systems Science
National University of Singapore
Email: zhenzhen@nus.edu.sg

© 2015-2021 NUS. The contents contained in this document may not be reproduced in any form or by any means, without the written permission of ISS, NUS, other than for the purpose for which it has been supplied.

At the end of this module, you can

- Identify common text analytics artifacts or resources
- Develop such artifacts/resources based on domain knowledge

- Linguistic/knowledge resources and their roles in text analytics
- Corpora
- Dictionaries
- Defining patterns using regular expressions




Linguistic Resources

- Sets of language data and descriptions in machine readable form
- Used for building text analytics systems
 - **Corpora** - to provide examples for statistical methods and machine learning algorithms to work
- Or for improving text analytics systems, needed by various processing steps
 - **Dictionaries** - valid terms, POS information, list of stop words, or words to be filtered
 - **Terminologies** – special domain words and phrases
 - **Patterns/rules** – for information extraction



- Taxonomy and ontology – a hierarchical conceptual model to map terms to concepts
- Prerequisite for advance text mining, together with terminology lexicon
 - E.g. to derive complex information such as temporal, causal, conditional and other types of semantic relations between biomedical entities instead of simple associations



- Often labelled or annotated, to provide examples for statistical methods and machine learning algorithms to work
- Quality of corpora is critical for the resulting models
 - Validity – correct (need “ground truth” to measure)
 - Reliability – consistent (measured by coefficients of agreement)



Corpus Annotation

- Objective tasks - easier, subjective tasks - much harder
- Define task and guidelines
 - The source text? What to annotate? What are the labels for them?
 - Criteria, decision rules and examples
- Train the annotators (humans)
 - Each annotator tries annotating the same set of articles.
 - Check self-agreement rate
 - Individual annotator annotates some randomly selected samples again
 - To eliminate poor performers, or improve their work
 - Check inter-annotator agreement (IAA) rate
 - To resolve conflicts, refine guidelines with example of boundary cases
 - To improve IAA rate before large scale annotation
- In actual annotation, still assign a portion of items to be annotated by two or more annotators for monitoring quality

- Agreement between multiple annotators
(assumption: *consistency implies validity*.)
- Used to evaluate and monitor the annotation quality
- Common measures:
 - Cohen's Kappa
 - Fleiss's Kappa
 - Scott's Pi
 - Krippendorff's Alpha
 - Etc.



Cohen's Kappa

- The agreement rate for qualitative items taking into account the possibility of chance agreement

$$k = \frac{p_o - p_e}{1 - p_e}$$

- p_o : observed agreement
- p_e : expected agreement

$$p_e = \frac{1}{N^2} \sum_k n_{k1} n_{k2}$$

- k : number of categories
- N : number of observations
- n_{ki} : number of times annotator i predicted category k



Example of Kappa

		B	
		Yes	No
A	Yes	a	b
	No	c	d

$$p_o = \frac{a + d}{a + b + c + d} = \frac{20 + 15}{50} = 0.7$$

$$p_{\text{Yes}} = \frac{a + b}{a + b + c + d} \cdot \frac{a + c}{a + b + c + d} = 0.5 \times 0.6 = 0.3$$

$$p_{\text{No}} = \frac{c + d}{a + b + c + d} \cdot \frac{b + d}{a + b + c + d} = 0.5 \times 0.4 = 0.2$$

		B	
		Yes	No
A	Yes	20	5
	No	10	15


$$p_e = p_{\text{Yes}} + p_{\text{No}} = 0.3 + 0.2 = 0.5$$

$$\kappa = \frac{p_o - p_e}{1 - p_e} = \frac{0.7 - 0.5}{1 - 0.5} = 0.4$$




Interpretation of Kappa


- Landis and Koch, 1977



- Krippendorff, 1980



- Green, 1997



- Artstein and Poesio, 2008: *“If a threshold needs to be set, 0.8 is a good value.”*

- Text analytics systems may be equipped with dictionaries in different languages for various purposes.
 - General domain dictionaries for more accurate tokenization, stemming, and POS tagging.
 - Terminology dictionaries for special domains or tasks
 - e.g. Biomedical domain
 - Customer Relation Management
 - IT
 - Market Intelligence
 - Opinions Mining, etc.



Valid Term Dictionary

- A list of valid terms in the language in concern
- Or as dictionary for terms to be used in the term vector (e.g. R Text Mining package)
 - Only terms in the dictionary appear in the document term vector or matrix.
 - It helps to restrict the dimension of the matrix a priori and to focus on specific terms for distinct text mining contexts.
- It may include useful information such as POS





Filter Dictionary

- Also known as *Stopword List* / *exclusion dictionary*
- To support **the stopwords removal** step in preprocessing
- A list of very common words
 - usually functional words like *preposition*, *conjunction*, etc.
 - or words that are unimportant for the mining task
- Example stopwords list (not complete):

<i>a</i>	<i>an</i>	<i>because</i>	<i>before</i>
<i>about</i>	<i>and</i>	<i>been</i>	<i>being</i>
<i>above</i>	<i>any</i>	<i>before</i>	<i>below</i>
<i>after</i>	<i>are</i>	<i>being</i>	<i>between</i>
<i>again</i>	<i>aren't</i>	<i>below</i>	<i>both</i>
<i>against</i>	<i>as</i>	<i>between</i>	<i>but</i>
<i>all</i>	<i>at</i>	<i>both</i>	<i>by</i>
<i>am</i>	<i>be</i>	<i>been</i>	<i>...</i>

From <http://www.ranks.nl/resources/stopwords.html>



Synonym Dictionaries

- Also known as *substitution* dictionary, to group similar words under one term
- Typically for known synonyms, user-defined synonyms

dislike, detest

- Also a direct way to deal with common misspellings with the correct spelling

dislike, dilike


- Can be used as a hard way to deal with inflections if no stemmer is used

like, likes, liked



Synonym Dictionaries

- Typically synonym words are listed in a file for string match
- Some tools allow certain flexibility in stating how the synonyms should be matched
 - Strictly as it appears in the definition, disallowing inflected forms
 - With any word starting with the term
 - With any word ending with the term



- A large lexical database of English
- Created and maintained by the Cognitive Science Laboratory of Princeton University
- *Nouns*, *verbs*, *adjectives* and *adverbs* are grouped into sets of cognitive synonyms (*synsets*), each expressing a distinct concept

Number of words, synsets, and senses


POS	Unique Synsets		Total
	Strings		Word-Sense Pairs
Noun	117798	82115	146312
Verb	11529	13767	25047
Adjective	21479	18156	30002
Adverb	4481	3621	5580
Totals	155287	117659	206941

Statistics from WordNet website

<http://wordnet.princeton.edu/wordnet/man/wnstats.7WN.html>

- Synsets are linked by conceptual-semantic and lexical relations
 - Lexical relations
 - Synonymy – e.g. *shut* and *close*, *happy* and *joyful*
 - Antonymy – e.g. *wet* and *dry*, *young* and *old*, *happy* and *sad*
 - Morphological relations
 - Semantic relations
 - Hyponymy (or ISA relation, super-subordinate relation) – e.g. *apple* and *fruit*, *bed* and *furniture*, *communicate* and *talk* and *whisper*
 - Meronymy (part-whole relation) – e.g. *leg* and *chair*
 - And more...

Figure 2. Network representation of three semantic relations among an illustrative variety of lexical concepts



From *Nouns in WordNet: A Lexical Inheritance System*

- Example information in Wordnet for “happy”:

Adjective

- (37) S: (adj) **happy#1** (enjoying or showing or marked by joy or pleasure)
- (2) S: (adj) felicitous#2, **happy#2** (marked by good fortune)
- S: (adj) glad#2, **happy#3** (eagerly disposed to act or to be of service)
- S: (adj) **happy#4**, well-chosen#1 (well expressed and to the point)

- Expanded view:

- (37) S: (adj) **happy#1** (enjoying or showing or marked by joy or pleasure)
 - see also
 - similar to
 - S: (adj) blessed#6 (characterized by happiness and good fortune)
 - S: (adj) blissful#1 (completely happy and contented)
 - S: (adj) bright#9 (characterized by happiness or gladness)
 - S: (adj) golden#2, halcyon#2, prosperous#3 (marked by peace and prosperity)
 - S: (adj) laughing#1, riant#1 (showing or feeling mirth or pleasure or happiness)
 - attribute
 - antonym
 - W: (adj) unhappy#1 [Opposed to: happy] (experiencing or marked by or causing sadness or sorrow or discontent)

- Free and open source
- Proved useful for a wide range of Natural Language Processing applications
 - Word sense disambiguation
 - Word semantic distance measuring
 - Mono- and cross-lingual Information retrieval,
 - Question-answering systems
 - Machine translation
 - Document structuring and categorisation

- Essential resources required for Opinion Mining to detect sentences containing subjective opinions.
- also known as *sentiment words*, *opinion words*, *polar words*, or *opinion-bearing words*.
- Lexicons or dictionaries of words or phrases that convey *positive* or *negative* sentiments, for example:

beautiful, wonderful, amazing...
bad, poor, awful...

- Such sentiment/opinion lexicon can be manually compiled (labor intensive and time consuming!), or ‘learned’ from dictionaries or corpora (not so easy too)

Challenges in Using Opinion Lexicon

- An opinion word's opinion orientation can be sensitive to its context.
 - E.g. *long* – **positive** or **negative**?
 - “The battery life is very *long*”
 - “The queue at the counter is very *long*”
- Sarcasm, in which the speakers say the opposite of what they mean
 - E.g. “What a **great** phone! It stopped working in two days.”





Defining Patterns using Regular Expressions



Defining patterns/rules

- With regular expression, we can extract strings containing certain characters, or not containing certain characters, or strings with pre-specified patterns of letters or numbers.
- Such patterns can be defined in a very compact way
 - E.g. regular expression for email addresses
`[a-zA-Z0-9._-]+@([a-zA-Z0-9.-]+\.)+[a-zA-Z]{2,4}`
 - Strings matching this expression can then be extracted
 - E.g. zhenzhen@nus.edu.sg

Regular expressions are very useful in extracting concepts expressed in a certain way, e.g. *currency, dates, e-mail addresses, phone numbers*, etc.



Common Operators

- Special characters (operators) are used to define character patterns

Operator	Purpose
.	(period) Match any single character E.g. .in matches both Windows , and Linux
^	Match the empty string that occurs at the beginning of a line or string E.g. ^tre will not match stretch
\$	Match the empty string that occurs at the end of a line
\d	Match any single digit
\D	Match any single non-digit character
\w	Match any single alphanumeric character



Common Operators

Operator	Purpose
?	Match the preceding character 0 or 1 time E.g. colou?r matches color (0) and colour (1)
*	Zero or more of the preceding character E.g. tre* matches tree (2), tread (1), and trough (0)
+	Match the preceding character 1 or more times E.g. tre+ matches tree , and tread
[...]	Match anything inside the square brackets for one character position once E.g. [0-9] matches any character in the range 0-9 [abc] matches a , b , or c
[^...]	Match any character excluding those in the square brackets E.g. [^A-M]in matches Windows , but not Linux




Common Operators

Operator	Purpose
{n}	Match the preceding character, or character range, n times E.g. [0-9]{3}-[0-9]{4} matches local phone number like 123-4567
{n,m}	Match the preceding character at least n times but not more than m times E.g. [A-Z]{2,4} matches <i>com</i> , <i>sg</i> , but not <i>abcde</i>
()	Group parts of search expression together
	Separate two alternative values E.g. gr(a e)y matches both <i>gray</i> and <i>grey</i>
\b	Match empty string, frequently used to indicate a word boundary E.g. \bhis\b matches <i>his</i> only, not <i>this</i> or <i>history</i>



Regular Expression

- Take a look at our email pattern regex again:



- GA Miller. WordNet: A Lexical Database for English, *Communications of the ACM*, 1995
- GA Miller. Nouns in WordNet: A Lexical Inheritance System, *International Journal of lexicography*, Oxford University Press, 1990
- Morato, Marzal, Llorens and Moreiro. WordNet Applications, in Proceedings of Global WordNet Conference, pp. 270-278, 2004.
- B. Liu. *Sentiment Analysis and Opinion Mining*, Morgan & Claypool, 2012.
- Grouin, Cyril, et al. Proposal for an Extension of Traditional Named Entities: from Guidelines to Evaluation, an Overview. *5th Linguistics Annotation Workshop (The LAW V)*. 2011.
- Regular Expression Tutorial:
<http://www.zytrax.com/tech/web/regex.htm>