Do Relation Graphs Help Stock Forecasting? A Placebo-Graph Test

Alexander Apartsin
Holon Institute of Technology, Holon, Israel
apartsin@gmail.com

Yehudit Aperstein*
Afeka Tel Aviv Academic College of Engineering, Tel Aviv, Israel
*Corresponding author

Abstract

Graph-based stock forecasters report gains from links between firms, such as shared industries or business concepts, yet the standard evaluation compares them only with models that lack the graph and the machinery that uses it, so the gain cannot be attributed to the links. We propose a placebo-graph test for this attribution: the forecaster is retrained with placebo graphs that keep the size and shape of the real graph but scramble who is linked to whom, and the paired difference in forecast accuracy is estimated over training seeds and test days. Applied to three published models in three equity markets, the real graph forecasts no better than its random and degree-preserving placebos on ranking accuracy, forecast-comparison tests and portfolio returns, with equivalence bounds of 0.002 to 0.005 in daily rank correlation. Where models beat simpler baselines, the gain comes from the architecture and its training, not from the specific links. A planted-signal experiment shows that the test detects a strong relational signal when the model can learn it, and that two of the models do not learn a planted neighbour signal even when it runs along their own graph. The test is cheap and model-agnostic, and it gives forecasters a routine check of whether a relational input adds predictive value.

Keywords: forecast evaluation ; placebo test ; graph neural networks ; stock return prediction ; equivalence testing ; reproducibility

1 Introduction

A growing literature forecasts stock returns with graph neural networks that pass information between related firms. The relations come from industry classifications, knowledge bases such as Wikidata, business-concept tags, supply chains or co-movement (Feng et al., 2019; Kim et al., 2019; Sawhney et al., 2021; Xu et al., 2021; Zheng et al., 2023). The economic motivation is sound: news and returns propagate along economic links (Cohen and Frazzini, 2008), and industry effects explain part of momentum (Moskowitz and Grinblatt, 1999). Published models report gains over sequence-only baselines and attribute them to the relation graph, in a field where machine-learning forecasts of returns are now standard (Gu et al., 2020) and graph convolutions over corporate relations were introduced early (Chen et al., 2018).

That attribution is rarely tested. A relational model differs from its sequence-only baseline in two ways at once: it receives the relation graph, and it has extra machinery for mixing information across stocks. A gain over the baseline can come from either. The comparison that isolates the graph keeps the machinery and replaces the graph with one that has the same size and shape but carries no information about which firms are related. If the real graph does not beat such a placebo, the specific relations are not what the model learned from.

This paper introduces PlaceboGraph, a validation protocol built on that comparison. A forecaster is retrained under a family of placebo graphs, each preserving a different property of the real graph: the number of links, every firm's number of links, the training-period co-movement structure, or none of the structure (uniform mixing across all firms, or no cross-firm links at all). The real graph's advantage over each placebo is estimated with seeds paired across conditions and a block bootstrap over test days, and the family of comparisons is corrected for multiple testing. Which placebo closes the gap diagnoses what the graph contributes.

We apply the protocol to three published models, each run on the authors' data with the authors' code (RSR in a PyTorch port verified against the original) and first reproduced against its published results or released checkpoint: the Relational Stock Ranking model of Feng et al. (2019) on NYSE and NASDAQ with industry and Wikidata relations, HIST (Xu et al., 2021) on the Chinese CSI300 with business-concept relations, and RT-GCN (Zheng et al., 2023) on NASDAQ with combined industry and Wikidata relations. In every case the real graph forecasts as well as its random and degree-preserving placebos and no better. The primary test, a two-way bootstrap of the daily rank correlation, finds no difference against any structure-matched placebo, and Diebold-Mariano and Giacomini-White tests (Diebold and Mariano, 1995; Harvey et al., 1997; Giacomini and White, 2006) find none against the random and degree-preserving placebos. With seeds and test days both resampled, equivalence bounds place the real graph's advantage over a random graph within 0.002 to 0.005 in daily rank correlation; on NASDAQ and CSI300 this is 3% to 9% of the model's own rank correlation.

A null result is only informative if the test can detect an effect. We therefore plant a relational signal into the returns of every market, built from each firm's real-graph neighbours and orthogonal to the firm's own inputs, and rerun the placebo family. The control separates two explanations of placebo

equivalence. For RSR the protocol detects the planted signal at a strength of 0.10 in correlation with next-day returns against every structure-matched placebo in both markets, and the equivalence bounds of the published RSR graphs against the random placebo lie below the advantage that this signal produces. Detection requires a strong signal: at strength 0.10 the planted term alone ranks NYSE stocks with a rank correlation of 0.15, above the total skill of published models, and a signal half as strong is not detected. We therefore report, for every cell, the smallest advantage the test detects with 80% power. For HIST and RT-GCN, the real graph does not separate from its placebos at a planted strength of 0.10, although the planted term alone ranks test-day stocks with a rank correlation of 0.09 on RT-GCN's data: the trained models' predictions are uncorrelated with it under every graph. These two models, trained with their published recipes, do not learn a neighbour-mean lead-lag signal of this form even when it runs along their own graph.

The protocol also locates where the reported gains come from. On NASDAQ, the Feng et al. model with Wikidata relations beats a uniform-mixing placebo, but random graphs, degree-preserving graphs and a graph without cross-firm links all match it: mixing every firm with the whole market hurts, while sparse links, real or random, add nothing over no links. HIST beats its sequence-only base model, and a concept graph without any links keeps about 80% of that gain; an LSTM trained for HIST's longer budget recovers about 40% of it: the improvement comes from HIST's additional modules and training, not from the predefined concepts.

The contributions are: (i) a model-agnostic placebo-graph protocol with paired inference, a diagnosis rule and an open implementation; (ii) a reproduction-first audit of three published relational stock forecasters across three markets; (iii) a planted-signal control that makes the equivalence results interpretable and separates graphs without usable information from models that do not learn relational signal; and (iv) the full battery of forecast-evaluation tests that the forecasting literature uses to compare models.

2 Related work

Relational stock forecasting Feng et al. (2019) introduced temporal relational ranking with industry and Wikidata relations on NYSE and NASDAQ; Kim et al. (2019) used hierarchical attention over Wikidata relations; Sawhney et al. (2021) used hypergraphs over the same data; HIST (Xu et al., 2021) combines predefined business concepts with learned hidden concepts on CSI300 through the Qlib platform (Yang et al., 2020); RT-GCN (Zheng et al., 2023) adds time-aware relation weighting. These papers compare against sequence-only baselines and, in some cases, remove one relation type at a time. None reports a placebo graph with the real graph's size and shape. Niu et al. (2024) evaluate financial relation graphs before any model is trained, by how well a graph explains past co-movement; PlaceboGraph instead tests whether a trained forecaster uses its graph, by retraining it under placebos. Student analyses of graph models for equity returns (Bocconi Students Investment Club (BSIC), 2026a,b) report a single random-graph control in which the random graph matches or beats the real one, without intervals or a family of controls.

Do graph models use their graphs? Errica et al. (2020) showed that structure-agnostic baselines rival graph networks on graph classification; Bechler-Speicher et al. (2024) showed that graph networks fit uninformative graph structure; Katsman et al. (2024) found that many graph benchmarks do not require graph learning. Coupette et al. (2025) propose evaluating graph datasets with perturbed graphs (empty, complete, random and shuffled) for graph-level classification. Hussain et al. (2021) compare stochastic-block-model, configuration-model and Erdős-Rényi nulls to attribute node-classification gains to communities or degree. In spatio-temporal forecasting, simple identity-based models match graph models (Shao et al., 2022, 2025), adaptive graphs replace predefined ones (Bai et al., 2020), and single rewired-graph controls appear in anomaly forecasting (Pillai, 2025). In fraud detection, shuffled edges outperform the real transaction graph under temporal shift (Maganti, 2026). Rewiring surveys recommend random and degree-preserving baselines (Attali et al., 2024), following the degree-preserving swap of Maslov and Sneppen (2002). PlaceboGraph differs from this work in four respects: a property-indexed family of placebos including correlation-matched graphs, paired inference over time and seeds, a diagnosis rule, and an audit of published forecasters run with their own code and data.

Forecast evaluation and reproducibility We use the Diebold-Mariano test with heteroskedasticity- and autocorrelation-consistent variance (Diebold and Mariano, 1995; Newey and West, 1987) and the small-sample correction of Harvey et al. (1997), the conditional predictive-ability test of Giacomini and White (2006), which allows for estimated models, the adjusted test of Clark and West (2007) for nested models, the model confidence set (Hansen et al., 2011), which extends the superior-predictive-ability test of Hansen (2005) to sets of models, block and stationary bootstraps (Künsch, 1989; Politis and Romano, 1994), false-discovery-rate control (Benjamini and Hochberg, 1995), Sharpe-ratio comparisons (Ledoit and Wolf, 2008) and equivalence testing (Schuirmann, 1987). Multiple testing in return prediction is a known source of spurious findings (Harvey et al., 2016), and recent work documents spurious predictability in financial machine learning from the data side (Nikolopoulos, 2026). Reproducibility audits in recommender systems found that simple baselines match most neural methods (Ferrari Dacrema et al., 2021); our audit is the relational-forecasting counterpart.

Economic links and permutation inference Return predictability along economic links is documented directly: customer returns predict supplier returns (Cohen and Frazzini, 2008), industry information diffuses with a lead-lag (Hou, 2007) and returns cross-predict within related segments (Menzly and Ozbas, 2010). Our planted signal reproduces this mechanism, a neighbour-mean lead-lag spillover, inside the forecasters' own data. Placebo graphs are a permutation test

on the adjacency, in the tradition of bootstrap and permutation inference against data snooping in forecast evaluation (White, 2000; Romano and Wolf, 2005): the real graph is compared with graphs drawn from a null that preserves a named property of it.

3 The PlaceboGraph protocol

3.1 Setup

A relational forecaster F maps a panel of firm histories X and a relation graph G to next-period scores. We write G as an $N \times N \times K$ binary tensor over N firms and K relation types, so that firms i and j are linked if any of the K entries for the pair is one. The protocol holds F, its hyperparameters, data, training budget and model-selection rule fixed, and varies only G.

3.2 The placebo family

Each placebo preserves a named property of the real graph G and destroys the rest (Table 1).

The random placebo reassigns the real graph's relation vectors to the same number of uniformly drawn firm pairs. The degree-preserving placebo applies ten successful double-edge swaps per link (Maslov and Sneppen, 2002), so every firm keeps its number of links while its partners change; when relations are typed, the swap acts on the union graph and each link carries its relation vector. The correlation-matched placebo places the same number of links on the firm pairs with the highest return correlation over the training period only, and assigns them the real relation vectors at random. This placebo answers whether the real graph adds anything beyond co-movement that a forecaster could estimate from its own training data. Uniform mixing and self-loops-only bracket the space: the first replaces sparse aggregation with a market average, the second removes cross-firm information while keeping the model's architecture. The no-graph base model is the sequence-only model from which the relational model is built.

3.3 Paired inference

Every condition is trained with the same S seeds, so that seed s shares initialisation and data order across conditions. For a daily metric $m_{c,s,t}$ of condition c, seed s and test day t (we use the cross-sectional rank correlation between scores and next-day returns, the rank IC), the real graph's advantage over placebo c is

$$\Delta_c = \frac{1}{ST} \sum_{s=1}^{S} \sum_{t=1}^{T} \left(m_{\text{real},s,t} - m_{c,s,t} \right). \tag{1}$$

Confidence intervals come from a two-way bootstrap that resamples seeds with replacement and, independently, contiguous ten-day blocks of test days, drawn as circular moving blocks (Künsch, 1989), using the same day blocks for the real graph and the placebo (5,000 resamples). Seed-to-seed training variation therefore enters every interval. The pairing is informative: the across-day correlation of daily rank IC between the real graph and a structure-matched placebo is 0.76 to 0.78 for the same seed on NYSE, against 0.53 to 0.61 for different seeds. In simulations with the split between seed-level and day-level variance measured in these data (seed shares 0.3 to 0.7, ten or 20 seeds), the test rejects a true null in 4% to 8% of samples at the 5% level. This comparison of daily rank IC is the primary test; the forecast-comparison tests, the model confidence set and the portfolio comparisons are secondary analyses reported in full. Two-sided bootstrap p-values are adjusted with the Benjamini-Hochberg procedure (Benjamini and Hochberg, 1995) within each family, defined as the placebo comparisons of one model in one market for one metric; we report raw p-values alongside. Each family contains five or six tests; the forecast-comparison, model-confidence-set, portfolio and equivalence analyses below form separate families, each again defined as one model in one market for one loss or portfolio. Pooling all metrics of a model into one family leaves every rank-IC verdict unchanged. We report the same comparisons for top-k portfolio returns.

3.4 Diagnosis

The pattern of placebo comparisons identifies what the graph contributes. If the real graph beats random, degree-preserving and correlation-matched placebos, the specific relations carry information. If it beats self-loops but not the structure-matched placebos, sparse aggregation helps but the identity of neighbours does not. If it beats only uniform mixing, dense mixing hurts and sparse links, real or not, add nothing over none. If it beats the no-graph base model but not the placebos, the benefit comes from the architecture. If it beats nothing, the graph is unused.

3.5 Positive control

To show that the test detects relational information when it is present, we plant a signal that only the real graph can deliver. For firm j on day t let $u_{j,t}$ be a source signal visible in firm j's model input on day t. For each firm i with at least one real-graph neighbour, the planted term $z_{i,t}$ is the mean of $u_{j,t}$ over i's neighbours, residualised day by day on $u_{i,t}$ among firms with neighbours and standardised. Firms without neighbours receive no planted term. The planted target is

$$\tilde{r}_{i,t+1} = r_{i,t+1} + \beta\, z_{i,t}, \tag{2}$$

with β chosen so that the planted term has correlation ρ with $\tilde{r}$ over all training cells (for HIST, whose data arrive as separate splits, within each split; this sets only the scale of the term). The residualisation makes the planted term invisible to a model that sees only firm i's own input (the correlation between $z_{i,t}$ and $u_{i,t}$ is below 0.001 in every market). We use two sources. The first, for RSR, is a fixed random projection $u_{j,t} = \langle e_{j,t}, w \rangle$ of the representation $e_{j,t}$ that the relational module aggregates, the most favourable case for detection ($\rho \in \{0.02, 0.05, 0.10\}$). The second, for all three models, is the firm's most recent daily return in the input window, so the planted term is a lead-lag spillover along the real graph ($\rho = 0.05$ for RSR on NYSE; $\rho \in \{0.05, 0.10\}$ for HIST and RT-GCN). For HIST, neighbours are stocks that share a predefined concept. The

Table 1: The placebo family. Each placebo is drawn afresh for every seed.

Placebo	Preserves	Destroys
Random	number of links; multiset of relation-type vectors	who is linked to whom
Degree-preserving	every firm's number of links (double-edge swaps)	which partners a firm has
Correlation-matched	number of links; links placed on the strongest training-period return correlations	semantic content of links
Uniform mixing	nothing; every firm mixes with all others	sparsity and identity
Self-loops only	nothing; no cross-firm links	all cross-firm information
No-graph base model	the model's sequence component only	the relational component

planted term reaches 99% of NYSE firms, 13% of NASDAQ firms in the RSR universe, 87% to 94% of CSI300 stocks and 98% of NASDAQ firms in the RT-GCN universe (47 neighbours on average). We rerun the placebo family at each strength, and report two diagnostics: the oracle rank IC of the planted term (its daily rank correlation with the planted target on test days), and the correlation between each trained model's test predictions and the planted term.

4 Data, models and reproduction

RSR on NYSE and NASDAQ We port the Relational Stock Ranking model (Feng et al., 2019) to PyTorch, preserving the authors' TensorFlow initialisation, loss (pointwise squared error plus a pairwise ranking hinge) and two-stage training, in which the relational module consumes the authors' pretrained sequential embeddings. Data are the authors' end-of-day panels: 1,737 NYSE and 1,026 NASDAQ stocks, 2013 to 2017, with their validation and test split (test year 2017, 237 trading days). On NASDAQ only 13% of firms have a Wikidata neighbour. We study the published best cells: the implicit-relation model (RSR-I) with industry relations on NYSE, and the explicit-relation model (RSR-E) with Wikidata relations on NASDAQ. Each condition is trained for 50 epochs with 20 seeds and the authors' market-specific hyperparameters, and keeps the epoch with the lowest validation loss; training windows follow the authors' code, in which the targets of the last training windows fall in the first days of the validation period.

HIST on CSI300 We run HIST (Xu et al., 2021) through Qlib (Yang et al., 2020) on the Alpha360 features of CSI300 constituents, with Qlib's benchmark configuration: training 2008 to 2014, validation 2015 to 2016, test January 2017 to July 2020 (871 test days). The predefined graph is the public stock-to-concept matrix (735 stocks by 4,635 concepts, 7,478 links). HIST is initialised from a Qlib LSTM trained with the same seed; that LSTM is the no-graph base model. For the concept graph, the random placebo moves links uniformly, the degree-preserving placebo swaps links while keeping every stock's and every concept's size, and the correlation-matched placebo keeps each concept's size and one randomly chosen true member and fills the remaining slots with that member's most correlated stocks over the training period. HIST's empty placebo removes every stock-to-concept link, so no information flows through predefined concepts; it is reported in the no-cross-firm-links row. HIST's learned hidden-concept module still mixes information across stocks under every placebo, so HIST always has a learned graph in addition to the predefined one.

Table 2: Reproduction of published results (real graph, mean and standard deviation over seeds). Published values: Feng et al. (2019), Tables 5 to 7; Qlib Alpha360 benchmark (20 seeds). [a]The RT-GCN authors' released checkpoint scored with our evaluation code.

Market	Model	Metric	Published	Ours	Seeds
NYSE	RSR-I (industry)	MSE	2.26e-04	2.27e-04	20
		top-1 IRR	1.06 ± 0.27	0.96 ± 0.58	20
NYSE	Rank-LSTM (no graph)	MSE	2.28e-04	2.27e-04	20
		top-1 IRR	0.56 ± 0.68	0.41 ± 0.69	20
NASDAQ	RSR-E (Wikidata)	MSE	3.80e-04	3.79e-04	20
		top-1 IRR	0.81 ± 0.85	0.87 ± 0.63	20
NASDAQ	Rank-LSTM (no graph)	MSE	3.79e-04	3.80e-04	20
		top-1 IRR	0.68 ± 0.60	0.52 ± 0.83	20
CSI300	HIST (concepts)	IC	0.0522	0.0503 ± 0.0035	10
		rank IC	0.0667	0.0661 ± 0.0025	10
	LSTM (no graph)	IC	0.0448	0.0445 ± 0.0037	10
		rank IC	0.0549	0.0545 ± 0.0024	10
NASDAQ	RT-GCN (time-aware)	rank IC	0.0278[a]	0.0374 ± 0.0040	10

RT-GCN on NASDAQ We run RT-GCN (Zheng et al., 2023) with the authors' model code and data: 854 NASDAQ stocks with 136 industry and Wikidata relation types (39,669 linked pairs, 98% of stocks linked), 1,295 training days and 172 test days, and the authors' configuration (time-aware relation weighting, Adam with learning rate 0.1 decayed at epochs 5 and 25, weight decay 0.1, batch 64, 100 epochs). The authors' code keeps the epoch with the lowest test loss; we hold out the last 20% of the training days for validation and keep the epoch with the lowest validation loss in every condition. RT-GCN always adds self-loops, so its uniform-mixing placebo is a complete graph with a single relation type.

Reproduction Table 2 compares our real-graph runs with published results. RSR matches the published mean squared errors to within 0.5% and the published top-1 investment returns within one seed standard deviation; HIST and its LSTM base reproduce Qlib's 20-seed benchmark to within 0.002 in IC. RT-GCN reaches a mean rank IC of 0.037 over ten seeds; the authors' released checkpoint, scored with the same evaluation code, reaches 0.028, so we compare against the checkpoint, which our runs exceed.

5 Results

5.1 The real graph matches its placebos

Figure 1 and Table 3 report the real graph's advantage in daily rank IC over each placebo. Against the three structure-matched placebos (random, degree-preserving and correlation-matched), 12 of 12 comparisons across 4 model-market cells show no difference after the Benjamini-Hochberg correction.

5.2 Where the gains come from

On NASDAQ the Wikidata graph beats uniform mixing by 0.025 in rank IC ($q = 0.005$), while random, degree-preserving and correlation-matched placebos match it, and so does the graph without cross-firm links (−0.0005). Uniform mixing lowers accuracy; sparse links, real or random, add nothing over none. On CSI300, HIST beats its LSTM base by 0.012 in rank IC ($q < 0.001$), yet every concept placebo, including the graph without concept links, retains that gain: the link-free graph keeps about 80% of it. HIST's improvement over the LSTM comes from its additional modules and their training, not from the predefined concepts. An LSTM trained further with HIST's optimisation budget gains 0.005 (95% CI [0.003, 0.007]), and HIST still exceeds it by 0.007 ([0.001, 0.012]). With predefined links removed, HIST's learned hidden-concept module is its remaining channel for cross-stock information, a learned graph in place of the curated one, as adaptive graphs are in spatio-temporal forecasting (Bai et al., 2020). Holding out the validation period strictly from the RSR training windows leaves the verdict against the random placebo unchanged in both markets (ten seeds). On NYSE no condition differs from the real graph after correction; the raw intervals against the graph without cross-firm links and the no-graph base model lie below zero ($q = 0.12$). RT-GCN on NASDAQ, which uses a dense graph combining industry and Wikidata relations, matches every placebo, including the graph without cross-firm links: the time-aware relation weighting adds no forecasting value with the real relations, with random ones, or with none. With seeds resampled and the family corrected for multiple testing, no comparison with a structure-matched placebo is significant. The smallest raw p-value, NASDAQ against the correlation-matched placebo (0.0012, 95% CI [0.0000, 0.0024], $p = 0.046$, $q = 0.14$), reflects a placebo that forecasts slightly worse than random wiring: against the random and degree-preserving placebos the real graph's advantage is −0.0005 and 0.0002. The two largest point estimates against structure-matched placebos (NYSE correlation-matched and NASDAQ RT-GCN degree-preserving) favour the placebo. The verdicts are stable over time: computed separately on the first and second half of each test period, the real graph beats no structure-matched placebo in either half.

The placebos differ in how they distribute links. The degree-preserving placebo keeps every firm's number of links exactly (NYSE: maximum 499, median 29, as in the real graph). The random placebo flattens the distribution (NYSE maximum 199), and the correlation-matched placebo concentrates links on highly co-moving firms (NYSE maximum 1,008, 11.5% of firms without links). Agreement across placebos with such different degree distributions shows that the equivalence does not depend on one particular graph shape.

5.3 The positive control

Figure 2 and Table 5 report the positive control for RSR. On NYSE the real graph's advantage over each structure-matched placebo grows with ρ; at $\rho = 0.02$ and 0.05 the intervals include zero in both markets. At $\rho = 0.10$ the real graph beats every graph placebo in both markets and, on NYSE, the no-graph base model. The oracle rank IC of the planted term is 0.08 at $\rho = 0.05$ and 0.15 at $\rho = 0.10$ on NYSE; the daily rank correlation of the strongest models in the Qlib CSI300 benchmark lies between 0.05 and 0.07 (Yang et al., 2020). The test therefore detects relational signal whose own ranking power exceeds that of published forecasters, and the minimum detectable effects in Table 9 state its resolution in every cell. The realistic return-based signal at $\rho = 0.05$ on NYSE produces a real-graph advantage of 0.003 against each structure-matched placebo (Table 4), with intervals that include zero whether or not seeds are resampled, and the trained RSR models barely track the planted term: their test predictions correlate +0.003 with it under the real graph and −0.015 under each placebo (20 seeds, pooled over planted test cells).

The same control applied to HIST and RT-GCN separates a different explanation. At $\rho = 0.10$, the real graph does not beat any structure-matched placebo for either model, although the planted term carries ranking information: its oracle rank IC on RT-GCN's test days is 0.09, more than twice RT-GCN's own rank IC. Planting leaves their real-graph rank IC unchanged (HIST 0.066 unplanted and 0.064 planted; RT-GCN 0.037 and 0.038), and RT-GCN's predictions correlate +0.002 with the planted term under every graph, the real one included. These models, trained with their published recipes, do not learn a neighbour-mean lead-lag signal of this form, although it exists in the data and runs along their own graph. For them, placebo equivalence shows that the trained model does not use this kind of relational signal; for RSR, which separates the real graph from every placebo once a strong planted signal runs along it, placebo equivalence shows that the published graphs carry no relational signal above the minimum detectable effect.

5.4 Forecast-comparison tests

Table 6 reports Diebold-Mariano tests with Newey-West variance and the Harvey-Leybourne-Newbold correction, Giacomini-White conditional tests with the lagged loss differential as instrument, and membership of the 90% model confidence set. Both use the daily loss averaged over the seeds (20 for RSR, ten for HIST and RT-GCN), which compares two seed ensembles; we also run the test for every seed separately, which compares single deployed models. With loss equal to minus the rank IC, the real graph has equal accuracy to the random and degree-preserving placebos for all three models and all three markets; it is more accurate than uniform mixing on NASDAQ and than the LSTM base on CSI300, matching the diagnosis above, and the Diebold-Mariano test also ranks it above the NASDAQ correlation-matched placebo, the placebo that forecasts slightly worse than random wiring (difference




Figure 1: Real graph minus placebo in daily rank IC: mean over paired seeds (20 for RSR, ten for HIST and RT-GCN) and test days, with 95% two-way bootstrap intervals (seeds and day blocks resampled). Structure-matched placebos: random, degree-preserving, correlation-matched. Filled markers: Benjamini-Hochberg $q < 0.05$.

Table 3: Real graph minus placebo, daily rank IC. Intervals: two-way bootstrap over seeds and ten-day blocks of test days (5,000 resamples). p: raw two-sided bootstrap p-value; q: Benjamini-Hochberg within the model-market cell for rank IC.

Market (model, graph)	Placebo	Δ rank IC	95% CI	p	q_{BH}	Verdict
NYSE (RSR-I, industry)	Random	-0.0010	[-0.0053, 0.0037]	0.644	0.646	no difference
	Degree-preserving	-0.0011	[-0.0059, 0.0037]	0.646	0.646	no difference
	Correlation-matched	-0.0018	[-0.0060, 0.0027]	0.420	0.646	no difference
	Uniform mixing	-0.0026	[-0.0095, 0.0042]	0.436	0.646	no difference
	No cross-firm links	-0.0046	[-0.0084, -0.0004]	0.037	0.124	no difference
	No-graph base model	-0.0111	[-0.0219, -0.0005]	0.041	0.124	no difference
NASDAQ (RSR-E, Wikidata)	Random	-0.0005	[-0.0032, 0.0017]	0.759	0.784	no difference
	Degree-preserving	0.0002	[-0.0014, 0.0019]	0.768	0.784	no difference
	Correlation-matched	0.0012	[0.0000, 0.0024]	0.046	0.138	no difference
	Uniform mixing	0.0254	[0.0104, 0.0409]	<0.001	0.005	real better
	No cross-firm links	-0.0005	[-0.0041, 0.0033]	0.784	0.784	no difference
	No-graph base model	-0.0042	[-0.0155, 0.0075]	0.450	0.784	no difference
CSI300 (HIST, concepts)	Random	0.0000	[-0.0022, 0.0025]	0.975	0.975	no difference
	Degree-preserving	0.0004	[-0.0013, 0.0021]	0.570	0.712	no difference
	Correlation-matched	-0.0011	[-0.0027, 0.0004]	0.137	0.244	no difference
	No cross-firm links	0.0021	[-0.0008, 0.0051]	0.146	0.244	no difference
	No-graph base model	0.0115	[0.0063, 0.0167]	<0.001	<0.001	real better
NASDAQ (RT-GCN, industry and Wikidata)	Random	0.0005	[-0.0019, 0.0028]	0.640	0.653	no difference
	Degree-preserving	-0.0014	[-0.0045, 0.0012]	0.279	0.653	no difference
	Correlation-matched	0.0008	[-0.0025, 0.0045]	0.634	0.653	no difference
	Uniform mixing	0.0013	[-0.0030, 0.0074]	0.653	0.653	no difference
	No cross-firm links	0.0008	[-0.0016, 0.0038]	0.563	0.653	no difference

Table 4: Positive control across models: real graph minus structure-matched placebo, daily rank IC (RSR 20 seeds, HIST and RT-GCN ten). *: Benjamini-Hochberg $q < 0.05$ within the cell, two-way bootstrap.

Model, market	Planted source	ρ	Random	Degree-preserving	Correlation-matched
RSR-I, NYSE	embedding	0.05	0.0063	0.0077	0.0052
	embedding	0.10	0.0289*	0.0282*	0.0255*
	return	0.05	0.0031	0.0030	0.0028
HIST, CSI300	return	0.05	-0.0003	0.0005	-0.0003
	return	0.10	0.0007	0.0010	0.0005
RT-GCN, NASDAQ	return	0.05	0.0001	0.0000	-0.0007
	return	0.10	0.0007	0.0000	0.0004

0.0012 in rank IC, $q = 0.013$; Giacomini-White $q = 0.06$). On NYSE the Diebold-Mariano test ranks the real graph below the graph without cross-firm links and the no-graph base model ($q = 0.036$; Giacomini-White $q = 0.09$), so its links do not help there. The Giacomini-White test finds no difference

Table 5: Positive control: real graph minus placebo, daily rank IC, by planted strength ρ (20 seeds per condition). *: Benjamini-Hochberg $q < 0.05$ within each strength.

Market	Placebo	$\rho = 0$	$\rho = 0.02$	$\rho = 0.05$	$\rho = 0.10$
NYSE	Random	-0.0010	0.0023	0.0063	0.0289*
NYSE	Degree-preserving	-0.0011	0.0037	0.0077	0.0282*
NYSE	Correlation-matched	-0.0018	0.0030	0.0052	0.0255*
NYSE	Uniform mixing	-0.0026	0.0004	0.0060	0.0333*
NYSE	No cross-firm links	-0.0046	-0.0007	0.0032	0.0286*
NYSE	No-graph base model	-0.0111	-0.0072	-0.0019	0.0232*
NASDAQ	Random	-0.0005	0.0008	0.0007	0.0056*
NASDAQ	Degree-preserving	0.0002	-0.0000	-0.0002	0.0022*
NASDAQ	Correlation-matched	0.0012	0.0006	0.0023	0.0070*
NASDAQ	Uniform mixing	0.0254*	0.0274*	0.0278*	0.0337*
NASDAQ	No cross-firm links	-0.0005	-0.0002	0.0005	0.0052*
NASDAQ	No-graph base model	-0.0042	-0.0043	-0.0034	0.0010

between the real graph and any structure-matched placebo




Figure 2: Positive control: real graph minus placebo in daily rank IC as a function of the planted relational signal strength ρ ($\rho = 0$ is the unplanted experiment). Bars: 95% two-way bootstrap intervals (seeds and day blocks). RSR only. Filled markers: Benjamini-Hochberg $q < 0.05$.

in any cell. For the nested comparison of each RSR variant with its no-graph base model, the Clark and West (2007) test finds on NASDAQ that every variant with a relational module, the real graph, every placebo and the graph without cross-firm links alike, improves on the base model in squared error ($q < 0.002$), and on NYSE that none does; the relational module helps on NASDAQ regardless of the graph it is given. Per seed (Table 7), the real graph is more accurate than a random or degree-preserving placebo in at most 3 of 20 seeds (RSR) or 2 of 10 (HIST, RT-GCN) and less accurate in up to 5 of 20, with no consistent direction; against the NASDAQ correlation-matched placebo it is more accurate in 10 of 20 seeds. With squared-error loss, the daily loss differentials are small but very stable, so they are highly significant, and their sign changes across placebos. They reflect the scale of the predicted returns, not ranking: RSR's predicted returns have a standard deviation of 0.0003 to 0.0007 on NYSE and 0.0014 to 0.0057 on NASDAQ, against 0.015 and 0.019 for realised returns, so squared error is almost entirely the variance of the returns and moves with small differences in prediction spread. RT-GCN's predicted returns are over-dispersed (standard deviation 0.42 to 0.49 against 0.033), and the real graph produces among the most dispersed predictions, which is why every placebo attains a lower squared error than the real graph. The model confidence set never singles out the real graph. On NASDAQ it keeps the real graph together with the random and degree-preserving placebos, the graph without cross-firm links and the no-graph base model. In the other three cells it excludes the real graph: on NYSE the no-graph base model has the highest rank IC, on CSI300 the correlation-matched placebo is the only member, and for RT-GCN the set keeps the degree-preserving and uniform-mixing placebos.

5.5 Economic value

Table 8 reports daily-rebalanced equal-weight long portfolios of the top-ranked stocks, with equal capital across the seed portfolios, net of 5 basis points per side for RSR and RT-GCN (turnover computed from the saved predictions) and gross for HIST, whose saved outputs contain no positions. Sharpe-ratio differences are tested with a circular block bootstrap over days and corrected within each model, market and portfolio. For the top-5 net portfolios no difference survives the correction; on NYSE the graph placebos reach net Sharpe ratios of 0.98 to 1.21 against 0.56 for the real graph (0.47 for the no-graph base model). Before costs, every NYSE graph placebo has a higher top-5 Sharpe ratio than the real graph ($q \leq 0.039$); on NASDAQ the real graph's top-10 net portfolio beats uniform mixing and the no-graph base model ($q = 0.007$). The real NYSE industry graph trades least, with daily top-5 turnover of 0.29 against 0.46 to 0.59 for the alternatives. RT-GCN rankings change slowly under every graph (daily top-5 turnover 0.04 to 0.05), because its scores are driven by predicted price levels.

5.6 Equivalence bounds

Failing to reject a difference is not evidence of equivalence. Table 9 reports, for the structure-matched placebos, 90% two-way bootstrap intervals, the two one-sided test of Schuirmann (1987) at the margin $\delta = 0.005$ in rank IC (a tenth of the rank IC of the strongest published CSI300 models), the smallest margin $\delta_{\min}$ at which equivalence holds, and the minimum detectable effect (MDE), the advantage that the primary test detects with 80% power at the 5% level. Against the random placebo the real graph's advantage lies within ±0.0047 (NYSE, RSR), ±0.0027 (NASDAQ, RSR), ±0.0020 (CSI300, HIST) and ±0.0024 (NASDAQ, RT-GCN) in rank IC, and equivalence at $\delta = 0.005$ holds in all four cells. Relative to each model's own rank IC these bounds are 9% (NASDAQ, RSR), 3% (CSI300) and 6% (NASDAQ, RT-GCN); on NYSE the RSR

Table 6: Diebold-Mariano statistics (positive: the real graph has higher loss) with Newey-West variance and Harvey-Leybourne-Newbold correction, Giacomini-White conditional statistics (instruments: constant and lagged loss differential), both Benjamini-Hochberg adjusted, and membership of the 90% model confidence set (MCS p-value in parentheses; loss = −rank IC, stationary bootstrap).

Market	Condition	DM, loss = −rank IC		GW, loss = −rank IC		DM, loss = MSE		In 90% MCS
		stat	q_{BH}	χ^2_2	q_{BH}	stat	q_{BH}	
NYSE (RSR)	Real graph	–	–	–	–	–	–	no (0.01)
	Random	0.55	0.586	0.30	0.863	23.53	<0.001	no (0.02)
	Degree-preserving	0.61	0.586	0.49	0.863	0.50	0.660	no (0.01)
	Correlation-matched	1.06	0.438	3.73	0.310	9.13	<0.001	no (0.00)
	Uniform mixing	1.08	0.438	2.30	0.474	-0.44	0.660	yes (0.10)
	No cross-firm links	2.62	0.036	7.75	0.091	5.72	<0.001	yes (0.16)
	No-graph base model	2.53	0.036	7.00	0.091	3.70	<0.001	yes (1.00)
NASDAQ (RSR)	Real graph	–	–	–	–	–	–	yes (0.76)
	Random	0.62	0.760	0.27	0.956	0.72	0.564	yes (0.76)
	Degree-preserving	-0.37	0.760	0.40	0.956	0.22	0.824	yes (0.76)
	Correlation-matched	-2.89	0.013	7.86	0.059	1.13	0.387	no (0.05)
	Uniform mixing	-3.86	<0.001	13.22	0.008	-8.21	<0.001	no (0.00)
	No cross-firm links	0.31	0.760	0.09	0.956	3.89	<0.001	yes (0.76)
	No-graph base model	0.90	0.738	4.09	0.259	-2.87	0.009	yes (1.00)
CSI300 (HIST)	Real graph	–	–	–	–	–	–	no (0.03)
	Random	-0.02	0.981	2.94	0.288	–	–	no (0.03)
	Degree-preserving	-0.79	0.534	0.70	0.706	–	–	no (0.02)
	Correlation-matched	2.05	0.101	4.41	0.241	–	–	yes (1.00)
	No cross-firm links	-1.76	0.131	3.87	0.241	–	–	no (0.01)
	No-graph base model	-4.74	<0.001	21.88	<0.001	–	–	no (0.00)
NASDAQ (RT-GCN)	Real graph	–	–	–	–	–	–	no (0.06)
	Random	-0.82	0.490	1.37	0.503	8.63	<0.001	no (0.01)
	Degree-preserving	2.06	0.205	5.37	0.341	8.96	<0.001	yes (1.00)
	Correlation-matched	-1.57	0.297	2.52	0.503	8.53	<0.001	no (0.06)
	Uniform mixing	-0.69	0.490	2.17	0.503	11.93	<0.001	yes (0.14)
	No cross-firm links	-1.20	0.388	1.73	0.503	9.11	<0.001	no (0.06)

Table 7: Diebold-Mariano tests per seed (loss = −rank IC): median statistic over the seeds and the number of seeds in which the real graph or the placebo is significantly more accurate at the 5% level.

Market	Placebo	Median DM	Real better	Placebo better
NYSE (RSR)	Random	0.05	1 of 20	4 of 20
	Degree-preserving	0.44	2 of 20	5 of 20
	Correlation-matched	0.33	1 of 20	3 of 20
	Uniform mixing	-0.01	0 of 20	3 of 20
	No cross-firm links	0.78	0 of 20	6 of 20
	No-graph base model	1.52	0 of 20	9 of 20
NASDAQ (RSR)	Random	-0.01	3 of 20	3 of 20
	Degree-preserving	-0.76	1 of 20	2 of 20
	Correlation-matched	-1.99	10 of 20	0 of 20
	Uniform mixing	-3.19	17 of 20	0 of 20
	No cross-firm links	0.08	0 of 20	3 of 20
	No-graph base model	0.31	0 of 20	6 of 20
CSI300 (HIST)	Random	0.18	2 of 10	2 of 10
	Degree-preserving	-0.65	1 of 10	0 of 10
	Correlation-matched	1.00	0 of 10	1 of 10
	No cross-firm links	-1.33	3 of 10	0 of 10
	No-graph base model	-3.59	10 of 10	0 of 10
NASDAQ (RT-GCN)	Random	-0.15	1 of 10	0 of 10
	Degree-preserving	0.73	0 of 10	2 of 10
	Correlation-matched	-1.38	2 of 10	2 of 10
	Uniform mixing	-0.65	1 of 10	1 of 10
	No cross-firm links	-0.73	0 of 10	1 of 10

model's rank IC is itself close to zero (0.004), so the NYSE bound is as large as the model's whole signal and the NYSE cell carries the least weight. The minimum detectable advantage over the random placebo is 0.006 (NYSE), 0.004 (NASDAQ), 0.003 (CSI300) and 0.003 (RT-GCN). For both RSR markets the advantage that the $\rho = 0.10$ planted signal produces against the random placebo (NYSE 0.029, NASDAQ 0.006) exceeds both the equivalence bound and the MDE.

6 Discussion

What the results mean for model builders The three audited models improve on their simplest baselines in some markets, and the protocol shows why: through the relational module itself, which improves squared error on NASDAQ whatever graph it is given (RSR), or through architecture and training (CSI300, HIST). Neither mechanism requires the curated relation graph, and a random graph with the same number of links delivers the same forecasts. Industry, Wikidata and concept relations are cheap to collect, so their equivalence to placebos is not a cost argument; it is an argument about attribution and about where modelling effort pays off.

Recommendations We recommend that relational forecasting papers report, alongside the sequence-only baseline, the random and degree-preserving placebos with paired intervals, and that reviewers ask for them. The protocol requires no change to the model, only a different graph file and the same training script, and its cost is a small multiple of the original experiment: the full audit of RSR (280 training runs) cost under seven US dollars of cloud computing.

Scope The audit covers three published models in four model-market cells and their published test periods: 2017 for RSR (237 days), January 2017 to July 2020 for HIST (871 days) and the authors' 172-day test period for RT-GCN. Other relation types such as supply-chain links, other horizons and rolling test years are extensions with the same protocol; for RSR a second test year requires re-estimating the authors' pretrained sequential

Table 8: Annualised performance of top-k portfolios. ΔSharpe q: circular block bootstrap over test days of the Sharpe difference between the real graph and the condition, Benjamini-Hochberg adjusted within each model, market and portfolio. Turnover excludes the entry day.

Market	Portfolio	Condition	Ann. return	Ann. vol.	Sharpe	Turnover	ΔSharpe q_{BH}
NYSE (RSR)	Top-5, net 5 bp	Real graph	0.207	0.367	0.56	0.29	–
		Random	0.318	0.326	0.98	0.55	0.223
		Degree-preserving	0.406	0.336	1.21	0.46	0.175
		Correlation-matched	0.342	0.324	1.05	0.54	0.223
		Uniform mixing	0.317	0.303	1.04	0.53	0.223
		No cross-firm links	0.360	0.330	1.09	0.57	0.223
		No-graph base model	0.124	0.263	0.47	0.59	0.896
NASDAQ (RSR)	Top-5, net 5 bp	Real graph	0.445	0.240	1.85	0.39	–
		Random	0.267	0.226	1.18	0.34	0.352
		Degree-preserving	0.398	0.232	1.72	0.38	0.352
		Correlation-matched	0.382	0.238	1.61	0.39	0.672
		Uniform mixing	0.012	0.167	0.07	0.59	0.114
		No cross-firm links	0.284	0.235	1.21	0.41	0.352
		No-graph base model	0.000	0.202	0.00	0.52	0.114
CSI300 (HIST)	Top-50, gross	Real graph	0.381	0.222	1.72	–	–
		Random	0.384	0.223	1.72	–	0.873
		Degree-preserving	0.387	0.221	1.75	–	0.352
		Correlation-matched	0.395	0.223	1.77	–	0.252
		No cross-firm links	0.382	0.221	1.73	–	0.873
		No-graph base model	0.371	0.218	1.70	–	0.873
NASDAQ (RT-GCN)	Top-5, net 5 bp	Real graph	0.738	0.677	1.09	0.04	–
		Random	0.794	0.669	1.19	0.04	0.698
		Degree-preserving	0.719	0.673	1.07	0.04	0.763
		Correlation-matched	0.713	0.680	1.05	0.03	0.763
		Uniform mixing	0.823	0.657	1.25	0.04	0.698
		No cross-firm links	0.877	0.668	1.31	0.05	0.460

Table 9: Equivalence against the structure-matched placebos: 90% two-way bootstrap interval of real minus placebo rank IC, the smallest symmetric margin $\delta_{\min}$ inside which equivalence holds, equivalence at $\delta = 0.005$, and the minimum detectable effect (MDE) of the primary test at 80% power.

Market	Placebo	Δ rank IC	90% CI	$\delta_{\min}$	Equiv. at $\delta = 0.005$	MDE
NYSE (RSR)	Random	-0.0010	[-0.0047, 0.0029]	0.0047	yes	0.0064
	Degree-preserving	-0.0011	[-0.0050, 0.0029]	0.0050	no	0.0067
	Correlation-matched	-0.0018	[-0.0054, 0.0019]	0.0054	no	0.0062
NASDAQ (RSR)	Random	-0.0005	[-0.0027, 0.0014]	0.0027	yes	0.0035
	Degree-preserving	0.0002	[-0.0010, 0.0014]	0.0014	yes	0.0021
	Correlation-matched	0.0012	[0.0002, 0.0022]	0.0022	yes	0.0017
CSI300 (HIST)	Random	0.0000	[-0.0018, 0.0020]	0.0020	yes	0.0033
	Degree-preserving	0.0004	[-0.0010, 0.0018]	0.0018	yes	0.0024
	Correlation-matched	-0.0011	[-0.0024, 0.0001]	0.0024	yes	0.0021
NASDAQ (RT-GCN)	Random	0.0005	[-0.0015, 0.0024]	0.0024	yes	0.0033
	Degree-preserving	-0.0014	[-0.0038, 0.0007]	0.0038	yes	0.0039
	Correlation-matched	0.0008	[-0.0019, 0.0037]	0.0037	yes	0.0048

embeddings, whose selection uses the 2016 validation year. The positive control plants one class of relational signal, a linear neighbour mean of a source visible in the input, and its thresholds refer to correlation with next-day returns in each test universe. The relation graphs are the snapshots released with each benchmark and may record links formed after the training period; such look-ahead can only favour the real graph over its placebos.

7 Conclusion

Placebo graphs separate what a relational forecaster learns from its graph from what it learns from its architecture. Applied to three published stock forecasters, they show that the curated relation graphs contribute no measurable forecasting value beyond random and degree-preserving graphs of the same size and shape, within equivalence bounds of 0.002 to 0.005 in daily rank correlation. A planted-signal control separates two reasons: RSR detects a strong planted neighbour signal, so its published graphs carry no relational signal above the test's resolution, while HIST and RT-GCN do not learn such a signal even when it runs along their own graph. The protocol is cheap enough to become a routine part of evaluating relational forecasters.

Data and code availability

Code to reproduce every table and figure, the placebo generators and the analysis scripts are available from the authors and will be released publicly with the published version.The data are the published datasets of the audited papers.

Declaration of generative AI and AI-assisted technologies in the manuscript preparation process

During the preparation of this work the authors used Claude (Anthropic) in order to write and run experiment code and to draft and edit the manuscript. After using this tool, the authors reviewed and edited the content as needed and take full responsibility for the content of the published article.

References

Hugo Attali, Davide Buscaldi, Nathalie Pernelle, and Fragkiskos D. Malliaros. Graph rewiring in GNNs to mitigate over-squashing and over-smoothing: A survey, 2024.

Lei Bai, Lina Yao, Can Li, Xianzhi Wang, and Can Wang. Adaptive graph convolutional recurrent network for traffic forecasting. In *Advances in Neural Information Processing Systems (NeurIPS)*, volume 33, 2020.

Maya Bechler-Speicher, Ido Amos, Ran Gilad-Bachrach, and Amir Globerson. Graph neural networks use graphs when they shouldn't. In *Proceedings of the 41st International Conference on Machine Learning (ICML)*, 2024.

Yoav Benjamini and Yosef Hochberg. Controlling the false discovery rate: A practical and powerful approach to multiple testing. *Journal of the Royal Statistical Society: Series B (Methodological)*, 57(1):289–300, 1995. doi: 10.1111/j.2517-6161.1995.tb02031.x.

Bocconi Students Investment Club (BSIC). Trading the network I: Do graph neural networks improve equity return predictions? `https://bsic.it/trading-the-network-i-do-graph-neural-networks-improve-equity-return-predictions/`, 2026a. Accessed 17 October 2026.

Bocconi Students Investment Club (BSIC). Trading the network II: What should an edge mean? `https://bsic.it/trading-the-network-ii-what-should-an-edge-mean/`, 2026b. Accessed 17 October 2026.

Yingmei Chen, Zhongyu Wei, and Xuanjing Huang. Incorporating corporation relationship via graph convolutional neural networks for stock price prediction. In *Proceedings of the 27th ACM International Conference on Information and Knowledge Management*, pages 1655–1658, 2018. doi: 10.1145/3269206.3269269.

Todd E. Clark and Kenneth D. West. Approximately normal tests for equal predictive accuracy in nested models. *Journal of Econometrics*, 138(1):291–311, 2007. doi: 10.1016/j.jeconom.2006.05.023.

Lauren Cohen and Andrea Frazzini. Economic links and predictable returns. *The Journal of Finance*, 63(4):1977–2011, 2008. doi: 10.1111/j.1540-6261.2008.01379.x.

Corinna Coupette, Jeremy Wayland, Emily Simons, and Bastian Rieck. No metric to rule them all: Toward principled evaluations of graph-learning datasets. In *Proceedings of the 42nd International Conference on Machine Learning (ICML)*, 2025.

Francis X. Diebold and Roberto S. Mariano. Comparing predictive accuracy. *Journal of Business & Economic Statistics*, 13(3):253–263, 1995. doi: 10.1080/07350015.1995.10524599.

Federico Errica, Marco Podda, Davide Bacciu, and Alessio Micheli. A fair comparison of graph neural networks for graph classification. In *International Conference on Learning Representations (ICLR)*, 2020.

Fuli Feng, Xiangnan He, Xiang Wang, Cheng Luo, Yiqun Liu, and Tat-Seng Chua. Temporal relational ranking for stock prediction. *ACM Transactions on Information Systems*, 37 (2):27:1–27:30, 2019. doi: 10.1145/3309547.

Maurizio Ferrari Dacrema, Simone Boglio, Paolo Cremonesi, and Dietmar Jannach. A troubling analysis of reproducibility and progress in recommender systems research. *ACM Transactions on Information Systems*, 39(2):20:1–20:49, 2021. doi: 10.1145/3434185.

Raffaella Giacomini and Halbert White. Tests of conditional predictive ability. *Econometrica*, 74(6):1545–1578, 2006. doi: 10.1111/j.1468-0262.2006.00718.x.

Shihao Gu, Bryan Kelly, and Dacheng Xiu. Empirical asset pricing via machine learning. *The Review of Financial Studies*, 33(5):2223–2273, 2020. doi: 10.1093/rfs/hhaa009.

Peter R. Hansen, Asger Lunde, and James M. Nason. The model confidence set. *Econometrica*, 79(2):453–497, 2011. doi: 10.3982/ECTA5771.

Peter Reinhard Hansen. A test for superior predictive ability. *Journal of Business & Economic Statistics*, 23(4):365–380, 2005. doi: 10.1198/073500105000000063.

Campbell R. Harvey, Yan Liu, and Heqing Zhu. ... and the cross-section of expected returns. *The Review of Financial Studies*, 29(1):5–68, 2016. doi: 10.1093/rfs/hhv059.

David Harvey, Stephen Leybourne, and Paul Newbold. Testing the equality of prediction mean squared errors. *International Journal of Forecasting*, 13(2):281–291, 1997. doi: 10.1016/S0169-2070(96)00719-4.

Kewei Hou. Industry information diffusion and the lead-lag effect in stock returns. *The Review of Financial Studies*, 20 (4):1113–1138, 2007. doi: 10.1093/revfin/hhm003.

Hussain Hussain, Tomislav Duricic, Elisabeth Lex, Roman Kern, and Denis Helic. On the impact of communities on semi-supervised classification using graph neural networks. In *Complex Networks & Their Applications IX*. Springer, Cham, 2021.

Isay Katsman, Ethan Lou, and Anna Gilbert. Revisiting the necessity of graph learning and common graph benchmarks, 2024.

Raehyun Kim, Chan Ho So, Minbyul Jeong, Sanghoon Lee, Jinkyu Kim, and Jaewoo Kang. HATS: A hierarchical graph attention network for stock movement prediction, 2019.

Hans R. Künsch. The jackknife and the bootstrap for general stationary observations. *The Annals of Statistics*, 17(3): 1217–1241, 1989. doi: 10.1214/aos/1176347265.

Olivier Ledoit and Michael Wolf. Robust performance hypothesis testing with the Sharpe ratio. *Journal of Empirical Finance*, 15(5):850–859, 2008. doi: 10.1016/j.jempfin.2008.03.002.

Saket Maganti. When graph structure becomes a liability: A critical re-evaluation of graph neural networks for Bitcoin fraud detection under temporal distribution shift, 2026.

Sergei Maslov and Kim Sneppen. Specificity and stability in topology of protein networks. *Science*, 296(5569):910–913, 2002. doi: 10.1126/science.1065103.

Lior Menzly and Oguzhan Ozbas. Market segmentation and cross-predictability of returns. *The Journal of Finance*, 65 (4):1555–1580, 2010. doi: 10.1111/j.1540-6261.2010.01578.x.

Tobias J. Moskowitz and Mark Grinblatt. Do industries explain momentum? *The Journal of Finance*, 54(4):1249–1290, 1999. doi: 10.1111/0022-1082.00146.

Whitney K. Newey and Kenneth D. West. A simple, positive semi-definite, heteroskedasticity and autocorrelation consistent covariance matrix. *Econometrica*, 55(3):703–708, 1987. doi: 10.2307/1913610.

Sotirios D. Nikolopoulos. Spurious predictability in financial machine learning, 2026.

Yingjie Niu, Lanxin Lu, Rian Dolphin, Valerio Poti, and Ruihai Dong. Evaluating financial relational graphs: Interpretation before prediction. In *Proceedings of the 5th ACM International Conference on AI in Finance*, 2024. doi: 10.1145/3677052.3698644.

Sneh Pillai. Graph-augmented LSTM for forecasting sparse anomalies in graph-structured time series, 2025.

Dimitris N. Politis and Joseph P. Romano. The stationary bootstrap. *Journal of the American Statistical Association*, 89(428):1303–1313, 1994. doi: 10.1080/01621459.1994.10476870.

Joseph P. Romano and Michael Wolf. Stepwise multiple testing as formalized data snooping. *Econometrica*, 73(4): 1237–1282, 2005. doi: 10.1111/j.1468-0262.2005.00615.x.

Ramit Sawhney, Shivam Agarwal, Arnav Wadhwa, Tyler Derr, and Rajiv Ratn Shah. Stock selection via spatiotemporal hypergraph attention network: A learning to rank approach. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 35, pages 497–504, 2021. doi: 10.1609/aaai.v35i1.16127.

Donald J. Schuirmann. A comparison of the two one-sided tests procedure and the power approach for assessing the equivalence of average bioavailability. *Journal of Pharmacokinetics and Biopharmaceutics*, 15(6):657–680, 1987. doi: 10.1007/BF01068419.

Zezhi Shao, Zhao Zhang, Fei Wang, Wei Wei, and Yongjun Xu. Spatial-temporal identity: A simple yet effective baseline for multivariate time series forecasting. In *Proceedings of the 31st ACM International Conference on Information and Knowledge Management (CIKM)*, pages 4454–4458, 2022. doi: 10.1145/3511808.3557702.

Zezhi Shao, Fei Wang, Yongjun Xu, Wei Wei, Chengqing Yu, Zhao Zhang, Di Yao, Tao Sun, Guangyin Jin, Xin Cao, Gao Cong, Christian S. Jensen, and Xueqi Cheng. Exploring progress in multivariate time series forecasting: Comprehensive benchmarking and heterogeneity analysis. *IEEE Transactions on Knowledge and Data Engineering*, 2025. doi: 10.1109/TKDE.2024.3484454.

Halbert White. A reality check for data snooping. *Econometrica*, 68(5):1097–1126, 2000. doi: 10.1111/1468-0262.00152.

Wentao Xu, Weiqing Liu, Lewen Wang, Yingce Xia, Jiang Bian, Jian Yin, and Tie-Yan Liu. HIST: A graph-based framework for stock trend forecasting via mining concept-oriented shared information, 2021.

Xiao Yang, Weiqing Liu, Dong Zhou, Jiang Bian, and Tie-Yan Liu. Qlib: An AI-oriented quantitative investment platform, 2020.

Zetao Zheng, Jie Shao, Jia Zhu, and Heng Tao Shen. Relational temporal graph convolutional networks for ranking-based stock prediction. In *Proceedings of the 39th IEEE International Conference on Data Engineering (ICDE)*, pages 123–136, 2023. doi: 10.1109/ICDE55515.2023.00017.