

## Multimedia MCI 错误返回码详解(包括 mciSendString)

Below is a list of the MCI error strings and numbers that are related to the **Multimedia MCI** control.

MCI Error Strings	MCI Error Numbers
MCIERR_BASE	256
MCIERR_INVALID_DEVICE_ID	257
MCIERR_UNRECOGNIZED_KEYWORD	259
MCIERR_UNRECOGNIZED_COMMAND	261
MCIERR_HARDWARE	262
MCIERR_INVALID_DEVICE_NAME	263
MCIERR_OUT_OF_MEMORY	264
MCIERR_DEVICE_OPEN	265

MCIERR_CANNOT_LOAD_DRIVER	266
MCIERR_MISSING_COMMAND_STRING	267
MCIERR_PARAM_OVERFLOW	268
MCIERR_MISSING_STRING_ARGUMENT	269
MCIERR_BAD_INTEGER	270
MCIERR_PARSER_INTERNAL	271
MCIERR_DRIVER_INTERNAL	272
MCIERR_MISSING_PARAMETER	273
MCIERR_UNSUPPORTED_FUNCTION	274
MCIERR_FILE_NOT_FOUND	275
MCIERR_DEVICE_NOT_READY	276

MCIERR_INTERNAL	277
MCIERR_DRIVER	278
MCIERR_CANNOT_USE_ALL	279
MCIERR_MULTIPLE	280
MCIERR_EXTENSION_NOT_FOUND	281
MCIERR_OUTOFRANGE	282
MCIERR_FLAGS_NOT_COMPATIBLE	283
MCIERR_FILE_NOT_SAVED	286
MCIERR_DEVICE_TYPE_REQUIRED	287
MCIERR_DEVICE_LOCKED	288
MCIERR_DUPLICATE_ALIAS	289

MCIERR_BAD_CONSTANT	290
MCIERR_MUST_USE_SHAREABLE	291
MCIERR_MISSING_DEVICE_NAME	292
MCIERR_BAD_TIME_FORMAT	293
MCIERR_NO_CLOSING_QUOTE	294
MCIERR_DUPLICATE_FLAGS	295
MCIERR_INVALID_FILE	296
MCIERR_NULL_PARAMETER_BLOCK	297
MCIERR_UNNAMED_RESOURCE	298
MCIERR_NEW_REQUIRES_ALIAS	299
MCIERR_NOTIFY_ON_AUTO_OPEN	300

MCIERR_NO_ELEMENT_ALLOWED	301
MCIERR_NONAPPLICABLE_FUNCTION	302
MCIERR_ILLEGAL_FOR_AUTO_OPEN	303
MCIERR_FILENAME_REQUIRED	304
MCIERR_EXTRA_CHARACTERS	305
MCIERR_DEVICE_NOT_INSTALLED	306
MCIERR_GET_CD	307
MCIERR_SET_CD	308
MCIERR_SET_DRIVE	309
MCIERR_DEVICE_LENGTH	310
MCIERR_DEVICE_ORD_LENGTH	311

MCIERR_NO_INTEGER	312
MCIERR_WAVE_OUTPUTSINUSE	320
MCIERR_WAVE_SETOUTPUTINUSE	321
MCIERR_WAVE_INPUTSINUSE	322
MCIERR_WAVE_SETINPUTINUSE	323
MCIERR_WAVE_OUTPUTUNSPECIFIED	324
MCIERR_WAVE_INPUTUNSPECIFIED	325
MCIERR_WAVE_OUTPUTSUNSUITABLE	326
MCIERR_WAVE_SETOUTPUTUNSUITABLE	327
MCIERR_WAVE_INPUTSUNSUITABLE	328
MCIERR_WAVE_SETINPUTUNSUITABLE	329

MCIERR_SEQ_DIV_INCOMPATIBLE	336
MCIERR_SEQ_PORT_INUSE	337
MCIERR_SEQ_PORT_NONEXISTENT	338
MCIERR_SEQ_PORT_MAPNODEVICE	339
MCIERR_SEQ_PORT_MISCELLOR	340
MCIERR_SEQ_TIMER	341
MCIERR_SEQ_PORTUNSPECIFIED	342
MCIERR_SEQ_NOMIDIPRESENT	343
MCIERR_NO_WINDOW	346
MCIERR_CREATEWINDOW	347
MCIERR_FILE_READ	348

MCIERR_FILE_WRITE	349
MCIERR_CUSTOM_DRIVER_BASE	512

下面是对应 **mciSendString** 的错误返回码：

## mciSendString Errors

The following errors are returned by the **mciSendString** function but not by **mciSendCommand**:

Value	Meaning
MCIERR_BAD_CONSTANT	The value specified for a parameter is unknown.
MCIERR_BAD_INTEGER	An integer in the command was invalid or missing.
MCIERR_DUPLICATE_FLAGS	A flag or value was specified twice.
MCIERR_MISSING_COMMAND_STRING	No command was specified.
MCIERR_MISSING_DEVICE_NAME	No device name was specified.



MCIERR_MISSING_STRING_ARGUMENT	A string value was missing from the command.
MCIERR_NEW_REQUIRES_ALIAS	An alias must be used with the "new" device name.
MCIERR_NO_CLOSING_QUOTE	A closing quotation mark is missing.
MCIERR_NOTIFY_ON_AUTO_OPEN	The "notify" flag is illegal with auto-open.
MCIERR_PARAM_OVERFLOW	The output string was not long enough.
MCIERR_PARSER_INTERNAL	An internal parser error occurred.
MCIERR_UNRECOGNIZED_KEYWORD	An unknown command parameter was specified.