For workspace administrators

Administrator Guide

Aperture Chat

The complete User Guide, plus the Admin console: accounts, groups, model access requests and diagnostics, workspace connectors, response actions, single sign-on, analytics, token budgets, support tickets, personal data protection, training datasets, the tenant audit trail, and alerts. No prior knowledge assumed.

54 sections · every instruction spelled out step by step

Generated October 31, 2026

Contents

PART 1 · GETTING STARTED

1 Welcome 4
2 Signing in 5
3 Request access and finish your first sign-in 8
4 Two-step verification and recovery codes 9
5 Finding your way around 14
6 Organizing chats: folders, pins, and the chat menu 16
7 Searching everything 20

PART 2 · CHAT

8 Your first chat 22
9 Understand model availability and request access 27
10 Reading and acting on replies 30
11 Work with code in chat 34
12 Edit tables and diagrams in a reply 37
13 Symbol shortcuts: / @ # $ > 40
14 Attaching files, web pages, and connected sources 43
15 Send options: Knowledge, Web, Agent, and Reasoning 46
16 Session details and sources 50
17 Check a source: open the cited document 52
18 Personal data in your chats 56

PART 3 · DRAFTS, DECKS, AND AGENTS

19 Drafting documents 59
20 Hand a chat request to Drafts 66
21 Open a Word or PDF file and keep its formatting 69
22 Templates and page layout 72
23 Building a slide deck 75
24 Editing slides: layouts, pictures, and text 81
25 Build a spreadsheet 85
26 Recover work kept only on this device 93
27 Agent profiles 96

PART 4 · LIBRARY AND AUTOMATIONS

28 Knowledge bases 99
29 The Tools library 103
30 Scheduled automations 106

PART 5 · APPEARANCE, YOUR ACCOUNT, AND HELP

31 Light and dark mode 111
32 Your account 112
33 Personalization memory 116
34 Install the app on your phone 119
35 Getting help 120

PART 6 · THE ADMIN CONSOLE

36 Opening the Admin console 123
37 Users 124
38 Groups 129
39 Model Access 132
40 Resolve model requests and trace access 135
41 Connections: workspace connectors 137
42 Connections: response actions and Library connections 143
43 Automations: preparing scheduled runs 145
44 SSO: single sign-on for your tenant 145
45 Analytics 149
46 Policies: service availability and memory governance 151
47 Personal Data Protection 154
48 Training datasets 158
49 Ethical walls and file properties 163
50 Data retention and conversation tags 167
51 Review feedback and reported issues 170
52 Reports: work support tickets 171
53 Audit 174
54 Alerts 177

PART 1

Getting started

1. Welcome

What Aperture Chat is and how to read this guide.

Aperture Chat is your organization's workspace assistant. You can chat with approved AI models, draft documents, slide decks, and spreadsheets, search your organization's knowledge, and schedule recurring work. Review the sources and work trace when a response uses connected knowledge or tools.

This guide explains where to look and what to choose. Words in bold — like **Save version** — match the labels on screen. If a step says “hover”, rest your pointer on the item without clicking; controls that offer extra help show it nearby.

How each task is taught

Each task appears in three matching forms: a narrated walkthrough video in the product, a written procedure in this guide, and the same procedure on the website guide. They come from one source, so they describe the same steps. Every walkthrough is a complete loop, from where you start to a result you can see, and it covers each way the product offers to do the task.

IN EACH WALKTHROUGH BOX	WHAT IT GIVES YOU
Before you begin	The role, access, earlier setup, and outside accounts or values you need first.
Step by step	Every action in order, with the exact labels on screen. Where there are several ways to do the task (an identity provider, a delivery target, a device), each path has its own complete list.
Check that it worked	What you should see when the task succeeded.
Troubleshooting	Messages you may meet, quoted as the product shows them, and what to do about each.

Walkthrough screens are real captures of a running workspace with sample accounts. Steps that happen in another product, such as an identity provider's console, are shown as labeled instruction cards rather than imitation screenshots.

GUIDE	WHO IT IS FOR	WHAT IT COVERS
User Guide	Everyone	**Chat**, model access requests, personalization memory, documents and decks, account sync, agents, knowledge and tools, search and commands, appearance, account security, and reporting a problem.
Administrator Guide	Workspace admins	Everything in the User Guide, plus the **Admin console**: users, groups, model access, connectors, response actions, **SSO**, analytics, support tickets, policies and memory governance, personal data protection, training datasets, audit, and alerts.
Platform Owner Guide	Platform owners	Everything in the other guides, plus setup readiness, providers and keys, organization policy, the connector ceiling, branding, releases, search indexing, and platform governance.

TIP

If a feature is not configured — a connector without credentials, a model that is not enabled — the screen reports that state. Ask your administrator about account, model, or connector access; workspace connectors are configured in **Admin console** → **Connections**.

2. Signing in

Reach the sign-in screen and get into your workspace.

- Open the web address your organization gave you for Aperture Chat in a modern browser (Chrome, Edge, Safari, or Firefox).
- On the sign-in screen, type your work email address in the field marked `you@company.com`.
- If your organization uses single sign-on (**SSO**), the screen recognizes your email domain and offers **Continue with SSO**. Click it — you are sent to your organization's identity provider (for example Microsoft, Google, or a WorkOS sign-in page), sign in there as usual, and return to Aperture Chat already signed in.
- When both methods are offered, choose Organization **SSO** or Email & password. The password field appears in Email & password mode; enter your password and click Sign in. Pressing Enter submits the method you selected.

GOOD TO KNOW

If both **SSO** and a password are available, either works. If your organization enforces **SSO** for your email domain, password sign-in is blocked on purpose — use the **SSO** button.

GOOD TO KNOW

See a message you do not expect? The sign-in screen reports real problems plainly (for example, a domain that is not allowed for **SSO**). **Copy** the message and send it to your administrator.

WALKTHROUGH · 3:50 · HELP › LEARN

Request access and enter your workspace

Ask for an account, then sign in with a temporary password, your own password, Organization SSO, or an authenticator code.

Before you begin

- Your workspace address, which your organization gives you (for example https://your-instance.example).
- Your work email address.
- For Organization **SSO**: an account at your organization's identity provider, such as Microsoft Entra ID, Okta, or Google.
- For a password account: the temporary password your administrator gives you after approving your request.
- If two-step verification is on for your account: your authenticator app, or one unused recovery code.

Step by step

1. Open your workspace address in a web browser. The sign-in page opens.
2. Under New to Aperture Chat?, choose **Request access**.
3. Enter First name, Last name, and Work email, then choose Submit access request.
4. Read Request received. The form does not send an email or set a password. Contact your administrator, who approves the request and tells you how to sign in.
5. When your administrator gives you a temporary password, return to the sign-in page and choose Email & password (it appears beside Organization **SSO** when your workspace offers both).
6. Enter your work email and the temporary password, then choose Sign in.
7. On Set a new password, type a password of at least 12 characters into New password and Confirm password, then choose **Set password** and continue.
8. Check that the welcome card, A good place to begin., says You're signed in.

Path: Organization SSO

1. Open your workspace address. Organization **SSO** is selected first when your workspace offers it.

2. Optionally type your work email. It selects your organization's provider, shown as Sign in with followed by the provider's name.
3. Choose **Continue with SSO**.
4. Sign in on your identity provider's page, including any multifactor check it asks for. Aperture Chat never sees that password.
5. You return to the workspace signed in. On your first visit your account is created automatically if your organization allows it; otherwise ask your administrator to add you.

Path: Email & password

1. Choose Email & password.
2. Enter your work email and your password, then choose Sign in.
3. If two-step verification is on, follow the **Authenticator code** path.
4. The workspace opens where you left off.

Path: Authenticator code

1. After Sign in, Two-step verification asks for a code. It shows the attempts remaining and when the challenge expires (about five minutes).
2. Open your authenticator app and type the current 6-digit code into **Authenticator code**.
3. Choose Verify and continue.
4. No phone? Choose **Use a recovery code instead**, type one unused recovery code, and choose Verify and continue. Each code works once.
5. If the challenge expires, choose Back to sign in and start again.

Path: Trouble signing in

1. Choose Trouble signing in? under the sign-in button.
2. For Organization **SSO**, use your organization's own password recovery.
3. For an email-and-password account, ask your workspace administrator for a temporary password.
4. If you lost your authenticator and have no recovery codes, ask your administrator to reset two-step verification for your account.

Check that it worked

- ✓ The welcome card A good place to begin. shows You're signed in.
- ✓ Your name appears on the account card at the bottom of the sidebar.

✓ With Organization **SSO**, the identity provider's page handled your password and you returned signed in.

Troubleshooting

WHAT YOU SEE	WHAT TO DO
"Invalid local credentials."	The password is wrong. Retype it (Show password helps), or ask your administrator for a new temporary password.
"Unknown local account."	There is no active password account for that email yet: the request may still be pending, or your account signs in with Organization **SSO**. Choose Organization **SSO**, or ask your administrator.
"SSO is enforced for this email domain; local sign-in is disabled. Use the configured identity provider."	Your organization requires single sign-on for your domain. Choose Organization **SSO** and **Continue with SSO**.
"Use a password with at least 12 characters." or "The passwords do not match."	On Set a new password, use 12 or more characters and type the same password in both fields.
"Choose a new password."	The new password matches the temporary one. Pick a different password.
"The MFA code is invalid." or "Too many MFA attempts."	Wait for the next code in your authenticator app and check that your phone's clock is set automatically. After too many attempts, wait for the timer, or choose Back to sign in.
"Verification unavailable"	The sign-in challenge expired or was used up. Choose Back to sign in and sign in again.
"Too many failed sign-in attempts for this account. Try again shortly."	Wait a minute before trying again, or use Trouble signing in?.
"Too many access requests for this email. Try again shortly."	Your request was already recorded. Contact your administrator instead of submitting again.

3. Request access and finish your first sign-in

Submit a request, understand the administrator handoff, and enter the workspace.

1. On the sign-in screen, choose **Request access**. Enter your first name, last name, and work email, then submit the form.

2. The Request received screen confirms submission for your email. If this email is new to the workspace, an administrator reviews the request. This form does not email you or create a password.
3. Contact your administrator for an update. After approval, they provide the workspace address and confirm whether to use organization **SSO** or a temporary password.
4. Choose Back to sign in. Your submitted email remains filled in. Use the sign-in method your administrator arranged.
5. If you received a temporary password, sign in with it and complete Set a new password. Enter a new password of at least 12 characters twice. After saving, the app continues with a new authenticated session and revokes your older sessions.
6. Complete any required authenticator verification. **Once** in the workspace, select an available model and send a short first message. If no model is available, ask your administrator to check your account, group, and model access.

GOOD TO KNOW

Submitting another access request does not approve an account or recover an existing password. Trouble signing in explains the recovery path: contact your administrator for local password access, or use your organization identity provider for **SSO**. If sign-in settings cannot load, choose Retry connection.

4. Two-step verification and recovery codes

Set up an authenticator, complete required verification, and manage recovery codes.

To add an authenticator after signing in with a local password, open your account drawer, find **Security**, choose **Manage security**, and select **Set up authenticator**. Confirm your current password, add the QR code or setup key to your authenticator, acknowledge that you added it, and choose **Verify authenticator** with a current six-digit code. **Copy** the one-time recovery codes into secure storage, acknowledge that you saved them, and choose **Done**. Copying alone does not store them for you; finish verification and code storage before leaving the panel.

- If sign-in asks you to set up an authenticator, choose **Begin authenticator setup**. Add the displayed QR code or setup secret to your authenticator app.
- Confirm that you added the account, enter the current six-digit **Authenticator code**, and choose **Verify and enable MFA** before the setup expires.
- Use **Copy recovery codes** and save the codes privately when they are shown. They are not saved to a file automatically. Each recovery code can be used once when your authenticator is unavailable; do not include these codes in screenshots or issue reports.
- On later sign-ins, enter your current authenticator code. **Use a recovery code instead** switches to a single-use recovery code when necessary.
- If you cancel or the challenge expires, return to sign-in and start again. A cancelled setup or failed verification does not finish sign-in.

When verification is enabled, the account card shows how many recovery codes remain. **Replace recovery codes** requires a fresh authenticator code or an unused recovery code; after replacement, all previous recovery codes stop working. Save the new set before leaving the dialog.

Turn off verification appears only when your organization's policy allows it. Confirm with an authenticator or recovery code; successful removal signs you out. Organization-required verification cannot be turned off here.

If you lose both the authenticator and all unused recovery codes, contact your administrator for the organization's verified recovery process. A new password does not remove the authenticator requirement. For identity-provider MFA, use that provider's recovery process.

TIP

Use the code currently shown for this workspace in your authenticator app. If it expires while you are typing, use the next code. Read the attempts, expiry, and any cooldown shown; wait for a cooldown to finish before trying again. If **Security** cannot load, choose Retry security settings. Keep setup keys and recovery codes out of shared documents, videos, and support attachments.

GOOD TO KNOW

SSO accounts manage voluntary authenticator setup in their identity-provider settings. Your identity provider may also require its own verification during **SSO**. Follow the provider's screen for that check; these instructions describe Aperture Chat's authenticator screens.

WALKTHROUGH · 2:57 · HELP › LEARN

Protect your account and recover access

Turn on two-step verification, sign in with a code or a recovery code, replace recovery codes, and change your password.

Before you begin

- An email-and-password account. With Organization **SSO**, your identity provider manages your password and multifactor settings, and the panel says so.
- An authenticator app on your phone, such as **Microsoft Authenticator**, Google Authenticator, or a password manager with one-time codes.
- A safe place for recovery codes, such as a password manager.
- Your current password. If you still have a temporary password, replace it first.

Step by step

1. Select your account card at the bottom of the sidebar. Under Preferences and security, choose Manage beside **Security**.
2. Under Two-step verification, choose **Set up authenticator**.
3. Enter your Current password and choose Continue setup.

4. In your authenticator app, scan the QR code, or type the Setup key shown under it.
5. Tick I added this account to my authenticator., type the 6-digit code from the app into **Authenticator code**, and choose **Verify authenticator**.
6. Choose **Copy recovery codes** and store them somewhere safe. Tick I stored these recovery codes somewhere safe., then choose **Done**.
7. Check that the **Security** row shows On · 10 recovery codes left, and that Two-step verification says Your authenticator is connected.

Path: Sign in with a code

1. Sign in with your email and password as usual.
2. On Two-step verification, type the current 6-digit code from your authenticator app.
3. Choose Verify and continue.

Path: Sign in with a recovery code

1. On Two-step verification, choose **Use a recovery code instead**.
2. Type one unused recovery code into Recovery code and choose Verify and continue.
3. Open **Account** and read the **Security** row: the number of recovery codes left has gone down by one.
4. When few codes remain, replace them.

Path: Replace recovery codes

1. **Account** › **Security** › Manage › **Replace recovery codes**.
2. Enter a current **Authenticator code** (or choose **Use a recovery code instead**).
3. Choose **Create** new recovery codes. The old set stops working at once.
4. **Copy** and store the new codes, tick I stored these recovery codes somewhere safe., and choose **Done**.

Path: Change your password

1. **Account** › **Password** › Change.
2. Enter Current password, then a New password of at least 12 characters, and the same in Confirm new password.
3. Choose Update password and wait for **Password** updated.
4. You stay signed in here; your older sessions on other devices are signed out.

Path: Lost or replaced phone

1. Sign in with your password and one recovery code (**Use a recovery code instead**).
2. If your organization allows it, choose **Turn off verification**, confirm with another recovery code, sign back in, and set up the new phone.
3. If verification is required by your organization, or you have no recovery codes left, ask your administrator to reset two-step verification for your account.
4. After the reset, sign in and set up your authenticator again.

Check that it worked


- ✓ The **Security** row shows On with the number of recovery codes left, and Two-step verification says Your authenticator is connected.
- ✓ Your next password sign-in asks for an **Authenticator code**.
- ✓ After signing in with a recovery code, the **Security** row shows one recovery code fewer.
- ✓ After a password change, the **Password** row shows **Password** updated.

Troubleshooting

WHAT YOU SEE	WHAT TO DO
"Current password is incorrect."	Retype your current password. If you have forgotten it, ask your administrator for a temporary password.
"The MFA code is invalid."	Wait for the next code and type it promptly. Codes depend on the time, so set your phone's clock to update automatically. A code that was already used is refused.
"Change the temporary password before enrolling MFA."	Sign in and choose your own password first, then set up the authenticator.
"Finish verification or save your recovery codes before leaving this panel."	Complete **Verify authenticator**, or copy and store the recovery codes and choose **Done**, before closing the panel.
"Required by your organization. You cannot turn this off."	Your organization requires two-step verification, so **Turn off verification** is not offered. To move to a new phone, ask your administrator to reset it.
"Your organization manages sign-in. Use your identity provider's security settings…" or the Security row says "Managed by your identity provider"	You sign in with Organization **SSO**. Change your password and multifactor settings at your identity provider.
The Security row says "On · No recovery codes left"	You have used every code. Choose Manage, then **Replace recovery codes**, while you still have your authenticator.
"Use a password with at least 12 characters." or "The new passwords do not match."	Use 12 or more characters and type the same new password in both fields.
"Password changes are only available for local password accounts."	Your account signs in with Organization **SSO**. Change the password at your identity provider.

5. Finding your way around

The sidebar, the main area, and what each navigation button opens.



The chat workspace: navigation on the left, model selection above, and the message composer in the main area. Example workspace with synthetic data.

The screen has two areas: a sidebar on the left and the main work area on the right. The sidebar is how you move between the platform's views and your saved chats.

Your first visit

The Getting started card explains what is ready for your account and what comes next. Open quick-start guide opens user help. Administrators see Open admin guide and Manage access. Follow the setup action offered for your role when no model is available. A missing model is an access or setup task, not a successful chat connection.

Choose a guide, take the suggested action, or select I'll explore on my own (or Dismiss welcome) when you are ready. Simply loading the page does not dismiss this card. You can return to guides from **Help** or console **Documentation** later.

SIDEBAR BUTTON	WHAT IT OPENS
New chat	A fresh conversation with your workspace assistant. This is the default view.
Search	**Search past work** for chats (including archived), documents and decks, agents, and indexed documents, plus commands. Shortcut: Ctrl+K (Windows) or ⌘K (Mac).
Drafts	A document and slide-deck editor with an AI assistant beside it.
Agents	Reusable agent profiles, plus an Automations tab for scheduled runs.
Library	Two tabs: **Knowledge** (searchable document collections) and **Tools** (connections, prompts, and skills).

Below the navigation buttons, your chat history is always listed under a small CHATS heading — folders first, then pinned chats, then recent chats. The next section covers organizing them.

Resizing and collapsing the sidebar

- Click the short bar at the top of the sidebar's edge to collapse it and give your work more room. Click it again to bring the sidebar back.
- Drag the sidebar's right edge to make it wider or narrower. Double-click that edge to collapse it.
- On a narrow window or a phone, the sidebar hides behind a menu button (three stacked lines, ≡) in the top-left corner. Tap it to open the menu; tap the dimmed area to close it.

Using the keyboard

Use Tab and Shift+Tab to move between controls and Enter or Space to activate the focused control. In a dialog, keyboard focus stays with that dialog. Use its Close or **Cancel** button, or Escape when available, to return to the control that opened it. Confirmations explain when an action is permanent before you commit it.

The bottom of the sidebar

- **Admin console** and Platform console — links shown only to administrators and platform owners (see “Where the consoles live”). Platform owners may also see a Release available notice here.
- **Help** — opens the guided walkthrough videos and this downloadable guide.
- **Dark mode / Light mode** and **Theme schedule** — two small buttons beside **Help**: the moon or sun switches the appearance instantly, and the clock sets a schedule (see “Light and dark mode” later in this guide).
- **Install app** — appears on phones and tablets, and adds the workspace to your home screen (see “Install the app on your phone”).
- Your account card — your initials or photo, name, and role. Click it to open the account drawer, including Personalization memory when your organization has enabled it.

Where the consoles live

Administrators choose **Admin console** near the bottom of the sidebar; platform owners also see Platform console. The account drawer's Workspace section lists the same consoles. Regular users see neither. The account drawer also holds **View as** role previews, **Usage this month**, and your **Archived chats** — all covered in “Your account”.

Returning to a view

The browser address follows the workspace view and console tab. Browser Back and Forward return to those views; opening a saved chat or draft link still checks your account's access. A link does not share private content or grant permission to another person.

6. Organizing chats: folders, pins, and the chat menu

Keep the chats you care about easy to find.

Your chat history is always visible under the CHATS heading: folders first, then a **Pinned** group when something is pinned, then your recent chats (labeled **Recent** only when a group sits above them). Click the CHATS heading to hide or show the whole list; this is remembered for your account on this device. While hidden, it shows a count and a dot for unread replies, and **Search** still finds every chat.

Folders

- Click the folder icon with a plus sign next to the CHATS heading.
- Type a name for the folder — a client, a matter, a project — and click **Create**.
- To file a chat into a folder, hover or focus its row, click the ⋯ (**More** actions) button, and choose Move to folder. Pick a folder, choose New folder to create one right there, or choose Remove from folder to take it out.
- Click a folder to expand or collapse the chats inside it.

> **GOOD TO KNOW**
> Deleting a folder does not delete its chats — they move back to the **Recent** list.

Pinned chats

- Hover or focus any chat row, click ⋯ (**More** actions), and choose Pin chat.
- The chat moves to the **Pinned** group, just below your folders, where it stays until you choose Unpin chat from the same menu.

Recent chats

- **Recent** chats — below folders and pinned chats — list your latest conversations. Click one to reopen it exactly where you left off.

- Hover or focus a row to reveal its ⋯ (**More** actions) button. The menu offers Pin chat (or Unpin chat), Move to folder, and **Archive**.
- A dot beside a chat marks a newest assistant reply you have not opened. Read status is saved to your account, so it matches in every browser and device.
- Archiving moves a chat out of the sidebar without deleting it — use it to tidy up. **Archived chats** are listed in your account drawer, where you can restore or permanently delete them.
- Click **View all chats** at the bottom of the list to browse your full history, including everything that no longer fits in the sidebar.

WALKTHROUGH · 1:36 · HELP › LEARN

Organize and find your work

Create folders and file chats in them, pin, archive and restore, rename chats, and hide your chat list.

Before you begin

- A few chats in your sidebar.
- **Folders** are kept in this browser: they do not follow you to another browser or device.

Step by step

1. Choose **Create** chat folder (the folder button beside CHATS), type a Folder name, and choose **Create**.
2. Point at a chat, choose its **More** actions button (…), then Move to folder, and choose the folder.
3. Check that the chat now sits inside the folder, with the folder's count updated.
4. To keep a chat at the top, choose … › Pin chat. It moves to **Pinned**.
5. To put a chat away, choose … › **Archive**. Find it later in your account card › **Archived chats** › View, and choose **Restore**.
6. To rename the open chat, choose Rename chat (the pencil beside its title), type the name, and choose Save chat name.
7. Choose the CHATS heading to hide your chat list; choose it again to show it.

Path: Folders

1. **Folders** can hold subfolders, up to four levels: choose **Create** subfolder in … on a folder.
2. … › Move to folder › Remove from folder takes a chat out again.
3. **Delete** … folder asks first; chats in it stay in **Recent**.

Path: Archive and delete

1. **Archive** keeps the chat and removes it from the sidebar (and unpins it).

2. **Account** card › **Archived chats** › View lists archived chats, with **Restore** and Permanently delete.
3. Permanently delete asks first, and **Delete** forever cannot be undone. Keep leaves the chat archived.

Path: Rename with AI

1. After the first reply, choose Rename chat with AI beside the title for a suggested name.

Path: See everything

1. **View all chats** opens All chats, with Filter chats to search titles.
2. View all pinned and View all folders appear when you have more than three.

Check that it worked

- ✓ The folder shows the filed chat and its count.
- ✓ The pinned chat appears under **Pinned**.
- ✓ An archived chat is listed under **Archived chats** until you restore it.
- ✓ With the list hidden, CHATS shows how many chats are tucked away.

Troubleshooting

WHAT YOU SEE	WHAT TO DO
My folders are missing in another browser	**Folders** are stored in the browser where you made them. **Create** them again there; the chats themselves are in your account.
"Chat title cannot be blank."	Type a name before choosing Save chat name, or choose **Cancel** renaming chat.
"The AI could not rename this chat. Try again."	**Try again**, or type a name yourself with Rename chat.
A chat disappeared from the sidebar	It may be archived (account card › **Archived chats**), inside a folder, or hidden with the CHATS heading. **Search** finds it either way.
A chat left its folder after you renamed it	Renaming a chat currently takes it out of its folder. Choose … › Move to folder and pick the folder again.

WALKTHROUGH · 0:34 · HELP › LEARN

Preview chats at a glance

Hover any listed chat to read its prompts and outputs in a compact, scrollable preview.

Before you begin

- **Chats** in your sidebar, in All chats, or in **Archived chats**.

Step by step

1. Point at a chat name in the sidebar and wait a moment; keyboard users can focus the chat row instead.
2. Read the **Chat** preview: the title and time, then Prompt 1 and Output 1, in order.
3. Scroll inside the preview to read later prompts and outputs. The footer counts prompts and outputs.
4. Move away, or press Escape, to close it without opening the chat.
5. Choose the chat if you want to open it.

Path: In All chats

1. Choose **View all chats** under your recent chats.
2. Point at any chat in All chats; the preview opens beside the list.
3. Filter chats narrows the list by title first.

Path: In Archived chats

1. **Account** card › **Archived chats** › View.
2. Point at an archived chat to preview it before you restore or delete it.

Check that it worked

- ✓ The preview shows **Chat** preview, the chat's title, and Prompt 1.
- ✓ The footer counts the prompts and outputs.

Troubleshooting

WHAT YOU SEE	WHAT TO DO
"This chat does not have previewable content yet."	The chat has no messages yet.
No preview appears	Rest the pointer on the chat name for a moment, or focus the row with the keyboard.

7. Searching everything

Find saved work, preview a result, or run an available command.

- Click **Search** near the top of the sidebar, just below **New chat**, or press Ctrl+K (Windows) or ⌘K (Mac) from anywhere.
- The **Search past work** box opens. Type a few words from what you remember: a chat title, message text, an agent or draft name, slide text, or text from an indexed document.
- Results are grouped by kind. **Chat** results lead, matching text is highlighted, and archived conversations are labeled explicitly. Saved documents and decks open in their matching editor.
- Hover over or keyboard-focus a supported chat or draft result to preview it. The chat row also offers folder, pin, and archive or restore actions when that conversation is available in the current workspace.
- Click a result to open it, or use Up and Down followed by Enter. Escape closes search. Recently opened results are available when the query is empty.

Commands and saved work

Commands appear in a separate section from search results. Type > at the start of this search box to see all commands available to your role and permissions, then keep typing to narrow them. **Commands** can open workspace views and permitted actions; an unavailable feature does not become accessible through search. The same > symbol inside a chat message has a different purpose: choosing an automation for that message.

GOOD TO KNOW

Search includes only work your account can access. If the panel says Indexing your workspace, results may be incomplete until indexing finishes; try again after it completes. A missing result is not proof the work was deleted. Unsaved device-only changes may need saving to your account before server search can find them.

WALKTHROUGH · 1:20 · HELP › LEARN

Search, commands, and workspace links

Search every chat, draft, agent, and document you can access, reopen recent results, and run commands from the keyboard.

Before you begin

- Some saved work to find. **Archived chats** are included.

Step by step

1. Choose **Search** in the sidebar, or press Ctrl+K (⌘K on a Mac).
2. Type words from a title or a message.
3. Read the results, grouped by kind: Previous chats, Documents & knowledge, **Agents**, Automations, **Drafts**, and more.

4. Use the arrow keys and Enter, or choose a result, to open it.
5. Press Ctrl+K again. With an empty box, **Recent** lists what you opened from **Search**.
6. Type > to list commands, add a word to narrow them (for example >dark), and press Enter to run one.

Path: Act on a chat from Search

1. Point at a chat result for its buttons: add to a folder, pin, and archive or restore.
2. **Archived chats** are marked **Archived** conversation and can be restored from here.

Path: Commands

1. **New chat**; Go to **Chat**, **Drafts**, **Agents**, Automations, **Knowledge**, or **Tools**.
2. Switch to dark mode or Switch to light mode; Open **Help**; **Sign out**.
3. **Install app** appears on phones and tablets.

Path: Workspace links

1. Each screen has its own address (for example /drafts or /chat/ followed by the chat's id).
2. Browser Back and Forward move between the screens you visited.
3. A link never shares private content: whoever opens it must sign in and have access.

Check that it worked

- ✓ Results list the matching chats and other work.
- ✓ Choosing a result opens it.
- ✓ A command such as >dark changes the workspace at once.

Troubleshooting

WHAT YOU SEE	WHAT TO DO
"Indexing your workspace… results may be incomplete until it finishes."	**Search** is still catching up. **Try again** in a moment.
"No chats or workspace items found for …"	Try fewer or different words, such as a word from the reply rather than the title.
"No commands match …"	Type > alone to see every command.
"Search failed."	Check your connection and search again.

PART 2

Chat

8. Your first chat

Send a message, pick a model, and control web search.

- Click **New chat** in the sidebar. A fresh chat greets you by the time of day — “Good morning”, “Good afternoon”, or “Good evening” with your first name (late at night it asks if you are burning the midnight oil) — above the tagline “Your approved models, your sources, your guardrails — ask Aperture Chat anything.” (The name reflects your organization's branding.)
- Click into the message box (the composer) — it reads **Ask anything…** — and type your question.
- Explore an idea, Compare options, and **Draft** a message offer starting points. Selecting one fills an editable prompt; review it before sending.
- Press Enter to send. Press **Shift+Enter** when you want a new line without sending.

Picking the model

The model selector sits in the top bar of every chat. Click it to choose which AI model answers this conversation. Each chat remembers its own choice, and the list only ever shows models your workspace has approved for you.

Use the arrow keys, Home, End, or type a model name to move through available models; Enter selects the highlighted model. Each row has its own star: Set [model name] as default model selects that model and remembers it for new chats. The filled star marks the single current default. Selecting a row without its star changes this conversation's model without changing the default. **Drafts** has a separate default drafting model, set with the star beside a row in its own selector.

Web search and the active-tools chip

- When the selected model supports it, public web search starts turned on. A chip at the bottom of the composer shows what is active: with one tool on it names it — for example **Web search** — and with several on it reads **Tools** with a count.
- Click the small × on that chip to clear the next message's active tools: **Knowledge**, **Web**, and **Agent**, selected MCP connections, and queued automations. Every new chat starts with web search on again when the model supports it.
- Replies that used the web come back with citations you can click, and every source is listed in the session details panel (covered below).

Sending

- The paper-plane button sends your message with the current settings.

- The chevron (˅) beside it opens send options — per-reply switches for **Knowledge**, **Web**, and **Agent**, plus the **Reasoning** level (covered in their own section).

Dictate instead of typing

- Click the microphone button in the send controls at the bottom-right of the composer to start dictating. A live waveform shows that the platform is hearing you.
- Click the button again — it becomes a stop square — and your words are transcribed and inserted into the composer as editable text. Nothing sends until you press Enter.
- If the microphone is blocked or no speech was heard, the composer says so plainly so you can fix the problem and try again. The **Drafts** workspace has the same dictation button for drafting instructions.

WALKTHROUGH · 1:56 · HELP › LEARN

Start chatting

Send your first message, watch it work, stop a reply, edit and resend your prompt, and copy the answer.

Before you begin

- A signed-in account with at least one available model. If the composer says Connect a model provider to start chatting..., see Choose models and request access.

Step by step

1. Choose **New chat** at the top of the sidebar.
2. Check the model selector at the top right (**Model**: and a name). Choose another model there if you need one.
3. Type your request where it says **Ask anything…**, or choose a starter such as Explore an idea. A starter only fills in the opening words.
4. Press Enter, or choose the paper-plane Send message button, to send. **Shift+Enter** adds a new line instead.
5. Watch Aperture Chat is working: a timer, each step as it lands, and what comes Next. The answer appears under it.
6. Read the reply. The work trace above it reads Worked for, the time it took, and the number of steps, and the chat is listed under **Recent** with a title from your request.
7. To keep the answer, choose **Copy** response text under the reply and wait for Copied.

Path: Stop a reply

1. While Aperture Chat is working, choose · stop at the top right of the trace.
2. The reply stops and keeps any text already written, with You stopped this response before it finished.

3. To ask again, use Edit and resend.

Path: Edit and resend

1. Point at your message and choose **Edit message** (the pencil).
2. Change the text. Escape cancels.
3. Choose Send edited message. Everything after that message is removed, and the model answers the new text.

Path: Regenerate

1. On a finished reply, choose **Regenerate response** (the circular arrows).
2. The model answers the same request again.
3. A stopped or failed reply has no actions; use Edit and resend instead.

Path: Reuse a prompt in a new chat

1. Point at your message and choose **Load prompt in new chat** (the paper plane beside the pencil).
2. A new chat opens with your prompt and its attachments in the message box, ready to send.

Check that it worked

- ✓ Your message and the model's reply both appear, and the trace above the reply reads Worked for and the time it took.
- ✓ The chat is listed under **Recent** in the sidebar.
- ✓ Copied appears beside the reply's actions after you copy it.

Troubleshooting

WHAT YOU SEE	WHAT TO DO
The message box says "Connect a model provider to start chatting…"	No model is available to your account. Open the model selector or **Why isn't a model listed?**, and request access.
"You stopped this response before it finished. Regenerate or resend the message to run it again."	A stopped reply has no Regenerate button. Choose **Edit message** on your prompt, then Send edited message.
A reply reads "… did not return a completion: …"	The model service failed. Resend with **Edit message**. If it repeats, tell your administrator. Some self-hosted models reject Regenerate with "System message must be at the beginning."; resend instead.
The pencil says "Wait for the current response to finish before editing"	Wait for the reply, or choose · stop first.
"The edited message could not be sent. Check the text and try again."	Make sure the edited text is not empty, then choose Send edited message again.
"Copy unavailable"	The browser blocked the clipboard. Select the reply text and copy it with the keyboard instead.

WALKTHROUGH · 1:46 · HELP › LEARN

Dictation, images, and diagrams

Dictate a message when your workspace has a transcription model, ask an image model for pictures, and copy, view, and download diagrams.

Before you begin

- For dictation: a microphone, permission for this site to use it, and a transcription model (a Gemini Flash model) set up by your platform owner.
- For images: an image-generation model available to you in the model selector.
- For diagrams: any available model. Ask for a diagram, flowchart, or process. Mermaid, Graphviz, PlantUML, arrow chains, numbered step or layer lists, and box drawings all render as figures.

Step by step

1. In the message box, choose Dictate a message (the microphone).
2. Allow microphone access if the browser asks.
3. Speak. A live waveform shows it is recording; recording stops by itself after 2 minutes.

4. Choose Stop dictation and transcribe (the square). The transcript is added to the message box as editable text.
5. Review the text, then send it yourself; dictation never sends on its own.

Path: Images

1. In the model selector, choose a model that can generate images.
2. Describe the picture you want; ask for up to 4.
3. The images appear in the reply, labeled Generated image.
4. Point at an image and choose **Download** to save it. **Download** links last 7 days.

Path: Diagrams

1. Ask for a diagram, for example: show the stages of a process as a flowchart.
2. The reply shows a figure in the workspace's colors, with **Copy**, **PNG**, **SVG**, **Code**, and Edit in its header. Mermaid, Graphviz (DOT), PlantUML, arrow chains (A → B → C), numbered step or layer lists, and box drawings are all drawn as figures.
3. **Notes** the model wrote alongside a text drawing appear under the figure.
4. Choose **Code** to read the source exactly as the model wrote it; choose Diagram to switch back. **Copy** copies that source.
5. Choose **PNG** or **SVG** to download the picture.

Check that it worked

- ✓ Dictation: the transcript appears in the message box, ready to edit.
- ✓ Images: **Download** saves the image as a file.
- ✓ Diagrams: the figure renders in the reply, and **PNG** downloads it as a picture file.

Troubleshooting

WHAT YOU SEE	WHAT TO DO
"No configured Gemini Flash model is available for dictation. …"	Your workspace has no transcription model. Type your message, and ask your platform owner to set one up.
"Microphone access was denied. Allow microphone use for this site to dictate."	Allow the microphone in your browser's site settings, then try again.
"Microphone capture is not available in this browser."	Use a current browser on a device with a microphone.
"No audio was captured. Check the selected microphone and try again." or "The dictation model heard no speech in the recording."	Check which microphone your device uses and speak closer to it.
"… returned no images for this request. Try rephrasing the prompt or selecting a different image model."	Rephrase the request, or choose another image model.
"This diagram could not be rendered. Open Code to inspect the source, or Edit to fix it."	The model's diagram source has an error. Open **Code** to see it, then ask the model to correct the diagram, or choose Edit to fix it yourself.

9. Understand model availability and request access

Read the server's reason, ask for a model when permitted, and follow its request status.

- Open the chat model selector and choose **Why isn't a model listed?** If no model is usable, the No models available control opens the same explanation.
- **Models in your organization** separates **Usable now** from **Not available to you**. Read the reason on the model row: **Locked** describes an access restriction; **Provider offline** means you already have access but the provider needs attention.
- Choose **Request access** only where it is enabled. The request goes to an administrator for review; sending it does not grant immediate access.
- While a request is pending, the row shows its date and **Withdraw request**. Use **Refresh model access** after your administrator resolves it, then select the usable model in the chat picker.

GOOD TO KNOW

Your organization may show only models you can already use. Its browsing policy controls whether you can inspect other enabled models and request access. Some restrictions cannot be lifted by a request; ask your administrator about the stated reason. An offline provider needs a platform-owner repair, not another group-access request.

WALKTHROUGH · 1:58 · HELP › LEARN

Choose models and request access

Pick the model for a chat, star your default, find out why a model is missing, and request, withdraw, and use a model your administrator approves.

Before you begin

- A signed-in account with at least one model available. If the selector reads No models available, start at **Why isn't a model listed?**.
- Your organization must allow access requests. If it shows only models you can already use, ask your administrator about others.
- An administrator to review requests. Approval happens in their **Admin console** › **Model Access**.

Step by step

1. In a chat, open the model selector (**Model**: and the model's name) at the top right.
2. Choose a model to use it in this chat. Each chat keeps its own model.
3. Choose the star beside a model to make it your default for new chats in this browser.
4. Choose **Why isn't a model listed?** at the bottom of the selector. **Models in your organization** lists **Usable now** and **Not available to you**, with the server's reason for each.
5. Beside a **Locked** model, choose **Request access**. The row changes to Request pending since and the date.
6. Wait for your administrator to approve. Approval adds you to a group that carries the model and signs you out of your current sessions.
7. Sign in again. The model is listed under **Usable now** and in the selector. Choose it and send a message.

Path: Withdraw a request

1. Open the model selector › **Why isn't a model listed?**.
2. Beside the pending model, choose **Withdraw request**.
3. Withdrew the request for the model appears, and **Request access** is offered again.

Path: Provider offline

1. A **Provider offline** badge means the connection behind the model is not working.
2. Requesting access does not fix a disconnected provider; the platform owner must reconnect it.
3. Choose **Refresh model access** later, or use another model in the meantime.

Path: After approval

1. If the dialog or a chat says Session is invalid or expired. Sign in again., sign in again.
2. Open the selector: the new model is listed. Choose it for this chat, or star it to make it your default.
3. Send a message; the reply comes from the newly granted model.

Check that it worked

- ✓ The selector shows **Model**: and your chosen model's name, and the reply comes from that model.
- ✓ The starred model is filled in, and new chats start with it.
- ✓ After approval and a fresh sign-in, the model is listed under **Usable now** with Available.

Troubleshooting

WHAT YOU SEE	WHAT TO DO
"Not granted to any of your groups. An administrator can add you to a group that has this model."	Choose **Request access**, or ask your administrator to add you to a group that has the model.
"The provider behind this model is not connected right now." (Provider offline)	A request cannot fix this. The platform owner must reconnect the provider. Use another model meanwhile.
"Disabled by the platform owner for the whole organization."	The model is switched off for everyone. Ask your administrator whether it will be enabled.
"Session is invalid or expired. Sign in again." right after a request	Your administrator approved the request, which signs you out. Sign in again; the model is then listed.
"Model access requests are disabled by organization policy."	Your organization does not take requests here. Contact your administrator directly.
"Too many access requests. Try again shortly."	Wait a minute. A pending request stays pending; you do not need to resend it.
The selector reads No models available	No model is usable for your account yet. Choose it to open **Models in your organization**, request access, or contact your administrator.

10. Reading and acting on replies

The work trace, citations, and the actions under every message.

The work trace

- While a reply is being produced, the trace runs on the page above it: the assistant's name and is working, a live timer, each step as it really happens, and what comes next.
- Choose · stop beside the timer to halt a reply. The conversation is kept.
- When the reply finishes, the line says how long it took, for example Worked for 12s, with the number of steps and any checks or flags.
- Click that line at any time to expand or fold the trace. It lists what actually happened: the model used, the sources searched, how long the model thought, and the checks that ran.

Actions under each response

- **Copy** — copies the response as clean, readable text.
- Thumbs up / thumbs down — sends feedback your administrators can review.
- **Branch** — starts a new chat that continues from that response, leaving the original untouched.
- **Regenerate response** — asks the model to answer the same prompt again. Version arrows appear on the response with a counter (for example “2 / 3”) so you can flip between the versions it has produced.
- **Transfer to Drafts** — opens a chooser with **Word document**, Slide deck, and Spreadsheet, and suggests the one that fits the reply. The result opens in **Drafts**, where you can edit, version, and export it.

Actions under your own messages

- **Edit message** — reopens your prompt for editing. Sending the edit removes the later replies and asks again from that point.
- **Load prompt in new chat** — copies the prompt and its attachments into a fresh chat's composer, ready to adjust and resend.

Diagrams in replies

When a reply contains a diagram (a flowchart, sequence, or similar), it renders as a real figure, not a code block. The figure's toolbar offers **Copy** for the diagram source, **PNG** and **SVG** to download it as an image file, and **Code** to flip between the drawing and its source text.

Generated images

- When the selected model can generate images, just ask for one — the finished images appear directly in the reply.
- Click **Download** under an image to save it as a file.

Citations and token usage

- When a reply cites your knowledge bases or the web, numbered markers appear in its text and a button sits under it. It reads View 2 citations when every row was cited, and View 2 sources when the list also holds a consulted web result, an attachment, or a tool result.
- Click a knowledge source or marker to open the real document at the cited passage (see “Check a source”). **Web** sources open their page in a new tab.
- A small token count appears under a reply only when the model provider actually reported one — the platform never shows an estimate dressed up as a real number.

WALKTHROUGH · 3:19 · HELP › LEARN

Follow the work trace and act on replies

Read what was really done for a reply, rate it with a note, branch it into a new chat, and send it to Drafts as a document, a deck, or a spreadsheet.

Before you begin

- A chat with an available model (see Start chatting).

Step by step

1. Send a message. Under the reply's heading, the work trace opens by itself: Aperture Chat is working, a timer, each step as it lands, and Next.
2. To fold it to one line while it runs, choose the arrow beside the timer (Collapse work trace). · stop stays available.
3. When the reply lands, the trace reads Worked for, the time it took, and the number of steps, such as Worked for 13s · 5 steps.
4. Choose that line (Expand work trace) to read every step: Routed to names the model, Thought for is the time until the first words arrived, and Delivered the reply gives the length.
5. Choose it again to fold it (Collapse work trace).
6. Choose Send positive feedback (thumbs up) or Send negative feedback (thumbs down) under the reply.
7. Optionally type a note in the box that opens, then choose Send note. Note sent confirms it.
8. Choose **Branch** response into new chat to continue from this reply in a separate chat.
9. Choose **Transfer to Drafts**, then **Word document**, Slide deck, or Spreadsheet under Open in **Drafts** as.

Path: Read the steps

1. Routed to names the model, and With lists what you switched on: knowledge, web search, tools, attachments.

2. Then what was really gathered: Found 2 passages in workspace knowledge, Searched the web, Read 1 attachment, Read 1 linked page, Recalled 2 memories, or Working as and an agent's name.
3. Thought for is the time until the first words arrived. Wrote the reply, Wrote python, Drew a diagram, and Built a table name what the reply holds.
4. Checks on the finished reply count in the summary, such as 1 check passed: Verified, **Code** blocks are all closed, Every citation links to a source.
5. A flag in amber is a problem to read before you rely on the reply, such as A code block was left open.

Path: Rate a reply

1. Choose the thumbs up or thumbs down under the reply. Positive feedback sent (or Negative feedback sent) appears.
2. In What worked well? or What went wrong?, add an optional note of up to 2,000 characters.
3. Choose Send note, or close the box to skip the note.

Path: Branch into a new chat

1. Choose **Branch** response into new chat under the reply.
2. A new chat opens, titled **Branch**: and the original title, holding the prompt and this reply.
3. Continue there; the original chat is unchanged.

Path: Transfer as a Word document

1. Choose **Transfer to Drafts** at the right of the reply's actions.
2. Under Open in **Drafts** as, choose **Word document**.
3. **Drafts** opens a new document titled after the chat, saved as Version 1, with the reply and any citations.
4. Edit it, save versions, and export it to Word or PDF (see **Draft** documents).

Path: Transfer as a slide deck

1. Choose **Transfer to Drafts**, then Slide deck.
2. **Drafts** opens the deck editor, with slides built from the reply's headings and points.
3. A reply with headings and short points makes the best deck. See Build a slide deck.

Path: Transfer as a spreadsheet

1. Choose **Transfer to Drafts**, then Spreadsheet. The line under it says what will happen, such as Its table becomes a sheet.

2. Each table in the reply becomes a sheet, with the edits you made in chat. A reply with no table puts its lines down the first column.
3. See Edit tables and diagrams in a reply.

Check that it worked

- ✓ The finished trace reads Worked for and the time, and Routed to names the model.
- ✓ Note sent appears beside the reply's actions after sending a note.
- ✓ A chat titled **Branch**: … appears under **Recent**.
- ✓ **Drafts** opens the reply in the format you chose, as Version 1, and the assistant rail says it was transferred.

Troubleshooting

WHAT YOU SEE	WHAT TO DO
Thinking keeps counting and no words arrive	The model is busy or slow. Wait, or choose · stop and resend. Thought for records how long the first words took.
"Connection dropped — resumed where it left off"	The connection dropped and the reply picked up again, so nothing is needed. If it repeats with no words arriving, choose · stop and resend when the model is less busy.
A step lands just after the reply appears	Steps play in one at a time, so the trace can finish a moment after the reply. The finished trace is the record.
"A code block was left open"	The reply ends inside a code block, so it may be cut off. Ask it to continue, or regenerate.
"HTML page ends early"	There is no closing tag, so the page may be cut off. Ask it to finish the page, or regenerate.
"Not met: …"	A check found something you asked for missing from the reply. Regenerate or ask a follow-up to cover it.
"Not met: Deliver the complete long-form piece" on a short answer	This is a known false alarm, not a fault in the reply. The check treats words such as brief, draft, memo, report, paper, page, or complete as a request for a long piece of at least 1,200 words, even in a one-line question. If the short answer is what you wanted, ignore the flag. You do not need to regenerate.
A flag says the reply cites a marker "with no source"	Those markers have nothing behind them in this reply. Do not rely on those claims until you have checked them.
"Could not branch"	The branch could not be created, often because the connection dropped. **Try again** when the chat has saved.
No actions under a reply	Actions appear only on finished replies. A stopped or failed reply has none; resend with **Edit message**.
Transfer to Drafts is missing	It appears on finished replies with text. Wait for the reply to finish.

11. Work with code in chat

Edit code in place, ask AI to change a selection, download a file, and preview it in the canvas.

Code in a reply is a working block, not just text. It is highlighted by language, and its toolbar lets you edit it where it sits, have AI change only the part you select, download it under a sensible file name, and open a

preview in the canvas at the right edge.

TIP

Select the smallest piece that needs changing before you use **Ask AI**, and say what should stay the same. You review the result before it replaces anything.

WALKTHROUGH · 3:33 · HELP › LEARN

Work with code in chat

Read highlighted code, save it as a named file, edit it in place, have AI change only the lines you select, and run a page in the artifact canvas.

Before you begin

- A chat with an available model. **Ask AI** uses the model selected for the chat.
- Preview runs HTML, **SVG**, and CSS. Other languages open in the canvas as source.

Step by step

1. Ask for code, and name the language and the function or page you want.
2. Read the code block: its language, its line count, and numbered, colored lines. Colors work out the language even when the reply did not name it.
3. Choose **Copy** to copy the code, or **Download** to save it as a named file.
4. Choose Edit, change the code, and choose **Done** (or press Esc). Saved appears in the toolbar.
5. Choose Undo to put back the code from before your last edit.
6. Select lines in the block with the pointer. Choose **Ask AI**, or press ⌘J (Ctrl+J on Windows).
7. Choose an action such as Add comments, or type your own instruction, and press Enter.
8. Read the suggestion's line changes, then choose **Replace** or **Discard**.
9. On an HTML, **SVG**, or CSS block, choose Preview to run it in the artifact canvas.

Path: Download

1. Choose **Download** in the block's toolbar. Pointing at it shows the name it will use.
2. The name comes from a filename in the block, then an HTML or **SVG** title, then the main function or class, then the nearest heading.

Path: Edit in place

1. Choose Edit. The block becomes an editor with the same colors.
2. Tab indents, Shift+Tab outdents, and Esc finishes.

3. Choose **Done**. Saved appears, and the edit is part of the reply, so **Copy**, **Download**, and **Transfer to Drafts** all carry it.
4. Undo puts back the code from before your last edit.

Path: Ask AI on a selection

1. Select the lines you want changed, in the block or in the editor.
2. Choose **Ask AI**, or press ⌘J (Ctrl+J on Windows).
3. Choose Fix bugs, Simplify, Add comments, Add error handling, Use clearer names, Add types, or Modernize syntax, or type your own instruction.
4. The suggestion shows lines added and removed. Type a follow-up to refine it, or choose **Try again** for another version.
5. Choose **Replace** to write it in, or **Discard** to leave your code as it was.
6. Only the lines you selected change.

Path: Artifact canvas

1. Choose Preview on a code block. The canvas slides in from the right.
2. Preview runs the page; **Code** shows the numbered source. Edit, **Done**, and Undo work here too, and **Ask AI** works on lines you select in the code.
3. Use the arrows to move between the code blocks in this chat.
4. Choose Expand the canvas to the full window for more room, and Close the artifact canvas (or Esc) to return to the chat.
5. The pull tab at the right edge of the chat reopens it.

Check that it worked

- ✓ **Download** saves a file with the code and a meaningful name, such as renewals_due.py.
- ✓ Saved appears after **Done**, and the code keeps your edit when you reopen the chat.
- ✓ After **Replace**, the suggestion shows in the block with Saved, and Undo offers the earlier code.
- ✓ Preview shows the running page, and an edit to its source changes the preview.

Troubleshooting

WHAT YOU SEE	WHAT TO DO
"Edited here only"	The edit could not be saved to the reply, so it lives on this screen. **Copy** your code, reload the chat, and edit again.
Edit and Ask AI are missing	They appear when the reply has finished. Wait for it, or choose · stop.
"The code changed since you selected it. Close this and select the code again."	The code moved under the selection. Close the box and select the lines again.
"Choose a model in the composer to edit code with AI."	Choose a model in the model selector at the top right, then select the code again.
Edit code with AI shows "System message must be at the beginning."	Some self-hosted models accept only one system message, so they refuse this request. Choose another model, or ask for the change in chat and paste it in with Edit.
"Personal data was hidden from the model. Check the ⟦ ⟧ placeholders."	Your organization conceals personal data, so the suggestion holds placeholders. **Replace** them before you accept it.
Preview shows only the source	Preview runs HTML, **SVG**, and CSS. Other languages open as source, and you run them yourself.
A page in the canvas cannot reach the internet or another site's files	The canvas runs pages in a sandbox. Ask for one self-contained page with inline CSS and scripts.
"A code block was left open" or "HTML page ends early" in the trace	The reply was cut off. Ask it to continue, or regenerate.

12. Edit tables and diagrams in a reply

Correct a table in place, send it to a spreadsheet, and shape a diagram before you share it.

Tables and structure diagrams in a reply can be changed directly, so a small fix does not need another prompt. Edits to a table save into the reply, and **Transfer to Drafts** carries them into a spreadsheet. Structure diagrams have themes, connector and corner styles, cards you can drag, arrows you can bend, and per-card colors, and their **PNG** export keeps what you see.

WALKTHROUGH · 3:00 · HELP › LEARN

Edit tables and diagrams in a reply

Correct a table where it sits, send it to a spreadsheet, and restyle, rearrange, and export a diagram, all without asking the model again.

Before you begin

- A chat with an available model, and a finished reply with a table or a diagram. The tools appear once the reply has finished.
- Style, dragging, and arrow handles work on structure diagrams, the boxes-and-arrows charts labeled Structure diagram. Other figures, such as a pie chart or a timeline, offer Edit on their source.

Step by step

1. Ask for a table. Saying markdown table keeps the answer in chat.
2. Click a cell, type the new value, and press Tab to move to the next cell or Enter to move down.
3. Use Add row, Add column, **Delete** row, or **Delete** column under the table. Undo steps back.
4. Choose **Done**.
5. Choose **Transfer to Drafts**, then Spreadsheet, to open the edited table as a sheet.
6. Ask for a flowchart, org chart, or process flow, and name the boxes.
7. On the diagram, choose Style, then a theme, **Connectors**, and Corners.
8. Drag a box to move it. Its arrows follow.
9. With a box selected, choose Header color and a swatch.
10. Click an arrow, and drag its round handle to bend it.
11. Choose **PNG** or **SVG** to save the chart as a picture.

Path: Edit a table

1. Click any cell, or point at the table and choose Edit table to start at the first header.
2. Type. Tab moves to the next cell, Enter moves down, Shift goes back, and Esc cancels the open cell.
3. Add row and Add column work from the cell you are in. **Delete** row and **Delete** column remove its row or column.
4. Undo steps back through your changes. **Done** closes the tools.
5. Your edits are saved into the reply, so **Copy** and **Transfer to Drafts** carry them.

Path: Send a table to a spreadsheet

1. Choose **Transfer to Drafts**. Spreadsheet is marked Suggested when the reply is mostly a table.
2. Check the line under it, such as Its table becomes a sheet, as edited here.
3. Choose Spreadsheet. Each table becomes its own sheet, with a bold frozen header.
4. See Build a spreadsheet with the assistant.

Path: Restyle a diagram

1. Choose Style in the diagram's toolbar.
2. Choose a theme: Aperture, Graphite, Forest, Indigo, Plum, Ember, Soft, or Blueprint.
3. Under **Connectors**, choose Elbow, Curved, or Straight. Under Corners, choose Rounded or Square.
4. Every choice applies and saves at once. Choose Style again to close the tray.

Path: Rearrange boxes and arrows

1. Drag a box by its body. Guides help it line up, and its arrows follow.
2. Click text in a box to retype it. With a box selected, the arrow keys nudge it, and Shift moves it further.
3. Point at a box for its chip: move it between rows, choose Header color, show it as a banner, or delete it.
4. Click an arrow for its chip: Solid, Dashed, or Dotted, reverse it, or edit its label. Drag either end to another box.
5. An arrow with a corner has a round handle to bend it. An arrow running straight between aligned boxes has none, and Straight connectors have none.
6. ⌘Z (Ctrl+Z on Windows) undoes a change. Reset layout puts dragged boxes back and straightens bent arrows.

Path: Edit in a form, or by its source

1. Choose Edit to open Edit diagram, a form for every box, its details, and the arrows, with a live preview.
2. Choose **Code** to read the source as the model wrote it. **Copy** copies that source.
3. On a pie chart, timeline, or other figure, Edit is the way to change it.

Check that it worked

- ✓ **Reopen** the chat: the table and the diagram keep your changes.
- ✓ The spreadsheet shows your edited values and any row you added.
- ✓ **PNG** and **SVG** download the chart as drawn, with your theme, colors, and layout.

Troubleshooting

WHAT YOU SEE	WHAT TO DO
"Build this as a spreadsheet?" appears instead of a reply	Asking for a table can offer the spreadsheet editor. Choose Continue in chat for a reply here, or Build in spreadsheet editor.
"That edit could not be saved. The reply changed underneath it; try again."	The reply changed while you were typing. Open the cell again and retype the change.
Style is missing from a diagram	Style appears on structure diagrams. Ask again for a flowchart with boxes and arrows, or use Edit on this figure.
The boxes have no arrows	Ask for them in words, such as connect each box to the next box with an arrow, or add them with Edit.
An arrow has no round handle	It runs straight between aligned boxes, or **Connectors** is set to Straight. Drag a box out of line, or choose Elbow or Curved.
Reset layout is greyed out	Nothing has been dragged or bent yet.
"The reply was cut off mid-diagram — showing everything that arrived. Use Edit to finish the chart, or regenerate the reply."	Choose Edit to finish the chart, or regenerate the reply.
"Diagram source needs repair"	The chart's structure is incomplete. Ask for the diagram again.
"Saving failed — try again."	The Edit diagram change did not save. Check your connection and choose Save diagram again.

13. Symbol shortcuts: / @ # $ >

Five characters that pull prompts, agents, knowledge, skill files, and automations into a message.

Start a word in the message box with one of five symbols and a menu opens with matching items. You can also choose **Send options** → **Resources** to browse without memorizing a symbol. Forgot one? The bottom of Session details (ⓘ) lists all five, and **Help** → Symbol shortcuts: / @ # $ > shows each menu in action.

TYPE	WHAT IT OPENS
/	Saved prompts (inserted as text) and enabled MCP connections (turned on for this message).
@	**Agent** profiles — the reply routes through the one you pick.
#	**Knowledge** bases and the files inside them. Picking one turns on **Knowledge** for that source.
$	Saved skill files. The one you pick is attached to the message.
>	Automations, including paused ones. The one you pick runs on your message when you send.

- Type the symbol, then keep typing to filter the list.
- Use the ↑ and ↓ arrow keys to move through the menu.
- Press Enter to insert the highlighted item, Tab to complete it, or Escape to dismiss the menu.

Browse resources

On the **Resources** tab, use **Find a resource** to search by name, or select All, **Knowledge** bases, Files in knowledge sources, MCP connections, **Prompts**, **Agents**, Skill files, or Automations. A selected connection or automation shows a check; choose it again to remove it. Read an empty or failed-loading state before retrying. The **Type shortcuts in chat** reference explains each symbol below the results.

TIP

The expanded composer focuses on editing a longer message. Return to the normal composer to browse resources, adjust send options, and send with the visible controls.

WALKTHROUGH · 2:08 · HELP › LEARN

Symbol shortcuts: / @ # $ >

Type a symbol in the message box to add a saved prompt, an agent, knowledge, a skill file, or an automation, then send.

Before you begin

- A chat with an available model.
- Items to choose from: saved prompts and skill files are shared by your administrators; agents, knowledge bases, and automations are ones you can use or have built.

Step by step

1. Click in the message box. At the start of a word, type one of the five symbols: / @ # $ or >.
2. A list opens above the message box. Keep typing to narrow it.
3. Use the up and down arrow keys to move, and Enter (or a click) to choose. Escape closes the list.

4. Check what was added: prompt text in the box, or a chip under it (**Agent**, **Knowledge**, a skill file, or an automation).
5. Finish your message and send it.

Path: / Prompts and MCP connections

1. Type / to list saved prompts and enabled MCP connections.
2. Choose a prompt to put its text in the message box; edit it before sending.
3. Choose a connection to turn it on for this message.

Path: @ Agents

1. Type @ to list the agent profiles you can use.
2. Choose one. @ and its name are added, and the **Agent** chip appears.
3. The reply runs through that agent's model, instructions, knowledge, and tools.

Path: # Knowledge

1. Type # to list knowledge bases and the files in them.
2. Choose a knowledge base, or a single file to search its source.
3. The **Knowledge** chip appears; the reply searches it and cites what it uses.

Path: $ Skill files

1. Type $ to list saved skill files, such as citation rules or an approval checklist.
2. Choose one. It is attached to the message as a file chip (Name.md).
3. The model follows it for this message.

Path: > Automations

1. Type > to list your automations, including paused ones.
2. Choose one. It is queued in the chip under the message box.
3. When you send, the automation runs on your message. × removes it before sending.

Check that it worked

- ✓ After choosing, the message box holds the prompt text or shows the matching chip.
- ✓ A message sent with # and $ returns a reply with markers such as [K1], and View N sources → lists what it used.
- ✓ Session details › Symbol shortcuts lists all five symbols at any time.

Troubleshooting

WHAT YOU SEE	WHAT TO DO
"No matching commands. Try another name."	Nothing matches what you typed after the symbol. **Delete** some letters, or check the item's name.
"No saved prompts or enabled MCP connections yet — add them under Tools"	Nothing is shared with you yet. Your administrator adds prompts and connections.
"No agent profiles available yet — create one under Agents"	Build an agent (if your account can) or ask your administrator to share one.
"No knowledge bases are enabled yet — add one under Knowledge"	Ask your administrator to share a knowledge base, or create one if your account can.
"Some files could not be loaded. Retry"	Choose Retry in the list. Sources that already loaded stay usable.
The list does not open	The symbol must start a word: type a space first if it follows other text.

14. Attaching files, web pages, and connected sources

Upload from your computer, fetch a page by link, or pull from your organization's drives.

- Click the paperclip button at the bottom-left of the composer.
- Click **Upload from computer** to attach files from this device. The model reads them as context for your next message.
- Or click **Web page by link** and paste one or more web addresses — the platform fetches up to 3 public pages and attaches them as cited sources for this message.
- Attached items appear as chips above the composer. Click the × on a chip to remove one before sending.

Attach from source

Below those options, under the **Attach from source** heading, the menu lists your organization's workspace sources: Google Drive, OneDrive, SharePoint, Box, and iManage. Which ones appear depends on your administrator: a source that is switched off or hidden in **Admin console** → **Connections** does not appear in the menu, and its files cannot be attached.

Connecting your own account

- Cloud sources read from your own account. The first time you pick one, the picker may ask you to connect it — click the Connect button for that source and a sign-in window opens.

- **Approve** read access in that window. The file list refreshes on its own once access is granted, and only you can see files from your account.
- The picker shows files at the top level of the drive or the folder configured for the source, within your account's permissions.

GOOD TO KNOW

If a source you expect is missing or needs configuration, ask your administrator: workspace connectors are set up, tested, and hidden or shown in **Admin console** → **Connections**. Your own Connect action in the attach menu remains separate and grants access only through your source account.

WALKTHROUGH · 2:09 · HELP › LEARN

Attach files and sources

Attach a file from your computer, a web page by link, or a file from a connected cloud source, and know what the model actually receives.

Before you begin

- A chat with an available model.
- For cloud sources (Google Drive, OneDrive, SharePoint, Box, iManage): your administrator must set up the connector, and you sign in to your own account the first time.
- Files up to 25 MB each. **Web** pages must be public addresses starting with http:// or https://.

Step by step

1. In the message box, choose Add attachment (the paperclip).
2. Choose **Upload from computer** and pick one or more files.
3. Wait for the file chip to finish uploading. Remove a file with the × on its chip.
4. Type your question about the file and send it.
5. Check the reply: it uses the file's content, the trace includes Read 1 attachment, and View 1 source → lists the file.

Path: Web page by link

1. Paperclip › **Web page by link**.
2. Type or paste the full address into **Web** page address, such as https://example.com, and choose Add link (or press Enter).
3. The link appears as a chip. Add up to 3 links per message.
4. Send your question. The page is fetched when you send, the trace includes Read 1 linked page, and View 1 source → lists it, or View 1 citation → when the reply marks the page.

Path: Cloud sources

1. Paperclip › choose a source under **Attach from source**: Google Drive, OneDrive, SharePoint, Box, or iManage.
2. The first time, choose Connect and approve read access in the sign-in window. Only you see files from your account.
3. Tick up to 10 files and choose Attach selected.
4. If the dialog says the source is not ready, your administrator must finish setting up that connector.

Path: What the model receives

1. Word (.docx) and text files (.txt, .md, .csv, .json, .xml, .html, .rtf, .eml, .log): the opening text, up to about 2,400 characters.
2. Images: the picture itself, if the selected model can read images; otherwise the model says it cannot see them.
3. Audio and video: a transcript, when your workspace has a transcription model. Media longer than 45 minutes is refused.
4. PDF, Excel, and PowerPoint files from your computer: currently only the file name. To ask about their content, add them to a knowledge base, attach them from a cloud source, or open a Word or PDF file in **Drafts** with Open in editor (in the **Drafts** paperclip menu).

Check that it worked

- ✓ The file chip finishes uploading without Upload failed.
- ✓ The reply states facts that appear only in your file or page.
- ✓ A web-page reply offers View 1 source →, or View 1 citation → when it marks the page.

Troubleshooting

WHAT YOU SEE	WHAT TO DO
"Attachment exceeds the 25 MB chat upload limit."	Split or compress the file, or add it to a knowledge base, which accepts larger files.
"Could not upload the attachment. Check your connection and try again."	Check your connection, remove the failed chip, and attach the file again.
The reply says it cannot see the content of a PDF, spreadsheet, or slide file	Files of those types uploaded from your computer currently reach the model by name only. Use a knowledge base or a cloud source instead, or open a Word or PDF file in **Drafts** with Open in editor.
"Enter a full web address starting with http:// or https://."	Paste the complete address, including https://.
"You can attach up to 3 web links per message."	Send the first three, then attach the rest in a follow-up message.
"Web source fetch failed for …"	The page could not be fetched (it may need a sign-in or be offline). **Copy** the text into your message instead.
"Google Drive is not ready." (or another source)	Your administrator has not finished that connector. Ask them, or upload the file from your computer.
A cloud source, such as Google Drive, is missing from the paperclip menu	Your workspace administrators hid it (**Admin console** › **Connections** › Hide). A hidden source is no longer offered in the attach menu, and the server refuses it with "Google Drive is not available in this workspace." Ask your administrator, or upload the file from your computer.
"Media longer than 45 minutes cannot be transcribed in this version."	Split the recording and upload the part you need.

15. Send options: Knowledge, Web, Agent, and Reasoning

Control what the model may use, one reply at a time.

- Click the chevron (˅) beside the paper-plane send button.
- The menu opens with **Send now** at the top — that simply sends with the current settings.
- Below it are three switches you can turn on or off for the next reply, and a **Reasoning** slider at the bottom.

SWITCH	WHAT IT DOES WHEN ON
Knowledge	The reply searches your enabled knowledge bases and cites what it finds, with links back to the sources. A picker lets you choose which bases to use.
Web	The reply uses public web search. Results come back as clickable citations, and the sources are listed in session details. Available when the selected model supports it.
Agent	The reply uses the selected agent profile and its permitted tools. Turning this on can choose the first available profile if none is selected; confirm the **Agent profile** field before sending, or choose a profile with @.

Reasoning level

The **Reasoning** group at the bottom of the menu is a three-position slider from **Fast** to **Smart**. **Fast** favors quicker answers; **Smart** makes the model think longer for more detailed output; the middle is a balanced default. The slider is only active when the selected model supports reasoning levels — otherwise it is disabled and says so.

Whenever tools are on, the active-tools chip appears next to the paperclip: the single tool's name, or **Tools** with a count. Click its × to turn off **Knowledge**, **Web**, and **Agent** and clear selected MCP connections and queued automations for the next message.

On the **Reply settings** tab, **Stream replies** controls whether text appears as the model produces it or only after the reply finishes. The **Resources** tab opens the searchable resource picker; **MCP connections and resources** also opens it from **Reply settings**. These controls change how the next reply is prepared or displayed; they do not supply missing provider or connector access.

WALKTHROUGH · 3:07 · HELP › LEARN

Knowledge, Web, Agent, and reply settings

Ground a reply in a knowledge base and check its sources, and choose Web, an agent, reasoning, streaming, and resources for a message.

Before you begin

- A chat with an available model.
- For **Knowledge**: at least one knowledge base shared with you (see **Knowledge** bases).
- For **Web**: your workspace must connect web search to the model you use. Otherwise **Web** is greyed out.
- For **Agent**: an agent profile you can use (see **Agent** profiles).

Step by step

1. In the message box, choose **Send options** (the arrow beside the paper plane). **Send options** opens on **Reply settings**.

2. Choose **Knowledge**, then choose the source to search, such as Litigation Playbook. Each source shows how many files it holds.
3. Choose Close send options. The **Knowledge** chip under the message box shows it is on.
4. Type your question and send it. Asking it to cite the source after each sentence gets you checkable markers such as [K1].
5. Check the reply: the work trace says what it found, such as Found 2 passages in workspace knowledge, and a button such as View 1 citation → appears under the answer.
6. Choose that button to open Session details › **Sources gathered**, with each file name, K number, and the passage used. Only passages the reply cited are listed. Choose a row to open the document at that passage.

Path: Web

1. When your workspace connects web search to the model you use, **Web** is on in every new chat, and the chip under the message box reads **Web search**.
2. Send your message. Aperture Chat searches public web sources and gives the results, with their addresses, to the model so the reply can cite them.
3. To answer without the web, turn off **Web** in **Send options** (or choose × on the chip, which turns every option off). That lasts for this chat; the next new chat starts with **Web** on again.
4. If **Web** is greyed out, your workspace has not connected web search to this model. Ask your administrator.

Path: Agent

1. **Send options** › **Agent**. An **Agent profile** list appears under it.
2. Choose the profile you want; the line under it counts its knowledge, files, and tools.
3. Send your message. The finished trace reads **Agent** worked for and the time, with a Working as step naming the profile. See **Agent** profiles to build your own.

Path: Reasoning and streaming

1. Under **Reasoning**, drag the slider toward **Fast** for quicker answers or **Smart** for deeper thinking, on models that support it.
2. Clear **Stream replies** to show each reply only when it is complete; leave it ticked to watch the answer arrive.

Path: Resources

1. **Send options** › **Resources** (or **MCP connections and resources**).

2. **Search** by name, or filter by **Knowledge** bases, Files in knowledge sources, MCP connections, **Prompts**, **Agents**, Skill files, or Automations.
3. Choose an item. A prompt's text fills the message box; other items turn on for this message.

Path: Turn everything off

1. Choose × on the chip under the message box.
2. **Knowledge**, **Web**, and **Agent** turn off, selected MCP connections clear, and queued automations are removed.

Check that it worked

- ✓ The chip under the message box names what is on (**Knowledge**, **Web search**, **Agent**, or **Tools** with a count).
- ✓ A knowledge reply that cited its sources shows View N citations →, and **Sources gathered** lists the files and passages.
- ✓ The reply's trace opens with Routed to and what you switched on, then reports what each option found.

Troubleshooting

WHAT YOU SEE	WHAT TO DO
Web is greyed out: "Web search is turned off for this model by your workspace configuration"	Your workspace has not connected web search to this model. Choose another model, or ask your administrator.
With Web on, the reply stays on Aperture Chat is working	Some self-hosted models currently reject web-search requests. Choose · stop, turn **Web** off, and resend; tell your administrator.
"Web search (…) is unavailable: … Turn off Web for this reply to continue without it."	The search service could not be reached. Turn **Web** off for this message, or try again later.
A knowledge reply has no View N citations button	Only sources the reply cited are listed, and this reply wrote no markers such as [K1]. Ask again and add "cite the source after each sentence". The trace still says what was found.
Knowledge cannot be chosen	No knowledge base is shared with you. Ask your administrator, or create one if your account can (see **Knowledge** bases).
"Create an agent profile in Agents to enable this mode."	No agent profile is available to you. Build one under **Agents**, or ask your administrator to share one.
An agent is listed as "(needs Hermes approval)" and cannot be chosen	It is a **Hermes** agent. Ask your administrator to turn on **Can use Hermes companion** for one of your groups.
"… does not support reasoning levels"	The selected model has no reasoning control. The slider has no effect for it.

16. Session details and sources

Real token usage, active tools, every source this chat gathered, and the symbol shortcuts.

- Click the round information button (ⓘ) at the right end of the chat's top bar.
- The session details panel opens for the current chat.
- **Current chat** and **Model** — the user-message and response counts, and which model is active.
- **Tokens used** — shown only when the model provider reported real numbers. Otherwise the panel says “Not reported by the provider”.
- **Tools** — exactly what is switched on for your next message: web search, knowledge, agent mode, plus any automations or MCP connections you added in the composer. “Off” means nothing is active.

- **Sources gathered** — the web sources and knowledge documents replies in this conversation cited, each with the passage it relied on. Click a knowledge row to open the document at that passage.
- Symbol shortcuts — at the bottom of the panel, the five symbols you can type in the message box and what each one pulls in. See "Symbol shortcuts: / @ # $ >".

The **Context window** meter describes how much context this conversation uses. For older conversations without provider counts it can show ≈ and estimated from message length. Treat that as an estimate; **Tokens used** remains based on actual provider reports. When the context window fills, start a new chat and include the details it needs to continue reliably.

WALKTHROUGH · 1:02 · HELP › LEARN

Session details and context

Open Session details to check the model, tokens used, how full the context window is, the sources a reply used, and the symbol shortcuts.

Before you begin

- A chat with at least one reply. **Sources gathered** appears after a reply that cited knowledge or the web, or that had a file attached.

Step by step

1. In a chat, choose Session info (the i button at the top right). Session details opens on the right.
2. Read Session summary: **Current chat**, **Tokens used**, **Model**, **Knowledge** bases, **Tools**, and **Agent profile**.
3. Read **Context window**: the meter and how many of the model's tokens this chat already uses.
4. Scroll to **Sources gathered** to see the sources behind your replies, with each K (knowledge) or W (web) number and the passage. Choose a document row to open it at that passage.
5. Scroll to Symbol shortcuts for the five symbols you can type in the message box.
6. Choose Close session details when you are done.

Path: From a reply's sources

1. Under a reply, choose View N citations → (or View N sources →, when the list includes something the reply consulted without citing it).
2. Session details opens at **Sources gathered**, with that reply under Selected response. The same button then reads Hide citations or Hide sources and closes it again.
3. Choose a document row to read it on the cited page. See Check a source: open the cited document.

Check that it worked

- ✓ **Tokens used** shows the counts the provider reported (in, out, and total), or Not reported by the provider.
- ✓ The context window meter shows a percentage and tokens used of the model's total.
- ✓ Selected response under **Sources gathered** lists the same number of sources as the button under the reply.

Troubleshooting

WHAT YOU SEE	WHAT TO DO
Tokens used reads "Not reported by the provider"	The model service did not return usage. Nothing is wrong with your chat; the context meter may use an estimate instead.
The context meter is marked estimated or ≈	It is based on message length, because the provider did not report usage for some messages.
The context window is nearly full	Start a new chat for a fresh window. Older details may otherwise matter less to the answer.
No Sources gathered section	No reply in this chat cited a source or had a file attached. Turn on **Knowledge** in **Send options**, and ask it to cite the source after each sentence.

17. Check a source: open the cited document

Open the document behind an answer, land on the cited passage, and verify it before you rely on it.

A cited answer is only as good as the passage behind it, so Aperture Chat takes you to that passage. Click a source row or an inline marker such as [K1] and the real document opens beside the chat, at the cited place, with the passage marked and quoted in a Cited passage callout.

- PDF, Word, PowerPoint, Excel, and scanned files open as real pages on servers that can convert them, with page, zoom, and go-to-page controls. **Text** files open as pages of text.
- Go to the cited passage returns to the mark after you browse. **Download** original saves the file as it was uploaded.
- A document is listed only when the reply wrote its marker. Passages that were searched but not cited stay out of the list, so a reply can show no sources at all. That can mean the documents did not apply, or that the reply drew on them without marking it. To get markers, ask again and add: cite the source after each sentence. Treat an unsourced answer as unchecked.
- A marker shows where the reply says a claim came from. Read the passage to confirm it says what the reply says.

- **Library** rows open the same viewer: click a file's name or its Preview button.

GOOD TO KNOW

Files uploaded before this feature have no stored original, so they open as their indexed text with a note, and there is no **Download** original. You can still read the passage. For real pages, ask whoever manages the knowledge base to upload the file again and remove the old copy. Uploading adds a new document.

WALKTHROUGH · 4:17 · HELP › LEARN

Check a source: open the cited document

Open the document behind an answer, land on the cited page with the passage marked, and check it before you rely on it.

Before you begin

- A knowledge base you can search, your own or one shared with you. **Knowledge** bases shows how to build one.
- Documents uploaded since this release. Older ones open as their indexed text until someone who manages the knowledge base uploads them again.
- For Word, PowerPoint, and Excel layouts: a server that can convert them. Otherwise they open as text, with a note saying so.

Step by step

1. In a chat, type # and choose your knowledge base, then type a plain question and send it.
2. Under the reply, choose View N citations →. If the list also holds something the reply did not mark, such as an attached file or a web result, it reads View N sources →. Session details opens at **Sources gathered**.
3. Read a row: the file, its K number, the page or Opens at the passage, and the cited sentence. Only documents the reply cited are listed.
4. Choose the row. The document opens on the cited page with the sentence marked and its passage shaded.
5. Read Cited passage at the top and compare it with the reply. Choose Show more, when it appears, for the whole passage.
6. Use Previous page and Next page, or type a number in the page box and press Enter. Use Zoom in and Zoom out to change the size.
7. Choose Go to the cited passage to return to the mark.
8. Choose **Download** original to save the file as it was uploaded.
9. Choose Close document, or press Escape, to return to the chat.

Path: From a marker in the reply

1. In the reply, choose a K marker such as K1 beside the fact you want to check.
2. The document opens at the same page and passage as its row in **Sources gathered**.
3. A W marker opens the web page it cites in a new browser tab.

Path: From the Library

1. Choose **Library** in the sidebar; **Knowledge** opens.
2. Open a knowledge base and find the file on Files.
3. Choose Preview (the eye), or the file's name.
4. The file opens at the first page with no Cited passage, because nothing was cited.

Check that it worked

- ✓ The viewer shows the page the row named, or the passage's page if the row named none, with the cited sentence marked.
- ✓ Cited passage matches the marked sentence and supports what the reply said.
- ✓ Go to the cited passage returns to the mark after you move away.
- ✓ The downloaded file is the document that was uploaded.

Troubleshooting

WHAT YOU SEE	WHAT TO DO
No View citations button under a reply	The reply wrote no marker, so nothing is listed. Check that the knowledge base is chosen, ask again and add "cite the source after each sentence", and treat an unsourced answer as unchecked.
A document you expected is not in Sources gathered	Only documents the reply wrote a marker for are listed, even if the trace found passages in others. Ask about that document by name.
A source is listed, but its passage has nothing to do with the answer	Listed means the reply wrote the marker, not that the passage supports it. A reply can name passages only to say they did not help. Open the source and read it. That is what this lesson is for.
"The original file is not available, so this shows the text that was indexed."	The document was uploaded before originals were kept. Ask whoever manages the knowledge base to upload it again and remove the old copy, because an upload adds a new document. A connected source gets its originals at the next sync.
"This server cannot show this file type with its original layout, so this shows the text that was indexed."	The server has no converter for this file type. The text and the passage are still shown. **Download** the original to see its layout.
"The original layout could not be prepared, so this shows the text that was indexed."	The conversion failed for this file. **Download** the original to read it.
"These words could not be marked on this page, so they are shown here."	The page's text differs from what was indexed, as a scan can. Read Cited passage, then find the words on the page.
"The cited sentence could not be picked out on this page, so the whole passage is shaded."	Read the shaded passage for the sentence.
"This is the best match for the passage, not an exact location."	The page is the closest match. Check the pages around it.
"This passage has moved or was removed, so this opens at the page it was cited from."	The document changed after the reply was written. Check that the reply still holds, and ask again.
"This document is no longer available"	It was removed, or you no longer have access to it. Ask the knowledge base's owner.

WHAT YOU SEE	WHAT TO DO
"This PDF is protected by a password"	It cannot be shown here. Choose **Download** original and open it with its password.
"Download failed. Try again."	Choose **Download** original again. If it keeps failing, check your connection.

18. Personal data in your chats

Locked chips for concealed values, what the model receives, and how rated answers are kept.

Your organization can conceal personal data in chats. When it does, the line under the message box ends with Personal data is concealed. As soon as you send a message, values such as Social Security, card, and account numbers, email addresses, phone numbers, health identifiers, and passwords or keys are replaced with a locked chip such as SSN or Email. The original value is not saved anywhere in the workspace, so it cannot be recovered from the chat later.

YOU SEE	WHAT IT MEANS
A locked chip in your message, such as SSN	The value was concealed before the chat was saved. Reopening the chat shows the chip, not the value.
[SSN] or [EMAIL] in a reply	Your organization keeps values from the model, so the model received a placeholder. Add the real value yourself in the system where it belongs, not in the chat.
A locked chip in a reply	Your organization lets the model read values for work that needs them. A value the model writes is concealed before you see it.
A note in the rating box about a de-identified copy	Your organization captures training examples from rated answers and notes. The copy is de-identified and never sent to a model provider.

GOOD TO KNOW

Concealment recognizes values by their format and check digits. It does not recognize names or free-text descriptions of someone's health, and it does not alter drafts or uploaded files. Follow your organization's policy for those.

WALKTHROUGH · 1:14 · HELP › LEARN

Personal data in your chats

Recognize the personal data your organization conceals, know what the model received, and see how rated answers are kept when your organization captures training examples.

Before you begin

- Your administrator has turned on **Personal Data Protection**. If not, none of this appears and chats are stored as typed.
- An available model.

Step by step

1. Look under the message box. When your organization protects personal data, the line ends with Personal data is concealed. Point at it for a short explanation.
2. Send your message as usual. Social Security, card, and account numbers, contact details, health identifiers, and secrets become locked chips, such as SSN or Email, as soon as the message is sent.
3. Read the reply. When your organization keeps values from the model, the model received placeholders only, so its reply shows locked chips, such as SSN, where a value belongs.
4. Add the real values yourself in the system where they belong, not in the chat.
5. When you rate a reply with the thumbs buttons, read the note box. If your organization captures training examples, it says so: a de-identified copy of rated answers and notes is kept and never sent to a model provider.

Path: Values kept from the model (shown)

1. Your sent message shows locked chips.
2. The model received placeholders instead of the values, so its reply shows locked chips in their place, such as SSN or Email.
3. The work trace records it: Concealed personal data in your message.

Path: Model allowed to read values (shown)

1. Your sent message still shows locked chips.
2. The model read the values for that turn, so it can use them, for example in a signature block.
3. Any value it writes is replaced with a locked chip before you see the reply and before the chat is saved.
4. The work trace may still say the model saw placeholders. In this mode that line is wrong.

Path: Rating answers when training capture is on (shown)

1. Choose thumbs up or thumbs down under a reply. The note box says your organization keeps a de-identified copy of rated answers and notes, and that it is never sent to a model provider.
2. Type a note and choose Send note, or close the box with ×. The rating counts either way.

3. Corrections you type in the chat, such as "That's wrong, the deadline is 60 days. Please revise.", can be kept the same way.

Check that it worked

- ✓ The line under the message box ends with Personal data is concealed.
- ✓ Your sent message shows a locked chip where you typed the value.
- ✓ Reopening the chat later still shows the chip, not the value.

Troubleshooting


WHAT YOU SEE	WHAT TO DO
Your message shows the value for a moment after you send it	The concealed copy replaces it within a moment. The original value is not saved.
The reply shows a locked chip where you expected a value	The model never received the value. Fill it in yourself where it belongs; do not paste it back into the chat.
A name or a description of someone's health was not concealed	Concealment recognizes numbers, codes, and contact details by their format. It does not recognize names or free text about health, so leave them out when your policy requires it.
A draft still contains a value	**Drafts** are documents of record and are not altered. Keep personal data out of drafts unless your policy allows it.
You need the original value from an earlier chat	It was never saved, so the chat cannot give it back. Use the system of record it came from.

PART 3

Drafts, decks, and agents

19. Drafting documents

Generate, edit, version, and export documents with the drafting assistant.



Drafts combines the document editor with a separate assistant and document controls. Example workspace with synthetic data.

Click **Drafts** in the sidebar. The view pairs a full document editor with an AI assistant rail on the left that writes into the editor for you. The rail at the top of the editor has three formats: **Document**, **Deck**, and Spreadsheet. This section covers documents; "Building a slide deck" and "Build a spreadsheet" cover the others.

> **GOOD TO KNOW**
>
> If the model selector says No models connected, AI drafting, AI rename, inline AI edits, and AI deck prompts are unavailable. You can still edit manually, import, save, use document history, and export. Follow the setup guidance for your role or ask your administrator for access to a working model.

Generating a draft

- Look at the Sources, **Web**, and Templates chips at the top of the assistant rail first: they show which context is on before you generate anything.

- In the assistant's message box, describe the document you need: a memo, an engagement letter, a summary. Be specific about audience and tone if it matters. The suggested requests under the heading fill the box for you.
- The assistant writes the document directly into the editor. You can also send any chat response here with **Transfer to Drafts**, or, when you ask for a document in chat, choose Write in **Drafts** on the card that appears (see "Hand a chat request to **Drafts**").
- Use the model selector in the toolbar area to choose which approved model writes and edits this draft.

Opening a file from this device

Click the paperclip in the assistant's message box. Under From this device are two choices. Attach to chat gives files to the assistant to read with your next request; they become sources, not the document. Open in editor opens one file as the document itself, so you can edit it directly or select text and use **Ask AI**.

- Open in editor accepts Word (.docx, .dotx, .doc), PDF (.pdf), **Markdown** (.md), plain text (.txt), and web page (.html) files. Word and PDF files keep their page setup, headers, footers, page numbers, tab stops, and tables; web pages keep their formatting; **Markdown** keeps its headings, lists, and emphasis. When something could not be carried over, an import note in the assistant rail says what. "Open a Word or PDF file and keep its formatting" walks through it.
- The file opens as a new draft and is saved to your account as one. The draft you had open stays in **Document history**; if it has unsaved changes, the unsaved-changes dialog asks first.
- Open in editor is unavailable while the assistant is still working on a request. In deck mode the same choice opens a PowerPoint file; see "Building a slide deck".

Editing like a document

The main toolbar keeps undo and redo, block style, bold, italic, underline, and inline AI editing close at hand. **Text** opens font, size, advanced styles, color, highlighting, and **Clear formatting**. **Paragraph** opens alignment, lists, and quotes. **More** opens **Copy document** and the **AI edit trail**. Select the intended text before opening a panel; Escape returns to the editor.

- The plus (+) **Insert** button opens links and citations alongside **Web image**, **Chart**, **Table**, **Divider**, and **Page break**. A manual page break starts a new page at your cursor; the editor also paginates longer documents automatically.
- Selecting text shows a floating toolbar beside it with **Ask AI**, block style, bold, italic, underline, strikethrough, link, and highlight.
- Type / at the start of a line for the command menu: AI actions such as **Continue writing** and **Summarize the document**, headings, lists, quotes, a table, a divider, a page break, a web image, or today's date. Keep typing to filter and press Enter to insert.
- Typing shortcuts format as you go: start a line with "#", "##", or "###" and a space for a title, heading, or subheading; "-" or "1." for a list; or ">" for a quote. Type "---" and press Enter for a divider, and wrap words in "**", "*", or "`" for bold, italic, or code.

- Click inside a table to insert or delete rows and columns, turn the header row on or off, or delete the table. Click a picture to set its size (Small, Half, Large, or Full width), alignment, and alt text, or to delete it.
- Pasting from Word, Google Docs, or a web page keeps headings, lists, tables, links, pictures, and emphasis but drops the source's fonts, sizes, and colors so the text matches your document. Ctrl+Shift+V (⌘⇧V on a Mac) pastes plain text.

Editing with AI

- Select a passage and choose **Ask AI** in the floating toolbar, or press Ctrl+J (⌘J on a Mac). With nothing selected, the same command writes new text at the cursor.
- Pick an action — **Improve writing**, **Fix spelling & grammar**, **Make shorter**, **Make longer**, **Simplify language**, **Turn into a bulleted list**, **Turn into a table**, Summarize, or **Use active voice** — or a tone or language, or type your own instruction.
- Review the suggestion. **Changes** marks what was added and removed; **Result** shows the finished text. Nothing in the document changes yet.
- Choose **Replace**, **Insert below**, **Try again**, or **Discard**. To adjust the suggestion instead, type a follow-up such as “shorter” or “add a number” in the box underneath.
- When the instruction asks only for different words (fill the blanks, fix the wording, translate), the suggestion is written into the original text and the review says Original formatting kept: fonts, underlines, tab stops, and blank lines stay as they were. You do not need to add “keep the formatting”. Requests to restyle or restructure replace the passage instead.

An accepted AI edit stays highlighted briefly and is recorded with the document; **More → AI edit trail** highlights the recorded edits again so you can review what changed.

Revise the document you already have

Describe the change in the assistant: shorten a section, change tone, apply a template, or transform the existing paper. Revision requests work from the current document. Ask explicitly to start over, replace, or clear it when that is your intention. The editor keeps instructions separate from the deliverable; review the resulting document and use Undo or a saved version when a change needs correction.

Ask for page layout in plain words, such as “Times New Roman 12, double spaced, 1-inch margins”, and the editor applies it to the page setup directly, with no model call. The rail says Applied … Nothing was rewritten., and the change is one step you can undo. “Templates and page layout” covers templates and layout requests together.

For an existing paper, **Assistant settings → Apply MLA layout** applies double-spaced 12-point Times New Roman, a student heading, centered title, body and reference indents, and a separate Works Cited page without asking a model. It preserves the paper's text and supports Undo. Fill missing student details and verify quotations and sources yourself; formatting is not citation verification.

The page navigator shows the current sheet and total pages outside the document text. Older drafts are paginated when opened, and manual edits reflow after you leave the editor. Page labels do not become part of the exported body.

Status bar, outline, find, and zoom

- The status bar under the page shows the current page, word and character counts, and reading time. When text is selected, it counts the selected words too.
- **Outline** lists the document's headings; select one to jump to that section.
- Find (Ctrl+F, or ⌘F on a Mac) searches the document, with **Match case** and whole-word options. **Find and replace** (Ctrl+H, or ⌘⇧H on a Mac) replaces one match at a time or all of them.
- The keyboard button lists every editor shortcut (Ctrl+/, or ⌘/ on a Mac). The zoom controls resize the page on screen from 50% to 200% without changing the document or its exports.

Versions and comparing

- Click **Save version** whenever the draft reaches a good state. Versions of this draft lists the versions made since you opened it. Leave **Drafts**, reload the page, or reopen the draft, and the list clears: the draft starts again at Version 1, with your latest saved work. Returning to a version changes only what is on screen. To keep it, export it now, or change something and choose **Save version**.
- **Compare versions** opens a read-only visual redline of two saved versions, so you can see exactly what changed between them. It needs two genuinely different saved versions before it activates.
- Open **Document history** to browse saved documents, decks, and spreadsheets. Hover or keyboard-focus an entry for a preview. **Archive** moves finished work into **Archived**, where **Unarchive** restores it; **Delete** requires confirmation and permanently removes the saved item and revisions.
- Read the save status: account-backed documents, decks, and spreadsheets can be reopened after sign-in on another device. A pending or failed save stays a working copy in this browser. If the status reads Local only, choose Retry beside it; if it reads **Draft** changed elsewhere, choose Reload server copy and review the account version before saving again.

Leaving with unsaved changes

When you leave an edited draft through workspace navigation, open another chat or draft, or choose **Sign out**, the unsaved-changes dialog lets you Keep editing, Save copy and continue, or **Discard** and continue. The saved copy goes into local document history in this browser. If browser storage fails, the app keeps you in the draft so you can recover it. A forced security sign-out can still interrupt work; save important changes regularly.

Exporting

- Click **Export** to open the export panel. In document mode it offers a **Word document** (an editable Word file with preview page breaks and embedded images), **Markdown** (best for plain text or web publishing), PDF document (an archival PDF/A file built on the server, with searchable text, embedded fonts, and bookmarks from your headings), and Print, which opens your browser's print dialog with the saved version.
- Choose PDF document when the file will be filed, sent, or kept. Long documents show progress and can be canceled.

- Exports always run from a saved version. If you have unsaved edits, the panel says **Save your edits first** and offers a one-click **Save version and export** (or **Save version and print**) button.
- When your browser supports it, choose **Choose a location** to select a destination, or **Browser downloads** to use its download folder. If the chosen location cannot be written, the file is sent to your browser downloads instead and the status says so. Word and print retain document formatting; **Markdown** preserves the text without its typography. Exporting a file does not by itself upload pending work to your account.

GOOD TO KNOW

If a provider's content filter withholds the model's reply, **Drafts** changes nothing and says which service withheld it, starting with No local draft was substituted. or No revision was applied. Choose a different model or try again.

TIP

On a narrow window, the assistant rail becomes a slide-out drawer so the editor gets the full screen. Open it with the pen tab on the left edge or Ctrl+. (⌘. on a Mac); resting the mouse on that edge previews it. Press Escape or click the dimmed area to close it.

WALKTHROUGH · 6:13 · HELP › LEARN

Draft documents

Start a document from a blank page, a chat request or reply, or a file; have the assistant write it; edit with AI; save a version; and export it.

Before you begin

- An available model for AI writing and editing. Without one, you can still type, open files, save, and export.
- To open a file in the editor: a Word (.docx or .doc), PDF (.pdf), **Markdown** (.md), text (.txt), or web page (.html) file.

Step by step

1. Choose **Drafts** in the sidebar. A blank document opens, with the **Document** Assistant on the left and the format rail at the top: **Document**, **Deck**, and Spreadsheet.
2. Keep **Document** selected.
3. In Ask the document assistant, describe the document you need, or choose a suggestion. Choose Apply instruction (the arrow).
4. Wait while the assistant writes on the page. The work trace under your request shows each step as it is reached, and Ready to write returns when it is done.
5. Type your title in the title field beside the format rail. The assistant's first draft replaces any title you typed, so do this after it finishes.

6. Select a passage, choose **Ask AI** in the floating toolbar (or press Ctrl+J, ⌘J on a Mac), and choose an action such as **Improve writing**.
7. Review the **Changes** or **Result** view. Original formatting kept means only the words change. Choose **Replace**; **Insert below**, **Try again**, and **Discard** are the alternatives.
8. Choose **Save version** (it reads Save in a narrower window) and wait for Saved at the end of the toolbar.
9. Choose **Export**, set Save to to **Browser downloads**, and choose **Word document**. The receipt names the downloaded file.

Path: From a chat request

1. In chat, ask for a document. When chat asks Write this in **Drafts**?, choose Write in **Drafts**.
2. **Drafts** writes it from your request and saves it. See Hand a chat request to **Drafts**.

Path: From a chat reply

1. Under a finished chat reply, choose **Transfer to Drafts**.
2. Open in **Drafts** as offers **Word document**, Slide deck, and Spreadsheet, with the best fit marked Suggested. Choose **Word document**.
3. **Drafts** opens a new document with the reply, saved as Version 1.
4. Continue from step 6 of the main steps.

Path: Open a file from this device

1. Choose Attach file (the paperclip) in the assistant's message box.
2. Under From this device, choose Open in editor, and pick a .docx, .pdf, .doc, .md, .txt, or .html file.
3. Word and PDF files keep their page setup, headers, footers, tab stops, and tables; **Markdown** keeps its headings and lists. The draft you had open stays in **Document history**.
4. Attach to chat instead gives the file to the assistant to read with your next request. See Open a Word or PDF file and keep its formatting.

Path: Write it yourself

1. Click on the page and type. **Markdown** shortcuts work: # and a space starts a title, - and a space starts a list.
2. Type / at the start of a line for the command menu: headings, lists, tables, page breaks, and AI actions.
3. Use **Text**, **Paragraph**, **More**, and **Insert** above the page for formatting. Templates and page layout have their own lesson.

Path: Export formats

1. **Word document**: an editable .docx with page breaks and images.
2. PDF document: an archival PDF/A file built on the server, with searchable text, embedded fonts, and bookmarks from your headings. Long documents show progress, and the X beside it cancels.
3. **Markdown**: a .md file for plain text or web publishing.
4. Print: opens the browser's print dialog with the saved version, for paper. Use PDF document when you need a file to keep or send.
5. Save to: **Browser downloads** saves straight to your downloads; **Choose a location** asks the browser where to save. If that location cannot be written, the file goes to your downloads and the receipt says so.

Check that it worked

- ✓ The toolbar shows Saved after **Save version**, and the version label at the top shows the new number.
- ✓ The export receipt names the file, for example synthetic-vendor-onboarding-checklist.docx, and offers **Download** again. A PDF receipt also lists its pages, PDF/A-2b archival, and any bookmarks.
- ✓ An opened file shows a note in the assistant rail: the file opened in the editor.

Troubleshooting

WHAT YOU SEE	WHAT TO DO
"AI drafting is unavailable." or Model: No models connected	No model is available to you. You can still type, open files, save, and export. Ask your administrator for model access.
"No local draft was substituted. …'s content filter withheld the model's reply (… sent the request to …). Choose a different model or try again."	The model provider's safety filter blocked the reply, so nothing was written to your page. Choose a different model in the model menu, or rephrase and try again. During an edit the message starts with "No revision was applied."
The document title changed to a template name, such as Board Update Draft	The assistant's first draft sets its own title, even if you typed one first. Type your title into the title field after it finishes, then save.
"Could not open … Choose a .docx, .pdf, .doc, .md, .txt, or .html file."	Save the file in one of those formats and open it again.
"Wait for the assistant to finish before opening another document."	Let the current request finish, then open the file.
Export says "Save your edits first"	Choose **Save version and export** (or **Save version and print**). Exports use the saved version.
Local only at the end of the toolbar	Your changes are kept in this browser. Choose Retry beside it, or export a copy before you leave.
"… could not be written to the chosen location, so it was sent to your browser downloads instead."	The browser could not save to the place you chose. Find the file in your downloads, or set Save to to **Browser downloads**.
The export stops and no receipt appears	**Try again**, or choose **Browser downloads** in Save to. For PDF document, the server may be busy or you may already have 2 PDF exports running, so wait a minute and try again.

20. Hand a chat request to Drafts

Send a document, deck, or spreadsheet request from chat straight into the editor.

When a chat message asks for a document (a memo, a letter, a report), a slide deck, or a spreadsheet, the message waits above the composer with a card. Write this in **Drafts**? offers Write in **Drafts** or Continue in chat; for slides, Build this as a slide deck? offers Build in deck editor or **Draft** slides in chat; spreadsheets, trackers, and budgets get the same choice. Nothing is sent until you choose.

- Write in **Drafts** (or Build in deck editor) opens **Drafts** and starts the document or deck from your request, with no retyping. The rail says Writing the document you asked for in chat. The chat's model (unless you starred a drafting default), its **Web** and knowledge choices, your attached files, and earlier messages in the conversation travel with the request; the card notes when your files and this conversation come along.
- Continue in chat (or **Draft** slides in chat) sends the message to the chat as usual.
- Edit request puts the message back in the composer so you can change it. While the card is waiting, Send is disabled: Choose **Drafts** or chat for the request above first.
- The card is not offered in **Agent** mode, with selected tools, for fetched links, or for queued automations, and outlines, summaries, emails, poems, code, and questions about writing stay in chat. **Transfer to Drafts** under any reply still sends a finished answer to the editor.

WALKTHROUGH · 2:33 · HELP › LEARN

Hand a chat request to Drafts

Ask chat for a document, a slide deck, or a spreadsheet, then have Drafts build it as an editable, saved draft, or keep it in chat, or change the request first.

Before you begin

- An available model. **Chat** only offers **Drafts** when a model is available to you.
- **Agent** mode off, with no tools or links chosen for the message. Those requests always go straight to chat.

Step by step

1. In a chat, ask for a document, for example: **Draft** a one-page memo to the operations team about the vendor review schedule.
2. Send it. **Chat** holds the request and asks Write this in **Drafts**? Send stays off until you choose.
3. Choose Write in **Drafts**.
4. **Drafts** opens and starts writing at once. The rail says Writing the document you asked for in chat, and the work trace under your request lists each step.
5. Wait for Ready to write to return and for Saved in the toolbar. The document is Version 1 in your account.
6. Read it through, then edit, save, and export it as in **Draft** documents.

Path: Ask for a slide deck

1. Ask for a presentation, for example: **Create** a slide deck about the vendor review timeline, with four slides.
2. **Chat** asks Build this as a slide deck?

3. Choose Build in deck editor. **Drafts** switches to **Deck** and the rail says Building the slide deck you asked for in chat.
4. Wait for the slides to fill the filmstrip. The assistant names the deck, so the toolbar can show Editing: choose **Save version** and wait for Saved.

Path: Ask for a spreadsheet

1. Ask for a tracker, budget, or workbook, for example: **Create** a spreadsheet to track four vendor reviews, with columns for vendor, owner, due date, and status.
2. **Chat** asks Build this as a spreadsheet?
3. Choose Build in spreadsheet editor. **Drafts** switches to Spreadsheet and the rail says Building the spreadsheet you asked for in chat.
4. Wait for Ready to build spreadsheets to return and for Saved in the toolbar. The assistant can add sheets, so open each tab at the bottom and check the cells and formulas. See Build a spreadsheet with the assistant.

Path: Keep it in chat

1. Choose Continue in chat (for a deck, **Draft** slides in chat).
2. The request is sent to this conversation and the reply arrives as usual.
3. To move a finished reply to **Drafts** later, choose **Transfer to Drafts** under it, then **Word document**, Slide deck, or Spreadsheet.

Path: Change the request first

1. Choose Edit request.
2. The request returns to the message box, with any files you attached. Change it and send it again.

Path: When the card does not appear

1. **Agent** mode, chosen tools, fetched links, and queued automations always send straight to chat.
2. Questions and short pieces usually stay in chat: emails, poems, short summaries, outlines, recaps, social posts, and code. An executive summary or a blog post counts as a document, so the card appears.
3. Adding in chat or right here to a request keeps it in chat.
4. Attached files, **Web**, and knowledge bases you chose come along to **Drafts**.

Check that it worked

- ✓ **Drafts** shows the document with Version 1 and Saved in the toolbar; a deck shows its slides in the filmstrip; a workbook shows its cells in the grid.

- ✓ The rail in **Drafts** records your request, and its work trace ends with Worked for and the time it took.
- ✓ Continue in chat puts the request and its reply in the conversation instead.

Troubleshooting

WHAT YOU SEE	WHAT TO DO
Send is off, and its tooltip says "Choose Drafts or chat for the request above first"	**Chat** is holding your request. Choose the **Drafts** button on the card, Continue in chat, or Edit request.
"Could not upload the attachment." on the card	A file you attached could not be uploaded. **Try again**, or choose Edit request and attach it again.
No card appears and the reply arrives in chat	The request read as a question or a short piece, or **Agent** mode, a tool, or a link was on. **Open Drafts** and ask there, or use **Transfer to Drafts** under the reply.
The new document has a template's name, such as Investment Memo Draft	The assistant renamed it after a template it matched. Type your own title into the title field, then save.
"No drafting model connected" in Drafts	**Drafts** has no model to write with. Your request waits in the assistant's message box; ask your administrator for model access.
"No local draft was substituted. …", "Deck request failed: …", or "The spreadsheet request failed: …"	The model could not finish. Choose Apply instruction to try again, or pick another model in the model menu.
"The model's reply was not valid spreadsheet changes twice, so nothing was applied. Try rephrasing the request."	Smaller models can struggle with large workbooks. Ask for fewer columns or rows, or choose a stronger model, and send it again.
"The model's structured output failed validation twice, so the deck was built from its outline instead."	Smaller models can return slides in the wrong format. See Build a slide deck for the sentence to add to your request, or choose a stronger model.

21. Open a Word or PDF file and keep its formatting

Edit an existing Word or PDF document in Drafts without losing its layout.

Open in editor turns a file from your device into the document itself. Word files (.docx, .dotx, .doc) and PDF files keep their page size and margins, headers and footers, page numbers, tab stops, and tables, so a contract or form looks the way it did. Edits and AI suggestions then work on that layout.

- Click the paperclip in the assistant's message box, choose Open in editor under From this device, and pick the file. It opens as a new draft and is saved to your account.

- Select a passage and choose **Ask AI**. When you ask only for different words, the review says Original formatting kept and the result keeps the original fonts, underlines, and tab stops.
- **Save version**, then **Export → Word document** to take it back to Word. The import note in the assistant rail lists anything that could not be carried over.
- To reuse a Word file's look for new drafts instead, open Templates in the assistant rail and choose Upload Word template.

WALKTHROUGH · 2:18 · HELP › LEARN

Open a Word or PDF file and keep its formatting

Open a Word or PDF file in Drafts with its page setup, headers, footers, tab stops, and tables intact, fill it in with Ask AI without losing the formatting, and export it back to Word.

Before you begin

- A Word (.docx, .dotx, or .doc) or PDF file on this device. A .docx keeps the most; a .doc opens from its readable text.
- An available model for **Ask AI**. Opening, editing, saving, and exporting work without one.
- PDFs must not be password-protected.

Step by step

1. Choose **Drafts** in the sidebar.
2. Choose Attach file (the paperclip) in the assistant's message box. Under From this device, choose Open in editor.
3. Pick the .docx file. It opens as a new draft with its page size, margins, fonts, header, footer with page numbers, tab stops, and tables. The rail says it opened in the editor.
4. Select the passage to change, then choose **Ask AI** in the floating toolbar.
5. Type the change and include the real values, for example Fill in the blanks: 1 November 2026, Northwind Example Supplies, and 100 Example Way, Springfield, and press Enter.
6. Review the suggestion. Original formatting kept means only the words change: bold text, fonts, and styles stay as they were. Choose **Replace**.
7. Choose **Save version** and wait for Saved.
8. Choose **Export**, set Save to to **Browser downloads**, and choose **Word document**. The receipt names the file.
9. Open the downloaded file in Word: the header, footer, page numbers, tab stops, and table are still there.

Path: Open a PDF

1. Choose Attach file › Open in editor and pick the .pdf file.

2. It is rebuilt as editable paragraphs with its page size, margins, fonts, and running header and footer. Page numbers become live fields.
3. Edit, save, and export it like any draft. **Word document** export gives you an editable .docx.

Path: Reuse a Word file as a template

1. Choose Templates in the assistant rail.
2. Choose Upload Word template (the upload button at the bottom of Templates) and pick the file.
3. On a blank page it places the template. On a page with text, it applies the template's page, header, footer, and styles without removing any words.
4. The template is listed under Uploaded in Templates, stored in this browser.

Path: Other files and Attach to chat

1. **Markdown** (.md), text (.txt), and web page (.html) files open the same way; **Markdown** keeps its headings and lists.
2. Attach to chat, instead of Open in editor, gives the file to the assistant to read with your next request.

Check that it worked

- ✓ The page shows the file's header and footer, with live page numbers such as Page 1 of 1.
- ✓ The review showed Original formatting kept, and the filled passage keeps its bold text.
- ✓ The toolbar shows Saved, and the export receipt names the .docx file.

Troubleshooting

WHAT YOU SEE	WHAT TO DO
"Could not open … Choose a .docx, .pdf, .doc, .md, .txt, or .html file."	Save the file in one of those formats and open it again.
"This PDF is password-protected. Remove the password and try again." or "The PDF could not be read."	Remove the password, or save a fresh PDF from the app that made it, then open it again.
Text from a PDF opens bolder than it was	Some PDF fonts (for example Georgia or Times New Roman in a PDF printed from a browser) can open as bold or semibold. Select the text and set its weight back, or open the original Word file instead when you have it.
"The Word file's full formatting could not be read, so it opened with simplified formatting."	Open the file in Word, save it again as .docx, and open the new copy.
"Legacy .doc files are imported from readable text or Word-saved HTML. Use .docx for higher fidelity."	Save the file as .docx in Word, then open it again to keep its formatting.
The review does not say Original formatting kept	The change restyled or restructured the passage (into a list or table, for example), so the reply replaces it as written. Check it, or choose **Discard** and ask for a smaller change.
"Wait for the assistant to finish before opening another document."	Let the current request finish, then open the file.

22. Templates and page layout

Start from a template, restyle a draft, and set the page layout in plain words.

Templates in the assistant rail lists document templates by category: Client Update, Approval Email, Legal Contract, Mutual NDA, Contract Amendment, Investment Memo, Board Update, Project Brief, Research Paper, Screenplay, and Implementation Plan. On an empty draft a template starts the document; on a draft with text it sets the draft in that template's layout without changing its words.

- **Use templates in chat** (off by default) lets the selected template shape what the assistant writes for new drafts.
- Upload Word template uses your own .docx or .dotx file as the layout.

- Type a layout request in the assistant, such as “Times New Roman 12, double spaced, 1–inch margins”. It is applied directly with no model call: Applied … Nothing was rewritten. Undo reverses it in one step.
- **Assistant settings** → **Apply MLA layout** formats a student paper; see “Drafting documents”.

WALKTHROUGH · 2:06 · HELP › LEARN

Start from a template and set the page layout

Start a document from a built-in template, have the assistant draft it from your request, and set line spacing, margins, and other page layout in plain words or with the MLA layout.

Before you begin

- An available model to draft from a template. Placing a template and changing the layout work without one.

Step by step

1. Choose **Drafts** in the sidebar. In the assistant rail, choose Templates.
2. Choose a category, such as Legal, then a template, such as Mutual NDA. On a blank page it places the template, with bracketed fields to fill in.
3. In Ask the document assistant, describe what to fill in: the parties, the date, and the purpose.
4. Choose **Create** Mutual NDA draft at the bottom of Templates. The assistant drafts the document from the template and your request.
5. Wait for Ready to write and Saved in the toolbar, then read the draft through.
6. In Ask the document assistant, type the layout you want in plain words, for example Use 1.5 line spacing and 1.25–inch margins, and press Enter.
7. The rail says the layout was applied directly in the editor and no model call was needed. No words were rewritten, and the change is already saved as a new version.

Path: Fill in the brackets yourself

1. After placing a template, type over each bracketed field, such as [Party A Legal Name].
2. Save a version when you are done.

Path: Apply a template to text you already have

1. Open the draft, choose Templates, and choose a template, such as Contract Amendment.
2. Its page setup, header, footer, and styles are applied. Your text is unchanged.
3. To reorganize the text into the template's sections, ask the assistant.

Path: Layout you can ask for

1. Line spacing: single, 1.5, or double.
2. Margins for every side or one side, in inches, centimeters, millimeters, or points.
3. Font and size, paper size (Letter, Legal, or A4), and landscape or portrait.
4. Justified or left-aligned text, first-line indents, paragraph gaps, page numbers, and header or footer text.
5. A named format: contract, letter, memo, report, academic, or screenplay.

Path: MLA layout

1. Choose **Assistant settings** (the sliders key beside the paperclip in the message box).
2. Choose **Apply MLA layout**: double spacing, 12-point Times New Roman, and a centered title. Your text is kept.
3. Undo reverses it. Save a version to keep it.

Path: Use templates in chat

1. Choosing a template turns on **Use templates in chat**. Turn it off in Templates when you want a free-form draft.
2. The selected template then shapes the new drafts you ask the assistant for.

Check that it worked

- ✓ The page shows the drafted agreement with the parties and date from your request.
- ✓ The rail records your layout request and that no model call was needed, and the page shows the new spacing and margins.
- ✓ The toolbar shows Saved, and the version label shows the new number.

Troubleshooting

WHAT YOU SEE	WHAT TO DO
A layout request was rewritten by the model instead of applied	The request mixed layout with other changes. Ask for the layout on its own, in plain words such as 1.5 line spacing and 1-inch margins.
A layout request changes nothing on a paper in MLA layout	MLA papers keep their layout (screen readers hear "This paper is set in MLA layout (12-point Times New Roman, double spaced); its layout is not changed here."). Undo the MLA layout first if you need a different one.
Create … draft is off	No model is available to you. Place the template and fill in the brackets yourself, or ask your administrator for model access.
The document title changed to the template's name	Type your own title into the title field, then save.

23. Building a slide deck

Turn a draft into slides, edit them, brand them, and export real PowerPoint.

Deck mode turns the **Drafts** workspace into a slide editor with a real PowerPoint export. Choose **Deck** on the format rail. If the draft already has document content, a dialog asks “Turn this draft into slides?” — choose **Start a blank deck** to keep the document untouched, or **Convert into slides** to split its headings and text into slides. Your document versions are kept either way.

The filmstrip

- Slide thumbnails run along the side. Click one to select it, or drag it to reorder the deck.
- Hover a thumbnail for its actions: move up, move down, duplicate, and delete (undo restores a deleted slide).
- **Add slide** at the end of the filmstrip opens the Add a slide panel on the left, where you pick the new slide's layout.
- **Slide sorter**, at the right of the deck toolbar, lays every slide out in a grid. Drag to reorder, double-click a slide to edit it, and use each slide's duplicate and delete buttons.

Slide layouts

Above the slide, **Layouts** previews the arrangements, including **Title**, **Title + bullets**, **Two columns**, **Image + caption**, Picture + bullets, Statement, Big number, **Section**, **Quote**, and **Closing**. Select one to switch the selected slide. The layout chip in the slide's corner opens the Change layout panel on the left, with the same layouts grouped as Openers, Content, Pictures, and Highlights. **Themes** offers seven designs — Aperture, Signal, Violet, Editorial, Midnight, Forest, and Swiss. Each has its own colors, fonts, and slide shape; a

change restyles every slide, keeps text, media, and layout, and can be undone. The chevron beside **Layouts** folds the strip away to give the slide more room.

Editing slide text

- Click any text region on a slide to edit it in place. A floating text toolbar appears beside the box: **Ask AI**, font size, Bold, Italic, Underline, Strikethrough, **Text** color with the deck's **Theme colors**, list level, and **Clear formatting**. With nothing highlighted it formats the whole box; highlight words to format only those. The deck toolbar above keeps undo and redo, **Text**, and **More** (copy the deck outline, keyboard shortcuts).
- When text no longer fits its box, the toolbar says **Text** overflows this box · shorten it, size it down, or drag a corner. Until you do, the slide shrinks the text to fit (Shrunk to fit, as PowerPoint does), and the PowerPoint export uses the same shrink.
- Drag a text box by its frame to move it. Guides snap it to the slide's edges and center and to other boxes; arrow keys nudge the selected box (Shift moves ten times as far).
- Inside bullet lists, press Tab to indent a bullet one level and Shift+Tab to outdent it.

Editing slides with AI

- **Edit slide with AI** (the AI pen in the deck toolbar, or Ctrl+J / ⌘J) opens the **Edit slide with AI** panel on the left and reworks the whole slide: **Improve this slide**, **Make it punchier**, **Cut the text in half**, **Write speaker notes**, **Pick a better layout**, **Split into two slides**, **Fix spelling & grammar**, a tone or language, or your own instruction.
- The review in the panel shows the slide before and after, plus any new speaker notes. Choose **Apply to slide**, **Try again**, or **Discard**; undo restores the previous slide.
- When the deck assistant builds or revises slides, it runs a fit check before you review them. Checking slide fit appears while it measures; Fit check: every slide's text fits its boxes. means nothing needed changing, otherwise it rewrites the text that was too large and says which slides it changed.
- To rewrite only part of a slide, highlight the text and choose **Ask AI**, then review the suggestion before replacing it.

Opening a PowerPoint file

- In deck mode, click the paperclip in the assistant's message box and choose Open in editor (Edit slides directly) to open a .pptx file as the deck itself.
- Each slide keeps its title, subtitle, bullets with their indent levels, two-column text, speaker notes, one picture, and its layout artwork as the background. **Text** with no place in the chosen layout moves into that slide's speaker notes instead of disappearing.
- If the presentation is larger than the deck limit, pictures are left out first and then layout artwork, and the assistant rail says so. The opened deck is a new deck; the deck you had open stays in **Document history**.

Starter templates and your brand template

- **Deck starters & brand themes**, above the slide (or the Templates chip in the assistant rail), opens the templates panel with five starter structures: **Pitch deck**, **Quarterly review**, **Project kickoff**, **Client proposal**, and **Training session**. Pick one and start it to get scaffold slides you replace.
- A **Use templates in chat** toggle (off by default) lets the selected template guide the deck assistant when it drafts for you.
- **Upload brand template** accepts your firm's own file — ".pptx or .potx — brand colors, fonts, logo, and every slide's text are extracted." The extracted theme is stored only on this device.
- **Once** a brand theme is loaded, **Apply to deck** restyles the current deck with its colors, fonts, and logo, and a "Load all N slides" button can replace the deck with every slide from the uploaded template.

Slide pictures

- Slide pictures in the deck toolbar opens the Slide picture panel on the left. Upload from this device adds a **PNG**, JPEG, WebP, or GIF; or type a description under Or describe the picture and choose Find web images (needs web search) or **Generate** AI picture (needs an image-generation model for your workspace).
- Alt text describes the picture for screen readers and is kept in the PowerPoint export. If the slide's layout has no place for a picture, the panel offers layouts that do.

Backgrounds and AI images

- The background button in the toolbar opens a per-slide menu: **Upload background…** (a **PNG**, JPEG, or WebP from this device), **Use on every slide**, **Remove from this slide**, and **Clear from all slides**.
- **Generate AI slide image** writes an image prompt for you, prefilled from the slide's content; press **Generate image** and the result becomes that slide's background. This needs an image-generation model enabled for your workspace — the button says so honestly when none is.
- In the assistant rail, **Toggle AI slide images** makes the assistant also generate an image for every slide whenever it drafts a deck.

Speaker notes

Every slide has a **Speaker notes** field below the stage. **Notes** export with the deck: they land in each slide's notes pane in the PowerPoint file, they appear in the **Markdown outline**, and they follow you into presentation mode.

Presenting from Aperture

- Click **Present deck** in the deck toolbar (the monitor icon), or press F5 (⌘Enter on a Mac); add Shift to start from the current slide. The deck opens full screen.
- Advance by clicking the slide or with the arrow keys or Space; move back with the left arrow. Type a slide number and press Enter to jump to it.

- The **Notes** button (or N) shows your speaker notes under the slide. **Presenter view** (or P) shows the current slide, the next slide, a timer you can pause or reset, and your notes side by side.
- Press B or W to black or white out the screen; press it again to return. Leave with Escape or the **Exit** button in the top corner.

Saving and exporting

- **Save version** stores decks to your account with revision history, like documents. Read the status to confirm the save reached the server. A local working copy or pending save remains only in this browser until synchronization succeeds; use the **Only on this device** reminder to find unfinished saves.
- **Document history** includes decks. Preview, reopen, archive, unarchive, and confirmed deletion use the same account controls as documents. A concurrent account edit can prevent a stale save or deletion; read the conflict message before retrying.
- Click **Export** to open the **Export deck** panel: **PowerPoint deck** produces an editable .pptx that mirrors the slides on screen — speaker notes included in each slide's notes pane — and **Markdown outline** exports slide titles, bullets, and speaker notes as text.
- Limits: a deck holds up to 100 slides and 8 MB of content. The editor tells you plainly if a deck exceeds them.

WALKTHROUGH · 3:58 · HELP › LEARN

Build a slide deck

Turn a document into slides, build a deck from an outline or a starter template, give it one of seven theme designs or your own brand, present it, and export a PowerPoint file.

Before you begin

- An available model for the deck assistant. Converting a document, templates, layouts, notes, presenting, and export work without one.
- Optional: your organization's PowerPoint brand template (.pptx or .potx, up to 30 MB, no macros).

Step by step

1. Choose **Drafts** in the sidebar, then choose **Deck** in the format rail at the top (**Document**, **Deck**, Spreadsheet). A blank deck opens with the **Deck** Assistant.
2. Type a title for the deck.
3. In Ask the deck assistant, describe the deck: how many slides and what each covers. Choose Apply instruction.
4. Wait while Building slides… runs; on smaller models this can take a few minutes. The work trace under your request lists each step. The filmstrip fills, and the rail says how many slides were drafted and reports its fit check.

5. Choose **Themes** above the slide and pick a design. **Slide sorter** shows it on every slide at once; Undo goes back.
6. Review each slide. **Add slide**, the slide's layout chip, Slide pictures, and **Edit slide with AI** open panels on the left (see Edit slides: layouts, pictures, and text).
7. Add speaker notes under the slide.
8. Choose **Save version** and wait for Saved.
9. Choose **Present deck**, then press P for presenter view. Escape exits.
10. Choose **Export**, set Save to to **Browser downloads**, and choose **PowerPoint deck**. The receipt names the .pptx file.

Path: Convert a document

1. In a document with content, choose **Deck** in the format rail.
2. Turn this draft into slides? appears. Choose **Convert into slides** (or **Start a blank deck**).
3. The headings become slides. Your document versions are kept either way.

Path: Start from a template

1. In a deck, choose **Deck starters & brand themes**.
2. Choose a starter: **Pitch deck**, **Quarterly review**, **Project kickoff**, **Client proposal**, or **Training session**.
3. Choose Start and the template's name. **Replace** the scaffold text with your content.

Path: Your brand template

1. In **Deck starters & brand themes**, choose Upload under Brand theme and pick your .pptx or .potx file.
2. On a deck with slides, the brand's colors, fonts, logo, and background are applied at once; Applied — remove takes them off, and **Apply to deck** applies a stored brand again.
3. Load all N slides replaces the deck with the template's own slide designs. The brand theme is stored only on this device.

Path: Layouts and themes

1. The strip above the slide has **Layouts** (for the selected slide) and **Themes** (for every slide). Both scroll sideways.
2. **Layouts**: **Title**, **Title + bullets**, **Two columns**, Picture + bullets, **Image + caption**, Statement, Big number, **Section**, **Quote**, and **Closing**.

3. **Themes** change the whole design, and your text stays as written: Aperture (clean type with a slim accent rule), Signal (bold color blocks with white type), Violet (a solid side panel beside the words), Editorial (serif type and hairline rules), Midnight (a dark slide with bright circles), Forest (a fine border framing every slide), and Swiss (oversized type and a single red square).
4. Fold away layouts and themes hides the strip for more room; Show layouts and themes brings it back.

Path: Present

1. Choose **Present deck**. Arrow keys, Space, or a click move forward.
2. Press N to show notes, P for presenter view (timer, next slide, notes), and B to black out the screen.
3. Press Escape, or choose **Exit**, to leave.

Path: Export formats

1. **PowerPoint deck**: an editable .pptx with your slides, pictures, alt text, and speaker notes.
2. **Markdown outline**: slide titles, bullets, and notes as text.

Check that it worked

- ✓ The filmstrip lists the slides, and the rail reports how many the assistant drafted and its fit check.
- ✓ **Presenter view** shows the current slide, a timer, the next slide, and your notes.
- ✓ The export receipt names the .pptx file.

Troubleshooting

WHAT YOU SEE	WHAT TO DO
Building slides… runs for several minutes	Larger decks take longer, especially on smaller models. Ask for fewer slides, or wait; your draft stays intact meanwhile.
"The model's structured output failed validation twice, so the deck was built from its outline instead."	Smaller models can return slides in the wrong format, so the deck may have only a couple of slides, with raw text on one. Undo, then ask again and add: Each slide's layout value is just the layout's name, with its fields beside it. Or choose a stronger model.
Generate AI picture is off: "No image-generation model is enabled for your workspace"	Your workspace has no image model. Upload your own picture from Slide pictures instead.
"Could not open … Choose a PowerPoint .pptx file."	Open in editor in a deck accepts .pptx and .potx files. Save other formats as .pptx first.
"… exceeds the 30 MB brand-template upload limit." or "Macro-enabled presentations are not accepted. Save as .pptx or .potx first."	Use a smaller template, and save it without macros.
After a brand is applied, slide text is hard to read on its background	Some brand templates pair a dark background with dark text. Choose Load all N slides to start from the template's own slide designs, or recolor the text with **Text** color.
"The brand template could not be read.", or another message in the Brand theme card	Check that the file is a valid PowerPoint template and try again.

24. Editing slides: layouts, pictures, and text

Add slides, change layouts, place pictures, format text, and edit with AI in the slide panel.

The panel on the left of the deck editor handles slide-by-slide work. **Add slide** opens Add a slide, the layout chip on a slide opens Change layout, Slide pictures opens Slide picture, and **Edit slide with AI** opens the AI review. Close the panel with its X or Escape; drag its edge to resize it.

- Pick a layout from Openers, Content, Pictures, or Highlights. Changing layout keeps the slide's text; if some items have no slot in the new layout, the status says so and Undo restores them.
- Add a picture with Upload from this device, Find web images, or **Generate** AI picture, and give it Alt text.

- Select text for the floating text toolbar: size, Bold, **Text** color with **Theme colors**, list level, and **Clear formatting**. Overflowing text shrinks to fit until you shorten it or enlarge the box.
- **Save version** when the slides look right; the PowerPoint export matches what you see.

WALKTHROUGH · 4:02 · HELP › LEARN

Edit slides: layouts, pictures, and text

Add slides from the layout panel, change a slide's layout, make one point with a Statement, Big number, or Picture + bullets slide, add a picture with alt text, format slide text, fix text that no longer fits, and edit a slide with AI.

Before you begin

- A deck open in **Drafts**. Build a slide deck shows how to start one.
- An available model for **Edit slide with AI** and the deck assistant. **Layouts**, pictures, and text formatting work without one.
- A picture on this device: **PNG**, JPEG, WebP, or GIF.
- **Generate** AI picture needs an image-generation model in your workspace.

Step by step

1. In the filmstrip, select the slide the new one should follow, then choose **Add slide** under the filmstrip.
2. In Add a slide, pick a layout. Openers, Content, Pictures, and Highlights jump to each group. Statement and Big number are under Highlights; Picture + bullets is under Pictures. The slide is added after the selected one.
3. Click a text box on the new slide and type over the placeholder text.
4. To change the slide's layout, choose the layout chip at the top right of the slide (for example **Two columns**), then pick a layout in Change layout. The slide keeps its words.
5. Choose Slide pictures in the toolbar. In the Picture panel, choose Upload from this device and pick a picture.
6. Type a short description in Alt text, then choose **Done**.
7. Select words in a text box. In the floating text toolbar, change the size, choose Bold, or choose **Text** color and a theme color. **Clear formatting** returns the text to the layout's style.
8. If the toolbar says Shrunk to fit, as PowerPoint does, or **Text** overflows this box, shorten the text, size it down, or drag a corner of the box.
9. Choose **Edit slide with AI** in the toolbar and pick an action such as **Cut the text in half**. Compare Before and After in the left panel.
10. Choose **Apply to slide**. **Try again** asks for another version; **Discard** leaves the slide as it was.
11. Choose **Save version** and wait for Saved.

Path: Make one point: Statement, Big number, Picture + bullets

1. Statement (Highlights): one sentence in large type, with a supporting line below it.
2. Big number (Highlights): the figure in the title box, and what it measures in the line below.
3. Picture + bullets (Pictures): a picture beside a short list. Add the picture from Slide pictures, then type the bullets.
4. A theme restyles these slides too, so check them again after you change it.

Path: Find a picture on the web

1. In the Picture panel, type a few words in Or describe the picture, then choose Find web images.
2. Choose a result to use it on the slide.
3. If nothing comes back, the panel says No web images were found. Try other words, or upload your own picture.

Path: Generate an AI picture

1. Describe the picture in Or describe the picture, then choose **Generate** AI picture.
2. It needs an image-generation model. Without one the button is off and the panel says No image-generation model is enabled for your workspace.

Path: Edit only some of the text with AI

1. **Highlight** words in a text box, then choose **Ask AI** in the floating text toolbar.
2. The left panel opens as Edit slide text with AI and changes only the highlighted words.
3. Type what to change or pick an action, review the **Changes**, and choose **Replace**.

Path: Have the deck assistant revise every slide

1. In Ask the deck assistant, describe the change, for example Make every slide title five words or fewer, and choose Apply instruction.
2. While it works, the rail lists its steps, including Checking slide fit.
3. When it finishes, the rail reports the result and the fit check, for example Fit check: every slide's text fits its boxes.

Path: Slide background

1. Choose Slide background in the toolbar.
2. **Upload background…** puts your own image behind this slide. **Use on every slide**, **Remove from this slide**, and **Clear from all slides** manage it.

Path: More room for the slide

1. Fold away layouts and themes (the arrow beside **Layouts**) hides the strip above the slide.
2. Show layouts and themes brings it back.

Check that it worked

- ✓ The filmstrip shows the new slide with its layout name, for example Slide 3: **Image + caption**.
- ✓ The picture is on the slide, and Alt text holds its description, which is kept in the PowerPoint export.
- ✓ After **Apply to slide**, the slide shows the After version, and the toolbar shows Saved after **Save version**.
- ✓ The rail's fit check reports that every slide's text fits its boxes.

Troubleshooting

WHAT YOU SEE	WHAT TO DO
"Pictures can be PNG, JPEG, WebP, or GIF."	Save the picture in one of those formats and upload it again.
"… has no picture. Switch this slide to a layout that holds one; its words come along."	Choose Picture + bullets or **Image + caption** under **Layouts** with a picture, then add the picture.
"No web images were found for … Try other words."	Try other words, or upload your own picture. The search reaches public web pictures, so it needs internet access from your browser.
Generate AI picture is off: "No image-generation model is enabled for your workspace"	Upload your own picture, or ask your administrator for an image model.
"Text overflows this box · shorten it, size it down, or drag a corner"	Shorten the text, choose a smaller size, drag a corner of the box, or use **Edit slide with AI** and **Cut the text in half**.
Bullets after the eighth disappear when you leave the slide	A bullet box keeps up to eight bullets; extra lines are not saved. Shorten the list, or use **Edit slide with AI** and **Split into two slides**.
"… had no slot in this layout — undo restores them."	The new layout has fewer text boxes. Undo, or pick a layout with more boxes.
Edit slide with AI is off	No model is available to you. Ask your administrator for model access; layouts, pictures, and formatting still work.

25. Build a spreadsheet

Have the assistant build a workbook, check its work, and finish it with formulas, tables, charts, and files.

Choose Spreadsheet on the format rail for an Excel-style workbook beside the Spreadsheet Assistant. It can build a whole workbook from a plain request, or change one cell or one table, and it writes real formulas you can read and change. Your workbook saves to your account like any other draft.

TIP

Always check the totals. Click the numbers you care about and read the status bar, press F2 on a total to see its formula, and ask the assistant to fix anything that looks wrong. A recalculation only proves a formula has no error, not that it adds the right cells.

WALKTHROUGH · 6:02 · HELP › LEARN

Build a spreadsheet with the assistant

Ask the Spreadsheet Assistant for a workbook in plain words, read how it was built, check its formulas, change one cell or a whole table with Ask AI, and go back with Undo or a saved version.

Before you begin

- **Access** to **Drafts** and an available model. The model picker at the top of the editor shows which one is in use.
- No file is needed. To build from your own data, have a **CSV** or Excel file ready.

Step by step

1. **Open Drafts** and choose Spreadsheet in the format rail.
2. In the message box, describe the sheet: name the columns, say how many rows, say what each calculated column does, and say where totals go. Or choose a suggestion and edit it.
3. Press Enter or choose the send key. The work trace runs in **Draft** chat while the grid waits.
4. When it finishes, read the trace. Recalculated every formula means no formula shows an error. It does not mean the numbers are right.
5. Select a calculated cell and press F2 to see the cells it reads. Press Esc to leave it unchanged.
6. Select the numbers above a total and compare the Sum in the status bar with the total.
7. If they differ, select the total, press F2, and read which cells it adds. Then select the cells to fix, choose **Ask AI**, and say exactly what to change.
8. To change one cell, type a label beside it if it needs one, select it, and choose **Ask AI** (Ctrl+J, ⌘J on a Mac). Type what you want or pick an action.
9. Check the Preview and the highlighted cells, then choose Apply, **Try again**, or **Discard**.
10. To change a whole table, select all of it and use **Ask AI** the same way.

11. If a change is wrong, choose Undo (Ctrl+Z, ⌘Z on a Mac). An AI change undoes in one step.
12. To revise the whole workbook, type in the message box again. It changes the workbook at once and saves a new version, so check the result. Short requests work better than one long one.
13. Choose **Document history** and, under Versions of this draft, choose a version to restore it. This changes only the screen, so export it or save a change to keep it. The list clears when you leave **Drafts**, reload, or reopen the draft, which then starts again at Version 1.

Path: Build from your own data

1. Choose the paperclip, then Attach to chat, and pick a **CSV** or Excel file.
2. Ask for what you want from it, for example Turn my attached data into a clean table with totals and a chart.
3. The assistant reads the file's rows as its data. To edit the file's cells yourself instead, choose Open in editor.

Path: Start from a chat

1. Ask for a spreadsheet in chat, for example a budget in Excel.
2. If the card Build this as a spreadsheet? appears, choose Build in spreadsheet editor. **Drafts** opens and starts building.
3. Continue in chat keeps the answer in the conversation instead.

Path: Send a table from a reply

1. Under a reply that has a table, choose **Transfer to Drafts**.
2. Choose Spreadsheet. Each table in the reply becomes a sheet you can edit.

Path: Use your sources or the web

1. Choose Sources above **Draft** chat and select a workspace source, or turn on **Web** if your workspace allows it.
2. Ask for the workbook as usual. With **Web** on, the assistant is told to put each source's name in a cell note on the numbers it supports.

Path: Ask AI actions

1. Select cells and choose **Ask AI**. Press Ctrl+J, ⌘J on a Mac, or right-click and choose **Ask AI** about this.
2. Write a formula for this cell, Explain these formulas, Fix formula errors, and Add a totals row are at the top of the list, with actions for cleaning and analyzing data below them.
3. After a Preview, type in the box under it to adjust the result, for example round to dollars.

Path: Choose another model

1. Open the model picker at the top of the editor and choose a model.
2. **Assistant settings**, beside the paperclip, also sets the reasoning level and whether sources must be cited.

Check that it worked

- ✓ The grid shows the columns you asked for, and the draft has taken the workbook's name.
- ✓ The work trace says Recalculated every formula, None show an error.
- ✓ Selecting a calculated cell shows a formula in the formula bar, not a typed number.
- ✓ The status bar's Sum matches the workbook's total, and the total's formula adds only the rows above it.
- ✓ After Undo the AI change is gone, and after restoring a version the label at the top names that version.

Troubleshooting

WHAT YOU SEE	WHAT TO DO
The result is not what you asked for: numbers in the wrong place, a blank sheet left over, or missing headers	Small models do this with long requests. **Restore** the last version in **Document history**, then ask again in smaller steps, and say exactly which row holds the headers. Build the table first, then add the chart in a second request.
A total is too high, often about double, yet the trace says None show an error	The formula works, so no error shows, but its range is wrong. Select the total and press F2: a range that reaches into another total counts those rows twice. **Ask AI** can correct it, and saying which rows to add and which row holds the total helps.
The work trace says a formula "still shows an error"	Select one of the named cells and use **Ask AI** with Fix formula errors, or correct the formula yourself. A cell with an error has a small mark in its corner.
The work trace says Fixing 25 formulas that errored	Nothing is wrong. The first pass left a formula error, so the cells went back to the model once. Read the check that follows it.
"The model's reply was not valid spreadsheet changes twice, so nothing was applied. Try rephrasing the request."	Your workbook is unchanged. Make the request shorter and more specific, or choose another model.
The work trace says Answered without changing the workbook	It treated your message as a question. Say what to change, for example add a column called Status.
The work trace says Skipped 2 changes	The assistant asked for something the workbook could not accept, and **Draft** chat lists each one. Ask for those changes again in plain words.
The grid will not accept typing and the box says "The spreadsheet assistant is building your workbook..."	The grid is locked while the assistant works, and a long request on a small model can take minutes. Wait for Worked for in the trace.
"New revisions will appear after you save or ask the assistant to revise." on a draft that had versions	The list covers versions made since you opened the draft. A reopened draft starts again at Version 1 with your latest saved work, and earlier versions are no longer listed. **Export** any version you want to keep before you leave it.
"No drafting model connected", or Ask AI is off	No model is available to you. Ask your administrator for model access. The grid, tables, charts, and exports still work without one.

WHAT YOU SEE	WHAT TO DO
Ask AI changed more cells than you expected	It works on the selection. Choose **Discard**, select only the cells you mean, and ask again.

WALKTHROUGH · 7:48 · HELP › LEARN

Work in a spreadsheet: formulas, tables, charts, and files

Start from a template or your own file, turn data into a table with formulas that use column names, summarize it with a pivot table and a chart, add rules that format, check, and filter it, then export an Excel file and compare versions.

Before you begin

- **Access** to **Drafts**. Nothing in this lesson needs a model.
- For your own data, an .xlsx, .xlsm, .csv, or .tsv file of 12 MB or less.
- New to spreadsheets in **Drafts**? Build a spreadsheet with the assistant is the shorter place to start.

Step by step

1. In **Drafts**, choose Spreadsheet in the format rail.
2. Choose the paperclip, then Open in editor, and pick your Excel or **CSV** file. It opens as a new workbook, and **Draft** chat records it.
3. If a column shows hash marks, select the columns, open Format (the highlighter key), and choose Auto-fit column width.
4. Type the header of any column you plan to calculate, such as Total, next to the data.
5. Click inside the data, open Format, and choose Format as table…. Check **Table** range and My data has a header row, type a **Table** name such as Invoices, and choose **Create** table.
6. Select the empty cells of the calculated column, type a formula with column names, such as =[@Units]*[@[Unit price]], and press Ctrl+Enter (⌘Enter on a Mac) to fill them all.
7. On another sheet, total the column by name, such as =SUM(Invoices[Total]), and compare it with the Sum in the status bar.
8. Click inside the table, open **Table** styles, and pick a style.
9. Open **Insert** (the plus key) and choose Pivot table…. Under Use as, set a field to Rows and a number field to Values, then choose **Create** pivot table.
10. Select the pivot's header and rows, open **Insert**, choose **Chart**…, pick a type, type a **Title**, and choose **Insert** chart.
11. Select cells, open Format, choose Conditional formatting…, pick a rule under Format cells if, and choose Add rule.

12. Select a column, open Data (the funnel key), choose Data validation…, type the Choices (comma separated), and choose Add rule.
13. Choose a column's filter button, clear the values you do not want or set a Condition, and choose Apply. Data › Clear filter choices brings the rows back.
14. Open Format and choose Freeze top row.
15. Choose **Export**. If the panel says **Save your edits first**, choose **Save version**. Then choose Excel workbook or **CSV** (current sheet).
16. Read any **Export** note in **Draft** chat, then open the file to check it.
17. After more edits, choose **Save version** again, then **Compare versions**, and check the cells that changed. Do this before you leave the draft, because a reopened draft starts a new version list. In a narrow window these two buttons read Save and Compare.

Path: Start from a template

1. Choose Spreadsheet, then Templates above **Draft** chat.
2. Select a workbook: Monthly budget, Sales tracker, Project plan, Invoice, Expense report, Loan calculator, Inventory tracker, or KPI dashboard.
3. Choose Start and the workbook's name, such as Start Sales tracker. It opens as a new spreadsheet draft.
4. The sample data is fictional. Type over it, and the formulas, tables, and charts follow.

Path: Start from a blank workbook

1. Choose Spreadsheet. A blank workbook starts on Sheet1.
2. Click a cell and type. Enter moves down and Tab moves right.
3. Type = to start a formula. Function names are suggested as you type, and Tab accepts one.

Path: Open an Excel workbook

1. Choose the paperclip, then Open in editor, and pick an .xlsx or .xlsm file.
2. Every sheet opens, and **Draft** chat says how many.
3. Read any line that starts with **Import** note. It names something the editor changed or could not keep.

Path: Make a table from the Table styles key

1. Click inside data that has a header row, with no tables on the workbook yet.
2. Open **Table** styles. The menu says which range it will format, such as Format A1:F31 as a table.
3. Pick a style. To name the table or add a totals row, choose **More** table options….

Path: Add a totals row to a table

1. Click inside the table and open **Table** styles, then **More** table options….
2. Turn on Totals row. Number columns get a total, and the table grows by one row.

Path: AutoSum and the function list

1. Select the cell under a column of numbers, open **More**, and choose Sum, Average, Count numbers, Max, or Min under AutoSum. In a wider window AutoSum has its own key.
2. For anything else, open **Insert** and choose Function…. **Search** by name or by what you want to do, then choose a function to start it in the cell.

Path: Sort and clean up data

1. Open Data and choose Sort A → Z… or Sort Z → A…. Add level sorts by a second column.
2. Remove duplicates… removes rows that repeat an earlier row in the columns you check.
3. Split text to columns… splits a column at a comma, semicolon, space, tab, or a separator you type.

Path: Name a cell or range

1. Select the cells, type a name in the Name box at the left of the formula bar, and press Enter.
2. Use the name in formulas, such as =B4*TaxRate. Data › Named ranges… lists every name.

Path: Notes, find, and shortcuts

1. **Insert** › Note adds a note to the selected cell. It exports to Excel as a comment.
2. Find in the status bar searches this sheet, all sheets, or formulas, and can replace.
3. The keyboard key in the status bar lists every shortcut. Ctrl+/ (⌘/ on a Mac) opens it too.

Check that it worked

- ✓ Every row of the calculated column shows a value, and the formula bar shows the same column-name formula in each one.
- ✓ =SUM(Invoices[Total]), the pivot's Grand Total, and the status bar's Sum all show the same number.
- ✓ Typing a value that is not on the list is refused, with a message starting Choose one of.
- ✓ The **Export** panel says Sent to your browser downloads, and the file opens again through Open in editor with its sheets, table, and chart.
- ✓ **Compare versions** lists the cells you changed, with what each held before and after.

Troubleshooting

WHAT YOU SEE	WHAT TO DO
A column shows hash marks (########)	The column is too narrow for the value, and nothing is lost. Select it, open Format, and choose Auto-fit column width, or drag the column's right edge.
A filter button covers a column's header	Auto-fit does not leave room for the button. Drag the column's right edge wider.
#REF! in a formula that uses [@Units]	The @ reads this row of the table, so the formula must sit inside the table, and typing beside a table does not add to it. Click a cell in the table's last column, open **Insert**, and choose Columns left, then type the header and formula in the new column. Columns right from the last column lands outside the table.
Double-clicking the square at a cell's corner opens the cell	Fill down another way: drag the square down the column, or select the cells and press Ctrl+D (⌘D on a Mac).
"That name is already used."	**Table** names must be unique in the workbook. Type another one.
"That range overlaps a table, so it was not formatted."	A range can belong to only one table. Pick cells outside it, or choose Convert to range on the existing table first.
"Click inside your data, or select a range with a header row, to make it a table."	The selected cell has no data around it. Click a cell in the data, then open **Table** styles again.
"This cell is part of a pivot table. Change the pivot from its panel."	Pivot cells are calculated. Click inside the pivot, open **Insert**, choose Pivot table…, and change it there, or change the source data.
"No field names found in the first row of the source."	Source data must start on a row of column names. Correct the range, for example to start at row 1.
"Choose one of: …"	The cell has a list rule. Pick a value from its arrow, or press Esc to cancel. To accept other values, select the cell, open Data › Data validation…, and turn off Reject entries that break the rule.
"Fill in the rule's values first."	The rule has no choices or limits yet. Fill in Choices (comma separated), or the Value fields, then choose Add rule.
"Old .xls files are not supported. Save it as .xlsx in Excel first."	Open the file in Excel, save it as .xlsx, and open that copy.

WHAT YOU SEE	WHAT TO DO
"… is larger than 12 MB."	Open a smaller file, or remove sheets you do not need and save a copy.
"Export note: Pivot tables export as values."	The file keeps the pivot's numbers, but they will not update there. Rebuild the pivot in the other app if you need it live.
"Export note: The filter on … overlaps a table, which has its own filter, so it was left out."	The table keeps its filter buttons in the file. Any choices made with them are not saved in the file, so set them again there.
Compare versions is off: "Save two different versions of this draft to compare them"	Make a change, choose **Save version**, and try again. Versions from before you reopened the draft no longer count.
"These versions hold the same cells."	Nothing in the cells differs between the two you picked. Choose another Base or Compared with.

26. Recover work kept only on this device

Distinguish a browser working copy from a completed account save.

The sidebar's **Only on this device** reminder appears when work has changes kept in this browser that have not reached your account. It can include chats whose last save failed, documents or decks with unsent changes, and older history from before account sync.

- Open the reminder to review the named items. For chats whose last save failed, choose **Retry all** and check the resulting save state.
- For documents and decks, choose **Open Drafts**, open the item, and save it to your account. Review any load, quota, connection, or conflict error before leaving the browser.
- Older browser history remains separate until you explicitly import each item from **Drafts** → **Document history** with **Import to my account**. Confirm the item belongs in this account before importing.
- **Archive** finished drafts when you want them out of the active list. **Account** archives remain recoverable; archiving a browser-only item does not prove it has been uploaded.

GOOD TO KNOW

Clear list dismisses these reminders without deleting or uploading work. New edits may appear again. **Hide this reminder** turns off this account's sidebar notice in this browser; save status remains in **Drafts** and chats. Downloading an export also leaves pending account saves to be resolved.

WALKTHROUGH · 3:06 · HELP › LEARN

Save, organize, and recover your drafts

Save documents, decks, and spreadsheets to your account, reopen them from Document history, archive and restore them, return to an earlier version while the draft is open, and recover work kept only on this device.

Before you begin

- At least one document, deck, or spreadsheet in **Drafts**.

Step by step

1. In a document, deck, or spreadsheet, choose **Save version** (it reads Save in a narrower window) and wait for Saved at the end of the toolbar.
2. Choose **Document history** (the clock at the top of the assistant rail). A document, a slide, or a grid icon marks each card's format.
3. Point at a card to preview it, or choose the card to reopen that draft.
4. To put finished work away, point at its card and choose **Archive**. **Draft** archived. Open **Archived** to restore it. confirms it.
5. Choose **Archived** to find it, then choose **Unarchive** to bring it back to Active.
6. Under Versions of this draft, choose a version to return to it. The list covers versions made since you opened the draft. To keep one, export it while it is on screen, or change something and choose **Save version**.
7. **Delete** is separate: choose **Delete**, read the confirmation, then choose **Delete** draft or **Cancel**.

Path: When a save fails

1. Local only at the end of the toolbar means the latest changes are kept in this browser but have not reached your account. Point at it to read why.
2. Choose Retry beside it once you are back online, or export a copy before you leave.
3. If **Draft** changed elsewhere appears, keep your local changes safe (export), then choose Reload server copy beside it.

Path: Only on this device

1. The sidebar reminder counts items only on this device. Choose it to open the list.
2. **Retry all** retries chat saves. **Open Drafts** opens **Drafts**: in **Document history**, drafts with unsent changes are marked Local changes. Open one and choose Retry.
3. **Clear list** dismisses the current reminders; **Hide this reminder** hides the notice. Neither uploads nor deletes your work.

Path: Leaving with unsaved edits

1. Keep your unsaved edits? appears when you leave or open something else.
2. Choose Keep editing, Save copy and continue, or **Discard** and continue.

Check that it worked

- ✓ Saved appears at the end of the toolbar, and the version label at the top shows the new number.
- ✓ A saved spreadsheet is listed in **Document history** beside your documents and decks.
- ✓ The draft is listed under **Archived** after archiving, and under Active after **Unarchive**.
- ✓ Versions of this draft lists each version made since you opened the draft, with its time.

Troubleshooting

WHAT YOU SEE	WHAT TO DO
Local only with Retry beside it (its tooltip ends "Your changes are kept on this device.")	The server save failed, and your changes are kept in this browser. Check your connection and choose Retry, or export a copy before you close the browser.
Not saved, with "… and browser storage could not keep a copy." beside it	Keep the workspace open, then choose Retry or export your changes.
"This draft exceeds the 2 MB server draft limit", "This deck exceeds the 8 MB server deck limit", or "This workbook exceeds the 8 MB server spreadsheet limit"	Split the document, or remove large images, then save again. For a workbook, move data to a separate file or remove what you no longer need.
"Draft changed elsewhere" with Reload server copy beside it	Another tab or device saved this draft. **Export** your local version if you need it, then choose Reload server copy.
"Save two different versions of this draft to compare them"	**Compare versions** needs two saved versions that differ. Save again after an edit. Versions from before you reopened the draft no longer count.
"New revisions will appear after you save or ask the assistant to revise." on a draft that had versions	The list covers versions made since you opened the draft. A reopened draft starts again at Version 1 with your latest saved work, and earlier versions are no longer listed. **Export** any version you want to keep before you leave it.

27. Agent profiles

Reusable bundles of model, prompts, knowledge, and tools.

An agent profile bundles a model route, meta prompts, knowledge bases, and MCP tools into one reusable configuration. A usable profile needs an approved, enabled model backed by a working provider. A saved profile marked not connected is a configuration example, not proof that it can run.

Creating an agent

- If your account has agent authoring permission, click **Agents** in the sidebar, then **New Agent**.
- Give it a name and a short description of what it is for.
- Work through the editor tabs: **Profile** (name, model, and description), **Knowledge** (assign knowledge bases), **Tools** (select MCP tools), **Prompts & Skills** (attach system prompts and skill files), **Access** (who can use it), and **Hermes** (the optional learning companion).
- Click the save button. Standard users create private profiles; administrators control group sharing and organization publishing. Check model readiness and access before trying the profile in chat.

Using an agent in chat

- Type @ in the composer and pick an available profile to use its configured model route, instructions, knowledge, and tools.
- The **Agent** switch in **Send options** can choose the first available profile when none is selected. Check **Agent profile** and select the intended configuration before sending.
- If no profiles appear, ask your administrator to check that a ready profile is available to your account.

From the **Agents** view you can also open a profile to edit it, jump straight into a chat with it, or delete it. The Automations tab at the top of this view holds your scheduled runs — covered in "Scheduled automations".

WALKTHROUGH · 2:31 · HELP › LEARN

Agent profiles

Build a private agent with its own instructions, model, knowledge, and skill files, then use it in chat and check that the reply follows it.

Before you begin

- Permission to build agents: your platform owner allows users to build their own agents, and your administrator grants **Can build agents** to one of your groups. Until then, **Agents** says Building agents is not available to you.
- An available model for the agent to use.
- Optional: knowledge bases, tools, prompts, and skill files shared with you, to attach to the agent.

- **Agents** that use the **Hermes** companion also need **Can use Hermes companion** on one of your groups. Until then they show Needs **Hermes** approval from your administrator, and you cannot chat with them.

Step by step

1. Choose **Agents** in the sidebar, then **New Agent**.
2. On **Profile**, type an **Agent** name and choose the AI model. Optionally start from a template such as Research Analyst.
3. In System prompt, write the agent's instructions: its role, what it should produce, and what it must never do. Meta prompt adds standing rules on every turn.
4. On **Knowledge**, tick the knowledge bases it should search on every message.
5. On **Tools**, tick any tools it may use in agent mode; tools that need approval ask before they run.
6. On **Prompts & Skills**, tick saved prompts and skill files to add to its instructions.
7. On **Access**, read Private — only you can use this agent.
8. Choose **Create** agent and wait for the agent's name followed by created. It is ready to use in chat.
9. In a chat, type @ and choose the agent, then type your question and send it.
10. Check the reply against the agent: the trace reads **Agent** worked for, Working as names the agent, and the answer should follow its instructions and cite its knowledge. Smaller models can drift, so read it.

Path: Use it from Send options

1. **Send options** › **Agent**, then choose the profile in **Agent profile**.
2. Check the selected profile before sending; turning **Agent** on can select the first one.

Path: Use it from the Agents page

1. On the agent's card or in its editor, choose **Chat** (or Use in **Chat**).
2. A chat opens with **Agent** mode on for that agent.

Path: Edit, duplicate, or delete

1. On the agent's card, choose Edit, change the settings, and choose Save **Profile**.
2. **More** actions on the card offers Duplicate and **Delete**.

Path: Share it

1. **Agents** you build stay private to your account.
2. Ask an administrator to share the agent with a group.

Check that it worked

- ✓ The agent appears under **Agents** with your chosen model.
- ✓ In chat, the **Agent** chip shows the agent, and the reply's trace reads **Agent** worked for, with Working as and the agent's name, and a step for the passages found in its knowledge.
- ✓ The answer draws on the instructions you wrote and its knowledge, and offers its citations. Here, three bullet points from the playbook, plus extras a smaller model added.

Troubleshooting

WHAT YOU SEE	WHAT TO DO
"Building agents is not available to you."	Your groups lack **Can build agents**, or the service policy does not allow user-built agents. Ask your administrator.
"Select a base AI model and enter an agent name before saving."	Type a name and choose an available model in AI model.
"… is not connected, so the agent cannot answer."	The agent's model has no working provider. Choose another model in **Profile** and save.
"Knowledge base … is turned off, so the agent answers without it."	Ask the knowledge base's owner to turn it back on, or untick it.
An agent card says "Needs Hermes approval from your administrator", or chat says "… uses the Hermes companion, which your administrator hasn't turned on for your groups."	That agent uses the **Hermes** companion. Ask your administrator to turn on **Can use Hermes companion** for one of your groups.
"No agent profiles available yet — create one under Agents" when typing @	You have no agents yet, or none is shared with you. Build one, or ask your administrator.
The reply ignores part of the instructions	Smaller models follow short, specific instructions best. Shorten the System prompt, or choose a stronger model.

PART 4

Library and automations

28. Knowledge bases

Give chats grounded, citable access to your documents, web pages, and APIs.

Knowledge lives in the **Library**: click **Library** in the sidebar, then the **Knowledge** tab. The **Knowledge Bases** panel lists every collection with its status, security posture, and whether it is enabled.

- Click New knowledge base and name the collection.
- Choose what feeds it. A knowledge base can start from Upload files (PDFs, Office files, email, images, audio, and video), Add web pages (public pages, re-fetched whenever you sync), or **Connect an API** (JSON or text from an endpoint, with a key or sign-in).
- **Connect an API** needs its own permission. Without it the choice is locked and says Connecting APIs needs approval. Ask your administrator to turn on Can add API sources for one of your groups.
- **Create** the base, then check its row in the table: it shows the status, the security posture, and whether the base is enabled.

GOOD TO KNOW

Only enabled knowledge bases can be searched from chat, and access control is enforced per source — people only ever retrieve what they are allowed to see.

Using knowledge in a conversation

- Type # in the composer to reference a knowledge source or choose from Files in knowledge sources. A file choice references its name in your prompt and searches that file's knowledge source; the row says which source will be searched.
- Or turn on the **Knowledge** switch in send options to let the reply search your enabled bases.
- Replies grounded in knowledge carry markers that open the cited document at the passage (see “Check a source”).

Going deeper

- When you add a web page, Pages to read chooses how far to go: This page, Linked pages, or Two levels. Linked pages stay on the same site, and anything its robots.txt excludes is skipped.
- Look for fresh pages on this site when answering lets a question fetch a page that was not read up front. The reply marks it Live page. Turn it Off to answer only from the pages already read.

- Handwriting and images, on the knowledge base's Settings, decides how scans and pictures are read. AI reading on uses an image-capable model for handwriting, stamps, and pictures. Standard OCR only keeps pages on your server and still reads printed scans.
- Each file keeps its own properties, such as author, dates, and sensitivity labels. Open a file's details under Indexed files to read them. Click a file's name or Preview to read the file itself.

GOOD TO KNOW

The # shortcut menu shows Loading files… while retrieving file choices. If Some files could not be loaded appears, use Retry in that menu. Files from sources that loaded successfully remain usable. If access was removed or a source needs configuration, ask your administrator to resolve it.

WALKTHROUGH · 4:22 · HELP › LEARN

Knowledge bases

Build a knowledge base from files, a website, or an API, read what each file carries about itself, choose how scans are read, and ask a question that cites it.

Before you begin

- To create your own: your administrator grants Can build knowledge bases to one of your groups. Without it, you use the knowledge bases shared with you.
- Files up to 250 MB each: PDF, Word, Excel, PowerPoint, email (.eml, .msg), text, **Markdown**, **CSV**, JSON, images, audio, and video.
- For web pages: public addresses. Sign-in pages and anything the site's robots.txt excludes are skipped; for pages behind a sign-in, paste the text instead.
- To read handwriting, stamps, and signatures: an image-capable model set up for your workspace. Without one, scanned pages use standard OCR.
- To connect an API: your administrator also grants Can add API sources. Until then, **Connect an API** is shown locked.
- **Connected** sources such as SharePoint, Box, Google Drive, and iManage are set up by administrators and shared with you.

Step by step

1. Choose **Library** in the sidebar; **Knowledge** opens.
2. Choose New knowledge base.
3. Type a Name, keep Start with on Upload files, and choose **Create**. Who can search it is Only me; administrators manage sharing.
4. Drag files onto Drag files here, or choose browse your computer.
5. Wait for each file to show Added and appear under Indexed files with its passage count. The base shows Ready.

6. In a chat, type # and choose your knowledge base, then type your question and send it.
7. Check the reply: it answers from your files and offers View N citations →. Open it to see each document the reply cited in **Sources gathered**, then choose a row to open the document on the cited page. Check a source covers that step by step.

Path: Add a web page or a whole site

1. In the knowledge base, open **Web** pages.
2. Type the Page address and an optional Name.
3. Under Pages to read, choose This page, Linked pages, or Two levels. Linked pages also reads the same-site pages this page links to; Two levels also reads the pages those pages link to.
4. For Linked pages or Two levels, set Most pages to read, up to 100.
5. Under Look for fresh pages on this site when answering, keep On to let a question look up a page that was not read up front, or choose Off to answer only from the pages read now and on Sync now.
6. Choose Fetch and add pages (Fetch and add page for This page). The site is listed as one item with its page count, and the notice says how many pages were read and how many more links were saved.
7. Sync now reads it again later. For a page behind a sign-in, tick Paste the text instead of fetching the page (for pages behind a sign-in), paste it, and choose Add text.

Path: Read a file's properties

1. On Files, choose the arrow beside a file (Show details).
2. Properties lists what the file carries about itself: title, author, dates, labels, and custom fields such as a matter number, plus its size and who uploaded it.
3. Who can find it says who can reach the file.
4. Properties are searchable, so you can ask for a file by its author or matter number.

Path: Choose how scans and pictures are read

1. Open Settings and find Handwriting and images.
2. Keep AI reading on so an image-capable model reads handwriting, stamps, signatures, and pictures in scanned pages, images, Word, and PowerPoint files.
3. Choose Standard OCR only to keep pages on this server. Standard OCR still reads printed scans.
4. Choose Save changes. The setting applies to files read from then on.
5. If the note says No image-capable model is set up for this workspace, scanned pages use standard OCR until an administrator adds one.

Path: Connect an API

1. Connecting an API needs Can add API sources as well. Without it, **Connect an API** shows a lock, and API says Connecting APIs needs approval.
2. Open API. Enter the API address, an optional Path and Name.
3. Under Sign-in choose None (public API), API key, Bearer token, or Sign in with provider (OAuth), and fill in its fields.
4. Choose Fetch and add. The JSON or text response becomes searchable passages; Sync now refreshes it.

Path: Ask without

1. **Send options** › **Knowledge**, then choose your knowledge base.
2. Send the question; the reply searches only that source.

Path: Turn it off or tidy it

1. The On switch (Assistants can search …) controls whether chats can search it.
2. **Delete** a file with the bin beside it under Indexed files.

Check that it worked

- ✓ Each file shows Added and is listed under Indexed files with a passage count.
- ✓ The knowledge base shows Ready and On.
- ✓ A question with # returns facts from your files and View N citations; **Sources gathered** names each document the reply cited (for a PDF, with the page).
- ✓ A website shows its page count under **Web** pages, with Looks for fresh pages when answering when that is on.
- ✓ Show details on a file lists its Properties.

Troubleshooting

WHAT YOU SEE	WHAT TO DO
"You can use the knowledge bases shared with you in chat. Ask an administrator if you need to add your own."	Creating knowledge bases is not granted to your groups. Ask your administrator for Can build knowledge bases.
"Skipped … (save it as .docx first)" or "(unsupported type)" or "(larger than … MB)"	Convert old .doc files to .docx, use a supported type, or split very large files.
"No readable text — only the name is searchable"	The file has no text layer (for example a picture-only PDF beyond the OCR limit). Upload a text version.
"Connecting APIs needs approval. Ask your administrator to turn on Can add API sources for one of your groups."	API sources need their own grant, on top of Can build knowledge bases. Ask your administrator. API data already indexed stays searchable.
"Give the knowledge base a name."	Type a Name before choosing **Create**.
"Enter the page address."	Type the full address, including https://.
A site reads fewer pages than you expected, and the notice says "skipped by robots.txt" or "could not be read"	Only public pages can be read, and pages the site's robots.txt excludes are skipped. Raise Most pages to read, or paste the text of pages behind a sign-in.
"This file carried no properties beyond its name."	The file holds no title, author, or custom fields. Add them in the program that made it and upload it again.
"No image-capable model is set up for this workspace, so scanned pages use standard OCR, which cannot read handwriting."	Ask an administrator to set up an image-capable model. Until then, upload typed versions of handwritten pages.
"Some files could not be loaded. Retry" in the # menu	Choose Retry. Sources that already loaded stay usable.

29. The Tools library

MCP connections, saved prompts, and skill files inside the Library.

Click **Library** in the sidebar, then the **Tools** tab. The **Tools Library and Connectors** panel has three sections:

TAB	WHAT LIVES THERE	WHERE IT APPEARS IN CHAT
Connections	MCP tools and connections available to models and agents.	Type / in the composer.
Prompts	Saved prompt templates, including `{{variables}}` you fill in when using them.	Type / in the composer.
Skills	Skill files — reusable instructions for recurring workflows.	Type $ in the composer.

- Click **New Prompt** or **New Skill** to create one: give it a name, a category, a description, and the content itself, then save.
- Click any existing card to review or edit it; the trash icon deletes it permanently.
- Every tool row shows its real status — draft, approval required, or enabled — so you always know whether a connection is actually live before relying on it.
- Add connection is locked until an administrator grants Can build tools to one of your groups; its tooltip says so. **Hermes** connections and **Hermes** agents show **Locked** until your administrator approves **Hermes** for you.

WALKTHROUGH · 1:23 · HELP › LEARN

Tools and the Library

Find the connections, saved prompts, and skill files you can use, read them, and add a private connection when your administrator allows it.

Before you begin

- **Prompts** and skill files are created by administrators; you can read and use them.
- To add your own connection: your administrator grants Can build tools to one of your groups, and you have the MCP server's address. Until then, Add connection is shown locked.
- **Hermes** connections also need **Can use Hermes companion** on one of your groups. Until then they show **Locked**.

Step by step

1. Choose **Library** in the sidebar, then **Tools**.
2. **Connections** lists the MCP connections you can use in **Agent** mode, with On, Off, Needs setup, or **Locked**.
3. Choose **Prompts** to see the saved prompts shared with you. Choose a prompt's View to read its content.
4. Choose **Skills** to see the skill files shared with you.
5. Use them in chat: type / for prompts and connections, and $ for skill files, or attach them to an agent.

Path: Add a private connection

1. Without Can build tools, Add connection shows a lock. With it, choose Add connection.
2. Type a Name, choose how Aperture connects (HTTP or SSE), and enter the Server URL starting with https://.
3. Choose Add connection. It starts turned off; set sign-in, access, and approval on the next screen, test it, and turn it on.
4. **Connections** you add are private to you; an administrator can share them.

Path: Read a connection's status

1. On: available under policy. Off: turned off. Needs setup: missing an address, token, or sign-in.
2. Last test failed: the latest connection test did not succeed.
3. Asks before each use: you approve each run in chat (**Approve** MCP tool run?).
4. **Locked**, with Needs **Hermes** approval from your administrator: a **Hermes** connection your groups cannot use yet.

Check that it worked

- ✓ **Prompts** and **Skills** list the items shared with you, and View shows each one's content.
- ✓ Typing / in chat lists the same prompts, and $ lists the same skill files.

Troubleshooting

WHAT YOU SEE	WHAT TO DO
"Connections are managed by your administrators. These are the ones you can use in Agent mode."	You cannot add connections yet. Ask your administrator for Can build tools if you need one.
Add connection is off, with a lock: "Adding your own MCP connections needs approval. Ask your administrator to turn on Can build tools for one of your groups."	Ask your administrator for Can build tools if you need your own connection.
"Locked" and "Needs Hermes approval from your administrator" on a connection	**Hermes** needs approval. Ask your administrator to turn on **Can use Hermes companion** for one of your groups.
"Shared prompts are managed by administrators." or "Skills are managed by administrators."	Ask your administrator to add or change a prompt or skill file.
"Use a full address starting with https://"	Enter the complete server address.
"Not signed in to the provider" or "No access token saved"	Open the connection's Sign-in tab and finish signing in, or ask your administrator.
"MCP tool run denied. No message was sent."	You chose Deny when asked to approve a tool run. Send again and choose **Approve** if you trust it.

30. Scheduled automations

Recurring chat or drafting runs, as one model call or a multi-step chain.

Automations are saved workflows that run a chat or drafting task on a schedule. They are useful for recurring digests, weekly status checks, report refreshes, policy reviews, and any workflow where the same model chain should run the same way each time. Enabled schedules run automatically in the background (times are UTC), and each scheduled run delivers its output as a new chat thread in your sidebar.

Creating an automation

- Click **Agents** in the sidebar, then the Automations tab, then **New automation**.
- Name it — for example “Monday client digest”.
- Choose what it runs against: chat or draft.
- Pick a trigger: **Daily** (a time each day), **Weekly** (a day and time), **Once** (a specific date and time), or **Cron expression** (such as `0 9 * * 1` for 9:00 every Monday, in UTC).
- Write the initial input — what the first step should work on.

- Build the model chain: each step has a model and an instruction, and each step's output feeds into the next step. Use **Add step** for multi-step chains and the × to remove a step.
- Click **Save automation**.

What to check before saving

- **Models** — every step must use a model you can actually access. If a model is missing, your admin may need to approve it for your group.
- Context — write the initial input as if the automation will run without you watching. Include the matter, audience, date range, source expectations, and desired output format.
- Cadence — use **Once** for a single future run, **Daily** or **Weekly** for regular recurring work, or a reviewed **Cron expression** for another schedule. All times are UTC; check the intended local-time equivalent before saving.
- Ownership — name the automation so another person can tell what it does later.

Running and managing

- Each automation card shows its schedule, its steps, and its last run with an honest result — succeeded or failed, with the reason.
- **Run now** executes the whole chain immediately and shows a transcript of every step's output.
- The toggle pauses or resumes the schedule; the pencil edits it; the trash deletes it.
- You can also queue an automation into any chat by typing > in the composer — it runs when you send.
- The list shows the automations you created. Organization administrators can review the automations in their workspace.

TIP

Always use **Run now** once after creating or editing an automation. If the run fails, the card shows the reason so you can fix the model choice, input, or instructions before depending on the saved schedule.

WALKTHROUGH · 2:42 · HELP › LEARN

Scheduled automations

Build an automation that runs a prompt through one or more models on a schedule, deliver it to a new chat or a new draft, run it now, and read its history.

Before you begin

- At least one model available to you. Without one, Automations says no approved models are available and **New automation** is off.
- The prompt you want to run, and when it should run (the time zone matters).

Step by step

1. Choose **Agents** in the sidebar, then Automations.
2. Choose **New automation**.
3. Under What it does, type a Name and the Prompt for the first step.
4. Under Steps, choose a model (or one of your agents) for step 1 and an optional instruction. Choose **Add step** to pass the result to another model.
5. Under Schedule, choose **Daily**, **Weekly**, **Once**, or Custom, set the time and Time zone, and check Next runs.
6. Under Deliver results to, choose **New chat** or New draft.
7. Leave On — runs on this schedule turned on, and choose **Save automation**.
8. On the automation's card, choose **Run now** to test it. Wait for the result and choose Open chat (or Open draft).

Path: Daily

1. How often › **Daily**, then set Time.
2. Next runs lists the coming days at that time.

Path: Weekly

1. How often › **Weekly**, choose the day (Mon to Sun), then set Time.
2. Next runs lists the coming weeks.

Path: Once

1. How often › **Once**, then set Run at to a date and time in the future.
2. Next runs shows that single run; if the time has passed it says No upcoming runs — this time has passed.

Path: Custom (cron)

1. How often › Custom, then type a **Cron expression** with five fields: minute, hour, day of month, month, day of week.
2. For example 30 7 * * 1–5 runs at 7:30 AM on weekdays. Check Next runs before saving.

Path: Deliver to a new draft

1. Under Deliver results to, choose New draft.
2. The last step is asked for a complete document, saved as a new draft.
3. After **Run now**, choose Open draft to edit and export it in **Drafts**.

Path: Pause, resume, edit

1. The switch on the card pauses the automation (Paused) or resumes it (Active).
2. Edit changes its steps, schedule, or delivery; choose Save changes.
3. Run history (N) lists recent runs: Succeeded, Failed, or Skipped, how each was started, and how long it took.

Check that it worked

- ✓ After saving, the card shows the schedule, the step chain, and Next run in ….
- ✓ **Run now** reports that the run saved the result to a new chat (or draft), and Output from this run shows each step.
- ✓ Open chat shows the delivered conversation, titled with the automation's name and the run time.
- ✓ Run history lists the run as Succeeded, run now.

Troubleshooting

WHAT YOU SEE	WHAT TO DO
"No approved models are available yet. An administrator must enable at least one available model before automations can run."	Ask your administrator for access to a model; **New automation** stays off until then.
"Give the automation a name." or "Every step needs a model or agent."	Type a Name and choose a model or agent for every step.
"Choose a date and time for the one-time run."	Set Run at for a **Once** schedule.
"Enter a cron expression, for example `0 9 * * 1`-5."	Type five fields separated by spaces, and check Next runs.
"Run failed: …" or Last run failed on the card	Read the message in Run history. A model or agent may be unavailable; edit the step and run it again.
Paused after failures	After 3 scheduled failures in a row the automation pauses itself. Fix the cause, then turn the switch back on.
An agent is listed as "(agent, needs Hermes approval)" and cannot be chosen for a step	That agent uses the **Hermes** companion. Ask your administrator to turn on **Can use Hermes companion** for one of your groups, or choose another model or agent.
An agent step does not use its tools	**Tools** and MCP servers need a person to approve them, so automations run agent steps without tools.

PART 5

Appearance, your account, and help

31. Light and dark mode

Switch appearance now or schedule it for this browser.


1. Find the moon or sun button beside **Help** near the bottom of the sidebar — a moon (**Dark mode**) while in light mode, a sun (**Light mode**) while in dark mode.
2. Click it. The entire platform switches immediately — no reload, nothing to save.
3. Click it again to switch back.

Schedule light and dark mode

Choose the clock button beside it to open **Theme schedule**. Enable **Switch automatically**, set different **Light mode at** and **Dark mode at** times, then choose **Save schedule**. The schedule uses this device's local time every day and is saved in this browser. You can still switch manually until the next scheduled change; disable the switch to stop automatic changes.

32. Your account

Your profile, personalization memory, password, role previews, usage, archives, and signing out.



Your account includes profile settings, password controls, and two-step verification. Example workspace with synthetic data.

Click your account card (your initials or photo) at the very bottom of the sidebar. The account drawer opens with everything about you in one place.

- **Profile** — choose Edit on the card with your name to change your display name, firm, website, bio, phone number, and photo (upload an image up to 5 MB, or paste a URL). Choose **Save profile** when done, or **Cancel** to discard. The card also shows your role, your organization, any personal token caps, and how you sign in.
- Workspace — administrators and platform owners see the consoles they can open here, plus **View as**, which previews the workspace as a lower role. A note reminds you which role you are previewing; switch back the same way.
- Personalization memory — opens your private memory manager when the feature is enabled. Use it to control, review, add, correct, pin, forget, or clear what the assistant remembers about you.
- **Security** — choose Manage to set up an authenticator for a local account, review the remaining recovery-code count, or replace codes after verifying your identity. Turning verification off is available only when organization policy permits it and signs you out. **SSO** accounts follow their identity provider.
- **Password** — accounts that sign in with a password choose Change, then enter the current password and the new one twice (at least 12 characters). The app continues with a new authenticated session after saving and revokes previous sessions. Accounts that sign in through **SSO** change their password with their identity provider.

- API access — when your role allows it, create a personal key for OpenAI-compatible tools. A key is shown once. Rotate replaces it and Revoke removes it, and each asks you to confirm.
- **Usage this month** — your Requests, **Chats**, and Tokens, counted from the first of the month in UTC. Requests include automatic chat titles.
- **Archived chats** — choose View to restore a chat you archived or delete it permanently.
- **Sign out** — ends your session and returns to the sign-in screen.

WALKTHROUGH · 4:33 · HELP › LEARN

Personalize, use mobile, and get help

Find your way around Account: edit your profile, read your usage, manage a personal API key, and review archived chats. Then set light or dark mode, install the app, and find Help.

Before you begin

- For installing: Safari on iPhone or iPad, Chrome on Android, or Chrome or Edge on a computer.
- For API access: your platform owner turns on **Downstream API access**. Administrators then have it; other people also need **Can use API** on one of their groups. Without it, **Account** does not list API access.

Step by step

1. Select your account card at the bottom of the sidebar. **Account** opens with your name, Role, Organization, and Sign-in at the top.
2. Choose Edit beside your name. Change the fields you need, such as Display name, Phone number, or Firm or organization, and choose **Save profile**. **Profile** saved. confirms it.
3. Under **Usage this month**, read Requests, **Chats**, and Tokens. The heading says when they reset.
4. Choose the moon button beside **Help** for **Dark mode**, or the sun for **Light mode**.
5. Choose the clock button (**Theme schedule**), turn on **Switch automatically**, set **Light mode at** and **Dark mode at** to different times, and choose **Save schedule**.
6. Choose **Help** at the bottom of the sidebar. It holds Report a problem, My reports, the walkthroughs, and the printable User guide (PDF).
7. To send a problem, idea, question, feedback, or security concern and follow the replies, see Report a problem and follow it up.

Path: Create a personal API key

1. Open **Account**. Under Preferences and security, expand API access.
2. **Copy** the Platform URL: it is the OpenAI-compatible base URL your tool asks for.
3. Choose **Create** key, then choose **Copy** beside New API key at once. For security, the full key is shown only once.

4. Paste the URL and key into your tool.
5. **Reopen Account**: API access shows Active key, the key masked, when it was created, and when it was last used.

Path: Rotate or revoke a key

1. To replace a key, choose Rotate key. **Replace** this API key? The current key stops working immediately.
2. Choose **Replace** key, copy the new key, and update every tool that used the old one. Keep key changes nothing.
3. To end access, choose Revoke. Revoke this API key? Any connected coding tools will lose access immediately.
4. Choose Revoke key. API access offers **Create** key again.

Path: Archived chats

1. Under Data, choose View beside **Archived chats**.
2. Point at a title to preview the chat.
3. **Restore** returns it to your sidebar at once.
4. Permanently delete asks first: **Delete** forever removes the full conversation and cannot be undone. Keep leaves it archived.

Path: Administrators and owners: Workspace

1. **Account** adds a Workspace section with **Admin console**, and **Platform owner console** for owners.
2. **View as** previews the workspace with another role. Choose a role on the rail; **Account** says Previewing, and which role is really yours.
3. Choose your own role to stop previewing.

Path: iPhone or iPad (Safari)

1. Open your workspace address in Safari and sign in. Add Aperture Chat to your home screen opens (or choose **Install app** in the menu).
2. Tap the **Share** button in the browser toolbar.
3. Scroll the share sheet and choose Add to Home Screen.
4. Tap Add. Aperture Chat appears on your home screen and opens full screen.

Path: Android (Chrome)

1. Open your workspace address in Chrome and sign in. The install card opens (or choose **Install app** in the menu).
2. If it offers **Install app**, choose it and confirm in the phone's install sheet.
3. Otherwise open the browser's ⋮ menu and choose Add to Home screen or **Install app**, then confirm.

Path: Computer (Chrome or Edge)

1. Aperture Chat shows no install card on computers.
2. Use the browser's own install control: the install icon at the right of the address bar, or the browser menu › Install (Chrome: Cast, save, and share › Install page as app; Edge: Apps › Install this site as an app).
3. Confirm Install. The app opens in its own window and appears with your other apps.

Path: On a narrow screen

1. Choose Open menu (top left) to reach navigation, chats, **Help**, **Install app**, and your account.
2. Choose where to go; the menu closes. The same permissions apply as on a computer.

Check that it worked

- ✓ **Profile** saved. appears, and **Account** shows the new details.
- ✓ After **Create** key and reopening **Account**, API access shows Active key with a masked value. After Revoke key, it offers **Create** key again.
- ✓ The workspace switches between light and dark at the scheduled times on this device.
- ✓ The installed app opens from your home screen or app list.
- ✓ **Help** opens with Report a problem and My reports at the top.

Troubleshooting

WHAT YOU SEE	WHAT TO DO
"Enter a display name."	Display name cannot be empty. Type the name people should see.
"Use a complete http(s) website URL."	Enter the full website address, including https://.
"Unsaved changes. Choose Cancel to discard them."	Escape keeps what you typed. Choose **Save profile** to keep it, or **Cancel** to discard it.
Account does not list API access	Ask your administrator. **Downstream API access** must be on for the platform, and standard users also need **Can use API** on one of their groups.
"Clipboard access is unavailable. Select and copy the value manually."	Your browser blocked **Copy**. Select the value in the box and copy it by hand before you close **Account**.
You closed Account before copying a new key	The full key cannot be shown again. Choose Rotate key to create a new one.
"Usage is unavailable right now."	Close **Account** and open it again. Your chats are not affected.
Tokens says Not reported	Your model provider did not report token counts. Requests and **Chats** are still counted.
"Choose a profile photo that is 5 MB or smaller."	Use a smaller image.
"Choose two different times."	**Light mode at** and **Dark mode at** must differ.
Help shows a dot	One of your reports has a reply or a new status. Open **Help** › My reports (see Report a problem and follow it up).

33. Personalization memory

Save and recall private preferences in plain English across chats and sessions.

Personalization memory belongs to your account, not to one conversation. When service policy and your organization administrator allow it, administrators and regular users can each build their own private memory. A saved item can influence a new chat immediately and still be available after you sign out and return in a later session.

Save a memory in ordinary English

- In any chat, state what should persist in natural language — for example: “Remember that I prefer a short summary before the detail,” “Please remember that I work in commercial litigation,” or “Remember my project codename is Silver Horizon.”
- Send the message. The assistant confirms the memory after it is saved; you do not need a slash command or special syntax.
- Start a new chat, or return in a later sign-in session, and ask a natural question such as “What do you remember about me?”, “What are my writing preferences?”, or “What is my project codename?” The same account memory is available across those sessions.

GOOD TO KNOW

Memory is different from the context window shown in Session details. The context window describes how much of the current chat the selected model can hold at once; personalization memory is durable account context that follows you into other chats and sessions.

Open and control the memory manager

- Click your account card — your name and role at the bottom-left of the sidebar.
- Click Personalization memory. The dialog titled “What the assistant remembers about you” opens.
- Use memory in my chats controls whether saved items are applied to answers. Learn from my conversations controls whether the assistant may notice durable preferences automatically. Turning a switch off does not expose or silently erase existing items.
- To add something directly, type it under Add something you want remembered, choose Standing instructions, Preferences, About you, Your work, or Other details, and click Add.
- Review the list below. Click a memory's wording to correct it; pin an important item; use Forget to remove one item; or choose Forget everything to clear the list.

GOOD TO KNOW

Only you can read your memory content. Administrators can see counts and purge memories for compliance, but the platform never shows them what an individual memory says.

TIP

If Personalization memory is missing from your account drawer, the feature is not currently available at the platform, organization, or group level. Ask your administrator; refreshing the page cannot override that policy.

CAREFUL

Do not use memory as a password or secret vault. Credentials, keys, and sensitive identifiers are rejected on purpose.

WALKTHROUGH · 1:36 · HELP › LEARN

Personalization memory

Save preferences in plain English, recall them in later sessions, and stay in control.

Before you begin

- Memory must be allowed by your platform and your organization. If it is off, the Personalization memory row says why.
- Only you can read your memories. Administrators see how many you have and can delete them, but never read them.

Step by step

1. Select your account card at the bottom of the sidebar. Under Preferences and security, choose Personalization memory.
2. Check Use memory in my chats (applies saved memories to answers) and Learn from my conversations (lets the assistant notice lasting preferences itself).
3. Type a memory in Add something you want remembered, choose its type (for example Preferences), and choose Add.
4. Choose Pin on a memory that should always apply. Choose its text to correct the wording.
5. In any chat, say Remember that … followed by the preference; it is saved for later chats.
6. In a new chat, ask a question the memory answers, and check that the reply uses it.

Path: Forget

1. Personalization memory › Forget on one memory removes it.
2. Forget everything asks Forget all …? This cannot be undone. before removing them all.

Path: Turn memory off

1. Turn off Use memory in my chats to stop applying memories. Saved memories stay private and manageable.
2. Turn off Learn from my conversations to save only what you add or ask it to remember.

Check that it worked

- ✓ The memory is listed in Personalization memory under its type, with Pin on if you pinned it.
- ✓ After Remember that … in chat, the sentence appears in the list.
- ✓ A later chat's reply uses it without being told again, and its work trace says Recalled and a count of memories.

Troubleshooting

WHAT YOU SEE	WHAT TO DO
"Memories cannot contain credentials, keys, or sensitive identifiers."	Passwords, keys, tokens, one-time codes, and card or account numbers are never stored. Keep them out of memory.
"Write a little more so the memory is useful later."	Write a full phrase of at least a few words.
"Pinned memories already fill your memory limit. Unpin or forget one before saving more."	Unpin or forget a memory, then add the new one.
"That memory kind is disabled by your organization's policy."	Choose another type, or ask your administrator.
The row says memory is turned off	"Memory is turned off for this platform.", "… for your organization.", or your groups' policy: ask your administrator. "You turned memory off for your account.": turn it back on here.
No note under the reply says a memory was saved	The reply does not currently show that note. Check Personalization memory to confirm the memory was saved. To see that saved memories were used, expand the work trace: it says Recalled and a count.

34. Install the app on your phone

Put your workspace on the home screen with its own icon and name.

On a phone or tablet, tap **Install app** near the bottom of the sidebar. The “Add … to your home screen” dialog previews your organization's app name and icon.

- On Android, choose **Install app** if offered, then follow the native install sheet. Otherwise open your browser's menu and choose “Add to Home screen” or “**Install app**”.
- On iPhone and iPad, tap the browser's **Share** button, scroll the share sheet, choose “Add to Home Screen”, then tap Add.
- Open the new home-screen icon to return to the same workspace in a full-screen app.

35. Getting help

Walkthrough videos and this guide, always one click away.

- Click **Help** at the bottom of the sidebar for guided videos, captions, transcripts, and this PDF. The guide also covers additional procedures.
- Administrators can also open **Documentation** inside the console for role-specific videos and a printable guide.
- Choose Report a problem in **Help** to describe a problem, the affected screen, and the expected result. **Share** only permitted details with your administrators; omit passwords, keys, and recovery codes.
- Choose My reports in **Help** to see each report's status (Received, In review, In progress, On hold, Resolved, or Closed), read replies, answer questions, or reopen a report that is still a problem.

WALKTHROUGH · 4:06 · HELP › LEARN

Report a problem and follow it up

Send a problem, idea, question, feedback, or security concern to your administrators, then follow its status, answer replies, and reopen it in My reports.

Before you begin

- Any signed-in account. No permission is needed to report.
- What you were doing, what you expected, and what happened. For a problem, the steps that make it happen again.
- Optionally, a screenshot (**PNG**, JPEG, GIF, or WebP, up to 10 MB) with no passwords or personal data.
- Your administrators answer reports in their **Admin console** › Reports.

Step by step

1. Choose **Help** at the bottom of the sidebar, then Report a problem.
2. Under What would you like to send?, choose Problem.
3. Under How much is this affecting you?, choose Blocking me, Slows me down, or Minor.
4. Type a short Subject. In Message, describe what you did, what you expected, and what happened.
5. Optionally add a screenshot: Choose image, Capture screen, or paste or drop an image into the form.
6. Leave Include technical details ticked to send the page, browser, and recent errors (What's included lists them). No chat content is attached.
7. Choose Send report and wait for Report #… sent.

8. Choose View status. My reports opens the report with its tracker at Received.
9. When **Help** shows a dot, choose **Help** › My reports and open the report to read the reply from Support team.
10. To answer, type in Add a reply and choose Send reply.
11. When it is resolved, find it under Closed in My reports.

Path: Idea, Question, or Feedback

1. **Help** › Report a problem, then choose Idea, Question, or Feedback.
2. The form skips How much is this affecting you? and changes its prompts: Idea asks what you'd like to do and the problem it would solve; Question asks anything about how the platform works; Feedback asks what's working well or could be better.
3. Fill in Subject and Message and choose Send report. Follow it in My reports like a problem.

Path: Security

1. **Help** › Report a problem, then choose **Security**.
2. Read the notice: **Security** concerns go only to your administrators and are never posted publicly.
3. Describe what you noticed and where. Do not include passwords, keys, or personal data.
4. Choose Send report. My reports lists it as a **Security** concern.

Path: With a screenshot

1. Choose image picks a file from your device. You can also paste an image, or drop one onto the Screenshot area.
2. Capture screen asks your browser to share the screen; choose this tab. The report panel hides itself for the picture, so the screenshot shows the page behind it.
3. Check the thumbnail for passwords or personal data. Remove screenshot (×) takes it off.
4. **PNG**, JPEG, GIF, or WebP images up to 10 MB are accepted.

Path: Reopen a resolved report

1. **Help** › My reports › Closed, then open the report.
2. Under Still having this problem?, optionally say what is still happening.
3. Choose **Reopen** report. It moves back to Open at Received, and your administrators see that you reopened it.

Check that it worked

- ✓ Report #… sent appeared after Send report.

- ✓ **Help** › My reports lists the report with its type, when it was last updated, and its status.
- ✓ The report's tracker and conversation show each status change and every reply.
- ✓ After **Reopen** report, the report is listed under Open again, at Received.

Troubleshooting


WHAT YOU SEE	WHAT TO DO
"Add both a subject and a message."	Fill in Subject and Message, then choose Send report.
"Choose a PNG, JPEG, GIF, or WebP image." or "Choose a screenshot that is 10 MB or smaller."	Attach a smaller image in one of those formats, or send the report without a screenshot.
"This browser can't capture the screen."	Take a screenshot with your device's own tool, then use Choose image, or paste it into the form.
"The issue report could not be sent."	The report was not received. Check your connection and choose Send report again. The form keeps what you typed in this browser tab.
"You're sending these very quickly. Wait a moment and try again."	You can send up to four reports and ten replies a minute. Wait a minute, then send again.
"This report is closed. Reopen it to add more detail."	It was resolved or closed while you were writing. Go back to My reports, open it, and choose **Reopen** report.
"Your reports could not be loaded."	Check your connection, then open **Help** › My reports again.
No dot on Help after a reply	The workspace checks for news when the page loads and whenever you open **Help** or close a panel. Open **Help** › My reports to check.

PART 6

The Admin console

36. Opening the Admin console

Where the console lives and what its eleven tenant-governance tabs control.



The Admin console opens the workspace controls available to your administrator account. Example workspace with synthetic data.

1. Click **Admin console** near the bottom of the sidebar. (Only workspace administrators and platform owners see it; the account drawer's Workspace section lists it too.)
2. The console opens with eleven tabs across the top: **Users**, **Groups**, **Model Access**, **Connections**, **SSO**, **Analytics**, Reports, Policies, **Datasets**, **Audit**, and **Alerts**. Policies is always present between **Analytics** and **Datasets**; service-wide availability determines which organization controls are active inside it.

Everything you change here writes through the admin API immediately — changes persist across refreshes and restarts, and every action lands in the tenant audit trail. Status messages under the header tell you honestly whether an action synced or failed.

> **TIP**
> The **Documentation** button at the top of the console opens narrated video walkthroughs of every tab, plus this guide as a PDF.

37. Users

Create tenant accounts, manage passwords, and remove leavers safely.

The **Users** tab lists the organization accounts you administer, with each person's role, groups, sign-in method, and status.

Reading and filtering the list

- Use the group filter to work one team at a time.
- Watch the Auth and Status columns: Auth shows sso or local, and Status shows Active, Inactive, or **Pending** for an approved person who has not signed in yet. When the default group is on, new **SSO** accounts start in **Default Users**; otherwise they have no groups until you add them.

Per-row actions

Every row has an Actions column with account controls:

- **Access** — opens the read-only **Model access trace** for this person, with their groups, each model's status, and the gates that explain it. See Resolve model requests and trace access for the full workflow.
- **Password** — opens the password dialog for that person: type a password or click **Generate** for a strong random one, optionally mark it a **Temporary password** (they must choose their own at first sign-in), and click **Set password**. The password is shown only here — share it over a safe channel.
- **Deactivate / Activate** — ends or restores sign-in access immediately, keeping the account's audit history intact. You can also select several accounts with their checkboxes and use the **Deactivate** button at the top.
- **Delete** (trash icon) — permanently deletes an eligible account and its chat history. The tooltip spells it out per person: “Permanently delete … and their chat history”. Administrator-account actions that are unavailable under current service policy remain disabled with an explanation.

GOOD TO KNOW

Password reset and authenticator recovery are separate. The current **Users** screen has no authenticator-reset action. If someone has lost their authenticator and recovery codes, verify their identity and follow the organization's authorized recovery process; setting a temporary password alone does not clear MFA. Identity-provider recovery remains with the **SSO** provider.

GOOD TO KNOW

Administrative continuity rules are enforced by the service. When an account action would violate them, the console blocks the action and explains that it is restricted by administrative continuity policy.

WALKTHROUGH · 3:29 · ADMIN CONSOLE › DOCUMENTATION

Approve access and finish sign-in

Take a real access request from the sign-in page to a working first chat, by temporary password or by organization SSO, and decline a request you do not recognize.

Before you begin

- An Admin account. **Admin console** › **Users** shows the **Access requests** panel only while someone is waiting.
- A model granted to **Default Users** in **Model Access**, so the approved person has something to chat with.
- For the **SSO** path: single sign-on already set up on the **SSO** tab, and the person's account at your identity provider with a verified email on an allowed domain.
- A safe way to share a temporary password, such as in person or your password manager's sharing. Aperture Chat sends no email.

Step by step

1. The person opens your workspace address, chooses **Request access**, enters First name, Last name, and Work email, and chooses Submit access request. They see Request received.
2. Choose **Admin console** at the bottom of the sidebar. **Users** opens with an **Access requests** panel that lists each person's name, email, and request time.
3. Check that you recognize the person and the email address.
4. In **Approve** as, keep User, then choose **Approve**. The status reads "… was approved as User."
5. In Finish sign-in setup, choose Set temporary password.
6. Choose **Generate** (or type at least 12 characters), keep **Temporary password** on, and choose **Set password**.
7. Choose **Copy**, share the password over your safe channel, then choose **Done** in the dialog and **Done** in Finish sign-in setup. The row now shows local under Auth.
8. The person chooses Email & password on the sign-in page, signs in with the temporary password, enters their own password twice on Set a new password, and chooses **Set password** and continue.
9. They land on the welcome card. Ask them to start a new chat, choose a model, and send a short message.
10. Confirm that a reply arrives. That proves the approval, the group, model access, and sign-in all work.

Path: Organization SSO, no password (shown)

1. Make sure single sign-on is set up on the **SSO** tab and the person has an account at your identity provider with a verified email on an allowed domain.
2. **Approve** the request as User. In Finish sign-in setup, choose **Done**. Do not set a password.
3. Tell the person to open the workspace, enter their work email, and choose **Continue with SSO**.
4. They sign in at the identity provider and land on the welcome card.
5. **Users** shows the account Active, with sso under Auth.

Path: Decline a request (shown)

1. In **Access requests**, choose **Decline** on the request you do not recognize. There is no confirmation step.
2. The status reads "… access request was declined." The pending account is deleted.
3. If that person tries to sign in, they see "Unknown local account." They can submit a new request later.

Path: Approve as Temp User or Admin

1. Temp User gives access to the designated Luna model only and stops after 30,000 reported tokens. It needs an enabled Luna model.
2. Admin appears in **Approve** as only when service policy allows it. Otherwise Policies › **Policy Controls** notes "Administrator accounts are created by your service team."
3. Arrange sign-in the same way: a temporary password or organization **SSO**.

Check that it worked

- ✓ The status reads "… was approved as User." and the request leaves the queue.
- ✓ **Users** shows the person Active, with local under Auth after a password is set, or sso for the **SSO** path.
- ✓ The person reaches the welcome card and gets a real reply to a first message.
- ✓ A declined person's sign-in attempt shows "Unknown local account."

Troubleshooting

WHAT YOU SEE	WHAT TO DO
"Access was not approved. This access request is no longer pending."	Another administrator already approved or declined it. Reload **Users** to see the current queue.
"Access was not approved. Enable a Luna model for this workspace before approving temporary access."	**Approve** as User instead, or ask your service team to enable a Luna model.
The approved person sees "Unknown local account."	Approved accounts start as **SSO** accounts. Set a temporary password (Finish sign-in setup, or **Password** in the row's Actions), or have them use **Continue with SSO**.
"Invalid local credentials."	The temporary password was mistyped. Set a new one; each new password replaces the last.
Set password stays unavailable in the password dialog	Passwords need at least 12 characters. Choose **Generate**.
The person's model menu reads No models available	None of their groups carries a model. Grant one to **Default Users** in **Model Access**, or choose **Access** on their **Users** row to see why.
"Too many access requests for this email. Try again shortly."	The sign-in page accepts three requests per email in a short window. Wait a minute, then submit once.

WALKTHROUGH · 2:39 · ADMIN CONSOLE › DOCUMENTATION

Users and accounts

Create SSO and password accounts, change roles, reset passwords, deactivate and reactivate, work in bulk, filter by group, explain model access, and delete leavers.

Before you begin

- An Admin account. You manage User, Temp User, Power User, Auditor, and **Agent** Approver accounts; admin rows are locked.
- A group to start people in. **Default Users** always exists.
- For password accounts: a safe way to share a temporary password.

Step by step

1. Choose **Admin console** at the bottom of the sidebar. **Users** is the first tab.
2. Choose **Add User**. Enter Name and Email, then choose a Role and a Starting group.

3. Choose **Create Account**. The status reads "… was created through the admin API." The new row shows sso under Auth.
4. For someone who signs in with a password, choose **Password** in the row's Actions, then **Generate**, keep **Temporary password** on, and choose **Set password**. Auth changes to local.
5. To change a role, choose it in the row's Role menu. It saves immediately.
6. To pause access, choose **Deactivate** in the row's Actions. Choose **Activate** to restore it.
7. To delete a leaver, choose the trash button in the row's Actions. Deletion is immediate and permanent.

Path: An SSO account (shown)

1. **Add User** creates an account that signs in through organization **SSO**: Auth reads sso.
2. **Share** the workspace address; the person enters their email and chooses **Continue with SSO**.
3. Without **SSO** set up, the account cannot sign in until you set a temporary password.

Path: A password account (shown)

1. **Add User** as above, then choose **Password** in the row's Actions.
2. Choose **Generate**, keep **Temporary password** on, choose **Set password**, then **Copy**.
3. **Share** the password safely. The person chooses their own at first sign-in.

Path: Several accounts at once (shown)

1. Tick the checkbox at the start of each row.
2. Choose **Deactivate** at the top of the list. The status reads "Deactivated N users through the admin API."
3. Bulk deactivation also deletes each person's saved personalization memories. A row's own **Deactivate** button keeps them.
4. Reactivate people one at a time with **Activate**.

Path: Explain one person's model access (shown)

1. Choose **Access** in the person's row.
2. Each model shows **Usable**, **Allowed, provider offline**, or **Blocked**, with every gate the policy checked.
3. The trace explains; it changes nothing. Fix access in **Groups** or **Model Access**.

Check that it worked

- ✓ New rows show the role, group, and Auth you chose.

- ✓ A deactivated row reads Inactive; **Activate** returns it to Active.
- ✓ After deletion the row is gone and the status reads "… was permanently deleted."

Troubleshooting

WHAT YOU SEE	WHAT TO DO
"User was not created. User email already exists."	Someone already has that address. Set Filter users by group to All groups and find them.
"Pick a starting group first — create one on the Groups tab if none exist yet."	**Create** a group on the **Groups** tab, then add the user again.
The Password button is unavailable	Passwords can be set only for active accounts other than yours and other administrators'. Reactivate the account first.
"Reactivate the account before setting its password."	Choose **Activate** in the row's Actions, then set the password.
"… was not deleted. Tenant admins can only delete regular users in their own tenant."	Administrator accounts are managed by your service team.
"This action is blocked by administrative continuity policy."	The change would leave the organization without an administrator. Ask your service team.
A password reset did not reset two-step verification	Correct: **Password** does not reset the authenticator, and this screen has no authenticator reset. Verify the person's identity through your organization's recovery process and contact your service team.

38. Groups

Groups carry permissions and model access — everything flows through them.

Groups are how access flows in the tenant: model grants, knowledge access controls, and permissions all attach to groups, not to individual people. Someone in no group has no group-based access, and a group that **SSO** group mapping manages follows the identity provider at every sign-in.

Runtime access and authoring permissions

TOGGLE	WHAT IT GRANTS
Can use chat	Start conversations and use assigned models.
Can use knowledge	Query approved knowledge bases.
Can use agents	Run approved agent workspaces.
Can use tools	Invoke enabled tools and MCP actions.
Can use API	**Create** personal keys for approved models when service policy allows API access.
Can use Hermes companion	Build and run agent profiles with the **Hermes** learning companion. Off until approved.
Can build agents	**Create** private agent profiles when service policy permits. Organization publishing stays admin-only.
Can build knowledge bases	**Create** private knowledge bases. Group sharing and organization management stay admin-only.
Can add API sources	Connect API endpoints, with keys or provider sign-in, to their own knowledge bases. Off until approved; needs Can build knowledge bases.
Can build tools	Add their own private MCP connections. Off until approved. Group sharing and stdio commands stay admin-only.
Can use memory	Allow personal preferences to be learned and reused within the workspace memory policy.

CAREFUL

Deleting a group removes its members' access that flowed through it. Check what the group grants before deleting.

WALKTHROUGH · 2:05 · ADMIN CONSOLE › DOCUMENTATION

Groups and permissions

Create a group, add people one at a time or by pasting emails, set each permission, and know how the protected Default Users group behaves.

Before you begin

- An Admin account.
- The people's accounts already exist. **Import** adds existing accounts only.

- **Can use API** stays locked while service policy keeps downstream API access off.

Step by step

1. Choose **Admin console** › **Groups**, then **Add Group**.
2. Enter a Group name and choose **Create** group. Leave Optional **SSO** group ID empty unless you use it.
3. Choose Manage on the new group's card.
4. On the group's **Users** tab, switch on each person you want in the group.
5. On the **Import** tab, paste email addresses (one per line, or separated by commas) and choose **Add users to group**.
6. On the **Permissions** tab, switch each permission on or off. Each switch saves immediately.
7. Open **Users** and choose the group in Filter users by group to confirm its members.

Path: Add people one at a time (shown)

1. Open the group with Manage, then its **Users** tab.
2. Switch on Add … to the group for each person. The pill changes to In group.

Path: Import by email (shown)

1. Open the group's **Import** tab and paste the addresses.
2. Choose **Add users to group**. Existing accounts are added; unknown addresses and administrator accounts stay in the box.

Path: Let SSO manage membership

1. On the **SSO** tab, map an identity-provider group value to this group (see Tenant **SSO** and provisioning).
2. Membership then follows each person's next **SSO** sign-in.

Path: Remove a group

1. Choose the trash button on its card, or tick several cards and choose Remove selected. There is no confirmation step.
2. Members lose the access that came through that group. **Default Users** cannot be removed.

Check that it worked

- ✓ The group's card shows the member count.
- ✓ **Users** filtered to the group lists exactly its members.

- ✓ Each permission you changed shows its new switch position, and the status reads "… group permissions synced with the admin API."

Troubleshooting

WHAT YOU SEE	WHAT TO DO
"Group was not created. Group name already exists."	Choose a different name, or manage the existing group.
"Group name is required before creating a group."	Enter a Group name before choosing **Create** group.
"No users were added to …. No eligible platform users were found for …."	Those addresses have no account, or belong to administrators. **Create** the accounts on **Users** first; the addresses stay in the box so you can retry.
Can use API reads "Downstream API access is unavailable under the current service policy."	Service policy controls downstream API access. Ask your service team.
"Default Users is protected by organization policy and cannot be removed."	**Default Users** is the baseline group. Adjust its permissions and models instead.
Can build agents is on, but people still cannot build agents	It also needs service policy to allow user-built agents. Policies › Default users can build agents shows whether it does.
A person sees "Connecting APIs needs approval. Ask your administrator to turn on Can add API sources for one of your groups."	Turn on Can add API sources for one of their groups. It works only with Can build knowledge bases, because API sources live inside a person's own knowledge base.
A person sees "Needs Hermes approval from your administrator"	Turn on **Can use Hermes companion** for one of their groups. Until then **Hermes** agents and **Hermes** connections stay locked for them.

39. Model Access

Decide which synced models users can see, and which groups can use them.

Model Access starts from the catalog available to your organization. You decide what portion of it your users actually see.

The catalog at a glance

- Click **Sync models** to refresh the catalog whenever service availability changes.

- Read the counters: the All, Enabled, and Disabled status counters carry live totals alongside how many groups are available for scoping.
- Use the search box and the funnel filters in the column headers to cut through the catalog: check off providers, check off model labs, or type text to match runtime routes, and Clear filter resets one. The table has seven columns: **Model**, **Provider**, **User Access**, **Groups**, **Filters**, **Knowledge**, and **Tools**. Everything starts hidden until you decide otherwise.
- Flip the **User Access** toggle on a row to make that model visible, and use **Choose groups** to narrow it to specific teams.
- Use the **Filters** column to attach per-model content filters, and the **Knowledge** and **Tools** columns to scope what each model may search and call.

GOOD TO KNOW

Because model access flows through groups, a tenant with no groups yet sees the guard up front — "**Create** a group before enabling models." — and the access switches stay off until one exists.

GOOD TO KNOW

Newly synced models arrive disabled until service availability and organization policy permit them. If a model you expect is missing, it is not currently available to this organization.

WALKTHROUGH · 1:51 · ADMIN CONSOLE › DOCUMENTATION

Tenant model access

Grant a model to the right groups, check the effect for one person in the access trace, and hide a model when you need to.

Before you begin

- An Admin account and at least one group.
- **Models** your service team has made available to your organization.
- **Access** is granted to groups only. There is no per-person grant or deny.

Step by step

1. Choose **Admin console** › **Model Access**, then **Sync models**.
2. Find the model with **Search** model names or the funnel filters in the column headings.
3. In the model's **Groups** column, choose the groups button (**Choose groups**, or N groups).
4. Tick each group that should use the model (Allow … for …). Each tick saves immediately.
5. On **Users**, choose **Access** for someone in that group. The model reads **Usable**, with group_grant passed.

Path: Grant or remove a group (shown)

1. Open the model's groups and tick or untick a group.
2. Members of a ticked group can use the model; the trace for someone outside it stops at group_grant.

Path: Hide a model from everyone (shown)

1. Turn off the model's **User Access** switch. The row reads Hidden from users.
2. Today only your service team can turn it back on: the switch is refused with "This model is not available to this organization." The same happens if you untick its last group.
3. To narrow access without hiding it, keep at least one group ticked.

Path: Give one person a model

1. **Create** a group for them (or use an existing one) and tick it on the model.
2. Or approve their request on **Model Access** (see Review model requests and explain access).

Check that it worked

- ✓ The **User Access** column reads Visible to N groups.
- ✓ The access trace for a member shows the model **Usable**, or **Allowed, provider offline** if only the provider is down.
- ✓ The person sees the model in their model menu.

Troubleshooting

WHAT YOU SEE	WHAT TO DO
"… user access could not sync. This model is not available to this organization. Nothing was changed."	The model has no groups from your organization left, so it can no longer be changed here. Ask your service team to restore its groups. Keep one group ticked when narrowing access.
"Create a group before enabling models."	**Create** a group on the **Groups** tab first. **Users** get models only through groups.
The trace reads Allowed, provider offline	The grant works, but the provider behind the model is not connected. Your service team reconnects it.
"Model is disabled by platform policy."	The model is turned off for the whole service. Ask your service team.
A model is missing from the catalog	Choose **Sync models**. If it is still missing, it has not been made available to your organization. Ask your service team.

40. Resolve model requests and trace access

Review requests through groups and diagnose each user's actual model access.

CAREFUL

Approval changes group membership. When the chosen group does not carry the model yet, it can also widen that model's availability for all group members. Review the group's purpose and members before approving.

GOOD TO KNOW

The trace is read-only and scoped to users you can administer. It explains existing permissions; opening it does not grant access, change a role, or bypass the organization's model ceiling.

WALKTHROUGH · 1:37 · ADMIN CONSOLE › DOCUMENTATION

Review model requests and explain access

Approve a person's model request into the right group, decline another, and confirm both from the person's view and the access trace.

Before you begin

- An Admin account and the groups you grant through.
- **Model** requests allowed by service policy. When they are not, people see only the models they can already use and cannot send requests.

Step by step

1. The person opens the model menu, chooses **Why isn't a model listed?**, and chooses **Request access** on a **Locked** model. They see "Request sent for …. An administrator will review it."
2. Choose **Admin console** › **Model Access**. **Access requests** lists the person, the model, and the server's reason.
3. In **Grant through group**, choose the narrowest group that should carry the model. A group marked (also grant model to group) does not carry it yet; approving grants it to every member.
4. Choose **Approve**. The panel reads "… can now use … through …."
5. Choose **Decline** for requests you will not grant. The panel reads "Declined the request from …."
6. Ask the person to reopen **Why isn't a model listed?**, and check **Users** › **Access** for them.

Path: Approve through a group that already has the model

1. Choose a group listed without a suffix. Approving adds the person to it; nobody else gains access.

Path: Approve and widen a group (shown)

1. Choose a group marked (also grant model to group).
2. Read the hint: approving grants the model to everyone in the group. Check its members first.

Path: Decline (shown)

1. Choose **Decline**. The request leaves the queue, and the person's model reads **Locked** again with **Request access** available.

Check that it worked


- ✓ The panel reads "… can now use … through …." and the request leaves the queue.
- ✓ The person's **Models in your organization** dialog no longer shows the model as **Locked**.
- ✓ **Users** › **Access** for the person shows group_grant passed for that model.

Troubleshooting

WHAT YOU SEE	WHAT TO DO
"Choose the group that should carry this model before approving."	Choose a group in **Grant through group**. If one is already shown, choose another group and then the one you want.
"Approved, but the server still reports: …"	The approval worked but another gate still blocks the model, such as an offline provider. The trace shows which.
"This request has already been resolved."	Another administrator approved or declined it. Choose **Refresh**.
Approve is refused because the model is disabled for the whole service	Ask your service team to enable the model, then approve again.
The person sees "Model access requests are disabled by organization policy."	Service policy does not allow model requests. Grant access through a group instead.
The person sees "A request for this model is already pending."	Their earlier request is still in your queue.

41. Connections: workspace connectors

Turn sources and tools on or off, configure and test them, and hide cloud sources from the attach menu.



Admin console → Connections → Connectors: each source's switch, Configure, Hide, and test results for this workspace. Example workspace with synthetic data.

Admin console → Connections → Connectors lists the sources and tools for this workspace: **Web Search**, Google Drive, OneDrive / SharePoint / Outlook, Box, iManage, MCP, and the other connectors your deployment allows. Off removes a connector everywhere: chat, pickers, the tool library, and the API. Hide only takes a cloud source out of the attach menu, so people don't see it as an option.

- Use a connector's switch to turn it on or off for everyone in this workspace. The status confirms it, for example “Box is now off for everyone in this workspace.”
- Choose **Configure** to fill in the connector's settings and secret, then Save configuration. Secrets are stored encrypted and are never shown again; replace them by saving a new value.
- Choose **Test connection** after saving. The result reports what the provider actually returned; a test before saving says Save the configuration first, then test the connection.
- Choose Hide on Google Drive, OneDrive / SharePoint / Outlook, Box, or iManage to take it out of the attach menu without switching it off. It shows a Hidden pill until you choose Show.
- A connector marked Off for all workspaces has been switched off for every workspace by your service team. You cannot turn it back on from this workspace until they allow it again.

GOOD TO KNOW

Users still connect their own Google, Microsoft, Box, or iManage account from the attach menu, and those delegated connections respect each person's own source permissions. The workspace configuration here supports sign-in and background knowledge sync; it never grants someone else's files.

Configure and test a source

- Choose **Configure** on the source row. Select Authentication method and fill in the fields shown for that method. Read the source's setup notes for its required permissions and redirect URI.
- Choose Save configuration. For an existing saved secret, leave its password field blank to retain it, or enter a new value to replace it. Wait for the save result before testing.
- For Google OAuth, save the client ID and secret first, then choose **Connect Google** Drive to authorize the workspace account used for knowledge sync. Complete the consent flow before checking the connection.
- Choose **Test connection** and read its result and individual checks. An incomplete, failed, or missing result is not proof of access. Resolve the reported issue before relying on the source.
- Set the source's switch and verify the resulting status. **Configure** the intended users' source-account access separately when they will attach files in chat.

SOURCE	CONFIGURATION SHOWN BY THE FORM
Google Drive	Google OAuth client ID and secret, with an optional Drive folder ID and source label. Paste access token is a testing option.
OneDrive / SharePoint / Outlook	Microsoft Graph directory ID, application ID, and client secret for app-only access, with optional site, drive, and root-folder IDs.
Box	**Client ID**, enterprise ID, and client secret for Client Credentials Grant; an optional folder ID limits the starting location. Developer token is a testing option.
iManage	Instance URL, API key (client ID), and OAuth client secret for Each user signs in. Service account for background sync adds the service username and password; chat still requires each user's OAuth sign-in.

Clear saved configuration

Clear configuration removes the source's saved fields, stored secret, shared OAuth data, and service-account password, and disables its saved configuration. Use it only when that removal is intended. An empty secret field alone retains the saved secret; clearing all visible fields and saving an existing configuration also performs a clear.

Web Search

Choose **Configure** on **Web Search**, then select **Search** engine and Results per search (1 to 10). DuckDuckGo is keyless. SearXNG requires an instance URL with JSON search output enabled. OpenAI, Anthropic, and OpenRouter choices use the corresponding saved provider key and bill searches to that provider account. Choose Save configuration, then **Test connection** to run a real query.

The engine choice applies to models without hosted web search of their own. OpenRouter-backed models use OpenRouter's built-in search regardless of this selection. The **Web Search** switch still governs availability for the workspace.

WALKTHROUGH · 5:50 · ADMIN CONSOLE › DOCUMENTATION

Manage workspace connectors

Turn sources on for your workspace, configure and test web search and each cloud file source, hide a source from the attach menu, and recognize a source your service team has turned off.

Before you begin

- An Admin account.
- For cloud sources: an administrator at the vendor (Google Cloud, Microsoft Entra, Box, or iManage) who can register an application and grant consent.
- Your workspace's address. Connector redirect URIs are that address followed by /api/connector-oauth/callback.
- For SearXNG: your own instance's address, with JSON output allowed. For OpenAI, Anthropic, or OpenRouter web search: an active key for that provider, which your service team adds.

Step by step

1. Choose **Admin console** › **Connections**. **Connectors** lists every source and tool for this workspace.
2. Turn a source on with its switch. The status reads "… is now on for everyone in this workspace." Off removes it everywhere: chat, pickers, the tool library, and the API.
3. Choose **Configure** on **Web Search**, pick a **Search** engine and Results per search, and choose Save configuration.
4. Choose **Test connection** and read every line of the result.
5. For a cloud source, do the vendor steps first (see the paths), then choose **Configure**, pick the Authentication method, fill in the vendor's values and the secret, and choose Save configuration.
6. Choose **Test connection** and read the result. For Google Drive, finish with **Connect Google** Drive.
7. To keep a cloud source out of people's attach menu without turning it off, choose Hide. The row reads Hidden; choose Show to offer it again.

8. Check from a person's account: the chat paperclip menu lists only the sources you have not hidden.

Path: Web Search (shown)

1. **Configure** › **Search** engine: DuckDuckGo (keyless), SearXNG (your own instance), or OpenAI, Anthropic, or OpenRouter web search.
2. DuckDuckGo needs no key, but it limits automated searches from busy servers, and the server must be able to reach it; the test names the reason when it fails.
3. SearXNG: enter the SearXNG instance URL. The instance must allow JSON output (search.formats must include json). **Test connection** runs a real search.
4. OpenAI, Anthropic, or OpenRouter web search reuse that provider's key, and each search is billed to that account. Your service team adds provider keys.
5. Results per search: how many results are added to the prompt as cited context, 1 to 10.

Path: Google Drive (shown)

1. In Google Cloud, enable the Drive API, set up the Google Auth Platform with the drive.readonly scope, and create a **Web** application client with the redirect URI.
2. **Configure** › Google OAuth (recommended): OAuth client ID, optional Drive folder ID and Source label, and the OAuth client secret. Save configuration.
3. Choose **Connect Google** Drive and sign in with the workspace account used for knowledge sync, then **Test connection**.
4. People connect their own Google account from the attach menu and see only their own files.

Path: OneDrive / SharePoint / Outlook (Microsoft Graph) (shown)

1. In Entra, register a single-tenant app, add Files.Read.All (and Sites.Read.All) as application permissions, grant admin consent, and create a client secret.
2. **Configure** › App-only (client credentials, recommended): Directory (tenant) ID, Application (client) ID, optional SharePoint site, Drive, and Root folder IDs, and the **Client secret**. Save configuration.
3. **Test connection** requests a token and calls Graph.
4. For chat attachments, also add the scopes as delegated permissions and the **Web** redirect URI.

Path: Box (shown)

1. In the Box Developer Console, create a Server app with Client Credentials Grant, App + Enterprise **Access**, and Read all files and folders; a Box admin authorizes it in Admin Console › Platform › Platform Apps.

2. **Configure** › Client Credentials Grant (recommended): **Client ID**, Enterprise ID, optional Folder ID, and the **Client secret**. Save configuration, then **Test connection**.
3. For chat attachments, also enable OAuth 2.0 (Authorization **Code**) on the app with the redirect URI.

Path: iManage (shown)

1. In iManage Control Center, add a **Web**, confidential application with the redirect URI and refresh tokens allowed.
2. **Configure** › Each user signs in (recommended): Instance URL, API key (client ID), Customer ID, **Library** ID, optional Workspace ID, and the OAuth client secret. Save configuration.
3. **Test connection** confirms the settings; each person completes verification by opening iManage from chat and signing in.
4. Service account for background sync is only for knowledge sync; chat always uses each person's own sign-in.

Path: Hide a cloud source (shown)

1. Choose Hide on Google Drive, OneDrive / SharePoint / Outlook, Box, or iManage. Its switch and credentials stay as they are, so knowledge sync keeps running.
2. People no longer see it in the chat or **Drafts** attach menu. Choose Show to offer it again.

Path: A source off for every workspace (shown)

1. When your service team turns a source off for every workspace, its row reads Off for all workspaces and its switch is locked off.
2. Your saved settings stay. Ask your service team to allow it again; then your own switch decides.

Check that it worked

- ✓ The switch shows the new state, and the status reads "… is now on for everyone in this workspace."
- ✓ **Web Search**'s **Test connection** reads "**Web search** is working through …" with a live result.
- ✓ A cloud source's **Test connection** lists Required fields, Authentication, and API access as passed, or names the next step.
- ✓ After Hide, the row reads Hidden and a person's paperclip menu no longer lists the source.

Troubleshooting

WHAT YOU SEE	WHAT TO DO
"Web search test failed: DuckDuckGo returned a page with no parseable results (it rate-limits automated queries). …"	DuckDuckGo limits automated searches from busy servers. Retry later, or switch to SearXNG or a provider's web search.
"Web search test failed: DuckDuckGo request failed: ConnectTimeout"	The server could not reach DuckDuckGo in time. Check that your deployment can reach the internet, retry, or choose SearXNG.
"Set the SearXNG instance URL, or switch the engine to DuckDuckGo."	Enter your SearXNG instance URL, or choose DuckDuckGo.
"OpenAI web search reuses the workspace's OpenAI provider key. Add an active OpenAI key under Providers, or switch to a keyless engine."	**Provider** keys are added by your service team. Ask them for the key, or choose DuckDuckGo or SearXNG.
"Google Drive is not connected: no refresh token is stored. …"	Save the client ID and secret, then choose **Connect Google** Drive and finish Google's consent screen.
"Microsoft Graph token request failed: token endpoint returned HTTP 400: AADSTS90002: Tenant '…' not found. …"	The Directory (tenant) ID is wrong. **Copy** it from the app's Overview page in Entra.
"Box token request failed: token endpoint returned HTTP 400: The client credentials are invalid"	Check the **Client ID** and secret, and that a Box admin authorized the app in Platform Apps.
"Fill in: …"	A required field (marked *) or the secret is empty. Fill it in and save again.
A row reads Saved · disabled	Its credentials are saved, but the source is switched off in this workspace. Turn its switch on.
A row reads Off for all workspaces and its switch is dimmed	Your service team has turned the source off for every workspace. Ask them to allow it again.

42. Connections: response actions and Library connections

Add admin-approved buttons to replies and know where MCP connections are managed.

Chat output actions

Chat output actions, also on the **Connections** tab, adds admin-approved buttons to assistant responses for export, formatting, or handoff. Choose New response action to create one; existing custom actions offer Edit and **Delete**. Each row shows Enabled or **Draft** and an enable switch. Creating these actions does not configure a source connector.

MCP connections and model-callable tools remain in **Library** → **Tools** → **Connections**. **Prompts** and **Skills** also remain in the **Tools** library. People add their own MCP connections only with Can build tools. When the MCP Servers connector is off in **Connectors**, nobody can use these connections.

WALKTHROUGH · 2:38 · ADMIN CONSOLE › DOCUMENTATION

Response actions and Library connections

Build a script response action, test it, give it to a group, use it on a real reply, edit or draft it, and find where tool connections are signed in.

Before you begin

- An Admin account.
- A short Python script: it reads the reply on standard input and prints the result.
- The group whose members should see the button.

Step by step

1. Choose **Admin console** › **Connections** and scroll past **Connectors** to **Chat output actions**. It lists every tool; response actions carry a Response action pill.
2. Choose New response action. Enter Action name, Timeout (seconds, 1–30), Description, and the Python script.
3. Under Who can run this action, tick the groups that should see it. With none ticked, everyone can.
4. Under Test run, paste sample text and choose Run test. Read "Finished in … ms." and the output.
5. Choose **Create** action. The status reads "… saved and available to models and chat." and the row reads Enabled.
6. A member opens any assistant reply and chooses the action's button below it. The result opens with **Copy** and **Download**.
7. Choose Edit to change it, or switch it off to set it to **Draft** and hide it from replies.

Path: Script response action (shown)

1. The script receives the reply text on standard input and prints its result.

2. To return files, write them to the folder in APERTURE_ARTIFACT_DIR: up to 8 files, 50 MB each and 75 MB per run. Links appear in the output.
3. Scripts run isolated, without platform secrets or provider keys, but can reach the network.

Path: Sign a connection in (OAuth)

1. Open **Library** › **Tools** › **Connections**, choose Edit on the connection, then Sign-in.
2. Register the Redirect URL at the provider, then choose Connect with provider and approve there.
3. The badge changes from Not signed in to Signed in — token saved.

Path: Remove an action

1. Choose the trash button on its row. It is deleted for the whole workspace at once, with no confirmation.

Check that it worked

- ✓ Run test shows "Finished in … ms." with the expected output.
- ✓ Members of the chosen group see the action's button on assistant replies, and it returns the result.
- ✓ After switching to **Draft**, the row reads **Draft** and the button no longer appears on replies.

Troubleshooting

WHAT YOU SEE	WHAT TO DO
"Script has a syntax error on line …"	Fix the line named in the message and run the test again.
"The script timed out."	Raise Timeout (up to 30 seconds) or simplify the script.
"The script exited with an error (code 1)."	Read the error output under the result and fix the script.
"Script cannot be empty. It reads input from stdin and prints its result."	Enter a script before saving.
A member does not see the button	Check that the action is Enabled and that one of their groups is ticked under Who can run this action.
A sign-in page reads "Sign-in link expired"	Start sign-in again from the connection's Sign-in tab with Connect with provider. The Authorize shortcut on **Connections** does not complete sign-in today.

43. Automations: preparing scheduled runs

What admins need to configure before users can rely on recurring model chains.

Users create and run automations from the Automations tab of the **Agents** view, and enabled schedules fire automatically in the background, delivering each run's output as a new chat or draft. Admins manage group and model access and the workspace connectors in **Connections**. Check the actual failure details to determine which setup needs attention.

Admin readiness checklist

1. Open **Model Access** and confirm the automation's model is visible to the user's group.
2. Open **Groups** and confirm the user belongs to the group that receives the model grant.
3. Open **Connections** and confirm any connector the automation needs is on, configured, and passes **Test connection**. **Users** complete their own source-account connection when the workflow needs delegated access.
4. If the automation uses knowledge, confirm the knowledge base is enabled and its source ACL allows the user's group.
5. Ask the user to press **Run now** after saving the automation; the transcript and last-run status will show whether the setup is complete.

GOOD TO KNOW

Admins do not need to expose every model to make automations work. Grant the smallest approved model set that fits the scheduled workflow, then expand only when a run proves it needs more capability.

44. SSO: single sign-on for your tenant

Connect an identity provider, provision on first sign-in, and map IdP groups.

The **SSO** tab lists every identity provider for your tenant as a card. When **Policy Controls** shows **SSO** configuration as available, you can add providers for your domains, test them, map identity-provider groups to tenant groups, and enforce **SSO**. Otherwise the tab is read-only and says so.

WALKTHROUGH · 4:53 · ADMIN CONSOLE › DOCUMENTATION

Tenant SSO and provisioning

Set up your organization's single sign-on from the Admin console: check that policy allows it, create and test the connection, sign a test person in, map groups, enforce it, and recognize the read-only state.

Before you begin

- An Admin account, with **SSO** management allowed by service policy: the **SSO** tab shows **Add SSO configuration**. If it shows "Organization policy makes **SSO** configuration read-only in this console." instead, ask your service team.

- An OpenID Connect application at your identity provider, with its issuer URL, client ID, and client secret, or your own WorkOS account with its client ID and API key. The paths below list the exact settings for Keycloak, Microsoft Entra ID, Okta, Google Workspace, and WorkOS.
- The redirect URI shown under the **Add SSO configuration** form, registered exactly at the identity provider.
- A groups claim in the ID token if you will map groups. Google sends none.
- A test account at the provider with a verified email on one of your domains.

Step by step

1. Choose **Admin console** › **SSO**. If it reads "Organization policy makes **SSO** configuration read-only in this console." and has no **Add SSO configuration** button, ask your service team to allow **SSO** management.
2. Choose **Add SSO configuration**.
3. In **Identity provider**, choose your preset: Microsoft Entra ID, Google Workspace, Okta, Custom OIDC provider, or WorkOS (AuthKit).
4. Enter the Issuer URL, **Client ID**, and Allowed email domains. Keep Provision new users on first sign-in (JIT) on.
5. Register the redirect URI shown under the form at your identity provider.
6. Paste the **Client secret** last, then choose **Create SSO** configuration. Enforcement starts off.
7. On the new card, choose **Test connection**. Discovery document, Signing keys (JWKS), and Sign-in readiness must all pass.
8. In a private window, enter the test person's email, choose **Continue with SSO**, and sign in at the provider. **Users** then lists them with sso under Auth.
9. On the card, choose Add mapping for each identity-provider group value, choose the tenant group, and choose Save mappings.
10. Have the test person sign in again, then check **Users** with Filter users by group.
11. When everyone can sign in through the provider, turn on Enforce for tenant sign-in.
12. Confirm that a local password on the domain is now refused.

Path: Custom OIDC provider, such as Keycloak (shown)

1. Choose Custom OIDC provider. Enter the issuer, such as https://your-keycloak-host/realms/your-realm.
2. At Keycloak: a confidential client with Client authentication on, Standard flow, Require PKCE S256, the redirect URI, and a Group Membership mapper named groups with Full group path off.
3. Map group values exactly as they appear in the token, such as litigation.

Path: Microsoft Entra ID

1. Choose Microsoft Entra ID. The issuer is prefilled; replace `{tenant-id}` with your Directory (tenant) ID. Never use common or organizations.
2. Use the client secret's Value, not its Secret ID.
3. At Entra: App registrations › New registration (**Web**, the redirect URI), Certificates & secrets › New client secret, and Token configuration › Add groups claim. Group claims carry object IDs, so map each group's object ID.

Path: Okta

1. Choose Okta. The preset fills https://{your-domain}.okta.com; replace it with your Okta domain.
2. At Okta: Applications › **Create** App Integration › OIDC, **Web** Application, Authorization **Code**, the redirect URI. For group mapping, use the custom authorization server, https://your-org.okta.com/oauth2/default, and add a groups claim to the ID token.

Path: Google Workspace

1. Choose Google Workspace. The issuer is https://accounts.google.com.
2. Google ID tokens carry no groups, so manage group membership on the **Groups** tab instead of mapping.

Path: WorkOS (AuthKit)

1. Choose WorkOS (AuthKit). WorkOS runs the sign-in page with your own WorkOS account; there is no issuer URL.
2. Enter the WorkOS client ID and WorkOS API key from **API Keys** in the WorkOS dashboard. The WorkOS organization ID is optional: with it, everyone goes straight to that organization's sign-in.
3. In the WorkOS dashboard under Redirects, add the redirect URI shown under the form. After creating, add the Initiate login URI the card lists.
4. **Test connection** checks API key, **Client ID**, and Organization with WorkOS. Map WorkOS role slugs, such as litigation, to tenant groups.

Path: When SSO management is read-only (shown)

1. The **SSO** tab shows "Organization policy makes **SSO** configuration read-only in this console."
2. Existing cards stay visible and keep working, but you cannot add, test, map, enforce, or remove. Ask your service team.

Check that it worked

- ✓ **Test connection** lists Discovery document, Signing keys (JWKS), and Sign-in readiness as passed.
- ✓ The test person reaches the workspace, and **Users** lists them with the USER role and sso under Auth.

- ✓ After their next sign-in, **Users** filtered to the mapped group lists them.
- ✓ The card reads enforced, and a local password on the domain is refused with "**SSO** is enforced for this email domain; local sign-in is disabled. Use the configured identity provider."

Troubleshooting

WHAT YOU SEE	WHAT TO DO
"Organization policy makes SSO configuration read-only in this console."	Service policy does not let administrators manage **SSO**, so the tab has no **Add SSO configuration** button. Ask your service team.
Create SSO configuration stays unavailable	Issuer URL and **Client ID** are required. For WorkOS, the WorkOS client ID and WorkOS API key are required.
"Issuer verified, but sign-in stays disabled until you add: client secret."	The secret was not saved, or allowed domains are missing. Cards cannot be edited: choose Remove and create the configuration again with every field.
Test connection fails at Discovery document	The issuer URL is wrong or unreachable from the server. Open the issuer followed by /.well-known/openid-configuration; for Entra use your tenant ID.
An older card shows Custom Oidc instead of the display name you typed	New cards keep the display name you type. Cards created before that change are labeled by provider type: identify them by their issuer, or remove and create them again.
Mapped groups do not appear after sign-in	The claim value must match exactly, including case and any leading slash, and the provider must add the groups claim to the ID token. Membership updates at the next sign-in.
"… is outside the domains allowed for this SSO provider."	The provider vouched for an address on another domain. Add the domain by recreating the configuration, or keep that person out.
"SSO is enforced for this email domain; local sign-in is disabled. Use the configured identity provider."	Expected after enforcement. The person chooses **Continue with SSO**. Turn enforcement off on the card to allow passwords again.

GOOD TO KNOW

The steps inside each identity provider's console (Microsoft Entra ID, Okta, Google Workspace, Keycloak) are spelled out step by step in the **Identity provider** setup topics of the interactive guide at https://aperturechat.com/guide.html. The redirect URI to register is the one shown in the **Add SSO configuration** form. For WorkOS, the WorkOS (AuthKit) path above lists the dashboard steps; the WorkOS card also lists the Initiate login URI to add after creating it.

CAREFUL

Enforcement blocks password sign-in for the allowed domains. A passing **Test connection** checks discovery and keys; it does not prove the client-secret exchange, callback, user session, or group mapping. Validate those with a real sign-in before you enforce.

45. Analytics

Runtime metadata, feedback, per-user usage, and token budgets for this tenant.

The **Analytics** tab measures how the organization actually uses the platform. Sections start collapsed behind descriptive headers — click a header to expand one — and each section carries its own filter row pairing a person picker (defaulting to **All admins and users**) with a date range and its presets (All, Today, Week, 30 days). Scoping one section never narrows another.

- **Runtime Clock Metadata** — organization-scoped execution timestamps captured from admin and user **Chat** and **Draft** completion events. The cards total runtime events, chat completions, and draft calls. Its **CSV** includes actor_id and actor_name columns, and when one user is selected the filename gains that user's suffix so exports stay unambiguous.
- **Chat Feedback Analytics** — response-level thumbs up and thumbs down signals submitted by tenant admins and users, with totals for overall, positive, and negative feedback.
- **Model Activity** — saved prompt volume by model, date, and person for the selected range, drawn as "**Prompts** by model", "Prompt trend", and "**Users** by prompt activity".
- **User Usage** — durable per-user usage for this organization's admins and users across chat, drafts, agents, automations, and the API gateway. Token counts are provider-reported only and stay blank when a provider reported none. The panel has its own **Filter usage by user** selector for drilling into one person.
- **Workspace Usage Budget** — a read-only view of the organization's service-managed ceiling and its current UTC accounting period. This panel shows where usage stands without exposing service-level configuration.
- **Token Allocations** — per-user and per-group token caps beneath the workspace ceiling, with Per day, Per week, or Per month UTC resets. The most restrictive applicable cap wins. Choose a user or group, enter a cap, pick the period, and click **Set cap**. Until you add one, the table says "No allocations yet. Everyone shares the workspace ceiling."

GOOD TO KNOW

Every number here comes from saved audit and usage events, and each **CSV** export button opens its own small date-range popover so a file contains exactly the rows you chose. If a panel has nothing to show, it says so plainly instead of showing sample data.

WALKTHROUGH · 2:03 · ADMIN CONSOLE › DOCUMENTATION

Tenant analytics

Scope each analytics section to a person and dates, export CSV, read usage and the workspace budget, and set a token cap that people actually hit.

Before you begin

- An Admin account.
- Some real activity: chats, drafts, or automations from people in your organization.
- The workspace ceiling comes from your service team; your caps sit inside it.

Step by step

1. Choose **Admin console** › **Analytics**. Every section starts collapsed.
2. Expand **Runtime Clock Metadata**. Choose a person and dates, or All, Today, Week, or 30 days.
3. Choose **CSV**, pick dates or All dates, and choose **Download** N rows.
4. Expand **Model Activity**, **User Usage**, and **Workspace Usage Budget** to read volume, tokens, and the ceiling.
5. Expand **Token Allocations**. Choose a person or group in the first menu, enter the Token cap, choose Per day, Per week, or Per month, and choose **Set cap**.
6. The row shows the cap and a meter of tokens used in the current UTC period.
7. Choose Remove allocation for … to lift the cap.

Path: Cap one person (shown)

1. Choose User · their name, enter the cap, choose the period, and **Set cap**.
2. **Once** they pass it, their next message reads "Your daily token budget has been reached. Requests are blocked until the next UTC day."

Path: Cap a group

1. Choose Group · its name instead. Members then see "Your group's daily token budget has been reached. Requests are blocked until the next UTC day."
2. When several caps apply, the most restrictive one wins.

Path: Export other sections

1. **Chat** Feedback and **User Usage** have their own **CSV** buttons with the same date choice.
2. Choosing one person in a section's filter adds them to the file name.

Check that it worked

- ✓ Each filter shows "N of M records" for its own section only.
- ✓ The **CSV** downloads with the section and person in its file name, such as aperture-admin-runtime-analytics-….
- ✓ The cap row shows used and capped tokens, and a capped person's next message is refused with the budget message.

Troubleshooting

WHAT YOU SEE	WHAT TO DO
"Enter a whole number of tokens (0 means no cap)."	Type digits only. 0 records the person or group with no cap.
"Unknown user for this workspace." or "Unknown group for this workspace."	The person or group was removed. Choose **Refresh** and pick again.
"Allocations total … tokens, more than the …-token workspace ceiling."	Allowed, but the ceiling still wins. Lower the caps or ask your service team to raise the ceiling.
The capped person waits several minutes before seeing the refusal	The chat retries a refused request before showing the message. The refusal itself is immediate on the server.
Token columns are blank for some rows	Tokens are counted only when the provider reports them; blank means none was reported.

46. Policies: service availability and memory governance

Apply downstream tenant defaults, configure memory, and govern by count without reading content.

The Policies tab is always present. **Policy Controls** and **Personal Data Protection** start collapsed. When service policy enables memory, Personalization Memory and Memory by User also appear collapsed. Otherwise, Memory governance explains the restriction; saved organization settings remain intact. Expand the panel you need; administrators can narrow available capabilities, while unavailable settings remain locked. **Personal Data Protection** has its own section in this guide.

Policy Controls

When your service team limits something you cannot change here, a Service policy note at the bottom of **Policy Controls** says so: administrator accounts created by the service team, administrators required to sign in with **SSO**, or newly available models starting without access until you grant a group in **Model Access**. No note means nothing is limited. Whether you can edit **SSO** is shown on the **SSO** tab itself.

Policy Controls sets defaults for the protected **Default Users** group: personal API keys, private-agent building, private knowledge-base and tool authoring, adding API sources, **Hermes** agents, and

personalization memory. A switch locks when its capability is unavailable under service policy; the saved group grant is preserved rather than silently erased. Use **Groups** for exceptions and **Model Access** for available models. Workspace connectors are managed in **Connections**.

Personalization Memory settings

- When service policy permits memory, expand Personalization Memory and turn on Memory for this organization. This makes the account-level Personalization memory row available to eligible users; existing memories stay saved but are not applied while this switch is off.
- Choose whether to allow Learn from conversations automatically. When off, only explicit requests such as “remember that …” and direct additions in the memory manager create memories. Every user can still opt out of automatic learning individually.
- Set Retention (days), from 1 through 3650. Older memories retire automatically when they pass this policy.
- Set Maximum memories per user, from 1 through 2000. The default is 200, which is a practical general-purpose limit; raise or lower it only when your retention, compliance, or workload policy calls for a different capacity. When the cap is passed, the least useful unpinned memories retire first.
- Expand Memory by User to review content-free counts. Click **Refresh** to reload the counts, or purge one person's memories when compliance or account cleanup requires it.

CAREFUL

Memory administration never grants reading access. Administrators see policy, counts, and purge controls only; the API and the interface do not return another person's memory content.

WALKTHROUGH · 2:38 · ADMIN CONSOLE › DOCUMENTATION

Policies and memory governance

Read what service policy allows, set the Default Users capabilities, tune personalization memory, purge a person's memories without reading them, and recognize when memory is unavailable.

Before you begin

- An Admin account.
- Service policy sets the ceiling: what is locked here is decided by your service team.

Step by step

1. Choose **Admin console** › Policies. Its sections start collapsed; expand **Policy Controls**.
2. If your service team limits anything you cannot change here, a Service policy note at the bottom of **Policy Controls** says so. No note means nothing is limited.
3. Switch on the Default users capabilities you want: downstream API, build agents, build knowledge bases, add API sources, build tools (their own MCP connections), use **Hermes** agents, and use memory. All except memory start off. Each saves with "Default user policy saved."

4. Confirm the change in **Groups** › **Default Users** › **Permissions**.
5. Expand Personalization Memory. Set Memory for this organization and Learn from conversations automatically.
6. Type Retention (days), 1 to 3650, or Maximum memories per user, 1 to 2000, and press Enter. The status reads "Memory policy saved."
7. Expand Memory by User and choose **Refresh**. To delete one person's memories, choose Purge, then Yes, purge.

Path: What the Service policy note can say

1. "Administrator accounts are created by your service team." Admin is not offered when you add or approve people.
2. "Administrators must sign in with **SSO**." Administrator accounts cannot use email and password.
3. "Newly available models start without access until you grant a group in **Model Access**." Grant each new model yourself.
4. Whether you can edit **SSO** is shown on the **SSO** tab itself.

Path: What each Default users switch changes

1. Downstream API: people can create personal API keys for their approved models.
2. Build agents, knowledge bases, or tools: people can create their own private ones. Sharing and publishing stay with administrators.
3. Add API sources: people can connect API endpoints, with keys or provider sign-in, to their own knowledge bases. It needs build knowledge bases first.
4. Use **Hermes** agents: people can open **Hermes** agents and **Hermes** connections. Off, these appear locked and never run.
5. Use memory: the assistant saves and recalls each person's private preferences.

Path: When memory is off for the platform (shown)

1. Policies shows a single Memory governance panel: "Personalization memory is unavailable under the current service policy. Saved organization settings remain intact."
2. Your saved settings return when service policy allows memory again.

Check that it worked

- ✓ The status reads "Default user policy saved." and the matching switch is on in **Groups** › **Default Users** › **Permissions**.
- ✓ "Memory policy saved." and the new value remains after reopening Policies.
- ✓ After a purge the status reads "Deleted N memories for …." and the person leaves Memory by User.

Troubleshooting

WHAT YOU SEE	WHAT TO DO
"Unavailable under the current service policy. The saved group grant is preserved."	Service policy has that capability off. Your earlier grant returns when it is turned back on.
"Turn on Memory for this organization below before granting the default group access."	Turn on Memory for this organization in Personalization Memory first.
"Turn on knowledge bases above first; API sources live inside a person's own knowledge base."	Switch on Default users can build knowledge bases, then Default users can add API sources.
A memory number did not change	Values outside 1 to 3650 days or 1 to 2000 memories are ignored. Type a value in range and press Enter.
"Memory policy was not saved. Personalization memory is unavailable under the current service policy."	Service policy has personalization memory off. Ask your service team.
"Default user policy could not be saved."	Nothing changed. Reload Policies and try again; if it repeats, check the **Audit** trail for the refusal.

47. Personal Data Protection

Conceal personal data in chats, records, and exports, and decide whether the model may read it.

Personal Data Protection is a panel on the Policies tab. It is off until an administrator turns it on, and it applies to everyone in the organization at once. When it is on, each detected value is replaced with a labeled placeholder, such as SSN or Card number, before a chat or record is saved or shown. People see the placeholder as a locked chip, and the line under their message box ends with Personal data is concealed.

Controls

CONTROL	WHAT IT DOES
Conceal personal data	Turns concealment on or off for the organization. Off: chats are stored and shown exactly as typed; content filters attached to individual models still apply.
Hide values from the model too	On by default. Typed prompts and attached file text reach the model provider as placeholders. Off: the model reads the original value for that turn, and the value is still concealed everywhere it is stored or shown, including the model's reply.
What to conceal	Government and personal IDs (Social Security number, ITIN, passport, driver's license, date of birth, vehicle identification number); Contact details (email, phone, street address); Financial accounts (payment card, card security code, bank account, ABA routing number, IBAN); Health identifiers (medical record number, health plan member or subscriber ID, Medicare beneficiary identifier); Secrets and credentials (private keys, API keys and access tokens, disclosed passwords or PINs); Network identifiers (IP addresses). At least one stays selected.
Try it with sample text	**Preview concealment** runs the selected kinds on sample text and reports how many values it concealed. The preview is not saved or logged.

Where it applies

- **Chat** messages, titles, and regenerated answers, before they are saved and every time they are shown.
- **Model** replies, including streamed text, before they reach the browser.
- **User Prompt Activity**, feedback notes, security alert snippets, and retention tags.
- Memories, issue reports, search results, the Elastic export, and training datasets.
- **Chats** saved before protection was turned on are concealed whenever they are shown or exported, and stored concealed the next time they are saved.

CAREFUL

Concealment is permanent for what it stores. Turning protection off does not bring values back, because the originals were never saved.

GOOD TO KNOW

Detection runs inside your deployment and checks formats and check digits: card numbers must pass the Luhn check, Social Security numbers must fall in issued ranges, and routing numbers, IBANs, and vehicle identification numbers must pass their checks. Look-alike characters, such as full-width digits or hidden spaces, cannot hide a value. It does not recognize names or free-text health details. **Drafts** are documents of record and are not altered; a draft request that contained personal data is recorded as DRAFT_NOT_CONCEALED. Uploaded files are stored as uploaded; only the text extracted for the model is concealed.

Evidence in Audit

- **User Prompt Activity** shows concealed prompts with the same chips. Choose **Refresh monitor** to load new activity.
- The **Audit Trail** records PROMPT_CONCEALED for each concealed message, with the sender, the model, and whether the model saw placeholders, and POLICY_UPDATED for each change to the panel. **Search** privacy to list them.

WALKTHROUGH · 3:30 · ADMIN CONSOLE › DOCUMENTATION

Protect personal data

Turn on Personal Data Protection, choose what to conceal and whether the model may read it, test it on sample text, and confirm the result in a real chat and in Audit.

Before you begin

- An Admin account.
- Your organization's decision on which kinds of personal data must not be stored in chats, and whether the model may read them.
- Synthetic test values, such as the sample already in the panel. Never test with a real person's data.

Step by step

1. Choose **Admin console** › Policies. **Personal Data Protection** sits below **Policy Controls**; its header reads Off or On.
2. Expand it and switch on **Conceal personal data**. It saves at once for everyone in the organization, and the header reads On.
3. Leave **Hide values from the model too** on unless the work needs the model to read the values. When on, typed prompts and attached file text reach the model provider as placeholders.
4. Under **What to conceal**, switch off any kind of personal data you do not want concealed. At least one stays on.
5. Under **Try it with sample text**, keep or edit the synthetic sample and choose **Preview concealment**. Read the count, the concealed text, and the pill for each detector. The preview is not saved or logged.
6. Read **Where it applies**, and the limits below it.
7. Have a person send a message with a synthetic value. It shows a locked chip such as SSN, and the line under their message box ends with Personal data is concealed.
8. Choose **Audit** › **User Prompt Activity** › **Refresh monitor**: the prompt shows the same chip.
9. In the **Audit Trail** choose **Refresh** and search privacy. PROMPT_CONCEALED records each concealed message; POLICY_UPDATED records your change.

Path: Keep values from the model (default, shown)

1. **Hide values from the model too**: on.
2. The model receives placeholders such as ⟦SSN⟧ instead of the value, so its reply refers to the placeholder, which shows as a locked chip.
3. Use this when the model does not need the value to do the work, such as drafting a note or summarizing a record.

Path: Let the model read the values (shown)

1. Switch off **Hide values from the model too**. The row reads "The model reads the original value for that turn. It is still concealed everywhere it is stored or shown."
2. Use this when the work needs the value, such as filling in a form or a signature block.
3. Values the model writes are concealed before the reply reaches the browser and before it is saved.

Path: Narrow what is concealed

1. Under **What to conceal**, switch a kind of personal data off or on. Each switch saves at once.
2. Each card lists the values it finds. For example, Contact details covers email addresses, phone numbers, and street addresses.
3. The last switch that is on cannot be turned off. To stop concealing, switch off **Conceal personal data** instead.

Path: Turn protection off (shown)

1. Switch off **Conceal personal data**. The header reads Off, and new chats are stored and shown exactly as typed.
2. Content filters attached to individual models still apply.
3. **Chats** saved while protection was on stay concealed: their values were never stored, so they cannot come back.

Check that it worked

- ✓ The panel header reads On.
- ✓ **Preview concealment** reports the values concealed, for example "6 values concealed", with a pill for each detector.
- ✓ A test message shows locked chips in the chat and in **Audit** › **User Prompt Activity**.
- ✓ The **Audit Trail** lists PROMPT_CONCEALED for the message and POLICY_UPDATED for your change.

Troubleshooting

WHAT YOU SEE	WHAT TO DO
The work trace says "The model saw placeholders" with Hide values from the model too off	That line is wrong in this mode: the model read the original values for that turn. The PROMPT_CONCEALED row in the **Audit Trail** shows what really happened, as concealed_from_model=false. The reply is still concealed before it is shown or saved.
A kind of personal data cannot be switched off	At least one stays selected. Switch another one on first, or switch off **Conceal personal data**.
Hide values from the model too is dimmed	It applies only while **Conceal personal data** is on.
"Nothing detected"	The sample has no value the selected kinds recognize. Detection checks formats and checksums, so a look-alike such as a card number that fails its check digit is left alone.
A name or a description of someone's health was not concealed	Detection does not recognize names or free-text health details. Ask people to leave them out, or add a content filter to the model.
A draft still contains a value	**Drafts** are documents of record and are not altered. A draft request that contained personal data is recorded in the **Audit Trail** as DRAFT_NOT_CONCEALED.
"Personal data protection settings could not be loaded."	Reload Policies. If it repeats, confirm your account is still an administrator.
"The setting was not saved."	Nothing changed. **Try again**; if it repeats, check the **Audit Trail** and your connection.

48. Training datasets

Capture de-identified ratings and corrections, route them into datasets, review them, and download them for fine-tuning.

The **Datasets** tab keeps a private, de-identified record of how your people rate and correct answers, so you can fine-tune an open-weight model on your own work later. It is off until you turn it on. Your model providers keep running under zero data retention: captured examples are never sent to a provider. They stay in your deployment until an administrator downloads a dataset, and every download is audited.

What is captured

SIGNAL	CAPTURED WHEN	BECOMES
Rated helpful	A person gives a reply thumbs up, with or without a note.	An approved answer.
Rated unhelpful	A person gives a reply thumbs down, with any note.	A rejected answer, with the note.
Corrected	The person's next message pushes back, such as “That's wrong, the deadline is 60 days. Please revise.” A regenerated reply counts too.	The first answer as rejected, and the reply that followed as preferred unless it was rated down or corrected again.

Corrections are recognized by a transparent rule: factual pushback such as “that's wrong”, “you missed”, or “should be” counts more than a style request such as “shorter” or “rewrite”, and an opener such as “No,” or “Actually” adds weight. Ordinary follow-up questions are not captured as corrections.

Safeguards

- Every captured text is de-identified with all kinds of personal data, whatever the **Personal Data Protection** settings are.
- **Conceal people and client names** (on by default) also replaces the full names of people in your workspace and your configured client and matter names. Other names are not detected.
- **Skip sensitive or regulated chats** (on by default): chats with a sensitive or regulated retention tag, confirmed or suggested, are never captured.
- **Never capture from these groups**: members of a selected group are never captured.
- **Review before export** (on by default): new examples wait for an administrator to approve them, and downloads include approved examples only unless you choose otherwise.
- Examples follow their chat: deleting a chat, a retention purge, or deleting the person or organization removes its examples.

How examples are labeled and routed

- Practice area: from the chat's subject retention tag when subject tagging is on, otherwise from keywords in the person's own words, for example Legal · Litigation or Financial · Tax.
- Kind of work: Drafting, Review & redlining, Research & Q&A, Summarization, Analysis, Extraction, Translation, Coding, or General.
- Department: the person's groups, other than **Default Users**.
- A dataset is a set of routing rules (signals, practice areas, kinds of work, departments, and models; an empty rule accepts everything) plus a training format. Membership is computed, so editing a rule re-routes every example, and one example can feed several datasets.

- **Suggested datasets** appear for practice areas and departments with three or more examples and no dataset yet.

Training formats

FORMAT	TRAIN.JSONL CONTAINS	USES
Supervised fine-tuning	**Chat** messages ending in the answer people approved, or the revised answer after a correction.	Helpful ratings and accepted corrections.
Preference pairs (DPO)	prompt, chosen, and rejected.	Corrections with an accepted revision.
Binary feedback (KTO)	prompt, completion, and a true or false label.	Every judged answer; works with thumbs ratings alone.

A download is a ZIP with a folder named after the dataset, holding train.jsonl in the dataset's format, metadata.jsonl with line-aligned labels and no user identity, and a README.md dataset card. Identical content captured twice, for example from a forked chat, is exported once. The **Audit Trail** records each capture setting change, scan, dataset change, review, and download; set its category filter to training to list them.

WALKTHROUGH · 4:36 · ADMIN CONSOLE › DOCUMENTATION

Build training datasets from ratings and corrections

Capture de-identified ratings and corrections, route them into datasets by practice area, department, and kind of work, review them, and download a file for fine-tuning an open-weight model.

Before you begin

- An Admin account.
- Your organization's approval to keep de-identified copies of rated answers for model training, and a decision on which groups are never captured.
- People who rate replies with the thumbs buttons or correct the assistant in chat.
- For the download: a place inside your organization to keep the file, such as the environment where you will fine-tune an open-weight model.

Step by step

1. Choose **Admin console** › **Datasets**. **Training Data Capture** reads Off, and nothing is collected.
2. Switch on **Capture training signals**. The header reads Capturing.
3. Under **Capture these signals**, keep or clear Helpful ratings, Unhelpful ratings and notes, and Corrections and regenerations.

4. Check the safeguards. **Review before export**, **Skip sensitive or regulated chats**, and **Conceal people and client names** are on by default.
5. Under **Never capture from these groups**, choose any group whose work must never be captured.
6. Choose **Scan existing chats** to capture chats saved before capture was on. The notice reads "Scanned N chats and captured N new examples."
7. From now on, ratings and corrections are captured as chats are saved. In **Captured Signals**, choose **Refresh** to see the counts and the work mix.
8. Under **Suggested datasets**, choose **Create** on a suggestion, or choose **New dataset**.
9. Check the Name, **Training format**, and routing rules, then choose **Create dataset**.
10. Choose Review on the dataset card. Read each example as it would be exported, then choose **Approve** or Exclude, or **Approve all shown**.
11. Choose **Download**, then **Download** N examples in the dialog. Keep the ZIP inside your organization.
12. Choose **Audit** › **Audit Trail** › **Refresh** and set the category filter to training to see each step recorded.

Path: Preference pairs (DPO) (shown)

1. Uses corrections whose revised answer was accepted: not rated down and not corrected again.
2. train.jsonl holds prompt, chosen (the revised answer), and rejected (the original answer).

Path: Supervised fine-tuning

1. Uses answers rated helpful and accepted revisions.
2. train.jsonl holds chat messages that end in the approved or revised answer.

Path: Binary feedback (KTO)

1. Uses every judged answer, so it works with thumbs ratings alone.
2. train.jsonl holds prompt, completion, and a true or false label.

Path: Create a dataset from scratch

1. Choose **New dataset** in the **Datasets** panel.
2. Type a Name and an optional Description, and choose a **Training format**.
3. Choose rule chips under Signals, Practice areas (a broad area includes its specialties), Kinds of work, Departments, and **Models**. Leave a rule empty to accept everything.
4. Optionally type a System prompt for every example, then choose **Create dataset**.

Path: Skip review

1. Switch off **Review before export**. New examples are approved as they are captured, and you can still exclude any of them.
2. Or keep review on and switch on **Include examples waiting for review** in the **Download** dialog, for one download.

Path: Edit, archive, or delete a dataset

1. The pencil edits the name, format, and rules. Every example is re-routed at once.
2. **Archive** stops routing examples to the dataset; **Restore** brings it back.
3. **Delete** removes the dataset definition. Its examples stay captured and keep routing to other datasets.

Check that it worked

- ✓ **Training Data Capture** reads Capturing, and **Captured Signals** counts examples.
- ✓ The dataset card shows approved examples and none waiting.
- ✓ The download is a ZIP with train.jsonl, metadata.jsonl, and README.md.
- ✓ The **Audit Trail** lists DATASET_CREATED, EXAMPLES_REVIEWED, and DATASET_EXPORTED.

Troubleshooting

WHAT YOU SEE	WHAT TO DO
Scan existing chats is dimmed	Switch on **Capture training signals** first.
"No examples captured yet"	Capture is off, or nobody has rated or corrected an answer since it was turned on. Turn capture on and choose **Scan existing chats** to include earlier work.
A rated chat was not captured	It may carry a sensitive or regulated retention tag; a chat in which a Social Security or card number was found is usually tagged. Or its owner is in a group under **Never capture from these groups**. Very short replies are also skipped.
A follow-up was not treated as a correction	A correction needs clear pushback, such as "that's wrong", "you missed", or "should be". A new question, or a style request such as "make it shorter" on its own, is not enough.
An example has the wrong practice area	Without a subject retention tag, the practice area comes from keywords, and the example says Practice area from keywords. Turn on subject tagging in Data Retention, or route by department instead.
Download is dimmed	No examples match the dataset yet. Check its rules and format: preference pairs need corrections whose revised answer was accepted.
The dialog says Download 0 examples	Nothing is approved yet. **Approve** examples, or switch on **Include examples waiting for review**.
"Training data settings could not be loaded."	Reload **Datasets**. If it repeats, confirm your account is still an administrator.

49. Ethical walls and file properties

Limit a document to a named group for every role, prove it holds, and read the audit trail.

An ethical wall limits a document to the members of chosen groups. It applies to every role, including administrators: outside the wall, chat cannot find the document and the viewer refuses to open it. A wall can be set on a document under its details, or read from a wall named in the file's own metadata.

CAREFUL

Know what a wall does not cover. People who manage the knowledge base still see that the file exists, who may find it, and its properties, so keep sensitive words out of file names and properties. A wall does not rewrite replies already saved, and administrators can still read those replies in **User Prompt Activity**.

WALKTHROUGH · 5:23 · ADMIN CONSOLE › DOCUMENTATION

Wall off documents and read file properties

Limit a document to chosen groups, prove that people outside them and administrators cannot find or open it, find the audit entries, and honor walls named in file metadata.

Before you begin

- An Admin account, or ownership of the knowledge base with Can build knowledge bases. Limit and Follow file are open to anyone who manages the base; Open, which lifts any wall, and **More** wall fields are for administrators.
- A knowledge base with the file in it. Upload files as **Knowledge** bases shows.
- A group that holds everyone who may see the file. **Groups** and permissions shows how to build one. Walls admit members of groups, never single people.
- Someone in that group to confirm the file still works for them, because you may be outside the wall yourself.

Step by step

1. Choose **Library** in the sidebar; **Knowledge** opens. Open the knowledge base.
2. On Files, choose the arrow beside the file (Show details). Read Properties and Who can find it.
3. Under Who can find it, choose Limit.
4. Tick each group that may find the file.
5. Choose Save access. The notice reads Only members of … can now find …, and the file shows Walled.
6. Sign in as someone outside the group, or ask them to check: the file is gone from the list, chat cannot find it, and an old citation says This document is no longer available.
7. Ask someone in the group to confirm they still get a cited answer.
8. In the **Admin console**, open **Audit**, expand **Audit Trail**, choose **Refresh**, and search document_wall for DOCUMENT_WALL_CHANGED, then view_denied for DOCUMENT_VIEW_DENIED.

Path: A wall named in the file

1. In the program or document system that holds the file, set a property named Ethical wall or Information barrier to the group's name or ID.
2. Upload or sync the file. It shows Walled, and Who can find it names the property and the group.
3. A name that matches no group shows Hidden, and nobody can find the file. Choose Limit, tick the right group, and choose Save access. Creating the group is not enough: the file stays Hidden until the base's walls are checked again, as Sync now does.

Path: Read another field as a wall

1. Open the knowledge base, then Settings.
2. Under Ethical walls, type the field name in **More** wall fields. Separate several with commas. Only administrators see **More** wall fields.
3. Choose Save changes. Files already in the base are checked again at once.

Path: Lift a wall or go back to the file

1. Show the file's details, then under Who can find it choose Open or Follow file.
2. Open lifts any wall: everyone who can use this base can find it. Only administrators can choose it. **Knowledge** base owners still have Limit and Follow file, so they can change a wall or remove a Limit wall.
3. Follow file uses the wall named in the file's own metadata, if any.
4. Choose Save access. Your choice is kept through later re-indexing.

Check that it worked

- ✓ The file shows Walled, and Who can find it names only the groups you chose.
- ✓ A person outside the group who does not manage the base does not see the file, chat returns no source from it, and an old citation says This document is no longer available.
- ✓ You, as an administrator outside the group, get the same refusal from Preview.
- ✓ A member of the group still gets a cited answer.
- ✓ The **Audit Trail** shows DOCUMENT_WALL_CHANGED, and DOCUMENT_VIEW_DENIED for each refused attempt.

Troubleshooting

WHAT YOU SEE	WHAT TO DO
You cannot open a file you walled, and it says "This document is no longer available"	That is the wall working: it screens administrators too. Ask a member of the group to check the file. If you need it yourself, someone who can edit your account must add you to the group. Under the default service policy, administrators cannot edit their own account: "You cannot modify this account under the current service policy."
A file shows Hidden, with "It names no group in this workspace, so nobody can find it until the group exists."	The file's wall names a group that does not exist here, and Who can find it quotes the name it read. Choose Limit, tick the right group, and choose Save access. Creating the group is not enough: the file stays Hidden until the base's walls are checked again, as Sync now does. Files-only bases have no Sync now.
"Limited to groups that no longer exist, so nobody can find it."	A group the wall named was deleted. Choose Limit again with a group that exists, then Save access.
A member of the group cannot find the walled file	A wall only narrows access and never adds to it. The group must also be able to use the knowledge base: check Who can search it under Settings.
"Create a group first; walls admit members of groups."	Walls admit groups, so create one in **Admin console** › **Groups**.
"Only administrators can lift an ethical wall."	**Knowledge** base owners cannot choose Open. Ask an administrator. Owners still have Limit and Follow file.
Save access stays unavailable	Change the option first. With Limit chosen, tick at least one group.
A saved reply still shows text from a walled file	A wall stops new searches and opening the file. Replies saved before it went up keep their text, so set walls before sharing a file. Your retention settings govern saved chats.
An administrator can read a walled figure in Audit	Walls cover the document, not chats. **User Prompt Activity** shows each prompt and its reply, including a reply from someone inside the wall. Keep that in mind when you choose who is an administrator.
A file is not walled even though its property names a group	Check the property's name. Ethical wall, Information barrier, their plurals, Wall groups, and names in **More** wall fields are read. Add the field under Settings › Ethical walls.

50. Data retention and conversation tags

Find tagged conversations, inspect their contents, and review batch actions.

WALKTHROUGH · 2:16 · ADMIN CONSOLE › DOCUMENTATION

Data retention and tagging

Keep chats forever by default, label conversations by client or matter, place a legal hold, and preview a finite schedule before anything is deleted.

Before you begin

- An Admin account.
- Your organization's retention rules, and the client or matter names and aliases people use.
- Saved chats to label. Labels come only from saved message text.

Step by step

1. Choose **Admin console** › **Audit** and expand Data Retention.
2. Schedule and rules: Keep chats for starts at Forever, with automatic deletion off.
3. Under Clients, matters, and regulated records, choose a Source type, enter Name or reference and aliases, and choose Add source to policy.
4. Choose Save Forever. The status reads "Forever saved. Automatic deletion is off for all chats."
5. Choose Tags and holds, then **Scan existing chats**. **Search** for the matter and review each suggestion.
6. Select the right chats, choose the label, and choose Confirm label.
7. Expand Legal holds, enter a Hold name, and choose Hold selected chats.
8. To consider a time limit, choose it in Schedule and rules and choose Preview effect. Save only after reviewing the counts.

Path: Keep forever (default, shown)

1. Leave Keep chats for at Forever. Choose Save Forever after adding sources; nothing is deleted.

Path: A finite schedule (previewed, shown)

1. Choose 1, 5, 7, or 10 years. Count age from and Review window (at least 7 days) appear.
2. Choose Preview effect and read how many chats are old enough, on hold, or kept.
3. Choose Save retention policy only when the counts are right. Eligible chats enter the review window first.

Path: A rule for one label

1. Each source has a Retention rule menu. A longer matching rule wins over the default schedule.
2. Tick Apply time limits only to labels with a rule to leave unlabeled chats at Forever.

Path: Manual archive or delete

1. In Tags and holds, select chats and choose **Archive** selected or **Delete** selected.
2. **Delete** asks first and cannot be undone. **Chats** under an active legal hold are skipped.

Check that it worked

- ✓ The source appears in the list with its aliases, and Save Forever confirms automatic deletion is off.
- ✓ The confirmed chats show the matter label; held chats show Legal hold.
- ✓ Preview effect reports the totals without changing anything.

Troubleshooting

WHAT YOU SEE	WHAT TO DO
"Enter a source name of at least two characters."	Enter the client or matter name.
"Aliases must be 3–160 characters long."	Remove very short aliases, such as initials.
"Preview this exact policy again before saving; the policy or affected chats changed."	Choose Preview effect again, then save.
Scan suggests nothing for a matter	Suggestions come from saved message text only. Add the aliases people actually write, save, and scan again.
Hold selected chats is unavailable	Select 1 to 500 chats and enter a Hold name of at least three characters.

How retention behaves, in detail

- Open **Audit** and expand Data Retention, then choose Schedule and rules. Forever is the default: automatic deletion is off until an administrator previews and saves a schedule. Choose 1, 5, 7, or 10 years, or keep Forever. One year means 365 days.
- Choose whether age starts at chat creation or the last message change. Renaming or archiving a chat does not restart its clock. Select a review window of at least 7 days. Saving a changed policy restarts that window for eligible chats.

- Add a stable client, matter, or regulated-record source and its aliases. A source can have a longer retention rule or Forever. Choose Apply time limits only to labels with a rule to leave all other chats stored indefinitely. The longest applicable duration wins; a matching Forever rule or active legal hold prevents automatic deletion.
- Save the source definitions, then use **Scan existing chats** in Data Retention → Tags and holds. New message saves also look for source mentions. Detected mentions are suggestions only: select the correct chats and source, then Confirm label. Remove / dismiss label rejects a false match. The label records who confirmed it and when.
- Optional sensitive-data suggestions check saved message text for email addresses, possible Social Security numbers, and payment cards. They do not detect every form of PII or regulated record, or inspect original uploaded files. Raw matched values are never copied into labels. Review before confirming a category.
- Choose Preview effect to see counts across all saved chats, including legal holds and chats without a deadline. Saving the policy recalculates existing and future chats. A shorter duration can make old chats eligible, but they still receive the review window. A longer duration delays deletion; it cannot restore deleted content. Saving Forever stops automatic deletion.
- To inspect chats, open **Audit**, expand Data Retention, and choose Tags and holds. This list includes tagged and untagged conversations available in your administrative scope.
- Use **Search** chats and tags to find titles, people, tags, or client/matter identifiers. Filter by tag type when you need a narrower set.
- Click a conversation title to open Tagged conversation and review its saved prompts and outputs. Close the preview to return to the same list.
- Select the intended chats. **Archive** selected keeps them stored and searchable but removes them from the active list. **Delete** selected opens a permanent-deletion confirmation; it does not delete until you choose Yes, delete.
- Under Legal holds, name a hold and choose Hold selected chats. This hold protects the selected records, including against manual deletion. For ongoing preservation of a client, also set that source's rule to Forever. Load active holds to review them; releasing a hold requires a second confirmation.
- Read the completed action status. **Chats** under an active hold are skipped by deletion. A failure or skipped record needs review; do not assume every selected row was deleted. The background scheduler handles automatic cleanup in bounded batches and writes an audit record per deleted chat.

CAREFUL

Permanent deletion removes the selected conversations and their attachments and cannot be undone. Preview contents and check the selected count before confirming. A tagging switch records classification; it is not a scheduled deletion rule or an action that places a hold.

51. Review feedback and reported issues

Read response ratings and written feedback in Analytics, and work reported problems in Reports.

WALKTHROUGH · 1:33 · ADMIN CONSOLE › DOCUMENTATION

Review feedback and reported issues

Follow a real rating with a note and a reported problem from the person's screen to your review in Analytics, then hand the report to Reports.

Before you begin

- An Admin account.
- People who rate replies or report problems from **Help**.

Step by step

1. The person rates a reply with the thumbs buttons below it and may add a note, then chooses Send note.
2. The person reports a problem from **Help** › Report a problem: they choose Problem (or Idea, Question, Feedback, or **Security**), enter a Subject and Message, add an optional screenshot, and choose Send report.
3. Choose **Admin console** › **Analytics** and expand **Chat** Feedback.
4. Choose the person and dates, or Today, Week, or 30 days.
5. Open a feedback row to read the note and the rated exchange.
6. Scroll to Reported platform issues and open a report to read it.
7. Choose Manage in Reports to reply, set the status, priority, and assignee, or add an internal note. The person follows it in **Help** › My reports.

Path: A rating with a note (shown)

1. Thumbs up or down, then an optional note. The row shows the sentiment, model, person, and note.

Path: A reported problem (shown)

1. **Help** › Report a problem. **Analytics** shows the subject, message, sender, time, and any screenshot.
2. Manage in Reports opens the Reports tab, where you reply, set the status, and keep internal notes (see Work reported problems in Reports).

Check that it worked

- ✓ The summary counts Total feedback, Positive, Negative, and Issue reports for your scope.


- ✓ Feedback and conversation shows the note and the rated exchange.
- ✓ Platform issue report shows the subject and message the person sent.
- ✓ Manage in Reports opens the Reports tab with the report in its queue.

Troubleshooting

WHAT YOU SEE	WHAT TO DO
The list is empty	Widen the person and date filter. Each section filters independently.
The conversation could not be loaded	The dialog says so and shows the saved reply preview only. Use the evidence that loaded.
"The screenshot preview could not be loaded."	The report has a screenshot that failed to load. Read the text and try again later.

52. Reports: work support tickets

Triage, answer, and resolve the problems, ideas, and questions people send from Help.



Admin console → Reports lists the tickets people send from Help, with Needs reply first. Example workspace with synthetic data.

Every report sent from **Help** → Report a problem becomes a ticket in **Admin console** → Reports. People choose what they are sending (Problem, Idea, Question, Feedback, or **Security**) and how much it affects them, and they follow the ticket and your replies in **Help** → My reports.

- Start with Needs reply: tickets that are new or where the reporter answered last. Open, Closed, and All show the rest; search finds a ticket by its number, subject, or reporter.
- Open a ticket to read the message, any screenshot, and technical details if the reporter chose to include them.
- Set Status (Received, In review, In progress, On hold, Resolved, or Closed), Priority, Assignee, and Type as you work it. Each change is recorded in the ticket's timeline and in the audit trail under support.*.
- Reply to the reporter to send a message they see in My reports; **Help** shows them a dot when there is news. Internal note keeps a comment visible only to administrators.
- When the reporter answers, the ticket returns to Needs reply. A reporter can reopen a resolved ticket with “Still having this problem?”.
- **Security** reports stay private to your deployment and are never shared outside it.

TIP

Alerts → Support-reports template creates a rule that notifies you when new reports, replies, or reopened reports arrive.

WALKTHROUGH · 3:08 · ADMIN CONSOLE › DOCUMENTATION

Work reported problems in Reports

Take a report from Help to resolved: find it in Reports, set its status, priority, and assignee, keep internal notes, reply to the person, and confirm every step in the Audit Trail.

Before you begin

- An Admin account. Reports lists the reports people in your organization send.
- People who send reports from **Help** › Report a problem. They follow your replies in **Help** › My reports.

Step by step

1. The person opens **Help** › Report a problem, chooses what they are sending (Problem, Idea, Question, Feedback, or **Security**), enters a Subject and Message, and chooses Send report. They see "Report #N sent".
2. Choose **Admin console** › Reports. Needs reply lists reports waiting on you; Open lists every report still being worked.
3. **Search** by subject, person, or #number, then select the report.
4. Set Status (such as In review), Priority, and Assignee. Each change saves at once and appears in the activity. The person sees status changes; priority and assignee changes are internal.
5. For a note only administrators see, choose Internal note, type it, and choose Add note.

6. To answer the person, choose Reply to and their first name, such as Reply to Jane, type your reply, and choose Send reply. They see it in **Help** › My reports.
7. When the person replies, the report returns to Needs reply. Choose **Refresh** to see it.
8. When it is fixed, type a closing reply and choose Reply and resolve, or set Status to Resolved.
9. Choose **Audit** › **Audit Trail**, choose **Refresh**, and set the category filter to support to see each step.

Path: A problem (shown)

1. Problem asks How much is this affecting you?: Blocking me, Slows me down, or Minor. That sets the starting priority, High, Normal, or Low; you can raise it to Urgent.
2. The report may carry a screenshot and, unless the person cleared Include technical details, the version, page, browser, and recent errors. Open Technical details on the report to read them.

Path: An idea, a question, or feedback

1. The same form, with prompts for that type. The report's Type shows it; change Type if the person chose the wrong one.
2. Work it the same way: reply, set a status, and resolve or close it.

Path: A security concern (shown)

1. Choosing **Security** tells the person: "**Security** concerns go only to your administrators and are never posted publicly."
2. The report's Type reads **Security** concern. Follow your organization's security process, and keep sensitive details in internal notes.

Path: Closed and reopened reports

1. Closed lists resolved and closed reports; All lists everything. The Status menu narrows the list to one status.
2. On a resolved report the person sees Still having this problem? and can choose **Reopen** report; it returns to your queue.

Path: An email for each new report

1. **Admin console** › **Alerts** › Support-reports template prefills New support reports, which watches support.issue_reported, support.issue_reporter_replied, and support.issue_reopened.
2. Add Email recipients and choose **Create** Rule (see **Alerts** and delivery).

Check that it worked

- ✓ The report shows the status, priority, and assignee you set, and each change appears in its activity.

- ✓ The person's My reports shows your reply and the progress tracker, never your internal note.
- ✓ After Reply and resolve, the status reads Resolved and the report leaves Open.
- ✓ The **Audit Trail**, filtered to support, lists the report, each change, your replies, and the person's reply.

Troubleshooting

WHAT YOU SEE	WHAT TO DO
"No reports yet"	Nobody in your organization has sent a report. Reports people send from **Help** › Report a problem appear here.
"Nothing matches"	A view, menu, or search is narrowing the list. Choose All, set the menus back to Any status and All types, and clear the search.
Reply and resolve is not offered	It appears only with Reply to selected while the report is open, and it needs a reply typed first.
"The change could not be saved."	Nothing changed. Choose **Refresh** and try again; another administrator may have changed the report.
"Reports could not be loaded."	Choose **Refresh**. If it repeats, confirm your account is still an administrator.
The open report does not show the person's latest reply	**Refresh** updates the list, not the report already open. Select another report and then this one again, or reload the page.

53. Audit

Grouped signals, Audit Insights trends, prompt monitoring, security alerts, and the tenant trail.

The **Audit** tab is the tenant's governance station. It opens on **Admin Audit** and **Audit** Insights, while the sections below start collapsed; click a section header to expand it. **User Prompt Activity**, **Security Alerts**, and the **Audit Trail** each carry their own filter row pairing a person picker with a date range, so one section's scope never narrows another. The **CSV** export buttons produce files of exactly the filtered rows, including actor_id and actor_name columns, so every exported row names who acted.

Admin Audit signals

- The banner at the top reads, for example, “7 of 18 signals need attention”. Expand all and Collapse all open or fold every group. List shows one compact row per signal; Cards shows each signal with its description. The layout you choose is remembered in this browser.
- **Security** signals: audit events, critical events, the prompt watchlist of active DLP or misuse alerts, alert response (the median time to acknowledge an alert), after-hours changes (outside 7 AM–7 PM or on weekends), and failed operations.

- Identity & access: active admins, active users, access requests awaiting review, accounts that have never signed in, role changes, and credential changes such as MFA, password, session, and API key events.
- **Models** & workspace: prompt volume, connector issues, ungrouped models, unassigned users (active users in no group), agent approvals waiting for review, and automation failures.
- **Groups** that need attention open automatically and all-clear groups fold to one summary line. Red rows need attention. Select any signal to open an investigation listing every record behind it, with a filter box to narrow the records.

Audit Insights

- **Audit** Insights charts the trends behind the signals for your organization. Choose a 7 days, 14 days, or 30 days range; the summary line counts the audit events and security alerts in range.
- **Audit** events by day stacks info, warning, and critical events. **Security** alerts by day draws DLP and behavior alerts as two lines, and Alert breakdown ranks alerts By rule or By person with their open and acknowledged counts.
- Most active people ranks who is acting, Activity by area groups events into areas such as **Chat**, Sign-in & identity, and Administration, and Activity by hour shades the hours outside 7 AM–7 PM in your local time.
- Select any bar, point, or row to open the same investigation view with the records behind it. If the loaded history reaches its page limit, a note says earlier days may be incomplete.

Sections below the dashboard

- **Recent Governance Activity**: the current tenant snapshot for identity, user, model, and connector posture: how many **SSO** configurations are enforced, how many users are active, and how many connectors are enabled.
- **User Prompt Activity**: drill into saved prompts from this organization's admins and users and their model responses by person, thread, model, and timestamp, scoped by the section's own user and date filter.
- **Security Alerts**: DLP and malicious-behavior flags raised from admin and user prompts, shown with redacted snippets for review. Click **Acknowledge** once an alert is handled, or **Reopen** if it needs another look.
- **Audit Trail**: the tenant's append-only transaction log, newest first. Its toolbar has a severity select, an action-category select, and a search box (**Search actions, people, targets…**) that narrow the rows together; the trail's **CSV** exports exactly the rows you are looking at. Click **Refresh** to reload it straight from the admin audit API.

GOOD TO KNOW

Security alerts fire on real prompt content, such as payment card numbers, shared credentials, and prompt-injection attempts, but show only redacted snippets, so reviewing an alert never re-exposes the sensitive value itself.

WALKTHROUGH · 1:33 · ADMIN CONSOLE › DOCUMENTATION

Tenant audit

Investigate a real flagged prompt from start to finish: the signal board, Audit Insights, the prompt and reply, the security alert, and the audit trail.

Before you begin

- An Admin account.
- A flagged prompt to investigate. This lesson follows a real prompt-injection attempt, the same one the **Alerts** and delivery lesson follows to a delivered email.

Step by step

1. Choose **Admin console** › **Audit**. The banner counts the signals that need attention.
2. Select a red signal, such as Prompt watchlist, to open its records. Close it to return.
3. In **Audit** Insights, choose 7, 14, or 30 days, then select a bar or point to list the records behind it.
4. Expand **User Prompt Activity**, search for the prompt, and open it to read the prompt and the model's reply.
5. Expand **Security Alerts** and choose **Acknowledge** once you have reviewed the alert.
6. Expand **Audit Trail**. Filter by severity, category, and text, then choose **CSV** to export what you see.

Path: Start from an alert email

1. The email names the rule, detection, person, and time, never the flagged text.
2. Open **Admin console** › **Audit** › **Security Alerts** and find the alert by detection and time, then follow the steps above.

Path: Export evidence

1. **User Prompt Activity** and **Audit Trail** each have a **CSV** button. The trail export carries exactly the filtered rows.

Check that it worked

- ✓ The investigation lists the flagged records with person, model, and time.
- ✓ The prompt dialog shows the exact prompt and the model's saved reply.
- ✓ The alert reads Acknowledged, and the trail shows the security.prompt_flagged events.

Troubleshooting

WHAT YOU SEE	WHAT TO DO
A signal opens with no records	The count reflects the current snapshot; check the **Audit Insights** range or the trail's date filter.
The prompt you expect is missing from User Prompt Activity	Each section has its own person and date filter. Choose All and clear the search.
"Security alert was not updated: …"	Nothing changed. **Refresh** and acknowledge again; another administrator may have changed it.

54. Alerts

Watch rules over audit activity, and honest delivery statuses for every alert.

The **Alerts** tab turns audit activity into notifications. It has three panels: **Email Delivery**, **Alert Rules**, and **Alert Deliveries**. Every alert is always logged in-app regardless of email — email is a delivery channel, not the record.

Email Delivery

For organization administrators this panel is a read-only status: it reports whether email delivery is configured at the service level. If email is not configured, rules still work — their alerts are logged in-app and the delivery log says so honestly.

Alert Rules

- Click Prompt-injection template to start from a rule that watches prompt-injection, system-prompt extraction, and credential-extraction attempts; **Suspicious-activity template** for security flags and elevated-severity events; Support-reports template for new reports people send from **Help**, their replies, and reopened reports; or **New rule** to build one from scratch. A template only fills in the form; nothing is saved until you click **Create** Rule.
- A rule has: a name; **Action patterns** — exact audit actions or prefixes such as security.* or admin.user_deleted; a **Minimum severity**; an optional **Watched user**; a threshold — how many matches within a time window before it fires; a cooldown between alerts; and email recipients. Leave recipients empty and the alert is in-app only.
- Only these detections narrows a rule to prompts flagged by specific detectors: Prompt injection, System-prompt extraction, Credential extraction, API key or token shared, Private key shared, **Password** shared, US Social Security number, and Payment card number. Leave all unchecked to match every event the action patterns allow. A rule that could never fire is refused with an explanation when you save it.
- Alert emails name the rule and the detection but never include the flagged prompt text.
- Rules you create here watch this organization's admin and user audit activity.

Alert Deliveries

Every alert trigger is listed with its real delivery status: sent, queued, failed with the actual SMTP error, email not configured, or logged in-app. The log exports to **CSV**, archived deliveries included. Click **Archive** on a delivery to clear it from the default view — its history is kept, and **Show archived** reveals archived deliveries so you can review or **Restore** them. Tenant admins can archive their tenant's deliveries only.

WALKTHROUGH · 2:13 · ADMIN CONSOLE › DOCUMENTATION

Alerts and delivery

Check email delivery, create a rule from the Prompt-injection template with a recipient, follow a real flagged prompt to a delivered email, and know the other rule templates, including Support-reports.

Before you begin

- An Admin account.
- Email delivery configured by your service team. Without it, alerts are still logged in-app.
- The addresses that should receive alerts.

Step by step

1. Choose **Admin console** › **Alerts**. **Email Delivery** should read Email configured.
2. In **Alert Rules**, choose Prompt-injection template. **Suspicious-activity template** and Support-reports template prefill other rules the same way.
3. Check the action pattern security.prompt_flagged, the minimum severity, Fire when, and Cooldown.
4. Enter Email recipients, separated by commas.
5. Under Only these detections, keep or change the ticked detectors.
6. Choose **Create** Rule. The rule appears in the list, enabled.
7. When a matching prompt is flagged, **Alert Deliveries** shows the delivery and its status, such as sent.

Path: Prompt-injection template (shown)

1. Watches security.prompt_flagged for Prompt injection, System-prompt extraction, and Credential extraction, at Warning and above, every match, with a 10-minute cooldown.

Path: Suspicious-activity template

1. Watches security.*: security flags, content-filter hits, and elevated governance events, at Warning and above, with a 15-minute cooldown and no detection filter.

Path: Support-reports template (shown)

1. Prefills New support reports: action patterns support.issue_reported, support.issue_reporter_replied, and support.issue_reopened, at Info and above, every match, with no cooldown.
2. Add Email recipients and choose **Create** Rule. Each new report from **Help**, each reply from the person who reported, and each reopened report then sends an email. Work the ticket in Reports.

Path: New rule

1. Enter a Rule name. **Action patterns** accepts exact actions or prefixes such as admin.* or auth.*; empty matches every action.
2. Choose a minimum severity, an optional **Watched user**, Fire when (matches within minutes), and a cooldown.
3. Detections apply only to security.prompt_flagged events.

Path: In-app only

1. Leave Email recipients empty. Deliveries read logged in-app.

Check that it worked

- ✓ The rule appears enabled, with its patterns, detections, and recipient count.
- ✓ **Alert Deliveries** shows the delivery with status sent and the recipient.
- ✓ The email arrives with the rule and detection in its subject and no flagged text.

Troubleshooting

WHAT YOU SEE	WHAT TO DO
"A rule name is required."	Enter a Rule name.
"'…' is not a valid email address."	Separate recipients with commas and check each address.
"Detections only apply to security.prompt_flagged events. …"	Add security.prompt_flagged or security.* to **Action patterns**, or clear the detections.
"None of the chosen detections can reach the minimum severity '…'. …"	Lower **Minimum severity** or choose other detections.
A delivery reads email not configured	Email delivery is managed at the service level. The alert stays logged in-app; ask your service team to configure email.
A delivery reads failed	Its detail shows the mail server's real error. **Share** it with your service team.