

Portland State Aerospace Society <http://psas.pdx.edu/>

Sheet: /
File: LTC3.sch

Title: Launch Tower Computer 3 (LTC3)

Size: B	Date: 2016-09-07	**Rev: A**
KiCad E.D.A. kicad 4.0.2+dfsg1-stable		Id: 1/6



+5V DC Supply



+12V DC Supply



+19V DC Supply



Voltage, Current, & Temp Sense

Current Sense Resistors
full-scale voltage = 0.300 V
R_sense_max = 0.300/Imax
5 A = 60mΩ

TODO: add MicroFit housing contacts to BOM



Power In





Main Power Switch, Front Panel

NOTES
1. V_sense should connect as close as possible to the largest load on the given power rail.
2. Place Rset resistors as close to package pins as possible.
3. Ceramic (Cin) capacitors should be located within 0.5 in of the input pins.
4. We may need heat sinks on the converters. The datasheet indicates a range of 2W to 5W of power dissipation given our specs.
5. Pay attention to the datasheet's recommendations regarding capacitor selection.

Portland State Aerospace Society <http://psas.pdx.edu/>

Sheet: /DC-DC Converters/
File: dcdc_converter.sch

Title: LTC3 DC-DC Converters

Size: B	Date: 2016-09-04	**Rev: A**
KiCad E.D.A. kicad 4.0.2+dfsg1-stable		Id: 2/6



BeagleBone Expansion Headers

I2C Devices

ADDR	Part	Type	Location
0x10	U203	BQ77PL900	B/PM
0x54	U501	EEPROM	BBB
0x90	U402	LTC2991	DC-DC
0x98	U203	LTC2990	Power In
0x9A	U301	LTC2990	B/PM

NOTES:
* Do NOT change ROCKET_IGNITE, pin default reset state is High-Z w/ pulldown resistor. Other pins can be configured in EEPROM at boot time.
* All I2C devices on LTC3 are slaves. The BBB is the only master so the LTC will not need arbitration.

Portland State Aerospace Society <http://psas.pdx.edu/>

Sheet: /BeagleBone Black Cape/
File: beaglebone_cape.sch

Title: LTC3 BeagleBone Black Cape Interface

Size: B	Date: 2016-09-04	**Rev: A**
KiCad E.D.A. kicad 4.0.2+dfsg1-stable		Id: 3/6

Circuit keeps ignition battery pack disconnected until
flight computer has asserted ROCKET_READY and
19 VDC rail (shore power) has been shut off.

Input Logic



Delay (5s)



Ignition Battery Relay



Rocket Umbilical

Rocket-to-BeagleBone Ethernet



TODO: conn. to umbilical conn. on front panel

VCC for CD74HC14



Bypass Capacitors (one per IC VCC)



BAKERCON Hazard Gauge

(super-bright LEDs, exterior panel)





Rocket Ignition Relay



TODO: add MicroFit housing contacts to BOM

TODO: find out if Dialight 557 LED indicators require current-limiting resistor

Breaker, Arm Switch, Shorting Bar, & Ignition Connector

(front panel)



Portland State Aerospace Society <http://psas.pdx.edu/>

Sheet: /Rocket Umbilical & Ignition Control/
File: rocket_interface.sch

Title: LTC3 Rocket Umbilical & Ignition Control

Size: B	Date: 2016-09-04	Rev: A
KiCad E.D.A. kicad 4.0.2+dfsg1-stable		Id: 4/6



Portland State Aerospace Society <http://psas.pdx.edu/>

Sheet: /External Device Power/
File: external_power.sch

Title: LTC3 External Device Power

Size: B	Date: 2016-09-04	**Rev: A**
KiCad E.D.A. kicad 4.0.2+dfsg1-stable		Id: 5/6













Trigger Outlets, Front Panel
Anderson PowerPole PP15-45

TODO: add MicroFit housing contacts to BOM

Portland State Aerospace Society <http://psas.pdx.edu/>

Sheet: /External Device Triggers/
File: external_triggers.sch

Title: LTC3 External Device Triggers

Size: B	Date: 2016-09-04	**Rev: A**
KiCad E.D.A. kicad 4.0.2+dfsg1-stable		Id: 6/6