

12"x10"x5" Vented Weatherproof Industrial Enclosure with Mounting Plate Model: NB121005-00V

Applications

- Remote Wireless LAN WiFi equipment installations
- Indoor and outdoor installations
- Rapid Deployment installations
- Corrosive environments
- Security and surveillance equipment installations

Features

- Molded fiberglass reinforced polyester (FRP) enclosure with integral mounting flanges
- Fully gasketed vented lid with stainless steel quick release latches with padlock hasps
- NEMA Type 3R, 3X / IP24 rated
- Features aluminum mounting plate



Description

The NB121005-00V is a rugged weatherproof enclosure that is ideal for both indoor and outdoor applications. Constructed from molded halogen free self extinguishing fiberglass reinforced polyester (FRP), it is well suited for high temperature or corrosive environments. The integral mounting flange allows it to be wall mounted as well as on a flat surface without the need for extra mounting hardware. The fully gasketed lid features a stainless steel continuous hinge and stainless steel quick release latches with padlock hasps. The light grey color of the NB121005-00V is cleaner, cooler and aesthetically pleasing. Users can enjoy the physical benefits of better heat reflection and better UV resistance due to the lighter color. The contoured body provides an attractive and contemporary appearance. Holes provided in the enclosure can be used for two Type-N bulkhead lightning protectors or connectors. In addition, a grounding lug and a cable conduit connector are provided.

Mounting Plate

The aluminum mounting plate included with the NB121005-00V feature cutouts for standard duplex power outlets.

Vented Lid

The NB121005-00V features a vented lid with removable filters and vent covers on the outside of the enclosure.

Optional Pole Mounting Kits

Available on the L-com web site, these optional kits allows the enclosure to be mounted on poles ranging from 1.2 to 11 inches in diameter.

Specifications

Enclosure Material	Halogen free, self extinguishing fiberglass reinforced polyester
Enclosure Color	Light Grey
Weight	7.6 lbs (3.4 kg)
Mounting Plate Material	.10" (2.5mm) Thick Anodized Aluminum
Mounting Plate Dimensions	12 x 9.13 inches (30.5 x 23.2 cm)
Outside Dimensions (max)	13.32 x 11.32 x 5.60 in. (38.83 x 28.75 x 14.22 cm)
Inside Dimensions	12.00 x 10.00 x 5.27 in. (4.69 inches plate to cover) (30.48 x 25.40 x 13.39 cm)
Flame Rating	UL 94-5V
RoHS Compliant	Yes
Cable Feed	1/2" Cable Conduit Connector
Ratings	NEMA Type 3R, 3X / IP24

