











TODO:
* Finish wiring up sub-sheets.
  * Bus entries need labels on both sides!

Notes:
 * LTC3 is a single board represented on multiple sheets.

Portland State Aerospace Society <http://psas.pdx.edu/>

Sheet: /
File: Launch_Tower_Computer_III.sch

Title: Launch Tower Computer 3 (LTC3)

Size: B	Date: 2015-12-23	**Rev: A**
KiCad E.D.A. kicad 4.0.0rc1a-stable		Id: 1/7

QUESTIONS:
* **Safe to use one current-sense resistor for both the LT8490 and the LTC2991?**
  * **Maybe. Check datasheets for input impedances. Add zero-ohm resistor btw. 2991 and shunt.**
* **What happens w/out a battery connected?**

PV_IN:
Open Circuit = 17 V
Short Circuit = 2.4 A

Current Sense (p. 20)

Supply Detection (p.34)

p. 15, p. 34

Shutdown (p. 27)

Input Feedback p.14

202kHz switch

Output Feedback (p. 17)

Temp Sense (p. 21)

Feedback Resistor Disconnect

LT8490
U202

Voltage, Current, & Temp Sense

I2C addr 0x98

CHARGING PARAMETERS:
Stage 2 Voltage: 33.6 V
Maximum Charging Current: 11.4 A
Maximum Trickle Current: 3 A
Switching Frequency: 202 kHz

Portland State Aerospace Society <http://psas.pdx.edu/>

Sheet: /Power In & Battery Charge Management/
File: battery_mgmt.sch

Title: Power In, Battery Management

Size: B	Date: 2015-12-16	Rev: A
KiCad E.D.A. kicad 4.0.0rc1a-stable		Id: 2/7



QUESTIONS:
* Leave XRST (open drain) unconnected (p.35)?
* Are caps on VOUT and IOUT necessary if both outputs are disabled (pp.30,33)?

NB:
* Page references are to the bq datasheet.
* "PHNTM" components represent off-board devices. Do not assign footprints to these components.
* bq77PL900 I2C addr is 0x10 (p.38).

UNCONNECTED PINS
* VOUT and IOUT are internally connected to ground when disabled (pp. 30, 33).
* XRST is an open-drain output with an internal 3k pull-up to VLOG (p. 35).

Portland State Aerospace Society <http://psas.pdx.edu/>

Sheet: /Battery, Balance & Protection/
File: battery_balance.sch

Title: Battery Balance

Size: B	Date: 2015-12-23	**Rev: A**
KiCad E.D.A. kicad 4.0.0rc1a-stable		Id: 3/7



+5V DC Rail



+12V DC Rail



+19V DC Rail



Voltage, Current, & Temp Sense

Current Sense Resistors
full-scale voltage = 0.300 V
R_sense_max = 0.300/Imax
1 A = 300mΩ
3 A = 100mΩ
5 A = 60mΩ
10 A = 30mΩ

NB:
1. V_sense should connect as close as possible to the largest load on the given power rail.
2. Place Rset resistors as close to package pins as possible.
3. Ceramic (Cin) capacitors should be located within 0.5 in of the input pins.
4. We may need heat sinks on the converters. The datasheet indicates a range of 2W to 5W of power dissipation given our specs.
5. Pay attention to the datasheet's recommendations regarding capacitor selection.

TODO:
* Capacitor values are minimums. Consider increasing these. Consult datasheet for more info.

Portland State Aerospace Society <http://psas.pdx.edu/>

Sheet: /DC-DC Converters/		
File: dcdc_converter.sch		
Title: LTC3 DC-DC Converters		
Size: B	Date: 2015-12-23	**Rev: A**
KiCad E.D.A. kicad 4.0.0rc1a-stable		Id: 4/7



BeagleBone Expansion Headers

TODO: connect these labels
to BBB GPIO pins.

ROCKET_READY

BQ_XALERT

EXT_PWR_EN_1
EXT_PWR_EN_2
EXT_PWR_EN_3
EXT_PWR_EN_4

5V_EN
12V_EN
19V_EN

BQ_EEPROM

ROCKET_IGNITE



Cape EEPROM

TODO:
* Pick GPIO for rocket-ready signal.
* Buffer btw rocket-ready signal and BB, ign. board, etc?
* Umbilical connection state
* Ignition fuse state

Portland State Aerospace Society <http://psas.pdx.edu/>

Sheet: /BeagleBone Black Cape/
File: beaglebone_cape.sch

Title: LTC3 BeagleBone Black Cape Interface

Size: B	Date: 2015-12-15	Rev: A
KiCad E.D.A. kicad 4.0.0rc1a-stable		Id: 5/7



Input Logic



Delay (5s)



Ignition Battery Switch



Rocket Umbilical



Ignition Switch



VCC for
CD74HC14

Bypass Capacitors
(one per IC VCC)

TODO:
* Select appropriate component values.
* Finish rocket umbilical connector.
  * Verify Enet jack "adapter" wiring.
  * Add umbilical connect sense lines circuitry.
* Label various LEDs.

QUESTIONS:
  *Will 5v from schmidt fry BBB GPIO?

Portland State Aerospace Society <http://psas.pdx.edu/>

Sheet: /Rocket Umbilical & Ignition Control/
File: rocket_interface.sch

Title: LTC3 Rocket Umbilical & Ignition Control

Size: B	Date: 2015-12-16	**Rev: A**
KiCad E.D.A. kicad 4.0.0rc1a-stable		Id: 6/7



External Device Power



External Device Triggers

TODO:
* Determine values for bleeder resistor and filter capacitor on each output connector.
* Pick new PolyFuses, 0.5–1.0A max.

Portland State Aerospace Society <http://psas.pdx.edu/>

Sheet: /External Device Power & Triggers/
File: external_devices.sch

Title: LTC3 External Power & Triggers

Size: B	Date: 2015-12-15	**Rev: A**
KiCad E.D.A. kicad 4.0.0rc1a-stable		id: 7/7