

Syntax Analysis (a.k.a. Parsing)

Grammar analysis and recursive descent parsing.

©SoftMoore Consulting

Slide 1


Parser

- Verifies that the grammatical rules of the language are satisfied
- Overall parser structure is based on context-free grammars (a.k.a. BNF/EBNF grammars)
- Input: stream of tokens from the scanner
From the perspective of the parser, each token is treated as a terminal symbol.
- Output: intermediate representation of the source code (e.g., abstract syntax trees)

©SoftMoore Consulting

Slide 2

Parser (continued)



©SoftMoore Consulting

Slide 3

Functions of the Parser

- Language recognition based on syntax, as defined by a context-free grammar
- Error Handling/Recovery
- Generation of intermediate representation (We will generate abstract syntax trees.)

The primary focus of this section is language recognition. Subsequent sections will cover error recovery and generation of abstract syntax trees.

©SoftMoore Consulting

Slide 4

Recursive Descent Parsing

- Parsing technique used in this course: recursive descent with single symbol lookahead.
(Briefly discuss other options.)
- Uses recursive methods to “descend” through the parse tree (top-down parsing) as it parses a program.
- The parser is constructed systematically from the grammar using a set of programming refinements.

©SoftMoore Consulting

Slide 5

Initial Grammar Transformations

- Start with an unambiguous grammar.
- Separate lexical grammar rules from structural rules.
 - Let the scanner handle simple rules (operators, identifiers, etc.).
 - Symbols from the scanner become terminal symbols in the grammar for the parser.
- Use a single rule for each nonterminal; i.e., each nonterminal appears on the left side of only one rule.
- Eliminate left recursion.
- Left factor wherever possible.
- Certain grammar restrictions will be discussed in subsequent slides.

©SoftMoore Consulting

Slide 6

Recursive Descent Parsing Refinement 1

- For every rule in the grammar
 $N = \dots$
 we define a parsing method with the name
`parseN()`
- Example: For the rule
`assignmentStmt = variable ":" expression ";"`
 we define a parsing method named
`parseAssignmentStmt()`
- Grammar transformations can be used to simplify the grammar before applying this refinement; e.g., substitution of nonterminals.

©SoftMoore Consulting

Slide 7

Recursive Descent Parsing Methods

The `parseN()` methods of the parser function as follows:

- The scanner method `getSymbol()` provides one symbol "lookahead" for the parsing methods.
- On entry into the method `parseN()`, the symbol returned from the scanner should contain a symbol that could start on the right side of the rule $N = \dots$.
- On exit from the method `parseN()`, the symbol returned from the scanner should contain the first symbol that could follow a syntactic phrase corresponding to N .
- If the production rules contain recursive references, the parsing methods will also contain recursive calls.

©SoftMoore Consulting

Slide 8

Parsing the "Right" Side of a Rule

- We now turn our attention to refinement of the method `parseN()` associated with a production rule " $N = \dots$ " by examining the form of the grammatical expression on the right side of the rule.
- As an example, for the rule
`assignmentStmt = variable ":" expression ";"`
 we have defined a parsing method named
`parseAssignmentStmt()`
 We focus on systematic implementation of this method by examining the right side of the rule.

©SoftMoore Consulting

Slide 9

Recursive Descent Parsing Refinement 2

- A sequence of syntax factors $F_1 F_2 F_3 \dots$ is recognized by parsing the individual factors one at a time in order.
- In other words, the algorithm for parsing $F_1 F_2 F_3 \dots$ is simply
 - the algorithm for parsing F_1 followed by
 - the algorithm for parsing F_2 followed by
 - the algorithm for parsing F_3 followed by
 - ...

©SoftMoore Consulting

Slide 10

Example: Recursive Descent Parsing Refinement 2

The algorithm used to parse
`variable ":" expression ";"`
 is simply

- the algorithm used to parse `variable` followed by
- the algorithm used to parse `":"` followed by
- the algorithm used to parse `expression` followed by
- the algorithm used to parse `;"`

©SoftMoore Consulting

Slide 11

Recursive Descent Parsing Refinement 3

- A single terminal symbol t on the right side of a rule is recognized by calling the "helper" parsing method `match(t)` defined as

```
private void match(Symbol expectedSymbol)
    throws IOException, ParseException
{
    if (scanner.getSymbol() == expectedSymbol)
        scanner.advance();
    else
        ... // throw ParseException
}
```

- Example: The algorithm for recognizing the assignment operator `":"` is simply the method call
`match(Symbol.assign)`

©SoftMoore Consulting

Slide 12

Recursive Descent Parsing Refinement 4

- A nonterminal symbol N on the right side of a rule is recognized by calling the method corresponding to the rule for N ; i.e., the algorithm for recognizing nonterminal N is simply a call to the method `parseN()`.
- Example: The algorithm for recognizing the nonterminal symbol expression on the right side of a rule is simply a call to the method `parseExpression()`.

©SoftMoore Consulting

Slide 13

Example: Application of the Recursive Descent Parsing Refinements

- Consider the rule for an assignment statement:
`assignmentStmt = variable ":" expression ";"` .
- The complete parsing method for recognizing an assignment statement is as follows:

```
public void parseAssignmentStmt()
{
    parseVariable();
    match(Symbol.assign);
    parseExpression();
    match(Symbol.semicolon);
}
```

©SoftMoore Consulting

Slide 14

First Sets

- The set of all **terminal** symbols that can appear at the start of a syntax expression E is denoted $\text{First}(E)$.
- First sets provide important information that can be used to guide decisions during parser development.

©SoftMoore Consulting

Slide 15

First Set Examples from CPRL

- `constDecl = "const" constId ":" literal ";"` .
 $\text{First}(\text{constDecl}) = \{ \text{"const"} \}$
- `varDecl = "var" identifiers ":" typeName ";"` .
 $\text{First}(\text{varDecl}) = \{ \text{"var"} \}$
- `arrayTypeDecl = "type" typeId "=" "array" ... ";"` .
 $\text{First}(\text{arrayTypeDecl}) = \{ \text{"type"} \}$
- `initialDecl = constDecl | arrayTypeDecl | varDecl` .
 $\text{First}(\text{initialDecl}) = \{ \text{"const"}, \text{"var"}, \text{"type"} \}$
- `statementPart = "begin" statements "end"` .
 $\text{First}(\text{statementPart}) = \{ \text{"begin"} \}$
- `loopStmt = ("while" booleanExpr)? "loop" ... ";"` .
 $\text{First}(\text{loopStmt}) = \{ \text{"while"}, \text{"loop"} \}$

©SoftMoore Consulting

Slide 16

Rules for Computing First Sets

- If t is a terminal symbol, $\text{First}(t) = \{ t \}$
- If all strings derived from E are nonempty, then $\text{First}(E F) = \text{First}(E)$
- If some strings derived from E can be empty, then $\text{First}(E F) = \text{First}(E) \cup \text{First}(F)$
- $\text{First}(E | F) = \text{First}(E) \cup \text{First}(F)$

©SoftMoore Consulting

Slide 17

Computing First Sets: Special Cases

The following rules can be derived as special cases of the previous rules

- $\text{First}((E)^*) = \text{First}(E)$
- $\text{First}((E)^+) = \text{First}(E)$
- $\text{First}((E)?) = \text{First}(E)$
- $\text{First}((E)^* F) = \text{First}(E) \cup \text{First}(F)$
- $\text{First}((E)^+ F) = \text{First}(E)$ if all strings derived from E are nonempty
- $\text{First}((E)^+ F) = \text{First}(E) \cup \text{First}(F)$ if some strings derived from E are empty
- $\text{First}((E)?) F = \text{First}(E) \cup \text{First}(F)$

©SoftMoore Consulting

Slide 18

Strategy for Computing First Sets

- Use a bottom-up approach
- Start with simplest rules and work toward more complicated (composite) rules.

©SoftMoore Consulting

Slide 19

Follow Sets

- The set of all **terminal** symbols that can follow immediately after a syntax expression E is denoted Follow(E).
- Understanding Follow sets is important not only for parser development but also for error recovery.
- If N is a nonterminal, we will use Follow(N) during error recovery when trying to parse N. To compute Follow(N) for a nonterminal N, you must analyze all rules that reference N.
- Computation of follow sets can be a bit more involved than computation of first sets.

©SoftMoore Consulting

Slide 20

Follow Set Examples from CPRL

- What can follow an initialDecl?
 - From the rule
 $\text{initialDecls} = (\text{initialDecl})^*$.
 we know that any initialDecl can follow an initialDecl, so the follow set for initialDecl includes the first set of initialDecl; i.e., "const", "var", and "type".
 - From the rules
 $\text{declarativePart} = \text{initialDecls} \text{ subprogramDecls} .$
 $\text{subprogramDecls} = (\text{subprogramDecl})^* .$
 $\text{subprogramDecl} = \text{procedureDecl} \mid \text{functionDecl} .$
 we know that a procedureDecl or functionDecl can follow an initialDecl, so the follow set for initialDecl includes "procedure" and "function".

©SoftMoore Consulting

Slide 21

Follow Set Examples from CPRL (continued)

- From the rules
 $\text{program} = \text{declarativePart} \text{ statementPart} "." .$
 $\text{statementPart} = "begin" \text{ statements } "end" .$
 we know that statementPart can follow an initialDecl, so the follow set for initialDecl includes "begin".
- Conclusion:
 $\text{Follow}(\text{initialDecl}) = \{ "const", "var", "type", "procedure", "function", "begin" \}$
- What can follow a loopStmt?
 - ... (left as an exercise)
 - Conclusion:
 $\text{Follow}(\text{loopStmt}) = \{ \text{identifier}, "return", "end", "if", "elsif", "else", "while", "loop", "exit", "read", "write", "writeln" \}$

©SoftMoore Consulting

Slide 22

Rules for Computing Follow Sets

Computing Follow(T)

- Consider all production rules similar to the following:
 $N = S T U . \quad N = S (T)^* U . \quad N = S (T) ? U .$
 - Follow(T) includes First(U).
 - If U can be empty, then Follow(T) also includes Follow(N).
- Consider all production rules similar to the following:
 $N = S T . \quad N = S (T)^* . \quad N = S (T) ? .$
 In all these cases, Follow(T) includes Follow(N).
- If T occurs in the form $(T)^*$ or $(T)^+$, then Follow(T) includes First(T).

©SoftMoore Consulting

Slide 23

Strategy for Computing Follow Sets

- Use a top-down approach.
- Start with first rule (the one containing the start symbol) and work toward the simpler rules.

©SoftMoore Consulting

Slide 24

Recursive Descent Parsing Refinement 5

- A syntax factor of the form $(E)^*$ is recognized by the following algorithm:
while current symbol is in First(E) loop
apply the algorithm for recognizing E
end loop
- Grammar Restriction 1:** First(E) and Follow($(E)^*$) must be disjoint in this context; i.e.,
 $\text{First}(E) \cap \text{Follow}((E)^*) = \emptyset$
 (Why?)

©SoftMoore Consulting

Slide 25

Example: Recursive Descent Parsing Refinement 5

- Consider the rule for initialDecls:
 $\text{initialDecls} = (\text{initialDecl})^* .$
- The CPRL method for parsing initialDecls is

```
public void parseInitialDecls()
{
    while (scanner.getSymbol() == Symbol.constRW ||
           scanner.getSymbol() == Symbol.varRW ||
           scanner.getSymbol() == Symbol.typeRW)
    {
        parseInitialDecl();
    }
}
```
- In CPRL, the symbols “const”, “var”, and “type” cannot follow initialDecls. (Which symbols can follow?)

©SoftMoore Consulting

Slide 26

Helper Methods in Class Symbol

Class Symbol provides several helper methods for testing properties of symbols.

```
public boolean isReservedWord()
public boolean isInitialDeclStarter()
public boolean isSubprogramDeclStarter()
public boolean isStmtStarter()
public boolean isLogicalOperator()
public boolean isRelationalOperator()
public boolean isAddingOperator()
public boolean isMultiplyingOperator()
public boolean isLiteral()
public boolean isExprStarter()
```

©SoftMoore Consulting

Slide 27

Method isStmtStarter()

```
/**
 * Returns true if this symbol can start a statement.
 */
public boolean isStmtStarter()
{
    return this == Symbol.exitRW
        || this == Symbol.identifier
        || this == Symbol.ifRW
        || this == Symbol.loopRW
        || this == Symbol.whileRW
        || this == Symbol.readRW
        || this == Symbol.writeRW
        || this == Symbol.writelnRW
        || this == Symbol.returnRW;
}
```

©SoftMoore Consulting

Slide 28

Method isInitialDeclStarter()

```
/**
 * Returns true if this symbol can start an initial declaration.
 */
public boolean isInitialDeclStarter()
{
    return this == Symbol.constRW
        || this == Symbol.varRW
        || this == Symbol.typeRW;
}
```

©SoftMoore Consulting

Slide 29

Using Helper Methods in Class Symbol

Using the helper methods in class Symbol, we can rewrite the code for parseInitialDecls() as follows:

```
public void parseInitialDecls()
{
    while (scanner.getSymbol().isInitialDeclStarter())
        parseInitialDecl();
}
```

©SoftMoore Consulting

Slide 30

Recursive Descent Parsing Refinement 6

- Since a syntax factor of the form $(E)^+$ is equivalent to $E(E)^*$, a syntax factor of the form $(E)^+$ is recognized by the following algorithm:

```

    apply the algorithm for recognizing E
    while current symbol is in First(E) loop
        apply the algorithm for recognizing E
    end loop

```
- Equivalently, the algorithm for recognizing $(E)^+$ can be written using a loop that tests at the bottom.

```

    loop
        apply the algorithm for recognizing E
    exit when current symbol is not in First(E)
    end loop

```

©SoftMoore Consulting

Slide 31

Recursive Descent Parsing Refinement 6 (continued)

- In Java, the loop structure that tests at the bottom is called a do-while loop, so the algorithm implemented in Java would more closely resemble the following:

```

do
    apply the algorithm for recognizing E
while current symbol is in First(E)

```
- Grammar Restriction 2:** If E can generate the empty string, then $\text{First}(E)$ and $\text{Follow}(E)^+$ must be disjoint in this context; i.e., $\text{First}(E) \cap \text{Follow}(E)^+ = \emptyset$ (Why?)

©SoftMoore Consulting

Slide 32

Recursive Descent Parsing Refinement 7

- A syntax factor of the form $(E)?$ is recognized by the following algorithm:

```

if current symbol is in First(E) then
    apply the algorithm for recognizing E
end if

```
- Grammar Restriction 3:** $\text{First}(E)$ and $\text{Follow}(E)?$ must be disjoint in this context; i.e., $\text{First}(E) \cap \text{Follow}(E)? = \emptyset$ (Same reason as before.)

©SoftMoore Consulting

Slide 33

Helper Method matchCurrentSymbol()

- Method `matchCurrentSymbol()` is similar to method `match()` except that it takes no parameters and doesn't throw an exception. It simply advances the scanner.
- Method `matchCurrentSymbol` is used when we already know that the next symbol in the input stream is the one we want. We could use `match()` for this purpose, but `matchCurrentSymbol()` is slightly more efficient.
- Method `matchCurrentSymbol()`

```

private void matchCurrentSymbol() throws IOException
{
    scanner.advance();
}

```

©SoftMoore Consulting

Slide 34

Example: Recursive Descent Parsing Refinement 7

- Consider the rule for an exit statement:
`exitStmt = "exit" ("when" booleanExpr)? ";" .`
- The method for parsing an exit statement is

```

public void parseExitStmt()
{
    match(Symbol.exitRW);
    if (scanner.getSymbol() == Symbol.whenRW)
    {
        matchCurrentSymbol();
        parseExpression();
    }
    match(Symbol.semicolon);
}

```

first set for optional when clause

slightly more efficient than `match(Symbol.whenRW)`

©SoftMoore Consulting

Slide 35

Example: Recursive Descent Parsing Refinement 7 (continued)

- The first set for the optional when clause is simply $\{ \text{"when"} \}$, so we use the reserved word when to tell us whether or not to parse a when clause.
- Questions: What is the follow set for the optional when clause? What problem would we have if it contained the reserved word "when"?

©SoftMoore Consulting

Slide 36

Recursive Descent Parsing Refinement 8

- A syntax factor of the form $E \mid F$ is recognized by the following algorithm:
 - if current symbol is in $\text{First}(E)$ then
 - apply the algorithm for recognizing E
 - elseif current symbol is in $\text{First}(F)$ then
 - apply the algorithm for recognizing F
 - else
 - parsing error
 - end if
- Grammar Restriction 4:** $\text{First}(E)$ and $\text{First}(F)$ must be disjoint in this context; i.e., $\text{First}(E) \cap \text{First}(F) = \emptyset$

©SoftMoore Consulting

Slide 37

Example: Recursive Descent Parsing Refinement 8

- Consider the rule in CPRL for `initialDecl`:
`initialDecl = constDecl | varDecl | arrayTypeDecl .`
- The CPRL method for parsing `initialDecl` is


```
public void parseInitialDecl()
{
    if (scanner.getSymbol() == Symbol.constRW)
        parseConstDecl();
    else if (scanner.getSymbol() == Symbol.varRW)
        parseVarDecl();
    else if (scanner.getSymbol() == Symbol.typeRW)
        parseArrayTypeDecl();
    else
        ... // throw an InternalErrorException
}
```

(This logic could also be implemented using a switch statement.)

©SoftMoore Consulting

Slide 38

LL(1) Grammars

- If a grammar satisfies the restrictions imposed by the previous parsing rules, then the grammar is called an **LL(1) grammar**.
- Recursive descent parsing using one symbol lookahead can be used only if the grammar is LL(1).
 - First 'L': read the source file from left to right
 - Second 'L': descend into the parse tree from left to right
 - Number '1': one token lookahead
- The phrase "recursive descent" refers to the fact that we descend (top-down) the parse tree using recursive method/function calls.

©SoftMoore Consulting

Slide 39

LL(1) Grammars (continued)

- Not all grammars are LL(1).
 - e.g., any grammar has left recursion is not LL(1)
- In practice, the syntax of most programming languages can be defined, or at least closely approximated, by an LL(1) grammar.
 - e.g., by using grammar transformations such as eliminating left recursion

©SoftMoore Consulting

Slide 40

Developing a Parser

Three major versions of the parser for the compiler project:

- Version 1: Language recognition based on a context-free grammar (with minor checking of language constraints)
- Version 2: Add error-recovery
- Version 3: Add generation of abstract syntax trees

©SoftMoore Consulting

Slide 41

Developing a Parser for CPRL Version 1: Language Recognition

- Use the parsing refinements discussed earlier.
- Verify that the grammar restrictions (in terms of first and follow sets) are satisfied by the grammar for CPRL.
- Use the grammar to develop version 1 of the parser.
 - requires grammar analysis
 - computation of first and follow sets

©SoftMoore Consulting

Slide 42

Variables versus Named Values

- From the perspective of the grammar, there is no real distinction between a variable and a named value.
`variable = (varId | paramId) ("[" expression "]")* .`
`namedValue = variable .`
- Both are parsed similarly, but we make a distinction based on the context where the identifier appears.
- For example, consider the assignment statement
`x := y;`
 The identifier "x" represents a variable, and the identifier "y" represents a named value.

©SoftMoore Consulting

Slide 43

Variables versus Named Values (continued)

- Loosely speaking, it's a variable if it appears on the left side of an assignment statement, and it's a named value if it is used as an expression.
- The distinction between a variable and a named value will become important later when we consider the topics of error recovery and code generation – the error recovery and code generation are different for a variable than for a named value.

©SoftMoore Consulting

Slide 44

Handling Grammar Limitations

- As given, the grammar for CPRL is "not quite" LL(1)
- Example: Parsing a statement.
`statement = assignmentStmt | ifStmt | loopStmt | exitStmt`
`| readStmt | writeStmt | writeLnStmt`
`| procedureCallStmt | returnStmt .`
- Use the lookahead symbol to select the parsing method.
 - "if" → parse an "if" statement
 - "while" → parse a loop statement
 - "loop" → parse a loop statement
 - identifier → parse either an assignment statement or procedure call statement (which one?)
- An identifier is in the first set of both an assignment statement and a procedure call statement.

©SoftMoore Consulting

Slide 45

Handling Grammar Limitations (continued)

- A similar problem exists when parsing a factor.
`factor = "not" factor | constValue | namedValue`
`| functionCall | "(" expression ")" .`
- An identifier is in the first set of constValue, namedValue, and functionCall.

©SoftMoore Consulting

Slide 46

Possible Solutions

- Use additional token lookahead – LL(2)
 - If the symbol following the identifier is "[" or ":", parse an assignment statement.
 - If it is "(" or ";", parse a procedure call statement.
- Redesign/factor the grammar; e.g., replace
`"s = i x | i y ."` with `"s = i (x | y) ."`
- Use an identifier table to store information about how the identifier was declared, and then later use the declaration information to determine if the identifier is a constant, variable, procedure name, etc.

We will use the third approach.

©SoftMoore Consulting

Slide 47

Class IdTable (Version 1)

- We will create a preliminary version class IdTable to help track identifiers that have been declared and to assist with basic constraint analysis of scope rules.

- Types of Identifiers

```
enum IdType
{
    constantId, variableId, arrayTypeId,
    procedureId, functionId;
}
```

Class IdTable will be extended in subsequent assignments to perform a more complete analysis of CPRL scope rules.

©SoftMoore Consulting

Slide 48

Procedure Example – Scope

```
var x : Integer;
var y : Integer;

procedure p is
  var x : Integer;
  var n : Integer;
begin
  x := 5;    // which x?
  n := y;    // which y?
end p;

begin
  x := 8;    // which x?
end.
```

©SoftMoore Consulting

Slide 49

Handling Scopes within Class IdTable

- Variables and constants can be declared at the program level or at the subprogram level, introducing the concept of scope.
- Class IdTable will need to search for names both within the current scope and possibly in enclosing scopes.
- Class IdTable is implemented as a stack of maps from identifier strings to their IdType.
 - When a new scope is opened, a new map is pushed onto the stack.
 - Searching for a declaration involves searching within the current level (top map in the stack) and then within enclosing scopes (maps under the top).

©SoftMoore Consulting

Slide 50

Selected Methods in IdTable

```
/**
 * Opens a new scope for identifiers.
 */
public void openScope()

/**
 * Closes the outermost scope.
 */
public void closeScope()

/**
 * Add a token and its type at the current scope level.
 * @throws ParseException if the identifier token is already
 *   defined in the current scope.
 */
public void add(Token idToken, IdType idType)
    throws ParseException
```

©SoftMoore Consulting

Slide 51

Selected Methods in IdTable (continued)

```
/**
 * Returns the id type associated with the identifier.
 * Returns null if the identifier is not found. Searches
 * enclosing scopes if necessary.
 */
public IdType get(Token idToken)
```

©SoftMoore Consulting

Slide 52

Adding Declarations to IdTable

- When an identifier is declared, the parser will attempt to add its token and IdType to the table within the current scope.
 - throws an exception if an identifier with the same name (same token text) has been previously declared in the current scope.
- Example from method parseConstDecl()


```
idTable.add(constId, IdType.constantId);
```

Throws a ParseException if
the identifier is already defined
in the current scope

©SoftMoore Consulting

Slide 53

Using IdTable to Check Applied Occurrences of Identifiers

When an identifier is encountered in the statement part of the program or a subprogram, the parser will

- check that the identifier has been declared
- use the information about how the identifier was declared to facilitate correct parsing (e.g., you can't assign a value to an identifier that was declared as a constant.)

©SoftMoore Consulting

Slide 54

Example Using IdTable to Check Applied Occurrences of Identifiers

```
// in method parseFactor()
else if (scanner.getSymbol() == Symbol.identifier)
{
    // Handle identifiers based on whether they are
    // declared as variables, constants, or functions.
    Token idToken = scanner.getToken();
    IdType idType = idTable.get(idToken);

    if (idType != null)
    {
        if (idType == IdType.constantId)
            parseConstValue();
        else if (idType == IdType.variableId)
            parseNamedValue();
        else if (idType == IdType.functionId)
            parseFunctionCall();
    }
}
```

©SoftMoore Consulting

Slide 55

Example Using IdTable to Check Applied Occurrences of Identifiers (continued)

```
else
    throw error("Identifier \"" + scanner.getToken()
        + "\" cannot be part of an expression.");
}
else
    throw error("Identifier \"" + scanner.getToken()
        + "\" has not been declared.");
}
```

©SoftMoore Consulting

Slide 56

Example: Parsing a Procedure Declaration

```
// procedureDecl = "procedure" procId ( formalParameters )?
// "is" initialDecls statementPart procId ";" .
match(Symbol.procedureRW);
Token procId = scanner.getToken();
match(Symbol.identifier);
idTable.add(procId, IdType.procedureId);
idTable.openScope();

if (scanner.getSymbol() == Symbol.leftParen)
    parseFormalParameters();

match(Symbol.isRW);
parseInitialDecls();
parseStatementPart();
idTable.closeScope();
```

Note that the procedure name is defined in the outer (program) scope, but its parameters and initial declarations are defined within the scope of the procedure.

©SoftMoore Consulting

Slide 57

Example: Parsing a Procedure Declaration (continued)

```
Token procId2 = scanner.getToken();
match(Symbol.identifier);

if (!procId.getText().equals(procId2.getText()))
    throw error(procId2.getPosition(),
        "Procedure name mismatch.");

match(Symbol.semicolon);
```

Note the check that the procedure names (procId and procId2) match. Technically, ensuring that the procedure names match goes beyond simple syntax analysis and represents more of a constraint check. As far as the context-free grammar is concerned, they are both just identifiers.

©SoftMoore Consulting

Slide 58

Example: Parsing a Statement

```
Symbol symbol = scanner.getSymbol();
if (symbol == Symbol.identifier)
{
    IdType idType = idTable.get(scanner.getToken());
    if (idType != null)
    {
        if (idType == IdType.variableId)
            parseAssignmentStmt();
        else if (idType == IdType.procedureId)
            parseProcedureCallStmt();
        else
            throw error(...);
    }
    else
        throw error(...);
}
(continued on next slide)
```

©SoftMoore Consulting

Slide 59

Example: Parsing a Statement (continued)

```
else if (symbol == Symbol.ifRW)
    parseIfStmt();
else if (symbol == Symbol.loopRW || symbol == Symbol.whileRW)
    parseLoopStmt();
else if (symbol == Symbol.exitRW)
    parseExitStmt();
...
```

©SoftMoore Consulting

Slide 60

Class ErrorHandler

- Used for consistency in error reporting.
- Implements the singleton pattern (only one instance)
- Obtain an instance of ErrorHandler by calling `ErrorHandler.getInstance()`

©SoftMoore Consulting

Slide 61

Key Methods Class ErrorHandler

```
/**
 * Reports the error. Stops compilation if the maximum
 * number of errors have been reported.
 */
public void reportError(CompilerException e)

/**
 * Reports the error and exits compilation.
 */
public void reportFatalError(Exception e)

/**
 * Reports a warning and continues compilation.
 */
public void reportWarning(String warningMessage)
```

©SoftMoore Consulting

Slide 62

Using ErrorHandler for Parser Version 1

- Version 1 of the parser does not implement error recovery. When an error is encountered, the parser will print an error message and then exit.
- In order to ease the transition to error recovery in the next version of the parser, most parsing methods will wrap the basic parsing methods in a try/catch block.
- Any parsing method that calls `match()` or the `add()` method of `IdTable` will need to have a try/catch block.
- Error reporting will be implemented within the catch clause of the try/catch block.

©SoftMoore Consulting

Slide 63

Using ErrorHandler for Parser Version 1 (continued)

```
public void parseAssignmentStmt() throws IOException
{
    try
    {
        parseVariable();
        match(Symbol.assign);
        parseExpression();
        match(Symbol.semicolon);
    }
    catch (ParserException e)
    {
        ErrorHandler.getInstance().reportError(e);
        exit();
    }
}
```

wrap the parsing statements in a try/catch block

This approach provides the framework that we will use for error recovery in the next section.

©SoftMoore Consulting

Slide 64

Implementing methods `parseVariable()` and `parseNamedValue()`

- To implement methods `parseVariable()` and `parseNamedValue()` we use a helper method to provide common logic for both methods.
- The helper method does not handle any parser exceptions but instead throws them back to the calling method where they can be handled appropriately.
- An outline of the helper method, `parseVariableExpr()`, is shown on the next couple of slides.
- Both `parseVariable()` and `parseNamedValue()` call the helper method to parse the grammar rule for variable.

©SoftMoore Consulting

Slide 65

Method `parseVariableExpr()`

```
// parses the following grammar rule:
// variable = ( varId | paramId ) ( "[" expression "]" ) * .
public void parseVariableExpr()
    throws IOException, ParserException
{
    Token idToken = scanner.getToken();
    match(Symbol.identifier);
    IdType idType = idTable.get(idToken);

    if (idType == null)
        throw error("..."); // has not been declared
    else if (idType != IdType.variableId)
        throw error(" ... "); // not a variable
```

(continued on next slide)

©SoftMoore Consulting

Slide 66

Method `parseVariableExpr()` (continued)

```
while (scanner.getSymbol() == Symbol.leftBracket)
{
    matchCurrentSymbol();
    parseExpression();
    match(Symbol.rightBracket);
}
```

©SoftMoore Consulting

Slide 67

Method `parseVariable()`

- Method `parseVariable()` simply calls the helper method to parse its grammar rule.

```
public void parseVariable() throws IOException
{
    try
    {
        parseVariableExpr();
    }
    catch (ParserException e)
    {
        ErrorHandler.getInstance().reportError(e);
        exit();
    }
}
```

- Method `parseNamedValue()` is implemented similarly.

©SoftMoore Consulting

Slide 68