

APPWEB-57 Smoke Checklist

Ticket: T-50 / TS06 - Asset Settings API

Prerequisites

- MySQL is running locally.
- The configured user/password is `root` / `root`.
- The API starts successfully and Swagger is available at `/swagger/index.html`.
- At least one organization and one asset exist in the same organization.

Manual Checks

1. Create an organization through `POST /api/v1/organization-sign-ups`.
2. Create a location under that organization through `POST /api/v1/organizations/{organizationId}/locations`.
3. Create an asset under the same organization and location through `POST /api/v1/organizations/{organizationId}/assets`.
4. Save organization-level default settings (no asset) through `PUT /api/v1/organizations/{organizationId}/asset-settings/default`.
5. Confirm the response is `200` and includes `id`, `organizationId`, `assetId` as `null`, and all threshold fields.
6. Save asset-specific settings through `PUT /api/v1/organizations/{organizationId}/assets/{assetId}/settings`.
7. Confirm the response is `200` and includes the `assetId` matching the created asset.
8. Confirm `GET /api/v1/organizations/{organizationId}/asset-settings` returns all settings for the organization.
9. Confirm `GET /api/v1/organizations/{organizationId}/assets/{assetId}/settings` returns the effective settings for that asset (asset-specific if present, otherwise the organization default).
10. Confirm saving settings with an `assetId` from another organization returns `404`.
11. Confirm requesting settings through another organization scope returns `404`.
12. Update the asset-specific settings again through `PUT /api/v1/organizations/{organizationId}/assets/{assetId}/settings` and confirm it overwrites the previous values (upsert behavior).

Endpoint Coverage

- GET /api/v1/organizations/{organizationId}/asset-settings
- GET /api/v1/organizations/{organizationId}/assets/{assetId}/settings
- PUT /api/v1/organizations/{organizationId}/assets/{assetId}/settings
- PUT /api/v1/organizations/{organizationId}/asset-settings/default

Contract Notes

- Asset settings belong to one organization.
- Asset-specific settings are linked to one asset through `assetId`.
- Organization-level default settings exist without an `assetId` (field is `null`).
- Settings do not depend on gateways.
- Any `assetId` in the request must belong to the same organization; otherwise the API returns `404`.
- The resource fields are: `id`, `organizationId`, `assetId`, `temperatureMin`, `temperatureMax`, `humidityMin`, `humidityMax`, `readingFrequencySeconds`, and `alertThresholdMinutes`.
- `PUT` endpoints follow upsert semantics: create if not present, update if already exists.
- `PUT` returns `200` with the saved resource body.
- The effective settings endpoint returns asset-specific settings when present; otherwise falls back to the organization default.
- Authentication, JWT, and role enforcement are out of scope for this ticket