

On this Lesson

- Organization of virtual memory systems
- Paging – virtual to physical address translation
- Organization of page tables
- Page faults
- Translation Lookaside Buffer
- Multi-level page tables
- Segmentation
- Caches on virtual memory systems

Virtual Memory

- Allows the operating system to administer the transfer of data between main memory and secondary memory.
- Provides a mechanism for the operating system to protect data between users.
- Allows the execution of programs that are larger than the installed physical memory
- Facilitates multiprocessing

Memory Terms

Virtual Memory (Primary Memory)



- Is the architectural memory, the memory space that can be accessed by fetch/load/store operations of a machine code program.
- It has 2^n memory locations, where n is the number of bits needed to specify a memory address.

Physical Memory

- Is the RAM memory physically installed in a computer.
- It has 2^m memory locations, where m could be less than n .

Secondary Memory

- Is the memory where programs are permanently stored.
- It has 2^z memory locations, where z is significantly larger than n or m .
- It is non-volatile



Paging

- Is the mechanism that facilitates the mapping of virtual addresses to physical addresses and the transfer of pages between physical memory and secondary memory.
- Mapping of virtual addresses to physical addresses is accomplished by means of a page table that is **resident in primary memory**.
- Each fetch/load/store access involves two memory accesses, one to the page table and one to access the physical address of the fetch/load/store operation.
- Transfer of pages between secondary memory and physical memory is made on demand (when the pages are needed by a program).

7