Introduction to Turbulence Modeling

or Why Turbulence Modeling is Black Magic

Truman E. Ellis

Institute for Computational and Engineering Sciences
The University of Texas at Austin

May 8, 2013

Reynolds Averaged Navier Stokes

Let $\phi = \bar{\phi} + \phi'$, where

$$\bar{\phi} = \lim_{T \to \infty} \int_{t_0}^{t_0 + T} \phi(t) \, dt$$

Interested in solving for $\bar{u}_i$. Nondimensionalizing such that $\rho = 1$,

Continuity Equation	Momentum Equation
$$\frac{\partial u_i}{\partial x_i} = 0$$	$$\frac{\partial u_i}{\partial t} + u_j \frac{\partial u_i}{\partial x_j} = -\frac{\partial p}{\partial x_i} + \frac{1}{Re} \frac{\partial^2 u_i}{\partial x_j \partial x_i}$$
$$\Downarrow$$	$$\Downarrow$$
$$\frac{\partial \bar{u}_i}{\partial x_i} = 0$$	$$\frac{\partial \bar{u}}{\partial t} + \bar{u}_j \frac{\partial \bar{u}_i}{\partial x_j} = -\frac{\partial \bar{p}}{\partial x_i} + \frac{\partial}{\partial x_j} \left[-\overline{u_i' u_j'} + \frac{1}{Re} \frac{\partial \bar{u}_i}{\partial x_j} \right]$$

But the Reynolds stress, $\overline{u_i' u_j'}$ is an unclosed quantity.

Modeling the Reynolds Stress

$$\frac{\partial \bar{u}}{\partial t} + \bar{u}_j \frac{\partial \bar{u}_i}{\partial x_j} = -\frac{\partial \bar{p}}{\partial x_i} + \frac{\partial}{\partial x_j} \left[-\overline{u_i' u_j'} + \frac{1}{Re} \left(\frac{\partial \bar{u}_i}{\partial x_j} + \frac{\partial \bar{u}_j}{\partial x_i} \right) \right]$$

Eddy Viscosity Hypothesis

$$\overline{u_i' u_j'} = -\nu_T \left(\frac{\partial \bar{u}_i}{\partial x_j} + \frac{\partial \bar{u}_j}{\partial x_i} \right) + \frac{2k}{3} \delta_{ij}$$

where $k = \frac{1}{2} \overline{u_i' u_i'}$.

This assumption is fundamentally flawed, but useful.

We still need a model for ν_T and k.

Spalart-Allmaras Model

- Model the eddy viscosity
- Assume k is negligible
- Surprisingly decent for the types of flows it was designed for
  - External aerodynamics with minimal flow separation
- Highly nonlinear equation

$$\frac{\partial \tilde{\nu}}{\partial t} + \bar{u}_j \frac{\partial \tilde{\nu}}{\partial x_j} = C_{b1}[1 - f_{t2}]\tilde{S}\tilde{\nu} + \frac{1}{\sigma}\left\{\nabla \cdot [(\nu + \tilde{\nu})\nabla\tilde{\nu}] + C_{b2}\left|\nabla\tilde{\nu}\right|^2\right\}$$
$$- \left[C_{w1}f_w - \frac{C_{b1}}{\kappa^2}f_{t2}\right]\left(\frac{\tilde{\nu}}{d}\right)^2 + f_{t1}\Delta U^2$$

$$\nu_T = \tilde{\nu}f_{v1}, \quad f_{v1} = \frac{\chi^3}{\chi^3 + v_{v1}^3}, \quad \chi = \frac{\tilde{\nu}}{\nu} \quad \cdots$$

$k - \epsilon$ Exact Equations

Turbulence Kinetic Energy Equation

$$\frac{\partial k}{\partial t} + \bar{u}_i \frac{\partial k}{\partial x_i} = -\overline{u_i' u_j'} \frac{\partial \bar{u}_i}{\partial x_j} - \frac{\partial}{\partial x_i} \left(\frac{1}{2} \overline{u_j' u_j' u_i'} + \overline{p' u_i'} \right) + \nu \frac{\partial^2 k}{\partial x_i \partial x_i} - \epsilon$$

Dissipation Equation

$$\frac{\partial \epsilon}{\partial t} + \bar{u}_i \frac{\partial \epsilon}{\partial x_i} = \nu \frac{\partial^2 \epsilon}{\partial x_i \partial x_i} + P_\epsilon + D_\epsilon - \Phi_\epsilon$$

$$P_\epsilon = -2\nu \left[\overline{\frac{\partial u_i'}{\partial x_j} \frac{\partial u_k'}{\partial x_j}} \frac{\partial \bar{u}_i}{\partial x_k} + \overline{\frac{\partial u_j'}{\partial x_i} \frac{\partial u_j'}{\partial x_k}} \frac{\partial \bar{u}_i}{\partial x_k} + \overline{u_k' \frac{\partial u_i'}{\partial x_j}} \frac{\partial^2 \bar{u}_i}{\partial x_k \partial x_j} + \overline{\frac{\partial u_i'}{\partial x_k} \frac{\partial u_i'}{\partial x_m} \frac{\partial u_k'}{\partial x_m}} \right]$$

$$D_\epsilon = -\frac{\partial}{\partial x_k} \left(\overline{u_k' \epsilon'} + 2\nu \overline{\frac{\partial p'}{\partial x_m} \frac{\partial u_k'}{\partial x_m}} \right)$$

$$\Phi_\epsilon = 2\nu^2 \overline{\frac{\partial^2 u_i'}{\partial x_k \partial x_m} \frac{\partial^2 u_i'}{\partial x_k \partial x_m}}$$

$k - \epsilon$ Approximations

Turbulence Kinetic Energy Equation

$$\frac{1}{2}\overline{u'_j u'_j u'_i} + \overline{p' u'_i} \approx -\frac{\nu_T}{\sigma_k}\frac{\partial k}{\partial x_i}$$

Dissipation Equation

From dimensional analysis

$$\nu_T \approx C_\mu \frac{k^2}{\epsilon}$$

$$P_\epsilon \approx -C_{\epsilon 1}\frac{\epsilon}{k}\overline{u'_i u'_j}\frac{\partial \bar{u}_i}{\partial x_j}$$

$$\Phi_\epsilon \approx C_{\epsilon 2}\frac{\epsilon^2}{k}$$

From gradient transport model

$$D_\epsilon \approx \frac{\partial}{\partial x_i}\left(\frac{\nu_T}{\sigma_\epsilon}\frac{\partial \epsilon}{\partial x_i}\right)$$

Channel Flow Predictions

Figure: Reynolds Stress Components

$$\overline{u_i' u_j'} - \frac{2}{3} k \delta_{ij}$$
$$\approx -\nu_T \left(\frac{\partial \bar{u}_i}{\partial x_j} + \frac{\partial \bar{u}_j}{\partial x_i} \right)$$

Channel Flow Predictions

$$\overline{u_i' u_j'} \frac{\partial \bar{u}_i}{\partial x_j} \approx$$

$$C_\mu \frac{k^2}{\epsilon} \left(\frac{\partial \bar{u}_i}{\partial x_j} + \frac{\partial \bar{u}_j}{\partial x_i} \right) \frac{\partial \bar{u}_i}{\partial x_j}$$

Figure: Production of Turbulent Kinetic Energy

Channel Flow Predictions

$$\frac{\partial}{\partial x_i}\left(\frac{1}{2}\overline{u'_k u'_k u'_i} + \overline{p'u'_i}\right)$$
$$\approx -\frac{\partial}{\partial x_i}\left(\frac{\nu_T}{\sigma_k}\frac{\partial k}{\partial x_i}\right)$$

Figure: Transport of Turbulent Kinetic Energy

Channel Flow Predictions

Figure: Time averaged velocity profile $Re = 2000$

Channel Flow Predictions

Figure: Time averaged velocity profile $Re = 10000$

Channel Flow Predictions

Figure: Turbulence kinetic energy profile *Re* = 2000

# Channel Flow Predictions

Figure: Dissipation profile $Re = 2000$

Notes on $k - \epsilon$

Fixes near the wall

- Wall functions
- Two-layer models
- SST $k - \omega$
- $\overline{v^2} - f$ four equation model (f is an elliptic relaxation function)

Boundary conditions

- BC on ϵ is not obvious
- Enforce both $k = 0$ and $\frac{\partial k}{\partial n} = 0$ at walls.

Popularity

- One of the earliest models
- Physically motivated derivation
- Insensitive to freestream conditions on k and ϵ

Typical Solution Procedure

From a presentation by a Fluent engineer

- Start calculations by performing 100 iterations or so with standard $k - \epsilon$ model and first order upwind differencing. For very simple flows (no swirl or separation) converge with second order upwind and $k - \epsilon$ model.

- If the flow involves jets, separation, or moderate swirl, converge solution with the realizable $k - \epsilon$ model and second order differencing.

- If the flow is dominated by swirl converge solution deeply using RSM and a second order differencing scheme. If the solution will not converge, use first order differencing instead.

Wilcox (1993) $k - \omega$ Model

Turbulence Kinetic Energy Equation

$$\frac{\partial k}{\partial t} + \bar{u}_j \frac{\partial k}{\partial x_j} = 2\nu_T \left|S\right|^2 - C_\mu k\omega + \frac{\partial}{\partial x_j}\left(\left(\nu + \frac{\nu_T}{\sigma_k}\right)\frac{\partial k}{\partial x_j}\right)$$

Specific Dissipation Equation

$$\frac{\partial \omega}{\partial t} + \bar{u}_j \frac{\partial \omega}{\partial x_j} = 2C_{\omega 1} \left|S\right|^2 - C_{\omega 2}\omega^2 + \frac{\partial}{\partial x_j}\left(\left(\nu + \frac{\nu_T}{\sigma_\omega}\right)\frac{\partial \omega}{\partial x_j}\right)$$

$$\omega \equiv \frac{\epsilon}{C_\mu k}$$

$$\nu_T = \frac{k}{\omega}$$

Notes on $k - \omega$

Wall Treatment

- Formally, ω is singular at a perfectly smooth wall
- Numerically, this is fixed by assuming a finite roughness
  - $\omega_{wall} = \frac{40000\nu_{wall}}{k_s^2}$, need $\frac{u_\tau k_s}{\nu} < 5$
- Produces decent results at the wall
- Can perform the same trick with two BCs on k

Other Notes

- Early models were very sensitive to freestream conditions on ω
- Menter proposed SST model to overcome this shortcoming
- Possible to write a $k - \epsilon$ model with $k - \omega$ "physics"

Other Ideas – Unsteady RANS

Figure 7.72 *Vortex shedding from a triangular cylinder. (a) composite showing time-average contours of U in the upper half, versus a steady solution in the lower half. The dashed lines indicate negative velocity. (b) time-averaged velocity profiles in the wake. (c) velocity along centerline: time-average, ———— ; steady computation, – – – – (Durbin, 1995).*

Other Ideas

- Large Eddy Simulation
- Reynolds Stress Models
  - Elliptic relaxation model solves 18 coupled, highly nonlinear PDEs
- Variational Multiscale
- Direct Numerical Simulation

DNS Velocity Field

Filtered Velocity Field
$\Delta = L/32$

Filtered Velocity Field
$\Delta = L/16$