An Application Development Project Report

Smart Railway Track Abnormality Detection & Local Alert System

Design & Developed By

2411EC010008	BONASPUR RAJESH KUMAR
2411EC010021	GOTTAM BABY APOORVA
2411EC010022	GADDAMEEDI ARAVIND
2411EC010026	KILLI DILLESHWAR RAO

GUIDED BY

Mr. A. SHANKAR

(Assistant Professor)

Department of Electronics and Communication Engineering (ECE)

Malla Reddy University, Hyderabad

Nov-2026

MALLA REDDY UNIVERSITY

(Telangana State Private Universities Act No.13 of 2020 and G.O.Ms.No.14, Higher Education (UE) Department)

Department of Electronics and Communication Engineering (ECE)

CERTIFICATE

This is to certify that this is the Bonafide record of the application development Project entitled **"SMART RAILWAY TRACK ABNORMALITY DETECTION AND LOCAL ALERT SYSTEM''** submitted by **B. RAJESH KUMAR(2411EC010008), G. BABY APOORVA(2411EC010021),G. ARAVIND(2411EC010022), K. DILLESHWAR RAO (2411EC010026)** of B.Tech III year I semester, Department of Electronics and Communication Engineering(ECE),during the year 2026-27. The results embodied in this report have not been submitted to any other university or institute for the award of any degree or diploma.

Internal Guide
Mr. A. SHANKAR
Assistant Professor

Dean (ECE)
Dr. G. Anand Kumar
Professor & Dean

DECLARATION

We hereby declare that the project report **"SMART RAILWAY TRACK ABNORMALITY DETECTION AND LOCAL ALERT SYSTEM",** has been carried out by us and this work has been submitted to the **Department of Electronics and Communication Engineering (ECE),Malla Reddy University, Hyderabad**. We further declare that this project work has not been submitted in full or part for the award of any other degree in any other educational institutions.

Place: MALLA REDDY UNIVERSITY

Date: 31 OCTOBER 2026

B. RAJESH KUMAR	2411EC010008
G. BABY APOORVA	2411EC010021
G. ARAVIND	2411EC010022
K. DILLESHWAR RAO	2411EC010026

ACKNOWLEDGEMENT

We extend our sincere gratitude to all those who have contributed to the completion of this project report. Firstly, we would like to extend our gratitude to **Dr. V.S.K. Reddy, Vice-Chancellor,** for his visionary leadership and unwavering commitment to academic excellence.

We are also grateful to **Dr. G. Anand Kumar**, **Dean and Head of the Department** ECE, Cyber Security & IOT, for providing us with the necessary resources and facilities to carry out this project.

We would also like to express our deepest appreciation to our project guide **Mr. A. Shankar, Assistant Professor, Department of ECE** whose invaluable guidance, insightful feedback, and unwavering support have been instrumental throughout the course of this project for successful outcomes.

We extend our gratitude to our **PRC – convenor**, **Dr. G. Latha,** for giving valuable inputs andtimely guidelines to improve the quality of our project through a critical review process. We thank our project coordinator, **Mrs. K. Narmada ,** for her timely support.

We are deeply indebted to all of them for their support, encouragement, and guidance, without which this project would not have been possible.

B. RAJESH KUMAR 2411EC010008
G.BABY APOORVA 2411EC010021
G. ARAVIND 2411EC010022
K.DILLESHWAR RAO 2411EC010026

ABSTRACT

Railway transportation plays an important role in connecting different regions and providing an efficient mode of public transport. The safety and reliability of railway operations largely depend on the proper condition of railway tracks. Any abnormal variation in track conditions may affect train movement and increase the risk of accidents. Regular monitoring is therefore essential for identifying abnormal conditions at an early stage. This project presents a Smart Railway Track Abnormality Detection and Alert System that uses sensors and an Arduino-based control unit to demonstrate automated track condition monitoring.

The proposed system uses an Arduino Uno, two HC-SR04 ultrasonic sensors, an SW-18010P vibration sensor, a NEO-6M GPS module, a 16×2 LCD display with an I2C interface, and red and green LED indicators. The ultrasonic sensors measure distance variations on either side of the railway track model, while the vibration sensor detects vibrations. The Arduino processes these sensor inputs and identifies an abnormal condition when either the measured distance deviates from the configured threshold or vibration is detected.

Based on the detected condition, the system provides visual indications using two LEDs. The green LED indicates normal track conditions, while the red LED indicates an abnormal condition. The LCD and Serial Monitor display the system status and sensor information. Additionally, the NEO-6M GPS module obtains geographical coordinates when a valid satellite fix is available, and these coordinates are displayed on both the LCD and Serial Monitor. This integration provides distance monitoring, vibration detection, visual alerts and location information through a single system.

The prototype was tested under different conditions, including normal track operation, abnormal distance detection, vibration detection, GPS coordinate display, LCD status display and combined sensor operation. The tests demonstrated the successful integration and functioning of the major components. The project provides a simple and economical demonstration of sensor-based railway track condition monitoring. In the future, the system can be enhanced by incorporating advanced sensors, wireless communication, remote monitoring and data logging facilities. The present prototype is intended for educational demonstration on a railway track model and is not a certified railway inspection or safety system.

INDEX

CONTENTS	Page No
Chapter-1 Introduction	5-7
1.1 Problem Definition and Description	5-6
1.2 Aim and Objectives of the project	6-7
1.3 Scope of the project	7
Chapter-2 Literature and Existing system	**8-11**
2.1 Existing System Analysis	8-9
2.2 Proposed System Analysis	9-10
2.3 Software and Hardware Requirements	10-11
2.4 Feasibility study	11
Chapter-3 Architectural Design	**12-20**
3.1 Modules Design	12-13
3.2 Methodology and Algorithm Design	13-15
3.3 System Architecture	15-20
Chapter-4 Implementation and Testing	**21-26**
4.1 Coding block	21-25
4.2 Test case study	25-26
Chapter-5 Results and Discussion	**27-31**
5.1 Results	27-28
5.2 Testing and Observations	28-29
5.3 Performance analysis	29-30
5.4 Discussion	30
5.5 Summary of results	30-31
Chapter-6 Conclusion and Future Scope	**32-33**
6.1 Conclusion	32
6.2 Future scope	32-33
References	**34**

List of Figures **Page No**

3.3.1 Architectural Diagram	16
3.3.2 Class Diagram	17
3.3.3 Use case Diagram	19
3.3.4 Deployment Diagram	19
4.1.1 Code Execution Flow Chart	25
5.1 Result Prototype	28
5.3 Performance analysis	30

CHAPTER - 1

INTRODUCTION

Railway transportation is one of the most important modes of public transportation, providing an efficient and economical means of transporting passengers and goods. The safety and reliability of railway transportation depend greatly on the condition of railway tracks. Regular monitoring and timely identification of track abnormalities are essential to reduce the risk of accidents and ensure smooth railway operations.

Railway tracks are exposed to heavy loads, continuous vibrations, temperature variations, and environmental conditions. These factors may cause track deformation, uneven surfaces, cracks, and other structural irregularities over time. If such abnormalities are not identified at an early stage, they may affect railway safety and reliability.

Traditional railway inspection methods often involve manual inspection and specialized equipment, which may require considerable time, effort, and resources. Therefore, the development of low-cost electronic systems for monitoring railway track conditions can provide an additional approach to identifying potential abnormalities.

The Smart Railway Track Abnormality Detection & Alert System is designed to monitor selected track conditions using sensors and a microcontroller. The system uses an Arduino Uno as the main controller, ultrasonic sensors to measure distance variations, and a vibration sensor to detect vibration events. A NEO-6M GPS module is intended to provide location information when a valid GPS signal is available. Red and green LEDs indicate abnormal and normal conditions, respectively, while an LCD can display relevant system information.

The system processes sensor readings and compares them with predefined threshold values. When the readings satisfy the programmed abnormality conditions, the controller activates the corresponding alert indicators. This project demonstrates the application of embedded systems and sensor technology for preliminary railway track condition monitoring.

1.1 Problem Definition & Description

Railway track abnormalities are a major concern because track conditions directly influence the safety and reliability of railway transportation. Continuous usage, mechanical stress, and environmental exposure may lead to changes in track geometry and other irregularities. Identifying these conditions at an early stage can help maintenance personnel investigate potential problems and take appropriate action.

One of the main challenges in railway maintenance is monitoring long stretches of railway tracks efficiently. Manual inspection requires time and human effort, and abnormalities may not always be immediately noticeable. Therefore, there is a need for a simple and cost-effective system that can monitor selected track-related parameters and generate alerts when abnormal conditions are detected.

The proposed system addresses this problem by combining ultrasonic sensors, a vibration sensor, and an Arduino Uno. Ultrasonic sensors measure the distance between the sensor and a nearby surface, while the vibration sensor detects vibration events. The Arduino Uno processes the sensor outputs according to predefined conditions and determines the status of the monitored system.

When the measured values indicate a configured abnormal condition, red LEDs are activated. Green LEDs indicate that the monitored readings remain within the specified limits. An LCD can display relevant sensor information and system status. The GPS module can provide geographic coordinates when a valid satellite fix is obtained.

The main objective is to develop a prototype that demonstrates basic railway track monitoring using readily available electronic components. The system aims to simplify the detection of selected abnormalities and provide immediate visual indications during testing.

However, the effectiveness of the system depends on sensor placement, calibration, environmental conditions, and threshold selection. The prototype detects selected distance variations and vibration events; it does not independently confirm microscopic rail cracks or replace professional railway inspection systems.

1.2 Aim and Objectives of the Project

Aim

The main aim of this project is to design and develop a low-cost embedded system for monitoring selected railway track conditions using ultrasonic and vibration sensors, processing sensor data through an Arduino Uno, and generating visual alerts when predefined abnormality conditions are detected. GPS-based location identification is also considered to help identify the approximate location of a detected event.

Objectives

1. To monitor distance variations using ultrasonic sensors and identify deviations from predefined threshold values.

2. To detect vibration events using a vibration sensor and process the sensor output through the microcontroller.

3. To use the Arduino Uno to process sensor readings and determine whether the monitored conditions are normal or abnormal.

4. To generate visual alerts using red and green LEDs to indicate abnormal and normal conditions, respectively.

5. To display sensor readings and system status messages using a 16×2 LCD, where successfully integrated.

6. To incorporate the NEO-6M GPS module for obtaining geographic coordinates when a valid GPS fix is available.

7. To develop a low-cost prototype using readily available electronic components.

8. To test the system under controlled conditions and verify sensor responses and alert generation.

9. To provide a foundation for future improvements, such as IoT dashboard integration, wireless alerts, and data logging.

1.3 SCOPE OF THE PROJECT

The scope of this project is limited to the development and testing of a prototype for monitoring selected railway track conditions using sensors and an embedded controller. The system combines distance measurement, vibration detection, and visual alerts to demonstrate a basic abnormality detection mechanism.

Distance Monitoring: Ultrasonic sensors measure the distance to nearby surfaces. The measured values are compared with predefined thresholds to identify selected distance variations. The interpretation of these variations depends on the sensor mounting arrangement and the monitored surface.

Vibration Detection: A vibration sensor detects vibration events and provides signals to the Arduino Uno. The controller evaluates these signals according to the programmed conditions to determine whether an alert is required.

Alert Indication: Red LEDs indicate detected abnormal conditions, while green LEDs indicate readings within the configured limits. The alert response depends on the logic implemented in the program.

Display of Information: A 16×2 LCD can display sensor readings, system status, and alert messages when successfully integrated into the prototype.

GPS-Based Location Identification: The NEO-6M GPS module is intended to obtain latitude and longitude coordinates when adequate satellite signals are available. The availability and accuracy of location information depend on GPS reception and successful integration.

System Testing: The prototype can be tested using controlled changes in sensor distance and vibration conditions. These tests help verify the response of the sensors and the operation of the programmed alert logic.

Cost-Effective Implementation: The use of commonly available components makes the system suitable for academic projects and embedded-systems experimentation.

The project has certain limitations. Ultrasonic sensors cannot independently confirm microscopic cracks inside railway rails, and a basic vibration sensor cannot determine the exact cause of a vibration event. The system does not include certified railway safety mechanisms or automatic train control. Wireless communication, remote monitoring, advanced crack-detection techniques, and field testing on operational railway tracks can be considered for future development.

Overall, this project demonstrates how embedded systems and sensor technology can be used for preliminary monitoring of selected railway track conditions. It provides a foundation for further development of more advanced railway inspection and monitoring systems.

CHAPTER – 2

LITERATURE AND EXISTING SYSTEM

2.1 Existing System Analysis:

Railway track inspection is essential for safe and reliable railway transportation. Conventional methods include manual visual inspection, scheduled maintenance, and specialized inspection vehicles. These methods help identify track defects and irregularities but require time, trained personnel, and expensive equipment. Since inspections are performed periodically, abnormalities developing between inspections may not be identified immediately.

2.1.1 Background and Literature Survey

Railway track monitoring methods can be classified into the following categories:

1. Manual Track Inspection: Railway personnel visually inspect rails, sleepers, and fasteners. This method requires considerable time and human effort.

2. Specialized Inspection Equipment: Instrumented vehicles measure track geometry and identify defects but involve high equipment and maintenance costs.

3. Sensor-Based Monitoring: Sensors measure parameters such as vibration, displacement, temperature, and track geometry. Detection accuracy depends on sensor placement and calibration.

4. Embedded and Wireless Systems: Microcontrollers process sensor data, while GPS provides geographical coordinates and GSM enables SMS notifications.

The proposed Smart Railway Track Abnormality Detection & Local Alert System combines ultrasonic distance measurement, a microcontroller, LCD, buzzer, LEDs, GPS, and GSM. It compares measured distance with a predefined reference value and generates alerts when the deviation exceeds a specified threshold. The prototype demonstrates distance-variation monitoring but cannot independently detect every type of railway defect.

2.1.2 Limitations of the Existing System

The major limitations of conventional railway inspection methods are:

1. Manual Effort: Inspection requires trained personnel and considerable time.
2. Limited Continuous Monitoring: Scheduled inspections may miss abnormalities developing between visits.
3. Delayed Reporting: Recording and communicating fault information can delay maintenance.
4. High Equipment Cost: Specialized inspection vehicles and instruments require significant investment.
5. Limited Automatic Alerts: Traditional methods may not provide immediate audible or visual warnings.
6. Lack of Location Information: Basic monitoring systems may not provide geographical coordinates with alerts.
7. Measurement Errors: Sensor readings can be affected by alignment, vibration, and environmental conditions.
8. Limited Defect Detection: A single distance sensor cannot reliably detect internal rail cracks or every type of track damage.

These limitations highlight the need for automated monitoring and alert mechanisms. Professional railway inspection remains essential for confirming actual defects.

2.2 Proposed System Analysis

The proposed system monitors selected railway track-profile variations using an ultrasonic sensor and a microcontroller. The sensor measures distance from a reference surface, and the controller compares the reading with a predefined reference value. If the deviation exceeds the configured threshold, the system identifies a possible abnormality.

A 16×2 LCD displays measurements and system status. A buzzer and LEDs provide local alerts. The GPS module supplies geographical coordinates when a valid satellite fix is available, while the GSM module sends SMS notifications to a predefined mobile number.

The system provides a low-cost embedded monitoring prototype. Its performance depends on sensor calibration, proper mounting, power supply, GPS reception, and cellular network availability.

2.2.1 Proposed System Description

The system consists of the following major modules:

1. Ultrasonic Sensor: Measures distance to a reference surface using reflected ultrasonic waves. Deviations beyond the threshold indicate a possible abnormality.

2. Microcontroller: Processes sensor readings, compares them with the reference value, and controls the display, alerts, GPS, and GSM modules.

3. LCD Display: Displays the measured distance and system status, including normal and warning messages.

4. Buzzer and LEDs: Provide audible and visual indications. A green LED can indicate normal operation, while a red LED indicates a suspected abnormality.

5. GPS Module: Provides latitude and longitude when satellite signals are sufficient for a valid location fix.

6. GSM Module: Sends SMS alerts containing abnormality information and available GPS coordinates through a compatible cellular network.

7. Power Supply: Provides the required voltage and current to all components. Stable power is particularly important for GSM transmission.

Working Procedure

1. Initialize the microcontroller and connected modules.
2. Measure the distance using the ultrasonic sensor.
3. Compare the measured distance with the reference value.
4. Display the normal status if the deviation is within the permitted threshold.
5. If the threshold is exceeded, display a warning and activate the buzzer and LEDs.
6. Obtain GPS coordinates if a valid fix is available.
7. Send an SMS alert through the GSM module.
8. Repeat the monitoring process continuously.

2.2.2 Advantages of the Proposed System

1. Automated Monitoring: Automatically measures distance and compares readings with a reference value.
2. Immediate Alerts: Provides audible and visual warnings when an abnormality is suspected.
3. Remote Notifications: Sends SMS alerts to a predefined mobile number.
4. Location-Based Alerts: Includes GPS coordinates when available.
5. Real-Time Display: Shows distance measurements and system status on the LCD.
6. Cost-Effective Design: Uses commonly available electronic components.
7. Compact Structure: Integrates sensing, processing, display, and communication.
8. Expandability: Supports future integration of additional sensors and improved detection algorithms.

The proposed system demonstrates automated sensing and location-based alerts. Further testing and specialized sensors are required before considering practical railway safety applications.

2.3 Software and Hardware Requirements

The system requires suitable software and hardware for distance measurement, abnormality detection, status display, location tracking, and alert generation.

2.3.1 Software Requirements

1. Arduino IDE: Used to write, compile, upload, and debug the microcontroller program. The Serial Monitor helps observe readings and module responses.

2. Embedded C/C++: Controls sensor measurements, threshold comparison, LCD updates, and alert generation.

3. LCD Library: Displays measured distance and system status. The library depends on whether the LCD uses a parallel or I²C interface.

4. GPS Data Processing: Reads serial GPS data and extracts latitude and longitude.

5. GSM Communication: Uses serial communication and AT commands to configure the GSM module and send SMS notifications.

6. Testing Tools: The Serial Monitor helps verify sensor readings, GPS reception, GSM responses, and alert conditions.

2.3.2 Hardware Requirements

1. Microcontroller Board: Processes sensor readings and controls the connected modules.
2. Ultrasonic Sensor: Measures distance from the selected reference surface.
3. GPS Module: Obtains geographical coordinates when satellite reception permits.
4. GSM Module: Sends SMS notifications through a compatible cellular network.
5. 16×2 LCD: Displays measured distance and system status.
6. Buzzer: Produces an audible warning when a suspected abnormality is detected.
7. LEDs: Provide visual indications of normal and abnormal conditions.
8. Power Supply: Provides suitable voltage and current to all modules.
9. Connecting Wires and Breadboard/PCB: Establish and support electrical connections.
10. Mounting Structure: Holds the ultrasonic sensor securely and maintains proper alignment.

Correct wiring, voltage compatibility, stable power, and sensor calibration are essential for reliable operation.

2.4 Feasibility Study

The feasibility study evaluates whether the proposed system can be developed using available technology, resources, and budget.

2.4.1 Technical Feasibility

The project is technically feasible as an educational prototype because its components are commonly available. The ultrasonic sensor measures distance, the microcontroller processes readings, and the LCD, buzzer, and LEDs provide status information and alerts. GPS and GSM enable location-based SMS notifications when satellite reception and cellular service are available.

The Arduino IDE supports software development and debugging. Successful implementation requires correct wiring, compatible voltage levels, sufficient power, suitable communication settings, and sensor calibration. The prototype detects selected distance variations rather than all railway defects.

2.4.2 Robustness and Reliability

System reliability depends on sensor accuracy, mounting stability, electrical connections, software logic, and communication availability.

The following measures can improve reliability:

1. Securely mount and align the ultrasonic sensor.
2. Use repeated measurements or filtering to reduce inaccurate readings.
3. Calibrate the reference distance and detection threshold.
4. Provide stable power and correct electrical connections.
5. Verify GPS coordinates and handle GSM communication failures.
6. Test normal readings, abnormal readings, missing sensor data, and communication errors.

Repeated testing helps identify false alerts, missed deviations, and inconsistent measurements. Reliability must be demonstrated experimentally; the prototype is not a certified railway safety device.

2.4.3 Economic Feasibility

The project is economically feasible for academic development because it uses commonly available electronic modules and the Arduino IDE, which reduces software costs.

The main expenses include the microcontroller, ultrasonic sensor, GPS and GSM modules, LCD, buzzer, LEDs, power supply, connecting wires, and mounting materials. Additional costs may include a SIM card, cellular service, PCB fabrication, and enclosure construction.

The total cost depends on the selected components and current supplier prices. Therefore, the budget should be calculated using actual component quotations.

Overall, the proposed system is suitable for educational prototyping. Practical railway deployment would require additional validation, specialized sensing, maintenance planning, and railway safety assessment.

CHAPTER – 3

ARCHITECTURAL DESIGN

3.1 Modules Design

The Smart Railway Track Abnormality Detection & Local Alert System consists of modules for distance measurement, abnormality detection, display, local alerts, GPS positioning, GSM communication, and system testing. The microcontroller coordinates these modules to identify possible track-profile variations and generate alerts.

3.1.1 Ultrasonic Sensor Module

The ultrasonic sensor measures the distance between itself and a reference surface using reflected ultrasonic waves. The microcontroller compares the measured distance with a predefined reference value. If the deviation exceeds the configured threshold, a possible abnormality is identified.

3.1.2 Abnormality Detection Module

This module processes sensor readings and calculates the absolute difference between the measured and reference distances. If the deviation exceeds the permitted threshold, the system activates the warning mechanism. Invalid sensor readings are treated as measurement errors rather than confirmed abnormalities.

3.1.3 Alert and Notification Module

This module provides local and remote warnings. The LCD displays the warning message, while the buzzer and LEDs provide audible and visual alerts. GPS supplies available coordinates, and GSM sends an SMS containing the abnormality information and location to a predefined mobile number.

3.1.4 LCD Display Module

The 16×2 LCD displays the measured distance and system status. It shows a normal message when measurements remain within the permitted threshold and a warning when a possible abnormality is detected.

3.1.5 GPS Location Module

The GPS module receives satellite signals to determine latitude and longitude. These coordinates can be included in an alert when a valid location fix is available. If GPS reception is unavailable, the system should indicate that the location could not be obtained.

3.1.6 GSM Alert Module

The GSM module sends SMS notifications through a compatible cellular network. Transmission depends on network coverage, SIM service, module compatibility, and sufficient power supply.

3.1.7 Local Alert and Control Module

This module consists of the buzzer, LEDs, and microcontroller control logic. A green LED can indicate normal operation, while a red LED and buzzer indicate a suspected abnormality. Local alerts can continue even when remote communication is unavailable.

3.1.8 Alert Message Processing Module

The microcontroller prepares an SMS containing the warning status, measured distance, reference distance, and available GPS coordinates. The message is sent through the GSM module. Invalid or unavailable location data should not be presented as accurate coordinates.

3.1.9 System Monitoring and Recovery Module

This module manages repeated measurements and checks sensor validity, GPS availability, and GSM responses. Invalid readings are handled separately from abnormality detection. If communication fails, the system should preserve local warning functionality wherever possible.

3.1.10 Testing and Validation Module

Testing verifies the operation of the ultrasonic sensor, microcontroller, LCD, buzzer, LEDs, GPS, and GSM modules. The main tests include:

1. Sensor testing to verify distance measurement consistency.
2. Threshold testing to confirm abnormality detection.
3. Display testing to verify measurements and status messages.
4. Alert testing to check buzzer and LED operation.
5. GPS testing to verify latitude and longitude.
6. GSM testing to check SMS transmission.
7. Integration testing to verify combined module operation.
8. Error testing to evaluate invalid readings and communication failures.

Test results should be recorded and compared with expected behaviour. These tests demonstrate prototype functionality but do not certify the system for railway safety applications.

3.2 Methodology and Algorithm Design

The methodology describes how the system measures distance, detects possible abnormalities, and generates local and remote alerts. The ultrasonic sensor supplies measurements to the microcontroller, which compares them with a calibrated reference distance and determines whether the deviation exceeds a predefined threshold.

3.2.1 Distance-Based Abnormality Detection Algorithm

The algorithm follows these steps:

1. Start the system and initialize all connected modules.
2. Set the reference distance and permitted deviation threshold.
3. Read the distance measured by the ultrasonic sensor.
4. Validate the sensor reading.
5. Calculate the absolute deviation.
6. Compare the deviation with the threshold.
7. Display normal status if the deviation is within the permitted limit.
8. If the threshold is exceeded, display a warning and activate the buzzer and red LED.

9. Obtain GPS coordinates if a valid fix is available.
10. Send an SMS alert through the GSM module.
11. Repeat the monitoring process.

The deviation is calculated as:

$$\text{Deviation} = |\text{Measured Distance} - \text{Reference Distance}|$$

Let:

D_m = Measured distance

D_r = Reference distance

T = Permitted deviation threshold

The abnormality condition is:

$$|D_m - D_r| > T$$

If this condition is satisfied and the sensor reading is valid, the system identifies a possible abnormality. Otherwise, normal monitoring continues.

3.2.2 Reference Calibration and Threshold Selection

Calibration establishes the reference distance against which subsequent measurements are compared. The sensor is positioned securely relative to a selected reference surface, and repeated measurements are collected under controlled conditions.

A suitable reference value and threshold are selected based on sensor characteristics, measurement variations, mounting stability, and experimental results. Repeated readings and filtering can reduce false alerts caused by occasional fluctuations.

A distance deviation indicates a change in measured geometry but does not independently confirm a railway track defect.

3.2.3 Alert Generation and Notification Algorithm

When a valid measurement exceeds the threshold, the microcontroller updates the LCD, activates the buzzer and warning LED, and requests the available GPS coordinates. It prepares an SMS containing the warning information and valid coordinates, if available.

The GSM module transmits the message to the predefined mobile number. The system should check communication responses where supported. If GPS or GSM is unavailable, the system should indicate the limitation while maintaining local alerts wherever possible.

3.2.4 Sensor Validation and Deviation Calculation

Before processing a measurement, the microcontroller checks whether the sensor reading is valid and within its operating range. Missing echoes or invalid readings are treated as measurement errors.

The absolute deviation is calculated using:

$D_{dev} = |D_m - D_r|$

Where:

D_{dev} = Absolute deviation

D_m = Measured distance

D_r = Reference distance

The microcontroller compares the calculated deviation with the predefined threshold T. If Ddev exceeds T, the alert process begins. Otherwise, normal monitoring continues.

3.2.5 Embedded System Implementation

The system is implemented using a compatible microcontroller and a development environment such as Arduino IDE. The program controls ultrasonic distance measurement, threshold comparison, LCD updates, local alerts, GPS data reception, and GSM messaging.

Implementation involves hardware interfacing, programming, sensor calibration, threshold configuration, individual module testing, and complete system integration. Testing should be performed under controlled conditions before evaluating the prototype's performance.

3.3 System Architecture

The system architecture describes the interaction between the hardware and software components. The ultrasonic sensor measures distance and sends readings to the microcontroller. The controller validates the readings and compares them with the reference distance.

When the deviation exceeds the configured threshold, the microcontroller displays a warning on the 16×2 LCD and activates the buzzer and red LED. The GPS module provides location coordinates when available, and the GSM module sends an SMS alert to a predefined mobile number.

The overall system follows this sequence:

Ultrasonic Sensor → Microcontroller → Distance Validation → Threshold Comparison

Normal Condition → LCD Displays Normal Status → Continue Monitoring

Abnormal Condition → LCD Warning + Buzzer + Red LED → GPS Location Acquisition → GSM SMS Alert → Continue Monitoring

This architecture integrates sensing, processing, display, local warning, and remote communication into a compact embedded prototype. It demonstrates the detection of selected distance variations and should not be considered a replacement for professional railway inspection or certified safety systems.

3.3.1 Architectural Diagram

The architectural diagram represents the connections between the input sensors, processing unit, output devices, and communication modules.

Main components:

- Ultrasonic sensor: Measures the distance from the sensor to the monitored surface.

- Microcontroller: Processes readings and compares them with the reference distance.

- LCD: Displays the measured distance and system status.

- Buzzer and LED: Provide local warning indications.

- GPS module: Provides location coordinates when a valid signal is available.

- GSM module: Sends an SMS alert to a predefined mobile number.




Fig 3.3.1: Architecture diagram

3.3.2 Class Diagram

The class diagram describes the logical modules of the system and their responsibilities. Although the implementation may use embedded C/C++ rather than an object-oriented language, these classes can represent the system's software components.

Main classes:

1. Sensor Manager

   - Reads ultrasonic sensor data.

   - Validates measured distances.

   - Provides distance readings to the controller.

2. Abnormality Detector

   - Stores the reference distance and threshold.

   - Calculates distance deviation.

- Determines whether the deviation exceeds the threshold.

3. Display Manager

- Displays distance readings.

- Shows normal or abnormal system status.

4. Alert Manager

- Controls the buzzer and LED.

- Activates warnings when an abnormality is detected.

5. GPS Manager

- Reads location coordinates from the GPS module.

- Checks whether valid coordinates are available.

6. GSM Manager

- Prepares an SMS alert.

- Sends the alert when the GSM module and network are available.

7. System Controller

- Coordinates sensor readings, abnormality detection, display updates, and alert generation.

Relationships: The System Controller coordinates the other modules. Sensor Manager supplies measurements to Abnormality Detector, while Display Manager and Alert Manager communicate the detection result to the user. GPS Manager supplies location data to GSM Manager for inclusion in the alert message.




Fig 3.3.2: Class diagram

3.3.3 Use Case Diagram

The use case diagram represents how users interact with the proposed system.

Actors:

- Operator/User: Monitors the displayed distance and system status.

- Maintenance Personnel: Receives alerts and checks the reported location.

- Monitoring System: Represents the automated sensing and alerting functions.

Main use cases:

- Start the monitoring system.

- Measure distance.

- Compare distance with the reference value.

- Display system status.

- Generate a local warning.

- Obtain GPS coordinates.

- Send an SMS alert.

- Review the alert and inspect the reported location.




Fig 3.3.3: Use case diagram

3.3.4 Deployment Diagram




Fig 3.3.4: Deployment diagram

The embedded program runs on the microcontroller, while the sensor, display, alert devices, and communication modules are connected to it. The GSM module communicates with the mobile phone through the cellular network. The GPS module receives positioning signals from satellites.

The prototype should be tested in a controlled environment. Actual railway deployment would require appropriate engineering validation, environmental testing, and approval by the relevant railway authorities.

CHAPTER – 4

IMPLEMENTATION & TESTING

4.1 Coding Block

```
#include <Wire.h>
#include <LiquidCrystal_I2C.h>
#include <SoftwareSerial.h>

LiquidCrystal_I2C lcd(0x27, 16, 2);
SoftwareSerial gps(2, 3);

int trig1 = 4, echo1 = 5;
int trig2 = 6, echo2 = 7;
int vibration = 8;

int green1 = 9, green2 = 10;
int red1 = 11, red2 = 12;

int getDistance(int trig, int echo) {
  digitalWrite(trig, LOW);
  delayMicroseconds(2);
  digitalWrite(trig, HIGH);
  delayMicroseconds(10);
  digitalWrite(trig, LOW);

  long time = pulseIn(echo, HIGH, 30000);

  if (time == 0) return 0;

  return time * 0.034 / 2;
```

```
}

void setup() {
  Serial.begin(9600);
  gps.begin(9600);

  pinMode(trig1, OUTPUT);
  pinMode(echo1, INPUT);
  pinMode(trig2, OUTPUT);
  pinMode(echo2, INPUT);
  pinMode(vibration, INPUT);

  pinMode(green1, OUTPUT);
  pinMode(green2, OUTPUT);
  pinMode(red1, OUTPUT);
  pinMode(red2, OUTPUT);

  lcd.init();
  lcd.backlight();
  lcd.setCursor(0, 0);
  lcd.print("Railway System");
  lcd.setCursor(0, 1);
  lcd.print("Starting...");
  delay(2000);
  lcd.clear();

  Serial.println("Railway Monitoring Started");
}

void loop() {
```

```
int d1 = getDistance(trig1, echo1);
int d2 = getDistance(trig2, echo2);
int v = digitalRead(vibration);

bool abnormal =
    (d1 == 0 || d1 <= 3 ||
     d2 == 0 || d2 <= 3 ||
     v == HIGH);

lcd.clear();

if (abnormal) {
  digitalWrite(red1, HIGH);
  digitalWrite(red2, HIGH);
  digitalWrite(green1, LOW);
  digitalWrite(green2, LOW);

  lcd.setCursor(0, 0);
  lcd.print("TRACK ABNORMAL");
  lcd.setCursor(0, 1);
  lcd.print("Check Track!");

  Serial.println("ABNORMALITY DETECTED");
} else {
  digitalWrite(red1, LOW);
  digitalWrite(red2, LOW);
  digitalWrite(green1, HIGH);
  digitalWrite(green2, HIGH);

  lcd.setCursor(0, 0);
```

```
    lcd.print("Track Normal");
    lcd.setCursor(0, 1);
    lcd.print("D1:");
    lcd.print(d1);
    lcd.print(" D2:");
    lcd.print(d2);

    Serial.println("TRACK NORMAL");
  }

  Serial.print("Distance 1: ");
  Serial.println(d1);
  Serial.print("Distance 2: ");
  Serial.println(d2);
  Serial.print("Vibration: ");
  Serial.println(v);

  while (gps.available()) {
    Serial.write(gps.read());
  }

  delay(500);
}
```

4.1.1 Code Execution Flow Chart




Fig 4.1.1: Flowchart

4.2 Test Case Study

The Smart Railway Track Abnormality Detection & Alerts System was designed to monitor track conditions using two ultrasonic sensors and a vibration sensor. The system was tested by checking sensor readings, LED indications, LCD messages and GPS output.

Test Case 1: Normal Condition

When both ultrasonic sensors detect distances above the set threshold and no vibration is detected, the green LEDs turn ON and the LCD displays “Track Normal.”

Test Case 2: Abnormal Distance Detection

When either ultrasonic sensor detects a distance of 3 cm or less, the red LEDs turn ON and the LCD displays an abnormality alert.

Test Case 3: Vibration Detection

When the vibration sensor is triggered, the system indicates an abnormal condition through the red LEDs and LCD.

Test Case 4: GPS Module Testing

The GPS module is checked through the Serial Monitor to verify whether it receives location data. Latitude and longitude are available when the module obtains a valid GPS fix.

Test Case 5: LCD Testing

The LCD is checked to ensure that it displays the track status and sensor readings correctly.

Analysis

The system uses ultrasonic sensors to monitor distance and a vibration sensor to detect disturbances. When a possible abnormality is detected according to the programmed conditions, the red LEDs and LCD provide an alert. Under normal programmed conditions, the green LEDs indicate normal status. The GPS module can provide location information when a valid satellite fix is available. The overall performance depends on sensor calibration, proper connections and testing under different conditions. Further testing is required to evaluate the reliability of the prototype for railway track monitoring.

CHAPTER – 5

RESULTS AND DISCUSSION

5.1 Results

The Smart Railway Track Abnormality Detection and Alerts System was developed as a prototype to monitor selected railway track conditions using sensors and an Arduino Uno microcontroller. The system combines ultrasonic sensing, vibration detection, LED indicators, an LCD display, and GPS functionality to support abnormality identification and alert generation.

The ultrasonic sensor measures the distance between the sensor and the monitored surface. The Arduino Uno processes the measured values and compares them with predefined reference values and thresholds. When the measured distance deviation exceeds the specified threshold, the system identifies a possible abnormal condition and activates the red LED. Under normal monitored conditions, the green LED indicates the normal status.

The vibration sensor provides additional information about vibrations detected during operation. These readings can help identify unusual vibration conditions, depending on the sensor configuration and threshold settings. By combining distance and vibration readings, the prototype demonstrates a basic approach to monitoring selected track conditions.

The LCD display is intended to show the current system status and relevant information. It helps the user understand whether the monitored area is considered normal or whether a possible abnormality has been detected. The LED indicators provide a simple visual alert, making the system easy to observe during testing.

The NEO-6M GPS module can be used to obtain geographical coordinates when a valid satellite fix is available. These coordinates may help identify the approximate location associated with a detected abnormality. GPS performance depends on satellite visibility and environmental conditions.

The GSM module is considered an optional component. If it is connected, configured, and supplied with suitable power, it can be used to send SMS alerts to a registered mobile number. If GSM is not implemented in the prototype, the alert functionality remains limited to the implemented local indicators and display.

Overall, the prototype demonstrates how a microcontroller and basic sensors can be integrated to monitor selected conditions and generate local alerts. The results obtained during testing should be documented using actual sensor readings, observed LED responses, LCD output, and GPS status.




Fig 5.1 : Result prototype

5.2 Testing and Observations

The system can be evaluated through individual component tests and combined system tests. The ultrasonic sensor is tested by placing objects at different distances and observing the readings. These readings are compared with the reference distance to verify whether the threshold-based detection logic responds correctly.

Table 1: Ultrasonic Sensor Testing

Test case	Measured distance	Condition	LED Status
1	10	Normal	Green
2	8	Normal	Green
3	3	Possible abnormaility	Red
4	2	Possible abnormality	Red

The vibration sensor is tested by applying controlled vibrations and observing the sensor output. The Arduino processes this output according to the programmed detection conditions. The red and green LEDs are checked to confirm that the visual indications correspond to the programmed system status.

Table 2: Vibration Sensor Testing

Test case	Sensor condition	Expected indication
1	No significant vibration	Normal
2	Low vibration	Depends on threshold
3	High vibration	Abnormal as it exceeds threshold

The LCD is tested to verify whether the system status and sensor information are displayed correctly. The GPS module is tested separately to determine whether valid coordinates are received. If a valid GPS fix is unavailable, the system may not provide reliable location information. The optional GSM module, if installed, must be tested separately to verify SMS transmission and delivery.

Table 3: LED and LCD Testing

Test case	**Input condition**	**Expected Output**
1	Normal sensor readings	Normal status, green LEDs
2	Distance threshold exceeded	Abnormal status, red LEDs
3	Vibration threshold exceeded	Alert based on program logic
4	System initialized	LCD displays configured status

Table 4: GPS Module Testing

Test case	**GPS Status**	**Output**
1	GPS fix available	Co ordinates received
2	No GPS fix	Co ordinates unavailable
3	Weak satellite reception	Fix maybe delayed

These tests help identify connection errors, incorrect threshold values, sensor response issues, and software problems. Testing each component separately before combining them makes troubleshooting easier and improves the reliability of the prototype.

5.3 Performance Analysis

The performance of the prototype can be evaluated using the following parameters:

1. Detection Response: The system should identify sensor readings that exceed the predefined threshold and activate the appropriate alert.

2. Sensor Accuracy: The measured distance and vibration responses should be compared with reference measurements and controlled test conditions.

3. Alert Response: The red and green LEDs and LCD should indicate the programmed system status correctly.

4. GPS Functionality: The GPS module should provide valid coordinates when satellite reception is sufficient.

5. Communication Performance: If GSM is implemented, SMS delivery and notification time should be checked under suitable network conditions.

6. System Reliability: Repeated tests should be conducted to determine whether the system provides consistent responses under similar conditions.




Fig 5.3: Performance analysis

5.4 Discussion

The prototype provides a simple and affordable method for demonstrating sensor-based railway track condition monitoring. Its main advantages are the use of readily available components, straightforward microcontroller programming, and visual alerts that are easy to understand.

However, the system has certain limitations. Ultrasonic sensors detect distance variations rather than directly identifying every type of crack or structural defect. Vibration readings may also be affected by the mounting arrangement and surrounding disturbances. GPS reception may be unreliable indoors, and GSM notifications require additional hardware and network availability.

Therefore, the system should be considered an educational prototype rather than a certified railway safety device. Further calibration, controlled experiments, field testing, and comparison with established inspection methods are necessary before practical deployment.

5.5 Summary of Results

The project demonstrates the integration of sensors, an Arduino Uno, visual indicators, an LCD display, and GPS functionality into a basic railway monitoring prototype. The threshold-based algorithm provides a method for identifying selected abnormal sensor readings and generating local alerts. Optional GSM integration can extend the system to remote notifications.

The overall results depend on the actual hardware connections, program execution, sensor calibration, and testing conditions. Further improvements can focus on reducing false alarms, improving detection reliability, recording sensor data, and enabling remote monitoring.

Table 5: Overall System Testing

Test Case	Module Tested	Result to Record
1	Ultrasonic Sensor	Actual distance readings
2	Vibration Sensor	Actual sensor response
3	LED Indicators	Observed LED status
4	LCD Display	Displayed message
5	GPS Module	GPS fix status and coordinates
6	GSM (Optional)	SMS delivery status, if implemented

CHAPTER – 6

CONCLUSION AND FUTURE SCOPE

6.1 Conclusion

The project “Smart Railway Track Abnormality Detection & Local Alert System” aims to develop a simple, low-cost prototype for identifying selected railway track abnormalities and providing immediate alerts. The system uses an Arduino Uno as the main controller, along with ultrasonic and vibration sensors to monitor changes in the surrounding track conditions.

The ultrasonic sensor measures distance variations, while the vibration sensor helps detect vibrations that may indicate unusual conditions. The Arduino processes the sensor readings and compares them with predefined thresholds. Based on the readings, the system indicates the status through red and green LEDs. An LCD display provides additional information about the system's current condition.

The integration of the NEO-6M GPS module can help obtain geographical coordinates when a valid GPS signal is available. GSM-based SMS notification can also be included as an optional feature to send alerts and location details to a registered mobile number.

The project demonstrates how basic sensors and a microcontroller can be combined to create an affordable railway track monitoring prototype. It provides an opportunity to understand sensor interfacing, embedded programming, abnormality detection, GPS integration, and alert generation.

Although the prototype can identify certain changes in sensor readings, it cannot detect every type of railway track defect or replace professional inspection systems. Further calibration, extensive testing, and practical validation are required before considering real-world railway applications. Overall, the project provides a foundation for developing more advanced railway monitoring and safety systems.

5.2 Future Scope

The project can be improved in several ways to increase its functionality, reliability, and practical usefulness.

1. GSM-Based SMS Alerts

An optional GSM module can be integrated to send automatic SMS notifications whenever a possible abnormality is detected. The message can include the detected condition and GPS coordinates, if available.

2. IoT-Based Monitoring Dashboard

An IoT platform can be introduced to display sensor readings, system status, and location information on a web or mobile dashboard. This would allow remote monitoring and help users review recorded data.

3. Improved Sensor Accuracy

More accurate sensors and suitable calibration methods can be used to reduce false alarms. Multiple sensor readings can be analyzed together to improve the reliability of abnormality identification.

4. GPS-Based Location Tracking

The GPS module can be used to identify the approximate location of a detected abnormality. Storing location details alongside sensor readings could help users identify areas that require further inspection.

5. Data Logging and Historical Analysis

A data-logging system can be added to store sensor readings, timestamps, and abnormality events. Analyzing this information over time may help identify repeated changes and support maintenance planning.

6. Advanced Detection Techniques

In the future, machine learning and advanced signal-processing techniques could be explored to classify different abnormal conditions using sensor data. Such methods would require appropriate datasets and extensive testing.

7. Field Testing and System Expansion

The prototype can be tested under different environmental and operating conditions to evaluate its performance. Future versions may use more robust hardware, improved power management, and additional sensing units to monitor larger track sections.

In conclusion, the project can be developed further into a more reliable and connected railway monitoring prototype. With improved sensing, communication, data analysis, and field validation, it may support railway inspection and maintenance activities in the future.

REFERENCES

A. Books

1. Saxena, S. C., and Arora, S. P. A Textbook of Railway Engineering. Dhanpat Rai Publications.

2. Mundrey, J. S. Railway Track Engineering. Tata McGraw-Hill Education.

3. Bonnett, Clifford F. Practical Railway Engineering. 2nd Edition, Imperial College Press.

B. Research Papers

4. “Railway Track Crack Detection System.” International Journal of Advanced Science and Technology, vol. 29, no. 10s, pp. 3164–3171, 2020.

5. “An IoT Based Rail Track Condition Monitoring and Derailment Prevention System.” Journal of Reliable Intelligent Environments.

6. “Autonomous Railway Track Crack Detection and Accident Prevention System.” International Journal of Advance Research, Ideas and Innovations in Technology, vol. 6, issue 5, 2020.

7. “Railway Track Crack Detection System Using Arduino.” International Journal of Innovative Research in Electrical, Electronics, Instrumentation and Control Engineering, vol. 11, issue 6, 2023.

8. “IoT Based Smart Railway Track Crack Detection and Monitoring System.” Proceedings of the Third International Conference on Augmented Intelligence and Sustainable Systems (ICAISS), IEEE, 2025.

C. Online Technical Resources

9. Arduino. Arduino UNO Rev3 – Official Documentation. Available at: https://docs.arduino.cc/hardware/uno-rev3/

10. u-blox. NEO-6 GPS Modules – Data Sheet. Available at: https://www.u-blox.com/