


# **CS2102: Database Systems**

## Lecture 5 — SQL (Part 3)

# Quick Recap: Where We are Right Now

- Querying a database


- Extracting information using SQL (DQL: data query language)
- Anything with "**SELECT ...**"



- Covered constructs

- Basic queries: **SELECT** [ **DISTINCT** ] ... **FROM** [ **WHERE** ]
- Multirelational queries / join queries: **(INNER) JOIN**, **NATURAL JOIN**, **OUTER JOIN**, etc
- Subquery expressions: **(NOT) IN**, **(NOT) EXISTS**, **ANY/SOME**, **ALL**
- Sorting & rank-based selection: **ORDER BY**, **LIMIT**, **OFFSET**

# Example Database — ER Diagram



# Example Database — Data Sample

**Countries (225 tuples)**

iso2	name	population	gdp	continent
SG	Singapore	5781728	488000000000	Asia
AU	Australia	22992654	1190000000000	Oceania
TH	Thailand	68200824	1160000000000	Asia
DE	Germany	80722792	3980000000000	Europe
CN	China	1373541278	21100000000000	Asia
...	...	...	...	...

**Borders (699 tuples)**

country1_iso2	country2_iso2
SG	<i>null</i>
AU	<i>null</i>
TH	KH
TH	LA
TH	MY
...	...

**Airports (3,372 tuples)**

code	name	city	country_iso2
SIN	Singapore Changi Airport	Singapore	SG
XSP	Seletar Airport	Singapore	SG
SYD	Sydney Int. Airport	Sydney	AU
MEL	Melbourne Int. Airport	Melbourne	AU
FRA	Frankfurt am Main Airport	Frankfurt	DE
...	...	...	...

**Cities (24,567 tuples)**

name	country_iso2	capital	population
Singapore	SG	primary	5745000
Kuala Lumpur	MY	primary	8285000
Nanyang	CN	<i>null</i>	12010000
Atlanta	US	admin	5449398
Washington	US	primary	5379184
...	...	...	...

**Routes (47,076 tuples)**

from_code	to_code	airline_code
ADD	BKK	SQ
ADL	SIN	SQ
AKL	SIN	SQ
AMS	SIN	SQ
BCN	GRU	SQ
...	...	...

**Users (9 tuples)**

user_id	name	age
101	Sarah	25
102	Judy	35
103	Max	52
104	Marie	36
105	Sam	30
...	...	...

**Visited (585 tuples)**

user_id	iso2
103	AU
103	US
103	SG
103	GB
104	GB
...	...

# Overview

- **Common SQL constructs**
  - **Aggregation**
  - Grouping
  - Conditional Expressions
- Structuring Queries
  - Common Table Expressions
  - Views
- Extended concepts
  - Universal Quantification
  - Recursive Queries
- Summary

# Aggregation

- Aggregate functions
  - Compute a single value from a set of tuples
  - Examples: **MIN()**, **MAX()**, **AVG()**, **COUNT()**, **SUM()**

*Find the lowest and highest population sizes among all countries, as well as the global population size (= sum over all countries).*

```
SELECT MIN(population) AS lowest,  
       MAX(population) AS highest,  
       SUM(population) AS global  
FROM countries;
```

lowest	highest	global
453	1412600000	7712195627

# Aggregation — Interpretation of NULL values

...	A	...
...	3	...
...	<i>null</i>	...
...	42	...
...	0	...
...	3	...

- Let  $R$  be a non-empty relation with attribute  $A$

Query	Interpretation	Result
<b>SELECT MIN(A) FROM R;</b>	Minimum non-null value in A	0
<b>SELECT MAX(A) FROM R;</b>	Maximum non-null value in A	42
<b>SELECT AVG(A) FROM R;</b>	Average of non-null values in A	12
<b>SELECT SUM(A) FROM R;</b>	Sum of non-null values in A	48
<b>SELECT COUNT(A) FROM R;</b>	Count of non-null values in A	4
<b>SELECT COUNT(*) FROM R;</b>	Count of rows in R	5
<b>SELECT AVG(DISTINCT A) FROM R;</b>	Average of distinct non-null values in A	15
<b>SELECT SUM(DISTINCT A) FROM R;</b>	Sum of distinct non-null values in A	45
<b>SELECT COUNT(DISTINCT A) FROM R;</b>	Count of distinct non-null values in A	3

# Aggregation — Interpretation of NULL values

Table R

...	A	...
-----	---	-----

Table S

...	A	...
...	<i>null</i>	...
...	<i>null</i>	...
...	<i>null</i>	...
...	<i>null</i>	...
...	...	...

- Let  $R, S$  be two relations with an attribute  $A$ 
  - Let  $R$  be an empty relation
  - Let  $S$  be a non-empty relation with  $n$  tuples but only null values for  $A$

Query	Result
<b>SELECT MIN(A) FROM R;</b>	null
<b>SELECT MAX(A) FROM R;</b>	null
<b>SELECT AVG(A) FROM R;</b>	null
<b>SELECT SUM(A) FROM R;</b>	null
<b>SELECT COUNT(A) FROM R;</b>	0
<b>SELECT COUNT(*) FROM R;</b>	0

Query	Result
<b>SELECT MIN(A) FROM S;</b>	null
<b>SELECT MAX(A) FROM S;</b>	null
<b>SELECT AVG(A) FROM S;</b>	null
<b>SELECT SUM(A) FROM S;</b>	null
<b>SELECT COUNT(A) FROM S;</b>	0
<b>SELECT COUNT(*) FROM S;</b>	$n$



# Aggregation — More Examples

*Find the first and last city in the United States  
with respect to their lexicographic sorting.*

```
SELECT MIN(name) AS lexi_first, MAX(name) AS lexi_last
FROM cities
WHERE country_iso2 = 'US';
```


lexi_first	lexi_last
Abbeville	Zuni Pueblo

*Find the number countries with at least 10% of the population  
compared to the country with the largest population size.*

```
SELECT COUNT(*) AS num_big_countries
FROM countries
WHERE population >= 0.1 * (SELECT MAX(population)
                           FROM countries);
```

num_big_countries
9

Scalar subquery!



# Aggregate Functions — Signatures

- Data type of attribute/column of a table affects:
  - Applicability of aggregate functions
  - Return data type of aggregate functions
- Examples
  - **MIN()**, **MAX()** defined for all data types; return data type same as input data type
  - **SUM()** defined for all numeric data types; **SUM(INTEGER)→BIGINT**, **SUM(REAL)→REAL**, ...
  - **COUNT()** defined for all data types; **COUNT(...)→BIGINT**
  - ...

# Overview

- **Common SQL constructs**

- Aggregation
- **Grouping**
- Conditional Expressions

- Structuring Queries

- Common Table Expressions
- Views

- Extended concepts

- Universal Quantification
- Recursive Queries

- Summary

# Grouping — GROUP BY Clause

- Aggregation so far

- Application of aggregate functions over all tuples of a relation
- Result relation has only one tuple

## → Grouping using **GROUP BY**

- Logical partition of relation into groups based on values for specified attributes
- In principle, always applied together with aggregation  
(**GROUP BY** without aggregation valid but typically not meaningful)
- Application of aggregation functions over each group
- One result tuple for each group

# GROUP BY — Example

*For each continent, find the lowest and highest population sizes among all countries, as well as the overall population size for that continent.*

Logical partition of "Countries" w.r.t. "continent"

iso2	name	population	area	gdp	gini	continent
DZ	Algeria	44700000	...	...	...	Africa
AO	Angola	33086278	...	...	...	Africa
...	...	...	...	...	...	...
AF	Afghanistan	40218234	...	...	...	Asia
BH	Bahrain	1569446	...	...	...	Asia
...	...	...	...	...	...	...
AR	Argentina	45605826	...	...	...	South America
BO	Bolivia	11428245	...	...	...	South America
...	...	...	...	...	...	...
BS	Bahamas	400516	...	...	...	North America
CA	Canada	38526760	...	...	...	North America
...	...	...	...	...	...	...
...	...	...	...	...	...	Europe

```
SELECT continent,  
       MIN(population) AS lowest,  
       MAX(population) AS highest,  
       SUM(population) AS overall  
FROM countries  
GROUP BY continent;
```

continent	lowest	highest	overall
Africa	99331	211400708	1354025807
Asia	579330	1412600000	4554731303
South America	575990	212688125	430763036
North America	52441	331893745	585036622
Europe	453	145478097	745055194
Oceania	10834	25997100	42583665

# GROUP BY — Example

*For each route, find the number of airlines that serve that route.*

Logical partition of "Routes" w.r.t. "from\_code" and "to\_code"

from_code	to_code	airline_code
SIN	FRA	SQ
SIN	FRA	LH
SIN	FRA	US
PEK	SIN	CA
PEK	SIN	SQ
MNL	SIN	3K
MNL	SIN	5J
MNL	SIN	PR
MNL	SIN	SQ
MNL	SIN	TR
SIN	ADL	ET
SIN	ADL	SQ
SIN	ADL	VA
SIN	HEL	AY
...	...	...

```
SELECT from_code, to_code,  
       COUNT(*) AS num_airlines  
FROM routes  
GROUP BY from_code, to_code;
```

from_code	to_code	num_airlines
SIN	FRA	3
PEK	SIN	2
MNL	SIN	5
SIN	ADL	3
SIN	HEL	1
MNL	KLO	6
ATL	JFK	10
KUL	BKK	9
...	...	...

20,326 tuples

# GROUP BY Clause — Defining Groups

- Given "**GROUP BY**  $a_1, a_2, \dots, a_n$ ", 2 tuples  $t$  and  $t'$  belong to the same group if

"( $t.a_1$  IS NOT DISTINCT FROM  $t'.a_1$ )" and

"( $t.a_2$  IS NOT DISTINCT FROM  $t'.a_2$ )" and

... and

"( $t.a_n$  IS NOT DISTINCT FROM  $t'.a_n$ )"


evaluates to "true"

- Example:

- Table  $R$  with three attributes  $A, B, C$

A	B	C
<i>null</i>	4	19
6	1	<i>null</i>
20	2	10
1	1	2
1	18	2
<i>null</i>	21	19
6	20	<i>null</i>


**SELECT ...  
FROM R  
GROUP BY A, C;**



A	B	C
<i>null</i>	4	19
<i>null</i>	21	19
6	1	<i>null</i>
6	20	<i>null</i>
20	2	10
1	1	2
1	18	2

# GROUP BY Clause — Restrictions to SELECT Clause

- If column  $A_i$  of table  $R$  appears in the **SELECT** clause, one of the following conditions must hold:
  - $A_i$  appears in the **GROUP BY** clause
  - $A_i$  appears as input of an aggregation function in the **SELECT** clause
  - The primary key ~~or a candidate key~~ of  $R$  appears in the **GROUP BY** clause



Valid in standard SQL but not supported by PostgreSQL.  
In this module, we follow PostgreSQL's tighter restriction

Example of an **invalid** query:

```
SELECT continent, gdp, SUM(population)
FROM countries
GROUP BY continent;
```



# GROUP BY — Grouping over Primary Key

- Assume table "Countries" was created as shown on the right

```
CREATE TABLE Countries (  
    iso2          CHAR(2) PRIMARY KEY,  
    name         VARCHAR(255) UNIQUE,  
    population    INTEGER,  
    gdp          BIGINT,  
    continent    VARCHAR(255)  
);
```

This query is **valid**!

```
SELECT name, population, COUNT(*)  
FROM countries  
GROUP BY iso2;
```

**Quick Quiz:** What is the "problem" with this query?

This query is **valid** SQL standard but **invalid** PostgreSQL!

```
SELECT name, population, COUNT(*)  
FROM countries  
GROUP BY name;
```

# GROUP BY — Grouping over Primary Key

- Assume table "Countries" was created as shown on the right
  - No key constraints on "Cities"

```
CREATE TABLE Countries (  
    iso2          CHAR(2) PRIMARY KEY,  
    name         VARCHAR(255) UNIQUE,  
    population    INTEGER,  
    gdp          BIGINT,  
    continent     VARCHAR(255)  
);
```

This query is **valid**!

```
SELECT n.name, n.population, COUNT(*)  
FROM cities c, countries n  
WHERE c.country_iso2 = n.iso2  
GROUP BY n.iso2;
```

This query is **invalid**!

```
SELECT n.name, c.name, COUNT(*)  
FROM cities c, countries n  
WHERE c.country_iso2 = n.iso2  
GROUP BY n.iso2;
```

This query is **valid**!

```
SELECT n.name, n.population, COUNT(*)  
FROM cities c, countries n  
WHERE c.country_iso2 = n.iso2  
GROUP BY n.iso2;
```

This query is **invalid**!

```
SELECT n.name, c.name, COUNT(*)  
FROM cities c, countries n  
WHERE c.country_iso2 = n.iso2  
GROUP BY n.iso2;
```

n.iso2	n.name	n.population	...	c.name	c.country_iso2	c.population	...
BS	Bahamas	400516	...	Nassau	BS	274400	...
BS	Bahamas	400516	..	Freeport City	BS	45945	...
BS	Bahamas	400516	...	Marsh Harbour	BS	6283	...
SG	Singapore	5453600	...	Singapore	SG	5271000	...
DJ	Djibouti	921804	...	Djibouti	DJ	562000	...
DJ	Djibouti	921804	...	Arta	DJ	null	...
DJ	Djibouti	921804	...	Ali Sabieh	DJ	37939	...
DJ	Djibouti	921804	...	Dikhil	DJ	35000	...
DJ	Djibouti	921804	...	Obock	DJ	21200	...
DJ	Djibouti	921804	...	Tadjourah	DJ	14820	...
AU	Australia	25997100	...	Sydney	AU	4840600	...
AU	Australia	25997100	...	Melbourne	AU	4529500	...
	...	...					...

# HAVING Clause — Conditions over Groups

- **HAVING** conditions

- Conditions check for each group defined by **GROUP BY** clause
- **HAVING** clause cannot be used without a **GROUP BY** clause
- Conditions typically involve aggregate functions

*Find all routes that are served by more than 12 airlines.*

```
SELECT from_code, to_code,  
       COUNT(*) AS num_airlines  
FROM routes  
GROUP BY from_code, to_code  
HAVING COUNT(*) > 12;
```

from_code	to_code	num_airlines
ORD	ATL	20
ATL	ORD	19
ORD	MSY	13
HKT	BKK	13

# HAVING Clause — Conditions over Groups

*Find all countries that have at least one city with a population size larger than the average population size of all European countries*

```
SELECT n.name, n.continent
FROM cities c, countries n
WHERE c.country_iso2 = n.iso2
GROUP BY n.name, n.continent
HAVING MAX(c.population) > (SELECT AVG(population)
                             FROM countries
                             WHERE continent = 'Europe');
```

name	continent
Bangladesh	Asia
Japan	Asia
Mexico	North America
India	Asia
Egypt	Africa
Philippines	Asia
Russia	Europe
Thailand	Asia
China	Asia
Brazil	South America
Argentina	South America
South Korea	Asia
Indonesia	Asia
United States	North America

# GROUP BY Clause — Restrictions to HAVING Clause

- If column  $A_i$  of table  $R$  appears in the **HAVING** clause, one of the following conditions must hold:
  - $A_i$  appears in the **GROUP BY** clause
  - $A_i$  appears as input of an aggregation function in the **HAVING** clause
  - The primary key ~~or a candidate key~~ of  $R$  appears in the **GROUP BY** clause

## Valid Queries


```
SELECT continent, COUNT(*)  
FROM countries  
GROUP BY continent  
HAVING AVG(population) > 25000000;
```

```
SELECT continent, COUNT(*)  
FROM countries  
GROUP BY continent  
HAVING continent = 'Asia';
```

```
SELECT continent, COUNT(*)  
FROM countries  
GROUP BY iso2  
HAVING name = 'China';
```


## Invalid Query

```
SELECT continent, COUNT(*)  
FROM countries  
GROUP BY continent  
HAVING name = 'China';
```



**Quick Quiz:** What is the result of this query?

# Conceptual Evaluation of Queries



# Overview

- **Common SQL constructs**

- Aggregation
- Grouping
- **Conditional Expressions**

- Structuring Queries

- Common Table Expressions
- Views

- Extended concepts

- Universal Quantification
- Recursive Queries

- Summary



# CASE — Conditional Expressions

- CASE expression
  - Generic conditional expression
  - Similar to case or if/else statements in programming languages
- Two basic ways for formulating CASE expressions

```
CASE  
  WHEN condition1 THEN result1  
  WHEN condition2 THEN result2  
  ...  
  WHEN conditionn THEN resultn  
  ELSE result0  
END
```

```
CASE expression  
  WHEN value1 THEN result1  
  WHEN value2 THEN result2  
  ...  
  WHEN valuen THEN resultn  
  ELSE result0  
END
```

# CASE — Conditional Expressions

*Find the number of all cities regarding the classification (defined by a cities population size).*

```
SELECT class, COUNT(*) AS city_count
FROM
  (SELECT name, CASE
    WHEN population > 10000000 THEN 'Super City'
    WHEN population > 5000000 THEN 'Mega City'
    WHEN population > 1000000 THEN 'Large City'
    WHEN population > 500000 THEN 'Medium City'
    ELSE 'Small City' END AS class
  FROM cities) t
GROUP BY class;
```

City Size	Urban Population (Million)
Super city	>10
Megacity	5–10
Large city	1–5
Medium city	0.5–1
Small city	<0.5

class	city_count
Medium City	576
Large City	546
Small City	38872
Mega City	104
Super City	40

# CASE — Conditional Expressions

*Find all countries and return the continent in Tamil.*

```
SELECT name, CASE continent
  WHEN 'Africa' THEN 'ஆப்பிரிக்கா'
  WHEN 'Asia' THEN 'ஆசியா'
  WHEN 'Europe' THEN 'ஐரோப்பா'
  WHEN 'North America' THEN 'வட அமெரிக்கா'
  WHEN 'South America' THEN 'தென் அமெரிக்கா'
  WHEN 'Oceania' THEN 'ஓசியானியா'
  ELSE NULL END AS continent
FROM countries;
```

name	continent
Afghanistan	ஆசியா
Albania	ஐரோப்பா
Algeria	ஆப்பிரிக்கா
Andorra	ஐரோப்பா
Angola	ஆப்பிரிக்கா
Antigua and Barbuda	வட அமெரிக்கா
Argentina	தென் அமெரிக்கா
...	...

# COALESCE — Conditional Expressions for NULL Values

- **COALESCE**(value1, value2, value3, ...)
  - Returns the first non-NULL value in the list of input arguments
  - Returns NULL if all values in the list of input arguments are NULL
  - Example: **SELECT COALESCE**(null, null, 1, null, 2) →

val
1

*Find the number of cities for each city type;  
consider cities with NULL for column "capital" as "other".*

```
SELECT type, COUNT(*) AS city_count
FROM
    (SELECT COALESCE(type, 'other') AS type
    FROM cities) t
GROUP BY type;
```

type	city_count
primary	206
other	30573
admin	5852
minor	3507

# NULLIF — Conditional Expressions for NULL Values

- **NULLIF**(*value*<sub>1</sub>, *value*<sub>2</sub>)

- Returns NULL if *value*<sub>1</sub>=*value*<sub>2</sub>; otherwise returns *value*<sub>1</sub>

- Examples:

**SELECT NULLIF(1, 1) AS val; →**

val
null

**SELECT NULLIF(1, 2) AS val; →**

val
1

- Common use case: convert “special” values (zero, empty string) to NULL values

*Find the minimum and average Gini Coefficients across all countries (unknown values are represented by 0)*

```
SELECT MIN(gini) AS min_gini,  
       AVG(gini) AS avg_gini  
FROM countries;
```

min_gini	avg_gini
0.0	33.08

```
SELECT MIN(NULLIF(gini, 0)) AS min_gini,  
       AVG(NULLIF(gini, 0)) AS avg_gini  
FROM countries;
```

min_gini	avg_gini
22.8	37.92

# Overview

- Common SQL constructs
  - Aggregation
  - Grouping
  - Conditional Expressions
- **Structuring Queries**
  - **Common Table Expressions**
  - Views
- Extended concepts
  - Universal Quantification
  - Recursive Queries
- Summary

# Common Table Expressions (CTEs)

country	city	airport
Saint Lucia	Castries	George F. L. Charles Airport

- **Motivation**

- SQL can quickly become complex and unreadable
- CTEs allow to structure SQL queries to improve readability

- ➔ **Common Table Expression CTE**

- Temporary named query
- One or more CTEs can be used within an SQL statement

**Example from last lecture:**


*Find all airports in European countries without a land border which cannot be reached by plane given the existing routes in the database.*

```
SELECT t1.country, t1.city, t1.airport
FROM
    (SELECT n.name AS country, c.name AS city,
        a.name AS airport, a.code
    FROM borders b, countries n, cities c, airports a
    WHERE b.country1_iso2 = n.iso2
        AND n.iso2 = c.country_iso2
        AND c.name = a.city
        AND c.country_iso2 = a.country_iso2
        AND b.country2_iso2 IS NULL
        AND n.continent = 'Europe') t1
LEFT OUTER JOIN
    routes r
ON t1.code = r.to_code
WHERE r.to_code IS NULL;
```

# Common Table Expressions (CTEs)

country	city	airport
Saint Lucia	Castries	George F. L. Charles Airport

- Same query using a CTE





# Common Table Expressions (CTEs)

- General syntax

- Each  $C_i$  is the name of a temporary table defined by query  $Q_i$
- Each  $C_i$  can reference any other  $C_j$  that has been declared before  $C_i$
- SQL statement  $S$  can reference any possible subset of all  $C_i$

- Note

- The goal of using CTEs is not to write less code
- CTEs help to improve readability, debugging, maintenance

**WITH**

$C_1$  **AS** ( $Q_1$ ),

$C_2$  **AS** ( $Q_2$ ),

...,

$C_n$  **AS** ( $Q_n$ )

SQL statement  $S$ ;

# Common Table Expressions (CTEs)

country	city	airport
Saint Lucia	Castries	George F. L. Charles Airport

- Extended example

- Multiples CTEs
- CTE referencing previously declared CTE
- CTEs are not required to be referenced

```
WITH IsolatedEuropeanCountries AS (  
    SELECT n.iso2, n.name AS country  
    FROM borders b, countries n  
    WHERE b.country1_iso2 = n.iso2  
        AND b.country2_iso2 IS NULL  
        AND n.continent = 'Europe'),  
AirportsInIsolatedEuropeanCountries AS (  
    SELECT n.country, c.name AS city, a.code, a.name AS airport  
    FROM IsolatedEuropeanCountries n, cities c, airports a  
    WHERE n.iso2 = c.country_iso2  
        AND c.name = a.city  
        AND c.country_iso2 = a.country_iso2),  
UnusedJustForFun AS (  
    SELECT COUNT(*)  
    FROM IsolatedEuropeanCountries)  
SELECT i.country, i.city, i.airport  
FROM AirportsInIsolatedEuropeanCountries i LEFT OUTER JOIN routes r  
    ON i.code = r.to_code  
WHERE r.to_code IS NULL;
```

# Overview

- Common SQL constructs
  - Aggregation
  - Grouping
  - Conditional Expressions
- **Structuring Queries**
  - Common Table Expressions
  - **Views**
- Extended concepts
  - Universal Quantification
  - Recursive Queries
- Summary

# Views — Virtual Tables

- Common observations when querying databases

(beyond the case of increasing complexity of SQL queries)

- Often only parts of a table (rows/columns) are of interest
- Often not all parts of a table (rows/columns) should be accessible to all users
- Often the same queries or subqueries are regularly and frequently used

## → View

- Permanently named query (= virtual table)
- Can be used like normal tables  
(with some restrictions; discussed later)
- The result of a query is not permanently stored!  
(query is executed each time the view is used)

```
CREATE VIEW <name> AS
SELECT ...
FROM ...
...
```

# Views — Example

**Assumption:** Finding all European countries without a land border is a very frequent query.

Find all airports in *European countries without a land border* which cannot be reached by plane given the existing routes in the database.

```
CREATE VIEW IsolatedEuropeanCountries AS
  SELECT n.iso2, n.name AS country
  FROM borders b, countries n
  WHERE b.country1_iso2 = n.iso2
        AND b.country2_iso2 IS NULL
        AND n.continent = 'Europe';
```

```
WITH AirportsInIsolatedEuropeanCountries AS (
  SELECT n.country, c.name AS city, a.code, a.name AS airport
  FROM IsolatedEuropeanCountries n, cities c, airports a
  WHERE n.iso2 = c.country_iso2
        AND c.name = a.city)
SELECT i.country, i.city, i.airport
FROM AirportsInIsolatedEuropeanCountries i LEFT OUTER JOIN routes r
  ON i.code = r.to_code
WHERE r.to_code IS NULL;
```

country	city	airport
Saint Lucia	Castries	George F. L. Charles Airport

# Views — Example

```
CREATE VIEW CountryUrbanizationStats AS  
SELECT  
  n.iso2, n.name, n.population AS overall_population, SUM(c.population) AS city_population,  
  SUM(c.population) / CAST(n.population AS NUMERIC) AS urbanization_rate  
FROM cities c, countries n  
WHERE c.country_iso2 = n.iso2  
GROUP BY n.iso2, n.name, n.population;
```

**Quick Quiz:** Why do we need this?

*Find all countries with a urbanization rate below 10%.*

```
SELECT name, urbanization_rate  
FROM CountryUrbanizationStats  
WHERE urbanization_rate < 0.1  
ORDER BY urbanization_rate ASC;
```

name	urbanization_rate
Grenada	0.039
Micronesia	0.061
Ethiopia	0.073
Burundi	0.087
Uganda	0.099

# Views — Usability

- No restriction when used in SQL queries (**SELECT** statements)
  - But what about **INSERT**, **UPDATE**, **DELETE** statements?

## ➔ Updatable View — requirements

- Only one entry in **FROM** clause (table or updatable view)
- No **WITH**, **DISTINCT**, **GROUP BY**, **HAVING**, **LIMIT**, or **OFFSET**
- No **UNION**, **INTERSECT** or **EXCEPT**
- No aggregate functions
- etc. (incl. no constraint violations)


# Overview

- Common SQL constructs
  - Aggregation
  - Grouping
  - Conditional Expressions
- Structuring Queries
  - Common Table Expressions
  - Views
- **Extended concepts**
  - **Universal Quantification**
  - Recursive Queries
- Summary



# Universal Quantification

- Small extension to existing example DB



- Query with universal quantification

- *"Find the names of all users that have visited all countries."*

→ Problem: SQL directly supports only existential quantification (**EXISTS**)

**Visited**

user_id	iso2
101	SG
101	DE
103	SG
103	CN
103	FR
...	...

**Users**

user_id	name	age
101	Sarah	25
102	Judy	35
103	Max	52
...	...	...

# Universal Quantification

- "Transformation" of query using logical equivalences
  - *"user who visited all countries" → "there does not exists a country the user has not visited"*
- Useful subquery
  - *All countries a user with  
user\_id = x has not visited*

```
SELECT n.iso2
FROM countries n
WHERE NOT EXISTS (SELECT 1
                  FROM visited v
                  WHERE v.iso2 = n.iso2
                  AND v.user_id = x);
```

} TRUE only for countries that do not have a match  
in "Visited" for all tuples where the user\_id = x

# Universal Quantification

*"Find the names of all users that have visited all countries."*

```
SELECT user_id, name
FROM users u
WHERE NOT EXISTS (SELECT n.iso2
                  FROM countries n
                  WHERE NOT EXISTS (SELECT 1
                                    FROM visited v
                                    WHERE v.iso2 = n.iso2
                                    AND v.user_id = u.user_id)
                  );
```

user_id	name
103	Max
107	Emma

→ While not overly common, SQL queries requiring universal quantification can get "ugly".

# Universal Quantification

- Alternative interpretation

- *"user who visited all countries" → "the number of tuples in "Visited" for that user must match the total number of countries"*

*"Find the names of all users that have visited all countries."*

```
SELECT u.user_id, u.name
FROM users u, visited v
WHERE u.user_id = v.user_id
GROUP BY u.user_id
HAVING COUNT(*) = (SELECT COUNT(*) FROM countries);
```

user_id	name
103	Max
107	Emma

# Overview

- Common SQL constructs
  - Aggregation
  - Grouping
  - Conditional Expressions
- Structuring Queries
  - Common Table Expressions
  - Views
- **Extended concepts**
  - Universal Quantification
  - **Recursive Queries**
- Summary

# Recursive Queries

```
CREATE TABLE connections AS
SELECT DISTINCT(from_code, to_code)
FROM routes;
```

- Small extension to existing example DB

- Create table "Connections" as shown
- Eliminates duplicate routes served by multiple airlines

- Interesting queries

- *"Find all airports that can be reached from SIN non-stop."*

```
SELECT to_code
FROM connections
WHERE from_code = 'SIN';
```

90 tuples

to_code
PEK
BKK
FRA
KUA
...

- *"Find all airports that can be reached from SIN with 1/2/3/... stops." → ???*

# Recursive Queries

*Find all airports that can be reached from SIN with 1 stop.*

825 tuples

```
SELECT DISTINCT(c2.to_code) AS to_code
FROM
    connections c1,
    connections c2
WHERE c1.to_code = c2.from_code
    AND c1.from_code = 'SIN';
```

to_code
DUB
PEK
SIN
MME
...

*Find all airports that can be reached from SIN with 2 stop.*

1,561 tuples

```
SELECT DISTINCT(c3.to_code) AS to_code
FROM
    connections c1,
    connections c2,
    connections c3
WHERE c1.to_code = c2.from_code
    AND c2.to_code = c3.from_code
    AND c1.from_code = 'SIN';
```

to_code
DUB
PEK
SIN
MME
...

# Recursive Queries

- Observation:  $X$  stops requires query with  $X$  joins
  - Requires to write a separate query for each  $X$

## → Recursive Queries using CTEs

Non-recursive term;  
can not reference "cte\_name"!

Recursive term  
referencing "cte\_name"

```
WITH RECURSIVE cte_name AS (  
     $Q_1$   
    UNION [ ALL ]  
     $Q_2$ (cte_name)  
)  
SELECT * FROM cte_name;
```



# Recursive Queries

*Find all airports that can be reached from SIN with 0..2 stops.*

(limitation to max. 2 stops purely for performance reasons)

```
WITH RECURSIVE flight_path AS (  
    SELECT from_code, to_code, 0 AS stops  
    FROM connections  
    WHERE from_code = 'SIN'  
    UNION ALL  
    SELECT c.from_code, c.to_code, p.stops+1  
    FROM flight_path p, connections c  
    WHERE p.to_code = c.from_code  
    AND p.stops < 2  
)  
SELECT DISTINCT to_code, stops  
FROM flight_path  
ORDER BY stops ASC;
```

to_code	stops	}	90 tuples	
PEK	0			
BKK	0			
FRA	0			
...	...	} <td rowspan="4">825 tuples</td>	825 tuples	
KUA	0			
DUB	1			
PEK	1			
SIN	1	} <td rowspan="8">1,561 tuples</td>	1,561 tuples	
...	...			
MME	1			
AMS	2			
BKK	2	}		
PER	2			
...	....			
ZYL	2			

*Find all airports that can be reached from SIN with 0..2 stops, including the exact paths.*

(limitation to max. 2 stops purely for performance reasons)

```

WITH RECURSIVE flight_path (airport_codes, stops, is_visited) AS (
    SELECT
        ARRAY[from_code, to_code],
        0 AS stops,
        from_code = to_code
    FROM connections
    WHERE from_code = 'SIN'
    UNION ALL
    SELECT
        (airport_codes || to_code)::char(3)[],
        p.stops + 1,
        c.to_code = ANY(p.airport_codes)
    FROM
        connections c,
        flight_path p
    WHERE p.airport_codes[ARRAY_LENGTH(airport_codes, 1)] = c.from_code
        AND NOT p.is_visited
        AND p.stops < 2
)
SELECT DISTINCT airport_codes, stops
FROM flight_path
ORDER BY stops;

```

airport_codes	stops	90 tuples
{SIN, PEK}	0	
{SIN, BKK}	0	
{SIN, FRA}	0	
...	...	4,058 tuples
{SIN, KUA}	0	
{SIN, BKK, PEK}	1	
{SIN, FRA, PEK}	1	
{SIN, DOH, PEK}	1	
...	...	
{SIN, MFM, DMK}	1	
{SIN, ADL, HKG, PEK}	2	184,059 tuples
{SIN, ADL, KUL, PEK}	2	
{SIN, ADL, SYD, PEK}	2	
...	....	
{SIN, TPE, FRA, CSS}	2	

# Dealing with the Limitations of (Basic) SQL

- Other types of queries poorly or not support by basic SQL
  - *"Sorted by GDP, are there somewhere in the ranking 5 Asian countries listed in a row."*
  - Queries/tasks common for time series: moving average, sliding window, etc.
- Common approaches
  - Keep or move logic into the application
  - Use features that make SQL turing-complete\*  
(e.g. using SQL/PSM — Persistent Stored Modules)
  - Use a different data model / DBMS  
(e.g., a graph database for recursive queries, or time series databases)

→ Covered in next lectures

\*strictly speaking the support of Recursive CTEs already made SQL turing-complete

# Summary

- Covered: SQL (DQL)

- Most common vocabulary for writing queries
- Basic means to "organize" complex queries (CTEs, Views)

- Limitations of SQL (more general: Relational Model)

- Universal quantification
- Recursive queries
- Sequential data
- Graph data
- ...

} RDBMS & SQL not the solution for everything

# Quick Quiz Solutions

## Quick Quiz (Slide 17)



## Quick Quiz (Slide 22)



## Quick Quiz (Slide 38)

